



American International University-Bangladesh

AIUB Eclipse

MD Siyam Talukder
Kazi Shoaib Ahmed Saad
Faysal Ahammed Chowdhury

Contents

1 Setup

1.1 Sublime Build

2 Stress Testing

2.1 Input Gen

2.2 Bash Script

3 Number Theory

3.1 Euler Totient Function

3.2 Phi 1 to N

3.3 Segmented Sieve

3.4 Extended GCD

3.5 Linear Diophantine Equation . .

3.6 Modular Inverse using EGCD . .

3.7 Exclusion DP

3.8 Legendres Formula

3.9 Binary Expo

3.10 Digit Sum of 1 to N

3.11 Pollard Rho

3.12 [Problem] How Many Bases - UVA

3.13 [Problem] Power Tower - CF . .

3.14 Formula and Properties

4 Combinatorics and Probability

4.1 Combinations

4.2 nCr for any mod

4.3 nCk without mod in O(r)

4.4 Lucas Theorem

4.5 Catalan Number

4.6 Derangement

4.7 Stars and Bars Theorem

4.8 Properties of Pascal's Triangle .

4.9 Contribution Technique

4.10 Probability and Expected Value .

5 Data Structure

5.1 Trie

5.2 Trie for bit

6 String

6.1 Hashing

6.2 Hashing with Updates

6.3 Hashing with Upd and Deletes .

6.4 Hashing on Tree

6.5 Compare 2 strings Lexicographically

6.6 KMP

6.7 KMP Automata

6.8 Prefix Occurance Count

6.9 Number of palindormic substring in L to R using Wavelet Tree . .

1 Setup

1.1 Sublime Build

```
"shell_cmd": "g++ -std=c++17 -o
\\\"$file_base_name\\\" \\\"$file\\\" &&
timeout 2.5s ./\\\"$file_base_name\\\" <
input.txt > output.txt",
"file_regex":
"^(\\.\\.?:)*\\.([0-9]+)?\\.([0-9]+)?\\.?"
"\\.\\*$",
"working_dir": "$file_path",
"selector": "source.c, source.c++"
```

2 Stress Testing

2.1 Input Gen

```
mt19937_64 rnd(chrono::steady_clock::now)
().time_since_epoch().count());
ll get_rand(ll l, ll r) {
    assert(l <= r);
    return l + rnd() % (r - l + 1);
}
```

2.2 Bash Script

```
// run -> bash script.sh
set -e
g++ code.cpp -o code
g++ gen.cpp -o gen
g++ brute.cpp -o brute
for((i = 1; ; ++i)); do
    ./gen $i > input_file
    ./code < input_file > myAnswer
    ./brute < input_file > correctAnswer
    diff -Z myAnswer correctAnswer >
    /dev/null || break
    echo "Passed test: " $i
done
echo "WA on the following test:"
cat input_file
echo "Your answer is:"
cat myAnswer
echo "Correct answer is:"
cat correctAnswer
```

3 Number Theory

3.1 Euler Totient Function

```
// Time:  $O(\sqrt{N})$ 
map<int, int> dp; // memo
int phi(int n) {
    if (dp.count(n)) return dp[n];
    int ans = n, m = n;
    for (int i = 2; i * i <= m; i++) {
        if (m % i == 0) {
            while (m % i == 0) m /= i;
            ans = ans / i * (i - 1);
        }
    }
    if (m > 1) ans = ans / m * (m - 1);
    return dp[n] = ans;
}
```

3.2 Phi 1 to N

```
void phi_1_to_n(int n) {
    vector<int> phi(n + 1);
    for (int i = 0; i <= n; i++)
        phi[i] = i;
    for (int i = 2; i <= n; i++) {
        if (phi[i] == i) {
            for (int j = i; j <= n; j += i)
```

```
phi[j] -= phi[j] / i;
        }
    }
}
```

3.3 Segmented Sieve

```
vector<char> segmentedSieve(ll L, ll R) {
    // generate all primes up to  $\sqrt{R}$ 
    ll lim = sqrt(R);
    vector<char> mark(lim + 1, false);
    vector<ll> primes;
    for (ll i = 2; i <= lim; ++i) {
        if (!mark[i]) {
            primes.emplace_back(i);
            for (ll j = i * i; j <= lim; j += i)
                mark[j] = true;
        }
    }
    vector<char> isPrime(R - L + 1, true);
    for (ll i : primes)
        for (ll j = max(i * i, (L + i - 1) / i * i); j <= R; j += i)
            isPrime[j - L] = false;
    if (L == 1) isPrime[0] = false;
    return isPrime;
}
```

3.4 Extended GCD

```
//  $ax + by = \gcd(a, b)$ 
int egcd(int a, int b, int& x, int& y) {
    if (b == 0) {
        x = 1, y = 0;
        return a;
    }
    int x1, y1;
    int d = egcd(b, a % b, x1, y1);
    x = y1;
    y = x1 - y1 * (a / b);
    return d;
}
```

3.5 Linear Diophantine Equation

```
//  $ax + by = c$ , find any  $x$  and  $y$ 
bool find_any_solution(int a, int b, int c, int &x0, int &y0, int &g) {
    g = egcd(abs(a), abs(b), x0, y0);
    if (c % g) return false;
    x0 *= c / g;
    y0 *= c / g;
    if (a < 0) x0 = -x0;
    if (b < 0) y0 = -y0;
    return true;
}
void shift_solution(int &x, int &y, int a, int b, int cnt) {
    x += cnt * b;
    y -= cnt * a;
}
int find_all_solutions(int a, int b, int c, int minx, int maxx, int miny, int maxy) {
    int x, y, g;
    if (!find_any_solution(a, b, c, x, y, g))
        return 0;
    a /= g, b /= g;
```

```
int sign_a = a > 0 ? +1 : -1;
int sign_b = b > 0 ? +1 : -1;
shift_solution(x, y, a, b, (minx - x) / b);
if (x < minx) shift_solution(x, y, a, b, sign_b);
if (x > maxx) return 0;
int lx1 = x;
shift_solution(x, y, a, b, (maxx - x) / b);
if (x > maxx) shift_solution(x, y, a, b, -sign_b);
int rx1 = x;
shift_solution(x, y, a, b, -(miny - y) / a);
if (y < miny) shift_solution(x, y, a, b, -sign_a);
if (y > maxy) return 0;
int lx2 = x;
shift_solution(x, y, a, b, -(maxy - y) / a);
if (y > maxy) shift_solution(x, y, a, b, sign_a);
int rx2 = x;
if (lx2 > rx2) swap(lx2, rx2);
int lx = max(lx1, lx2);
int rx = min(rx1, rx2);
if (lx > rx) return 0;
return (rx - lx) / abs(b) + 1;
}
```

3.6 Modular Inverse using EGCD

```
// finding inverse(a) modulo m
int x, y;
int g = extended_euclidean(a, m, x, y);
if (g != 1) cout << "No solution!";
else {
    x = (x % m + m) % m;
    cout << x << endl;
}
```

3.7 Exclusion DP

```
ll f[N], g[N];
for (int i = N - 1; i >= 1; i--) {
    f[i] = nC4(div_cnt[i]);
    g[i] = f[i];
    for (int j = i + 1; j < N; j += i) {
        g[i] -= g[j];
    }
}
```

Here, $f[i]$ = how many pairs/k-tuple such that their gcd is i or it's multiple (count of pairs those are divisible by i).

$g[i]$ = how many pairs/k-tuple such that their gcd is i .

$g[i] = f[i] - \sum_{i|j} g[j]$.

Sum of all pair gcd:

We know, how many pairs are there such that their gcd is i for every i (1 to n). So now, $\sum_{i=1}^n g[i] * i$.

Sum of all pair lcm ($i = 1, j = 1$):

We know, $\text{lcm}(a, b) = \frac{a*b}{\text{gcd}(a, b)}$.

Now, $f[i]$ = All pair product sum of those, whose gcd is i or it's multiple.
 $g[i]$ = All pair product sum of those, whose gcd is i .

$$\text{Ans} = \sum_{i=1}^n \frac{g[i]}{i}.$$

All pair product sum = $(a_1 + a_2 + \dots + a_n) * (a_1 + a_2 + \dots + a_n)$

3.8 Legendres Formula

// $\frac{n!}{p^x}$ - you will get the largest x

```
int legendre(int n, int p) {
    int ex = 0;
    while(n) {
        ex += (n / p);
        n /= p;
    }
    return ex;
}
```

3.9 Binary Expo

```
int power(int x, long long n, int mod) {
    int ans = 1 % mod;
    while (n > 0) {
        if (n & 1) {
            ans = 1LL * ans * x % mod;
        }
        x = 1LL * x * x % mod;
        n >>= 1;
    }
    return ans;
}
```

3.10 Digit Sum of 1 to N

// for n=10, ans = 1+2+...+9+1+0

```
ll solve(ll n) {
    ll res = 0, p = 1;
    while (n / p > 0) {
        ll left = n / (p * 10);
        ll cur = (n / p) % 10;
        ll right = n % p;
        res += left * 45 * p;
        res += (cur * (cur - 1) / 2) * p;
        res += cur * (right + 1);
        p *= 10;
    }
    return res;
}
```

3.11 Pollard Rho

```
namespace PollardRho {
    mt19937 rnd(chrono::steady_clock::now().
        time_since_epoch().count());
    const int P = 1e6 + 9;
    ll seq[P];
    int primes[P], spf[P];
    inline ll add_mod(ll x, ll y, ll m) {
        return (x += y) < m ? x : x - m;
    }
    inline ll mul_mod(ll x, ll y, ll m) {
        ll res = __int128(x) * y % m;
        return res;
        // ll res = x * y - (ll)((long double)x
        // * y / m + 0.5) * m;
        // return res < 0 ? res + m : res;
    }
}
```

```
inline ll pow_mod(ll x, ll n, ll m) {
    ll res = 1 % m;
    for (; n >>= 1) {
        if (n & 1) res = mul_mod(res, x, m);
        x = mul_mod(x, x, m);
    }
    return res;
}
// O(it * (logn)^3), it = number of
// rounds performed
inline bool miller_rabin(ll n) {
    if (n <= 2 || (n & 1 ^ 1)) return (n
        == 2);
    if (n < P) return spf[n] == n;
    ll c, d, s = 0, r = n - 1;
    for (; !(r & 1); r >>= 1, s++) {}
    // each iteration is a round
    for (int i = 0; primes[i] < n &&
        primes[i] < 32; i++) {
        c = pow_mod(primes[i], r, n);
        for (int j = 0; j < s; j++) {
            d = mul_mod(c, c, n);
            if (d == 1 && c != 1 && c != (n -
                1)) return false;
            c = d;
        }
        if (c != 1) return false;
    }
    return true;
}
void init() {
    int cnt = 0;
    for (int i = 2; i < P; i++) {
        if (!spf[i]) primes[cnt++] = spf[i]
            = i;
        for (int j = 0, k; (k = i *
            primes[j]) < P; j++) {
            spf[k] = primes[j];
            if (spf[i] == spf[k]) break;
        }
    }
}
// returns O(n^(1/4))
ll pollard_rho(ll n) {
    while (1) {
        ll x = rnd() % n, y = x, c = rnd() %
            n, u = 1, v, t = 0;
        ll *px = seq, *py = seq;
        while (1) {
            *py++ = y = add_mod(mul_mod(y, y,
                n), c, n);
            *py++ = y = add_mod(mul_mod(y, y,
                n), c, n);
            if ((x = *px++) == y) break;
            v = u;
            u = mul_mod(u, abs(y - x), n);
            if (!u) return __gcd(v, n);
            if (++t == 32) {
                t = 0;
                if ((u = __gcd(u, n)) > 1 && u <
                    n) return u;
            }
        }
    }
    if (t && (u = __gcd(u, n)) > 1 && u
        < n) return u;
}
```

```
}
}
vector<ll> factorize(ll n) {
    if (n == 1) return vector<ll>();
    if (miller_rabin(n)) return vector<ll>
        {n};
    vector<ll> v, w;
    while (n > 1 && n < P) {
        v.push_back(spf[n]);
        n /= spf[n];
    }
    if (n >= P) {
        ll x = pollard_rho(n);
        v = factorize(x);
        w = factorize(n / x);
        v.insert(v.end(), w.begin(), w.end());
    }
    return v;
}
}
```

3.12 [Problem] How Many Bases - UVa

// Given a number N^M , find out the number of integer bases in which it has exactly T trailing zeroes.

```
int solve_greater_or_equal(vector<int>
    e, int t) {
    int ans = 1;
    for (auto i : e) {
        ans = 1LL * ans * (i / t + 1) % mod;
    }
    return ans;
}
// e contains  $e_1, e_2 \rightarrow p_1^{e_1}, p_2^{e_2}$ 
int solve_equal(vector<int> e, int t) {
    return (solve_greater_or_equal(e, t) -
        solve_greater_or_equal(e, t + 1) +
        mod) % mod;
}
```

3.13 [Problem] Power Tower - CF

// A sequence w_1, w_2, \dots, w_n and Q queries, l and r will be given.

Calculate $w_l^{(w_{l+1}^{(w_{l+2}^{(w_r)})})}$

// $n^x \bmod m = n^{\phi(m) + x \bmod \phi(m)} \bmod m$

```
inline int MOD(int x, int m) {
    if (x < m) return x;
    return x % m + m;
}
int power(int n, int k, int mod) {
    int ans = MOD(1, mod);
    while (k) {
        if (k & 1) ans = MOD(ans * n, mod);
        n = MOD(n * n, mod);
        k >>= 1;
    }
    return ans;
}
int f(int l, int r, int m) {
    if (l == r) return MOD(a[l], m);
    if (m == 1) return 1;
    return power(a[l], f(l + 1, r,
        phi(m)), m);
}
```

3.14 Formula and Properties

- $\phi(n) = n \cdot \frac{p_1-1}{p_1} \cdot \frac{p_2-1}{p_2} \dots$
- $\phi(p^e) = p^e - \frac{p^e}{p} = p^e \cdot \frac{p-1}{p}$
- For $n > 2$, $\phi(n)$ is always even.
- $\sum_{d|n} \phi(d) = n$
- NOD: $(e_1 + 1) \cdot (e_2 + 1) \dots$
- SOD: $\frac{p_1^{e_1+1}-1}{p_1-1} \cdot \frac{p_2^{e_2+1}-1}{p_2-1} \dots$
- $\log(a \cdot b) = \log(a) + \log(b)$
- $\log(a^x) = x \cdot \log(a)$
- $\log_a(x) = \frac{\log_b(x)}{\log_b(a)}$
- Digit Count of n: $\lfloor \log_{10}(n) \rfloor + 1$
- Arithmetic Progression Sum: $\frac{n}{2} \cdot (a + p), \frac{n}{2} \cdot (2a + (n-1)d)$
- Geometric Sum: $S_n = a \cdot \frac{r^n-1}{r-1}$
- $(1^2 + 2^2 + \dots + n^2) = \frac{n(n+1)(2n+1)}{6}$
- $(1^3 + 2^3 + \dots + n^3) = \frac{n^2(n+1)^2}{4}$
- $(2^2 + 4^2 + \dots + (2n)^2) = \frac{2n(n+1)(2n+1)}{3}$
- $(1^2 + 3^2 + \dots + (2n-1)^2) = \frac{n(2n-1)(2n+1)}{3}$
- $(2^3 + 4^3 + \dots + (2n)^3) = 2n^2(n+1)^2$
- $(1^3 + 3^3 + \dots + (2n-1)^3) = n^2(2n^2-1)$
- For any number n and bases $> \sqrt{n}$, there will be no representation where the number contains 0 at its second least significant digit. So it is enough to check for bases $\leq \sqrt{n}$.
- For some x and y , let's try to find all m such that $x \bmod m \equiv y \bmod m$. We can rearrange the equation into $(x - y) \equiv 0 \pmod{m}$. Thus, if m is a factor of $|x - y|$, then x and y will be equal modulo m .

4 Combinatorics and Probability

4.1 Combinations

// Prime Mod in $O(n)$

```
void prec() {
    fact[0] = 1;
    for (int i = 1; i < N; i++) {
        fact[i] = 1LL * fact[i-1] * i % mod;
    }
    ifact[N-1] = inverse(fact[N-1]);
    for (int i = N-2; i >= 0; i--) {
        ifact[i] = 1LL * ifact[i+1] * (i+1) % mod;
    }
}
int nCr(int n, int r) {
    if (r > n) return 0;
}
```

```

    return 1ll * fact[n] * ifact[r] % mod
        * ifact[n - r] % mod;
}
int nPr(int n, int r) {
    if (r > n) return 0;
    return 1ll * fact[n] * ifact[n - r] %
        mod;
}

```

4.2 nCr for any mod

```

// Time:  $O(n^2)$ 
// nCr =  $(n-1)C(r-1) + (n-1)C(r)$ 
for (int i = 0; i < N; i++) {
    C[i][i] = 1;
    for (int j = 0; j < i; j++) {
        C[i][j] = (C[i - 1][j] + C[i - 1][j + 1]) % mod;
    }
}

```

4.3 nCk without mod in O(r)

```

ll nCk(ll n, ll k) {
    double res = 1;
    for (ll i = 1; i <= k; ++i)
        res = res * (n - k + i) / i;
    return (ll)(res + 0.01);
}

```

4.4 Lucas Theorem

```

// Credit: YouKnOwWho
// returns nCr modulo mod where mod is a
// prime
// Complexity: log(n)
const int N = 1e6 + 3, mod = 1e6 + 3;
template <const int32_t MOD>
struct modint {
    int32_t value;
    modint() = default;
    modint(int32_t value_) : value(value_) {}
    inline modint<MOD> operator +
        (modint<MOD> other) const {
        int32_t c = this->value +
            other.value; return modint<MOD>(c
            >= MOD ? c - MOD : c); }
    inline modint<MOD> operator -
        (modint<MOD> other) const {
        int32_t c = this->value -
            other.value; return modint<MOD>(c
            < 0 ? c + MOD : c); }
    inline modint<MOD> operator *
        (modint<MOD> other) const {
        int32_t c = (int64_t)this->value *
            other.value % MOD; return
            modint<MOD>(c < 0 ? c + MOD : c); }
    inline modint<MOD> & operator +=
        (modint<MOD> other) { this->value
            += other.value; if (this->value >=
            MOD) this->value -= MOD; return
            *this; }
    inline modint<MOD> & operator -=
        (modint<MOD> other) { this->value
            -= other.value; if (this->value <
            0) this->value += MOD; return
            *this; }
}

```

```

inline modint<MOD> & operator ==
    (modint<MOD> other) { this->value
        = (int64_t)this->value *
        other.value % MOD; if (this->value
        < 0) this->value += MOD; return
        *this; }
inline modint<MOD> operator - () const
    { return modint<MOD>(this->value ?
        MOD - this->value : 0); }
modint<MOD> pow(uint64_t k) const {
    modint<MOD> x = *this, y = 1; for
    (; k; k >>= 1) { if (k & 1) y *=
        x; x *= x; } return y; }
modint<MOD> inv() const { return
    pow(MOD - 2); } // MOD must be a
    prime
inline modint<MOD> operator /
    (modint<MOD> other) const { return
        *this * other.inv(); }
inline modint<MOD> operator /=
    (modint<MOD> other) { return
        *this *= other.inv(); }
inline bool operator == (modint<MOD>
    other) const { return value ==
        other.value; }
inline bool operator != (modint<MOD>
    other) const { return value !=
        other.value; }
inline bool operator < (modint<MOD>
    other) const { return value <
        other.value; }
inline bool operator > (modint<MOD>
    other) const { return value >
        other.value; }
};
template <int32_t MOD> modint<MOD>
    operator * (int32_t value,
        modint<MOD> n) { return
        modint<MOD>(value) * n; }
template <int32_t MOD> modint<MOD>
    operator * (int64_t value,
        modint<MOD> n) { return
        modint<MOD>(value % MOD) * n; }
template <int32_t MOD> istream &
    operator >> (istream & in,
        modint<MOD> &n) { return in >>
        n.value; }
template <int32_t MOD> ostream &
    operator << (ostream & out,
        modint<MOD> n) { return out <<
        n.value; }
using mint = modint<mod>;
struct combi {
    int n; vector<mint> facts, finvs, invs;
    combi(int n): n(n), facts(n),
        finvs(n), invs(n) {
        facts[0] = finvs[0] = 1;
        invs[1] = 1;
        for (int i = 2; i < n; i++) invs[i]
            = invs[i - 1] * (-mod / i);
        for (int i = 1; i < n; i++) {
            facts[i] = facts[i - 1] * i;
            finvs[i] = finvs[i - 1] * invs[i];
        }
    }
}

```

```

}
inline mint fact(int n) { return
    facts[n]; }
inline mint finv(int n) { return
    finvs[n]; }
inline mint inv(int n) { return
    invs[n]; }
inline mint ncr(int n, int k) { return
    n < k or k < 0 ? 0 : facts[n] *
    finvs[k] * finvs[n - k]; }
};
combi C(N);
mint lucas(ll n, ll r) {
    if (r > n) return 0;
    if (n < mod) return C.ncr(n, r);
    return lucas(n / mod, r / mod) *
        lucas(n % mod, r % mod);
}
cout << lucas(100000000, 2322) << '\n';

```

4.5 Catalan Number

```

const int MOD = 1e9 + 7, int MAX = 1e7;
int catalan[MAX];
void init(ll n) {
    catalan[0] = catalan[1] = 1;
    for (ll i = 2; i <= n; i++) {
        catalan[i] = 0;
        for (ll j = 0; j < i; j++) {
            catalan[i] += (catalan[j] *
                catalan[i - j - 1]) % MOD;
            if (catalan[i] >= MOD) {
                catalan[i] -= MOD;
            }
        }
    }
}

```

4.6 Derangement

```

// number of combinations such that
//  $a_i! = i$  of a permutation  $a$ 
const int N = 1e6 + 100, int p = 1e9 + 7;
ll der[N];
void countDer() {
    der[1] = 0;
    der[2] = 1;
    for (ll i = 3; i <= N; ++i) {
        der[i] = (i - 1) % p * (der[i - 1] %
            p + der[i - 2] % p);
        der[i] %= p;
    }
}

```

4.7 Stars and Bars Theorem

- Find the number of k -tuples of non-negative integers whose sum is n . $\binom{n+k-1}{n}$
- Find the number of k -tuples of non-negative integers whose sum is $\leq n$. $\binom{n+k}{k}$
- Combination with Repetition (choose k elements from n objects, same element can be chosen multiple times). $\binom{n+k-1}{k}$
- How many ways to go from $(0, 0)$ to (n, m) . $\binom{n+m}{m}$

Pascals Triangle is equivalent to nCr:

4.8 Properties of Pascal's Triangle


- $(a + b)^n = \sum_{k=0}^n \binom{n}{k} a^k b^{n-k}$
- $(k + 1)^n = \sum_{i=0}^n k^i \cdot \binom{n}{i}$
- $\sum_{i=0}^n \binom{n}{i} = 2^n$
- $\binom{k}{n} = \frac{k}{n} \binom{k-1}{n-1}$
- $\sum_{k=0}^m \binom{n+k}{k} = \binom{n+m+1}{m}$
- $\binom{n}{0}^2 + \binom{n}{1}^2 + \dots + \binom{n}{n}^2 = \binom{2n}{n}$
- $1 \binom{n}{1} + 2 \binom{n}{2} + \dots + n \binom{n}{n} = n 2^{n-1}$

4.9 Contribution Technique

- Sum of all pair sums: $\sum_{i=1}^n \sum_{j=1}^n (a_i + a_j)$
Every element will be added $2n$ times.
 $\sum_{i=1}^n (2 \times n \times a_i) = 2 \times n \times \sum_{i=1}^n a_i$.
- Sum of all subarray sums — $\sum_{i=1}^n (a_i \times i \times (n - i + 1))$.
- Sum of all Subsets sums — $\sum_{i=1}^n (2^{n-1} \times a_i)$.
- Product of all pair product — $\prod_{i=1}^n (a_i^{2 \times n})$.
- XOR of subarray XORs — How many subarrays does an element have? ($i \cdot (n - i + 1)$ times).
If subarray count is odd then this element can contribute in total XORs.
- Sum of max minus min over all subset — Sort the array. $Min = 2^{n-i}$, $Max = 2^{i-1}$.
 $\sum_{i=1}^n (a_i \cdot 2^{i-1} - a_i \cdot 2^{n-i})$.
- Sum using bits — $\sum_{k=0}^{30} (cnt_k[1] \times 2^k)$.
- Sum of Pair XORs — XOR will 1 if two bits are different $\sum_{k=0}^{30} (cnt_k[0] \times cnt_k[1] \times 2^k)$.
- Sum of Pair ANDs — $\sum_{k=0}^{30} (cnt_k[1]^2 \times 2^k)$.
- Sum of Pair ORs — $\sum_{k=0}^{30} ((cnt_k[1]^2 + 2 \times cnt_k[1] \times cnt_k[0]) \times 2^k)$.
- Sum of Subset XORs — where $cnt_0! = 0$
 $\sum_{k=0}^{30} (2^{cnt_k[1] + cnt_k[0] - 1} \times 2^k)$.
- Sum of Subset ANDs — $\sum_{k=0}^{30} ((2^{cnt_k[1]} - 1) \times 2^k)$.
- Sum of Subset ORs — $\sum_{k=0}^{30} ((2^n - 2^{cnt_k[0]}) \times 2^k)$.
- Sum of subarray XORs — Convert to prefix xor, then solve for pairs.
- Sum of product of all subsequence — $\prod_{i=1}^n (a_i + 1) - 1$. Example array — $[a, b]$ the subsequences are $\{a\}, \{b\}, \{a, b\}$ so ans is $a + b + (a \cdot b)$

4.10 Probability and Expected Value

- Expected value: $E = \sum_{i=1}^n P_i \cdot i$
- Variance: $V(x) = E(x^2) - \{E(x)\}^2$
- To get two consecutive heads, what is the expected number of tosses?



- To get n heads, what is the expected number of tosses? Let's define: to get n heads, we need to toss $E(n)$ times. Now — I can get a head; I need to toss $E(n-1)$ more times, or if I get a tail; I need to toss $E(n)$ times. So, the recurrence is: $E(n) = 0.5 \cdot (1 + E(n-1)) + 0.5 \cdot (1 + E(n))$
- You have n bulbs, all of which are initially off. In each move, you randomly select one bulb. If the selected bulb is **off**, you toss a coin:
 - If you get head, you turn it on.
 - If you get tail, you do nothing.

If the bulb is already **on**, you skip that move (nothing happens).

Now, what is the expected number of moves required to turn all bulbs on?

The coin is not fair — the probability of getting tail is p . This problem can also be solved recursively.

Let's assume at some moment, x bulbs are already on, and the expected number of moves needed from here is $e(x)$.

The probability of picking an already on bulb is $\frac{x}{n}$. In that case, the expected number of moves is $\frac{x}{n} \times (1 + e(x))$.

The probability of picking an off bulb is $\frac{n-x}{n}$.

Now two things can happen:

- With probability p , you get tail, so you stay at the same state ($e(x)$ more moves).
- With probability $(1-p)$, you get head, so one more bulb turns on ($e(x+1)$ moves from there).

So, the recurrence relation is:

$$e(x) = \frac{x}{n}(1 + e(x)) + \frac{n-x}{n}(p(1 + e(x)) + (1-p)(1 + e(x+1)))$$

5 Data Structure

5.1 Trie

```
const int N = 10; // change here
const char base_char = '0'; // change here

struct TrieNode {
    int cnt;
    TrieNode * nxt[N];
    TrieNode() {
        cnt = 0;
        for (int i = 0; i < N; i++) nxt[i] = NULL;
    }
} *root;

void insert(const string &s) {
    TrieNode *cur = root;
    int n = (int)s.size();
    for (int i = 0; i < n; i++) {
        int idx = s[i] - base_char;
        if (cur -> nxt[idx] == NULL) cur ->
            nxt[idx] = new TrieNode();
        cur = cur -> nxt[idx];
        cur -> cnt++;
    }
}

void rem(TrieNode *cur, string &s, int pos) { // free :: De Allocated Memory
    if (pos == s.size()) return;
    int idx = s[pos] - base_char;
    rem(cur -> nxt[idx], s, pos + 1);
    cur -> nxt[idx] -> cnt--;
    if (cur -> nxt[idx] -> cnt == 0) {
        free(cur -> nxt[idx]);
        cur -> nxt[idx] = NULL;
    }
}

int query(const string &s) { // "s" is a prefix of some element or not
    int n = (int)s.size();
    TrieNode *cur = root;
    for (int i = 0; i < n; i++) {
        int idx = s[i] - base_char;
        if (cur -> nxt[idx] == NULL) return 0;
        cur = cur -> nxt[idx];
    }
    return cur -> cnt;
}

void del(TrieNode *cur) {
    for (int i = 0; i < N; i++) if (cur ->
        nxt[i]) del(cur -> nxt[i]);
    delete(cur);
}

int32_t main() {
    root = new TrieNode(); // init new trie
    del(root); // clear trie
}
```

5.2 Trie for bit

```
struct Trie {
    static const int B = 31;
    struct node {
        node* nxt[2];
        int sz;
        node() {
            nxt[0] = nxt[1] = NULL;
        }
    };
    node* root;
```

```
    sz = 0;
}
}*root;
Trie() {
    root = new node();
}

void insert(int val) {
    node* cur = root;
    cur -> sz++;
    for (int i = B - 1; i >= 0; i--) {
        int b = val >> i & 1;
        if (cur -> nxt[b] == NULL) cur ->
            nxt[b] = new node();
        cur = cur -> nxt[b];
        cur -> sz++;
    }
}

int query(int x, int k) { // number of values s.t. val ^ x < k
    node* cur = root;
    int ans = 0;
    for (int i = B - 1; i >= 0; i--) {
        if (cur == NULL) break;
        int b1 = x >> i & 1, b2 = k >> i & 1;
        if (b2 == 1) {
            if (cur -> nxt[b1]) ans += cur ->
                nxt[b1] -> sz;
            cur = cur -> nxt[b1];
        } else cur = cur -> nxt[b1];
    }
    return ans;
}

int get_max(int x) { // returns maximum of val ^ x
    node* cur = root;
    int ans = 0;
    for (int i = B - 1; i >= 0; i--) {
        int k = x >> i & 1;
        if (cur -> nxt[!k]) cur = cur ->
            nxt[!k], ans <= 1, ans++;
        else cur = cur -> nxt[k], ans <= 1;
    }
    return ans;
}

int get_min(int x) { // returns minimum of val ^ x
    node* cur = root;
    int ans = 0;
    for (int i = B - 1; i >= 0; i--) {
        int k = x >> i & 1;
        if (cur -> nxt[k]) cur = cur ->
            nxt[k], ans <= 1;
        else cur = cur -> nxt[!k], ans <= 1, ans++;
    }
    return ans;
}

void del(node* cur) {
    for (int i = 0; i < 2; i++) if (cur ->
        nxt[i]) del(cur -> nxt[i]);
    delete(cur);
}

} t;
```

6 String

6.1 Hashing

```
const int N = 1e6 + 9; // change here
const int MOD1 = 127657753, MOD2 = 987654319;
const int p1 = 137, p2 = 277; // change here

int ip1, ip2;
pair<int, int> pw[N], ipw[N];
void prec() {
    pw[0] = {1, 1};
    for (int i = 1; i < N; i++) {
        pw[i].first = 111 * pw[i - 1].first
            * p1 % MOD1;
        pw[i].second = 111 * pw[i - 1].second * p2 % MOD2;
    }
    ip1 = power(p1, MOD1 - 2, MOD1);
    ip2 = power(p2, MOD2 - 2, MOD2);
    ipw[0] = {1, 1};
    for (int i = 1; i < N; i++) {
        ipw[i].first = 111 * ipw[i - 1].first * ip1 % MOD1;
        ipw[i].second = 111 * ipw[i - 1].second * ip2 % MOD2;
    }
}

struct Hashing {
    int n;
    string s;
    vector<pair<int, int>> hash_val;
    vector<pair<int, int>> rev_hash_val;
    Hashing() {}
    Hashing(string _s) {
        s = _s;
        n = s.size();
        hash_val.emplace_back(0, 0);
        for (int i = 0; i < n; i++) {
            pair<int, int> p;
            p.first = (hash_val[i].first + 111
                * s[i] * pw[i].first % MOD1) %
                MOD1;
            p.second = (hash_val[i].second +
                111 * s[i] * pw[i].second %
                MOD2) % MOD2;
            hash_val.push_back(p);
        }
        rev_hash_val.emplace_back(0, 0);
        for (int i = 0, j = n - 1; i < n;
            i++, j--) {
            pair<int, int> p;
            p.first = (rev_hash_val[i].first +
                111 * s[i] * pw[j].first %
                MOD1) % MOD1;
            p.second = (rev_hash_val[i].second
                + 111 * s[i] * pw[j].second %
                MOD2) % MOD2;
            rev_hash_val.push_back(p);
        }
    }
    pair<int, int> get_hash(int l, int r)
    { // 1 indexed
        pair<int, int> ans;
```

```

ans.first = (hash_val[r].first -
hash_val[l - 1].first + MOD1) *
11l * ipw[l - 1].first % MOD1;
ans.second = (hash_val[r].second -
hash_val[l - 1].second + MOD2) *
11l * ipw[l - 1].second % MOD2;
return ans;
}
pair<int, int> rev_hash(int l, int r)
{ // 1 indexed
pair<int, int> ans;
ans.first = (rev_hash_val[r].first -
rev_hash_val[l - 1].first +
MOD1) * 11l * ipw[n - r].first %
MOD1;
ans.second = (rev_hash_val[r].second -
rev_hash_val[l - 1].second +
MOD2) * 11l * ipw[n - r].second
% MOD2;
return ans;
}
pair<int, int> get_hash() { // 1
indexed
return get_hash(1, n);
}
bool is_palindrome(int l, int r) {
return get_hash(l, r) == rev_hash(l,
r);
}
};

```

6.2 Hashing with Updates

```

using T = array<int, 2>;
const T MOD = {127657753, 987654319};
const T p = {137, 277}; // change here
T operator + (T a, int x) {return {(a[0]
+ x) % MOD[0], (a[1] + x) % MOD[1]};}
T operator - (T a, int x) {return {(a[0]
- x + MOD[0]) % MOD[0], (a[1] - x +
MOD[1]) % MOD[1]};}
T operator * (T a, int x) {return
{((int)((long long) a[0] * x %
MOD[0]), (int)((long long) a[1] * x
% MOD[1]));}
T operator + (T a, T x) {return {(a[0] +
x[0]) % MOD[0], (a[1] + x[1]) %
MOD[1]};}
T operator - (T a, T x) {return {(a[0] -
x[0] + MOD[0]) % MOD[0], (a[1] -
x[1] + MOD[1]) % MOD[1]};}
T operator * (T a, T x) {return
{((int)((long long) a[0] * x[0] %
MOD[0]), (int)((long long) a[1] *
x[1] % MOD[1]));}
ostream& operator << (ostream& os, T
hash) {return os << "(" << hash[0]
<< ", " << hash[1] << ")";}
T pw[N], ipw[N];
void prec() {
pw[0] = {1, 1};
for (int i = 1; i < N; i++) {
pw[i] = pw[i - 1] * p;
}
ipw[0] = {1, 1};

```

```

T ip = {power(p[0], MOD[0] - 2,
MOD[0]), power(p[1], MOD[1] - 2,
MOD[1])};
for (int i = 1; i < N; i++) {
ipw[i] = ipw[i - 1] * ip;
}
}
struct Hashing {
int n;
string s; // 1 - indexed
vector<array<T, 2>> t; // (normal, rev)
hash
array<T, 2> merge(array<T, 2> l,
array<T, 2> r) {
l[0] = l[0] + r[0];
l[1] = l[1] + r[1];
return l;
}
void build(int node, int b, int e) {
if (b == e) {
t[node][0] = pw[b] * s[b];
t[node][1] = pw[n - b + 1] * s[b];
return;
}
int mid = (b + e) >> 1, l = node <<
1, r = l | 1;
build(l, b, mid);
build(r, mid + 1, e);
t[node] = merge(t[l], t[r]);
}
void upd(int node, int b, int e, int
i, char x) {
if (b > i || e < i) return;
if (b == e && b == i) {
t[node][0] = pw[b] * x;
t[node][1] = pw[n - b + 1] * x;
return;
}
int mid = (b + e) >> 1, l = node <<
1, r = l | 1;
upd(l, b, mid, i, x);
upd(r, mid + 1, e, i, x);
t[node] = merge(t[l], t[r]);
}
array<T, 2> query(int node, int b, int
e, int i, int j) {
if (b > j || e < i) return {T({0,
0}), T({0, 0})};
if (b >= i && e <= j) return t[node];
int mid = (b + e) >> 1, l = node <<
1, r = l | 1;
return merge(query(l, b, mid, i, j),
query(r, mid + 1, e, i, j));
}
Hashing() {}
Hashing(string _s) {
n = _s.size();
s = "." + _s;
t.resize(4 * n + 1);
build(1, 1, n);
}
void upd(int i, char c) {
upd(1, 1, n, i, c);
s[i] = c;
}

```

```

}
T get_hash(int l, int r) { // 1 -
indexed
return query(1, 1, n, l, r)[0] *
ipw[l - 1];
}
T rev_hash(int l, int r) { // 1 -
indexed
return query(1, 1, n, l, r)[1] *
ipw[n - r];
}
T get_hash() {
return get_hash(1, n);
}
bool is_palindrome(int l, int r) {
return get_hash(l, r) == rev_hash(l,
r);
}
};

```

6.3 Hashing with Upd and Deletes

```

// update or delete a char in the string
or check whether a range [l,r] is a
palindrome or not (Palindromic Query I
- Toph)
#define int long long
const int N = 1e5 + 9;
int en;
struct ST {
pair<int, int> tree[4 * (N + N)];
void build(int n, int b, int e) {
if (b == e) {
tree[n].first = b;
tree[n].second = 1;
return;
}
int mid = (b + e) >> 1, l = n << 1,
r = l + 1;
build(l, b, mid);
build(r, mid + 1, e);
tree[n].second = tree[l].second +
tree[r].second;
}
void upd(int n, int b, int e, int i,
int x1, int x2) {
if (b > i || e < i) return;
if (b == e && b == i) {
tree[n].first = x1;
tree[n].second = x2;
return;
}
int mid = (b + e) >> 1, l = n << 1,
r = l + 1;
upd(l, b, mid, i, x1, x2);
upd(r, mid + 1, e, i, x1, x2);
tree[n].second = tree[l].second +
tree[r].second;
}
pair<int, int> query(int n, int b, int
e, int x) {
if (b > e) return {-1, -1};
if (tree[n].second < x) return
{tree[n].second, -1};
if (b == e) return tree[n];
}
}
int mid = (b + e) >> 1, l = n << 1,
r = l + 1;
pair<int, int> L = query(l, b, mid,
x);
if (L.second != -1) return L;
pair<int, int> R = query(r, mid + 1,
e, x - L.first);
return R;
}
} st, st2;
using T = array<int, 2>;
const T MOD = {127657753, 987654319};
const T p = {137, 277};
// add operators overloading of T (from
only upd) + prec()
int get(int i, int n) {
return n - i + 1;
}
}
struct Hashing {
int n; string s;
vector<T> tree, lazy;
void push(int node, int b, int e) {
if (lazy[node][0] == 1) return;
tree[node] = tree[node] * lazy[node];
if (b != e) {
int l = node << 1, r = l + 1;
lazy[l] = lazy[l] * lazy[node];
lazy[r] = lazy[r] * lazy[node];
}
lazy[node] = T{1, 1};
}
void build(int node, int b, int e) {
lazy[node] = T{1, 1};
if (b == e) {
tree[node] = pw[b] * s[b];
return;
}
int mid = (b + e) >> 1, l = node <<
1, r = l | 1;
build(l, b, mid);
build(r, mid + 1, e);
tree[node] = tree[l] + tree[r];
}
void upd(int node, int b, int e, int
i, T x) {
push(node, b, e);
if (b > i || e < i) return;
if (b == e && b == i) {
tree[node] = x;
return;
}
int mid = (b + e) >> 1, l = node <<
1, r = l + 1;
upd(l, b, mid, i, x);
upd(r, mid + 1, e, i, x);
tree[node] = tree[l] + tree[r];
}
void del(int node, int b, int e, int
i, int j) {
push(node, b, e);
if (b > j || e < i) return;
if (b >= i && e <= j) {
lazy[node] = lazy[node] * ipw[1];
push(node, b, e);
}
}
}

```

```

    return;
}
int mid = (b + e) >> 1, l = node <<
    1, r = l + 1;
del(l, b, mid, i, j);
del(r, mid + 1, e, i, j);
tree[node] = tree[l] + tree[r];
}
T query(int node, int b, int e, int i,
    int j) {
    push(node, b, e);
    if (b > j || e < i) return {0, 0};
    if (b >= i && e <= j) return
        tree[node];
    int mid = (b + e) >> 1, l = node <<
        1, r = l + 1;
    T L = query(l, b, mid, i, j);
    T R = query(r, mid + 1, e, i, j);
    return L + R;
}
Hashing() {}
Hashing(string _s) {
    s = _s;
    n = s.size();
    s = '.' + s;
    tree.resize(4 * n + 1);
    lazy.resize(4 * n + 1);
    build(1, 1, n);
}
void upd(int i, char c, int cur) {
    T x = pw[i] * c;
    if (cur == 1) i = st.query(1, 1, en,
        i).first;
    else i = st2.query(1, 1, en, i).first;
    upd(1, 1, n, i, x);
}
void del(int i, int cur) {
    int orgi = i;
    T x = pw[i] * 011;
    if (cur == 1) i = st.query(1, 1, en,
        i).first;
    else i = st2.query(1, 1, en, i).first;
    upd(1, 1, n, i, x);
    del(1, 1, n, i + 1, n);
    if (cur == 1) st.upd(1, 1, en, i, i,
        0);
    else st2.upd(1, 1, en, i, i, 0);
}
T get_hash(int l, int r, int cur) { // 1
    - indexed
    int ll = st.query(1, 1, en, l).first;
    int rr = st.query(1, 1, en, r).first;
    if (cur == 2) {
        ll = st2.query(1, 1, en, l).first;
        rr = st2.query(1, 1, en, r).first;
    }
    return query(1, 1, n, ll, rr) *
        ipw[l - 1];
}
};
int32_t main() {
    prec(); // must include
    string s; cin >> s;
    int n = s.size();

```

```

    int q; cin >> q;
    string t = s;
    reverse(t.begin(), t.end());
    Hashing hs(s), hs2(t);
    en = n + q + 5;
    st.build(1, 1, en);
    st2.build(1, 1, en);
    while (q--) {
        char c; cin >> c;
        if (c == 'C') {
            int l, r; cin >> l >> r;
            int l2 = get(l, n);
            int r2 = get(r, n);
            if (hs.get_hash(l, r, 1) ==
                hs2.get_hash(r2, l2, 2)) cout
                << "Yes!\n";
            else cout << "No!\n";
        }
        else if (c == 'U') {
            int i; char x; cin >> i >> x;
            int i2 = get(i, n);
            hs.upd(i, x, 1);
            hs2.upd(i2, x, 2);
        }
        else {
            int i; cin >> i;
            int i2 = get(i, n);
            hs.del(i, 1);
            hs2.del(i2, 2);
            --n;
        }
    }
}

```

6.4 Hashing on Tree

// Given a tree, Check whether it is symmetrical or not. Problem - CF G. Symmetree

// The value for each node is it's subtree size and position is the level (ordered). But the order of childs doesn't matter (unordered)

```

const int N = 2e5 + 9;
vector<int> g[N];
vector<array<int, 3>> hashh[N]; // hash1,
    hash2, node
int n, sz[N];
const int MOD1 = 1e9 + 9, MOD2 = 1e9 + 21;
const int p1 = 1e5 + 19, p2 = 1e5 + 43;
void dfs2(int u, int p, int lvl) {
    array<int, 3> my_hash;
    my_hash[0] = 111 * sz[u] *
        pw[lvl].first % MOD1;
    my_hash[1] = 111 * sz[u] *
        pw[lvl].second % MOD2;
    my_hash[2] = u;
    bool leaf = true;
    for (auto v : g[u]) {
        if (v != p) {
            dfs2(v, u, lvl + 1);
            leaf = false;
        }
    }
    if (!leaf) {
        int sum1 = 1, sum2 = 1;

```

```

        for (auto here : hashh[u]) {
            auto [x, y, _] = here;
            sum1 = (sum1 * x) % MOD1;
            sum2 = (sum2 * y) % MOD2;
        }
        my_hash[0] = power(my_hash[0], sum1,
            MOD1);
        my_hash[1] = power(my_hash[1], sum2,
            MOD2);
    }
    hashh[p].push_back(my_hash);
}
bool ok(int u) {
    map<pair<int, int>, int> mp;
    for (auto [x, y, who] : hashh[u]) {
        mp[{x, y}]++;
    }
    int odd = 0;
    pair<int, int> val;
    for (auto [here, cnt] : mp) {
        odd += cnt & 1;
        if (cnt & 1) val = here;
    }
    if (odd == 0) return true;
    if (odd > 1) return false;
    int node;
    for (auto [x, y, who] : hashh[u]) {
        pair<int, int> here = {x, y};
        if (here == val) node = who;
    }
    return ok(node);
}
void solve() {
    cin >> n; clr(n);
    for (int i = 2; i <= n; i++) {
        int u, v; cin >> u >> v;
        g[u].push_back(v);
        g[v].push_back(u);
    }
    dfs(1, 0); // calc. subtree size
    dfs2(1, 0, 1);
    if (ok(0)) cout << "YES\n";
    else cout << "NO\n";
}

```

6.5 Compare 2 strings Lexicographically

// Time: $O(\log n)$

```

string s;
Hashing hs;
// return 0 if both equal
// return 1 if first substring greater
// return -1 if second substring greater
// here lcp() provides the len of longest
    common prefix
int compare(int i, int j, int x, int y) {
    int common_prefix = lcp(i, j, x, y);
    int len1 = j - i + 1, len2 = y - x + 1;
    if (common_prefix == len1 and len1 ==
        len2) return 0;
    else if (common_prefix == len1) return
        -1;
    else if (common_prefix == len2) return
        1;

```

```

    else return (s[i + common_prefix - 1]
        < s[j + common_prefix - 1] ? -1 :
        1);
}

```

6.6 KMP

```

vector<int> build_lps(string &pat) {
    int n = pat.size();
    vector<int> lps(n, 0);
    for (int i = 1; i < n; i++) {
        int j = lps[i - 1];
        while (j > 0 and pat[i] != pat[j]) {
            j = lps[j - 1];
        }
        if (pat[i] == pat[j]) j++;
        lps[i] = j;
    }
    return lps;
}
int kmp(string &txt, string &pat) {
    string s = pat + '#' + txt;
    vector<int> lps = build_lps(s);
    int ans = 0;
    for (auto x : lps) {
        if (x == pat.size()) ans++;
    }
    return ans;
}
int kmp(string &txt, string &pat) {
    vector<int> lps = build_lps(pat);
    int n = txt.size(), m = pat.size();
    int ans = 0;
    int j = 0;
    for (int i = 0; i < n; i++) {
        while (j > 0 and txt[i] != pat[j]) {
            j = lps[j - 1];
        }
        if (txt[i] == pat[j]) j++;
        if (j == m) {
            ans++;
            j = lps[j - 1];
        }
    }
    return ans;
}

```

6.7 KMP Automata

// like DFA. if string is "abcdeabg", aut[7]['c'] = 3. Means 7th index e 'c' bosaile LPS koto, aut[7]['g'] = 8

```

void compute_automaton(string s,
    vector<vector<int>>& aut) {
    s += '#';
    int n = s.size();
    vector<int> pi = build_lps(s);
    aut.assign(n, vector<int>(26));
    for (int i = 0; i < n; i++) {
        for (int c = 0; c < 26; c++) {
            if (i > 0 && 'a' + c != s[i])
                aut[i][c] = aut[pi[i - 1]][c];
            else
                aut[i][c] = i + ('a' + c == s[i]);
        }
    }
}

```

6.8 Prefix Occurance Count

```
// Count the number of occurrences of each
// prefix
vector<int> ans(n + 1);
for (int i = 0; i < n; i++) ans[lps[i]]++;
for (int i = n - 1; i > 0; i--)
    ans[lps[i - 1]] += ans[i];
for (int i = 0; i <= n; i++) ans[i]++;
```

6.9 Number of palindromic substring in L to R using Wavelet Tree

```
// Problem - Kattis palindromes
ll f(int x) {
    return (1ll * x * (x + 1)) / 2;
}
ll f(int l, int r) {
    if (l > r) return 0;
    return f(r) - f(l - 1);
}
bool ok(int l, int r) {
    return hash_s.is_palindrome(l, r);
}
int32_t main() {
    cin >> s;
    n = s.size();
    hash_s = Hashing(s);
    for (int i = 1; i <= n; i++) {
        int l = 0, r = min(n - i, i - 1),
            cnt = 1;
        while (l <= r) {
            int mid = (l + r) >> 1;
            if (ok(i - mid, i + mid)) {
                cnt = mid;
                l = mid + 1;
            }
            else r = mid - 1;
        }
        pi1[i] = cnt + 1;
        pi1_left[i] = pi1[i] - i;
        pi1_right[i] = i + pi1[i];
    }
    for (int i = 2; i <= n; i++) {
        if (s[i - 1] == s[i - 2]) {
            int l = 0, r = min(n - i, i - 1),
                cnt = 2;
            while (l <= r) {
                int mid = (l + r) >> 1;
                if (ok(i - 1 - mid, i + mid)) {
                    cnt = mid;
                    l = mid + 1;
                }
                else r = mid - 1;
            }
            pi2[i] = cnt + 1;
        }
        else pi2[i] = 0;

        pi2_left[i] = pi2[i] - i;
        pi2_right[i] = i + pi2[i];
    }
    // wavelet trees (odd_len_left,
    // odd_len_right, even_len_left,
    // even_len_right)
    t1.init(pi1_left + 1, pi1_left + n + 1, -N, N);
```

```
t2.init(pi1_right + 1, pi1_right + n + 1, -N, N);
t3.init(pi2_left + 1, pi2_left + n + 1, -N, N);
t4.init(pi2_right + 1, pi2_right + n + 1, -N, N);

int q; cin >> q;
while (q--) {
    int l, r; cin >> l >> r;
    // define k, find cnt > k and
    // summation whose are <= k;
    int m = (l + r) / 2;
    int k = 1 - l;
    ll ans = f(l, m);
    ans += t1.sum(l, m, k);
    int cnt = t1.GT(l, m, k);
    ans += 1ll * k * cnt;
    k = 1 + r;
    ans += -f(m + 1, r);
    ans += t2.sum(m + 1, r, k);
    cnt = t2.GT(m + 1, r, k);
    ans += 1ll * k * cnt;
    if (l + 1 <= m) { // a bit different
        // than others
        k = -l;
        ans += f(l + 1, m);
        ans += t3.sum(l + 1, m, k);
        cnt = t3.GT(l + 1, m, k);
        ans += 1ll * k * cnt;
    }
    k = 1 + r;
    ans += -f(m + 1, r);
    ans += t4.sum(m + 1, r, k);
    cnt = t4.GT(m + 1, r, k);
    ans += 1ll * k * cnt;
    cout << ans << '\n';
}
}
```

It is easier to explain by considering only palindromes centered at indices (so, odd length), the idea is the same anyway. For each index i , r_i will be the longest radius of a palindrome centered there (in other words, the amount of palindromes centered at index i). Directly from manacher, this takes $\mathcal{O}(n)$ to calculate.

For a query $[l, r]$, we first compute $m = \frac{l+r}{2}$. Now we want to calculate

$$\sum_{i=l}^m \min(i - l + 1, r_i) + \sum_{i=m+1}^r \min(r - i + 1, r_i)$$

$$\sum_{i=l}^m \min(i - l + 1, r_i) = \sum_{i=l}^m i + \min(1 - l, r_i - i).$$

The sum over i can be found in constant time. As for the other term, if we create some array $r'_i = r_i - i$ during the preprocessing, then the queries are asking for some over range of $\min(C, r'_i)$ where C is constant. You can solve this in $\mathcal{O}(\log n)$ per query using wavelet tree.