Lab Report – EE-170L Computer Programming (Lab 02)

NAME	Muhammad Fazil safdar
Reg.no	0724
SEMESTER	2nd
LAB report	6
DATE	21/4/2026

1. Objectives

- Understand the concept and syntax of the **for loop** in C++.
- Learn how to implement **nested for loops** for structured and repeated operations.
- Apply loops to solve problems such as counting, pattern printing, and mathematical computations.

2. Theory

2.1 The for Loop

A for loop is a control structure that allows code to be executed repeatedly based on a condition. It is typically used when the number of iterations is known beforehand.

Syntax:

```
for (initialization; condition; update) {
    // statements to execute
}
```

initialization: Executed once at the beginning. Used to initialize loop control variables.

- Condition: Evaluated before each iteration. If true, the loop body executes.
- Update: Executed after each iteration. Typically used to modify the loop variable.

Flow Diagram:

Code

```
Start
  |
Initialization
  |
Condition True? ---- No ---> Exit Loop
  |
  v
Statements
  |
Update
  |
Go back to Condition
```

2.2 Nested for Loops

A nested loop is a loop inside another loop. The inner loop completes all its iterations for each iteration of the outer loop. Useful for multi-dimensional data like tables and patterns.

3. Programs Implemented

3.1 Countdown from 5 to 1

```
#include <iostream>          // Include input-output stream
using namespace std;         // Use standard namespace

int main() {       // beginning of main function
   for (int i = 5; i > 0; i--) {  // Initialize i=5; loop while i>0; decrement i
 cout << i <<end l; // Print current value of i
   }
   cout << "outside loop now"; // Print after loop ends
   return 0;          // End of program
}
```

Output:

```
5
4
3
2
1
outside loop now
```

3.2 Prime Number Check

```
#include <iostream>
using namespace std;
```

```
int main() {
    int num;                        // Variable to store user input
    cout << "Enter a number please\n";     // Prompt user
    cin >> num;                         // Read input
    int flag = 0;                       // Flag to track if number is not prime

    for (int i = 2; i < num; i++) {        // Loop from 2 to num-1
        if (num % i == 0) {                // Check if num is divisible by i
            flag = 1;                   // Set flag if divisible
            break;                      // Exit loop early
        }
    }

    if (flag == 1) {
        cout << num << " is not a prime number\n";          // Not prime
        } else {
        cout << num << " is a prime number\n";      // Prime
        }
        return 0;
}
```

3.3 Nested Loop Pattern Printing

```
#include <iostream>

using namespace std;


int main() {

    for (int num = 7; num > 0; num--) {        // Outer loop from 7 to 1

        for (int j = 1; j <= num; j++) {      // Inner loop from 1 to num

            cout << j << " ";                // Print numbers in row

        }

        cout << "\n";                         // New line after each row

    }

    return 0;

}
```

Output:

```
1 2 3 4 5 6 7

1 2 3 4 5 6

1 2 3 4 5

1 2 3 4

1 2 3

1 2

1
```

4. Lab Tasks

4.1 While Loop: Display Numbers from 1 to 10

```
#include <iostream>

using namespace std;

int main() {
    int i = 1;                    // Initialize counter
    while (i <= 10) {             // Loop while i <= 10
        cout << i << endl;        // Print current number
        i++;                      // Increment counter
    }
    return 0;
}
```

4.2 Multiplication Table using Nested For Loops

```
#include <iostream>

using namespace std;
```

```
int main() {
    for (int i = 1; i <= 10; i++) {        // Outer loop for rows
        for (int j = 1; j <= 10; j++) {    // Inner loop for columns
            cout << i * j << "\t";         // Print product with tab
        }
        cout << endl;                      // New line after each row
    }
    return 0;
}
```

4.3 Sum of Numbers from 1 to N

```
#include <iostream>      // include input/output library
using namespace std;     // use standard namespace


int main() {
    int n, sum = 0;      // declare n and initialize sum
    cout << "Enter a positive integer: "; // ask user for input
    cin >> n;            // read input into n


    for (int i = 1; i <= n; i++) {   // loop from 1 to n
        sum += i;                    // add i to sum
    }
```

```
    cout << "Sum = " << sum << endl; // display result
    return 0;       }               // end program
```

4.4 Triangle Pattern Printing

```
#include <iostream>
using namespace std;

int main() {
    int n, sum = 0;                         // Declare variables
    cout << "Enter a positive integer: ";  // Prompt user
    cin >> n;                               // Read input

    for (int i = 1; i <= n; i++) {          // Loop from 1 to n
        sum += i;                           // Add i to sum
    }

    cout << "Sum = " << sum;                // Display result
    return 0;
}
```

5. Conclusion

- The lab provided hands-on experience with **for loops**, **while loops**, and **nested loops**.
- Students learned how to control program flow using loop constructs.
- Practical applications included counting, checking prime numbers, generating multiplication tables, and printing patterns.
- These concepts are foundational for solving repetitive tasks efficiently in programming.