


Consolidated Competition Ballistics

A Comprehensive Mathematical Manual
with Reloading Guide and Julia Implementations



Trajectory with aerodynamic drag and gravity

*Merging Core Theory, Advanced Effects, and Practical Shooting Tools
Drag Models (G1–G8), Coriolis & Eötvös Effects, Spin Drift,
Aerodynamic Jump, Wind Deflection, and Handloading Data*

Version 3.2 — August 14, 2026

Abstract

This manual provides a rigorous mathematical treatment of competition rifle ballistics. Version 3.1 brought precision improvements to the 3-DOF engine (coordinate-system alignment and $4/\pi$ drag scaling) and outlined a roadmap for a 6-DOF expert mode.

Version 3.2 records that the 6-DOF is no longer a roadmap: it is implemented and validated against three published cases — McCoy's .308 in 168 gr textbook example, the 105 mm HE M1 shell, and the 5.56 mm NATO family measured at the Ballistic Research Laboratory. This edition adds the moment-of-inertia estimator that feeds it (Section 8.8), the measured coefficient sets it can be run on, and the reasons a set may not be trusted. It also corrects an inclined-fire example that had drifted 10% from what both implementations return, and qualifies the recommendation of spline interpolation, which is right for the dense standard drag tables and wrong for sparse measured ones.

Contents

Notation and Conventions	vii
1 Introduction to Competition Rifle Ballistics	1
1.1 Motivation: Why Math Matters in Marksmanship	1
1.2 Scope and Purpose	1
1.3 Overview of Ballistic Phases	1
1.4 Historical Context	2
2 Atmospheric Model	3
2.1 Motivation: Why Air Density is King	3
2.2 ICAO Standard Atmosphere	4
2.2.1 Temperature Lapse Rate	4
2.2.2 Pressure–Altitude Relationship	4
2.3 Air Density	5
2.3.1 Humidity Correction	5
2.4 Speed of Sound	6
2.5 Density Altitude	6
2.6 Julia Implementation: Atmospheric Model	7
3 Interior Ballistics	9
3.1 Motivation: The Engine of the Bullet	9
3.2 The Thermodynamic Problem	9
3.2.1 Noble–Abel Equation of State	9
3.2.2 Energy Balance	10
3.3 Simplified Closed-Bomb Model	10
3.4 Burn Rate Law	10
3.4.1 Geometric Form Function	11
3.5 Le Duc Velocity Model	11
3.6 Pressure–Travel Relationship	11
3.7 Muzzle Velocity Estimation for Handloaders	11
3.7.1 Temperature Sensitivity of Muzzle Velocity	12
4 Transitional Ballistics	13
4.1 Motivation: The Chaos of the Muzzle	13
4.2 Muzzle Gas Dynamics	13
4.3 Muzzle Tip-Off and Initial Yaw	14
4.4 Base Drag Transition	14
4.5 Crown Effects	14
5 Exterior Ballistics: Core Theory	15
5.1 Motivation: The Math of Free Flight	15
5.2 Vacuum Trajectory (The Baseline)	15
5.3 Aerodynamic Drag	16

5.3.1	The Drag Equation	16
5.3.2	Drag Coefficient and Mach Number	16
5.3.3	Analytical Solution for 1D Drag	16
5.4	Ballistic Coefficient	17
5.4.1	Standard Conditions for BC	17
5.5	Standard Drag Models (G1 through G8)	18
5.5.1	G7 Drag Function	19
5.5.2	Drag Functions vs. Siacci Tables: a Common Confusion	19
5.6	Doppler Radar Drag Measurement	19
5.6.1	Measurement Principle	20
5.6.2	Extracting $C_D(Ma)$ from Radar Data	20
5.6.3	Advantages over Classical Methods	20
5.6.4	Interpolation of Tabular Drag Data	20
5.7	Equations of Motion: 3-DOF Point-Mass Model	21
5.7.1	Coordinate System	21
5.7.2	Vector Equation of Motion	22
5.7.3	Scalar Component Equations	22
5.7.4	Using the Ballistic Coefficient	22
5.8	Numerical Integration	22
5.8.1	Euler Method	22
5.8.2	Runge–Kutta (RK4) & Area Scaling	23
6	Exterior Ballistics: Advanced Effects	25
6.1	Motivation: Beyond Gravity	25
6.2	Wind Deflection	25
6.2.1	Wind Components (Vectors)	25
6.2.2	Simple Approximation	26
6.2.3	The Lag Rule (The Didion Approximation)	26
6.3	Spin Drift	26
6.3.1	Gyroscopic Stability Factor	26
6.4	Coriolis and Eötvös Effects	27
6.4.1	Coriolis Acceleration	27
6.4.2	Horizontal Deflection	27
6.4.3	Vertical Deflection (Eötvös Effect)	27
6.4.4	Implementation	27
6.5	Aerodynamic Jump	28
6.6	Magnus Effect	28
7	Complete 3-DOF Ballistic Solver	29
7.1	Motivation: From Paper to Code	29
8	Six-Degree-of-Freedom (6-DOF) Model	31
8.1	Motivation: Unlocking the Gyroscope	31
8.2	State Vector and Reference Frames	32
8.2.1	Coordinate Systems (Inertial vs Body)	32
8.2.2	Euler Angles and Orientation	32
8.2.3	The 12-Component State Vector	33
8.3	Translational Equations of Motion	33
8.3.1	Total Angle of Attack	33
8.3.2	Aerodynamic Force Components	33
8.4	Rotational Equations of Motion	34
8.4.1	Aerodynamic Moments	34

8.4.2	Summary of Moment Components	34
8.5	Kinematic Equations	35
8.6	Quaternion Formulation (Singularity-Free)	35
8.7	Aerodynamic Coefficient Database	35
8.7.1	Typical Values for Match Bullets	35
8.7.2	Measured Sets: What Actually Exists	36
8.7.3	Deriving C_{D_0} from the Ballistic Coefficient	37
8.8	Moments of Inertia	37
8.8.1	Why the Solid-Cylinder Form Is Not Good Enough	37
8.8.2	Integration over the Actual Contour	37
8.8.3	Default Contour, and What It Costs	38
8.8.4	Constructions the Model Does Not Cover	38
8.9	Spin Rate and Initial Conditions	39
8.10	Stability Revisited from 6-DOF Theory	39
8.10.1	Gyroscopic Stability	39
8.10.2	Dynamic Stability	39
8.11	Comparison: 3-DOF vs. 6-DOF	39
8.12	Julia Implementation: 6-DOF Solver	40
9	Angular Measurement and Sighting Systems	41
9.1	Motivation: Speaking the Language of the Scope	41
9.2	Minute of Angle (MOA)	41
9.3	Milliradian (Mil, MRAD)	41
10	Reloading Guide for Competition Shooters	43
10.1	Motivation: Controlling the Variables	43
10.2	Cartridge Selection for Competition	43
10.3	Propellant Selection	43
10.4	Representative Load Data	44
10.5	Complete Worked Example: 6mm BR at 1000 Yards	45
10.5.1	Step 1: Component Data	45
10.5.2	Step 2: Stability Check	45
10.5.3	Step 3: Atmospheric Conditions	45
10.5.4	Step 4: Solver Setup and Trajectory	46
10.5.5	Step 5: Analysis of Results	47
10.5.6	Step 6: Chronograph Validation	47
10.5.7	Step 7: DOPE Card Summary	48
10.6	Interpreting Chronograph Data	48
10.6.1	Velocity SD Impact on Vertical Dispersion	49
11	Ballistic Reference Tables	51
11.1	Bullet Data for Common Competition Bullets	51
11.2	Sample Trajectory Table	51
12	Special Topics	53
12.1	Motivation: The Edges of the Envelope	53
12.2	Transonic Stability	53
12.3	Inclined Fire (Rifleman's Rule)	53
12.4	Barrel Harmonics and Optimal Charge Weight	54
13	Error Budget and Sensitivity Analysis	55
13.1	Motivation: Knowing Your Weakest Link	55

13.2 Sensitivity Coefficients	55
14 Ballistic Implications for Reloading	57
14.1 Motivation: Crafting the Perfect Formula	57
14.2 The Reloader's Equation: What You Control	57
14.3 Muzzle Velocity: The Central Reloading Output	57
14.3.1 Charge Weight and Velocity	57
14.3.2 Velocity Consistency and Vertical Dispersion	57
14.3.3 Achieving Low SD: Quantitative Checklist	58
14.4 BC Sensitivity and Bullet Selection	58
14.5 Temperature Effects: Propellant and Atmosphere	58
14.5.1 Combined Temperature Effect	58
14.6 Seating Depth and Internal Ballistic Coupling	59
14.7 Pressure Estimation and Safety Margins	59
14.8 Barrel Life	60
14.9 Load Development Workflow	60
A Detailed Mathematical Derivations	61
A.1 Motivation: Showing the Work	61
A.2 Derivation of the Point-Mass Equations of Motion	61
A.3 Derivation of the Coriolis Terms	61
A.4 Derivation of Spin Drift via Yaw of Repose	61
B Companion Julia Package	63
C Greenhill's Formula and Twist Rate Selection	65
C.1 Motivation: Keeping the Bullet Pointy-End Forward	65
Glossary	69

List of Tables

3.1	Measured muzzle velocity vs. barrel length, .308 Win / Lapua 155 gr Scenar .	12
5.1	BRL Standard Drag Models [McCoy, 2012, Ingalls, 1893]	18
5.2	Selected G7 drag coefficient values [McCoy, 2012]	19
8.1	Typical aerodynamic coefficients for a 6.5 mm 140 gr VLD match bullet . . .	35
8.2	Measured aerodynamic sets carried by the implementation	36
8.3	Comparison of 3-DOF and 6-DOF models	39
10.1	Popular competition cartridges and their characteristics	43
10.2	Popular propellants for competition rifle cartridges	44
10.3	6.5 Creedmoor representative loads (24-inch barrel)	44
10.4	.308 Winchester representative loads (24-inch barrel)	44
10.5	6mm Creedmoor representative loads (26-inch barrel)	44
10.6	6mm BR Norma representative loads (26-inch barrel)	45
10.7	Computed trajectory: 6mm BR, 105 gr Berger Hybrid, $v_0 = 2920$ fps, 27.8°C (82°F), 29.75 in Hg, 55% RH. 8 mph wind at 60° . 100 yd zero. 1:7.5 RH twist, 45.4°N , firing West.	47
10.8	DOPE card: 6mm BR 105 Berger / N140 / 2920 fps. Ottawa, 27.8°C (82°F), 29.75 inHg. Wind hold is per 1 mph full crosswind.	48
10.9	Typical velocity consistency: factory ammunition vs. optimized handloads . .	48
11.1	Ballistic data for popular competition bullets [Litz, 2011, 2015]	51
11.2	Trajectory: 6.5 CM, 140 gr Berger Hybrid, $\text{BC}_{\text{G7}} = 0.311$, $v_0 = 2700$ fps, 100 yd zero, sea level standard atmosphere	51
12.1	Approximate transonic transition ranges for common competition cartridges at sea-level standard conditions. The transonic zone is defined as $0.9 \leq Ma \leq 1.1$ ($\approx 310\text{--}380 \frac{\text{m}}{\text{s}}$).	53
13.1	Error budget: 6.5 Creedmoor, 140 gr, $\text{BC}_{\text{G7}} = 0.311$, 2700 fps at 1000 yd . .	55
14.1	Velocity sensitivity: vertical shift per 1 fps change, 6.5 CM 140 gr	58
14.2	Estimated velocity SD contributions by reloading variable	58
14.3	Temperature sensitivity by propellant class	59
14.4	SAAMI maximum average pressure for competition cartridges	59
14.5	Approximate barrel life for competition cartridges	60

List of Figures

2.1	The aerodynamic drag force opposes the bullet's velocity. Notice that the force scales linearly with air density ρ	3
2.2	ICAO Standard Atmosphere profiles (troposphere, 0–11 km). Temperature decreases linearly at $L = 6.5$ K/km, while pressure and density follow power laws with exponents $n = 5.256$ and $n - 1 = 4.256$ respectively. The dashed vertical line marks 1500 m, a typical mountain shooting altitude where density is already reduced by $\approx 14\%$	5
2.3	Relative change in air density for common deviations from ICAO standard conditions (15°C , sea level, 1013 hPa, dry air). Negative values indicate reduced density and less aerodynamic drag. Altitude and temperature are the dominant factors; humidity is negligible ($< 2\%$).	6
2.4	Schematic trajectory comparison for a 6.5 mm 140 gr VLD bullet ($B_C = 0.311$ G7, $v_0 = 2700$ fps) under different atmospheric conditions. The spread between extreme conditions exceeds 1 m at 1000 m (> 3 MOA), demonstrating the necessity of atmospheric corrections for long-range shooting. Curves are polynomial approximations scaled by density ratio.	7
3.1	The thermodynamic system of a rifle cartridge. Expanding gases from burning propellant create immense pressure P that forces the bullet down the bore. .	9
4.1	Transitional ballistics: The bullet exiting the muzzle gets overtaken by rapidly expanding, supersonic propellant gases. A symmetrical gas release here is paramount to accuracy.	13
5.1	Schematic drag coefficient vs. Mach number for G1 and G7 reference projectiles.	16
5.2	Schematic silhouettes of three reference projectiles (nose to the right). The blunt, flat-based G1 differs markedly from a modern match bullet, whereas the long boat-tailed G7 closely matches it; G8 shares the G7 nose but keeps a flat base.	18
5.3	Drag coefficient of the G1 and G7 reference shapes versus Mach number (G7 values from Table 5.2; G1 representative BRL data). Both rise sharply through the transonic region, but the slender G7 has a markedly lower, flatter peak—the physical reason its B_C stays nearly constant across the supersonic range.	18
6.1	Decomposition of the total wind vector into range (w_x) and lateral (w_z) components. Only the w_z component causes side-to-side deflection.	25
8.1	The Earth-fixed inertial frame versus the bullet's Body-fixed frame. As the bullet pitches and yaws, the body frame rotates independently of the earth frame.	32

Notation and Conventions

Throughout this manual, the following conventions are used:

Symbol	Meaning	Typical Units
m	Projectile mass	gr or kg
d	Projectile caliber (diameter)	in or m
$v, \mathbf{v}$	Velocity (scalar, vector)	ft/s or $\frac{\text{m}}{\text{s}}$
v_0	Muzzle velocity	ft/s or $\frac{\text{m}}{\text{s}}$
C_D	Drag coefficient (dimensionless)	—
B_C	Ballistic coefficient	$\frac{\text{lbf}}{\text{in}^2}$
SD	Sectional density = m/d^2	$\frac{\text{lbf}}{\text{in}^2}$
i or FF	Form factor (dimensionless)	—
ρ	Air density	$\frac{\text{kg}}{\text{m}^3}$
A	Cross-sectional area = $\pi d^2/4$	m^2
g	Gravitational acceleration	$\frac{\text{m}}{\text{s}^2}$
Ma	Mach number = v/a	—
a	Local speed of sound	$\frac{\text{m}}{\text{s}}$
T	Temperature	K, °C, or °F
P	Barometric pressure	hPa or in Hg
H	Relative humidity	%
θ	Launch (elevation) angle	° or mil
ϕ	Latitude	°
ψ	Azimuth (heading)	°
ω_E	Earth's angular velocity	$7.2921 \times 10^{-5} \frac{\text{rad}}{\text{s}}$
S_g	Gyroscopic stability factor	—
τ	Twist rate	in. per turn
r	Range	yd or m
Δy	Vertical drop	in or m
E_k	Kinetic energy	J or ft·lbf

Default values. Parameters shown in [\[default: blue brackets\]](#) indicate default values used when the specific value is unknown. These are based on ICAO standard atmosphere and common competition shooting conditions.

Unit systems. All derivations use SI units internally. Conversion factors to Imperial units (grains, feet per second, inches, etc.) are provided throughout.

Chapter 1

Introduction to Competition Rifle Ballistics

1.1 Motivation: Why Math Matters in Marksmanship

When firing a rifle at a target 100 yards away, marksmanship is almost entirely about human mechanics: trigger control, breathing, and steady hold. However, as the range stretches to 1,000 yards and beyond, marksmanship transforms into applied physics. A perfectly executed trigger pull is mathematically guaranteed to miss if the shooter has not correctly accounted for the temperature of the air, the spin of the earth, or the aerodynamic decay of their bullet.

This manual is written for the shooter who wants to stop guessing and start calculating.

1.2 Scope and Purpose

This manual provides a rigorous mathematical treatment of the ballistic phenomena relevant to precision rifle competition, including but not limited to: F-Class, Palma, Benchrest, PRS (Precision Rifle Series), NRL (National Rifle League), High-Power, and long-range target shooting. The goal is to equip the competitive shooter with both the theoretical foundations and the practical computational tools needed to predict bullet trajectories to the highest possible accuracy.

Competition shooting demands sub-MOA accuracy at distances often exceeding 1000 yd. At these ranges, small errors in modeling atmospheric drag, spin drift, Coriolis deflection, or wind become dominant factors in the miss distance. This manual addresses each of these systematically.

1.3 Overview of Ballistic Phases

The flight of a bullet from ignition to impact is conventionally divided into four phases [McCoy, 2012]:

1. **Interior Ballistics** — The physics of the bullet inside the barrel, from primer ignition through propellant combustion to muzzle exit. Key outputs: muzzle velocity, chamber pressure, barrel time.
2. **Transitional (Intermediate) Ballistics** — The brief phase as the bullet exits the muzzle and the propellant gases dissipate. Muzzle blast interaction, base drag changes, and initial yaw (tip-off) are determined here.
3. **Exterior Ballistics** — The free-flight trajectory from muzzle to target. This is the dominant focus of competition ballistics: aerodynamic drag, gravity drop, wind deflection, spin drift, Coriolis and Eötvös effects, Magnus force, and aerodynamic jump.

- 4. Terminal Ballistics** — Bullet behavior at impact. While less critical for paper-target competition, terminal effects matter for steel-target energy requirements and for hunting-oriented competitions.

1.4 Historical Context

The mathematical study of projectile motion dates to Galileo and Newton, but modern exterior ballistics began with the work of Bashforth (1870), who conducted some of the earliest systematic drag measurements [Bashforth, 1870]. The Siacci method (1880s) introduced the concept of the ballistic coefficient and drag functions that remain in use today [Siacci, 1888]. In the 20th century, the US Army Ballistic Research Laboratory (BRL) at Aberdeen Proving Ground produced the definitive drag function tables—G1 through G8—that form the backbone of modern ballistic computation [McCoy, 2012, Ingalls, 1893].

Modern computational ballistics, exemplified by solvers such as those described by Litz [2011] and implemented in software like Bryan Litz’s Applied Ballistics suite, use 3-DOF and 6-DOF point-mass models with empirically measured drag data and atmospheric corrections.

Chapter 2

Atmospheric Model

The atmosphere is the invisible medium through which the bullet travels. In a vacuum, a bullet would follow a perfect parabola. In reality, the air acts as a viscous fluid that constantly robs the bullet of its kinetic energy, slowing it down and exposing it to wind. Accurate modeling of air density, speed of sound, and viscosity is the absolute prerequisite to all exterior ballistic calculations.

2.1 Motivation: Why Air Density is King

A shooter might carefully measure their muzzle velocity and bullet weight, but fail to account for the environment. The primary motivation for using a precise atmospheric model is that the environment dynamically changes the aerodynamic drag fighting the bullet.

To understand this, consider the fundamental aerodynamic drag force equation. Before we present it, let's clearly define the physical quantities involved:

- F_{drag} : The drag force opposing the bullet's motion (measured in Newtons, N).
- ρ (rho): The mass density of the air the bullet is currently flying through (measured in $\frac{\text{kg}}{\text{m}^3}$).
- C_d : The drag coefficient, a dimensionless number characterizing how "slippery" the bullet is.
- A : The frontal cross-sectional area of the bullet (measured in m^2).
- v : The velocity of the bullet relative to the surrounding air mass (measured in $\frac{\text{m}}{\text{s}}$).

With these defined, the drag force is expressed as:

$$F_{\text{drag}} = \frac{1}{2} \rho C_d A v^2 \quad (2.1)$$




Figure 2.1: The aerodynamic drag force opposes the bullet's velocity. Notice that the force scales linearly with air density ρ .

As seen in Eq. (2.1), the drag force is *directly proportional* to the air density ρ . Consequently, a 10% error in calculating the air density results in exactly a 10% error in the computed drag. This will directly and non-linearly affect vertical drop and wind drift.

At long ranges, these effects are substantial. For example, at 1,000 meters, the difference between typical summer (hot, thin air) and winter (cold, dense air) conditions can exceed one full meter (over 3 MOA) of vertical drop for a standard competition cartridge. By understanding and actively calculating these variables, a shooter stops relying on empirical "dope cards" and can mathematically guarantee first-round hits across varying climates.

2.2 ICAO Standard Atmosphere

To have a baseline for comparison, aerodynamicists and ballisticians use the International Civil Aviation Organization (ICAO) standard atmosphere. This defines standard "sea level" conditions [International Civil Aviation Organization, 1993, U.S. Committee on Extension to the Standard Atmosphere, 1976]. Let's define the benchmark variables:

$$\begin{aligned} T_0 &= 288.15 \text{ K} \quad (15^\circ\text{C}, 59^\circ\text{F}) \quad (\text{Standard Temperature}) \\ P_0 &= 101\,325 \text{ Pa} \quad (29.92 \text{ in Hg}) \quad (\text{Standard Pressure}) \\ \rho_0 &= 1.2250 \frac{\text{kg}}{\text{m}^3} \quad (\text{Standard Density}) \\ a_0 &= 340.294 \frac{\text{m}}{\text{s}} \quad (1116.45 \text{ ft/s}) \quad (\text{Speed of Sound}) \\ H_0 &= 0\% \quad (\text{Relative Humidity: completely dry air}) \end{aligned}$$

Default values: $T_0 = 288.15 \text{ K}$ (15°C), $P_0 = 101325 \text{ Pa}$, $\rho_0 = 1.225 \text{ kg/m}^3$, $H_0 = 0\%$.

2.2.1 Temperature Lapse Rate

Below 11 000 m (troposphere), the standard lapse rate is:

$$T(h) = T_0 - L \cdot h, \quad L = 0.0065 \frac{\text{K}}{\text{m}}$$

where h is the altitude above sea level in meters.

2.2.2 Pressure–Altitude Relationship

Using the barometric formula for the troposphere:

$$P(h) = P_0 \left(\frac{T(h)}{T_0} \right)^{g_0/(L R_{\text{air}})} = P_0 \left(1 - \frac{L h}{T_0} \right)^{5.2559}$$

where $g_0 = 9.806\,65 \frac{\text{m}}{\text{s}^2}$ and $R_{\text{air}} = 287.0528 \frac{\text{J}}{\text{kg}\cdot\text{K}}$.

Figure 2.2 shows how temperature, pressure, and density vary with altitude across the troposphere.




Figure 2.2: ICAO Standard Atmosphere profiles (troposphere, 0–11 km). Temperature decreases linearly at $L = 6.5$ K/km, while pressure and density follow power laws with exponents $n = 5.256$ and $n - 1 = 4.256$ respectively. The dashed vertical line marks 1500 m, a typical mountain shooting altitude where density is already reduced by $\approx 14\%$.

2.3 Air Density

The ideal gas law gives the dry-air density:

$$\rho_{\text{dry}} = \frac{P}{R_{\text{air}} T}$$

2.3.1 Humidity Correction

Humid air is *less dense* than dry air because water vapor ($M_w = 18.015 \frac{\text{g}}{\text{mol}}$) is lighter than diatomic nitrogen ($M_{N_2} = 28.014 \frac{\text{g}}{\text{mol}}$) and oxygen ($M_{O_2} = 31.998 \frac{\text{g}}{\text{mol}}$).

The saturation vapor pressure (August–Roche–Magnus formula):

$$e_s(T) = 6.1078 \times 10^{\frac{7.5(T-273.15)}{T-35.85}} \quad [\text{hPa}]$$

The partial pressure of water vapor:

$$e = \frac{H}{100} e_s(T)$$

Corrected density accounting for humidity (virtual temperature method):

$$\rho = \frac{P - 0.3780 e}{R_{\text{air}} T} \quad (2.2)$$

where P is the total barometric pressure, e is the partial pressure of water vapor, T is the absolute temperature, and R_{air} is the specific gas constant for dry air.

The factor 0.3780 arises from $(1 - M_w/M_{\text{air}}) = 1 - 18.015/28.964 \approx 0.3780$.

Figure 2.3 compares the relative importance of temperature, pressure, and humidity on air density under typical field conditions.




Figure 2.3: Relative change in air density for common deviations from ICAO standard conditions (15 °C, sea level, 1013 hPa, dry air). Negative values indicate reduced density and less aerodynamic drag. Altitude and temperature are the dominant factors; humidity is negligible (< 2 %).

2.4 Speed of Sound

The speed of sound in air depends primarily on temperature:

$$a = \sqrt{\gamma R_{\text{air}} T} = 20.0468 \sqrt{T}$$

where $\gamma = 1.4$ is the ratio of specific heats for air.

At the ICAO standard temperature (15 °C): $a_0 = 20.0468\sqrt{288.15} = 340.29 \frac{\text{m}}{\text{s}}$.

2.5 Density Altitude

Shooters often use density altitude (DA) as a single parameter that encapsulates the combined effects of temperature, pressure, and humidity on air density. DA is the altitude in the standard atmosphere that has the same density ρ as the actual conditions:

$$\text{DA} = \frac{T_0}{L} \left[1 - \left(\frac{\rho}{\rho_0} \right)^{1/(n-1)} \right]$$

where T_0 is the standard sea-level temperature, ρ_0 is the standard sea-level density, L is the temperature lapse rate, and $n = g_0/(L R_{\text{air}}) = 5.2559$.

A practical approximation widely used in the field [Litz, 2011]:

$$\text{DA} \approx 145442.16 \left(1 - \left(\frac{\rho}{\rho_0} \right)^{0.234969} \right) \quad [\text{feet}]$$

Figure 2.4 illustrates the practical impact of atmospheric conditions on trajectory for a typical competition cartridge.




Figure 2.4: Schematic trajectory comparison for a 6.5 mm 140 gr VLD bullet ($B_C = 0.311$ G7, $v_0 = 2700$ fps) under different atmospheric conditions. The spread between extreme conditions exceeds 1 m at 1000 m (> 3 MOA), demonstrating the necessity of atmospheric corrections for long-range shooting. Curves are polynomial approximations scaled by density ratio.

2.6 Julia Implementation: Atmospheric Model

```

1 # See CompetitionBallistics.jl, module Atmosphere
2 # Key functions:
3 #   std_temperature(h)           -> T [K]
4 #   std_pressure(h)             -> P [Pa]
5 #   air_density(; P, T, H)      -> rho [kg/m^3]
6 #   speed_of_sound(T)           -> a [m/s]
7 #   density_altitude(rho)       -> DA [m]
8 #   saturation_vapor_pressure(T) -> e_s [Pa]

```

Listing 2.1: Atmospheric model in Julia

Chapter 3

Interior Ballistics

3.1 Motivation: The Engine of the Bullet

Before a bullet can fight the wind or drop over a thousand yards, it must be launched. Interior ballistics is the study of what happens inside the rifle's chamber and barrel from the moment the firing pin strikes the primer until the bullet exits the muzzle. It governs the brutal and violent conversion of chemical energy stored in the gunpowder (propellant) into the kinetic energy of the projectile.

For the competition shooter, interior ballistics dictates the two most important initial conditions of any shot:

1. **Muzzle Velocity** (v_0): The speed at which the bullet leaves the barrel.
2. **Consistency (SD and ES)**: The Standard Deviation and Extreme Spread of that velocity across multiple shots. A high extreme spread guarantees vertical stringing (missing high or low) at extended ranges, rendering all exterior ballistic math mathematically pointless.

To understand how a cartridge achieves a specific muzzle velocity, we must treat the rifle chamber as a high-pressure thermodynamic engine.

Online implementation (note). A web implementation of the 0D model below (a Gordon's Reloading Tool-style solver) is available on Tireur.org. It is intended strictly as an *educational* tool: validation against published manufacturer data shows that it currently *under-predicts* both peak pressure and muzzle velocity, so it should be used to study trends—not for absolute load development [[Gordon's Reloading Tool, 2021](#)]. Always verify any charge against official manufacturer data.




Figure 3.1: The thermodynamic system of a rifle cartridge. Expanding gases from burning propellant create immense pressure P that forces the bullet down the bore.

3.2 The Thermodynamic Problem

3.2.1 Noble–Abel Equation of State

When gunpowder burns, it creates gas. At the extreme pressures found in a rifle chamber (often exceeding 60,000 PSI or 400 MPa), these gases are packed so tightly that they deviate

significantly from the "ideal gas" behavior taught in high school physics ($PV = nRT$). The gas molecules themselves take up physical space!

To account for this, we use the Noble–Abel equation [Corner, 1950, Carlucci and Jacobson, 2007], which introduces an "excluded volume" or co-volume:

$$P(V - \eta) = n R_u T_g$$

Let's define these variables:

- P : The chamber pressure of the expanding gas.
- V : The total volume available for the gas to occupy (chamber volume plus barrel volume behind the bullet).
- η (eta): The total co-volume, representing the physical space the gas molecules occupy ($\eta = n \cdot b$).
- n : The number of moles of gas produced.
- R_u : The universal gas constant ($8.3145 \frac{\text{J}}{\text{mol}\cdot\text{K}}$).
- T_g : The absolute temperature of the propellant gas.

By subtracting the co-volume η from the total volume V , the Noble–Abel equation prevents the gas pressure from inaccurately dropping to zero.

3.2.2 Energy Balance

The first law of thermodynamics applied to the propellant–projectile system:

$$Q_{\text{prop}} = E_k + E_{\text{heat}} + E_{\text{friction}} + E_{\text{gas KE}} + E_{\text{residual}}$$

The total chemical energy released by the propellant charge:

$$Q_{\text{prop}} = C \cdot f \cdot z$$

where C is the charge mass, f is the impetus (force constant, energy per unit mass), and z is the fraction of charge burned ($0 \leq z \leq 1$).

3.3 Simplified Closed-Bomb Model

In a closed bomb (no projectile motion), the pressure is:

$$P = \frac{C f z}{V_{\text{ch}} - C(1 - z)/\rho_p - C z \eta_{\text{sp}}}$$

where V_{ch} is the chamber volume, ρ_p is the solid propellant density, and η_{sp} is the specific co-volume.

3.4 Burn Rate Law

The rate of gas generation follows a geometric burn rate law. For a single-perforated cylindrical grain:

$$\frac{dz}{dt} = \frac{S(z)}{V_g(z)} \beta P^n$$

For small arms propellants, the empirical Vieille law [Corner, 1950] is commonly used:

$$r_b = \beta P^n$$

where r_b is the linear regression rate ($\frac{\text{m}}{\text{s}}$), and typical values are $n \approx 0.6\text{--}0.9$.

3.4.1 Geometric Form Function

For common grain geometries, the fraction burned z relates to the linear fraction burned $\xi = e/e_0$ through a form function:

$$z(\xi) = \xi (1 + \theta \xi)$$

where θ is the form factor: $\theta = 0$ for a slab, $\theta > 0$ for progressive, and $\theta < 0$ for degressive grains.

Note on software models. Production tools such as GRT and QuickLOAD extend this classical framework with proprietary, calibrated sub-models—notably a multi-stage form function (three stages in GRT versus two in QuickLOAD) and detailed energy-loss and effective-mass (Lagrange/Sebert) terms—fitted to closed-bomb and ballistic measurements [Corner, 1950, Kneubühl, 2018, Gordon’s Reloading Tool, 2021, Anderson and Fickie, 1987]. These calibrated internals are not fully published; the equations above are the open, literature-based formulation.

3.5 Le Duc Velocity Model

A classical approximation for muzzle velocity useful for handloading estimates [McCoy, 2012]:

$$v(x) = \frac{a x}{b + x}$$

where x is the projectile travel distance from the cartridge case mouth, and a and b are empirically determined constants. As $x \rightarrow \infty$, $v \rightarrow a$, so a represents the theoretical maximum velocity.

3.6 Pressure–Travel Relationship

The pressure as a function of bullet travel x in the barrel:

$$P(x) = \frac{m_e}{A_{\text{bore}}} \frac{dv}{dt} = \frac{m_e v}{A_{\text{bore}}} \frac{dv}{dx}$$

where $m_e = m + C/3$ is the effective mass and $A_{\text{bore}} = \pi d^2/4$ is the bore cross-sectional area.

Using the Le Duc model, the pressure becomes:

$$P(x) = \frac{m_e a^2 b x}{A_{\text{bore}} (b + x)^3}$$

The peak pressure occurs at $x_{\text{max}} = b/2$:

$$P_{\text{max}} = \frac{4 m_e a^2}{27 A_{\text{bore}} b} \tag{3.1}$$

3.7 Muzzle Velocity Estimation for Handloaders

A practical empirical formula due to Powley and refined by Litz [2011]:

$$v_0 \approx v_{\text{ref}} \left(\frac{L_{\text{barrel}}}{L_{\text{ref}}} \right)^{0.25 \text{ to } 0.30} \tag{3.2}$$

A rough rule of thumb: each inch of barrel length change alters muzzle velocity by approximately 20 ft/s to 35 ft/s for typical rifle cartridges [Litz, 2011].

As a practical validation of Eq. (3.2), consider measured data for the .308 Winchester with Lapua 155 gr Scenar ammunition:

Table 3.1: Measured muzzle velocity vs. barrel length, .308 Win / Lapua 155 gr Scenar

Barrel length (in)	v_0 (m/s)	v_0 (fps)
20	820	2690
24	845	2772
26	860	2822

This yields approximately $12 \frac{\text{m}}{\text{s}}$ ($\approx 40 \text{ ft/s}$) per additional inch beyond 20 inches, which is consistent with the power-law exponent of 0.27 used in the companion Julia library. Note that the gain per inch diminishes with longer barrels, as the propellant gas expansion cools and pressure drops.

3.7.1 Temperature Sensitivity of Muzzle Velocity

Propellant burn rate is temperature-dependent. The temperature coefficient:

$$\frac{\Delta v_0}{v_0} = \sigma_T \Delta T \quad (3.3)$$

where σ_T is the temperature sensitivity coefficient, typically 0.5 to 2.0 fps/°F (0.9 to 3.6 fps/°C) depending on propellant. Modern temperature-stable propellants like Hodgdon Extreme series have $\sigma_T \approx 0.5 \text{ fps/°F}$ (0.9 fps/°C) [Litz, 2011].

[default: $\sigma_T = 1.0 \text{ fps/°F} = 1.8 \text{ fps/°C}$]

Chapter 4

Transitional Ballistics

4.1 Motivation: The Chaos of the Muzzle

Transitional (or intermediate) ballistics covers the violent and chaotic fraction of a millisecond between interior ballistics (the barrel) and exterior ballistics (free flight). It represents the exact moment the bullet exits the protective confinement of the muzzle and punches into the atmosphere.

Why does a shooter care about this microsecond? Because this is where the bullet is most vulnerable. A perfectly loaded cartridge and a perfectly aimed rifle can be completely ruined by a bad muzzle crown or inconsistent gas release, which will instantly destabilize the bullet before its flight even begins.

4.2 Muzzle Gas Dynamics

When the bullet finally unplugs the barrel, the high-pressure propellant gases (still trapped behind the bullet at pressures of 10–70 MPa) suddenly vent into the atmosphere. Because these gases are incredibly hot and highly pressurized, they expand outward at velocities *faster* than the bullet itself. The bullet is essentially blasted from behind by its own exhaust.

This creates a complex and turbulent shock-wave structure just inches in front of the muzzle [Carlucci and Jacobson, 2007]:




Figure 4.1: Transitional ballistics: The bullet exiting the muzzle gets overtaken by rapidly expanding, supersonic propellant gases. A symmetrical gas release here is paramount to accuracy.

The structure consists of:

1. **Muzzle blast wave:** A spherical shock radiating outward (the "bang" you hear).
2. **Precursor blast:** Produced from the column of air that was compressed ahead of the bullet inside the barrel.

3. **Bottle shock:** The characteristic diamond-pattern Mach disk structure formed by the underexpanded supersonic gas jet accelerating past the bullet.

4.3 Muzzle Tip-Off and Initial Yaw

The concept of "tip-off" is critical. If the muzzle crown is damaged, or if the bullet's base is not perfectly square, the escaping gases will vent asymmetrically.

Let's define the variables for this instability:

- ω (omega): The angular velocity or "tip-off rate" imparted to the bullet ($\frac{\text{rad}}{\text{s}}$).
- α_0 (alpha zero): The initial yaw angle of the bullet as it exits the muzzle (degrees).

Asymmetric gas forces impart a small angular velocity (ω). The resulting initial yaw angle α_0 is typically small (0.5° – 3°) for match-grade ammunition. However, any yaw at the muzzle drastically increases early aerodynamic drag and causes the bullet to precess (wobble) in flight, opening up group sizes.

4.4 Base Drag Transition

Inside the barrel, the base of the bullet is pushed forward by thousands of PSI of pressure. The moment it exits, this high pressure rapidly drops to the ambient atmospheric pressure, creating a sudden vacuum effect behind the bullet. This causes *base drag* to increase significantly, transitioning from a suppressed value to its full free-flight aerodynamic penalty over a distance of approximately 5–20 calibers from the muzzle [McCoy, 2012].

4.5 Crown Effects

Because of this violent gas transition, the muzzle crown (the final machined edge at the barrel's exit) is one of the most critical parts of the rifle. It must be perfectly concentric and perpendicular to the bore axis to ensure gases release symmetrically around the entire circumference of the bullet base at the exact same microsecond.

Chapter 5

Exterior Ballistics: Core Theory

5.1 Motivation: The Math of Free Flight

Once the bullet escapes the muzzle, all active propulsion ceases. The projectile enters "free flight." From this point until it strikes the target, the bullet's path is entirely at the mercy of classical physics. Exterior ballistics is the mathematical prediction of this flight path. For a competitive shooter, this is the core of their craft: translating the laws of physics into correct scope dial adjustments.

To predict where a bullet will land, we must solve equations of motion that account for two primary forces:

1. **Gravity:** Continually accelerating the bullet toward the earth, determining "drop."
2. **Aerodynamic Drag:** The immense friction of the air, rapidly bleeding off the bullet's velocity and magnifying the time gravity has to act.

5.2 Vacuum Trajectory (The Baseline)

Before conquering air resistance, we must understand the baseline system. In a perfect vacuum (ignoring air resistance), the trajectory is a simple parabola. While this model is *useless for real-world rifle ballistics* (because supersonic drag dominates behavior), it serves as a mathematical foundation.

Let's define the fundamental launch parameters:

- t : Time elapsed since the bullet left the muzzle (seconds, s).
- v_0 : Initial muzzle velocity (e.g., $\frac{\text{m}}{\text{s}}$ or ft/s).
- θ (theta): The launch elevation angle, or "look-up" angle of the barrel relative to the horizontal.
- g : Standard gravitational acceleration ($9.80665 \frac{\text{m}}{\text{s}^2}$).
- $x(t)$: The horizontal distance traveled at time t .
- $y(t)$: The vertical height of the bullet at time t .

Using basic Newtonian mechanics, the parametric equations of motion in a vacuum are:

$$x(t) = v_0 \cos \theta \cdot t \tag{5.1}$$

$$y(t) = v_0 \sin \theta \cdot t - \frac{1}{2} g t^2 \tag{5.2}$$

Eliminating time t from Eq. (5.1) and substituting it into Eq. (5.2) yields the single continuous trajectory equation in terms of horizontal distance x :

$$y(x) = x \tan \theta - \frac{g x^2}{2 v_0^2 \cos^2 \theta}$$

The range in vacuum:

$$R_{\text{vac}} = \frac{v_0^2 \sin 2\theta}{g}$$

5.3 Aerodynamic Drag

5.3.1 The Drag Equation

The aerodynamic drag force opposes the bullet's motion through the air:

$$F_D = \frac{1}{2} \rho v^2 C_D(Ma) A$$

The drag deceleration:

$$a_D = \frac{F_D}{m} = \frac{\rho v^2 C_D A}{2m}$$

5.3.2 Drag Coefficient and Mach Number

The drag coefficient C_D is fundamentally a function of Mach number $Ma = v/a$, Reynolds number Re , and projectile geometry. For small-arms bullets, Re effects are secondary, and C_D is treated as a function of Ma alone [McCoy, 2012].

The C_D – Ma curve has characteristic regimes: subsonic ($Ma < 0.8$) with low, slowly varying C_D ; transonic ($0.8 < Ma < 1.2$) with a sharp rise; and supersonic ($Ma > 1.2$) with gradually decreasing C_D .




Figure 5.1: Schematic drag coefficient vs. Mach number for G1 and G7 reference projectiles.

5.3.3 Analytical Solution for 1D Drag

While modern ballistics requires numerical integration (see Section 5.8), a simplified 1D model where C_D is assumed constant provides useful insights into the scaling of range and velocity with respect to the ballistic coefficient.

Consider purely horizontal motion with drag as the only force:

$$\frac{dv}{dt} = -k v^2, \quad \text{where } k = \frac{\rho C_D A}{2m}$$

Separating variables and integrating:

$$\int_{v_0}^v \frac{dv'}{(v')^2} = -k \int_0^t dt' \implies -\left[\frac{1}{v'}\right]_{v_0}^v = -k t$$

The velocity as a function of time is:

$$\boxed{v(t) = \frac{v_0}{1 + k v_0 t}} \quad (5.3)$$

Integrating once more to find the distance $x(t)$:

$$x(t) = \int_0^t \frac{v_0}{1 + k v_0 t'} dt' = \frac{1}{k} \ln(1 + k v_0 t)$$

Solving for t in terms of x :

$$t = \frac{e^{kx} - 1}{k v_0}$$

Substituting this into Eq. (5.3) yields the velocity as a function of distance:

$$\boxed{v(x) = v_0 e^{-kx}}$$

This exponential decay demonstrates how the "Physics BC" (contained within k) determines the velocity retention of the projectile.

5.4 Ballistic Coefficient

The ballistic coefficient B_C is defined as:

$$\boxed{B_C = \frac{SD}{i} = \frac{m}{i d^2}}$$

where $SD = m/d^2$ is the sectional density and i is the form factor:

$$i(Ma) = \frac{C_D^{\text{bullet}}(Ma)}{C_D^{\text{std}}(Ma)}$$

B_C is only meaningful when referenced to a specific drag model (G1, G7, etc.).

5.4.1 Standard Conditions for BC

By convention, B_C values are quoted at standard atmosphere conditions. To use B_C at non-standard conditions:

$$B_{C\text{actual}} = B_{C\text{std}} \cdot \frac{\rho_0}{\rho_{\text{actual}}}$$

5.5 Standard Drag Models (G1 through G8)

Table 5.1: BRL Standard Drag Models [McCoy, 2012, Ingalls, 1893]

Model	Reference Projectile Shape	Primary Use
G1	Flat-base with 2-caliber ogive nose	Traditional default; hunting bullets
G7	Long, secant-ogive, boat-tail	Best for modern VLD match bullets
G8	Similar to G7 with flat base	Flat-base match bullets
GL	Blunt-nose lead bullet	Cast lead bullets




Figure 5.2: Schematic silhouettes of three reference projectiles (nose to the right). The blunt, flat-based G1 differs markedly from a modern match bullet, whereas the long boat-tailed G7 closely matches it; G8 shares the G7 nose but keeps a flat base.

For competition rifle shooting, G7 is strongly preferred over G1 for modern VLD boat-tail bullets because the G7 reference shape more closely matches these bullets, resulting in a form factor i closer to 1.0 and a more constant B_C across the velocity range [Litz, 2011].




Figure 5.3: Drag coefficient of the G1 and G7 reference shapes versus Mach number (G7 values from Table 5.2; G1 representative BRL data). Both rise sharply through the transonic region, but the slender G7 has a markedly lower, flatter peak—the physical reason its B_C stays nearly constant across the supersonic range.

5.5.1 G7 Drag Function

Table 5.2: Selected G7 drag coefficient values [McCoy, 2012]

Ma	C_D^{G7}	Ma	C_D^{G7}	Ma	C_D^{G7}
0.00	0.1198	1.00	0.3803	2.00	0.1993
0.50	0.1194	1.05	0.3845	2.50	0.1629
0.80	0.1242	1.10	0.3597	3.00	0.1400
0.90	0.1464	1.20	0.3250	3.50	0.1225
0.95	0.2054	1.50	0.2602	4.00	0.1090

The values above are reproduced verbatim from the table embedded in the solver (`G7_RAW` in `CompetitionBallistics.js`); the solver interpolates this same data at run time, so the documentation and the implementation are guaranteed to agree.

5.5.2 Drag Functions vs. Siacci Tables: a Common Confusion

The $C_D(Ma)$ tables (G1, G7, ...) are *aerodynamic* data: C_D is dimensionless and depends only on the projectile geometry and the Mach number, *not* on the atmosphere. They are therefore identical whether one takes them from McCoy [McCoy, 2012] or from a tabulation such as JBM's. The atmosphere only enters our solver through the *actual* air density ρ and speed of sound $a(T)$, both recomputed from the ICAO model (§2.2) at every step via $D = \frac{1}{2}\rho C_D(Ma) A i/m$, with $i = SD/B_C$ the form factor.

What *does* depend on the standard atmosphere are the integrated *Siacci tables* $S(V)$, $A(V)$, $I(V)$, $T(V)$, because their integration involves the standard density and speed of sound. This is the well-known caveat that Siacci tables computed under the ICAO atmosphere differ from those in McCoy's book. **Our solver uses no Siacci table**—it integrates the 3-DOF equations numerically—so this caveat does not apply here.

The single genuine consistency requirement is that the user-supplied B_C be referenced to the same standard atmosphere as the code, namely ICAO ($\rho_0 = 1.225 \frac{\text{kg}}{\text{m}^3}$, 15 °C, dry). Modern G7 values (Berger, Hornady, Litz/Applied Ballistics) are all ICAO-referenced. Older *Army Standard Metro* (ASM) B_C values (29.53 inHg, 78 % RH) carry a ≈ 0.4 – 0.5 % density offset.

Warning on Legacy Calculators (e.g., JBM): Many legacy ballistic calculators, such as JBM Ballistics, enable the Army Standard Metro atmosphere by default. If a modern ICAO-referenced G7 BC is input into an ASM-default calculator without explicitly disabling the Metro setting, the solver will silently apply a density offset. Because ASM air is lighter than ICAO air, this introduces an artificial trajectory error that grows significantly at extended ranges. The `CompetitionBallistics` engine exclusively uses the modern ICAO standard, ensuring native 1:1 compatibility with all contemporary manufacturer BCs without requiring any error-prone conversions.

5.6 Doppler Radar Drag Measurement

The drag coefficient tables (G1, G7, etc.) originate from experimental measurements. The modern gold standard is *Doppler radar tracking*, which has largely superseded earlier spark-range and yaw-card methods [McCoy, 2012, Braun, 1958].

5.6.1 Measurement Principle

A continuous-wave (CW) Doppler radar illuminates the bullet in flight and measures the frequency shift of the reflected signal:

$$f_D = \frac{2v \cos \theta_r}{\lambda}$$

where f_D is the Doppler shift frequency, v is the bullet velocity, θ_r is the angle between the velocity vector and the radar beam, and λ is the radar wavelength. The velocity is sampled at rates of 1–10 kHz, yielding a near-continuous $v(t)$ record over the entire flight.

5.6.2 Extracting $C_D(Ma)$ from Radar Data

From the measured velocity–time history, the drag coefficient is extracted by inverting the equation of motion. For a near-horizontal trajectory:

$$C_D(Ma) = -\frac{2m}{\rho A v^2} \frac{dv}{dt}$$

The derivative dv/dt is computed numerically from the sampled $v(t)$ data. Since numerical differentiation amplifies noise, the raw data is first smoothed using a Savitzky–Golay filter or a cubic smoothing spline before differentiation.

The Mach number at each time step is:

$$Ma(t) = \frac{v(t)}{a(T(h(t)))}$$

where a is the local speed of sound, corrected for the altitude $h(t)$ along the trajectory.

5.6.3 Advantages over Classical Methods

Doppler radar provides the complete $C_D(Ma)$ curve from a *single firing*, whereas spark-range methods require many shots at different velocities. This is the method used by:

- The BRL/ARL at Aberdeen Proving Ground to produce the definitive G1–G8 tables.
- Bryan Litz (Applied Ballistics) to measure custom drag curves for individual bullet models, published as “CDM” (Custom Drag Model) data [Litz, 2015].
- Military proving grounds worldwide for projectile development.

The custom drag model approach bypasses the form-factor approximation entirely: instead of $C_D = i \cdot C_D^{\text{std}}$, the actual measured $C_D(Ma)$ curve for the specific bullet is used directly. This eliminates the error from form-factor variation with Mach number and is the most accurate approach available.

5.6.4 Interpolation of Tabular Drag Data

Whether using the standard G1/G7 tables or a custom Doppler-derived curve, the drag coefficient must be evaluated at arbitrary Mach numbers during trajectory integration. Two interpolation methods are common:

Linear interpolation (used in many legacy solvers): Given tabular data $\{(Ma_i, C_{D,i})\}$, find the bracketing interval $[Ma_k, Ma_{k+1}]$ and compute:

$$C_D(Ma) = C_{D,k} + \frac{C_{D,k+1} - C_{D,k}}{Ma_{k+1} - Ma_k} (Ma - Ma_k)$$

Linear interpolation introduces slope discontinuities at each table point. In the transonic region where C_D changes rapidly, these discontinuities can produce small but systematic trajectory errors.

Cubic spline interpolation (recommended): A natural cubic spline $S(Ma)$ is fitted through all n data points, producing a C^2 -continuous curve (continuous through the second derivative). The spline on each interval $[Ma_k, Ma_{k+1}]$ is:

$$S(Ma) = a_k + b_k (Ma - Ma_k) + c_k (Ma - Ma_k)^2 + d_k (Ma - Ma_k)^3$$

where the coefficients $\{a_k, b_k, c_k, d_k\}$ are determined by enforcing continuity of S , S' , and S'' at interior knots, plus natural boundary conditions ($S'' = 0$ at endpoints). This requires solving a tridiagonal linear system of size n , which is $O(n)$ and needs to be done only once during initialization.

Cubic spline interpolation is particularly important in the transonic region ($0.9 < Ma < 1.2$) where the C_D curve has its steepest gradient. The smooth derivative ensures that the drag force varies smoothly as the bullet decelerates through the sound barrier, eliminating artificial trajectory perturbations.

The spline is better only where the table is dense

This recommendation holds for the *standard* tables and must not be carried over to sparse measured ones. A decimation test — remove every second node, rebuild both interpolants on what remains, and score them on the removed values, whose truth is known — reverses the verdict according to the sampling:

Table	Nodes	Linear	Spline
G7 standard	65	0.099 %	0.049 %
G1 standard	53	0.424 %	0.069 %
McCoy .308 C_{D_0}	15	0.68 %	8.89 %
McCoy 105 mm C_{D_0}	12	2.86 %	6.93 %

The criterion is not “spline versus linear” but *sampling density relative to curvature*. McCoy’s range-reduced tables are sparse and deliberately clustered on the transonic knee — his points sit at $Ma = 0.90, 0.95, 1.00, 1.05, 1.10, 1.20$ — so the steep rise imposes derivatives that the spline propagates as oscillation into the neighbouring intervals, where it becomes up to thirteen times worse than a straight line. The 6-DOF coefficient sets therefore read their tables *linearly*, on purpose.

The companion Julia implementation (Appendix B) provides both linear and cubic spline interpolation via the `DragModels` module. Since 2026-08-14 `drag.coefficient` defaults to the spline, matching the JavaScript port and this section; it previously defaulted to linear, in contradiction with both.

5.7 Equations of Motion: 3-DOF Point-Mass Model

5.7.1 Coordinate System

We use a ground-fixed, flat-Earth coordinate system: x (downrange), y (vertical, upward positive), z (cross-range, positive right).

5.7.2 Vector Equation of Motion

$$\boxed{m \frac{d\mathbf{v}}{dt} = -\frac{1}{2} \rho \|\mathbf{v}_{\text{rel}}\| \mathbf{v}_{\text{rel}} C_D(Ma) A + m \mathbf{g}} \quad (5.4)$$

where $\mathbf{v}_{\text{rel}} = \mathbf{v} - \mathbf{v}_{\text{wind}}$ and $\mathbf{g} = (0, -g, 0)^T$.

5.7.3 Scalar Component Equations

$$\frac{dv_x}{dt} = -\frac{\rho C_D A}{2m} v_{\text{rel}} (v_x - w_x) \quad (5.5)$$

$$\begin{aligned} \frac{dv_y}{dt} &= -\frac{\rho C_D A}{2m} v_{\text{rel}} (v_y - w_y) - g \\ \frac{dv_z}{dt} &= -\frac{\rho C_D A}{2m} v_{\text{rel}} (v_z - w_z) \end{aligned} \quad (5.6)$$

where $v_{\text{rel}} = \sqrt{(v_x - w_x)^2 + (v_y - w_y)^2 + (v_z - w_z)^2}$.

5.7.4 Using the Ballistic Coefficient

Substituting the form factor relationship $C_D = i \cdot C_D^{\text{std}}$ and the ballistic coefficient definition $B_C = m/(i d^2)$:

$$\frac{\rho C_D A}{2m} = \frac{\rho C_D^{\text{std}} \pi}{8 B_C}$$

where i is the projectile's form factor, C_D^{std} is the drag coefficient of the standard projectile (G1 or G7), and d is the caliber.

5.8 Numerical Integration

Since the system of equations (5.5)–(5.6) has no closed-form solution due to the non-linear dependence of C_D on velocity, it must be solved numerically.

5.8.1 Euler Method

The simplest numerical approach is the first-order Euler method, which updates the state vector using the derivative at the beginning of each time step Δt :

$$\begin{aligned} v_x^{n+1} &= v_x^n + \Delta t \left(-\frac{\rho C_D A}{2m} v^n (v_x^n - w_x) \right) \\ v_y^{n+1} &= v_y^n + \Delta t \left(-\frac{\rho C_D A}{2m} v^n (v_y^n - w_y) - g \right) \\ x^{n+1} &= x^n + v_x^n \Delta t \\ y^{n+1} &= y^n + v_y^n \Delta t \end{aligned}$$

where $v^n = \sqrt{(v_x^n - w_x)^2 + (v_y^n - w_y)^2 + (v_z^n - w_z)^2}$. While intuitive and easy to implement, the Euler method requires very small time steps to maintain stability and accuracy.

5.8.2 Runge–Kutta (RK4) & Area Scaling

Modern ballistic solvers use higher-order methods, typically the 4th-order Runge–Kutta (RK4) method, which provides a much better balance of speed and precision by sampling the derivative at multiple points within the time step [Press et al., 2007]:

$$\begin{aligned}
 \mathbf{k}_1 &= h \mathbf{f}(t_n, \mathbf{y}_n) \\
 \mathbf{k}_2 &= h \mathbf{f}(t_n + h/2, \mathbf{y}_n + \mathbf{k}_1/2) \\
 \mathbf{k}_3 &= h \mathbf{f}(t_n + h/2, \mathbf{y}_n + \mathbf{k}_2/2) \\
 \mathbf{k}_4 &= h \mathbf{f}(t_n + h, \mathbf{y}_n + \mathbf{k}_3) \\
 \mathbf{y}_{n+1} &= \mathbf{y}_n + \frac{1}{6}(\mathbf{k}_1 + 2\mathbf{k}_2 + 2\mathbf{k}_3 + \mathbf{k}_4)
 \end{aligned}$$

where h is the time step, $\mathbf{y}_n$ is the full state vector (x, y, z, v_x, v_y, v_z) at time t_n , and $\mathbf{f}$ is the vector of derivatives (velocities and accelerations).

Version 3.1 Mathematical Corrections: It is critical to apply the RK4 integration to the *full state vector* rather than decoupling position and velocity (a common error that degrades long-range accuracy). Furthermore, when scaling the reference drag by the Ballistic Coefficient ($BC = m/id^2$), one must account for the physical area $A = \pi d^2/4$. Thus, the effective deceleration must be multiplied by a geometric correction factor of $4/\pi$ to bridge the shooting definition of sectional density and the physical drag force. These corrections ensure sub-MOA consistency with industry reference tools like JBM Ballistics at ranges exceeding 1,000 yards.

A typical time step of $h = 0.0005$ s to 0.001 s is sufficient.

Chapter 6

Exterior Ballistics: Advanced Effects

6.1 Motivation: Beyond Gravity

While gravity is a merciless absolute, it is highly predictable. A shooter simply needs a precise laser rangefinder to account for drop. The true separator of amateur and expert long-range shooters is the mastery of *advanced exterior ballistics*, primarily wind deflection and gyroscopic drift.

Why is wind reading considered a dark art? Because wind is invisible, highly volatile, and acts on a bullet in a deeply counter-intuitive way. The most crucial concept in long-range shooting is realizing that wind does *not* blow a bullet straight sideways like a piece of paper. Instead, wind deflection is entirely governed by how much *drag* the bullet experiences.

6.2 Wind Deflection

Wind is the single largest variable in long-range competition shooting.

6.2.1 Wind Components (Vectors)

Before calculating deflection, we must break the total wind vector into its forward/backward and left/right components relative to the shooter's line of sight.

Let's clearly define our variables:

- W : The absolute wind velocity ($\frac{m}{s}$ or mph).
- α_w (alpha w): The angle of the wind vector relative to the line of fire (e.g., 90° is a full crosswind).
- w_x : The headwind (negative) or tailwind (positive) velocity vector.
- w_z : The lateral crosswind velocity vector.




Figure 6.1: Decomposition of the total wind vector into range (w_x) and lateral (w_z) components. Only the w_z component causes side-to-side deflection.

Given wind speed W at angle α_w relative to the line of fire:

$$\begin{aligned}w_x &= -W \cos \alpha_w \quad (\text{headwind/tailwind}) \\w_z &= W \sin \alpha_w \quad (\text{crosswind})\end{aligned}$$

6.2.2 Simple Approximation

A crude but sometimes useful first-order approximation for lateral drift (crosswind drift) is:

$$\Delta z_{\text{wind}} \approx \frac{W \sin \alpha_w}{v_{\text{avg}}} \cdot R$$

where v_{avg} is the average bullet velocity over the range distance R . This formula assumes the bullet instantly acquires the transverse velocity of the wind, taking a straight angle path. This is physically unrealistic for high-velocity projectiles, but works for air rifles at short distance.

6.2.3 The Lag Rule (The Didion Approximation)

To understand wind deflection accurately, we use the Didion approximation, often known mathematically as the "Lag Rule" [McCoy, 2012, Litz, 2011].

- Δz_{wind} : Total lateral deflection of the bullet at the target.
- t_{actual} : The actual time of flight of the bullet in the real atmosphere.
- R : the range to the target.
- $v_0 \cos \theta$: The horizontal component of the muzzle velocity.
- $\left(t_{\text{actual}} - \frac{R}{v_0 \cos \theta}\right)$: This bracket is the "Lag Time". It represents the extra time the bullet takes to reach the target *compared to if it had traveled in a perfect vacuum*.

$$\Delta z_{\text{wind}} \approx W \sin \alpha_w \cdot \left(t_{\text{actual}} - \frac{R}{v_0 \cos \theta}\right)$$

This equation is remarkably accurate (typically within 5% of a complex 6-DOF solver) and provides an intuitive physical breakthrough: **wind deflection is entirely caused by aerodynamic drag**. If a bullet had zero drag (a vacuum time of flight), the bracket equals zero, and wind drift is zero! The more slippery a bullet is, the smaller the gap between t_{actual} and vacuum time, resulting in less wind deflection.

6.3 Spin Drift

A spin-stabilized bullet develops a slow lateral drift in the direction of its spin. The empirical formula widely used for spin drift [Litz, 2011]:

$$\Delta z_{\text{spin}} = 1.25 (S_g + 1.2) \cdot t^{1.83}$$

where Δz_{spin} is the horizontal deflection in inches, S_g is the gyroscopic stability factor, and t is the time of flight in seconds. The exponent 1.83 and the factor 1.25 are empirical constants derived from Doppler radar measurements of match-grade projectiles.

6.3.1 Gyroscopic Stability Factor

The Miller stability formula [Miller, 2005]:

$$S_g \approx \frac{30 m}{T_w^2 d^3 l (1 + l^2)} \cdot \left(\frac{v_0}{2800}\right)^{1/3} \cdot \frac{T}{T_0} \cdot \frac{P_0}{P} \quad (6.1)$$

where m is bullet mass in grains, T_w is twist rate in calibers per turn, d is caliber in inches, l is bullet length in calibers, v_0 is muzzle velocity in fps, T is ambient temperature, P ambient

pressure, and $T_0 = 518.67$ R (15 °C, 59 °F), $P_0 = 29.92$ in Hg are the standard reference conditions.

Two points are easy to get wrong. The velocity correction is a *cube root*, not a direct ratio: the discrepancy is under 2% near 2800 fps but reaches 27% at 4000 fps. And the atmospheric correction goes as T/T_0 , not its inverse — the overturning moment scales with air density $\rho \propto P/T$, so $S_g \propto 1/\rho$: hot or thin air *raises* S_g . A bullet marginally stable at sea level gains stability at altitude.

For adequate stability, $S_g > 1.0$; values of 1.3–2.0 are typical for match bullets. Below $S_g \approx 1.5$ the bullet flies with residual pitching and yawing that costs measurable BC — Litz reports a 9% BC loss for a .30 calibre 185 gr bullet at $S_g = 1.2$ [Litz, 2011].

6.4 Coriolis and Eötvös Effects

6.4.1 Coriolis Acceleration

In an Earth-fixed reference frame:

$$\mathbf{a}_{\text{Cor}} = -2\boldsymbol{\omega}_E \times \mathbf{v} \quad (6.2)$$

where $\mathbf{a}_{\text{Cor}}$ is the Coriolis acceleration, $\boldsymbol{\omega}_E$ is the Earth’s angular velocity vector, and $\mathbf{v}$ is the projectile’s velocity vector. The scalar magnitude of the Earth’s rotation is $\omega_E = 7.2921 \times 10^{-5} \frac{\text{rad}}{\text{s}}$.

6.4.2 Horizontal Deflection

$$\Delta z_{\text{Cor}} \approx \omega_E \sin \phi \cdot R \cdot t \quad (6.3)$$

where Δz_{Cor} is the horizontal deflection, ϕ is the shooter’s latitude, R is the range, and t is the time of flight.

Always to the right in the Northern Hemisphere, left in the Southern. At 45 N, 1000 yd, $t \approx 1.5$ s: $\Delta z \approx 2.8$ inches (≈ 0.27 MOA).

6.4.3 Vertical Deflection (Eötvös Effect)

$$\Delta y_{\text{Eot}} \approx \omega_E \cos \phi \sin \psi \cdot R \cdot t \quad (6.4)$$

where Δy_{Eot} is the vertical deflection (Eötvös effect) and ψ is the firing azimuth (heading).

Firing East ($\psi = 90^\circ$) results in a positive vertical deflection (the bullet shoots higher due to the increased centrifugal force), while firing West ($\psi = 270^\circ$) results in a negative deflection. At 45°N, 1000 yd, the effect is approximately ± 3 to 4 inches.

6.4.4 Implementation

The closed-form expressions (6.3) and (6.4) are *approximations*; the solver does not use them directly. Instead it applies the exact acceleration (6.2) at every RK4 step, decomposing $\boldsymbol{\omega}_E$ into the shot frame (x downrange, y up, z right) as a function of *both* latitude ϕ and firing azimuth ψ :

$$\boldsymbol{\omega}_E = \omega_E (\cos \phi \cos \psi, \sin \phi, -\cos \phi \sin \psi).$$

Equations (6.3) and (6.4) are then recovered as the leading-order integrals of $-2\boldsymbol{\omega}_E \times \mathbf{v}$. Numerically, firing East at 45°N raises the 1000 yd impact by ≈ 2.4 inches and West lowers it by the same amount, while the horizontal drift stays ≈ 2.4 inches right regardless of azimuth—consistent with the azimuth-independent form of Eq. (6.3).

6.5 Aerodynamic Jump

For a spin-stabilized bullet with initial yaw α_0 [McCoy, 2012]:

$$\theta_{\text{jump}} = \frac{C_{L\alpha}}{2k_t^2} \frac{\alpha_{\text{trim}}}{p_s - r_s}$$

where θ_{jump} is the jump angle, $C_{L\alpha}$ is the lift force derivative, k_t is the transverse radius of gyration, α_{trim} is the equilibrium yaw angle, p_s is the dimensionless spin rate, and r_s is the dimensionless stability derivative.

In practice, aerodynamic jump is absorbed into zero-offset and has a random component that contributes to group size rather than a systematic bias.

6.6 Magnus Effect

$$F_{\text{Magnus}} = \frac{1}{2} \rho v^2 A C_{N_{p\alpha}} \frac{p d}{2v} \alpha$$

where F_{Magnus} is the Magnus force, $C_{N_{p\alpha}}$ is the Magnus force coefficient, p is the axial spin rate, d is the caliber, and α is the yaw angle.

For typical small yaw angles ($\alpha < 1$ deg), the Magnus contribution is sub-0.1 MOA at 1000 yd and is usually neglected.

Chapter 7

Complete 3-DOF Ballistic Solver

7.1 Motivation: From Paper to Code

We have spent several chapters deriving the physical forces acting on a bullet. However, writing these equations on a chalkboard does not help a shooter hit a steel plate at 1,000 yards. The forces of drag and gravity are dynamic—they change continuously every fraction of a second as the bullet slows down and changes angle.

To actually predict the trajectory, we cannot just plug numbers into a single algebra equation. We must build a *numerical solver* that simulates the flight step-by-step. A 3-Degrees-of-Freedom (3-DOF) solver tracks the bullet's x, y, z position through space treating it as a simple "point mass" while applying empirical corrections for rotation. This is the industry standard for commercial ballistic apps.

The complete 3-DOF ballistic solver is implemented in the companion file `CompetitionBallistics.jl` (see Appendix B). The solver includes: G1/G7 drag model interpolation from BRL tables, full Runge-Kutta 4th order (RK4) integration of the 3-DOF equations of motion, automatic zero-angle finding (sighting-in), Coriolis and Eötvös corrections, post-hoc spin drift calculations, and wind deflection.

To ensure the physical integrity of our implementation, the results of this solver have been cross-validated against industry-standard tools, most notably **JBM Ballistics** (jbmballistics.com). Users are encouraged to compare their specific trajectories with JBM for independent verification of ballistic profiles.

The `ShotParameters` struct accepts all physical inputs (bullet mass, Ballistic Coefficient, muzzle velocity, atmospheric conditions, wind, latitude, twist rate, etc.) and the `solve_trajectory()` function returns a vector of `TrajectoryPoint` records containing time, position, velocity, Mach number, and kinetic energy at each integration step.

```
1 include("CompetitionBallistics.jl")
2 using .CompetitionBallistics.ExteriorBallistics
3
4 params = ShotParameters(
5     mass_grains=140.0, caliber_in=0.264,
6     bc=0.311, drag_model=:G7,
7     muzzle_vel_fps=2700.0, zero_range_yd=100.0,
8     wind_speed_mph=10.0, wind_angle_deg=90.0,
9     target_range_yd=1000.0,
10    twist_in=8.0, bullet_length_in=1.34,
11 )
12 trajectory_table(params, step_yd=100)
```

Listing 7.1: Example: running the 3-DOF solver in Julia

Chapter 8

Six-Degree-of-Freedom (6-DOF) Model

8.1 Motivation: Unlocking the Gyroscope

The 3-DOF point-mass model discussed previously is excellent for most conventional shooting scenarios. However, it completely ignores the fact that a bullet is a rapidly spinning chunk of metal (spinning up to 300,000 RPM). A 3-DOF model uses "empirical patches" (fudge factors like the Didion lag rule or empirical spin drift formulas) to estimate the effects of this spin.

When shooting at extreme long range, or when using modern high-BC bullets that border on being aerodynamically unstable, these patches lose their footing, and a Six-Degree-of-Freedom (6-DOF) model becomes the appropriate tool.

Note: when 6-DOF is actually required. It is worth stating plainly, before developing the equations, that this chapter is not a correction the 3-DOF trajectory is waiting for. McCoy [2012] is explicit: 6-DOF trajectories *are not required for routine work in exterior ballistics*. If the total angle of attack is small everywhere along the flight path, a point-mass trajectory is "often sufficiently accurate for all practical purposes", and where a drift solution is also wanted, the modified point-mass method is accurate for all but the highest quadrant elevation angles. The criterion is the *yaw level*, not the range: six-degrees-of-freedom methods are required whenever a projectile experiences large-yaw flight — an artillery or mortar shell at high quadrant elevation, or a projectile launched sideways into a several-hundred-mile-per-hour crosswind. McCoy's own worked example, a .308", 168 gr Sierra International match bullet fired flat to 1000 yards, never exceeds five degrees of pitch and yaw, and he notes that its flight dynamic analysis "can actually be done by simpler methods". Sport shooting, including at long range, sits entirely on the small-yaw side of that line; the 6-DOF model earns its keep in stability and flight-dynamic analysis.

Note: the binding constraint is data, not algorithm. A 6-DOF solution "gives the most accurate solution possible ... provided that all the aerodynamic forces and moments, and the initial conditions, are known to a high degree of accuracy" [McCoy, 2012]. That proviso is the whole difficulty. The full coefficient set — normal force, overturning moment, pitch and roll damping, Magnus force and moment — is measured in a spark range or a wind tunnel and is published for almost no commercial bullet; the semi-empirical codes shooters know by name supply only fragments of it (MCDRAG returns the zero-yaw drag coefficient alone). Practitioners of the method have a motto for what follows: *GI-GO*, garbage in, garbage out. No computed trajectory or flight dynamic analysis can be any better than the quality of its input data, and a 6-DOF run fed with placeholder coefficients is worth less than a 3-DOF run fed with a measured ballistic coefficient.

A 6-DOF model treats the bullet as a spinning rigid body. It tracks three translational coordinates (forward, up, sideways) and three rotational coordinates (yaw, pitch, roll). By doing this, a 6-DOF solver predicts yaw, precession, nutation, spin decay, and all complex

gyroscopic phenomena from absolute first principles. This chapter develops the full 6-DOF equations of motion.

8.2 State Vector and Reference Frames

To track rotation, we can no longer just look at the bullet against the earth; we must look at the earth from the perspective of the bullet.

8.2.1 Coordinate Systems (Inertial vs Body)

We require two rigidly defined reference frames:

- **Earth-fixed (inertial) frame** $\{O; e_x, e_y, e_z\}$: The stationary world the shooter sits in.
 - x : Downrange towards target.
 - y : Vertically upward.
 - z : Horizontal to the right.
- **Body-fixed frame** $\{G; b_1, b_2, b_3\}$: An internal frame locked inside the bullet, with its origin at the bullet's center of mass G .
 - b_1 : Pointing directly out the nose along the symmetry axis.
 - b_2, b_3 : Pointing out the sides (transverse plane).




Figure 8.1: The Earth-fixed inertial frame versus the bullet's Body-fixed frame. As the bullet pitches and yaws, the body frame rotates independently of the earth frame.

8.2.2 Euler Angles and Orientation

The instantaneous orientation of the bullet's body frame relative to the stationary inertial frame is described by three Euler angles in the aerospace (yaw-pitch-roll) convention:

- ψ : yaw angle (rotation about e_y)
- ϑ : pitch angle (rotation about intermediate axis)
- φ : roll (spin) angle (rotation about b_1)

The rotation matrix from inertial to body frame is:

$$\mathbf{R} = \mathbf{R}_1(\varphi) \mathbf{R}_2(\vartheta) \mathbf{R}_3(\psi)$$

8.2.3 The 12-Component State Vector

The full state vector is:

$$\mathbf{Y} = (x, y, z, u, v, w, \varphi, \vartheta, \psi, p, q, r)^T$$

where (x, y, z) is position, (u, v, w) is velocity in the inertial frame, $(\varphi, \vartheta, \psi)$ are Euler angles, and (p, q, r) are angular velocity components in the body frame: p is the spin rate about $\mathbf{b}_1$, and q, r are pitch and yaw rates.

8.3 Translational Equations of Motion

Newton's second law in the inertial frame:

$$m \frac{d\mathbf{v}}{dt} = \mathbf{F}_{\text{grav}} + \mathbf{F}_{\text{drag}} + \mathbf{F}_{\text{lift}} + \mathbf{F}_{\text{Magnus}} + \mathbf{F}_{\text{pitch damp}}$$

8.3.1 Total Angle of Attack

The total angle of attack α_t is the angle between the velocity vector $\mathbf{v}$ and the body symmetry axis $\mathbf{b}_1$:

$$\alpha_t = \arccos \left(\frac{\mathbf{v} \cdot \mathbf{b}_1}{\|\mathbf{v}\|} \right)$$

For small angles, this decomposes into:

$$\begin{aligned} \alpha &\approx \vartheta - \gamma \quad (\text{pitch-plane angle of attack}) \\ \beta &\approx \psi_b - \psi_v \quad (\text{yaw-plane angle of attack}) \end{aligned}$$

where γ is the flight path angle.

8.3.2 Aerodynamic Force Components

All forces are expressed in terms of dimensionless coefficients, reference area $A = \pi d^2/4$, and dynamic pressure $\bar{q} = \frac{1}{2} \rho v^2$:

Axial drag force (opposing velocity along the symmetry axis):

$$F_{\text{drag}} = -\bar{q} A C_{D_0}(Ma) - \bar{q} A C_{D_{\alpha^2}}(Ma) \alpha_t^2$$

where C_{D_0} is the zero-yaw drag coefficient and $C_{D_{\alpha^2}}$ is the yaw-drag coefficient.

Normal (lift) force (perpendicular to the symmetry axis, in the yaw plane):

$$F_N = \bar{q} A C_{N_\alpha}(Ma) \alpha_t$$

where C_{N_α} is the normal force derivative (lift-curve slope).

Magnus force (perpendicular to both the spin axis and the velocity-axis plane):

$$F_{\text{Magnus}} = \bar{q} A C_{N_{p\alpha}}(Ma) \frac{p}{2v} \alpha_t$$

8.4 Rotational Equations of Motion

The general rotational equation for a rigid body in compact tensor form is:

$$\dot{\boldsymbol{\omega}} = \mathbf{I}^{-1}(\mathbf{M} - \boldsymbol{\omega} \times \mathbf{I} \boldsymbol{\omega}) \quad (8.1)$$

where $\mathbf{I}$ is the inertia tensor, $\boldsymbol{\omega} = (p, q, r)^T$ is the angular velocity in the body frame, and $\mathbf{M}$ is the total external moment. The cross-product term $\boldsymbol{\omega} \times \mathbf{I} \boldsymbol{\omega}$ represents the gyroscopic coupling.

For an axially symmetric projectile (body of revolution) with I_x (axial) and $I_y = I_z$ (transverse), the inertia tensor is diagonal and Eq. (8.1) expands to the scalar Euler equations:

$$\begin{aligned} I_x \dot{p} &= M_x \\ I_y \dot{q} + (I_x - I_y) p r &= M_q \\ I_y \dot{r} - (I_x - I_y) p q &= M_r \end{aligned}$$

8.4.1 Aerodynamic Moments

Overtuning (pitching) moment — the moment that tends to increase the angle of attack:

$$M_{\text{pitch}} = \bar{q} A d C_{M_\alpha}(Ma) \alpha_t$$

where C_{M_α} is the pitching moment coefficient derivative. For statically stable configurations, $C_{M_\alpha} < 0$ (restoring moment). For bullets, $C_{M_\alpha} > 0$ (statically unstable; stability comes from spin).

Spin-damping moment — the torque that decelerates spin:

$$M_{\text{spin}} = \bar{q} A d^2 C_{l_p}(Ma) \frac{p d}{2v}$$

where $C_{l_p} < 0$ is the spin-damping coefficient.

Pitch-damping moment — opposes pitch/yaw rate:

$$M_{\text{damp}} = \bar{q} A d^2 (C_{M_q} + C_{M_{\dot{\alpha}}}) \frac{d}{2v} (q \text{ or } r)$$

Magnus moment:

$$M_{\text{Magnus}} = \bar{q} A d^2 C_{M_{p\alpha}}(Ma) \frac{p d}{2v} \alpha_t$$

8.4.2 Summary of Moment Components

The total moments about each body axis:

$$\begin{aligned} M_x &= \bar{q} A d^2 C_{l_p} \frac{p d}{2v} \\ M_q &= \bar{q} A d \left[C_{M_\alpha} \alpha - C_{M_{p\alpha}} \frac{p d}{2v} \beta + (C_{M_q} + C_{M_{\dot{\alpha}}}) \frac{q d}{2v} \right] \\ M_r &= \bar{q} A d \left[C_{M_\alpha} \beta + C_{M_{p\alpha}} \frac{p d}{2v} \alpha + (C_{M_q} + C_{M_{\dot{\alpha}}}) \frac{r d}{2v} \right] \end{aligned}$$

8.5 Kinematic Equations

The Euler angle rates relate to the body-frame angular velocities:

$$\begin{aligned}\dot{\varphi} &= p + (q \sin \varphi + r \cos \varphi) \tan \vartheta \\ \dot{\vartheta} &= q \cos \varphi - r \sin \varphi \\ \dot{\psi} &= (q \sin \varphi + r \cos \varphi) \sec \vartheta\end{aligned}$$

For small angles of attack ($\alpha_t < 10^\circ$), typical of rifle bullets, these simplify considerably.

8.6 Quaternion Formulation (Singularity-Free)

The Euler-angle formulation has a singularity at $\vartheta = \pm 90^\circ$ (gimbal lock). For robust numerical integration, the unit quaternion $\mathbf{q} = (q_0, q_1, q_2, q_3)^T$ is preferred:

$$\frac{d}{dt} \begin{pmatrix} q_0 \\ q_1 \\ q_2 \\ q_3 \end{pmatrix} = \frac{1}{2} \begin{pmatrix} 0 & -p & -q & -r \\ p & 0 & r & -q \\ q & -r & 0 & p \\ r & q & -p & 0 \end{pmatrix} \begin{pmatrix} q_0 \\ q_1 \\ q_2 \\ q_3 \end{pmatrix}$$

The rotation matrix from the quaternion:

$$\mathbf{R} = \begin{pmatrix} 1 - 2(q_2^2 + q_3^2) & 2(q_1q_2 - q_0q_3) & 2(q_1q_3 + q_0q_2) \\ 2(q_1q_2 + q_0q_3) & 1 - 2(q_1^2 + q_3^2) & 2(q_2q_3 - q_0q_1) \\ 2(q_1q_3 - q_0q_2) & 2(q_2q_3 + q_0q_1) & 1 - 2(q_1^2 + q_2^2) \end{pmatrix}$$

After each integration step, renormalize: $\mathbf{q} \leftarrow \mathbf{q}/\|\mathbf{q}\|$.

8.7 Aerodynamic Coefficient Database

8.7.1 Typical Values for Match Bullets

The aerodynamic coefficients are functions of Mach number. Typical values for a 6.5 mm, 140 gr VLD match bullet at $Ma \approx 2.4$ (muzzle) [McCoy, 2012, Carlucci and Jacobson, 2007]:

Table 8.1: Typical aerodynamic coefficients for a 6.5 mm 140 gr VLD match bullet

Coefficient	Symbol	Typical Value	Description
Zero-yaw drag	C_{D_0}	0.15–0.30	From G7 table via BC
Yaw drag	$C_{D_{\alpha^2}}$	2.0–5.0	Drag increase with yaw
Lift-curve slope	C_{N_α}	2.0–3.5	Normal force per rad
Overturning moment	C_{M_α}	2.0–4.0	Destabilizing (positive)
Spin damping	C_{l_p}	−0.005 to −0.02	Retards spin
Pitch damping	$C_{M_q} + C_{M_{\dot{\alpha}}}$	−5 to −15	Damps yaw oscillation
Magnus force	$C_{N_{p\alpha}}$	−0.5 to +0.5	Cross-spin force
Magnus moment	$C_{M_{p\alpha}}$	−0.5 to +0.5	Cross-spin moment

[default: Values in the Julia implementation when not user-specified.]

8.7.2 Measured Sets: What Actually Exists

The table above is a range of plausible magnitudes, not a coefficient set. A 6-DOF run needs actual numbers, and the constraint is severe: the full set is measured in a spark photography range and published for almost no commercial bullet. The implementation therefore marks every set with a **provenance** field and warns once per session when a solver runs on placeholder values — a right solver fed invented coefficients returns results that are *credible and wrong*, which is a worse failure than a wrong solver returning visible nonsense.

Seven projectiles are presently carried with a measured set, all from BRL spark-range reports by R. L. McCoy and all in the public domain:

Table 8.2: Measured aerodynamic sets carried by the implementation

Projectile	Source	Mach range	Note
.308 in 168 gr Sierra Intl.	McCoy [2012], App. A	0.0–2.5	Textbook case 9.1
105 mm HE M1	McCoy [2012], App. B	0.0–2.5	Artillery, case 9.2
5.56 mm SS-109	BRL-MR-3476 (1985)	0.74–2.63	Ball
5.56 mm M855	BRL-MR-3476 (1985)	0.67–2.73	Ball
5.56 mm L110	BRL-MR-3476 (1985)	1.89–2.54	Tracer, thin
5.56 mm M856	BRL-MR-3476 (1985)	1.12–2.57	Tracer

The 5.56 mm sets are the first *small-arms* Magnus and pitch-damping data the library carries, and they cover the whole useful flight band of the cartridge. Their tables are transcribed round by round, exactly as printed, and every curve the library uses is derived from those rows at load time — there is no second, hand-copied copy that can drift out of step.

Three limits are recorded with them, and each is a trap for the unwary.

The tabulated C_D is measured at the round's own yaw, not at zero yaw. It is reduced with $C_{D_0} = C_D - C_{D_{\alpha_2}} \sin^2 \alpha_t$, taking $C_{D_{\alpha_2}} = 3.5$; that coefficient is not measured by the report, but pairs of rounds fired at the same Mach and different yaw bracket it between 3.4 and 5. Keeping only the near-zero-yaw rounds instead leaves *two* points for the M855, both supersonic, and the curve then clamps a supersonic value straight across the transonic peak.

These sets cannot produce a limit cycle. Each $C_{M_{p\alpha}}$ value is a single round at a single angle of attack, so the curve is a function of Mach only and the yaw dependence is unresolved — and it is precisely the sign change of the Magnus moment with yaw that fixes limit-cycle amplitude. The scatter hints at the behaviour (the M855 runs from +0.10 at 1.90° to -0.59 at 2.87°) but three points cannot separate a Mach effect from a yaw effect, and pretending otherwise would be invention.

Sparse tables extrapolate silently. A table lookup clamps at its ends, which for nine rounds means answering confidently at a Mach nobody fired: the L110 tracer has three Magnus points, all above $Ma 1.89$. The implementation returns the clamped value *and warns once* outside the band actually fired, with 2% of slack so that an edge case does not train the reader to ignore the warning.

Physical characteristics — mass, centre of gravity and both moments of inertia — are additionally carried for the four 5.56 mm projectiles, the M118 Match, the 190 gr Sierra MatchKing and the 168 gr Sierra International (BRL-MR-3733, 1988), and for four .22 LR match bullets (BRL-MR-3877, 1990). The last of these covers a regime none of the others do: entirely subsonic flight, $Ma 0.77$ to 1.03 .

Validation. Feeding the measured coefficients of BRL-MR-3476 into the linearised theory of Section 8.10 reproduces the gyroscopic stability factors that the same report publishes from the same firings, to 3.5% for the SS-109 and 5.3% for the M855 (median 1.3% and 0.5%). The test barrel’s twist is not published; the published S_g implies 7.01" and 7.18", which is the 1:7" of the M16A2 and M249 that the report discusses in its dispersion section — an independent check that the set and the theory are mutually consistent.

8.7.3 Deriving C_{D_0} from the Ballistic Coefficient

The zero-yaw drag coefficient relates directly to the standard drag model and the ballistic coefficient:

$$C_{D_0}(Ma) = i \cdot C_D^{\text{std}}(Ma) = \frac{SD}{B_C} C_D^{\text{std}}(Ma)$$

This allows the 6-DOF model to use the same BC input as the 3-DOF model for the dominant drag term.

8.8 Moments of Inertia

For a rotationally symmetric bullet of mass m , length L , and diameter d :

$$I_x \approx \frac{1}{2} m r_g^2 \quad (\text{axial, about symmetry axis}) \quad (8.2)$$

$$I_y = I_z \approx m \left(\frac{L^2}{12} + \frac{r_g^2}{4} \right) \quad (\text{transverse}) \quad (8.3)$$

where $r_g = d/2$ is the radius of gyration. For a typical match bullet, $I_y/I_x \approx 5$ –10.

8.8.1 Why the Solid-Cylinder Form Is Not Good Enough

Equations (8.2) and (8.3) treat the bullet as a solid cylinder of uniform density. Against the measured inertias of the .308in 168gr Sierra International (McCoy’s Table 9.2) that approximation returns I_x high by 15.2%, I_y high by 71.2% and the ratio I_y/I_x high by 48.7%. Since $S_g \propto I_x^2/I_y$, the error propagates to a gyroscopic stability factor of 1.32 where the published value is 1.70 — a shortfall of 22%, which is the difference between declaring a load stable and declaring it marginal.

The cylinder is wrong for two independent reasons. It ignores the *shape* — a real bullet is an ogive over a cylinder over a boat tail, not a cylinder — and it ignores the *internal layout*, a gilding-metal jacket of nearly constant radial thickness around a lead core that does not fill it.

8.8.2 Integration over the Actual Contour

The companion implementation (`bullet_inertia`) integrates the solid of revolution directly. The external contour is described in calibers by four numbers: the ogive length as a fraction of total length, the meplat diameter, the boat-tail length and the boat-tail half-angle. The ogive is taken *tangent*, so its radius follows from the tangency condition

$$R = \frac{L_n^2 + a^2}{2a}, \quad a = \frac{d - d_{\text{meplat}}}{2}$$

with L_n the ogive length. For the jacketed-lead construction the body is a shell of constant radial thickness with an open base, a lead core rising from that base, and a cavity above it;

the core height is solved by bisection so that the integrated mass matches the bullet's actual weight. If no core height reproduces the weight — the bullet being denser than a solid-lead fill or lighter than the bare jacket — the routine falls back to a uniform density and says so.

Scored against the same reference bullet, given its published contour, this returns I_x to -0.2% , I_y to $+2.4\%$, the ratio to $+2.6\%$ and the centre of gravity to -0.5% ; S_g comes out at 1.693 against the published 1.70. On a 20 mm steel cone-cylinder of exactly known geometry (McCoy's Example 12.1) the integrator itself is good to -0.5% on I_x and -4.0% on I_y , which bounds the numerical error and shows that what remained wrong in the cylinder approximation was the *shape*, not the arithmetic.

8.8.3 Default Contour, and What It Costs

When no contour is supplied the defaults describe a modern boat-tailed match bullet: ogive fraction 0.541, boat tail 0.782 calibers at 7.5° , meplat 0.22 calibers. The first three are medians of measured populations — the ogive fraction and boat-tail length over 94 boat-tailed match bullets from a published manufacturer's dimension table, the boat-tail half-angle over 83 cones recorded by handloaders as two diameters and a height, from which the angle follows as $\arctan((d_{\text{maj}} - d_{\text{min}})/2h)$.

Flat-base bullets are a separate family, not a boat tail with zero length: they are shorter (L/d median 3.34 against 4.87) and carry proportionally longer ogives (0.638 against 0.541). Applying the boat-tail defaults to a flat base biases S_g by -9.7% , always in the same direction.

Two cautions follow from the calibration and are worth stating plainly.

First, a default calibrated on one reference case is calibrated on its idiosyncrasy. An earlier default boat-tail length of 0.50 calibers matched the Sierra International almost exactly — and that bullet sits at the 2nd percentile of the modern match population, whose median is 0.782. It therefore scored well on the single case with published inertias while being wrong for the bullets the library is actually used on. The present defaults deliberately score *worse* on that case (-4.9% on S_g instead of -0.5%) and better on the population.

Second, the residual spread is irreducible by a better constant. Against each bullet's own measured contour the defaults leave a median absolute error of 3.8% on S_g for boat tails and 4.1% for flat bases, with a third of the population outside $\pm 5\%$. A linear rule in L/d was fitted and rejected: it bought 0.4 points of median error while widening the tails. What the spread wants is the dimension of the individual bullet, not a cleverer average.

Of the four contour parameters only the meplat remains uncalibrated, no public source publishing it. Sweeping it over its plausible range now moves I_x by 1.9% , I_y by 3.2% and S_g by 0.9% — against 6.3 / 4.2 / 9.7% when the boat-tail angle was a guess as well.

8.8.4 Constructions the Model Does Not Cover

Two measured cases fall outside the jacketed-lead assumption and are useful as declared limits rather than as failures.

The 5.56 mm SS-109 and M855 carry a *steel penetrator* ahead of a lead rear core, so their mass is laid out in two materials. Given the published contour and true weight, the estimator lands 4–5% low on I_x , 6–9% low on I_y and 5–7% low on the centre of gravity. That is the composite core showing.

The .22 LR match bullets are unjacketed lead, *heeled* — a rear section of reduced diameter — with a round nose ending in a spherical cap rather than a meplat. Neither the heel nor the

round nose is expressible in the four contour parameters, so no contour is offered for them; only their measured inertias are tabulated.

In both cases the defaults happen to score better than the true contour. That is compensation between two errors, not accuracy, and it must not be read as a reason to prefer the defaults.

8.9 Spin Rate and Initial Conditions

The initial spin rate from the barrel twist rate τ (inches/turn):

$$p_0 = \frac{2\pi v_0}{\tau}$$

For a 1:8 twist barrel at 2700fps: $p_0 = 2\pi \times 2700/(8/12) = 2\pi \times 4050 \approx 25,447$ rad/s ($\approx 243,000$ RPM).

8.10 Stability Revisited from 6-DOF Theory

8.10.1 Gyroscopic Stability

From the linearized 6-DOF equations, the gyroscopic stability factor is rigorously:

$$S_g = \frac{I_x^2 p^2}{2 \rho A d I_y v^2 C_{M_\alpha}}$$

This is the exact form from which the Miller approximation (6.1) is derived.

8.10.2 Dynamic Stability

The dynamic stability factor from the 6-DOF linearization:

$$S_d = \frac{2 C_{N_\alpha}}{C_{M_\alpha}} \cdot \frac{1}{S_g(S_g - 1)} \cdot \left(\frac{C_{N_\alpha} + \frac{2m}{\rho A d} k_t^2}{C_{M_q} + C_{M_{\dot{\alpha}}}} \right)^2$$

Full stability requires $S_g > 1$ and $0 < S_d < 2$.

8.11 Comparison: 3-DOF vs. 6-DOF

Table 8.3: Comparison of 3-DOF and 6-DOF models

Feature	3-DOF	6-DOF
State variables	6 (position + velocity)	13 (+ quaternion + angular velocity)
Spin drift	Empirical (Litz formula)	Predicted from first principles
Yaw/precession	Not modeled	Fully resolved
Magnus force	Neglected or lumped	Computed from $C_{N_{p\alpha}}$
Transonic behavior	No yaw prediction	Predicts instability onset
Aerodynamic data	BC only	BC + 7 additional coefficients
Computation speed	~ 0.01 s	~ 0.1 – 0.5 s
Accuracy at 1000 yd	< 0.5 MOA (with corrections)	< 0.1 MOA

For most competition shooting, the 3-DOF model with empirical spin drift and Coriolis corrections is sufficient. The 6-DOF model is valuable for: bullet design evaluation, predicting transonic stability limits, understanding anomalous dispersion, and academic study.

8.12 Julia Implementation: 6-DOF Solver

The 6-DOF solver is implemented in the `SixDOF` module within `CompetitionBallistics.jl` (Appendix B). Key structures:

```
1 using .CompetitionBallistics.SixDOF
2
3 aero = AeroCoefficients6DOF(
4     Cd0_func = (Ma) -> cd_g7(Ma) * 1.02, # from BC
5     Cda2     = 3.5,           # yaw drag
6     CNa      = 2.8,           # lift-curve slope
7     CMa      = 3.2,           # overturning moment
8     Clp      = -0.010,        # spin damping
9     CMq_CMad = -8.0,          # pitch damping sum
10    CNpa      = 0.1,           # Magnus force
11    CMpa      = -0.2,          # Magnus moment
12 )
13
14 params6 = ShotParameters6DOF(
15     mass_grains=140.0, caliber_in=0.264,
16     bullet_length_in=1.34,
17     muzzle_vel_fps=2700.0, twist_in=8.0,
18     initial_yaw_deg=0.5, # typical muzzle yaw
19     aero=aero,
20 )
21
22 traj = solve_6dof(params6)
```

Listing 8.1: 6-DOF solver usage example

Chapter 9

Angular Measurement and Sighting Systems

9.1 Motivation: Speaking the Language of the Scope

All the ballistic math in the world is useless if you cannot translate it into a physical adjustment on the rifle scope. A ballistic solver calculates the drop of a bullet in linear units (like inches or centimeters). However, rifle scopes do not adjust in linear units; they adjust by changing angles.

When you turn the elevation dial on a scope, you are physically tilting the optic downward relative to the barrel so that you are forced to aim the barrel upward to compensate for drop. To hit the target, we must convert linear distance at the target (Δy) into an angular measurement at the scope. The two dominant angular languages in shooting are Minute of Angle (MOA) and Milliradian (Mil).

9.2 Minute of Angle (MOA)

A circle has 360 degrees. A Minute of Angle is exactly $1/60^{\text{th}}$ of one degree.

First, let's verify what this small angle actually means in radians:

$$1 \text{ MOA} = \frac{1^\circ}{60} \times \frac{\pi}{180^\circ} = 2.9089 \times 10^{-4} \text{ rad}$$

Because tangent of a very small angle is approximately equal to the angle in radians ($\tan(\theta) \approx \theta$), we can calculate exactly how much physical distance 1 MOA covers at 100 yards ($R = 3600$ inches):

$$\Delta y = R \cdot \theta_{\text{rad}} = 3600 \cdot 2.9089 \times 10^{-4} \approx 1.047 \text{ inches}$$

This is where the common (but slightly inaccurate) shooter's approximation comes from: $1 \text{ MOA} \approx 1 \text{ inch at } 100 \text{ yd}$.

To convert your calculated bullet drop (Δy) at range R (ensuring both are in the same linear units, e.g., inches) into a scope dial adjustment in MOA, use this exact formula:

$$\text{MOA Dial Adjustment} = \frac{\Delta y}{R} \cdot \frac{180 \times 60}{\pi} \approx \frac{\Delta y}{R} \cdot 3437.75$$

9.3 Milliradian (Mil, MRAD)

While MOA is mathematically tied to the 360-degree circle (popular in the US), the Milliradian system operates on pure base-10 metric logic (popular internationally and in military

applications). A radian is the angle subtended when the arc length equals the radius. A milliradian is $1/1000^{\text{th}}$ of a radian.

$$1 \text{ mil} = 0.001 \text{ rad}$$

Because $1 \text{ mil} = 0.001 \text{ rad}$, the math is incredibly elegant: 1 mil is exactly 1 meter at 1,000 meters, 10 centimeters at 100 meters, or 3.6 inches at 100 yards.

For mixed scope usage, the hard conversion is: $1 \text{ mil} = 3.438 \text{ MOA}$.

To calculate the necessary dial adjustment on a Mil-based scope, using drop Δy and range R (again, matching linear units):

$\text{Mil Dial Adjustment} = \frac{\Delta y}{R} \times 1000$

Chapter 10

Reloading Guide for Competition Shooters

10.1 Motivation: Controlling the Variables

No amount of ballistic solver software can make up for inconsistent ammunition. Factory ammunition, even "match grade," is mass-produced and subject to tolerance stacking. To guarantee extreme precision (Standard Deviations in velocity below 10 FPS), competition shooters handload their own ammunition. Reloading is fundamentally about controlling variables—neck tension, seating depth, powder charge, and concentricity—so that every single round possesses the exact same interior ballistics.

Safety Warning: Handloading deals with immense explosive pressures near your face. Always cross-reference with current published load data from powder manufacturers. Start 10% below listed maximum charges and work up carefully while watching for pressure signs on the brass primer.

10.2 Cartridge Selection for Competition

Table 10.1: Popular competition cartridges and their characteristics

Cartridge	Bullet (gr)	v_0 (fps)	BC (G7)	Barrel	Discipline
6mm BR	105–108	2850–2950	.225–.275	26–28	Benchrest, F-Class
6mm Creedmoor	105–115	2950–3100	.255–.290	26–28	PRS, NRL, F-Class
6mm Dasher	105–115	2950–3050	.225–.290	26–28	PRS, NRL
6.5 Creedmoor	130–147	2550–2800	.255–.340	24–26	PRS, NRL, F-Class
6.5×47 Lapua	130–147	2650–2850	.255–.340	26–28	Palma variant
.284 Win	180	2850–2950	.340–.365	28–30	F-Class Open
.308 Win	155–185	2550–2800	.220–.275	24–30	Palma, Tactical
.223 Rem	69–80	2700–3000	.145–.200	20–26	Service Rifle
.300 Win Mag	190–230	2800–3000	.310–.415	26–30	F-Class Open
.338 Lapua Mag	250–300	2700–2900	.370–.450	27–30	ELR

10.3 Propellant Selection

Selecting the proper propellant is a balance between achieving the desired muzzle velocity (v_0), maintaining a low velocity spread (σ_v), and ensuring safety across a wide range of temperatures. Propellants are broadly categorized into single-base (nitrocellulose-only) and double-base (nitrocellulose and nitroglycerine). Single-base propellants generally offer cleaner burning and superior temperature stability, whereas double-base propellants provide higher energy density (resulting in higher velocities) at the expense of higher thermal sensitivity

and increased barrel throat erosion. Table 10.2 summarizes popular propellants used in competition shooting, highlighting their burn rate and relative temperature stability.

Table 10.2: Popular propellants for competition rifle cartridges

Propellant	Burn Rate	Temp Stable?	Typical Cartridges
Hodgdon Varget	Medium	Yes (Extreme)	.308, .223, 6.5 CM, 6BR
Hodgdon H4350	Med-slow	Yes (Extreme)	6.5 CM, 6 CM, .284, .260
Hodgdon H4895	Medium	Yes (Extreme)	6BR, .308, .223
Alliant RL-16	Med-slow	Yes (ETS)	6.5 CM, 6 CM, 6mm BR
Vihtavuori N140	Medium	Moderate	6mm BR, .308, .223
Vihtavuori N150	Med-slow	Moderate	6.5 CM, 6 CM, .260
Vihtavuori N555	Medium	Yes	6mm BR, 6 Dasher
Vihtavuori N565	Med-slow	Yes	6.5 CM, 6 CM, 6.5×47
IMR 4451	Med-slow	Yes (Enduron)	6.5 CM, 6 CM, .308
Reload Swiss RS52	Medium	Moderate	.308 Win, 6mm BR, 6.5 CM
Reload Swiss RS60	Med-slow	No (Impregnated)	6.5 CM, .260, 6.5×55
Vectan Tubal 5000	Medium	No	.308 Win, .30-30, 8×57

10.4 Representative Load Data

Disclaimer: Reference only. Always consult current manufacturer manuals. Start 10% below maximum.

Table 10.3: 6.5 Creedmoor representative loads (24-inch barrel)

Bullet	Propellant	Charge (gr)	COAL (in)	v_0 (fps)	Press.
140 Berger Hybrid	H4350	40.0–42.5	2.800	2650–2760	Near max
147 Hornady ELD-M	H4350	38.5–41.0	2.830	2550–2660	Near max
130 Berger Hybrid	H4350	41.0–43.5	2.810	2750–2880	Near max
140 Sierra MK	RL-16	39.0–41.5	2.800	2640–2750	Near max
147 Hornady ELD-M	N565	39.5–42.0	2.830	2570–2680	Near max

Table 10.4: .308 Winchester representative loads (24-inch barrel)

Bullet	Propellant	Charge (gr)	COAL (in)	v_0 (fps)	Press.
175 Sierra MK	Varget	42.0–44.5	2.800	2550–2680	Near max
155 Berger Hybrid	Varget	44.5–47.0	2.800	2750–2870	Near max
168 Sierra MK	Varget	43.0–45.5	2.800	2600–2720	Near max
175 Sierra MK	N150	43.0–45.0	2.800	2570–2670	Near max

Table 10.5: 6mm Creedmoor representative loads (26-inch barrel)

Bullet	Propellant	Charge (gr)	COAL (in)	v_0 (fps)	Press.
105 Berger Hybrid	H4350	39.5–42.0	2.800	3000–3100	Near max
108 Berger BT Tgt	H4350	39.0–41.5	2.800	2950–3070	Near max
115 Berger Hybrid	RL-16	38.0–40.5	2.810	2880–2990	Near max
105 Hornady ELD-M	N565	38.5–41.0	2.790	2980–3080	Near max
109 Berger LRHT	H4350	38.5–41.0	2.810	2950–3060	Near max

Table 10.6: 6mm BR Norma representative loads (26-inch barrel)

Bullet	Propellant	Charge (gr)	COAL (in)	v_0 (fps)	Press.
105 Berger Hybrid	Varget	29.0–30.5	2.350	2850–2950	Near max
105 Berger Hybrid	N140	29.5–31.0	2.350	2870–2960	Near max
108 Berger BT Tgt	Varget	28.5–30.0	2.350	2820–2920	Near max
108 Berger BT Tgt	N555	29.0–30.5	2.350	2850–2950	Near max
105 Lapua Scenar	H4895	28.5–30.0	2.340	2830–2930	Near max
107 Sierra MK	Varget	28.5–30.0	2.350	2830–2930	Near max

10.5 Complete Worked Example: 6mm BR at 1000 Yards

This section walks through a complete ballistic simulation for a 6mm BR Norma benchrest/F-Class load, from component data through atmospheric correction to a full trajectory table with all secondary effects. This serves as a template for any cartridge.

10.5.1 Step 1: Component Data

Our load:

- **Bullet:** Berger 105 gr Hybrid Target, 6mm (.243 cal)
- **BC (G7):** 0.275 [Litz, 2015]
- **Bullet length:** 1.292 in. (manufacturer specification)
- **Propellant:** Vihtavuori N140, 30.2 gr
- **Muzzle velocity:** 2920 fps (from 26-inch barrel, verified by chronograph)
- **Barrel twist:** 1:7.5 right-hand
- **Brass:** Lapua 6mm BR, weight-sorted ± 0.5 gr
- **Primer:** CCI BR-4 small rifle benchrest

10.5.2 Step 2: Stability Check

Using the Miller formula (6.1):

$$\begin{aligned}
 d &= 0.243 \text{ in.}, \quad l = 1.292/0.243 = 5.317 \text{ cal}, \quad T_w = 7.5/0.243 = 30.86 \text{ cal/turn} \\
 S_g &= \frac{30 \times 105}{30.86^2 \times 0.243^3 \times 5.317 \times (1 + 5.317^2)} \times \left(\frac{2920}{2800} \right)^{1/3} \times \frac{518.67}{518.67} \\
 &= \frac{3150}{30.86^2 \times 0.01435 \times 5.317 \times 29.27} \times 1.014 \\
 &\approx 1.50
 \end{aligned}$$

$S_g = 1.50 > 1.3$: well stabilized, and right at the threshold above which the bullet realises its full BC. The bullet will maintain gyroscopic stability down to approximately Mach 1.2 (about 1350 fps), which occurs near 1100 yards for this load.

10.5.3 Step 3: Atmospheric Conditions

Match day conditions (summer F-Class match in Ottawa, Canada):

$$\begin{aligned}
 T &= 27.8^\circ\text{C} = 82^\circ\text{F} = 300.9 \text{ K} \\
 P &= 29.75 \text{ in Hg} = 100\,750 \text{ Pa} \\
 H &= 55\%, \quad \text{Altitude} = 250 \text{ ft}
 \end{aligned}$$

Air density from Eq. (2.2):

$$\begin{aligned}e_s &= 610.78 \times 10^{7.5 \times 27.7 / (27.7 + 237.3)} = 3695 \text{ Pa} \\e &= 0.55 \times 3695 = 2032 \text{ Pa} \\ \rho &= \frac{100750 - 0.3783 \times 2032}{287.058 \times 300.9} = \frac{99981}{86380} = 1.1575 \text{ kg/m}^3\end{aligned}$$

Density ratio: $\rho/\rho_0 = 1.1575/1.2250 = 0.9449$. The air is 5.5% less dense than standard, so the bullet will retain velocity longer and shoot approximately 0.8 MOA flatter at 1000 yards compared to standard conditions.

Speed of sound (at 27.8°C): $a = 20.047\sqrt{300.9} = 347.7 \text{ m/s}$.

Muzzle Mach number: $Ma_0 = 890.0/347.7 = 2.56$ (well into the supersonic regime).

10.5.4 Step 4: Solver Setup and Trajectory

The complete Julia solver call for this scenario:

```
1 params_6br = ShotParameters(  
2     # Bullet: Berger 105 Hybrid Target  
3     mass_grains      = 105.0,  
4     caliber_in       = 0.243,  
5     bc               = 0.275,           # G7  
6     drag_model       = :G7,  
7  
8     # Launch  
9     muzzle_vel_fps   = 2920.0,  
10    sight_height_in  = 1.5,  
11    zero_range_yd    = 100.0,  
12  
13    # Atmosphere: Ottawa, summer match  
14    temp_F           = 82.0,           # 27.8 C  
15    pressure_inhg    = 29.75,  
16    humidity_pct     = 55.0,  
17    altitude_ft      = 250.0,  
18  
19    # Wind: 8 mph from 2 o'clock (60 deg off nose)  
20    wind_speed_mph   = 8.0,  
21    wind_angle_deg   = 60.0,  
22  
23    # Target  
24    target_range_yd  = 1000.0,  
25  
26    # Spin: 1:7.5 RH twist  
27    twist_in         = 7.5,  
28    twist_direction  = 1,  
29    bullet_length_in = 1.10,  
30  
31    # Location: Ottawa, ON  
32    latitude_deg     = 45.4,  
33    azimuth_deg      = 270.0,         # firing West  
34    enable_coriolis  = true,  
35    enable_spin_drift = true,  
36 )  
37  
38 trajectory_table(params_6br, step_yd=100)
```

Listing 10.1: 6mm BR complete trajectory example

The solver output for this configuration:

Table 10.7: Computed trajectory: 6mm BR, 105 gr Berger Hybrid, $v_0 = 2920$ fps, 27.8°C (82°F), 29.75 in Hg, 55% RH. 8 mph wind at 60° . 100 yd zero. 1:7.5 RH twist, 45.4°N , firing West.

Range (yd)	Drop (in)	Elev (MOA)	Vel (fps)	Mach	Energy (ft-lb)	ToF (s)	Wind (in)	Spin (in)
100	0.0	0.0	2766	2.43	1784	0.106	0.3	0.0
200	-2.3	1.1	2617	2.30	1597	0.219	1.5	0.1
300	-9.0	2.9	2473	2.17	1427	0.339	3.6	0.2
400	-20.7	5.0	2334	2.05	1271	0.466	6.8	0.4
500	-38.2	7.3	2200	1.93	1129	0.602	11.1	0.7
600	-62.5	10.0	2070	1.82	1000	0.747	16.8	1.1
700	-94.8	12.9	1945	1.71	883	0.903	24.0	1.6
800	-136.5	16.3	1824	1.60	776	1.070	32.9	2.3
900	-189.5	20.1	1708	1.50	681	1.250	43.9	3.1
1000	-256.0	24.5	1596	1.40	594	1.445	57.0	4.1

10.5.5 Step 5: Analysis of Results

Velocity retention. The bullet arrives at 1000 yards at 1596 fps (Mach 1.40), still well above the transonic threshold (≈ 1340 fps). The 6mm BR with a high-BC 105 gr bullet retains adequate supersonic margin.

Total elevation. From the 100-yard zero, the shooter dials 24.5 MOA of elevation (approximately 7.1 mils). This is competitive with the 6.5 Creedmoor (28.5 MOA for 140 gr, Table 11.2) despite the lighter bullet, thanks to the higher muzzle velocity.

Wind deflection. The 8 mph wind at 60° produces a crosswind component $W_{\text{cross}} = 8 \sin 60^\circ = 6.93$ mph and a headwind component $W_{\text{head}} = 8 \cos 60^\circ = 4.0$ mph. The total wind deflection at 1000 yards is 57.0 inches (5.4 MOA). For a full-value 10 mph crosswind, this would scale to approximately 74 inches — about 4% more than the 6.5 Creedmoor (77.1 in.) but comparable, illustrating that the 6mm BR’s higher velocity partly compensates for the lower BC.

Spin drift. The 1:7.5 RH twist produces 4.1 inches of rightward drift at 1000 yards (0.39 MOA). This is a systematic bias that should be dialed into the scope or included in the wind hold.

Coriolis and Eötvös. Firing West at 45.4°N latitude:

- Horizontal Coriolis: ≈ 2.7 inches right (0.26 MOA), same direction as spin drift.
- Eötvös (firing West): ≈ 3.4 inches *down* (the bullet loses the “boost” of the Earth’s rotation), adding about 0.3 MOA to the required elevation.

Total horizontal correction: Wind 57.0 in. + spin drift 4.1 in. + Coriolis 2.7 in. = 63.8 inches total rightward deflection (6.1 MOA).

10.5.6 Step 6: Chronograph Validation

A 20-round chronograph string from this load:

2918, 2925, 2914, 2928, 2920, 2916, 2922, 2919, 2927, 2921,
2915, 2923, 2926, 2917, 2920, 2924, 2919, 2922, 2916, 2925

Statistics: $\bar{v} = 2920.9$ fps, $ES = 14$ fps, $SD = 3.9$ fps. The SD of 3.9 fps produces a vertical dispersion of:

$$\sigma_y(1000 \text{ yd}) \approx 0.23 \times 3.9 = 0.90 \text{ inches} \quad (0.09 \text{ MOA})$$

This is well below the F-Class X-ring diameter (2.5 inches) and represents a benchrest-grade load.

10.5.7 Step 7: DOPE Card Summary

Table 10.8: DOPE card: 6mm BR 105 Berger / N140 / 2920 fps. Ottawa, 27.8 °C (82°F), 29.75 inHg. Wind hold is per 1 mph full crosswind.

Range (yd)	Elevation (MOA)	Wind/1 mph (MOA)	Spin+Cor (MOA)
200	1.1	0.07	0.01
300	2.9	0.11	0.03
400	5.0	0.16	0.05
500	7.3	0.21	0.08
600	10.0	0.27	0.12
700	12.9	0.33	0.17
800	16.3	0.39	0.23
900	20.1	0.47	0.30
1000	24.5	0.54	0.39

This DOPE card gives the shooter all the information needed: dial the elevation, hold or dial the wind column multiplied by the estimated crosswind speed, and add the spin+Coriolis correction. The total process—from the mathematical models of Chapters 2–6 through the Julia solver of Chapter 7 to this practical output—represents the complete ballistic pipeline that this manual describes.

10.6 Interpreting Chronograph Data

$$\bar{v} = \frac{1}{N} \sum_{i=1}^N v_i, \quad ES = v_{\max} - v_{\min}, \quad SD = \sqrt{\frac{1}{N-1} \sum_{i=1}^N (v_i - \bar{v})^2}$$

Target values: $ES < 20$ fps (excellent: < 10), $SD < 8$ fps (excellent: < 4).

As a practical benchmark, the following table shows typical velocity consistency for factory versus hand-loaded ammunition:

Table 10.9: Typical velocity consistency: factory ammunition vs. optimized handloads

Ammunition type	ES (m/s)	ES (fps)
Standard factory match	9–10	30–33
Premium factory match	5–7	16–23
Optimized handloads	2–3	7–10
Benchrest-grade handloads	< 2	< 7

The gap between factory and hand-loaded ammunition is the primary motivation for reloading in competition shooting: reducing velocity spread by a factor of 3–5 translates directly into tighter vertical dispersion at long range (see below).

10.6.1 Velocity SD Impact on Vertical Dispersion

$$\sigma_y(R) \approx \left| \frac{\partial y}{\partial v_0} \right|_R \cdot \sigma_v \quad (10.1)$$

Chapter 11

Ballistic Reference Tables

11.1 Bullet Data for Common Competition Bullets

Table 11.1: Ballistic data for popular competition bullets [Litz, 2011, 2015]

Bullet	Wt (gr)	Cal	BC G1	BC G7	SD	Twist
Berger 105 Hyb 6mm	105	.243	0.536	0.275	0.254	1:7.5
Berger 140 Hyb 6.5	140	.264	0.607	0.311	0.287	1:8
Hornady 147 ELD-M	147	.264	0.697	0.351	0.301	1:7.5
Berger 180 Hyb 7mm	180	.284	0.683	0.350	0.319	1:8.5
Sierra 175 MK .308	175	.308	0.505	0.259	0.264	1:10
Berger 185 Jugg .308	185	.308	0.552	0.283	0.279	1:10
Hornady 178 ELD-M	178	.308	0.535	0.274	0.268	1:10
Berger 300 Hyb .338	300	.338	0.818	0.419	0.375	1:9.4

11.2 Sample Trajectory Table

Table 11.2: Trajectory: 6.5 CM, 140 gr Berger Hybrid, $BC_{G7} = 0.311$, $v_0 = 2700$ fps, 100 yd zero, sea level standard atmosphere

Range (yd)	Drop (in)	Come-Up (MOA)	Velocity (fps)	Energy (ft-lb)	ToF (s)	10 mph Wind (in)	Spin Drift (in)
100	0.0	0.0	2545	2015	0.115	0.5	0.0
200	-2.8	1.3	2396	1786	0.237	2.1	0.1
300	-10.7	3.4	2252	1578	0.365	5.0	0.3
400	-24.5	5.9	2113	1389	0.501	9.2	0.5
500	-45.0	8.6	1979	1219	0.646	15.1	0.9
600	-73.4	11.7	1851	1066	0.800	22.8	1.4
700	-111.0	15.1	1728	929	0.965	32.5	2.0
800	-159.5	19.0	1610	807	1.143	44.6	2.8
900	-221.1	23.5	1498	698	1.334	59.3	3.8
1000	-298.0	28.5	1393	604	1.541	77.1	5.1

Chapter 12

Special Topics

12.1 Motivation: The Edges of the Envelope

Standard exterior ballistics hold true while the bullet is flying supersonic. However, new bizarre aerodynamic phenomena occur when the bullet slows down and breaks the sound barrier in reverse (the transonic zone). This chapter briefly introduces edge-case ballistics that ruin otherwise perfect shots at extreme long ranges.

12.2 Transonic Stability

The dynamic stability factor S_d must be considered alongside the gyroscopic stability factor S_g [McCoy, 2012]. For full stability: $S_g > 1.0$ and $0 < S_d < 2$.

As a bullet decelerates through the transonic zone ($0.9 \lesssim Ma \lesssim 1.2$), the centre of pressure shifts rapidly and the aerodynamic damping can change sign, potentially causing a well-stabilized supersonic bullet to become dynamically unstable. The practical consequence is increased dispersion—often dramatically so—once the bullet enters this regime. Long-range competitors should therefore know at what range their chosen load crosses into the transonic zone and treat that as the effective maximum range for precision fire.

Table 12.1: Approximate transonic transition ranges for common competition cartridges at sea-level standard conditions. The transonic zone is defined as $0.9 \leq Ma \leq 1.1$ (≈ 310 – $380 \frac{\text{m}}{\text{s}}$).

Cartridge	Bullet (gr)	v_0 (m/s)	Enters transonic (m)	Subsonic (m)
.223 Rem	77 SMK	838	≈ 600	≈ 750
.308 Win	155 Lapua Scenar	860	≈ 750	≈ 950
.308 Win	175 SMK	775	≈ 820	≈ 1075
6.5 Creedmoor	140 Berger Hybrid	823	≈ 950	≈ 1200
.300 Win Mag	185 Berger Jugg	943	≈ 1275	≈ 1600
.338 Lapua Mag	300 Berger Hybrid	838	≈ 1500	≈ 1900

Bullets with higher BC values and higher muzzle velocities remain supersonic longer, but the relationship is not linear: the steep drag rise in the transonic zone means that once a bullet begins to slow through $Ma \approx 1.1$, it decelerates rapidly. The solver in Chapter 7 captures this behavior through the fine resolution of the G7 drag table in the transonic region.

12.3 Inclined Fire (Rifleman’s Rule)

$$R_{\text{effective}} = R_{\text{slant}} \cdot \cos \alpha \quad (12.1)$$

The perpendicular gravity component $g_{\perp} = g \cos \alpha$ causes the bullet to drop away from the line of sight. Since $\cos \alpha < 1$ for any nonzero inclination (up or down), the drop is always less than flat fire.

Rather than applying the approximate range-scaling of Eq. (12.1) as a post-correction, the solver handles inclination exactly: it resolves gravity in the line-of-sight frame, applying $g_{\perp} = g \cos \alpha$ perpendicular to the sight line and $g_{\parallel} = g \sin \alpha$ along the flight path, then integrates normally. This captures the slight up/down asymmetry (the along-path component accelerates a descending shot and decelerates a climbing one) that the pure cosine rule omits. For the reference 6.5 mm load at $\pm 30^\circ$ and 1000 yd, the drop along the sight line falls from -300.6 inches (flat) to -258.4 inches (uphill) and -252.2 inches (downhill).

These three figures were -272 , -233 and -228 until 2026-08-14 — about 10 % shallower, in a constant ratio. They predate the reference-area correction on C_D (the BRL tables refer drag to $\pi d^2/4$, so the solver carries a factor $4/\pi$; omitting it understates drag by 27 %). Both implementations now return the values above, to the digit.

12.4 Barrel Harmonics and Optimal Charge Weight

Barrel vibrations cause the muzzle to describe an elliptical pattern at the moment of bullet exit. The OCW method seeks charge weights where the muzzle vertical angle is at an extremum, creating a flat spot that compensates for velocity variation.

Chapter 13

Error Budget and Sensitivity Analysis

13.1 Motivation: Knowing Your Weakest Link

In competition shooting, you are constantly fighting physics. An "Error Budget" is a mathematical tool to figure out which physical variable is most likely to cause you to miss. It helps a shooter answer the question: *"Should I spend \$500 on a better laser rangefinder, or \$500 on a better scale to weigh my gun powder?"*

By running a sensitivity analysis, we systematically slightly tweak one variable at a time (like making the wind 1 mph faster, or the muzzle velocity 10 ft/s slower) and observe how much the bullet's impact point moves at a specific range.

13.2 Sensitivity Coefficients

For any given trajectory output Y (such as vertical drop or wind deflection) at a specific range R , we can define the sensitivity S_i to a specific parameter p_i :

Let's define the terms:

- Y : The output of the ballistic solver (e.g., vertical drop in inches).
- p_i : The input parameter being analyzed (e.g., Muzzle Velocity in fps).
- Δp_i : A small, realistic uncertainty or error in that parameter.

$$S_i = \frac{\partial Y}{\partial p_i} \approx \frac{Y(p_i + \Delta p_i) - Y(p_i - \Delta p_i)}{2 \Delta p_i}$$

Table 13.1: Error budget: 6.5 Creedmoor, 140 gr, $BC_{G7} = 0.311$, 2700 fps at 1000 yd

Parameter	Uncertainty	Vertical (in)	Horizontal (in)
Muzzle velocity	± 10 fps	2.5	—
BC	$\pm 3\%$	3.2	1.8 (wind)
Wind speed (10 mph cross)	± 2 mph	—	15.4
Wind direction	$\pm 10^\circ$	—	6.8
Temperature	$\pm 5.6^\circ\text{C}$ ($\pm 10^\circ\text{F}$)	0.8	—
Range estimation	± 5 yd	1.5	—
Spin drift (uncompensated)	—	—	5.1
Coriolis (45°N , uncomp.)	—	< 1.0	2.8

Key insight: Wind reading dominates the error budget at long range. Wind-related errors are 3–5 times larger than all other sources combined.

Chapter 14

Ballistic Implications for Reloading

14.1 Motivation: Crafting the Perfect Formula

This chapter bridges the complex mathematical formulas of the preceding chapters with the tangible, practical decisions a competition handloader must make at their physical reloading bench. It demonstrates how to apply ballistic theories (like interior pressure curves and exterior sensitivity) to actual brass, powder, and projectiles to achieve peak performance.

14.2 The Reloader's Equation: What You Control

From the 3-DOF equation of motion (5.4), the trajectory depends on three groups of quantities:

1. **Bullet parameters** (m , d , B_C , L): fixed once the bullet is selected.
2. **Launch parameters** (v_0 , σ_v , α_0): directly controlled by propellant charge, seating depth, neck tension, primer choice, and case preparation.
3. **Environmental parameters** (ρ , T , P , H , wind): not controllable, but the reloader can minimize their *impact* through component choices that reduce trajectory sensitivity.

14.3 Muzzle Velocity: The Central Reloading Output

14.3.1 Charge Weight and Velocity

The relationship between propellant charge weight C and muzzle velocity v_0 is approximately linear over the useful loading range:

$$v_0 \approx v_{\text{base}} + k_C (C - C_{\text{base}})$$

where k_C is the velocity gain per grain, typically 15–40 fps/gr. For 6.5 Creedmoor with H4350, $k_C \approx 25$ fps/gr [Litz, 2011].

14.3.2 Velocity Consistency and Vertical Dispersion

From Eq. (10.1), the vertical group size at range R due to velocity variation:

$$\sigma_y(R) = \left| \frac{\partial y}{\partial v_0} \right|_R \cdot \sigma_v$$

Table 14.1: Velocity sensitivity: vertical shift per 1 fps change, 6.5 CM 140 gr

Range (yd)	$ \partial y/\partial v_0 $ (in/fps)	Vertical for SD=10 fps (in)
300	0.02	0.2
600	0.08	0.8
800	0.15	1.5
1000	0.25	2.5
1200	0.40	4.0
1500	0.72	7.2

14.3.3 Achieving Low SD: Quantitative Checklist

Assuming independent error sources, the combined SD is:

$$\sigma_{v,\text{total}} = \sqrt{\sigma_{\text{charge}}^2 + \sigma_{\text{brass}}^2 + \sigma_{\text{primer}}^2 + \sigma_{\text{seat}}^2 + \sigma_{\text{neck}}^2 + \sigma_{\text{lot}}^2}$$

Table 14.2: Estimated velocity SD contributions by reloading variable

Variable	Typical σ (fps)	Careful prep (fps)
Charge weight (± 0.1 gr thrown)	6–12	2–4 (weighed ± 0.02 gr)
Brass volume variation (unsorted)	4–8	1–2 (sorted)
Primer seating depth variation	2–5	1–2 (uniformed pockets)
Seating depth variation	2–4	<1 (consistent BTO)
Neck tension variation	2–6	1–2 (turned, annealed)
Propellant lot variation	0–3	0 (single lot)
RSS total (typical)	9–17	
RSS total (prepared)		3–5

- **Annealing:** Heating the case neck and shoulder to $\approx 750^\circ\text{F}$ (incipient red) is essential for maintaining consistent neck tension. Without annealing, brass work-hardens, resulting in inconsistent bullet release force and increased SD.
- **Tempilaq:** For torch-based annealing, temperature-indicating liquids are recommended to calibrate heating times accurately and avoid overheating the case body.

14.4 BC Sensitivity and Bullet Selection

A 10% higher BC reduces wind deflection by approximately 8–12%. **Choosing the highest-BC bullet your twist rate can stabilize is the single most impactful choice for reducing wind sensitivity**, which is the dominant error source (Table 13.1).

14.5 Temperature Effects: Propellant and Atmosphere

14.5.1 Combined Temperature Effect

$$\Delta y_{\text{total}}(R, \Delta T) = \underbrace{\frac{\partial y}{\partial v_0} \sigma_T \Delta T}_{\text{velocity effect}} + \underbrace{\frac{\partial y}{\partial \rho} \frac{\partial \rho}{\partial T} \Delta T}_{\text{density effect}} \quad (14.1)$$

where Δy_{total} is the total vertical shift at range R , ΔT is the temperature deviation from a reference point, σ_T is the propellant's temperature sensitivity, and ρ is the air density. The terms $\partial y/\partial v_0$ and $\partial y/\partial \rho$ represent the trajectory's sensitivity to muzzle velocity and air density changes, respectively.

For temperature-sensitive propellants, the two effects are *additive*. Using a temperature-stable propellant is ballistically equivalent to reducing the effective sensitivity by 60–80%.

Table 14.3: Temperature sensitivity by propellant class

Propellant Class	σ_T (fps/°F [fps/°C])	Δv_0 for $\pm 22.2^\circ\text{C}$ [$\pm 40^\circ\text{F}$]
Standard (IMR 4064, etc.)	1.5–2.0 [2.7–3.6]	± 60 –80 fps
Temperature-stable (Varget, H4350)	0.3–0.8 [0.5–1.4]	± 12 –32 fps
Highly stable (RL-16, N565)	0.2–0.5 [0.36–0.9]	± 8 –20 fps

14.6 Seating Depth and Internal Ballistic Coupling

Seating depth affects freebore volume (pressure curve), engraving resistance (pressure peak timing), and initial alignment (reducing α_0). The empirical relationship:

$$\frac{\partial v_0}{\partial(\text{jump})} \approx -3 \text{ to } -8 \text{ fps per } 0.001 \text{ in. increase}$$

The group size model:

$$G(j) = \sqrt{G_{\text{base}}^2 + G_{\alpha}^2(j) + G_v^2(j)}$$

Typical sweet spots: jam/light contact (0.000–0.005 in.), moderate jump (0.015–0.030 in.), and extended jump (0.060–0.100 in.) [Litz, 2011].

14.7 Pressure Estimation and Safety Margins

Table 14.4: SAAMI maximum average pressure for competition cartridges

Cartridge	MAP (psi)	MAP (MPa)
.223 Remington	55,000	379
6.5 Creedmoor	62,000	427
.308 Winchester	62,000	427
.300 Winchester Magnum	64,000	441
.338 Lapua Magnum	60,916	420

From the Le Duc model peak pressure (3.1):

$$P_{\text{peak}} \approx 1.6 \times P_{\text{avg}} = 1.6 \times \frac{m_e v_0^2}{2 A_{\text{bore}} L_{\text{travel}}}$$

14.8 Barrel Life

Table 14.5: Approximate barrel life for competition cartridges

Cartridge	Barrel Life (rounds)
6mm BR / 6 Dasher	2500–3500
6.5 Creedmoor	2500–3000
.308 Winchester	5000–8000
.284 Winchester	1500–2500
.300 Winchester Magnum	1200–2000

The ballistic signature of barrel wear:

$$v_0(N) \approx v_{0,\text{new}} - k_{\text{wear}} \cdot N^{0.7}$$

$$\sigma_v(N) \approx \sigma_{v,\text{new}} + k_{\sigma} \cdot N^{0.5}$$

14.9 Load Development Workflow

Based on the mathematical models above:

- Step 1: Bullet selection.** Maximize B_C . Verify $S_g > 1.4$ using Eq. (6.1).
- Step 2: Propellant selection.** Temperature-stable. Calculate Δv_0 over competition temperature range using Eq. (3.3).
- Step 3: Brass preparation.** Sort by weight/capacity. Uniform necks and primer pockets.
- Step 4: Charge weight exploration.** Satterlee ladder or OCW test. Identify velocity nodes.
- Step 5: Seating depth optimization.** Test at 0.010 in. increments from lands.
- Step 6: Validation.** 20+ rounds over chronograph. SD < 8 fps (target < 5). Run the solver (Chapter 7) to verify vertical dispersion at max range.
- Step 7: Temperature verification.** Compute come-up shift using Eq. (14.1).

Appendix A

Detailed Mathematical Derivations

A.1 Motivation: Showing the Work

The models and formulas used throughout this manual are not mere rules of thumb—they are robust physical laws rooted in classical mechanics and aerospace engineering. This appendix provides the rigorous mathematical derivations for these core equations.

A.2 Derivation of the Point-Mass Equations of Motion

Starting from Newton’s second law, neglecting lift (valid for small yaw):

$$m \ddot{\mathbf{r}} = -m g \hat{\mathbf{e}}_y - \frac{1}{2} \rho C_D A \|\mathbf{v}_{\text{rel}}\| \mathbf{v}_{\text{rel}}$$

Expressing in component form with $\mathbf{v}_{\text{rel}} = \mathbf{v} - \mathbf{v}_w$ and dividing by m , introducing $C_D A / (2m) = \pi C_D^{\text{std}} / (8 B_C)$, recovers Eqs. (5.5)–(5.6).

A.3 Derivation of the Coriolis Terms

In a rotating reference frame:

$$m \mathbf{a}_{\text{rot}} = \mathbf{F} - 2m (\boldsymbol{\omega} \times \mathbf{v}_{\text{rot}}) - m \boldsymbol{\omega} \times (\boldsymbol{\omega} \times \mathbf{r})$$

The centrifugal term is absorbed into local g . In local coordinates at latitude ϕ :

$$\boldsymbol{\omega} = \omega_E (0, \cos \phi, \sin \phi)^T$$

Computing the cross product, the dominant terms for $v_x \gg v_y, v_z$ (where x is downrange, y is vertical, and z is cross-range):

$$\begin{aligned} a_z^{\text{Cor}} &\approx 2\omega_E v_x \sin \phi \\ a_y^{\text{Cor}} &\approx 2\omega_E v_x \cos \phi \sin \psi \end{aligned}$$

where ψ is the firing azimuth. Integrating these twice with respect to time yields the deflection approximations used in Chapter 6.

A.4 Derivation of Spin Drift via Yaw of Repose

The equilibrium yaw angle from gyroscopic precession:

$$\alpha_{\text{repose}} = \frac{g}{v^2} \cdot \frac{I_x \omega_s}{C_{M_\alpha} \frac{1}{2} \rho v^2 A d}$$

This produces $F_{\text{side}} = C_{L_\alpha} \frac{1}{2} \rho v^2 A \alpha_{\text{repose}}$, causing the spin drift deflection.

Appendix B

Companion Julia Package

The complete Julia implementation of all mathematical models in this manual is provided as a standalone file: `CompetitionBallistics.jl`. This file contains six sub-modules:

1. `BallisticUtils` — Unit conversions, sectional density, form factor, Miller stability, Greenhill twist.
2. `Atmosphere` — ICAO standard atmosphere, humidity correction, density altitude.
3. `InteriorBallistics` — Le Duc model, burn fraction, barrel length correction, temperature sensitivity, closed-bomb pressure.
4. `DragModels` — G1 and G7 BRL tabular data with both linear and cubic spline interpolation.
5. `ExteriorBallistics` — Full 3-DOF RK4 solver with wind, Coriolis, spin drift, zero-finding, and trajectory table output.
6. `ReloadingAnalysis` — Chronograph statistics, velocity-induced vertical dispersion, ladder test analysis, seating depth sensitivity, temperature shift tables, BC estimation from two chronographs, load quality scoring.

```
1 include("CompetitionBallistics.jl")
2 using .CompetitionBallistics
3 using .CompetitionBallistics.ExteriorBallistics
4 using .CompetitionBallistics.ReloadAnalysis
5
6 params = ShotParameters(
7     mass_grains=140.0, caliber_in=0.264,
8     bc=0.311, drag_model=:G7,
9     muzzle_vel_fps=2700.0, zero_range_yd=100.0,
10    wind_speed_mph=10.0, wind_angle_deg=90.0,
11    target_range_yd=1000.0,
12    twist_in=8.0, bullet_length_in=1.34,
13 )
14 trajectory_table(params, step_yd=100)
15
16 # Chronograph analysis
17 v = [2695, 2702, 2688, 2710, 2699, 2693, 2701, 2707]
18 stats = chronograph_stats(v)
19 vert = velocity_vertical_dispersion(params, stats.sd,
20                                     range_yd=1000.0)
```

Listing B.1: Quick-start usage of `CompetitionBallistics.jl`

The file requires only the Julia standard library (`Statistics`, `Printf`).

Appendix C

Greenhill's Formula and Twist Rate Selection

C.1 Motivation: Keeping the Bullet Pointy-End Forward

A rifle barrel contains spiral grooving called "rifling" to impart intense spin to the bullet. Without this spin, the bullet would tumble end-over-end as soon as it hit the air. The "twist rate" characterizes how aggressive this spiral is (e.g., 1 turn in 8 inches, or 1:8).

George Greenhill, a mathematics professor at the Royal Military Academy in the late 1800s, developed a famous empirical formula to determine the optimal twist rate to stabilize a bullet. It proves that heavier (longer) bullets require significantly faster twist rates.

Let's define the variables:

- T : The required rifling twist rate (length of one full turn in calibers).
- d : The diameter of the bullet (inches).
- l : The overall length of the bullet (inches).
- ρ_b, ρ_a : Density of the bullet and density of air, respectively.
- C : The Greenhill empirical constant (typically 150).

$$T = \frac{C d^2}{l} \sqrt{\frac{\rho_b}{\rho_a}}$$

For lead-core jacketed bullets at standard temperatures, the formula is vastly simplified to calculate the required twist (in inches per turn):

$$T_{\text{inches}} \approx \frac{150 d^2}{l}$$

Use $C = 150$ for muzzle velocities $v < 2800$ fps, and $C = 180$ for higher velocities $v > 2800$ fps [Greenhill, 1879].

Modern Gyroscopic Stability Guidance (S_g): While Greenhill's is an excellent historical rule of thumb, modern shooters use Miller's gyroscopic stability factor (S_g).

- $S_g < 1.0$: Unstable (tumbling).
- $S_g \in [1.0, 1.5]$: Marginally stable. The bullet flies straight but with residual yaw that costs BC — up to 9% at $S_g = 1.2$.
- $S_g \gtrsim 1.5$: Full BC realised. This is the threshold Litz recommends [Litz, 2011].
- $S_g > 2.0$: Amply stable. Spin drift grows with S_g , but Doppler radar data contradicts the older claim that "over-stabilisation" costs accuracy: at flat-fire ranges a higher S_g *reduces* drag, especially transonic. Over-spinning matters mainly for jacket integrity on thin-jacketed bullets.

Bibliography

- Ronald D. Anderson and Keith D. Fickie. IBHVG2 – a user’s guide. Technical Report BRL-TR-2829, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, 1987.
- Francis Bashforth. *A Mathematical Treatise on the Motion of Projectiles*. Asher & Co., London, 1870.
- W. F. Braun. The free flight aerodynamics range. Technical Report Report No. 1048, Ballistic Research Laboratories, Aberdeen Proving Ground, MD, 1958.
- Donald E. Carlucci and Sidney S. Jacobson. *Ballistics: Theory and Design of Guns and Ammunition*. CRC Press, 2007.
- John Corner. *Theory of the Interior Ballistics of Guns*. John Wiley & Sons, New York, 1950.
- Gordon’s Reloading Tool. *Gordon’s Reloading Tool – User Manual*, 2021. <https://grtools.de>.
- A. G. Greenhill. On the rotation required for the stability of an elongated projectile. *Minutes of the Proceedings of the Royal Artillery Institution*, 10:577–593, 1879.
- James M. Ingalls. *Exterior Ballistics in the Plane of Fire*. D. Van Nostrand Company, 1893.
- International Civil Aviation Organization. *Manual of the ICAO Standard Atmosphere (extended to 80 km)*, 1993. ICAO Doc 7488/3, 3rd edition.
- Beat P. Kneubühl. *Ballistik – Theorie und Praxis*. Springer, 2018. ISBN 978-3-662-58299-2.
- Bryan Litz. *Applied Ballistics for Long Range Shooting*. Applied Ballistics, LLC, 2nd edition, 2011.
- Bryan Litz. *Ballistic Performance of Rifle Bullets*. Applied Ballistics, LLC, 3rd edition, 2015.
- Robert L. McCoy. *Modern Exterior Ballistics: The Launch and Flight Dynamics of Symmetric Projectiles*. Schiffer Publishing, 2nd edition, 2012. 1st edition 1999; 2nd edition 2012, ISBN 978-0-7643-3825-0.
- Don Miller. The new twist rule. *Precision Shooting*, March 2005.
- William H. Press, Saul A. Teukolsky, William T. Vetterling, and Brian P. Flannery. *Numerical Recipes: The Art of Scientific Computing*. Cambridge University Press, 3rd edition, 2007.
- Francesco Siacci. *Balistica*. Arnaldo Forni Editore, Bologna, 1888.
- U.S. Committee on Extension to the Standard Atmosphere. U.s. standard atmosphere, 1976. Technical Report NOAA-S/T 76-1562, NOAA, NASA, USAF, 1976.

Glossary

BC	Ballistic Coefficient — ratio of sectional density to form factor.
BRL	Ballistic Research Laboratory (US Army, Aberdeen Proving Ground).
COAL	Cartridge Overall Length.
BTO	Base To Ogive length.
DA	Density Altitude.
ELR	Extreme Long Range (> 1500 yd).
ES	Extreme Spread (max velocity – min velocity).
MOA	Minute of Angle (≈ 1.047 in. at 100 yd).
Mil	Milliradian (≈ 3.6 in. at 100 yd).
OCW	Optimal Charge Weight.
PRS	Precision Rifle Series.
NRL	National Rifle League.
SD	Sectional Density or Standard Deviation (context-dependent).
VLD	Very Low Drag (bullet design).
S_g	Gyroscopic Stability Factor.
G1/G7	Standard drag model designations.