AMLET
Reference manual



Fabian Bastin

October 17, 2026

Abstract

This document explains how to install and use the software AMLET v0.13.1, designed to estimate multinomial and mixed logit models. The current documentation is unfortunately far from be completed, and is full omissions and possibly errors. Any suggestion concerning this document and/or the software should be send to bastin@iro.umontreal.ca.

The latest version of this document, as well as the software itself, can be retrieved at the internet address http://amlet.slashbin.net.

Contents

1 Introduction **3**
- 1.1 What is AMLET? . . . 3
- 1.2 Supported systems . . . 3
- 1.3 Requirements . . . 4
  - 1.3.1 Hardware requirements . . . 4
  - 1.3.2 Software requirements . . . 4
  - 1.3.3 Windows users . . . 5
- 1.4 Acknowledgements . . . 5
- 1.5 Installation . . . 6

2 First steps with AMLET **7**
- 2.1 Standalone application . . . 7
- 2.2 Driver file . . . 8

3 Discrete choice models **11**
- 3.1 Supported models . . . 11
- 3.2 Supported distributions . . . 12
- 3.3 Sampling methods . . . 13
  - 3.3.1 Halton sequences . . . 14
  - 3.3.2 Sobol sequences . . . 15
  - 3.3.3 Rank-1 lattices . . . 15
- 3.4 Pseudo-random numbers generators . . . 15
- 3.5 Results validation . . . 16

4 Data files **17**
- 4.1 Data files . . . 17
  - 4.1.1 GAUSS-like formats . . . 17

5 Output files **20**
5.1 Results file 20
5.1.1 Definition 20
5.1.2 Content 20
5.2 Log file 21

A Example of driver file **22**
A.1 Multinomial logit 22
A.1.1 Driver file 22
A.2 Mixed logit 23
A.2.1 Driver file 23

B Numerical issues **25**
B.1 Choice probability computation 25
B.2 Data file problems 25

C Legal aspects **26**
C.1 Licenses and acknowledgements 26
C.1.1 MIT License 26
C.1.2 Open Software License v 2.1 27
C.1.3 BSD License 30

Index **32**

Chapter 1

Introduction

1.1 What is AMLET?

AMLET is an acronym for Another Mixed Logit Estimation Tool. As its name suggests, it is a software mainly designed to estimate various kind of mixed logit models. It can be used either as a standalone program, either as a C library. AMLET is an open source project (see Appendix C.1; the last version can be downloaded at the address `http://amlet.slashbin.net`.

1.2 Supported systems

AMLET development is primarily Unix-oriented, while the software can also be used on Windows systems, with some technical limitations[1]. Most of the development and tests have been performed on Linux systems. The software should also runs without major trouble on BSD systems, or Mac OS X. Windows users should be able to compile AMLET using MinGW, available at `http://www.mingw.org`, at the expense of some loss of performance. For Windows users, it is recommended to install Linux in a virtual machine, using for instance VirtualBox, available for free at `http://www.virtualbox.org`. See Section 1.3.3 for more details.

Unless otherwise stated, we will assume in this document that you work on a Unix-like system; the explications are still valid for the other environment. We also assume that you use `bash` as your shell, since it is the default choice for major Linux distributions, as well as `mingw`; some users could have to slighty adapt the explanation if they use csh shells, and its variants. If you do not know what is your

[1] In particular, the timings will be less accurate.

current shell, you probably already use `bash`. It can also be determined by reading the file `/etc/password`.

1.3 Requirements

1.3.1 Hardware requirements

There is no formal minimum requirements for AMLET, since they crucially depend on the size of dataset size and the number of random variables that are present in the model. We however recommand a minimum of 1Go RAM, knowing that the available memory constrains the achievable accuracy. AMLET should work smoothly on any modern computer.

1.3.2 Software requirements

Various software elements are required in order to correctly install AMLET, as well as some optional elements, if you want to install additional tools along with the main package.

C compiler We recommand to use the compiler delivered with your computer; on Linux-machine and mingw, this is typically the GNU C Compiler (gcc).

Compilers The code is mainly written in C and C++, but contains portions written in Fortran, mainly imported from LAPACK. Consequently, both a C and a Fortran compilers are requires; the code has been successfully tested with `gcc` and `gfortran`, available in any Linux distribution.

Unix shell In order to easily perform the installation, autotools (autoconf, automake, libtoolize) are highly recommanded. The detailed installation process can however often be pursued without them. If you are using Mac OS X, you can experience problems with `libtoolize`. Using the development environment proposed in the third-party software collections fink (`http://www.finkproject.org/`) can resolve this issue.

Lex, Yacc Driver parsing with AMLET requires standard lexical analyser and parser. AMLET requires flex, and yacc or bison.

Perl Some optional analysis tools provided with AMLET rely on Perl scripting language.

Oratio, Ophelia These are two companion libraries, that have to be installed first and can be downloaded on `http://amlet.slashbin.net`.

1.3.3 Windows users

The most convenient solution is to install Linux on a Virtual Machine, using for instance VirtualBox (http://www.virtualbox.org). A virtual machine allows to emulate a PC, allowing the installation of a complete operating system. There are of course some overheads in executation time, as it means that one operating system is running inside another one, but a Virtual Machine can be easily uninstalled if no more needed, without affecting the host Operating System. It is therefore the easiest solution.

A more complex solution is to install MinGW, standing for Minimal Gnu system for Windows. MinGW can be download at the address http://www.mingw.org. Pay attention to install all the development packages during the installation, in order to have to required tools to compile the code. It is also a good idea to install a correct text editor. Various editors are available under Windows: Vim, Emacs, Xemacs.

1.4 Acknowledgements

Like for many projects, the development of AMLET has only been possible with the help of many people. First of all, I would like to express my gratitude so Cinzia Cirillo, for the hard work that we have achieved together. This software could not has been written without her advices, based on her huge experience of the practical aspects of the problem. I would also like to thank Philippe L. Toint, who was my Ph.D. advisor during four years, and teached me the most important aspects of nonlinear programming. Finally, my thanks go to Belgian National Fund for Scientific Research, who gave me the grant that made the initial work on this project possible. The development of AMLET has been initiated at the University of Namur (Belgium), continued in the Imperial College London (United Kingdom) and Cerfacs (Toulouse, France). I pursue it during my (very limited) free time at the University of Montreal (Canada).

The documentation of a software is always a difficult exercise. I would therefore like to thank anyone that helped us to improve the present document. In particular, I would like to express my gratitude to Roberta "Speedy" Pellicanò for her suggestions, during my study stay in the University Frederico II of Naples, Italy (June 2004), and Jasper Knockaert. The software has also benefit from many suggestions during its development. The following list is certainly far from be complete; my apologies go to each one I have forgotten. I will cite here (by alphabetical order) Michel Bierlaire and Stéphane Hess.

Finally, the painting reproduced the front cover is due to Pieter van Steenwyck, under the name *Ars longa, vitta brevis*.

1.5 Installation

AMLET is currently distributed in source code only, so that the installation process primarily involves the compilation of the various source files. AMLET first requires the installation of the libraries ORATIO and OPHELIA. We refer to their respective documentations for details about the corresponding installation procedures.

As for the libraries, you can compile AMLET with the commands

```
./configure
make
sudo make install
```

Optimization compilation options can be specified as arguments of `configure`, for instance:

```
./configure CFLAGS=''-O2'' FFLAGS="-O2"
```

Chapter 2

First steps with AMLET

AMLET can be used as a C library or a standalone application. When used as a library, more complex models can be described and more analysis can be performed, but at the expense of some programming efforts. The use as a standalone application is easier, but the range of models that can be estimated is more limited.

2.1 Standalone application

When AMLET is used as a command-line application, it has to be launched from a text-console. The basic usage is

```
amlet [OPTIONS] FILE
```

where `FILE` designs the driver file (see Section 2.2), and `[OPTIONS]` corresponds to optional options, as described in Table 2.1. The options can be used in short or long form; for instance, the command

```
amlet -o log driver
```

has the same effect that

```
amlet --output log driver
```

We briefly describe these options here, and cover them in more details in the relevant sections.

debug is meant for development purposes, delivering additional messages on the standard output in order to help debugging code;

help option makes AMLET displaying some brief help on the screen, and then exits.

short	long	argument	function
`-d`	`--debug`	-	activate debug mode
`-h`	`--help`	-	print help message
`-o`	`--output`	file name	save the log information into a file
`-v`	`--verbose`	-	verbose mode
`-V`	`--version`	-	print version number

Table 2.1: command-line options

output allows the user to define the name of the log file (see Section 5.2).

verbose option informs AMLET to print additional information on the screen during execution.

version prints the version number on the screen, afterwhat the program exits.

2.2 Driver file

The AMLET driver file expresses a specification of the model to calibrate, as well as of the optimization method to apply. The driver has to be written in raw text format; examples of driver files can be found in Appendix A. It basically consists of two kinds of lines: the command ones and the affectations ones. A command line has the following form:

```
command parameters;
```

In other terms if consists of a command followed by the parameters to apply to this command. An affection line has the form

```
variable = value;
```

The value can be an integer, a real, a string or a set, depending on the variable that has to be affected. In some cases, a predefined constant identifier can be used instead of a numerical quantity. String values are any sequence of characters, enclosed within double quotes; a correct string would be for example

```
``this is a string''
```

You cannot use double quotes inside a string. We give in Table 2.2 the name of the main variables, in alphabetical order. There will be discussed in more details in the relevant sections.

Parameter	Default value	Function
b	$(0,\ldots,0)^T$	starting point
btype		type of the utilities coefficients
bgen		logit parameters for synthetic population generation
bgentype		type of the utilities coefficents during observations generation
censor		0 if all individuals face to all alternatives, 1 otherwise
iddep		dependent variable index
idcensor		variable index corresponding to the alternatives availability
draws		indicates if new draws are to be generated or if they have to be read from an external file
drawsname		name of the file containing the draws
eps		tolerance used for optimization
format	Train96	format of the data file
hessian_update		Hessian approximation method
level_accuracy		significance level used for objective accuracy evaluation
method		optimization method
np		number of individuals
nalt		number of alternatives
niter		maximum number of iterations during the optimization process
nobs		total number of observations
nrep		number of draws
nvar		number of variables (coefficients)
problem		problem name
robust		indicates if robust estimation of variance-covariance matrix has to be used
rangen		random numbers generation method
legacy_rng	false	reproduce the random draws of AMLET 0.13.1 (see Section 3.4)
sampling		sampling method
randomization		randomization strategy
seed1		seed of the random generator
validation	false	results validation

Table 2.2: variables

You can also write comments with the characters # or @. The remaining of the line is then ignored by AMLET, except if these characters are part of a string. The driver file is case unsensitive, except for filenames, depending on the operating system on which AMLET is executed.

Commands

We now briefly review the commands of AMLET. First, the command `output` expresses the name of file where the results will be saved:

```
output ``results'';
```

where `results` has to be replaced with the name that you want. If no `output` command is present in the drive file, the name will be set by default to the name of the driver file followed by `.output`.

The next two commands allow to specify an existing observations file or to generate a file that will be filled with synthetic data. Assuming that your observations file has the name `data`, you can load it into AMLET with the command

```
load ``data'';
```

On the other name, synthetic data can be obtained with the command

```
generate ``data'';
```

The structure of the data files is explained in Section 4.1.

Chapter 3

Discrete choice models

3.1 Supported models

AMLET allows the estimation of multinomial (or conditional) logit models as well as mixed logit models. When use as a standalone program AMLET automatically determines the model type from the utility description. The executable version of AMLET currently supports linear-in-parameters utilities only, i.e., for $i = 1, \ldots, I$, $j = 1, \ldots, J$,

$$U_{ij}(x_{ij}) = \sum_{k=1}^{n} \beta_{ik} x_{ijk} = \beta^T x_{ij},$$

where n is the number of dependant variables. Each component of the vector β can be fixed, constant or random, as summarized in Table 3.1.

`FIXED`	fixed coefficient
`CONSTANT`	constant (non-random) coefficient
`LOGNORMAL`	lognormally-distributed coefficient
`NORMAL`	normally-distributed coefficient
`SPLINE`	spline-distributed coefficient
`TRIANGULAR`	triangularly-distributed coefficient
`UNIFORM`	uniformly-distributed coefficient

Table 3.1: parameters types

3.2 Supported distributions

The following distributions are currently supported for the coefficient of utilities in a mixed logit model and for observations when generating synthetic data.

Lognormal lognormally distributed coefficient; the coefficient is calculated as

$$e^{\mu+\sigma X}$$

where $X \sim N(0,1)$, and μ and σ are the parameters to estimate. Therefore μ and σ are respectively the mean and the standard deviation of the logarithm of the coefficient.

Since lognormally distributed coefficients are always positive; you have to enter the negative of the explanatory variable in your dataset if necessary.

Normal normally distributed coefficient, with the mean and standard deviation being estimated.

Spline *To check.*

Triangular Triangularly distributed coefficient, with the mean and "spread" being estimated. A triangular distribution with mean b and spread a has a zero density outside $[b-a, b+a]$, while it increases linearly from $b-a$ to b and it decreases linearly from b to $b+a$.

Uniform uniformly distributed coefficient, with the mean b and "spread" a being estimated. A uniformly distributed coefficient of mean b and spread a has therefore the distribution of $U[b-a, b+a]$.

You can also use the previous distributions to generate synthetic data, as well as the following one:

Bernouilli an observation can be drawn from a Bernouilli of parameter p ($0 \leq p \leq 1.0$), that has to be specified.

The used distributions are specified in the variables `btype` and `bgentype` as set of identifiers. The truncated normal distributions (`truncated_normal` and `truncated_normal_b`) and the Bernouilli distribution can only be used in `bgentype`, to generate synthetic data.

3.3 Sampling methods

Multi-dimensional integrals are approximated by drawings points from the underlying distributions of the random parameters. Standard Monte-Carlo draws can be used as well as some quasi-Monte Carlo techniques:

- Halton sequences [3],
- Lattice nets [10],
- Modified Latin Hypercube Sampling as proposed in Hess et al. [5],
- Sobol sequences, following the recommendations of Joe and Kuo [6].

These various quasi-Monte Carlo sequences can be generated by using the library ORATIO(). The generation method can be defined by with the variable `sampling`, and is set by default to the standard Monte-Carlo approach. Possible values are summarized in Table 3.2.

Pseudo-random numbers	`monte_carlo`
Halton sequences	`halton`
Modified Latin Hypercube Sampling	`mlhs`
Rank-1 Lattice	`lattice`
Sobol sequences	`sobol`

Table 3.2: sampling methods

The number of random draws to use per individual is defined with the variable `nrep`, and is set by default to 1000. A higher value is sometimes needed, especially if the accuracy and bias on the objective are important. To use more draws, say 10000 per individual, write

```
nrep = 10000;
```

When lattices are used, AMLET uses the tabulated rank-1 lattice with the largest number of points (a prime number) not greater than `nrep`, and sets `nrep` to this number, for instance 887 for `nrep = 1000`.

The methods with a variable sample size (`mcbtrda` and `mcrtrda`) estimate the simulation error as for independent draws. With quasi-Monte Carlo draws, AMLET therefore replaces them by the same methods with a fixed sample size (`mcbtr` and `mcrtr`), with a warning. While Halton are the most popular sequences in discrete choice theory, we recommend the use of Sobol sequences of rank-1 lattices. However, the advantage of quasi-Monte Carlo sequences is not clear, as shown in [10].

3.3.1 Halton sequences

A popular alternative to pseudo-random draws in the field of mixed logit modelling is the use of Halton sequences (Halton [3]). While we strongly recommend the use of Sobol sequences instead of Halton ones, it is possible to select this approach by correspondly setting the variable `sampling`:

```
sampling = halton;
```

One major drawback of Halton sequences is the correlation between sequences associated to successive dimensions when the dimensionality is quite high (order of 10 or superior). Two techniques have been proposed to break such correlations: scrambling (Bhat [1]) and shuffling (Hess et al. [4]). Both of them can be used in AMLET. It is also possible to randomize the sequences by randomly shifting the sequences, for each dimension, as proposed by Bhat [1]. While all these techniques are not strictly speaking randomizations methods, all of them can be set using the variable `randomization`, whose default value is `none`, as summarized in Table 3.3.

`none`	no randomization
`scrambling`	scramble the Halton sequences
`shifting`	randomly shift the Halton sequences
`shifting_scrambling`	randomly shift and scramble the Halton sequences
`shuffling`	randomly shuffle the Halton sequences
`shifting_shuffling`	randomly shift and shuffle the Halton sequences

Table 3.3: Randomization strategies for Halton sequences

In AMLET, all individuals use the same Halton points, each with its own random shift, so that `none` and `shifting` give the same draws. `scrambling` applies the Braaten-Weller permutations (up to dimension 16), and `shuffling` shuffles the order of the points of each individual, dimension by dimension. Up to the 2026 rebuild, AMLET ignored the variable `randomization`; it still does with `legacy_rng = true`.

3.3.2 Sobol sequences

3.3.3 Rank-1 lattices

3.4 Pseudo-random numbers generators

Each method requires the use of a uniform random numbers generator, whose quality is important to ensure quality of the results. Even if a quasi-Monte Carlo is used, the randomization part also involves the use of a pseudo-random numbers generator. The choice of a good one is still a tricky question (see for instance the relevant discussion in L'Ecuyer [7] and McCullough [9]). Unlike many econometric packages, as LIMDEP, AMLET allows the user to choose between several random number generators, defined in the random numbers generator library. Three generators are currently available: the standard minimal one, proposed by Park and Miller [11], the MRG32K3a generator, due to L'Ecuyer, and the generator MT19937 designed by Matsumoto and Nishimura [8]. To date no significant differences have been observed when using one technique instead of another one, while it is known that the sandard minimal generator has severe statistical deficiencies. By default we use the MRG32K3a generator that benefits from strong theoretical properties and is well tested, and our implementation allows to consider substreams. The choice of the random number generator can be defined with the variable `rangen`. Possible values are summarized in Table 3.4.

Standard minimal	`standard`
L'Ecuyer's generator	`ecuyer`
MRG32K3a (default)	`mrg32k3a`
MT19937	`mt19937`

Table 3.4: random number generators

Up to the 2026 rebuild of AMLET 0.13.1, the MRG32K3a generator of ORATIO 0.7.5 differed from L'Ecuyer's: its first component used x_{n-1} instead of x_{n-2}, and the jumps to the next stream or substream were not reduced modulo m. It now produces L'Ecuyer's MRG32K3a sequences, streams and substreams, so that simulated results differ from those of AMLET 0.13.1. To reproduce them, set

```
legacy_rng = true;
```

in the driver file. The legacy generator is not MRG32K3a and its statistical properties are unknown: use it only to reproduce earlier results.

Each random generator produces a sequence of points that mimics draws from an uniform distribution on $(0, 1)$.. These sequences are however deterministic due

to their numerical nature, so they can be reproduced when some initial conditions are fixed. Typically, they can be expressed by a single strictly positive integer, known as the *seed*. This value can be defined in the driver file by means of the variable `seed1`, for example:

```
seed1 = 12345;
```

Most of the time, the seed can be recovered at any point during the random draws generation process, allowing the replication of a sequence starting at any draw of the initial sequence. This is useful for instance when dealing with a newly generated synthetic population, where the same random generator is used for creating the population and the random draws. In this case, the output file will contain both the initial seed and the seed after the population generation. Note however that the MT19937 cannot be restarted with a single seed, except the initial one.

The default value for `seed1` is 12345. If a seed value of 0 is used, AMLET will determine a seed based on the computer clock, that will be used to initiate the pseudo-random draws sequence.

For more information, we refer the reader to the documentation accompying the ORATIO library.

3.5 Results validation

The source file `validation.c`, associated to the header file `validation.h`, contains basic validation routines concerned with validation of the estimation results, on a statistical point of view. The validation is currently quite simple, as it simply repeats `nsim` times the simulation of the objective function, using a different set of random realizations for each simulation. The mean, standard deviation, and a confidence interval at 0.9 for the objective function are given on output. In order to activate the validation function, you need to set the variable `validation` to `true` in the driver file:

```
validation = true;
```

Chapter 4

Data files

4.1 Data files

Every model needs data in order to proceed to its calibration, so the possibilty to enter data in a convenient format is important. AMLET unfortunately currently supports basic formats only, even if development is planned on this issue. The supported formats reflect the original purpose of the package, which was only testing a new optimisation method.

4.1.1 GAUSS-like formats

Preliminary AMLET design mimics Train's GAUSS codes for mixed logit estimation (cross-sectional and panel versions). These routines are available at the address `http://elsa.berkeley.edu/~train/software.html`. We also refer the reader to Revelt and Train [12], and Train [13], for more details. AMLET has currently no capabilities to construct new data from a preexisting dataset, for instance dummy observations for alternatives specific constants, so please be sure that your data are completely specified before using AMLET.

The format of the data file is specified by assign to the variable `format` of the driver file the value `Train96` of `Train99`, the number being a reference to Train's code release year. For instance, the following line

```
format = Train96;
```

indicated that data are stored in `Train96` format, which is also taken as default if no format is specified in the driver file.

```
   0    1    0    0
   0    0    1    0
   0    0    0    1
 1.6 -2.0  3.2  4.1
   0  2.5  1.0  0.8
-1.2 -1.5 -0.4 -1.6
   0    1    0    0
   0    1    0    0
   0    0    1    0
   0    0    0    1
 2.4 -3.0  2.3  3.0
   0  1.7  1.2  1.5
-1.6 -2.0 -1.2 -2.4
   0    0    0    1
```

Figure 4.1: Train96 Format

Train96 format

This format is primarily designed for cross-sectional data, as illustrated in Figure 4.1.1. In this figure, each indiviual is facing four alternatives, corresponding four columns. The six first rows of each record (containing seven rows) corresponds to the independent variables. Since each individual is assumed to deliver one observation, this format cannot be used for panel data. An additional row is devoted to the dependent (decision) variable, with one on the column corresponding to the chosen alternatives, and 0 elsewhere. The line position in each record must be indicated with the variable `iddep` in the driver file. For Figure 4.1.1, we would have

```
iddep = 7;
```

By default, all alternatives are available to each individual. If you want to specify alternative availabilities, you have to set the censor variable to 1 in the driver file:

```
censor = 1;
```

The variable `idcensor` then represents the line describing alternative availabilities. The corresponding line in the driver file is simply a 0-1 line, with one on available alternatives, and 0 elsewhere.

Train99 format

This format is used for panel data. It adds to the base name the suffixes `_x`, `_y` and `_times`.

Chapter 5

Output files

The estimation process would be useless if no exploitable results were delivered to the user. The software therefore delivers various files at the of the optimisation process. Their content if meaning is described below

5.1 Results file

5.1.1 Definition

The result of the estimation process is written in the file defined by the command `output` inside the driver file (see Section 2.2). If no name is precised, the default name is the name of the driver file followed by `.output`.

The main characteristics of the problem are first summarized. It is always a good idea to name the problem under consideration, by setting the variable `problem` in the driver file, for instance

```
Problem = ``test'';
```

5.1.2 Content

t-statistics

The t-statistics can be computed in various ways, depending on the options present in the driver file. Each method involves the computation of the information matrix. However, due to the sampling errors, robust t-statistics are not necessarily better than those obtained with the outer approximation. The sampling errors are indeed amplified when computing second-order derivatives.

5.2 Log file

AMLET generates a log file during its execution. It will contain detailed information on the process, from initialisation tasks to a complete recording of the optimisation iterates. The default name of the log file is `amlet.log`, but this name can be change with the `-o` and `--option` options at the start of the software (see Chapter 2).

Appendix A

Example of driver file

We illustrate the behaviour of AMLET on a 1987 dataset made of 210 non-business trips between Sydney, Canberra and Melbourne. In this dataset, each traveller chooses a mode from four available alternatives (plane, car, bus and train). This dataset is described in more details in Greene [2] (Example 19.18), and is available at the address
http://www.ats.ucla/stat/limdep/how_to_run_statistical_analysis_.htm.
A formatted version for AMLET is present inside the directory `testing` of the AMLET source code, as the file `model_australia`.

A.1 Multinomial logit

A.1.1 Driver file

```
# Problem name;
PROBLEM = ``Australia problem'';

# name of the output file
output "results_mnl";

# number of observations
nobs = 210;
np = 210;

# number of aternatives
nalt = 4;

# number of variables
```

```
nvar = 7;

# number of variable that is the dependant variable (choice)
iddep = 7;

# 1 if all people do not face nalt alternatives, else 0
censor = 0;

# maximum number of iterations in the maximization
niter = 150;

# tolerance for convergence
eps = 1e-6;

# type of parameters
btype = { CONSTANT, CONSTANT, CONSTANT,
          CONSTANT, CONSTANT, CONSTANT };
# starting point
b = { 0, 0, 0, 0, 0, 0 };

# data file
load "model_australia";

method = MCBTR;
hessian_update = BFGS;

iapprox = false;
robust = false;
```

A.2 Mixed logit

A.2.1 Driver file

```
# Problem name;
PROBLEM = "Australia problem";

# name of the output file
output "results_mmnl";

# number of observations
nobs = 210;
np = 210;

# number of aternatives
```

```
nalt = 4;

# number of variables
nvar = 7;

# number of variable that is the dependant variable (choice)
iddep = 7;

# 1 if all people do not face nalt alternatives, else 0
censor = 0;

# maximum number of iterations in the maximization
niter = 150;

# tolerance for convergence
eps = 1e-6;

# type of parameters
btype = { CONSTANT, CONSTANT, CONSTANT,
          CONSTANT, NORMAL, CONSTANT };
# starting point
b = { 0, 0, 0, 0, 0, 0, 0 };

# data file
load "model_australia";

method = MCBTRDA;
hessian_update = BFGS;

iapprox = false;
robust = true;
```

Appendix B

Numerical issues

B.1 Choice probability computation

We start from the logit expression

$$P_{ij} = \frac{e^{U_\ell}}{\sum_{k \in \mathcal{A}_i} e^{U_k}}. \tag{B.1}$$

If some of the utilities are too large, the computation of (B.1) can face some overflow. A simple way to avoid this problem is to substract some quantity α since

$$\frac{e^{U_\ell - \alpha}}{\sum_{k \in \mathcal{A}_i} e^{U_k - \alpha}} = \frac{e^{U_\ell}}{\sum_{k \in \mathcal{A}_i} e^{U_k}}.$$

Moreover, is all utilities are too small, they could be evaluated to 0, leading to the ratio $0/0$ in (B.1). A simple way to circumvent this issue is to normalize with respect to the highest utility, i.e. take

$$\alpha = \max\{U_k,\ k \in \mathcal{A}_i\} - \beta.$$

We want to keep each term e^{U_k}, $k \in \mathcal{A}_i$, in the same range, so β has to be kept low. Since $de^x/dx = e^x$, the precise value of β does not significantly affect small utilities, so a simple, while practical, choice is to set β to 0. As a consequence, $e^{U_k - \alpha} \in (0, 1]$ for all $k \in \mathcal{A}_i$.

B.2 Data file problems

Appendix C

Legal aspects

C.1 Licenses and acknowledgements

All of the code is placed under the MIT License, except the files whose header states another license: some files are placed under a BSD license, and the files whose copyright notice names other authors besides Fabian Bastin remain under the OSL v2.1. These licenses are reproduced below.

This product includes software developed by the NetBSD Foundation, Inc. and its contributors.

C.1.1 MIT License

Copyright (c) 2002-2026 Fabian Bastin

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

C.1.2 Open Software License v 2.1

This Open Software License (the "License") applies to any original work of authorship (the "Original Work") whose owner (the "Licensor") has placed the following notice immediately following the copyright notice for the Original Work:

Licensed under the Open Software License version 2.1

1) Grant of Copyright License. Licensor hereby grants You a world-wide, royalty-free, non-exclusive, perpetual, sublicenseable license to do the following:

   a) to reproduce the Original Work in copies;

   b) to prepare derivative works ("Derivative Works") based upon the Original Work;

   c) to distribute copies of the Original Work and Derivative Works to the public, with the proviso that copies of Original Work or Derivative Works that You distribute shall be licensed under the Open Software License;

   d) to perform the Original Work publicly; and

   e) to display the Original Work publicly.

2) Grant of Patent License. Licensor hereby grants You a world-wide, royalty-free, non-exclusive, perpetual, sublicenseable license, under patent claims owned or controlled by the Licensor that are embodied in the Original Work as furnished by the Licensor, to make, use, sell and offer for sale the Original Work and Derivative Works.

3) Grant of Source Code License. The term "Source Code" means the preferred form of the Original Work for making modifications to it and all available documentation describing how to modify the Original Work. Licensor hereby agrees to provide a machine-readable copy of the Source Code of the Original Work along with each copy of the Original Work that Licensor distributes. Licensor reserves the right to satisfy this obligation by placing a machine-readable copy of the Source Code in an information repository reasonably calculated to permit inexpensive and convenient access by You for as long as Licensor continues to distribute the Original Work, and by publishing the address of that information repository in a notice immediately following the copyright notice that applies to the Original Work.

4) Exclusions From License Grant. Neither the names of Licensor, nor the names of any contributors to the Original Work, nor any of their trademarks or service marks, may be used to endorse or promote products derived from this Original Work without express prior written permission of the Licensor. Nothing in this License shall be deemed to grant any rights to trademarks, copyrights, patents, trade secrets or any other intellectual property of Licensor except as expressly stated herein. No patent license is granted to make, use, sell or offer to sell embodiments of any patent claims other than the licensed claims defined in Section 2. No right is granted to the trademarks of Licensor even if such marks are included in the Original Work. Nothing in this License shall be interpreted to prohibit Licensor from licensing under different terms from this License any Original Work that Licensor otherwise would have a right to license.

5) External Deployment. The term "External Deployment" means the use or distribution of the Original Work or Derivative Works in any way such that the Original Work or Derivative Works may be used by anyone other than You, whether the Original Work or Derivative Works are distributed to those persons or made available as an application intended for use over a computer network. As an express condition for the grants of license hereunder, You agree that any External Deployment by You of a Derivative Work shall be deemed a distribution and shall be licensed to all under the terms of this License, as prescribed in section 1(c) herein.

6) Attribution Rights. You must retain, in the Source Code of any Derivative Works that You create, all copyright, patent or trademark notices from the Source Code of the Original Work, as well as any notices of licensing and any descriptive text identified therein as an "Attribution Notice." You must cause the Source Code for any Derivative Works that You create to carry a prominent Attribution Notice reasonably calculated to inform recipients that You have modified the Original Work.

7) Warranty of Provenance and Disclaimer of Warranty. Licensor warrants that the copyright in and to the Original Work and the patent rights granted herein by Licensor are owned by the Licensor or are sublicensed to You under the terms of this License with the permission of the contributor(s) of those copyrights and patent rights. Except as expressly stated in the immediately proceeding sentence, the Original Work is provided under this License on an "AS IS" BASIS and WITHOUT WARRANTY, either express or implied, including, without limitation, the warranties of NON-INFRINGEMENT, MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY OF THE ORIGINAL WORK IS WITH YOU. This DISCLAIMER OF WARRANTY constitutes an essential part of this License. No license to Original Work is granted hereunder except under this disclaimer.

8) Limitation of Liability. Under no circumstances and under no legal theory, whether in tort (including negligence), contract, or otherwise, shall the Licensor be liable to any person for any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or the use of the Original Work including, without limitation, damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses. This limitation of liability shall not apply to liability for death or personal injury resulting from Licensor's negligence to the extent applicable law prohibits such limitation. Some jurisdictions do not allow the exclusion or limitation of incidental or consequential damages, so this exclusion and limitation may not apply to You.

9) Acceptance and Termination. If You distribute copies of the Original Work or a Derivative Work, You must make a reasonable effort under the circumstances to obtain the express assent of recipients to the terms of this License. Nothing else but this License (or another written agreement between Licensor and You) grants You permission to create Derivative Works based upon the Original Work or to exercise any of the rights granted in Section 1 herein, and any attempt to do so except under the terms of this License (or another written agreement between Licensor and You) is expressly prohibited by U.S. copyright law, the equivalent laws of other countries, and by international treaty.

Therefore, by exercising any of the rights granted to You in Section 1 herein, You indicate Your acceptance of this License and all of its terms and conditions. This License shall terminate immediately and you may no longer exercise any of the rights granted to You by this License upon Your failure to honor the proviso in Section 1(c) herein.

10) Termination for Patent Action. This License shall terminate automatically and You may no longer exercise any of the rights granted to You by this License as of the date You commence an action, including a cross-claim or counterclaim, against Licensor or any licensee alleging that the Original Work infringes a patent. This termination provision shall not apply for an action alleging patent infringement by combinations of the Original Work with other software or hardware.

11) Jurisdiction, Venue and Governing Law. Any action or suit relating to this License may be brought only in the courts of a jurisdiction wherein the Licensor resides or in which Licensor conducts its primary business, and under the laws of that jurisdiction excluding its conflict-of-law provisions. The application of the United Nations Convention on Contracts for the International Sale of Goods is expressly excluded. Any use of the Original Work outside the scope of this License or after its termination shall be subject to the requirements and penalties of the U.S. Copyright Act, 17 U.S.C. Â§101 et seq., the equivalent laws of other countries, and international treaty. This section shall survive the termination of this License.

12) Attorneys Fees. In any action to enforce the terms of this License or seeking damages relating thereto, the prevailing party shall be entitled to recover its costs and expenses, including, without limitation, reasonable attorneys' fees and costs incurred in connection with such action, including any appeal of such action. This section shall survive the termination of this License.

13) Miscellaneous. This License represents the complete agreement concerning the subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable.

14) Definition of "You" in This License. "You" throughout this License, whether in upper or lower case, means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, "You" includes any entity that controls, is controlled by, or is under common control with you. For purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

15) Right to Use. You may use the Original Work in all ways not otherwise restricted or conditioned by this License or by law, and Licensor promises not to interfere with or be responsible for such uses by You.

This license is Copyright (C) 2003-2004 Lawrence E. Rosen. All rights reserved. Permission is hereby granted to copy and distribute this license without modification. This license may not be modified without the express written permission of its copyright owner.

C.1.3 BSD License

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The names of its contributors may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Bibliography

[1] Chandra R. Bhat. Simulation estimation of mixed discrete choice models using randomized and scrambled Halton sequences. *Transportation Research B*, 37(3):837–855, 2003.

[2] William H. Greene. *Econometric Analyis*. Prentice Hall, Upper Saddle River, USA, fifth edition, 2003.

[3] John H. Halton. On the efficiency of certain quasi-random sequences of points in evaluating multi-dimensional integrals. *Numerische Mathematik*, 2:84–90, 1960.

[4] Stéphane Hess, John Polak, and Andrew Daly. On the performance of shuffled Halton sequences in the estimation of discrete choice models. In *Proceedings of European Transport Conference*, Strasbourg, France, 2003. PTRC.

[5] Stéphane Hess, Kenneth Train, and John Polak. On the use of a modified latin hypercube sampling (mlhs) approach in the estimation of a mixed logit model for vehicle choice. *Transportation Research B*, Forthcoming.

[6] Stephen Joe and France Y. Kuo. Remark on algorithm 659: Implementing sobol's quasirandom sequence generator. *ACM Transactions on Mathematical Software (TOMS)*, 29(1):49–57, 2003.

[7] Pierre L'Ecuyer. Uniform random numbers generators: a review. In S. Andradóttir and K. J. Healy and, editors, *Proceedings of the 29th conference on Winter simulation*, pages 127–134, New York, USA, 1997. ACM Press.

[8] Makoto Matsumoto and Takuji Nishimura. Mersenne twister: A 623-dimensionally equidistributed uniform pseudorandom number generator. *ACM Trans. on Modeling and Computer Simulation*, 8(1):3–30, 1998.

[9] B. D. McCullough. A review of TESTU01. *Journal of Applied Econometrics*, 21:677–682, 2006.

[10] David Munger, Pierre L'Ecuyer, Fabian Bastin, Cinzia Cirillo, and Bruno Tuffin. Estimation of the mixed logit likelihood function by randomized quasi-monte carlo. *Transportation Research Part B*, 46(2):305–320, 2012.

[11] Stephen K. Park and Keith W. Miller. Random number generators: good ones are hard to find. *Communications of the ACM*, 31(10):1192–1201, 1988.

[12] David Revelt and Kenneth Train. Mixed logit with repeated choices of appliance efficiency levels. *Review of Economics and Statistics*, 80(4):647–657, 1998.

[13] Kenneth Train. Halton sequences for mixed logit. Working paper No. E00-278, Department of Economics, University of California, Berkeley, 1999.