

IDEALISATIONS

So far we have only considered search problems in environments that are:


- ▶ **Single-agent.** There is a single agent acting, the one we control.
- ▶ **Static.** When the agent is not acting, the world doesn't change.
- ▶ **Deterministic.** Every action has a unique outcome.
- ▶ **Fully observable.** The full state description is accessible to the agent.

Problem solving in the real world rarely satisfies these assumptions.

Today, we will drop the assumption of **determinism** and **full observability**.

RECAP: VACUUM WORLD

Vacuum World consists of two locations, each of which may or may not contain dirt and the vacuum is in one of the locations.









RECAP: VACUUM WORLD

States space consists of each possible configuration (2×2^2 possible states).

- ▶ s_0 : Initial state
- ▶ $\text{ACTIONS}(s)$: for each state three possible actions: L, R, S.
- ▶ $\text{RESULTS}(s, a)$: applying a in s leads to a state s' .
- ▶ $\text{GOAL-TEST}(s)$: *are all squares clean?*
- ▶ $\text{STEP-COST}(s, a)$: each step costs 1.

RECAP: VACUUM WORLD


POSSIBLE STATES



RECAP: VACUUM WORLD

TRANSITION MODEL AND SIMPLE SOLUTION

The transitions in the Vacuum World can be represented as a graph.



OUTLINE

NON-DETERMINISM

PARTIAL OBSERVABILITY

THE ERRATIC VACUUM WORLD

Let us consider an erratic vacuum:

- ▶ When applied to a dirty square it cleans the square and sometimes cleans up dirt in an adjacent square, too.
- ▶ When applied to a clean square it sometimes deposits dirt in that square.

ERRATIC VACUUM WORLD

PROBLEM DESCRIPTION

- ▶ s_0 : Initial state
- ▶ $ACTIONS(s)$: for each state three possible actions: L, R, S.
- ▶ $RESULTS(s, a)$: applying a in s leads to **a set of states** S' .
- ▶ $GOAL-TEST(s)$: *are all squares clean?*
- ▶ $STEP-COST(s, a)$: each step costs 1.

ERRATIC VACUUM WORLD

PROBLEM DESCRIPTION

- ▶ s_0 : Initial state
- ▶ $ACTIONS(s)$: for each state three possible actions: L, R, S.
- ▶ $RESULTS(s, a)$: applying a in s leads to **a set of states** S' .
- ▶ $GOAL-TEST(s)$: *are all squares clean?*
- ▶ $STEP-COST(s, a)$: each step costs 1.

Q: What is a solution to the erratic vacuum problem starting in the state 1?

REPRESENTING NONDETERMINISM

Search problems with nondeterminism: $\text{RESULTS}(s, a)$ returns a *set* of states.

Example. $\text{RESULTS}(1, \textit{Suck}) = \{5, 7\}$.

REPRESENTING NONDETERMINISM

Search problems with nondeterminism: $\text{RESULTS}(s, a)$ returns a *set* of states.

Example. $\text{RESULTS}((d, d, 1), \text{Suck}) = \{(c, d, 1), (c, c, 1)\}$.

REPRESENTING NONDETERMINISM


Search problems with nondeterminism: $\text{RESULTS}(s, a)$ returns a *set* of states.

Example. $\text{RESULTS}(1, \textit{Suck}) = \{5, 7\}$.

REPRESENTING NONDETERMINISM

Search problems with nondeterminism: $\text{RESULTS}(s, a)$ returns a *set* of states.


Example. $\text{RESULTS}(1, \text{Suck}) = \{5, 7\}$.



REPRESENTING NONDETERMINISM

Search problems with nondeterminism: $\text{RESULTS}(s, a)$ returns a *set* of states.

Example. $\text{RESULTS}(1, \text{Suck}) = \{5, 7\}$.




Non-deterministic action is represented with an **AND node**:
outgoing edges representing all outcomes **linked by an arc**.

REPRESENTING NONDETERMINISM

Search problems with nondeterminism: $\text{RESULTS}(s, a)$ returns a *set* of states.

Example. $\text{RESULTS}(1, \text{Suck}) = \{5, 7\}$.



Non-deterministic action is represented with an **AND node**: outgoing edges representing all outcomes **linked by an arc**.

OR nodes are as usual, with deterministic ACTIONS.

AND-OR SEARCH TREES


AND-OR tree is a tree with levels of AND and OR nodes.

- ▶ Root is OR node (agent choice).
- ▶ OR nodes have outgoing edges for all applicable actions.
- ▶ AND nodes have outgoing edges for all outcomes of action.

AND-OR SEARCH TREES

AND-OR tree is a tree with levels of AND and OR nodes.

- ▶ Root is OR node (agent choice).
- ▶ OR nodes have outgoing edges for all applicable actions.
- ▶ AND nodes have outgoing edges for all outcomes of action.



SOLUTION TO A NON-DETERMINISTIC SEARCH PROBLEM


A **solution** to a nondeterministic search problem is a subtree T' of T s.t.:

1. The root node of T is in T' .
2. Every leaf of T' is a goal state.
3. Every OR node of T' has exactly one outgoing edge (agent choice).
4. Every AND node of T' has the same outgoing edges as in T (nature choice).

SOLUTION TO A NON-DETERMINISTIC SEARCH PROBLEM

A **solution** to a nondeterministic search problem is a subtree T' of T s.t.:

1. The root node of T is in T' .
2. Every leaf of T' is a goal state.
3. Every OR node of T' has exactly one outgoing edge (agent choice).
4. Every AND node of T' has the same outgoing edges as in T (nature choice).



SOLUTIONS AS CONDITIONAL PLANS AND POLICIES

Deterministic search problems: Solution is a path in state space
it can be turned into a sequence of *ACTIONS* (sequential plan).

SOLUTIONS AS CONDITIONAL PLANS AND POLICIES

Deterministic search problems: Solution is a path in state space
it can be turned into a sequence of `ACTIONS` (sequential plan).

Non-deterministic search problems: Solution is a subtree of state space,
it can be turned into a conditional plan (contingency plan).

SOLUTIONS AS CONDITIONAL PLANS AND POLICIES

Deterministic search problems: Solution is a path in state space
it can be turned into a sequence of ACTIONS (sequential plan).

Non-deterministic search problems: Solution is a subtree of state space,
it can be turned into a conditional plan (contingency plan).


Language of **conditional plans**:

$$\pi ::= \varepsilon \mid a \mid \text{if } s \text{ then } \pi_1 \text{ else } \pi_2 \mid \pi_1; \pi_2$$

where ε is the empty plan, $a \in \text{ACTIONS}$ and s is a state.


The construct $\pi_1; \pi_2$ denotes sequential composition: first execute π_1 , then π_2 .

SOLUTIONS AS CONDITIONAL PLANS AND POLICIES



T' as a **conditional plan**: $\pi = \text{Suck}; \text{if } s_5 \text{ then } (\text{Right}; \text{Suck}).$

SOLUTIONS AS CONDITIONAL PLANS AND POLICIES



T' as a **conditional plan**: $\pi = \text{Suck}; \text{if } s_5 \text{ then } (\text{Right}; \text{Suck})$.

T' as a **policy** (a mapping from states to ACTIONS):

Policy Π : $\Pi(s_1) = \text{Suck}$, $\Pi(s_5) = \text{Right}$, $\Pi(s_6) = \text{Suck}$.

AND-OR GRAPH SEARCH

function AND-OR-GRAPH-SEARCH(*problem*) returns a conditional plan, or failure
OR-SEARCH(*init state of problem*, []) // *problem* is implicit parameter

function OR-SEARCH(*state*, *path*)
 if *state* is a goal **then return** ε // if in goal state, empty plan suffices
 if *state* is on *path* **then return** failure // fail if looping
 for each *action* applicable in *state* **do** // recursively search for plan
 plan \leftarrow AND-SEARCH(RESULTS(*state*, *action*), [*state* | *path*])
 if *plan* \neq failure **then return** *action*; *plan* // append plan to action
 return failure // if all recursive searches for a plan fails

function AND-SEARCH(*states*, *path*)
 for each s_i in *states* **do** // recursively find plans for each outcome state
 plan_i \leftarrow OR-SEARCH(s_i , *path*)
 if *plan_i* = failure **then return** failure
 return **if** s_1 **then** *plan₁* **else if** s_2 **then** *plan₂* **else** \dots **if** s_{n-1} **then** *plan_{n-1}* **else**
 plan_n // if $n = 1$ then the returned plan is just *plan₁*

AND-OR GRAPH SEARCH

function AND-OR-GRAPH-SEARCH(*problem*) returns a conditional plan, or failure
OR-SEARCH(*init state of problem*, []) // *problem* is implicit parameter

function OR-SEARCH(*state*, *path*)
 if *state* is a goal **then return** ε // if in goal state, empty plan suffices
 if *state* is on *path* **then return failure** // fail if looping
 for each *action* applicable in *state* **do** // recursively search for plan
 plan \leftarrow AND-SEARCH(RESULTS(*state*, *action*), [*state* | *path*])
 if *plan* \neq failure **then return** *action*; *plan* // append plan to action
 return failure // if all recursive searches for a plan fails

function AND-SEARCH(*states*, *path*)
 for each s_i in *states* **do** // recursively find plans for each outcome state
 plan_i \leftarrow OR-SEARCH(s_i , *path*)
 if *plan_i* = failure **then return failure**
 return **if** s_1 **then** *plan₁* **else if** s_2 **then** *plan₂* **else** \dots **if** s_{n-1} **then** *plan_{n-1}* **else**
 plan_n // if $n = 1$ then the returned plan is just *plan₁*

Q: Which algorithm do we get when all ACTIONS are deterministic?

THE SLIPPERY VACUUM WORLD


Let us consider a slipping vacuum:

- ▶ everything normal, except that
- ▶ movement action sometimes fails.

THE SLIPPERY VACUUM WORLD

Let us consider a slipping vacuum:

- ▶ everything normal, except that
- ▶ movement action sometimes fails.



ACYCLIC AND CYCLIC SOLUTIONS

Acyclic solutions are not always possible.

ACYCLIC AND CYCLIC SOLUTIONS

Acyclic solutions are not always possible.

Cyclic solutions: Subtrees T' where every leaf is either a goal or a loop node.

Cyclic solutions guarantee reaching the goal, but only when assuming **fairness**:
Every possible outcome of an action will eventually happen.

ACYCLIC AND CYCLIC SOLUTIONS

Acyclic solutions are not always possible.

Cyclic solutions: Subtrees T' where every leaf is either a goal or a loop node.

Cyclic solutions guarantee reaching the goal, but only when assuming **fairness**:
Every possible outcome of an action will eventually happen.

We need a language of conditional plans with loops.

$$\pi ::= \varepsilon \mid a \mid \text{if } s \text{ then } \pi_1 \text{ else } \pi_2 \mid \pi_1; \pi_2 \mid \text{while } cond \text{ do } \pi_1$$

where *cond* is some logical condition.

ACYCLIC AND CYCLIC SOLUTIONS

Acyclic solutions are not always possible.

Cyclic solutions: Subtrees T' where every leaf is either a goal or a loop node.

Cyclic solutions guarantee reaching the goal, but only when assuming **fairness**:
Every possible outcome of an action will eventually happen.

We need a language of conditional plans with loops.

$$\pi ::= \varepsilon \mid a \mid \text{if } s \text{ then } \pi_1 \text{ else } \pi_2 \mid \pi_1; \pi_2 \mid \text{while } \textit{cond} \text{ do } \pi_1$$

where *cond* is some logical condition.

The slipping vacuum: *Suck ; Right; while not in 6 do Right; Suck*

OUTLINE

NON-DETERMINISM

PARTIAL OBSERVABILITY

LIMITING OBSERVABILITY

We are now back to deterministic domains.

LIMITING OBSERVABILITY

We are now back to deterministic domains.

We considered searching under **full observability**:
the full state description is observable by the agent.

LIMITING OBSERVABILITY

We are now back to deterministic domains.

We considered searching under **full observability**:
the full state description is observable by the agent.

Under **partial observability** the full state might not be observable:
e.g. vacuum cleaning robot not knowing which squares are clean.

LIMITING OBSERVABILITY

We are now back to deterministic domains.

We considered searching under **full observability**:
the full state description is observable by the agent.

Under **partial observability** the full state might not be observable:
e.g. vacuum cleaning robot not knowing which squares are clean.

Null observability: is the case when *nothing* can be observed about the states.
Search problems under null observability are called
conformant problems or **sensorless problems**.

LIMITING OBSERVABILITY

We are now back to deterministic domains.

We considered searching under **full observability**:
the full state description is observable by the agent.

Under **partial observability** the full state might not be observable:
e.g. vacuum cleaning robot not knowing which squares are clean.

Null observability: is the case when *nothing* can be observed about the states.
Search problems under null observability are called
conformant problems or **sensorless problems**.

Example. Consider the vacuum where it is not known which squares are clean,
and the robot doesn't have any sensors.

Q: Can the problem still be solved, and if so, what is the solution?

BELIEF STATES

Belief state: A set of (physical) states.

Contains the states considered possible by an agent in a given state.

BELIEF STATES

Belief state: A set of (physical) states.

Contains the states considered possible by an agent in a given state.

We generally use s for (physical) states and b for belief states.

BELIEF STATES

Belief state: A set of (physical) states.

Contains the states considered possible by an agent in a given state.

We generally use s for (physical) states and b for belief states.

If a problem has n states, there can be up to 2^n belief states:
an exponential blow-up in the worst case.

BELIEF STATES

Belief state: A set of (physical) states.

Contains the states considered possible by an agent in a given state.

We generally use s for (physical) states and b for belief states.

If a problem has n states, there can be up to 2^n belief states:
an exponential blow-up in the worst case.

Conformant problems can be solved by
any of the standard graph and tree search algorithms (e.g. A^*),
just using belief states instead of physical states.


BELIEF STATES

Formally, given a fully observable problem
(s_0 , ACTIONS, RESULTS, GOAL-TEST),
we can define a corresponding conformant problem
(b_0 , ACTIONS', RESULTS', GOAL-TEST')
with initial belief state b_0 by:


$$\begin{aligned}\text{ACTIONS}'(b) &= \bigcup_{s \in b} \text{ACTIONS}(s) \\ \text{RESULTS}'(b, a) &= \bigcup_{s \in b} \text{RESULTS}(s, a) \\ \text{GOAL-TEST}(b) &= \bigwedge_{s \in b} \text{GOAL-TEST}(s)\end{aligned}$$

CONFORMANT SEARCH

DETERMINISTIC SENSORLESS VACUUM




SEARCHING WITH OBSERVATIONS (SENSING)



Assume the robot doesn't initially know which squares are dirty, but it has a *Sense* action to check whether the current square is clean or dirty.

Suppose the number of *Suck* actions have to be minimised.

SEARCHING WITH OBSERVATIONS (SENSING)




Assume the robot doesn't initially know which squares are dirty, but it has a *Sense* action to check whether the current square is clean or dirty.

Suppose the number of *Suck* actions have to be minimised.

Q1: What would then be a solution to the cleaning problem?

SEARCHING WITH OBSERVATIONS (SENSING)




Assume the robot doesn't initially know which squares are dirty, but it has a *Sense* action to check whether the current square is clean or dirty.

Suppose the number of *Suck* actions have to be minimised.

Q1: What would then be a solution to the cleaning problem?

Q2: Can we use the GRAPH-SEARCH to solve problems with partial observability and sensing?

SEARCHING WITH OBSERVATIONS (SENSING)



Assume the robot doesn't initially know which squares are dirty, but it has a *Sense* action to check whether the current square is clean or dirty.

Suppose the number of *Suck* actions have to be minimised.

Q1: What would then be a solution to the cleaning problem?

Q2: Can we use the GRAPH-SEARCH to solve problems with partial observability and sensing?

Q3: And what about AND-OR-GRAPH-SEARCH?

PERCEPTS AS A MODEL FOR SENSING

A general treatment of observations/sensing under partial observability:
including a new function in the problem description: $\text{PERCEPT}(s)$
which codes the observation made by the agent in state s .

PERCEPTS AS A MODEL FOR SENSING

A general treatment of observations/sensing under partial observability:
including a new function in the problem description: $\text{PERCEPT}(s)$
which codes the observation made by the agent in state s .

Example: $\text{PERCEPT}(s) = \textit{dirty/clean}$.


PERCEPTS AS A MODEL FOR SENSING

A general treatment of observations/sensing under partial observability:
including a new function in the problem description: $\text{PERCEPT}(s)$
which codes the observation made by the agent in state s .

Example: $\text{PERCEPT}(s) = \text{dirty/clean}$.

Full observability corresponds to $\text{PERCEPT}(s) = \{s\}$.

Null observability corresponds to $\text{PERCEPT}(s) = \emptyset$.



THE NEW RESULTS FUNCTION

We define the following new functions:

1. POSSIBLE-PERCEPTS takes a belief state b and returns all the observations that are possible to receive in that belief state:

$$\text{POSSIBLE-PERCEPTS}(b) = \{\text{PERCEPT}(s) \mid s \in b\}.$$

2. UPDATE takes a belief state b and an observation o and filters away the states that are not consistent with the observation:

$$\text{UPDATE}(b, o) = \{s \in b \mid o = \text{PERCEPT}(s)\}.$$


So $\text{UPDATE}(b, o)$ is the updated belief an agent has after having received observation o in belief state b .

New RESULTS function on belief states that takes observations into account:


$$\text{RESULTS}'(b, a) = \left\{ \text{UPDATE}\left(\bigcup_{s \in b} \text{RESULTS}(s, a), o\right) \mid o \in \text{POSSIBLE-PERCEPTS}\left(\bigcup_{s \in b} \text{RESULTS}(s, a)\right) \right\}$$

Note that $\text{RESULTS}(b, a)$ is a set of belief states, that is, a set of sets of states.

FROM FULL TO PARTIAL OBSERVABILITY TO MULTIPLE AGENTS



FROM FULL TO PARTIAL OBSERVABILITY TO MULTIPLE AGENTS



Such models are one of the main topics of the course 02287.

THE END OF LECTURE 4