

# Functional Programming in Typed Racket

Florian BIERMANN

fbie@itu.dk

IT University of Copenhagen & UCAS

2016-05-26



IT University  
of Copenhagen

# Who am I?

Just call me Florian!

# Who am I?

Just call me Florian!

- ▶ I am from Germany and live in Denmark.

# Who am I?

Just call me Florian!

- ▶ I am from Germany and live in Denmark.
- ▶ Second year PhD student at IT University of Copenhagen and UCAS.

# Who am I?

Just call me Florian!

- ▶ I am from Germany and live in Denmark.
- ▶ Second year PhD student at IT University of Copenhagen and UCAS.
- ▶ My Chinese is really bad (but I am trying to learn!)

# Who am I?

Just call me Florian!

- ▶ I am from Germany and live in Denmark.
- ▶ Second year PhD student at IT University of Copenhagen and UCAS.
- ▶ My Chinese is really bad (but I am trying to learn!)
- ▶ If you do not understand what I say or if I speak too fast, **please tell me right away!**

# Why Functional Programming?

Functional programming is old but recently it has become very popular!

# Why Functional Programming?

Functional programming is old but recently it has become very popular!

- ▶ Makes it easier to think about what a program does.



# Why Functional Programming?

Functional programming is old but recently it has become very popular!

- ▶ Makes it easier to think about what a program does.
- ▶ Good for parallel programming, performance (see next lecture).

# Why Functional Programming?

Functional programming is old but recently it has become very popular!

- ▶ Makes it easier to think about what a program does.
- ▶ Good for parallel programming, performance (see next lecture).
- ▶ Used in financial industry, modern compilers and more.

# Why Functional Programming?

Functional programming is old but recently it has become very popular!

- ▶ Makes it easier to think about what a program does.
- ▶ Good for parallel programming, performance (see next lecture).
- ▶ Used in financial industry, modern compilers and more.
- ▶ Jobs in functional programming pay better!



**Racket** and its sister-language **Typed Racket** are Scheme-dialects.



**Racket** and its sister-language **Typed Racket** are Scheme-dialects.

- As the names say, Racket is untyped, Typed Racket has types.



**Racket** and its sister-language **Typed Racket** are Scheme-dialects.

- ▶ As the names say, Racket is untyped, Typed Racket has types.
- ▶ Functional language but with support for objects.



**Racket** and its sister-language **Typed Racket** are Scheme-dialects.

- ▶ As the names say, Racket is untyped, Typed Racket has types.
- ▶ Functional language but with support for objects.
- ▶ Great meta-programming (we won't look at that).

# Hello World in Typed Racket

```
;; Tell run-time which language to use.  
#lang typed/racket  
  
;; Now print something.  
(print "Nihao!")
```



# A More Interesting Program

```
#lang typed/racket
```

```
;; Define x as the result of the computation.  
(define x (* (+ 2 4) (+ 42 9)))
```

# Do You Think This Looks Strange?

In Racket, all expressions are written like this:

```
(function arg1 arg2 ... argN)
```

Operators are also just functions:

(+ x y)	$\Rightarrow$	$x + y$
(> x y)	$\Rightarrow$	$x > y$
(/ x y)	$\Rightarrow$	$\frac{x}{y}$
(f x y)	$\Rightarrow$	$f(x, y)$

# Local Bindings

Just like local variables in Java, but you can never change them!

```
#lang typed/racket
```

```
(let ([x (* 2 16)]  
      [y (* 3 17)])  
  (+ x y))
```

What does this program do?

*Note:* You cannot reference `x` and `y` after the last closing parenthesis of the `let` expression!

# A First Function

```
#lang typed/racket

(: times-two (-> Number Number))
(define (times-two x)
  (* 2 x))
```

Several new things on this slide:

- ▶ Functions need no return statement. Their return value is the last executed statement!
- ▶ Type annotations start with `:` and describe the type of a symbol.
- ▶ The type of `times-two` is *Number*  $\rightarrow$  *Number*.