

# Functional Programming in Typed Racket

Florian Florian  
fbie@itu.dk

IT University of Copenhagen & UCAS

2016-05-26



IT University  
of Copenhagen

# Who am I?

Just call me Florian!

# Who am I?

Just call me Florian!

- ▶ I am from Germany and live in Denmark.

# Who am I?

Just call me Florian!

- ▶ I am from Germany and live in Denmark.
- ▶ Second year PhD student at IT University of Copenhagen and UCAS.

# Who am I?

Just call me Florian!

- ▶ I am from Germany and live in Denmark.
- ▶ Second year PhD student at IT University of Copenhagen and UCAS.
- ▶ My Chinese is really bad (but I am trying to learn!)

# Who am I?

Just call me Florian!

- ▶ I am from Germany and live in Denmark.
- ▶ Second year PhD student at IT University of Copenhagen and UCAS.
- ▶ My Chinese is really bad (but I am trying to learn!)
- ▶ If you do not understand what I say or if I speak too fast, **please tell me right away!**

All slides and course materials are available on:

<https://github.com/fbie/parallel-functional-lectures>

# Why Functional Programming?

Functional programming is old but recently it has become very popular!



# Why Functional Programming?

Functional programming is old but recently it has become very popular!

- ▶ Makes it easier to think about what a program does.

# Why Functional Programming?

Functional programming is old but recently it has become very popular!

- ▶ Makes it easier to think about what a program does.
- ▶ Parallel in its nature → easy to parallelize (next lecture).

# Why Functional Programming?

Functional programming is old but recently it has become very popular!

- ▶ Makes it easier to think about what a program does.
- ▶ Parallel in its nature → easy to parallelize (next lecture).
- ▶ Used in financial industry, modern compilers and more.

# Why Functional Programming?

Functional programming is old but recently it has become very popular!

- ▶ Makes it easier to think about what a program does.
- ▶ Parallel in its nature → easy to parallelize (next lecture).
- ▶ Used in financial industry, modern compilers and more.
- ▶ Jobs in functional programming pay better!



**Racket** and its sister-language **Typed Racket** are Scheme-dialects.



**Racket** and its sister-language **Typed Racket** are Scheme-dialects.

- Racket is dynamically typed, Typed Racket has a static, strong type system.



**Racket** and its sister-language **Typed Racket** are Scheme-dialects.

- ▶ Racket is dynamically typed, Typed Racket has a static, strong type system.
- ▶ Functional language, no side-effects (mostly).



**Racket** and its sister-language **Typed Racket** are Scheme-dialects.

- ▶ Racket is dynamically typed, Typed Racket has a static, strong type system.
- ▶ Functional language, no side-effects (mostly).
- ▶ Good for meta-programming (we won't look at that).



# Hello World in Typed Racket

```
;; Tell run-time which language to use.  
#lang typed/racket  
  
;; Now print something.  
(print "Nihao!")
```

# A More Interesting Program

```
#lang typed/racket
```

```
;; Define x as the result of the computation.  
(define x (* (+ 2 4) (+ 42 9)))
```

# A More Interesting Program

```
#lang typed/racket
```

```
;; Define x as the result of the computation.  
(define x (* (+ 2 4) (+ 42 9)))
```

We can check its value in the interactive mode:

```
> x  
59
```

# Do You Think This Looks Strange?

In Racket, all expressions are written like this:

```
(function arg1 arg2 ... argN)
```

# Do You Think This Looks Strange?

In Racket, all expressions are written like this:

```
(function arg1 arg2 ... argN)
```

Operators are also just functions:

(+ x y)	$\Rightarrow$	$x + y$
(> x y)	$\Rightarrow$	$x > y$
(/ x y)	$\Rightarrow$	$\frac{x}{y}$
(f x y)	$\Rightarrow$	$f(x, y)$

# Do You Think This Looks Strange?

In Racket, all expressions are written like this:

```
(function arg1 arg2 ... argN)
```

Operators are also just functions:

(+ x y)	$\Rightarrow$	$x + y$
(> x y)	$\Rightarrow$	$x > y$
(/ x y)	$\Rightarrow$	$\frac{x}{y}$
(f x y)	$\Rightarrow$	$f(x, y)$

Some functions are *variadic*:

(+ x y z)	$\Rightarrow$	$x + y + z$
-----------	---------------	-------------

# Local Bindings

Just like local variables in Java, but you can never change them!

```
#lang typed/racket
```

```
(let ([x (* 2 16)]  
      [y (* 3 17)])  
  (+ x y))
```

What does this program do?

*Note:* You cannot reference `x` and `y` after the last closing parenthesis of the `let` expression!

# The Same Program in Java

```
int x = 2 * 16;  
int y = 3 * 17;  
x + y;
```



# A First Function

```
#lang typed/racket

(: times-two (-> Number Number))
(define (times-two x)
  (* 2 x))
```

# A First Function

```
#lang typed/racket

(: times-two (-> Number Number))
(define (times-two x)
  (* 2 x))
```

Several new things on this slide:

# A First Function

```
#lang typed/racket

(: times-two (-> Number Number))
(define (times-two x)
  (* 2 x))
```

Several new things on this slide:

- Functions need no return statement. Their return value is the last executed statement!

# A First Function

```
#lang typed/racket

(: times-two (-> Number Number))
(define (times-two x)
  (* 2 x))
```

Several new things on this slide:

- ▶ Functions need no return statement. Their return value is the last executed statement!
- ▶ Type annotations start with `:` and describe the type of a symbol.

# A First Function

```
#lang typed/racket

(: times-two (-> Number Number))
(define (times-two x)
  (* 2 x))
```

Several new things on this slide:

- ▶ Functions need no return statement. Their return value is the last executed statement!
- ▶ Type annotations start with `:` and describe the type of a symbol.
- ▶ The type of `times-two` is *Number*  $\rightarrow$  *Number*.

# Types in Typed Racket

We write the function type  $A \rightarrow B$  as:

`(-> A B)`

where `A` is the parameter type and `B` is the return type.

# Types in Typed Racket

We write the function type  $A \rightarrow B$  as:

`(-> A B)`

where `A` is the parameter type and `B` is the return type.

`(-> A B C)`

Which types are parameter types, which ones are return types?

# Polymorphic Types

Polymorphic types in Typed Racket are very explicit:

```
(: twice (All (A) (-> A (Pairof A A))))  
(define (twice a)  
  (pair a a))
```



# Polymorphic Types

Polymorphic types in Typed Racket are very explicit:

```
(: twice (All (A) (-> A (Pairof A A))))  
(define (twice a)  
  (pair a a))
```

“For all types  $A$ , the type of `twice` is such that iff you pass it a value of some type  $A$  it will return a pair of values of type  $A$ .”

# Polymorphic Types

Polymorphic types in Typed Racket are very explicit:

```
(: twice (All (A) (-> A (Pairof A A))))  
(define (twice a)  
  (pair a a))
```

“For all types *A*, the type of *twice* is such that iff you pass it a value of some type *A* it will return a pair of values of type *A*.”

It's just like generic types in Java!

# The Same Program in Java

```
public class Pairof<A> {  
    public final A fst, snd;  
  
    public Pairof(A a) {  
        fst = a;  
        snd = a;  
    }  
  
    public static Pairof<A> twice(A a) {  
        return new Pairof<A>(a);  
    }  
}
```

**Note:** There is no build-in pair type in Java :(

# Local Bindings, Revisited

Let's turn our local binding example into a function!

```
(: two-three-sum (-> Number Number Number))  
(define (two-three-sum a b)  
  (let ([x (* 2 a)]  
        [y (* 3 b)]])  
    (+ x y)))
```

# Local Bindings, Revisited

Let's turn our local binding example into a function!

```
(: two-three-sum (-> Number Number Number))  
(define (two-three-sum a b)  
  (let ([x (* 2 a)]  
        [y (* 3 b)]])  
    (+ x y)))
```

Now, we can call it like any other function:

```
> (two-three-sum 1 1)  
5  
> (two-three-sum 20 20)  
100
```

# Anonymous Functions

You can define functions without giving them a name. Such functions are called *lambda expressions*:

```
> ((lambda (x) x) 2)  
2
```

# Anonymous Functions

You can define functions without giving them a name. Such functions are called *lambda expressions*:

```
> ((lambda (x) x) 2)  
2
```

Here, we have defined a lambda expression and applied it to the value 2. We call this function the *identity function*.

# Anonymous Functions

You can define functions without giving them a name. Such functions are called *lambda expressions*:

```
> ((lambda (x) x) 2)  
2
```

Here, we have defined a lambda expression and applied it to the value 2. We call this function the *identity function*.

We will often come across lambda expressions in functional programming!



# Structs in Typed Racket

Structs are containers for values.

```
(struct (myNumberBox [value : Number]))  
(struct (myStringBox [value : String]))
```

# Structs in Typed Racket

Structs are containers for values.

```
(struct (myNumberBox [value : Number]))  
(struct (myStringBox [value : String]))
```

We can also use type polymorphism here:

```
(struct (A) (myPolyBox [value : A]))
```

# That Was a Quick Intro

Next, we will do a live coding session!

# That Was a Quick Intro

Next, we will do a live coding session!

- ▶ I code on the big screen and show you how to do functional programming in Racket.

# That Was a Quick Intro

Next, we will do a live coding session!

- ▶ I code on the big screen and show you how to do functional programming in Racket.
- ▶ You help with ideas and suggestions and experiment yourselves!

# That Was a Quick Intro

Next, we will do a live coding session!

- ▶ I code on the big screen and show you how to do functional programming in Racket.
- ▶ You help with ideas and suggestions and experiment yourselves!
- ▶ All code we write will be available on
  - ▶ [github.com/fbie/parallel-functional-programming](https://github.com/fbie/parallel-functional-programming)

# That Was a Quick Intro

Next, we will do a live coding session!

- ▶ I code on the big screen and show you how to do functional programming in Racket.
- ▶ You help with ideas and suggestions and experiment yourselves!
- ▶ All code we write will be available on
  - ▶ [github.com/fbie/parallel-functional-programming](https://github.com/fbie/parallel-functional-programming)
- ▶ You can download Racket from
  - ▶ [racket-lang.org](https://racket-lang.org)

# Java Equivalent to Maybe

```
public abstract class Maybe<A> {}

public class None<A> extends Maybe<A> {
    public None() {}
}

public class Some<A> extends Maybe<A> {
    public final A a;
    public Some(A a) {
        this.a = a;
    }
}
```



# Java Equivalent to Cons List

```
public abstract class LinkedList<A> {}

public class Nil<A> extends LinkedList<A> {
    public Nil() {}
}

public class Cons<A> extends LinkedList<A> {
    public final A a;
    public final LinkedList<A> tail;

    public Cons(A a, LinkedList<A> tail) {
        this.a = a;
        this.tail = tail;
    }
}
```

# Java Equivalent to Binary Tree

```
public abstract class BinaryTree<A> {}

public class Leaf<A> extends BinaryTree<A> {
    public final A a;
    public Leaf(A a) {
        this.a = a;
    }
}

public class Node<A> extends BinaryTree<A> {
    public final BinaryTree<A> left, right;
    public Node(BinaryTree<A> left,
                BinaryTree<A> right) {
        this.left = left; this.right = right;
    }
}
```