



















Global Settings

Global Settings

1. Applications

- Native connector for JD Edwards (Oracle, DB2 or MS-SQL)
- Native connector for Oracle Database
- Native connector for Microsoft Active Directory
- All databases accessible with jdbc can be set

<div>Type to filter </div> <div>Select Application </div> <div></div>						
Application ID 	Application Name 	Application Type 	Database 	Host 	User (Audit) 	Date (Audit) 
10	JDE_TEMPLATE	JDE	ORACLE	132.145.46.174	admin	2022-02-13
20	ORACLE_TEMPLATE	DATABASE	ORACLE	132.145.46.174	admin	2022-02-13

Click on add or edit to set a new datasource or modify an existing datasource and follow the wizard

1.1. Global Settings

Edit Application

1

Global

2

Connexion

3

Options

Application ID

10

Application Name *

JDE_TEMPLATE

Application Type *

JD Edwards

Database *

Oracle

Cancel

Save

Parameter	Description	Comments
Application ID	Unique ID	Automatic increment number used in all table joins
Application Name	Name of your application	
Application Type	Native or custom connector	JD Edwards, Database, LDAP, Weblogic, Custom Application
Database	Type of database	Oracle, MySQL, IBM DB2, Microsoft SQL Server, LDAP

1.2. Connections

Edit Application

1

Global

2

Connexion

3

Options

Direct connection

DB-Link

Create DB LINK

Host

132.145.46.174

Port

1521

Database

jdeorcl

User

system

Password

.....

Cancel

Save

Some parameters could be hidden depending on the type of the application

Parameter	Description	Comments
Host	Database server	
Port	Database port	
Database	Service Name	Service Name and not SID for Oracle later than 12.2

Parameter	Description	Comments
User	Login to database	login could have read-only rights but with access to dictionary or catalog
Password	Password for the user	

1.3. Options

Parameters differs depending on the type of the application

1.3.1. JD Edwards

Edit Application

1

Global

2

Connexion

3

Options

JDE DTA
PS920DTA

JDE SY
SY920

F00950
SY920

JDE CTL
PS920CTL

JDE SVM
SVM920

JDE CO
PS920

JDE OL
OL920

Navigation

☒ Standard Menu (Y/N)

☒ E1 Pages (Y/N)

☒ E1 Composite (Y/N)

Cancel

Save

Parameter	Description	Comments
JDE DTA	Business Data	PRODDTA
JDE CTL	Control Tables	PRODCTL
JDE CO	Central Objects	PD920
JDE SY	System Tables	SY920
JDE SVM	Server Map	SVM920

Parameter	Description	Comments
JDE OL	Object Librarian	OL920
F00950	Security table location (sometimes not in SYSTEM)	SY920
Standard Menu (Y/N)	Collect Tasks Menus	
E1 Pages (Y/N)	Collect E1 Pages	Before Tools Release 9.2 and E1 composite
E1 Composite (Y/N)	Collect E1 Composite Pages	After Tools Release 9.2

1.3.2. Database / Custom Application

NONE

1.3.3. LDAP

Parameter	Description	Comments
LDAP Context	Search	OU=Utilisateurs,DC=nomana-it,DC=fr
LDAP Filter	Filtering type of object	(&(objectClass=user))
LDAP Exclude	Exclude node	OU=Applications,OU=Utilisateurs,DC=nomana-it,DC=fr

2. Users

3. Query

4. DWH