



# Car detection using YOLO and Faster R-CNN

---

Filip Buljan, Lovro Akmačić, Lucia Crvelin, Lorena  
Švenjak, Tomislav Čupić

Zagreb, May 2025.



Sveučilište u Zagrebu  
Fakultet elektrotehnike i računarstva  
Zavod za elektroničke sustave i obradbu informacija



# Overview

---

- Problem

- About the problem
- Existing methods
- Our approach to the problem
- Eksperimental results of methods

- Conclusion

- Future improvements



# About

---

- Used two state-of-the-art deep models
  - YOLO (You only look once)
  - Faster R-CNN (Region based Convolutional network)
- Implementation and evaluation
- Comparing the results of models



# Why car detection matters and why is it challenging

---

- Autonomous driving
- Surveillance and traffic analysis
- Varying object sizes and angles
- Lightning Conditions
- Speed vs. accuracy trade-off



# Existing methods overview

---

- YOLO
  - Single stage detector
  - Entire image in a single pass
  - Real-time performance
  - Fast
  - Less accurate for small objects



# Existing methods overview

---

- Faster R-CNN
  - Two stage detector
  - Region proposal network (RPN)
  - High precision
  - Better bounding boxes
  - Slower and more expensive



# Our approach

---

- YOLOv8
  - pre-trained
  - Detection and counting with bounding boxes and confidence scores

# Yolo model – test output example







# Our approach


---

- Faster R-CNN
  - Pre-trained model – COCO
  - Fine tuned model
    - Classification head for cars only
    - Trained with annotated car dataset
    - Improved precision

# Pre-trained Faster R-CNN – test output example



# Fine-tuned Faster R-CNN – test output example





# Our approach

---

- Our own custom model
- Bad results
- Challenges:
  - Structure of the network
  - Small dataset
  - Custom loss function
  - Connecting postprocessing with training process



# Experiment results

---

- YOLOv8 results
  - Precision - 0.919
  - Recall – 0.857
  - mAP@50 – 0.904
  - mAP50-95 – 0.360
- Fast and accurate
- Low precision at IoU thresholds



# Experiment results

---

- Faster R-CNN pre-trained
  - mAP@50 – 0.7768
  - mAP@75 – 0.0645
- Bad localization and detection of small object
- Weak performance without tuning



# Experiment results

---

- Faster R-CNN Fine-tuned:
  - mAP@50 – 0.9987
  - mAP@75 – 0.7541
- High precision after fine-tuning
- Still weak on small objects
- Fine-tuning is an effective strategy



## Video of GUI:

---

- <https://drive.google.com/file/d/19FnDuNmnvrjnNum3ipGIGDVimcg3iWXY/view?usp=sharing>





# Conclusion

---

- YOLOv8 – ideal for fast real-time identification of an object
  - Highly efficient for car detection
  - Not precise
- Faster R-CNN – ideal when accuracy is critical
  - superior precision



# Future improvements

---

- Edge deployment
- Robustness to challenging conditions
- Improvements in detection
- Different datasets