

A platform to analyse impacts of the exception events on the bus velocity of São Paulo^{*}

No Author Given

No Institute Given

Abstract This work presents a platform to understand the impacts of exception events in the buses velocity of São Paulo, through modules able to identify exception events and correlate them with real heterogeneous data related to public transportation.

Keywords: Smart cities · social networks · public transportation.

1 Introduction

Exception events happen sporadically or suddenly and are capable of generating significant delays or even unavailability of the operation of public transport. This type of events are reported by citizens and authorities in Social Networks, which can be used by Smart City systems. As an example, the public transport can benefit by integrating Social Networks content with the planning, management and operational activities of public transport, addressing their respective sociotechnical factors [14]. In this work we present a new platform validated with real and heterogeneous data sources (*tweets*, AVL — Automatic Vehicle Location and GTFS¹ — Google Transit Feed Specification data) to understand automatically exception events impacts in the São Paulo’ buses velocity.

2 Related Work

Several works studies how to use *tweets* processing for analyzing problems related to public transport. These studies can be classified into *event impact analysis*, *planning* and *management of public transport*. For example, [24] used *tweets* to analyze the impact of the terrorist attacks in Paris (2015) on mobility patterns regarding the use of public transport. Similarly, [11] developed a tool based on *tweets* to visualize and explore the decisions of passengers of the Tokyo Metro in abnormal events such as typhoons, fires, earthquakes, etc. In this same context, [20] proposed a technique to predict passenger flow in the New York

^{*} This research is part of the INCT of the Future Internet for Smart Cities funded by CNPq, proc. 465446/2014-0, CAPES proc.88887.136422/2017-00, and FAPESP, proc. 2014/50937-1.

¹ Google Transit: <https://developers.google.com/transit>. Accessed in December 11, 2018.

Metro and identify events based on *hashtags*. [2] studied the relationship between traffic events and the demand for bicycles.

In respect to public transport planning and management, [17] presents a platform developed and used by the Bangalore Public Transport Agency, which allows report issues related to public transport, improving the operation planning and the service provided to the population. Analogously, [9] used *tweets* to identify the popularity of points of interest and age distribution, in order to determine the best points for bicycle stations and thus encourage the use of this mode of transport. Also related to the points of interest, [16] used *tweets* to identify human activities patterns and their respective impacts on the demand for public transport.

In [5] a hierarchical approach was created to classify *tweets* related to transport. They have demonstrated that it is possible to use this information for transportation planning and management purposes. This technique was applied in a case study associated with sporting events in the United Kingdom. The hierarchy is composed of three levels (I) *tweets* classified among those that express the need for transport services, opinions and incidents; (II) identification of the transport category and (III) topics.

Another study that contributes to the planning of public transport is the one carried out in [6,7], in which *tweets* were processed to identify user disposition to trips related to leisure, suggesting to them activities with less time of travel and probability of delays. Another relevant point considered was the level of access to public transport, which, when high, positively impacts people’s happiness and correlates with positive feelings, according to the analysis of feelings carried out by [8], using *tweets* published in Greater London.

Neither of the presented works tackle the identification of different types of exception events from *tweets* published by an authority to characterize the velocity impact on buses of São Paulo. In this work we propose a new platform, explained ahead, for deal with this problem. The cited works are connected to our on aspects related to *tweets* processing for analysis of the impact of events on public transport, planning and management.

3 Data set

Corpus Twitter. The *Twitter* was chosen as a data source for the construction of the data set related to the events of exception due to the fact of containing public data about the daily life of the city, made available in real time by citizens and public agencies. These characteristics make tweets a rich source of data, used by numerous studies addressing urban and urban mobility problems, as analysed in the section 2. In this work, the dataset used to identify the exception events is composed by *tweets*, in Brazilian Portuguese, of the profiles contained in Table 1, which were selected manually according to the agencies responsible for reporting exception events. Such profiles are public in nature, meaning access to tweets does not involve privacy issues.

Table 1. TIME INTERVAL AND NUMBER OF TWEETS COLLECTED

<i>Twitter profile</i>	<i>Total (Ttl.) tweets</i>	<i>Start date</i>	<i>End date</i>
@BombeirosPMESP	6,632	2017-05-21	2017-12-01
@CETSP_	5,735	2017-02-20	2017-12-01
@CPTM_oficial	6,301	2017-04-24	2017-12-01
@governosp	6,011	2017-05-10	2017-12-01
@metrosp_oficial	8,621	2017-06-07	2017-12-01
@Policia_Civil	3,417	2015-04-15	2017-11-30
@PMESP	4,365	2016-06-02	2017-11-30
@saopaulo_agora	3,960	2016-11-18	2017-11-30
@smtsp_	1,316	2017-04-26	2017-12-01
@SPCEDEC	1,301	2015-06-09	2017-12-01
@sptrans_	9,956	2017-06-13	2017-12-01
@TurismoSaoPaulo	3,369	2012-06-12	2017-11-29
Total	60,984	—	—

Corpus SPTrans. The SPTrans (São Paulo Transportation Company)² corpus has data specified in GTFS, detailed in Table 2 and data of geolocation of all the buses of São Paulo, referring to the year of 2017 — *obtained by the law on access to information*³. In respect to AVL data set, it is important to note inconsistencies in the two AVL files of January 11, according to SPTrans meta data each file must have 19 fields, however, the file with data from 09h to 10h has 21 fields in line 1,075,548 and the file with data from 10h to 11h has 35 fields in line 60,025. The gaps mentioned before were ignored in processing, the original data was converted from *string* to its respective type (*long*, *double*, *int* or *string*), time values were standardized using *POSIX timestamps*, and data referring to latitude and longitude were converted to *legacy coordinate pairs*⁴. In order to enable *geospatial queries*, *geospatial indexes*⁴ were created in the *MongoDB* collections containing geolocalized information.

4 Platform to identify impacts on buses speeds in the city of São Paulo

Architecture According to the Figure 1 the platform is composed by a (1) *tweets* processing streaming module (which can be replaced by any real time processing software), where the *tweets* are collected, preprocessed and processed; (2) classification models; (3) address extraction and geolocalization module and (4, 5 and 6) correlation data modules (the process responsible for finding abnormal association rules in the velocity dataset, showed in 6 note of Figure 1, is beyond the scope of this article). The modules from architecture are explained in details ahead.

² <http://www.sptrans.com.br>. Accessed in December 11, 2018.

³ http://www.planalto.gov.br/ccivil_03/_ato2011-2014/2011/lei/l12527.htm (in Portuguese). Accessed in December 11, 2018.

⁴ <https://docs.mongodb.com/manual/geospatial-queries>. Accessed in December 11, 2018.

Table 3. SPTrans’AVL data set description


Month	Ttl. AVL files	Ttl. size (GB)
January	744	102,44
February	672	93,21
March	744	102,64
April	720	97,04
May	744	101,46
June	720	97,13
July	744	104,95
August	744	108,38
September	720	109,89
October	744	110,92
November ^a	717	108,16
December ^b	738	110,89
Total	8,751	1,247,09

Table 2. Data set and total records specified in SPTrans’ GTFS

Data set	Ttl. records
<i>agency.txt</i>	1
<i>calendar.txt</i>	6
<i>fare_attributes.txt</i>	6
<i>fare_rules.txt</i>	5,400
<i>frequencies.txt</i>	39,625
<i>routes.txt</i>	291,634
<i>shapes.txt</i>	800,767
<i>stop_times.txt</i>	95,144
<i>stops.txt</i>	19,933
<i>trips.txt</i>	2,273
Total	1,254,779

^a Missing data: 01/11 — from 12h to 15h.

^b Missing data: 15/12 — from 01h to 09h.

Figure 1. Platform Architecture

Natural Language Processing Before the Natural Language Processing (NLP), the *tweets* were preprocessed — removing *URLs*, *datetime*, mentions to other *tweets*, emoticons, punctuations — to reduce the dimension of feature space. A particular attention was paid to *hashtags*, which are relevant to excep-

tion events classification, but adds noise to the address extraction phase. In order to mitigate this problem, *hashtags* are identified and replaced by empty spaces in the address extraction process. Also, it is important to note that *hashtags* are not removed from original *tweets*.

After the preprocessing phase we applied NLP techniques to *tweets*, such as (I) *Tokenization* — process to obtain the words, i.e. tokens (features used to train the classification model), in a *tweet*, removing numbers and characters that do not belong to the alphabet (*TweetTokenizer*⁵); (II) morphological decomposition to get a given word into its inflected form using lemmatization (word lemma identification) or stemming (identification of the root of the word using heuristics to determine the location of its flexion — *RSLPStemmer*⁶); process used to features space reduction, besides of Brazilian Portuguese *stopwords* removal⁷ (common words without meaning) [3, 12, 18, 22, 23]. This procedure reduced the number of tweets, from 60,984 to 59,834. Then, are processed to be represented by a bag-of-words, which contains feature vectors created using the *Term Frequency - Inverse Document Frequency* (TF-IDF) measure that be used by classification models.

Classification model Finding exception events involves the identification of events related to an exception, which is possible through classification. Based on [2, 5, 11, 15] we can use the following classes of exception events to classify the *tweets*: (I) Accidents, (II) social events, (III) urban events, (IV) natural disasters and (V) irrelevant. Using the these classes, 59,834 *tweets* were manually classified. This labeled data was transformed to a binary representation of features (TF-IDF), which was used to train models to classify *tweets* in exception events.

In this work we used supervised learning, since we know how the input data can be classified, being the following algorithms⁸ normally applied to classify textual data sets: (Complement and Multinomial) Naive Bayes, Decision Tree, K-Nearest Neighbors, Logistic Regression, Multi-layer Perceptron, Random Forest and Support Vector Machine [4, 13, 19].

Addresses and geolocalization extraction Analyzing the content of *tweets* from the selected accounts, it is possible to observe that the texts published normally follows a given template and, therefore, are actually semi-structured. So, we used this regular expression to extract addresses from *tweets*: $ER = \{L_1|S_1|L_2|S_2|\dots|L_n|S_n\}\{[a - z\dot{A} - \ddot{y}] + \}$. That expression is divided in two sets, in the first ($\{L_1|S_1|L_2|S_2|\dots|L_n|S_n\}$), (L — in Portuguese: *logradouro*,

⁵ NLTK module used to the tokenization process. <https://www.nltk.org/api/nltk.tokenize>. Accessed in December 09, 2018.

⁶ NLTK module used to the stemming process. https://www.nltk.org/_modules/nltk/stem/rslp. Accessed in December 09, 2018.

⁷ Brazilian Portuguese *stopwords* were obtained from NLTK — <https://www.nltk.org>. Accessed in December 19, 2018.

⁸ We used the algorithms implemented by *Sci-Kit Learn*, with the standard hyper-parameters. It is not the focus of this work hyper-parameters tuning.

meaning public spaces such as avenue, etc.) and (S — public spaces acronyms) are concatenated to specify a filter and identify *strings* initialized with public spaces or its respective acronyms. The second set ($\{[a - z\dot{A} - \ddot{y}] + \}$), represents a filter to identify a set of words after L or S, candidates to compose the wanted addresses.

These words are treated as candidates because it is hard to know how many words after L or S belongs to the address, however, the selected accounts publish *tweets* with visible patterns in the texts, after and before the addresses. As a consequence, a possible method to find the wanted address is the removal of these patterns after and before of the address. After address extraction, we used the Google Maps Geocoding API⁹ to geolocate the found address (only 1.5% of *tweets* have geolocalization [21]). The HTTP response from this API is processed to get the values from location (which contains latitude and longitude information) and formatted address.

Finding bus lines affected by exception events In order to find the bus lines affected by exception events, it is necessary to correlate the coordinates of exception events with the existing coordinates in the shapes data set — a set of latitude and longitude used for drawing bus lines on a map to represent its respective paths — existing in SPTrans’ GTFS. According to Section 3, all coordinates are stored in legacy pairs and in collections with geospatial indexes. Thus, it is possible to use the `$near` function from MongoDB¹⁰ to find shapes close to the exception event coordinates. The GTFS defines that the *shape_id* (i.e. bus code line) is part of attributes contained in the shape file, which is used as parameter to correlate the bus code line with others GTFS files with details about the bus direction, identification, etc.

Velocity impact analysis After we found the bus lines impacted by exception events, we select the movement data that will be analyzed, e.g. if the exception event happened on 08/17/2017 (Thursday), every other Thursday in the month of August (3, 10, 24 and 08/31/2017) will be considered in the analysis, this because the days of the week have different patterns of movement (seasonality), e.g. on Fridays many social events occur that usually lead to a more congested traffic. Besides, the months also have different characteristics — holidays at the end of the year, vacations, beginning of school periods, etc. —, as Fig. 4, because of this the selected days are restricted to the month of occurrence of the event.

In another step, we also filtered the data related to the impacted lines within a radius of 100 and 1,000m of the exception event in question, in addition to

⁹ <https://developers.google.com/maps/documentation/geocoding>. Accessed in December 20, 2018.

¹⁰ <https://docs.mongodb.com/manual/reference/operator/query/near>. Accessed in December 18, 2018.

considering the same time range as the *tweet* time¹¹. So, if the *tweet* time is at 5:15 p.m., we considered the AVL data between 5:00 p.m. and 6:00 p.m.

Next, we aggregated the selected data to descriptively analyze the instantaneous speed of each bus line, thereby extracting data on the maximum, minimum, mean, median, variance, standard deviation and percentage of equal and non-zero data. After that, we compared the average speed of the occurrence time range with the average speed of days that do not reference the exception event, for each set of lines affected by the exception event and for each line. Finally, we considered that the line was impacted if the mean of the average speeds of the analyzed days is greater than or equal to the average speed of the day referring to the exception event. Based on this, we assumed that the set of lines has been impacted if the number of impacted lines is greater than or equal to 50%.

5 Results

Classification models The methodology was applied to the *Corpus Twitter*¹², which contains 60,984 *tweets*. At the end of *tweets* preprocessing and processing, we have 59,834 examples, the corpus got 414,637 words, with a vocabulary size of 13,915 words. All *tweets* were manually classified according to identified exception events. The distribution of the examples for each class follows, 7,07% Accident, 83,24% Irrelevant — to non exception events, 4,52% Natural Disaster, 2,35% Social Event and 2,81% Urban Event. This labeled data set was used to train exception events classification models, based on a *bag-of-words*, described in Section 4. To represent the original distribution of the data, we use the stratified 10-fold cross-validation approach¹³. In which, in each training and test configuration, we apply the tf-idf method only in the training data to then perform the fit of the classification methods.

TODO: Explicar que utilizou várias configurações de hiperparâmetros para os métodos, mas apresenta-se na Tabela apenas os melhores resultados.

For the evaluation of the statistical methods, we considered the accuracy metric, and the micro and macro approaches for precision, recall and f1-score metrics. However, we present in the Table 4 only accuracy and values of precision, recall and f1-score for macro approach, the values for the micro approach directly reflect to the same values of the metric accuracy.

According to Table 4, the model using the Multi-layer Perceptron algorithm obtained greater accuracy for the classification task.

Of the 60,984 *tweets* 10,027 were classified into exception events and from that subset we found 7,710 addresses (which represents 76.89% of the total of

¹¹ It is important to note that this work does not consider the exact start and end of the exception events, but a time range of one hour from the time in the *tweet timestamp*.

¹² Data set publicly available at: <https://github.com/fcas/mobility-analysis/blob/master/datasets/tweets.zip>. Accessed in December 14, 2018.

¹³ https://scikit-learn.org/0.16/modules/generated/sklearn.cross_validation.StratifiedKFold.html. Accessed in December 26, 2018.


Table 4. Metrics of the evaluations of the algorithms used to classify the *tweets* in exception events

Algorithm	Accuracy	Precision	Recall	f1-score
Complement Naive Bayes	0,941	0,949	0,941	0,944
Decision Tree	0,965	0,965	0,965	0,965
K-Nearest Neighbors	0,970	0,971	0,970	0,970
Logistic Regression	0,969	0,968	0,969	0,968
Multi-layer Perceptron	0,973	0,972	0,973	0,972
Multinomial Naive Bayes	0,953	0,952	0,953	0,949
Random Forest	0,970	0,970	0,970	0,970
Support Vector Machine	0,833	0,694	0,833	0,757

tweets classified as exception events. The reasons for *tweets* without address extracted are:

1. *Tweets* with only the point of interest, in other words, the address is not explicitly stated.
2. *Tweets* without address information.
3. *Tweets* with unusual public place name (for example *passageway*, *road complex*, *connection to*).
4. *Tweets* with addresses with concatenated words (for example *avenidapaulista*)

Figure 2 illustrates the addresses¹⁴ most affected by exception events and Figure 3 shows the distribution of these events in the central region of São Paulo. It is important to note that the exception events found are concentrated in the addresses and regions where they normally occur in São Paulo, which validates the methodology developed.

Figure 2. Addresses most impacted by ex-**Figure 3.** Distribution of exception events in the central region of São Paulo

We considered that a bus line is affected by an exception event if a coordinate from *shape* is within a radius of 1,000m away from the event. Using this criterion,


¹⁴ Complete list is available at <https://docs.google.com/spreadsheets/d/1gn1cTDifUJEPdgcU67SC45GdYHRKmiHtAfJwRBm088s/edit?usp=sharing>. Accessed on December 20, 2018.

the total of 1,073 bus lines were affected by exception events during this period, with line “33121” (TERM. PRINC. ISABEL / TERM. STO. AMARO) being the most impacted bus line code. This particular line was impacted by 1,623 exception events and the full table publicly available in ¹⁵.

Table 5. Percentage of impact on the average speed of the groups of lines affected by exception events at 1,000m and 100m distance respectively, in the months of 2017

Month	<i>Accident</i>		<i>Natural Disaster</i>		<i>Social Event</i>		<i>Urban Event</i>	
January	83,33	100	64,23	98,00	100	—	100	—
February	70,58	100	66,25	100	100	100	80	—
March	50,00	—	66,66	100	85,00	100	68,18	100
April	87,50	100	61,11	100	82,75	100	76,92	100
May	65,13	100	58,82	100	93,33	100	50,00	100
June	54,46	100	61,53	100	76,47	100	72,41	100
July	61,48	98,41	66,66	100	69,23	100	58,13	100
August	57,86	87,17	55,35	100	85,54	100	68,10	90,90
September	64,21	100	42,10	100	92,30	100	62,06	100
October	70,49	—	56,81	—	80,00	—	61,11	—
November	66,66	100	57,99	100	92,85	100	74,35	100
December	—	—	—	—	—	—	—	—
Total	66,51	98,39	59,77	99,80	87,04	100	70,11	98,86

Figure 4. Distribution of geolocation exception classes over the months of 2017



Using the methodology described above, we can observe in Tab. 5 that the social event-related exception events have an average of 87,04% impact on the average speed in the groups of bus lines affected by a radius of 1,000m and 100% to a radius of 100m, this probably due to the large number of people involved in this type of event, number of avenues with modified or interrupted traffic flow.

¹⁵ <https://docs.google.com/spreadsheets/d/1jIqUuIJg7FhXD5C8MFF8stbv0D3uiUgMfN2b0ltT7zE/edit?usp=sharing>. Accessed in December 20, 2018.

Urban events, in turn, impacts 70,11% at 1,000m and 98,86% at 100m, even though these events are being carried out with alternative routes planning and warn signs on public roads. The third and fourth most affected classes are those of accidents and natural disasters, respectively, 66,51% and 59,77 % at 1,000m and 98,39 % and 99,80 % to 100m, which normally blockages or detours on public roads used by buses.

In addition, January, February and March were the three months most affected by exception events related to natural disasters, a period of high rainfall in São Paulo, where landslides, tree falls and floods usually occurs. In relation to social events, the year 2017 was marked with numerous political manifestations, in this context, May was the most impacted month by this type of exception event, mainly due to the protests against the government Temer ¹⁶. The events related to accidents usually occur in greater concentration in the periods of holidays and holidays, which can be observed in the months of January and April (single month of 2017 with two prolonged holidays), with a mean impact of 83.33% and 87.50% at the average speeds, respectively. Impacts related to urban events occurs normally during all months, due to which they percentages are uniform.

The months close to 100% of impact at average speeds are justified because of the small volume of events for a given class in a given month, as Fig.4, which also happens for scenarios with geolocated data next to the exception events. Similarly, the months and classes without impact data are months with little data for the analyzed class.

6 Conclusions and future works

This work presents a new methodology for exception events classification and analyze their respective impacts on velocity of the public transport system by bus of the São Paulo city. Using *tweets* from selected public service providers, we found that Multi-layer Perceptron was the best algorithm for classifying *tweets* in exception events. We also showed that it is possible to extract addresses from semi-structured *tweets* using only regular expressions. Classifying these events are the first step to better understand how these exceptional events impact the velocity of buses, using the methodology developed we found that social events reduces the velocity of 87,04% of a group impacted, urban event 70,11%, accident 66,51% and natural disaster 59,77% from a distance of 1,000m.

Although validated using selected Twitter profiles written in Brazilian Portuguese language, this method can be generalized for different languages and cities. GTFS is a ubiquitous format for public transport and tools like NLTK supports several languages.

Future work

¹⁶ www1.folha.uol.com.br/poder/2017/05/1884977-manifestacao-anti-temer-reune-hundreds-of-people-in-av-paulista.shtml. Accessed on December 2, 2018

Acknowledgment

This research is part of the INCT of the Future Internet for Smart Cities funded by CNPq proc. 465446/2014-0, Coordenação de Aperfeiçoamento de Pessoal de Nível Superior – Brasil (CAPES) – Finance Code 001, FAPESP proc. 14/50937-1, and FAPESP proc. 15/24485-9.

References

1. Atefeh, F., Khreich, W.: A survey of techniques for event detection in twitter. *Computational Intelligence* **31**(1), 132–164 (2015)
2. Chen, L., Zhang, D., Wang, L., Yang, D., Ma, X., Li, S., Wu, Z., Pan, G., Nguyen, T.M.T., Jakubowicz, J.: Dynamic Cluster-Based Over-Demand Prediction in Bike Sharing Systems. *UBICOMP* pp. 841–852 (2016). <https://doi.org/10.1145/2971648.2971652>
3. Collobert, R., Weston, J., Bottou, L., Karlen, M., Kavukcuoglu, K., Kuksa, P.: Natural language processing (almost) from scratch. *Journal of Machine Learning Research* **12**(Aug), 2493–2537 (2011)
4. Dwivedi, S.K., Arya, C.: Automatic text classification in information retrieval: A survey. In: *Proceedings of the Second International Conference on Information and Communication Technology for Competitive Strategies*. p. 131. ACM (2016)
5. Gal-Tzur, A., Grant-Muller, S.M., Kuflik, T., Minkov, E., Nocera, S., Shoor, I.: The potential of social media in delivering transport policy goals. *Transp. Policy* **32**, 115–123 (2014). <https://doi.org/10.1016/j.tranpol.2014.01.007>
6. Gkiotsalitis, K., Stathopoulos, A.: Joint leisure travel optimization with user-generated data via perceived utility maximization. *Transp. Res. Part C Emerg. Technol.* **68**, 532–548 (2016). <https://doi.org/10.1016/j.trc.2016.05.009>, <http://dx.doi.org/10.1016/j.trc.2016.05.009>
7. Gkiotsalitis, K., Stathopoulos, A.: A utility-maximization model for retrieving users’ willingness to travel for participating in activities from big-data. *Transp. Res. Part C Emerg. Technol.* **58**, 265–277 (2015). <https://doi.org/10.1016/j.trc.2014.12.006>, <http://dx.doi.org/10.1016/j.trc.2014.12.006>
8. Guo, W., Gupta, N., Pogrebna, G., Jarvis, S.: Understanding happiness in cities using twitter: Jobs, children, and transport. *IEEE 2nd Int. Smart Cities Conf. Improv. Citizens Qual. Life, ISC2 2016 - Proc.* (2016). <https://doi.org/10.1109/ISC2.2016.7580790>
9. Gutev, A., Nenko, A.: Better Cycling - Better Life: Social Media Based Parametric Modeling Advancing Governance of Public Transportation System in St. Petersburg. *Proc. Int. Conf. Electron. Gov. Open Soc. Challenges Eurasia* pp. 242–247 (2016). <https://doi.org/10.1145/3014087.3014123>, <http://doi.acm.org/10.1145/3014087.3014123>
10. Guyon, I., Elisseeff, A.: An introduction to feature extraction. *Feature extraction* pp. 1–25 (2006)
11. Itoh, M., Yokoyama, D., Toyoda, M., Tomita, Y., Kawamura, S., Kitsuregawa, M.: Visual Exploration of Changes in Passenger Flows and Tweets on Mega-City Metro Network. *IEEE Trans. Big Data* **2**(1), 85–99 (2016). <https://doi.org/10.1109/TBDATA.2016.2546301>, <http://ieeexplore.ieee.org/document/7445832/>

12. Korenius, T., Laurikkala, J., Järvelin, K., Juhola, M.: Stemming and lemmatization in the clustering of finnish text documents. In: Proceedings of the Thirteenth ACM International Conference on Information and Knowledge Management. pp. 625–633. CIKM '04, ACM, New York, NY, USA (2004). <https://doi.org/10.1145/1031171.1031285>, <http://doi.acm.org/10.1145/1031171.1031285>
13. Kotsiantis, S.B., Zaharakis, I., Pintelas, P.: Supervised machine learning: A review of classification techniques. *Emerging artificial intelligence applications in computer engineering* **160**, 3–24 (2007)
14. Kuflik, T., Minkov, E., Nocera, S., Grant-Muller, S., Gal-Tzur, A., Shoor, I.: Automating a framework to extract and analyse transport related social media content: The potential and the challenges. *Transportation Research Part C: Emerging Technologies* **77**, 275–291 (2017)
15. Lecue, F., Tallevi-Diotallevi, S., Hayes, J., Tucker, R., Bicer, V., Sbodio, M., Tommasi, P.: Smart traffic analytics in the semantic web with STAR-CITY: Scenarios, system and lessons learned in Dublin City. *J. Web Semant.* **27**, 26–33 (2014). <https://doi.org/10.1016/j.websem.2014.07.002>, <http://dx.doi.org/10.1016/j.websem.2014.07.002>
16. Maghrebi, M., Abbasi, A., Rashidi, T.H., Waller, S.T.: Complementing Travel Diary Surveys with Twitter Data: Application of Text Mining Techniques on Activity Location, Type and Time. *IEEE Conf. Intell. Transp. Syst. Proceedings, ITSC 2015-October*, 208–213 (2015). <https://doi.org/10.1109/ITSC.2015.43>
17. Mukherjee, T., Chander, D., Eswaran, S., Singh, M., Varma, P., Chugh, A., Dasgupta, K.: Janayuja: A People-centric Platform to Generate Reliable and Actionable Insights for Civic Agencies. *Acm Dev* 2015 pp. 137–145 (2015). <https://doi.org/10.1145/2830629.2830642>
18. Nadkarni, P.M., Ohno-Machado, L., Chapman, W.W.: Natural language processing: an introduction. *Journal of the American Medical Informatics Association* **18**(5), 544–551 (2011)
19. Narayanan, U., Unnikrishnan, A., Paul, V., Joseph, S.: A survey on various supervised classification algorithms. In: 2017 International Conference on Energy, Communication, Data Analytics and Soft Computing (ICECDS). pp. 2118–2124. IEEE (2017)
20. Ni, M., He, Q., Gao, J.: Forecasting the Subway Passenger Flow Under Event Occurrences With Social Media. *IEEE Trans. Intell. Transp. Syst.* **18**(6), 1623–1632 (2016). <https://doi.org/10.1109/TITS.2016.2611644>
21. Niu, W., Caverlee, J., Lu, H., Kamath, K.: Community-based geospatial tag estimation. In: Advances in Social Networks Analysis and Mining (ASONAM), 2016 IEEE/ACM International Conference on. pp. 279–286. IEEE (2016)
22. Roy, A., Majumder, A.G., Nath, A.: Understanding natural language processing and its primary aspects. *International Journal* **5**(8) (2017)
23. Setiawan, E.B., Widiantoro, D.H., Surendro, K.: Feature expansion using word embedding for tweet topic classification. *Proceeding 2016 10th Int. Conf. Telecommun. Syst. Serv. Appl. TSSA 2016 Spec. Issue Radar Technol.* (2011) (2017). <https://doi.org/10.1109/TSSA.2016.7871085>
24. Wen, X., Lin, Y.R., Pelechris, K.: PairFac: Event Analytics through Discriminant Tensor Factorization. *Cikm* pp. 519–528 (2016). <https://doi.org/10.1145/2983323.2983837>
25. Zhou, X., Chen, L.: Event detection over twitter social media streams. *The VLDB journal* **23**(3), 381–400 (2014)