

Package ‘BBMV’

April 23, 2018

Type Package

Title Models for Continuous Traits Evolving in Macroevolutionary
Landscapes of any Shape

Version 2.1

Date 2018-04-23

Author Florian C. Boucher

Maintainer Florian C. Boucher <floboboucher@gmail.com>

Depends R (>= 3.1.0), ape

Suggests coda, geiger

Description Provides a set of functions to fit general macroevolutionary models for continuous traits evolving in adaptive landscapes of any shape. This package implements the Fokker-Planck-Kolmogorov model (FPK), in which the trait evolves under random diffusion but is also subject to a force that pulls it towards specific values - this force can be of any shape. FPK has a version in which hard reflective bounds exist at the extremes of the trait interval: this second model is called BBMV.

License GPL-2

NeedsCompilation no

R topics documented:

BBMV-package	2
ACE_FPK	4
charac_time	4
ConvProp_bounds	5
DiffMat_backwards	5
DiffMat_forward	6
find.mle_FPK	6
find.mle_FPK_multiple_clades_same_V_different_sig2	8
fit_FPK_multiple_clades_different_V_different_sig2	9
FormatTree_bounds	11
FPK_sim_traitgram	11
get.landscape.FPK	12
get.landscape.FPK.MCMC	13
lnL_FPK	15
lnl_FPK_multiclades_same_V_different_sig2	16
LogLik_bounds	18

log_prior_5pars_root_bounds	18
log_prior_nclades_plus_3_pars	19
MH_MCMC_FPK	19
MH_MCMC_FPK_multiclades	22
posterior_vs_prior	24
prep_mat_exp	25
proposal_5pars_root_bounds	26
proposal_nclades_plus_3_pars	26
reformat_multiclade_results	27
Sim_FPK	28
trans_from_fixed	29
Uncertainty_FPK	30
VectorPos_bounds	31

Index	32
--------------	-----------

BBMV-package	<i>Models for Continuous Traits Evolving in Macroevolutionary Landscapes of any Shape</i>
--------------	---

Description

Provides a set of functions to fit general macroevolutionary models for continuous traits evolving in adaptive landscapes of any shape. This package implements the Fokker-Planck-Kolmogorov model (FPK), in which the trait evolves under random diffusion but is also subject to a force that pulls it towards specific values - this force can be of any shape. FPK has a version in which hard reflective bounds exist at the extremes of the trait interval: this second model is called BBMV.

Details

Package:	BBMV
Type:	Package
Title:	Models for Continuous Traits Evolving in Macroevolutionary Landscapes of any Shape
Version:	2.1
Date:	2018-04-23
Author:	Florian C. Boucher
Maintainer:	Florian C. Boucher <flofloboucher@gmail.com>
Depends:	R (>= 3.1.0), ape
Suggests:	coda, geiger
Description:	Provides a set of functions to fit general macroevolutionary models for continuous traits evolving in adaptive
License:	GPL-2

Index of help topics:

ACE_FPK	Ancestral Character Estimation
BBMV-package	Models for Continuous Traits Evolving in Macroevolutionary Landscapes of any Shape
ConvProp_bounds	Convolution of the diffusion matrix with the trait density vector.
DiffMat_backwards	Diffusion matrix building

DiffMat_forward	Diffusion matrix building
FPK_sim_traitgram	Simulations with traitgram
FormatTree_bounds	Tree formatting.
LogLik_bounds	Likelihood of the FPK model
MH_MCMC_FPK	MCMC estimation
MH_MCMC_FPK_multiclades	MCMC estimation on multiple clades
Sim_FPK	Simulation of the BBM+V process.
Uncertainty_FPK	Parameter uncertainty
VectorPos_bounds	Discretization of a continuous trait value into a probability vector.
charac_time	Characteristic time measurement
find.mle_FPK	Maximum-likelihood estimation
find.mle_FPK_multiple_clades_same_V_different_sig2	Maximum-likelihood estimation
fit_FPK_multiple_clades_different_V_different_sig2	Fit independent models in several clades.
get.landscape.FPK	Plot macroevolutionary landscapes estimated by the FPK or BBM+V models
get.landscape.FPK.MCMC	Plot posterior distribution of macroevolutionary landscapes.
lnL_FPK	Creation of the likelihood function
lnL_FPK_multiclades_same_V_different_sig2	Likelihood functions for multiple clades
log_prior_5pars_root_bounds	Prior function.
log_prior_nclades_plus_3_pars	Prior function.
posterior_vs_prior	Posterior vs. prior comparison for the FPK model.
prep_mat_exp	Matrix exponential.
proposal_5pars_root_bounds	Parameter update for the MCMC function
proposal_nclades_plus_3_pars	Parameter update for the multiclade MCMC function
reformat_multiclade_results	Format the output of a multiclade fit
trans_from_fixed	Linear transformations

Author(s)

Florian C. Boucher Maintainer: Florian C. Boucher <flofloboucher@gmail.com>

References

Inferring bounded evolution in phenotypic characters from phylogenetic comparative data. F.C. Boucher and V. Demery. *Systematic Biology*, 65, 651-661, 2016

A general model for estimating macroevolutionary landscapes from phylogenetic comparative data. F.C. Boucher, V. Demery, E. Conti, L. J. Harmon and J. Uyeda. *Systematic Biology*, syx075, <https://doi.org/10.1093/sysbio/syx075>

ACE_FPK	<i>Ancestral Character Estimation</i>
---------	---------------------------------------

Description

Function to perform Ancestral Character Estimation under the FPK (or BBM+V) model

Usage

```
ACE_FPK(fit, specific.point = NULL)
```

Arguments

fit	An FPK model fit, as returned by find.mle_FPK .
specific.point	If set to NULL (the default), then the function will produce an ACE at all internal nodes in the tree. Alternatively, specific.point can be used to ask for an ACE at any specific point in the tree (i.e., not a node): specific.point must then be a vector with three elements: c(parent_node,child_node,time_from_start_of_branch).

Value

For each internal node, the function returns a table giving the probability density of the trait. The first column gives all possible trait values on the discretized trait grid, and the second the probability density at each of these points. If only a specific.point was asked, the function only returns one such table.

Author(s)

F. C. Boucher

charac_time	<i>Characteristic time measurement</i>
-------------	--

Description

Calculate the characteristic time it takes for the FPK process to reach its stationary distribution.

Usage

```
charac_time(Npts, fit)
```

Arguments

Npts	The number of points used in the discretization procedure.
fit	A FPK model fit, as returned by find.mle_FPK .

Value

The function returns the characteristic time of the process as a numeric value.

Author(s)

F. C. Boucher

ConvProp_bounds

*Convolution of the diffusion matrix with the trait density vector.***Description**

Internal function used for likelihood calculation and simulation.

Usage

ConvProp_bounds(X, t, prep_mat)

Arguments

X	A trait density vector.
t	The time over which to do the convolution (usually the length of one branch).
prep_mat	The diagonalized diffusion matrix.

Author(s)

F. C. Boucher

DiffMat_backwards

*Diffusion matrix building***Description**

Internal function that builds the discretized diffusion matrix of the FPK process going backwards in time (for likelihood calculations)

Usage

DiffMat_backwards(V)

Arguments

V	A vector giving the values of the evolutionary potential (V) at each point in the gridded trait interval.
---	---

Author(s)

F. C. Boucher

DiffMat_forward	<i>Diffusion matrix building</i>
-----------------	----------------------------------

Description

Internal function that builds the discretized diffusion matrix of the FPK process going forward in time (for simulations)

Usage

```
DiffMat_forward(V)
```

Arguments

V	A vector giving the values of the evolutionary potential (V) at each point in the gridded trait interval.
---	---

Author(s)

F.C. Boucher

find.mle_FPK	<i>Maximum-likelihood estimation</i>
--------------	--------------------------------------

Description

Find the maximum-likelihood estimate of the FPK model.

Usage

```
find.mle_FPK(model, method = "Nelder-Mead", init.optim = NULL, safe = F)
```

Arguments

model	An FPK or BBMV model, as generated by lnL_FPK or lnL_BBMV .
method	The optimization routine to be used: can be either "Nelder-Mead" (the default) or "L-BFGS-B". See the documentation of the optim function for more details. From our experience, "Nelder-Mead" seems to produce better results.
init.optim	A vector of initial values for model parameters to start the optimization algorithm. If left NULL (as is by default), the function chooses a reasonable starting point, but you might want to play around with it.
safe	If safe is set to TRUE, the function runs three different optimizations starting with different values of the rate of evolution (sigma). This can prove useful in difficult cases. Default to FALSE for a single optimization (which is quicker).

Value

A list with the following elements:

lnL	the log-likelihood of the model
aic	the Akaike Information Criterion of the model
k	the number of parameters of the model
par	a list of the MLEs of model parameters
par_fixed	a list with the parameters that were fixed. This includes the bounds use to discretize the model and eventually some of the parameters describing the shape of the macroevolutionary landscape.
root	A table giving the probability density of the trait at the root of the tree. The first column gives all possible trait values on the discretized trait grid, and the second the probability density at each of these points.
convergence	Convergence code returned by optim. 0 indicates successful convergence. For other values see the help of the optim function.
message	Convergence message returned by optim. See the help of the optim function.
tree	the tree used as input
trait	the trait vector used as input
Npts	the number of points used to discretize trait space.

Author(s)

F. C. Boucher

Examples

```
## Not run:
# Simulate data: tree + continuous trait
library(geiger)
tree=sim.bdtree(stop='taxa',n=10) # tree with few tips for quick tests
tree$edge.length=100*tree$edge.length/max(branching.times(tree)) # rescale the tree
# Simulate trait evolving on a macroevolutionary landscape with two peaks of equal heights
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating
# they are just here for technical purposes but are not reached
V6=10*(x^4-0.5*(x^2)+0.*x) # this is the evolutionary potential: it has two wells
TRAIT= Sim_FPK(tree,x0=0,V=V6,sigma=10,bounds=c(-5, 5))
# fit the FPK model:
ll_FPK4=lnL_FPK(tree,TRAIT,Npts=25,a=NULL,b=NULL,c=NULL) # the full model
fit4=find.mle_FPK(model=ll_FPK4)

## End(Not run)
```

```
find.mle_FPK_multiple_clades_same_V_different_sig2
```

Maximum-likelihood estimation

Description

Maximum-likelihood estimation of the FPK model on multiple clades at once.

Usage

```
find.mle_FPK_multiple_clades_same_V_different_sig2(model,
  method = "Nelder-Mead", init.optim = NULL)
find.mle_FPK_multiple_clades_same_V_same_sig2(model,
  method = "Nelder-Mead", init.optim = NULL)
```

Arguments

model	An FPK or BBMV model fitted to multiple clades, as generated by lnl_FPK_multiclades_same_V_different_sig2 , lnl_BBMV_multiclades_same_V_different_sig2 , lnl_BBMV_multiclades_same_V_same_sig2 , or lnl_FPK_multiclades_same_V_same_sig2 .
method	The optimization routine to be used: can be either "Nelder-Mead" (the default) or "L-BFGS-B". See the documentation of the optim function for more details. From our experience, "Nelder-Mead" seems to produce better results.
init.optim	A vector of initial values for model parameters to start the optimization algorithm. If left NULL (as is by default), the function chooses a reasonable starting point, but you might want to play around with it.

Author(s)

F. C. Boucher

Examples

```
## Not run:
# We first create a potential that we will use to simulate trait evolution
# It has two peaks of very unequal heights
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating
a=8 ; b=-4 ; c=1
V6=a*x^4+b*(x^2)+c*x
step_size=(max(bounds)-min(bounds))/(100-1)
V6_norm=exp(-V6)/sum(exp(-V6)*step_size) # the step size on the grid
par(mfrow=c(1,1))
plot(V6_norm,type='l')

# Now we simulate a tree and a continuous trait for 3 independent clades.
#The trait evolves in the same macroevolutionary landscape but with different evolutionary rates.
tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=1,bounds=bounds)
tree1=tree ; TRAIT1=TRAIT
```



```

tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=0.5,bounds=bounds)
tree2=tree ; TRAIT2=TRAIT

tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=0.1,bounds=bounds)
tree3=tree ; TRAIT3=TRAIT
rm(tree) ; rm(TRAIT)

TREES=list(tree1,tree2,tree3)
TRAITS=list(TRAIT1,TRAIT2,TRAIT3)

# Fit the FPK model using ML
testbFPK4=lnl_FPK_multiclades_same_V_different_sig2(trees=TREES,
  traits=TRAITS,a=NULL,b=NULL,c=NULL,Npts=50)
fitbFPK4=find.mle_FPK_multiple_clades_same_V_different_sig2(model=testbFPK4,
  method='Nelder-Mead',init.optim=NULL)

## End(Not run)

```

fit_FPK_multiple_clades_different_V_different_sig2

Fit independent models in several clades.

Description

This function is a wrapper for functions that fit the FPK or BBMv model to a single clade that does it repetitively over several clades.

Usage

```

fit_FPK_multiple_clades_different_V_different_sig2(trees, traits,
  a = NULL, b = NULL, c = NULL, Npts = 50, method = "Nelder-Mead", init.optim = NULL)
fit_BBMV_multiple_clades_different_V_different_sig2(trees, traits, bounds,
  a = NULL, b = NULL, c = NULL, Npts = 50, method = "Nelder-Mead", init.optim = NULL)

```

Arguments

trees	A list of phylogenetic trees in 'phylo' format, one per clade.
traits	A list of trait vectors for species in each clade. Should be in the same order as trees.
bounds	The two bounds that constrain trait values when fitting the BBMv model. Specified by a numeric vector containing the minimum and maximum bound of the trait interval as the first and second element, respectively.
a	The value of the x^4 term in the evolutionary potential. If set to NULL (the default), this parameter will be estimated. If a numeric value is provided, this parameter will be fixed to the value specified.
b	The value of the quadratic term in the evolutionary potential. If set to NULL (the default), this parameter will be estimated. If a numeric value is provided, this parameter will be fixed to the value specified.

c	The value of the linear term in the evolutionary potential. If set to NULL (the default), this parameter will be estimated. If a numeric value is provided, this parameter will be fixed to the value specified.
Npts	The number of points used in the discretization procedure.
method	The optimization routine to be used: can be either "Nelder-Mead" (the default) or "L-BFGS-B". See the documentation of the optim function for more details. From our experience, "Nelder-Mead" seems to produce better results.
init.optim	A vector of initial values for model parameters to start the optimization algorithm. If left NULL (as is by default), the function chooses a reasonable starting point, but you might want to play around with it.

Author(s)

F. C. Boucher

Examples

```
## Not run:
# We first create a potential that we will use to simulate trait evolution
# It has two peaks of very unequal heights
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating
a=8 ; b=-4 ; c=1
V6=a*x^4+b*(x^2)+c*x
step_size=(max(bounds)-min(bounds))/(100-1)
V6_norm=exp(-V6)/sum(exp(-V6)*step_size) # the step size on the grid
par(mfrow=c(1,1))
plot(V6_norm,type='l')

# Now we simulate a tree and a continuous trait for 3 independent clades.
tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=1,bounds=bounds)
tree1=tree ; TRAIT1=TRAIT

tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=0.5,bounds=bounds)
tree2=tree ; TRAIT2=TRAIT

tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=0.1,bounds=bounds)
tree3=tree ; TRAIT3=TRAIT
rm(tree) ; rm(TRAIT)

TREES=list(tree1,tree2,tree3)
TRAITS=list(TRAIT1,TRAIT2,TRAIT3)

# Fit the FPK model using ML
fitmFPK4=fit_FPK_multiple_clades_different_V_different_sig2(trees=TREES,
  traits=TRAITS,a=NULL,b=NULL,c=NULL,Npts=50)

## End(Not run)
```

FormatTree_bounds	<i>Tree formatting.</i>
-------------------	-------------------------

Description

Internal function used for likelihood calculation and simulation.

Usage

```
FormatTree_bounds(tree, trait, V, bounds)
```

Arguments

tree	A phylogenetic tree in phylo format.
trait	A vector of traits at the tips of the tree or a list with vectors of multiple measurements for each tip.
V	A vector giving the evolutionary potential.
bounds	A vector of bounds of the trait interval.

Author(s)

F. C. Boucher

FPK_sim_traitgram	<i>Simulations with traitgram</i>
-------------------	-----------------------------------

Description

Simulates a trait evolving according to the FPK model and also plots evolution along branches of this tree using a traitgram.

Usage

```
FPK_sim_traitgram(tree, x0, a, b, c, bounds, sigsq, time_step, res.x = 200,
  ylim.plot = NULL, return.trait = FALSE)
```

Arguments

tree	The phylogenetic tree on which to simulate the trait evolving.
x0	The initial value of the trait (at the root of the tree).
a	The coefficient for the x^4 term of the potential.
b	The coefficient for the quadratic term of the potential.
c	The coefficient for the linear term of the potential.
bounds	The bounds on the trait interval.
sigsq	The evolutionary rate.
time_step	The time step for incremental simulations (should be smaller than the shortest branch in the tree).

res.x	The number of points to use for discretizing the trait interval.
ylim.plot	The y limits of the plot. If left to NULL, the bounds of the trait interval will be used, but you might want to zoom in a bit more if the bounds are not reached.
return.trait	If set to TRUE, the function returns a named vector of trait values at the tips of the tree.

Details

The function is slower than [Sim_FPK](#) since it simulates step by step along branches. It should be used to visualize trait evolution, but [Sim_FPK](#) should be preferred for quick simulations.

Value

The function is mainly designed to produce a plot, but eventually returns a named vector of trait values at the tips of the tree.

Author(s)

F. C. Boucher

See Also

[Sim_FPK](#)

get.landscape.FPK	<i>Plot macroevolutionary landscapes estimated by the FPK or BBM+V models</i>
-------------------	---

Description

Plots a line representing the adaptive landscape estimated in a BBM+V or an FPK model.

Usage

```
get.landscape.FPK(fit, Npts = 100, main = "Macroevoolutionary landscape"
, ylab = "N.exp(-V)", xlab = "Trait", xlim = NULL, ylim = NULL)
add.ML.landscape.FPK(fit,Npts=100,COLOR=1,LTY='dashed')
```

Arguments

fit	An FPK model fit, as returned by find.mle_FPK .
Npts	The number of points used to discretize the trait interval for plotting.
main	Title for the plot.
ylim	The upper limit of the plotting region when multiple adaptive landscapes are plotted together.
xlim	The limits of the x-axis.
ylab	Label of the y-axis.
xlab	Label of the x-axis.
COLOR	The color of the line when added to a plot of the posterior of a MCMC run.
LTY	The type of the line when added to a plot of the posterior of a MCMC run.

Value

A plot of the adaptive landscape across the trait interval.

Author(s)

F. C. Boucher

Examples

```
## Not run:
# Simulate data: tree + continuous trait
library(geiger)
tree=sim.bdtree(stop='taxa',n=10) # tree with few tips for quick tests
tree$edge.length=100*tree$edge.length/max(branching.times(tree)) # rescale the tree
# Simulate trait evolving on a macroevolutionary landscape with two peaks of equal heights
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating
V6=10*(x^4-0.5*(x^2)+0.*x) # this is the evolutionary potential: it has two wells
TRAIT= Sim_FPK(tree,x0=0,V=V6,sigma=10,bounds=c(-5, 5))
# fit the FPK model:
ll_FPK4=lnL_FPK(tree,TRAIT,Npts=25,a=NULL,b=NULL,c=NULL) # the full model
fit4=find.mle_FPK(model=ll_FPK4)
# Plot the landscape estimated
get.landscape.FPK(fit=fit4)

## End(Not run)
```

get.landscape.FPK.MCMC

Plot posterior distribution of macroevolutionary landscapes.

Description

The function plots the median value of the macroevolutionary landscape across the posterior in a solid line and draws a polygon that stretches between two quantiles of the posterior.

Usage

```
get.landscape.FPK.MCMC(chain, bounds, Npts = 100, burnin = 0.1,
  probs.CI = c(0.05, 0.95), COLOR_MEDIAN = "red", COLOR_FILL = "red",
  transparency = 0.3, main = "Macroevoolutionary landscapes MCMC",
  ylab = "N.exp(-V)", xlab = "Trait", xlim = NULL, ylim = NULL)
```

Arguments

chain	An data.frame object representing the output of an MCMC chain, as obtained by MH_MCMC_FPK .
bounds	The bounds on the trait interval
Npts	The number of points used in the discretization procedure.
burnin	The percentage of generations discarded as burnin.

probs.CI	A vector of the two quantiles of the posterior distribution between which samples should be considered.
COLOR_MEDIAN	The color used to plot the median macroevolutionary landscape across the posterior.
COLOR_FILL	The color used to plot the polygon that stretches between the two quantiles of the posterior.
transparency	The transparency used for plotting the polygon
main	Title of the graph.
ylab	y label of the graph.
xlab	X label of the graph.
xlim	
ylim	

Author(s)

F.C. Boucher

See Also[MH_MCMC_FPK](#)**Examples**

```
## Not run:
# Simulate data: tree + continuous trait
library(geiger)
tree=sim.bdtree(stop='taxa',n=10) # tree with few tips for quick tests
tree$edge.length=100*tree$edge.length/max(branching.times(tree)) # rescale the tree
# Simulate trait evolving on a macroevolutionary landscape with two peaks of equal heights
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating: for technical purposes only
V6=10*(x^4-0.5*(x^2)+0.*x) # this is the evolutionary potential: it has two wells
TRAIT= Sim_FPK(tree,x0=0,V=V6,sigma=10,bounds=c(-5, 5))
# Run a MCMC chain to fit the FPK model
MCMC=MH_MCMC_FPK(tree,trait=TRAIT,bounds=c(5,5),Nsteps=10000,record_every=100,
  plot_every=100,Npts=20,pars_init=c(0,-4,-4,0,1),prob_update=c(0.2,0.25,0.25,0.25,0.05),
  verbose=TRUE,plot=TRUE,save_to='MCMC_FPK_test.Rdata',save_every=100,
  type_priors=c(rep('Normal',4),'Uniform'),
  shape_priors=list(c(0,10),c(0,10),c(0,10),c(0,10),NA),proposal_type='Uniform',
  proposal_sensitivity=c(0.1,0.1,0.1,0.1,1),prior.only=F)
get.landscape.FPK.MCMC(chain=MCMC,bounds=c(5,5),Npts=100,burnin=0.1,
  probs.CI=c(0.025,0.975),COLOR_MEDIAN='red',COLOR_FILL='red',transparency=0.3,
  main='Macroevolutionary landscapes MCMC',ylab='N.exp(-V)',xlab='Trait',
  xlim=NULL,ylim=NULL)

## End(Not run)
```

lnL_FPK

*Creation of the likelihood function***Description**

Functions that builds the likelihood function of the FPK or BBMV model

Usage

```
lnL_FPK(tree, trait, a = NULL, b = NULL, c = NULL, Npts)
lnL_BBMV(tree, trait, bounds, a = NULL, b = NULL, c = NULL, Npts)
```

Arguments

tree	A phylogenetic tree in 'phylo' format
trait	A named vector of trait values for the tips of the tree. It should match tip labels in the phylogeny. Alternatively, a named list with one element per tip in the tree, each element being in turn a numeric vector with multiple measurements of the trait for this tip.
bounds	The two bounds that constrain trait values when fitting the BBMV model. Specified by a numeric vector containing the minimum and maximum bound of the trait interval as the first and second element, respectively.
a	The value of the x^4 term in the evolutionary potential. If set to NULL (the default), this parameter will be estimated. If a numeric value is provided, this parameter will be fixed to the value specified.
b	The value of the quadratic term in the evolutionary potential. If set to NULL (the default), this parameter will be estimated. If a numeric value is provided, this parameter will be fixed to the value specified.
c	The value of the linear term in the evolutionary potential. If set to NULL (the default), this parameter will be estimated. If a numeric value is provided, this parameter will be fixed to the value specified.
Npts	The number of points used in the discretization procedure.

Value

A list of several items, including the data and model call, but most importantly the likelihood function (\$fun element).

Author(s)

F.C. Boucher

See Also

[find.mle_FPK](#)

Examples

```
## Not run:
# Simulate data: tree + continuous trait
library(geiger)
tree=sim.bdtree(stop='taxa',n=10) # tree with few tips for quick tests
tree$edge.length=100*tree$edge.length/max(branching.times(tree)) # rescale the tree
# Simulate trait evolving on a macroevolutionary landscape with two peaks of equal heights
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating
V6=10*(x^4-0.5*(x^2)+0.*x) # this is the evolutionary potential: it has two wells
TRAIT= Sim_FPK(tree,x0=0,V=V6,sigma=10,bounds=c(-5, 5))
# create a likelihood function for the FPK model:
ll_FPK4=lnl_FPK(tree,TRAIT,Npts=25,a=NULL,b=NULL,c=NULL) # the full model

## End(Not run)
```

```
lnl_FPK_multiclades_same_V_different_sig2
```

Likelihood functions for multiple clades

Description

These functions create likelihood functions of the FPK or BBMV model over multiple, independent, clades.

Usage

```
lnl_FPK_multiclades_same_V_different_sig2(trees, traits,
  a = NULL, b = NULL, c = NULL, Npts = 50)
lnl_FPK_multiclades_same_V_same_sig2(trees, traits,
  a = NULL, b = NULL, c = NULL, Npts = 50)
lnl_BBMV_multiclades_same_V_different_sig2(trees, traits,bounds,
  a = NULL, b = NULL, c = NULL, Npts = 50)
lnl_BBMV_multiclades_same_V_same_sig2(trees, traits,bounds,
  a = NULL, b = NULL, c = NULL, Npts = 50)
```

Arguments

trees	A list of phylogenetic trees in 'phylo' format, one per clade.
traits	A list of trait vectors for species in each clade. Should be in the same order as trees.
bounds	The two bounds that constrain trait values when fitting the BBMV model. Specified by a numeric vector containing the minimum and maximum bound of the trait interval as the first and second element, respectively.
a	The value of the x^4 term in the evolutionary potential. If set to NULL (the default), this parameter will be estimated. If a numeric value is provided, this parameter will be fixed to the value specified.
b	The value of the quadratic term in the evolutionary potential. If set to NULL (the default), this parameter will be estimated. If a numeric value is provided, this parameter will be fixed to the value specified.

c	The value of the linear term in the evolutionary potential. If set to NULL (the default), this parameter will be estimated. If a numeric value is provided, this parameter will be fixed to the value specified.
Npts	The number of points used in the discretization procedure.

Author(s)

F. C. Boucher

See Also
[find.mle_FPK_multiple_clades_same_V_different_sig2](#) [find.mle_FPK_multiple_clades_same_V_same_sig2](#)
Examples

```
## Not run:
# We first create a potential that we will use to simulate trait evolution
# It has two peaks of very unequal heights
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating
a=8 ; b=-4 ; c=1
V6=a*x^4+b*(x^2)+c*x
step_size=(max(bounds)-min(bounds))/(100-1)
V6_norm=exp(-V6)/sum(exp(-V6)*step_size) # the step size on the grid
par(mfrow=c(1,1))
plot(V6_norm,type='l')

# Now we simulate a tree and a continuous trait for 3 independent clades.
tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=1,bounds=bounds)
tree1=tree ; TRAIT1=TRAIT

tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=0.5,bounds=bounds)
tree2=tree ; TRAIT2=TRAIT

tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=0.1,bounds=bounds)
tree3=tree ; TRAIT3=TRAIT
rm(tree) ; rm(TRAIT)

TREES=list(tree1,tree2,tree3)
TRAITS=list(TRAIT1,TRAIT2,TRAIT3)

# Fit the FPK model using ML
testbFPK4=lnl_FPK_multiclades_same_V_different_sig2(trees=TREES,
  traits=TRAITS,a=NULL,b=NULL,c=NULL,Npts=50)
fitbFPK4=find.mle_FPK_multiple_clades_same_V_different_sig2(model=testbFPK4,
  method='Nelder-Mead',init.optim=NULL)

## End(Not run)
```

LogLik_bounds	<i>Likelihood of the FPK model</i>
---------------	------------------------------------

Description

Internal functions use to calculate the likelihood of the FPK model, used in ML and MCMC estimation.

Usage

```
LogLik_bounds(tree_formatted, dCoeff, dMat, bounds)
LogLik_bounds_est_root(tree, trait, dCoeff, V, x0_pos, bounds)
```

Arguments

tree_formatted	A formatted tree as returned by FormatTree_bounds .
dCoeff	The diffusion coefficient.
dMat	The discretized diffusion matrix.
V	A numeric vector giving the value of the evolutionary potential in each point of the trait grid.
bounds	A vector giving the bounds of the trait interval.
x0_pos	The value of the trait at the root of the tree.
tree	A phylogenetic tree in phylo format.
trait	A trait vector for tip taxa.

Author(s)

F. C. Boucher

log_prior_5pars_root_bounds	<i>Prior function.</i>
-----------------------------	------------------------

Description

Internal function that calculates the log prior, used in MCMC estimation of the BBM+V model.

Usage

```
log_prior_5pars_root_bounds(type = c(rep("Normal", 4), "Uniform") , shape =
  list(c(0, 10), c(0, 10), c(0, 10), c(0, 10), NA), pars, Npts)
```

Arguments

type	A vector giving the type of prior for each parameter.
shape	A list giving the shape of the prior for each parameter.
pars	The parameter values at which the prior should be evaluated.
Npts	The number of points on the grid.

Author(s)

F. C. Boucher

log_prior_nclades_plus_3_pars
Prior function.

Description

Internal function that calculates the log prior, used in MCMC estimation of the BBM+V model.

Usage

```
log_prior_nclades_plus_3_pars(type = NULL, shape = NULL, pars, n_clades)
```

Arguments

type	A vector giving the type of prior for each parameter.
shape	A list giving the shape of the prior for each parameter.
pars	The parameter values at which the prior should be evaluated.
n_clades	The number of clades included in the multiclade analysis.

Author(s)

F. C. Boucher

MH_MCMC_FPK *MCMC estimation*

Description

The function estimates the parameters of the BBM+V model using an MCMC chain with the Metropolis Hastings algorithm and a Gibbs sampler.

Usage

```
MH_MCMC_FPK(tree, trait, bounds, Nsteps = 5e+05, record_every = 100, plot_every = 500,
  Npts = 50, pars_init = c(0, 0, 0, 0, 25), prob_update = c(0.2, 0.2, 0.2, 0.2, 0.2),
  verbose = TRUE, plot = TRUE, save_to = "MCMC_FPK_test.Rdata", save_every = 10000,
  type_priors = c(rep("Normal", 4), "Uniform"),
  shape_priors = list(c(0, 10), c(0, 10), c(0, 10), c(0, 10), NA),
  proposal_type = "Uniform", proposal_sensitivity = c(0.1, 0.1, 0.1, 0.1, 1),
  prior.only = F, burnin.plot = 0.1)
```

Arguments

tree	A phylogenetic tree in phylo format.
trait	A named vector of trait values for the tips of the tree. It should match tip labels in the phylogeny.
bounds	A vector with two elements giving the bounds on the trait interval.
Nsteps	The number of generations in the MCMC chain.
record_every	The frequency used for sampling the MCMC chain.
plot_every	The frequency at which the chain is plotted (if plot=TRUE).
Npts	The number of points on the grid between the bounds.
pars_init	A vector giving the initial parameters for starting the algorithm, which correspond to the following: $c(\log(\text{sig}^2/2), a, b, c, x_0)$.
prob_update	A vector giving the relative frequencies of update of the different parameters of the model.
verbose	If TRUE, will print some generations of the chain to the screen.
plot	If TRUE, the chain is plotted from time to time.
save_to	The path to the file where the chain is saved (can be useful in case the chain crashes).
save_every	Sets how often the chain is saved.
type_priors	A character vector specifying the type of priors used. Either 'Uniform' or 'Normal'. See Details.
shape_priors	A list that gives the shape for each prior. See Details.
proposal_type	The type of proposal function, only 'Uniform' is available (the default).
proposal_sensitivity	A numeric vector specifying the width of the uniform proposal for each parameter. See Details.
prior.only	Default to FALSE for estimation of the posterior. If TRUE, the likelihood is not evaluated: this is mostly useful for internal test of the Gibbs sampler.
burnin.plot	The percentage of samples considered as burnin and thus not shown on the trace plot that the function produces.

Details

When specifying initial parameters yourself, be careful since x_0 is actually the index of the point on the grid (between 1 and N_{pts_int}), not the actual root value. Also the first parameter is the diffusion coefficient ($\log(\text{sig}^2/2)$), not the evolutionary rate (sig^2). Finally, be careful that the bounds you propose must contain all trait values in your dataset.

Priors can be either 'Normal' (preferred) or 'Uniform' for $\log(\text{sig}^2/2)$, a , b and c . The only option for x_0 is a discrete uniform prior, specified by 'Uniform'.

Each element of the `shape_priors` list should be a vector giving $c(\text{mean}, \text{sd})$ for normal priors and $c(\text{min}, \text{max})$ for continuous uniform priors. The shape is not specified for the root prior (it is set as 'NA' by default), since it is fixed to be discrete uniform on the grid.

Elements of the `proposal_sensitivity` vector can be any positive number for continuously varying parameters: $c(\log(\text{sig}^2/2), a, b, c)$. Default values should often be a good start. Only integer numbers are possible for x_0 and give how many steps at a time can be travelled on the trait grid when updating these parameters. It is recommended to keep it to 1, as it is by default.

Value

A matrix of numeric values giving values of all parameters, the likelihood, prior and posterior at each generation sampled in the MCMC chain (one row per sample taken). The matrix has the following columns:

step	The number of the generation sampled.
sigsq	The evolutionary rate.
a	The coefficient of the x^4 term of the evolutionary potential.
b	The coefficient of the x^2 term of the evolutionary potential.
c	The coefficient of the x term of the evolutionary potential.
root	The value of the trait at the root of the tree.
lnprior	The logarithm of the prior.
lnlik	The logarithm of the likelihood.
quasi-lnpost	The logarithm of the (unnormalized) posterior.
Acceptance	Whether the proposed MCMC move was accepted (1) or not (0).
Par_updated	Which parameter was updated in this generation.

Author(s)

F. C. Boucher

Examples

```
## Not run:
# Simulate data: tree + continuous trait
library(geiger)
tree=sim.bdtree(stop='taxa',n=10) # tree with few tips for quick tests
tree$edge.length=100*tree$edge.length/max(branching.times(tree)) # rescale the tree
# Simulate trait evolving on a macroevolutionary landscape with two peaks of equal heights
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating: for technical purposes only
V6=10*(x^4-0.5*(x^2)+0.*x) # this is the evolutionary potential: it has two wells
TRAIT= Sim_FPK(tree,x0=0,V=V6,sigma=10,bounds=c(-5, 5))
# Run a MCMC chain to fit the FPK model
MCMC=MH_MCMC_FPK(tree,trait=TRAIT,bounds=c(5,5),Nsteps=10000,record_every=100,
  plot_every=100,Npts=20,pars_init=c(0,-4,-4,0,1),prob_update=c(0.2,0.25,0.25,0.25,0.05),
  verbose=TRUE,plot=TRUE,save_to='MCMC_FPK_test.Rdata',save_every=100,
  type_priors=c(rep('Normal',4),'Uniform'),
  shape_priors=list(c(0,10),c(0,10),c(0,10),c(0,10),NA),proposal_type='Uniform',
  proposal_sensitivity=c(0.1,0.1,0.1,0.1,1),prior.only=F)

## End(Not run)
```

MH_MCMC_FPK_multiclades

MCMC estimation on multiple clades

Description

This function estimates parameter of the FPK model on multiple clades at once, making the assumption that they share the same macroevolutionary landscape but have different rates of evolution.

Usage

```
MH_MCMC_FPK_multiclades(trees, traits, bounds, Nsteps = 5e+05, record_every = 100,
  plot_every = 500, Npts = 50, pars_init = NULL, prob_update = NULL, verbose = TRUE,
  plot = TRUE, save_to = "MCMC_FPK_test.Rdata", save_every = 10000, type_priors = NULL,
  shape_priors = NULL, proposal_type = "Normal", proposal_sensitivity = NULL,
  prior.only = F, burnin.plot = 0.1)
```

Arguments

trees	A list of phylogenetic trees in 'phylo' format, one per clade.
traits	A list of trait vectors for species in each clade. Should be in the same order as trees.
bounds	The two bounds that constrain trait values when fitting the BBMV model. Specified by a numeric vector containing the minimum and maximum bound of the trait interval as the first and second element, respectively.
Nsteps	The number of steps in the MCMC chain.
record_every	How often to record a generation in the chain.
plot_every	How often to plot the trace of the chain.
Npts	The number of points used in the discretization procedure.
pars_init	The initial parameter values.
prob_update	A numeric vector with the relative probability of update of each parameter of the model.
verbose	If TRUE, prints generations to the screen.
plot	If TRUE, plots the trace of parameter values along iterations during the MCMC run.
save_to	The directory in which the chain should be saved.
save_every	How often to save the chain.
type_priors	The type of priors used, can be either normal (preferred) or uniform for log(sig ² /2), a, b and c, ; and can only be discrete uniform for x0.
shape_priors	A list that gives the shape for each prior. (mean,sd) for normal priors and (min,max) for continuous uniform priors. The shape is not specified for the root prior, since it is fixed to be discrete uniform on the grid.
proposal_type	The type of proposal function, only uniform is available so far.
proposal_sensitivity	The width of the uniform proposal. The entire value for x0 gives how many steps at a time can be travelled on the trait grid (better to keep it to 1)
prior.only	If TRUE, only the prior is explored but the likelihood is ignored. Default to false for estimation of the posterior.
burnin.plot	The frequency of samples that should be discarded as burnin in trace plots.

Details

When specifying initial parameters yourself, be careful since x_0 is actually the index of the point on the grid (between 1 and N_{pts_int}), not the actual root value. Also the first n parameter, n being the number of clades studied, are diffusion coefficients ($\log(\sigma^2/2)$), not evolutionary rates (σ^2). Finally, be careful that the bounds you propose must contain all trait values in your dataset.

Priors can be either 'Normal' (preferred) or 'Uniform' for $\log(\sigma^2/2)$, a , b and c . The only option for x_0 is a discrete uniform prior, specified by 'Uniform'.

Each element of the `shape_priors` list should be a vector giving $c(\text{mean}, \text{sd})$ for normal priors and $c(\text{min}, \text{max})$ for continuous uniform priors. The shape is not specified for the root prior (it is set as 'NA' by default), since it is fixed to be discrete uniform on the grid.

Elements of the `proposal_sensitivity` vector can be any positive number for continuously varying parameters: $c(\log(\sigma^2/2), a, b, c)$. Default values should often be a good start. Only integer numbers are possible for x_0 and give how many steps at a time can be travelled on the trait grid when updating these parameters. It is recommended to keep it to 1, as it is by default.

Value

A matrix of numeric values giving values of all parameters, the likelihood, prior and posterior at each generation sampled in the MCMC chain (one row per sample taken). The matrix has the following columns:

<code>step</code>	The number of the generation sampled.
<code>sigsq_clade_i</code>	The evolutionary rate, one column per clade.
<code>a</code>	The coefficient of the x^4 term of the evolutionary potential.
<code>b</code>	The coefficient of the x^2 term of the evolutionary potential.
<code>c</code>	The coefficient of the x term of the evolutionary potential.
<code>lnprior</code>	The logarithm of the prior.
<code>lnlik</code>	The logarithm of the likelihood.
<code>quasi-lnpost</code>	The logarithm of the (unnormalized) posterior.
<code>Acceptance</code>	Whether the proposed MCMC move was accepted (1) or not (0).
<code>Par_updated</code>	Which parameter was updated in this generation.

Author(s)

F. C. Boucher

Examples

```
## Not run:
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating
a=8 ; b=-4 ; c=1
V6=a*x^4+b*(x^2)+c*x
step_size=(max(bounds)-min(bounds))/(100-1)
V6_norm=exp(-V6)/sum(exp(-V6)*step_size)
par(mfrow=c(1,1))
plot(V6_norm,type='l')

# Now we simulate a tree and a continuous trait for 3 independent clades.
tree=sim.bdtree(stop='taxa',n=25) # tree with few tips for quick tests
```

```

tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=1,bounds=bounds)
tree1=tree ; TRAIT1=TRAIT

tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=0.5,bounds=bounds)
tree2=tree ; TRAIT2=TRAIT

tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=0.1,bounds=bounds)
tree3=tree ; TRAIT3=TRAIT
rm(tree) ; rm(TRAIT)

TREES=list(tree1,tree2,tree3)
TRAITS=list(TRAIT1,TRAIT2,TRAIT3)

# Fit the FPK model using ML:
# In all clades the macroevolutionary landscape is the same
#but they have different evolutionary rates
testbFPK4=lnl_FPK_multiclades_same_V_different_sig2(trees=TREES,
  traits=TRAITS,a=NULL,b=NULL,c=NULL,Npts=50)
fitbFPK4=find.mle_FPK_multiple_clades_same_V_different_sig2(model=testbFPK4,
  method='Nelder-Mead',init.optim=NULL)

# And now MCMC run
mcmc1=MH_MCMC_FPK_multiclades(trees=TREES,traits=TRAITS,
  bounds=fitmFPK4_SE$fits$fit_clade_1$par_fixed$bounds,Nsteps=10000,record_every=100,
  plot_every=200,Npts=25,pars_init=NULL,prob_update=NULL,verbose=TRUE,plot=TRUE,
  save_to='MCMC_FPK_test.Rdata',save_every=1000,type_priors=NULL,shape_priors=NULL,
  proposal_type='Normal',proposal_sensitivity=NULL,prior.only=F,burnin.plot=0.1)

get.landscape.FPK.MCMC(chain=mcmc1,bounds,Npts=100,burnin=0.1,probs.CI=c(0.25,0.75),
  COLOR_MEDIAN='red',COLOR_FILL='red',transparency=0.3,main='Macroevolutionary landscapes MCMC',
  ylab='N.exp(-V)',xlab='Trait',xlim=NULL,ylim=c(0,2))

## End(Not run)

```

posterior_vs_prior *Posterior vs. prior comparison for the FPK model.*

Description

Plots the posterior vs. prior distributions of parameters of the FPK model.

Usage

```
posterior_vs_prior(chain,param='a',burnin=0.2,type_prior='Normal',shape_prior=c(0,10))
```

Arguments

chain An data.frame object representing the output of an MCMC chain, as obtained by [MH_MCMC_FPK](#).

param	The parameter of the model for which we want to compare prior and posterior.
burnin	The percentage of generations discarded as burnin.
type_prior	A character specifying the type of prior used for this parameter.
shape_prior	A numeric vector giving the shape of the prior used for this parameter.

Author(s)

F.C. Boucher

See Also[MH_MCMC_FPK](#)**Examples**

```
## Not run:
# Simulate data: tree + continuous trait
library(geiger)
tree=sim.bdtree(stop='taxa',n=10) # tree with few tips for quick tests
tree$edge.length=100*tree$edge.length/max(branching.times(tree)) # rescale the tree
# Simulate trait evolving on a macroevolutionary landscape with two peaks of equal heights
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating: for technical purposes only
V6=10*(x^4-0.5*(x^2)+0.*x) # this is the evolutionary potential: it has two wells
TRAIT= Sim_FPK(tree,x0=0,V=V6,sigma=10,bounds=c(-5, 5))
# Run a MCMC chain to fit the FPK model
MCMC=MH_MCMC_FPK(tree,trait=TRAIT,bounds=c(5,5),Nsteps=10000,record_every=100,
  plot_every=100,Npts=20,pars_init=c(0,-4,-4,0,1),prob_update=c(0.2,0.25,0.25,0.25,0.05),
  verbose=TRUE,plot=TRUE,save_to='MCMC_FPK_test.Rdata',save_every=100,
  type_priors=c(rep('Normal',4),'Uniform'),
  shape_priors=list(c(0,10),c(0,10),c(0,10),c(0,10),NA),proposal_type='Uniform',
  proposal_sensitivity=c(0.1,0.1,0.1,0.1,1),prior.only=F)
get.landscape.FPK.MCMC(chain=MCMC,bounds=c(5,5),Npts=100,burnin=0.1,
  probs.CI=c(0.025,0.975),COLOR_MEDIAN='red',COLOR_FILL='red',transparency=0.3,
  main='Macroevolutionary landscapes MCMC',ylab='N.exp(-V)',xlab='Trait',
  xlim=NULL,ylim=NULL)
posterior_vs_prior(chain=MCMC,param='a',Npts=100,burnin=0.2,type_prior='Normal',shape_prior=c(0,10))

## End(Not run)
```

prep_mat_exp

*Matrix exponential.***Description**

Internal function used for likelihood calculation and simulation.

Usage

prep_mat_exp(dCoeff, dMat, bounds)

Arguments

dCoeff	The diffusion coefficient.
dMat	The diffusion matrix.
bounds	A vector with two bounds for the trait interval.

Author(s)

F. C. Boucher

proposal_5pars_root_bounds

Parameter update for the MCMC function

Description

Internal function that proposes parameter updates used in MCMC estimation of the BBMV model.

Usage

```
proposal_5pars_root_bounds(type = "Uniform", sensitivity, pars)
```

Arguments

type	The type of proposal function, only 'Uniform' is available (the default).
sensitivity	A numeric vector specifying the width of the uniform proposal for each parameter.
pars	The current parameters in the MCMC chain.

Author(s)

F. C. Boucher

proposal_nclades_plus_3_pars

Parameter update for the multiclade MCMC function

Description

Internal function that proposes parameter updates used in MCMC estimation of the BBMV model.

Usage

```
proposal_nclades_plus_3_pars(type = "Uniform", sensitivity, pars, n_clades)
```

Arguments

type	The type of proposal function, only 'Uniform' is available (the default).
sensitivity	A numeric vector specifying the width of the uniform proposal for each parameter.
pars	The current parameters in the MCMC chain.
n_clades	The number of clades under study.

Author(s)

F. C. Boucher

reformat_multiclade_results
*Format the output of a multiclade fit***Description**

This function takes the output of a multiclade fit and formats it as a list of model fits for each clade. Functions used to analyze single clade fits can then be used.

Usage

```
reformat_multiclade_results(fit)
```

Arguments

fit	A multiclade model fit, as returned by find.mle_FPK_multiple_clades_same_V_different_sig2 , find.mle_FPK_multiple_clades_same_V_same_sig2 , fit_BBMV_multiple_clades_different_V_different_sig2 or fit_FPK_multiple_clades_different_V_different_sig2 .
-----	---

Value

A list containing model fits for each clade, in the same format as the object returned by [find.mle_FPK](#).

Author(s)

F.C. Boucher

Examples

```
## Not run:
# We first create a potential that we will use to simulate trait evolution
# It has two peaks of very unequal heights
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating
a=8 ; b=-4 ; c=1
V6=a*x^4+b*(x^2)+c*x
step_size=(max(bounds)-min(bounds))/(100-1)
V6_norm=exp(-V6)/sum(exp(-V6)*step_size) # the step size on the grid
par(mfrow=c(1,1))
plot(V6_norm,type='l')
```

```

# Now we simulate a tree and a continuous trait for 3 independent clades.
tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=1,bounds=bounds)
tree1=tree ; TRAIT1=TRAIT

tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=0.5,bounds=bounds)
tree2=tree ; TRAIT2=TRAIT

tree=sim.bdtree(stop='taxa',n=25)
tree$edge.length=100*tree$edge.length/max(branching.times(tree))
TRAIT= Sim_FPK(tree,x0=0.5,V=V6,sigma=0.1,bounds=bounds)
tree3=tree ; TRAIT3=TRAIT
rm(tree) ; rm(TRAIT)

TREES=list(tree1,tree2,tree3)
TRAITS=list(TRAIT1,TRAIT2,TRAIT3)

# Fit the FPK model
testbFPK4=lnl_FPK_multiclades_same_V_different_sig2(trees=TREES,
  traits=TRAITS,a=NULL,b=NULL,c=NULL,Npts=50)
fitbFPK4=find.mle_FPK_multiple_clades_same_V_different_sig2(model=testbFPK4,
  method='Nelder-Mead',init.optim=NULL)
fits=reformat_multiclade_results(fitbFPK4)

## End(Not run)

```

Sim_FPK

Simulation of the BBM+V process.

Description

The function simulates a continuous trait evolving according to the FPK process along the branches of a phylogenetic tree.

Usage

```
Sim_FPK(tree, x0 = 0, V = rep(0, 100), sigma, bounds)
```

Arguments

tree	A phylogenetic tree in phylo format.
x0	The value of the trait at the root of the tree.
V	A vector giving the values of the evolutionary potential at each point of the discretized trait grid. Default is a flat potential, i.e. bounded Brownian Motion.
sigma	The square root of the diffusion rate.
bounds	A vector giving the values of the bounds of the trait interval.

Value

A numeric vector with values of the trait at the tips of the tree. Names correspond to tip labels in the tree.

Author(s)

F. C. Boucher

Examples

```
# Simulate data: tree + continuous trait
library(geiger)
tree=sim.bdtree(stop='taxa',n=20) # tree with few tips for quick tests
tree$edge.length=100*tree$edge.length/max(branching.times(tree)) # rescale the tree
# Simulate a trait evolving on the tree with a linear trend towards small values
TRAIT= Sim_FPK(tree,x0=0,V=seq(from=0,to=5,length.out=50),sigma=10,bounds=c(-5, 5))
```

trans_from_fixed

Linear transformations

Description

Internal function used to convert back and forth between the actual trait interval and [-1.5;1.5]

Usage

```
trans_from_fixed(x, bounds)
trans_to_fixed(x, bounds)
```

Arguments

x	A single value or vector of trait values.
bounds	The actual bounds on the trait interval

Value

A single value or vector of trait values transformed to the other interval.

Author(s)

F. C. Boucher

Uncertainty_FPK	<i>Parameter uncertainty</i>
-----------------	------------------------------

Description

This function plots likelihood profiles around the MLEs of parameters and returns 95% confidence intervals.

Usage

```
Uncertainty_FPK(fit, tree, trait, Npts = 50, effort_uncertainty = 100,
  scope_a = c(-10, 10), scope_b = c(-10, 10), scope_c = c(-10, 10))
```

Arguments

<code>fit</code>	An FPK model fit, as returned by find.mle_FPK .
<code>tree</code>	The phylogenetic tree.
<code>trait</code>	The named trait vector
<code>Npts</code>	The number of points used to discretize the trait interval.
<code>effort_uncertainty</code>	Determines the number of values at which the likelihood should be calculated for each parameter.
<code>scope_a</code>	Extreme values that should be investigated for parameter a.
<code>scope_b</code>	Extreme values that should be investigated for parameter b.
<code>scope_c</code>	Extreme values that should be investigated for parameter c.

Value

A list with 95% confidence intervals for all parameters.

Author(s)

F. C. Boucher

Examples

```
## Not run:
# Simulate data: tree + continuous trait
library(geiger)
tree=sim.bdtree(stop='taxa',n=10) # tree with few tips for quick tests
tree$edge.length=100*tree$edge.length/max(branching.times(tree)) # rescale the tree
# Simulate trait evolving on a macroevolutionary landscape with two peaks of equal heights
x=seq(from=-1.5,to=1.5,length.out=100)
bounds=c(min(x),max(x)) # the bounds we use for simulating: for technical purposes only
V6=10*(x^4-0.5*(x^2)+0.*x) # this is the evolutionary potential: it has two wells
TRAIT= Sim_FPK(tree,x0=0,V=V6,sigma=10,bounds=c(-5, 5))
# fit the FPK model:
ll_FPK4=lnL_FPK(tree,TRAIT,Npts=25,a=NULL,b=NULL,c=NULL) # the full model
fit4=find.mle_FPK(model=ll_FPK4)
# Measure uncertainty on model parameters
Uncertainty_FPK(fit=fit4,tree,trait=TRAIT,Npts=25,effort_uncertainty= 100,
```

```
scope_a=c(-1,10),scope_b=c(-5,5),scope_c=c(-2,2))  
## End(Not run)
```

VectorPos_bounds	<i>Discretization of a continuous trait value into a probability vector.</i>
------------------	--

Description

Internal function used for likelihood calculation and simulation.

Usage

```
VectorPos_bounds(x, V, bounds)
```

Arguments

x	A numeric value of the trait or a vector containing multiple measurements.
V	The evolutionary potential used
bounds	A vector with the values of both bounds.

Author(s)

F. C. Boucher

Index

*Topic **phylogenetic comparative methods ; evolution ; adaptation ; FPK model ; macroevolutionary landscape**

BBMV-package, [2](#)

ACE_FPK, [4](#)

add.ML.landscape.FPK
(get.landscape.FPK), [12](#)

BBMV (BBMV-package), [2](#)

BBMV-package, [2](#)

charac_time, [4](#)

ConvProp_bounds, [5](#)

DiffMat_backwards, [5](#)

DiffMat_forward, [6](#)

find.mle_FPK, [4](#), [6](#), [12](#), [15](#), [27](#), [30](#)

find.mle_FPK_multiple_clades_same_V_different_sig2,
[8](#), [17](#), [27](#)

find.mle_FPK_multiple_clades_same_V_same_sig2,
[17](#), [27](#)

find.mle_FPK_multiple_clades_same_V_same_sig2
(find.mle_FPK_multiple_clades_same_V_different_sig2),
[8](#)

fit_BBMV_multiple_clades_different_V_different_sig2,
[27](#)

fit_BBMV_multiple_clades_different_V_different_sig2
(fit_FPK_multiple_clades_different_V_different_sig2),
[9](#)

fit_FPK_multiple_clades_different_V_different_sig2,
[9](#), [27](#)

FormatTree_bounds, [11](#), [18](#)

FPK_sim_traitgram, [11](#)

get.landscape.FPK, [12](#)

get.landscape.FPK.MCMC, [13](#)

lnL_BBMV, [6](#)

lnL_BBMV (lnL_FPK), [15](#)

lnL_BBMV_multiclades_same_V_different_sig2,
[8](#)

lnL_BBMV_multiclades_same_V_different_sig2
(lnL_FPK_multiclades_same_V_different_sig2),
[16](#)

lnL_BBMV_multiclades_same_V_same_sig2,
[8](#)

lnL_BBMV_multiclades_same_V_same_sig2
(lnL_FPK_multiclades_same_V_different_sig2),
[16](#)

lnL_FPK, [6](#), [15](#)

lnL_FPK_multiclades_same_V_different_sig2,
[8](#), [16](#)

lnL_FPK_multiclades_same_V_same_sig2,
[8](#)

lnL_FPK_multiclades_same_V_same_sig2
(lnL_FPK_multiclades_same_V_different_sig2),
[16](#)

log_prior_5pars_root_bounds, [18](#)

log_prior_nclades_plus_3_pars, [19](#)

LogLik_bounds, [18](#)

LogLik_bounds_est_root (LogLik_bounds),
[18](#)

MH_MCMC_FPK, [13](#), [14](#), [19](#), [24](#), [25](#)
MH_MCMC_FPK_multiclades, [22](#)

optim, [6–8](#), [10](#)

posterior_vs_prior, [24](#)

reformat_exp, [25](#)

proposal_5pars_root_bounds, [26](#)

proposal_nclades_plus_3_pars, [26](#)

reformat_multiclade_results, [27](#)

Sim_FPK, [12](#), [28](#)

trans_from_fixed, [29](#)

trans_to_fixed (trans_from_fixed), [29](#)

Uncertainty_FPK, [30](#)

VectorPos_bounds, [31](#)