




Prüfbericht-Nr.: <i>Test Report No.:</i>	50061773 001	Auftrags-Nr.: <i>Order No.:</i>	164067052	Seite 1 von 25 Page 1 of 25
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	22.06.2016	
Auftraggeber: <i>Client:</i>	ARB Corporation Ltd. 42-44 Garden St, Kilsyth, Victoria 3137, Australia			
Prüfgegenstand: <i>Test item:</i>	ARB Fridge Freezer			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	10800010, 10800020, 10800030, 10800040			
Auftrags-Inhalt: <i>Order content:</i>	FCC Certification and Verification			
Prüfgrundlage: <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart C Section 15.209 FCC KDB Publication 447498 v06 CFR47 FCC Part 15: Subpart B Section 15.107 CFR47 FCC Part 15: Subpart B Section 15.109 RSS-247 Issue 1 May 2015 RSS-102 Issue 5 March 2015 RSS-Gen Issue 4 November 2014			
Wareneingangsdatum: <i>Date of receipt:</i>	27.06.2017			
Prüfmuster-Nr.: <i>Test sample No.:</i>	N/A			
Prüfzeitraum: <i>Testing period:</i>	29.06.2016 - 21.09.2016			
Ort der Prüfung: <i>Place of testing:</i>	Shenzhen Accurate Technology Co., Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von / tested by: 		kontrolliert von / reviewed by: 		
11.09.2016	Owen Tian / Senior Project Manager	10.11.2016	Winnie Hou / Technical Certifier	
Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
<p>* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet</p> <p>Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested</p>				
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>				

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: *Passed*

5.1.2 PEAK OUTPUT POWER

RESULT: *Passed*

5.1.3 99% BANDWIDTH

RESULT: *Passed*

5.1.4 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100KHZ BANDWIDTH

RESULT: *Passed*

5.1.5 SPURIOUS EMISSION

RESULT: *Passed*

5.1.6 20dB BANDWIDTH

RESULT: *Passed*

5.1.7 FREQUENCY SEPARATION

RESULT: *Passed*

5.1.8 NUMBER OF HOPPING FREQUENCY

RESULT: *Passed*

5.1.9 TIME OF OCCUPANCY

RESULT: *Passed*

5.1.10 CONDUCTED EMISSIONS

RESULT: *Passed*

Contents

1.	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS	4
2.	TEST SITES	4
2.1	TEST FACILITIES	4
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	5
2.3	TRACEABILITY	6
2.4	CALIBRATION	6
2.5	MEASUREMENT UNCERTAINTY	6
2.6	LOCATION OF ORIGINAL DATA	6
2.7	STATUS OF FACILITY USED FOR TESTING	6
3.	GENERAL PRODUCT INFORMATION	7
3.1	PRODUCT FUNCTION AND INTENDED USE	7
3.2	FOR DETAILS REFER TO THE USER MANUAL AND CIRCUIT DIAGRAM. RATINGS AND SYSTEM DETAILS	7
3.3	INDEPENDENT OPERATION MODES	8
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	8
3.5	SUBMITTED DOCUMENTS	8
4.	TEST SET-UP AND OPERATION MODES	9
4.1	PRINCIPLE OF CONFIGURATION SELECTION	9
4.2	TEST OPERATION AND TEST SOFTWARE	9
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	9
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	9
4.5	TEST SETUP DIAGRAM	10
5.	TEST RESULTS	12
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	12
5.1.1	<i>Antenna Requirement</i>	<i>12</i>
5.1.2	<i>Peak Output Power</i>	<i>13</i>
5.1.3	<i>99% Bandwidth</i>	<i>14</i>
5.1.4	<i>Conducted spurious emissions measured in 100kHz Bandwidth</i>	<i>15</i>
5.1.5	<i>Spurious Emission</i>	<i>16</i>
5.1.6	<i>20dB Bandwidth</i>	<i>17</i>
5.1.7	<i>Frequency Separation</i>	<i>18</i>
5.1.8	<i>Number of hopping frequency</i>	<i>19</i>
5.1.9	<i>Time of Occupancy</i>	<i>20</i>
5.1.10	<i>Conducted emissions</i>	<i>21</i>
6.	PHOTOGRAPHS OF THE TEST SET-UP	22
7.	LIST OF TABLES	25
8.	LIST OF PHOTOGRAPHS	25

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:
Appendix 1: Test Result

2. Test Sites

2.1 Test Facilities

Shenzhen Accurate Technology Co., Ltd.

F1, Bldg. A, Changyuan New Material Port, Keyuan Rd., Science & Industry Park Nanshan District, Shenzhen 518057, P.R. China

FCC Registration No.: 752051

Test site Industry Canada No.: 5077A-2

The tests at the test site have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Type	S/N	Calibrated until
Spurious emission				
Spectrum Analyzer	Rohde&Schwarz	FSV40	101495	2017-01-09
Test Receiver	Rohde&Schwarz	ESCS30	100307	2017-01-09
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	2017-01-09
Loop Antenna	Schwarzbeck	FMZB1516	1516131	2017-01-09
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	2017-01-09
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	2017-01-09
RF Switching Unit+PreAMP	Compliance Direction	RSU-M2	38322	2017-01-09
Pre-Amplifier	Rohde&Schwarz	CBLU11835 40-01	3791	2017-01-09
Radio Spectrum Test				
Spectrum Analyzer	Rohde & Schwarz	ESPI3	100396/003	2017-01-09
Spectrum Analyzer	Agilent	E7405A	MY45115511	2017-01-09
Conducted Emission				
Test Receiver	Rohde & Schwarz	ESCS30	100307	2017-01-09
L.I.S.N.	Schwarzbeck	NLSK8126	8126431	2017-01-09
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100815	2017-01-09
50Ω Coaxial Switch	Anritsu Corp	MP59B	6200283933	2017-01-09

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements are $\pm 3\text{dB}$.

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix 1 of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The Shenzhen Accurate Technology Co., Ltd. test facility located at F1, Bldg. A, Changyuan New Material Port, Keyuan Rd., Science & Industry Park Nanshan District, Shenzhen 518057, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3. General Product Information

3.1 Product Function and Intended Use

The EUTs are fridge freezer with wireless communication module.

The EUTs have been specifically designed for tough off road conditions and its primary purpose is for cooling down food and beverages. It may also be used as a freezer if desired.

The EUTs can connect to remote display via wireless signal to report the temperature.

The EUTs are identical in function, circuit design and electronic components employed, except different capacity and rating. Details as below:

Model	Rating	Compressor	Capacitor
10800010	AC100-240V, 50/60Hz, 1,0-0,6A; DC12V, 5,1A or DC24V, 2,8A	BD35F with refrigerant R134a/47g	47L
10800020	AC100-240V, 50/60Hz, 0,8-0,4A; DC12V, 5,0A or DC24V, 2,5A	BD35F with refrigerant R134a/44g	35L
10800030	AC100-240V, 50/60Hz, 1,0-0,5A; DC12V, 5,3A or DC24V, 3,0A	BD35F with refrigerant R134a/56g	60L
10800040	AC100-240V, 50/60Hz, 1,2-0,6A; DC12V, 7,3A or DC24V, 3,5A	BD50F with refrigerant R134a/63g	78L

3.2 For details refer to the User Manual and Circuit Diagram. Ratings and System Details

Table 2: Rating of EUT

Kind of Equipment:	ARB Fridge Freezer
Type Designation:	10800010, 10800020, 10800030, 10800040
FCC ID	2AA2H-ARB-MONITOR
IC	11414A-ARBMONITOR

Table 3: Technical Specification of EUT

Technical Specification	Value
Operating Frequency band	2435 – 2449 MHz
Channel separation	1MHz
Channel	2435MHz, 2436MHz, 2437MHz, 2438MHz, 2439MHz, 2440MHz, 2441MHz, 2442MHz, 2443MHz, 2444MHz, 2445MHz, 2446MHz, 2447MHz, 2448MHz, 2449MHz
Extreme Temperature Range	-20°C to +55°C
Operation Voltage	AC100-240V 50/60Hz or DC 12/24V
Modulation	GFSK
Antenna Type	Internal Antenna, Non-User Replaceable
Antenna Gain	3dBi
RF Output Power	0.0093W (9.68dBm)

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Transmitting
 - 1. Low channel
 - 2. Middle channel
 - 3. High channel
- B. On, Receiving
- C. On, Refrigeration
- D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Bill of Material
- PCB Layout
- Photo Document
- Technical Description
- Circuit Diagram
- Instruction Manual
- Rating Label

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.4: 2014 and ANSI C63.10: 2013.

Due to models' differences indicated in clause 3.1, full test was applied on model 10800010 only. The EUT was named as 10900026 during test, the license holder changed model number to 10800010 finally.

4.3 Special Accessories and Auxiliary Equipment

N/A

4.4 Countermeasures to achieve EMC Compliance

The test sample, which has been tested, contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Equipment Configuration for Mains Conduction Measurement





Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Passed**

Test standard	:	FCC Part 15.247(b)(4) and Part 15.203 RSS-Gen 6.7
Limit	:	the use of antennas with directional gains that do not exceed 6 dBi

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is 2dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT photo for details.

Channel	Channel Frequency (MHz)	Peak Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2435	9.07	0.0081	<0.125
Middle Channel	2442	9.38	0.0087	<0.125
High Channel	2449	9.68	0.0093	<0.125

5.1.3 99% Bandwidth

RESULT:**Passed**

Date of testing : 2016-06-29
Test standard : RSS-Gen clause 6.6
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
Operation Mode : A
Ambient temperature : 25°C
Relative humidity : 55%
Atmospheric pressure : 101 kPa

Table 5: Test result of 99% Bandwidth

Channel	Channel Frequency (MHz)	99% Bandwidth (kHz)	Limit (MHz)	Result
Low Channel	2435	978	/	Pass
Mid Channel	2442	978	/	Pass
High Channel	2449	972	/	Pass

**5.1.4 Conducted spurious emissions measured in 100kHz
Bandwidth****RESULT:****Passed**

Date of testing	:	2016-06-29
Test standard	:	FCC part 15.247(d) RSS-247 Clause 5.5
Basic standard	:	ANSI C63.10: 2013
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	:	Shield room

Test setup

Test Channel	:	Low/ High
Operation mode	:	A
Ambient temperature	:	25°C
Relative humidity	:	55%
Atmospheric pressure	:	101 kPa

All emissions are more than 20dB below fundamental, details refer to Appendix 1, and compliance is achieved as well.

5.1.5 Spurious Emission

RESULT:**Passed**

Date of testing	:	2016-09-21
Test standard	:	FCC part 15.247(d) FCC Part 15.205 RSS-247 Clause 3.3
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Table 4 & Table 5
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Test Channel	:	Low/ Middle/ High
Operation mode	:	A
Ambient temperature	:	23°C
Relative humidity	:	48%
Atmospheric pressure	:	101 kPa

Remark:

During the pretest the EUT was rotated through three orthogonal axes to determine the attitude that maximizes the emissions. After that the EUT was manually handled to find the orientation that has the maximum emission, which is the orientation shown in the test setup photos.

Testing was carried out within frequency range 9kHz to the tenth harmonics.

For details refer to Appendix 1.

5.1.6 20dB Bandwidth**RESULT:****Passed**

Date of testing : 2016-06-29
Test standard : FCC Part 15.247(a)(1)
RSS-247 Clause 5.1(1)
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
Operation Mode : A
Ambient temperature : 25°C
Relative humidity : 55%
Atmospheric pressure : 101 kPa

Table 6: Test result of 20dB Bandwidth

Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)	Limit (MHz)	Result
Low Channel	2435	702	/	Pass
Mid Channel	2442	630	/	Pass
High Channel	2449	658	/	Pass

5.1.8 Number of hopping frequency**RESULT:****Passed**

Date of testing : 2016-06-29
Test standard : FCC part 15.247(a)(1)(iii)
RSS-247 Clause 5.1(4)
Basic standard : ANSI C63.10: 2013
Limits : ≥ 15 non-overlapping channels
Kind of test site : Shield room

Test setup

Test Channel : Low/ Middle/ High
Operation Mode : B
Ambient temperature : 25°C
Relative humidity : 55%
Atmospheric pressure : 101 kPa

Table 8: Test result of Number of hopping frequency

Frequency Range	Measured Quantity of Hopping Channel	Limit	Result
<u>2400</u> to <u>2483.5</u> MHz	15	≥ 15	Pass

5.1.9 Time of Occupancy

RESULT:**Passed**

Date of testing : 2016-06-29
Test standard : FCC part 15.247(a)(1)(iii)
RSS-247 Clause 5.1(4)
Basic standard : ANSI C63.10: 2013
Limits : <0.4s
Kind of test site : Shield room

Test setup

Test Channel : Low/ Middle/ High
Operation Mode : A
Ambient temperature : 25°C
Relative humidity : 55%
Atmospheric pressure : 101 kPa

Table 9: Test result of Time of Occupancy

Channel	Pulse width (ms)	Dwell time (s)	Limit (s)	Result
Low Channel	0.22	0.013	0.4	Pass
Mid Channel	0.22	0.013	0.4	Pass
High Channel	0.22	0.013	0.4	Pass

Note:

Dwell time = Pulse width x (Hopping rate / Number of channels) x Period

Period = 0.4 (seconds/ channel) x Number of channels

5.1.10 Conducted emissions**RESULT:****Passed**

Date of testing	:	2016-06-30
Test standard	:	FCC Part 15.107(a) & FCC Part 15.207(a) RSS-Gen Clause 8.8
Basic standard	:	ANSI C63.10: 2013 & ANSI C63.4: 2014
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.207(a) & FCC Part 15.207(a) RSS-Gen Table 3
Kind of test site	:	Shield room

Test setup

Input Voltage	:	AC 100-240V 50/60Hz
Operation Mode	:	C
Earthing	:	Not connected
Ambient temperature	:	25°C
Relative humidity	:	55%
Atmospheric pressure	:	101 kPa

For details refer to Appendix 1.

6. Photographs of the Test Set-Up


Photograph 1: Set-up for Spurious Emissions (9kHz-30MHz)




Photograph 2: Set-up for Spurious Emissions (30MHz-1GHz)



Photograph 3: Set-up for Spurious Emissions (1GHz-18GHz)



Photograph 4: Set-up for Spurious Emissions (18GHz-26GHz)



Photograph 5: Set-up for Conducted Emissions



7. List of Tables

Table 1: List of Test and Measurement Equipment	5
Table 2: Rating of EUT	7
Table 3: Technical Specification of EUT	8
Table 4: Test result of Peak Output Power	13
Table 5: Test result of 99% Bandwidth.....	14
Table 6: Test result of 20dB Bandwidth	17
Table 7: Test result of Frequency Separation	18
Table 8: Test result of Number of hopping frequency	19
Table 9: Test result of Time of Occupancy.....	20

8. List of Photographs

Photograph 1: Set-up for Spurious Emissions (9kHz-30MHz)	22
Photograph 2: Set-up for Spurious Emissions (30MHz-1GHz)	22
Photograph 3: Set-up for Spurious Emissions (1GHz-18GHz)	23
Photograph 4: Set-up for Spurious Emissions (18GHz-26GHz)	23
Photograph 5: Set-up for Conducted Emissions	24

List of Figures

Figure 1: Test figure of spurious emissions, mode A.1, Horizontal polarity (9kHz – 30MHz),	2
Figure 2: Test figure of spurious emissions, mode A.1, Vertical polarity (9kHz – 30MHz)	2
Figure 3: Test figure of spurious emissions, mode A.1, Horizontal polarity (30MHz – 1GHz)	3
Figure 4: Test figure of spurious emissions, mode A.1, Vertical polarity (30MHz – 1GHz)	4
Figure 5: Test figure of spurious emissions, mode A.1, Horizontal polarity (1GHz – 18GHz)	5
Figure 6: Test figure of spurious emissions, mode A.1, Vertical polarity (1GHz – 18GHz)	6
Figure 7: Test figure of spurious emissions, mode A.1, Horizontal polarity (18GHz – 25GHz)	7
Figure 8: Test figure of spurious emissions, mode A.1, Vertical polarity (18GHz – 25GHz)	8
Figure 9: Test figure of spurious emissions, mode A.2, Horizontal polarity (9kHz – 30MHz)	9
Figure 10: Test figure of spurious emissions, mode A.2, Vertical polarity (9kHz – 30MHz)	9
Figure 11: Test figure of spurious emissions, mode A.2, Horizontal polarity (30MHz – 1GHz)	10
Figure 12: Test figure of spurious emissions, mode A.2, Vertical polarity (30MHz – 1GHz)	11
Figure 13: Test figure of spurious emissions, mode A.2, Horizontal polarity (1GHz – 18GHz)	12
Figure 14: Test figure of spurious emissions, mode A.2, Vertical polarity (1GHz – 18GHz)	13
Figure 15: Test figure of spurious emissions, mode A.2, Horizontal polarity (18GHz – 25GHz)	14
Figure 16: Test figure of spurious emissions, mode A.2, Vertical polarity (18GHz – 25GHz)	15
Figure 17: Test figure of spurious emissions, mode A.3, Horizontal polarity (9kHz – 30MHz)	16
Figure 18: Test figure of spurious emissions, mode A.3, Vertical polarity (9kHz – 30MHz)	16
Figure 19: Test figure of spurious emissions, mode A.3, Horizontal polarity (30MHz – 1GHz)	17
Figure 20: Test figure of spurious emissions, mode A.3, Vertical polarity (30MHz – 1GHz)	18
Figure 21: Test figure of spurious emissions, mode A.3, Horizontal polarity (1GHz – 18GHz)	19
Figure 22: Test figure of spurious emissions, mode A.3, Vertical polarity (1GHz – 18GHz)	20
Figure 23: Test figure of spurious emissions, mode A.3, Horizontal polarity (18GHz – 25GHz)	21
Figure 24: Test figure of spurious emissions, mode A.3, Vertical polarity (18GHz – 25GHz)	22
Figure 25: Test figure of Radiated emissions in restricted bands, Mode A.1, Horizontal	22
Figure 26: Test figure of Radiated emissions in restricted bands, Mode A.1, Vertical	24
Figure 27: Test figure of Radiated emissions in restricted bands, Mode A.3, Horizontal	25
Figure 28: Test figure of Radiated emissions in restricted bands, Mode A.3, Vertical	26
Figure 29: Test figure of conducted emissions in 100kHz Bandwidth, Mode A.1	27
Figure 30: Test figure of conducted emissions in 100kHz Bandwidth, Mode A.2	28
Figure 31: Test figure of conducted emissions in 100kHz Bandwidth, Mode A.3	29
Figure 32: Test figure of Frequency Band Edge in 100kHz Bandwidth, Mode A.1	30
Figure 33: Test figure of Frequency Band Edge in 100kHz Bandwidth, Mode A.3	30
Figure 36: Test figure of Conducted emissions, Mode C, line live	31
Figure 37: Test figure of Conducted emissions, Mode C, line neutral	32

Figure 1: Test figure of spurious emissions, mode A.1, Horizontal polarity (9kHz – 30MHz),

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: ARB Monitor M/N:10900026
Manufacturer: Mobicoool
Operating Condition: TX 2435MHz
Test Site: 2# Chamber
Operator: LGWADE
Test Specification: DC 3.7V
Comment: X

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 2: Test figure of spurious emissions, mode A.1, Vertical polarity (9kHz – 30MHz)

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: ARB Monitor M/N:10900026
Manufacturer: Mobicoool
Operating Condition: TX 2435MHz
Test Site: 2# Chamber
Operator: LGWADE
Test Specification: DC 3.7V
Comment: Y

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 3: Test figure of spurious emissions, mode A.1, Horizontal polarity (30MHz – 1GHz)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: tuv2015 #3810

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: ARB Monitor

Mode: TX 2435MHz

Model: 10900026

Manufacturer: Mobicool

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/09/21/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	99.1796	53.05	-14.40	38.65	43.50	-4.85	QP			
2	101.2883	52.96	-14.33	38.63	43.50	-4.87	QP			
3	194.4533	46.27	-13.49	32.78	43.50	-10.72	QP			

Figure 4: Test figure of spurious emissions, mode A.1, Vertical polarity (30MHz – 1GHz)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: tuv2015 #3811

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: ARB Monitor

Mode: TX 2435MHz

Model: 10900026

Manufacturer: Mobicool

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 16/09/21/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	31.3992	42.20	-9.34	32.86	40.00	-7.14	QP			
2	99.1796	52.51	-14.40	38.11	43.50	-5.39	QP			
3	101.2883	51.54	-14.33	37.21	43.50	-6.29	QP			

Figure 5: Test figure of spurious emissions, mode A.1, Horizontal polarity (1GHz –18GHz)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 2# Chamber

Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2939
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ARB Monitor
Mode: TX 2435MHz
Model: 10900026
Manufacturer: Mobicoool

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/09/21/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2435.000	105.50	-7.37	98.13	/	/	peak			
2	4870.032	50.56	0.07	50.63	74.00	-23.37	peak			
3	4870.032	44.27	0.07	44.34	54.00	-9.66	AVG			

Figure 6: Test figure of spurious emissions, mode A.1, Vertical polarity (1GHz – 18GHz)




ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel: +86-0755-26503290
Fax: +86-0755-26503396

Job No.: LGW2015 #2938
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ARB Monitor
Mode: TX 2435MHz
Model: 10900026
Manufacturer: Mobicool

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/09/21/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2435.000	104.36	-7.37	96.99	/	/	peak			
2	4870.027	50.55	0.07	50.62	74.00	-23.38	peak			
3	4870.027	44.27	0.07	44.34	54.00	-9.66	AVG			

Figure 7: Test figure of spurious emissions, mode A.1, Horizontal polarity (18GHz –25GHz)




ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2948
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ARB Monitor
Mode: TX 2435MHz
Model: 10900026
Manufacturer: Mobicool

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/09/21/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26042.764	34.09	16.50	50.59	74.00	-23.41	peak			
2	26042.764	24.16	16.50	40.66	54.00	-13.34	AVG			

Figure 8: Test figure of spurious emissions, mode A.1, Vertical polarity (18GHz – 25GHz)




ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2949
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ARB Monitor
Mode: TX 2435MHz
Model: 10900026
Manufacturer: Mobicool

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/09/21/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26072.999	33.07	17.18	50.25	74.00	-23.75	peak			
2	26072.999	23.45	17.18	40.63	54.00	-13.37	AVG			

Figure 9: Test figure of spurious emissions, mode A.2, Horizontal polarity (9kHz – 30MHz)

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: ARB Monitor M/N:10900026
Manufacturer: Mobicool
Operating Condition: TX 2442MHz
Test Site: 2# Chamber
Operator: LGWADE
Test Specification: DC 3.7V
Comment: X

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 10: Test figure of spurious emissions, mode A.2, Vertical polarity (9kHz – 30MHz)

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: ARB Monitor M/N:10900026
Manufacturer: Mobicool
Operating Condition: TX 2442MHz
Test Site: 2# Chamber
Operator: LGWADE
Test Specification: DC 3.7V
Comment: Z

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 11: Test figure of spurious emissions, mode A.2, Horizontal polarity (30MHz – 1GHz)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: tuv2015 #3813

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: ARB Monitor

Mode: TX 2442MHz

Model: 10900026

Manufacturer: Mobicool

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/09/21/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	99.1796	52.99	-14.40	38.59	43.50	-4.91	QP			
2	103.4419	51.09	-14.70	36.39	43.50	-7.11	QP			
3	190.4050	45.38	-13.64	31.74	43.50	-11.76	QP			

Figure 12: Test figure of spurious emissions, mode A.2, Vertical polarity (30MHz – 1GHz)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: tuv2015 #3812

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: ARB Monitor

Mode: TX 2442MHz

Model: 10900026

Manufacturer: Mobicool

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 16/09/21/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	32.0667	42.48	-9.54	32.94	40.00	-7.06	QP			
2	52.3912	34.35	-12.78	21.57	40.00	-18.43	QP			
3	99.1796	52.37	-14.40	37.97	43.50	-5.53	QP			

Figure 13: Test figure of spurious emissions, mode A.2, Horizontal polarity (1GHz – 18GHz)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2940

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: ARB Monitor

Mode: TX 2442MHz

Model: 10900026

Manufacturer: Mobicool

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/09/21/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2442.000	105.30	-7.35	97.95	/	/	peak			
2	4884.034	50.53	0.15	50.68	74.00	-23.32	peak			
3	4884.034	45.23	0.15	45.38	54.00	-8.62	AVG			

Figure 14: Test figure of spurious emissions, mode A.2, Vertical polarity (1GHz – 18GHz)




ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2941
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ARB Monitor
Mode: TX 2442MHz
Model: 10900026
Manufacturer: Mobicool

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/09/21/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2442.000	104.84	-7.35	97.49	/	/	peak			
2	4884.029	50.03	0.15	50.18	74.00	-23.82	peak			
3	4884.029	45.22	0.15	45.37	54.00	-8.63	AVG			

Figure 15: Test figure of spurious emissions, mode A.2, Horizontal polarity (18GHz – 25GHz)




ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2951
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ARB Monitor
Mode: TX 2442MHz
Model: 10900026
Manufacturer: Mobicool

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/09/21/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26174.038	33.97	16.50	50.47	74.00	-23.53	peak			
2	26174.038	23.31	16.50	39.81	54.00	-14.19	AVG			

Figure 16: Test figure of spurious emissions, mode A.2, Vertical polarity (18GHz – 25GHz)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2950

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: ARB Monitor

Mode: TX 2442MHz

Model: 10900026

Manufacturer: Mobicool

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 16/09/21/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26113.368	33.05	17.16	50.21	74.00	-23.79	peak			
2	26113.368	23.56	17.16	40.72	54.00	-13.28	AVG			

Figure 17: Test figure of spurious emissions, mode A.3, Horizontal polarity (9kHz – 30MHz)

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: ARB Monitor M/N:10900026
Manufacturer: Mobicool
Operating Condition: TX 2449MHz
Test Site: 2# Chamber
Operator: LGWADE
Test Specification: DC 3.7V
Comment: X

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 18: Test figure of spurious emissions, mode A.3, Vertical polarity (9kHz – 30MHz)

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: ARB Monitor M/N:10900026
Manufacturer: Mobicool
Operating Condition: TX 2449MHz
Test Site: 2# Chamber
Operator: LGWADE
Test Specification: DC 3.7V
Comment: Y

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 19: Test figure of spurious emissions, mode A.3, Horizontal polarity (30MHz – 1GHz)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: tuv2015 #3814

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: ARB Monitor

Mode: TX 2449MHz

Model: 10900026

Manufacturer: Mobicool

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/09/21/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	99.1796	52.81	-14.40	38.41	43.50	-5.09	QP			
2	101.2883	51.30	-14.33	36.97	43.50	-6.53	QP			
3	194.4533	45.12	-13.49	31.63	43.50	-11.87	QP			

Figure 20: Test figure of spurious emissions, mode A.3, Vertical polarity (30MHz – 1GHz)




ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: tuv2015 #3815
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ARB Monitor
Mode: TX 2449MHz
Model: 10900026
Manufacturer: Mobicool

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/09/21/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	32.5197	42.88	-9.68	33.20	40.00	-6.80	QP			
2	99.1796	52.09	-14.40	37.69	43.50	-5.81	QP			
3	101.2883	50.00	-14.33	35.67	43.50	-7.83	QP			

Figure 21: Test figure of spurious emissions, mode A.3, Horizontal polarity (1GHz –18GHz)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2943

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: ARB Monitor

Mode: TX 2449MHz

Model: 10900026

Manufacturer: Mobicool

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 16/09/21/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2449.000	105.00	-7.33	97.67	/	/	peak			
2	4898.033	50.25	0.22	50.47	74.00	-23.53	peak			
3	4898.033	44.15	0.22	44.37	54.00	-9.63	AVG			

Figure 22: Test figure of spurious emissions, mode A.3, Vertical polarity (1GHz – 18GHz)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2942

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: ARB Monitor

Mode: TX 2449MHz

Model: 10900026

Manufacturer: Mobicool

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 16/09/21/

Time:

Engineer Signature: LGWADE

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2449.000	105.21	-7.33	97.88	/	/	peak			
2	4898.024	50.62	0.22	50.84	74.00	-23.16	peak			
3	4898.024	44.45	0.22	44.67	54.00	-9.33	AVG			

Figure 23: Test figure of spurious emissions, mode A.3, Horizontal polarity (18GHz –25GHz)




ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2015 #2952
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ARB Monitor
Mode: TX 2449MHz
Model: 10900026
Manufacturer: Mobicool

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/09/21/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26295.801	34.04	16.50	50.54	74.00	-23.46	peak			
2	26295.801	24.06	16.50	40.56	54.00	-13.44	AVG			

Figure 24: Test figure of spurious emissions, mode A.3, Vertical polarity (18GHz – 25GHz)




Figure 25: Test figure of Radiated emissions in restricted bands, Mode A.1, Horizontal



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LGW2015 #2944
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ARB Monitor
Mode: TX 2435MHz
Model: 10900026
Manufacturer: Mobicool

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/09/21/
Time:
Engineer Signature: LGWADE
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2341.040	60.58	-7.79	52.79	74.00	-21.21	peak			
2	2341.040	50.13	-7.79	42.34	54.00	-11.66	AVG			
3	2352.880	61.60	-7.77	53.83	74.00	-20.17	peak			
4	2352.880	51.34	-7.77	43.57	54.00	-10.43	AVG			
5	2362.640	62.49	-7.71	54.78	74.00	-19.22	peak			
6	2362.640	51.93	-7.71	44.22	54.00	-9.78	AVG			
7	2374.480	62.93	-7.63	55.30	74.00	-18.70	peak			
8	2374.480	52.96	-7.63	45.33	54.00	-8.67	AVG			
9	2386.240	63.62	-7.55	56.07	74.00	-17.93	peak			
10	2386.240	53.75	-7.55	46.20	54.00	-7.80	AVG			

Figure 26: Test figure of Radiated emissions in restricted bands, Mode A.1, Vertical




Figure 27: Test figure of Radiated emissions in restricted bands, Mode A.3, Horizontal




Figure 28: Test figure of Radiated emissions in restricted bands, Mode A.3, Vertical




Figure 29: Test figure of conducted emissions in 100kHz Bandwidth, Mode A.1




Figure 30: Test figure of conducted emissions in 100kHz Bandwidth, Mode A.2




Figure 31: Test figure of conducted emissions in 100kHz Bandwidth, Mode A.3






Figure 32: Test figure of Frequency Band Edge in 100kHz Bandwidth, Mode A.1



Date: 29.NOV.2013 08:46:01

Figure 33: Test figure of Frequency Band Edge in 100kHz Bandwidth, Mode A.3



Date: 29.NOV.2013 08:53:52

Figure 34: Test figure of Conducted emissions, Mode C, line live


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT:
Manufacturer: Mobicool
Operating Condition: Transmitting
Test Site: 1#Shielding Room
Operator: LAN
Test Specification: L 120V/60Hz
Comment: Mains Port
Start of Test: 30/6/2016 / 11:47:18AM

SCAN TABLE: "V 150K-30MHz fin"

Short Description:	SUB STD VTERM2 1.70					
Start	Stop	Step	Detector	Meas.	IF	Transducer
Frequency	Frequency	Width		Time	Bandw.	
150.0 kHz	30.0 MHz	4.5 kHz	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
Average						



MEASUREMENT RESULT: "U-1202-01_fin"

30/6/2016 11:49AM								
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	
MHz	dBμV	dB	dBμV	dB				
0.167739	54.30	10.5	65	10.8	QP	L1	GND	
0.879278	33.40	10.8	56	22.6	QP	L1	GND	
12.806998	31.40	11.3	60	28.6	QP	L1	GND	

MEASUREMENT RESULT: "U-1202-01_fin2"

30/6/2016 11:49AM								
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	
MHz	dBμV	dB	dBμV	dB				
0.163769	36.50	10.5	55	18.8	AV	L1	GND	
0.933537	16.40	10.8	46	29.6	AV	L1	GND	
12.014561	26.80	11.3	50	23.2	AV	L1	GND	

Figure 35: Test figure of Conducted emissions, Mode C, line neutral


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT:
Manufacturer: Mobicool
Operating Condition: Transmitting
Test Site: 1#Shielding Room
Operator: LAN
Test Specification: N 120V/60Hz
Comment: Mains Port
Start of Test: 30/6/2016 / 11:50:31AM

SCAN TABLE: "V 150K-30MHz fin"

Short Description: SUB STD VTERM2 1.70
Start Stop Step Detector Meas. IF Transducer
Frequency Frequency Width QuasiPeak Time Bandw.
150.0 kHz 30.0 MHz 4.5 kHz Average 1.0 s 9 kHz NSLK8126 2008



MEASUREMENT RESULT: "U-1202-02_fin"

30/6/2016 11:52AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.176674	52.10	10.5	65	12.5	QP	N	GND
0.200748	51.70	10.5	64	11.9	QP	N	GND
12.705153	32.30	11.3	60	27.7	QP	N	GND

MEASUREMENT RESULT: "U-1202-02_fin2"

30/6/2016 11:52AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.166406	36.20	10.5	55	18.9	AV	N	GND
0.204796	31.00	10.5	53	22.4	AV	N	GND
12.014561	27.30	11.3	50	22.7	AV	N	GND