

---

# FCC Test Report

---

Report No.: AGC05894170501FE05

**FCC ID** : 2AA2Z020170501  
**APPLICATION PURPOSE** : Original Equipment  
**PRODUCT DESIGNATION** : Quadrotor  
**BRAND NAME** : N/A  
**MODEL NAME** : i3HW, i3, i3s, i3H, i3HS, i4, i4S, i4H, i4HS, i4HW, i7, i7S, i7W, i7H, i7HS, i7HW, X4A  
**CLIENT** : YI ZHAN TOYS CO., LTD.  
**DATE OF ISSUE** : June 09, 2017  
**STANDARD(S)**  
**TEST PROCEDURE(S)** : FCC Part 15 Rules  
**REPORT VERSION** : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	June 09, 2017	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY ..... 4

2. GENERAL INFORMATION..... 5

    2.1. PRODUCT DESCRIPTION ..... 5

    2.2. TABLE OF CARRIER FREQUENCY ..... 5

3. MEASUREMENT UNCERTAINTY..... 6

4. DESCRIPTION OF TEST MODES..... 6

5. SYSTEM TEST CONFIGURATION ..... 7

    5.1. CONFIGURATION OF EUT SYSTEM..... 7

    5.2. EQUIPMENT USED IN EUT SYSTEM..... 7

    5.3. SUMMARY OF TEST RESULTS ..... 7

6. TEST FACILITY..... 8

7. RADIATED EMISSION..... 9

    7.1TEST LIMIT ..... 9

    7.2. MEASUREMENT PROCEDURE..... 10

    7.3. TEST SETUP ..... 12

    7.4. TEST RESULT ..... 13

8. BAND EDGE EMISSION..... 18

    8.1. MEASUREMENT PROCEDURE..... 18

    8.2 TEST SETUP ..... 18

    8.3 RADIATED TEST RESULT ..... 18

9. 20DB BANDWIDTH ..... 23

    9.1. MEASUREMENT PROCEDURE..... 23

    9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... 23

    9.3. MEASUREMENT RESULTS ..... 23

APPENDIX A: PHOTOGRAPHS OF TEST SETUP..... 26

APPENDIX B: PHOTOGRAPHS OF EUT ..... 27


## 1. VERIFICATION OF CONFORMITY

<b>Applicant</b>	YI ZHAN TOYS CO., LTD.
<b>Address</b>	North Road of Zhenxing, Guangyi Street, Chenghai District, Shantou City, Guangdong Province, China
<b>Manufacturer</b>	YI ZHAN TOYS CO., LTD.
<b>Address</b>	North Road of Zhenxing, Guangyi Street, Chenghai District, Shantou City, Guangdong Province, China
<b>Product Designation</b>	Quadrotor
<b>Brand Name</b>	N/A
<b>Test Model</b>	i3HW
<b>Serial Model</b>	i3, i3s, i3H, i3HS, i4, i4S, i4H, i4HS, i4HW, i7, i7S, i7W, i7H, i7HS, i7HW, X4A
<b>Difference Description</b>	All the same except the appearance.
<b>Date of test</b>	June 05, 2017 to June 09, 2017
<b>Deviation</b>	None
<b>Condition of Test Sample</b>	Normal
<b>Test Result</b>	Pass
<b>Report Template</b>	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Tested by




Max Zhang(Zhang Yi) June 09, 2017

Reviewed by



Bart Xie(Xie Xiaobin)) June 09, 2017

Approved by



Solger Zhang(Zhang Hongyi)  
Authorized Officer June 09, 2017

## 2. GENERAL INFORMATION

### 2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

<b>Operation Frequency</b>	2.407 GHz to 2.477GHz
<b>Maximum field strength</b>	87.37dBuV/m@3m(AV)
<b>Modulation</b>	GFSK
<b>Number of channels</b>	71
<b>Antenna Gain</b>	0dBi
<b>Antenna Designation</b>	Integrated Antenna (Met 15.203 Antenna requirement)
<b>Hardware Version</b>	YZ-i3T V1.0
<b>Software Version</b>	V15
<b>Power Supply</b>	DC 3V by battery

### 2.2. TABLE OF CARRIER FREQUENCY

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	1	2407MHZ
	2	2408MHZ
	:	:
	:	:
	70	2476MHZ
	71	2477MHZ

Note: Channel spacing=1MHz

### 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.18\text{dB}$
2	All emissions, radiated	$\pm 3.91\text{dB}$
3	Temperature	$\pm 0.5^\circ\text{C}$
4	Humidity	$\pm 2\%$

### 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX in GFSK modulation
2	Middle channel TX in GFSK modulation
3	High channel TX in GFSK modulation
Note: 1. Only the result of the worst case was recorded in the report, if no other cases. 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode. 3. The EUT had been programmed in continuous transmission conditions for the test modes.	

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1:



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	QUADROTOR	i3HW	2AA2Z020170501	EUT

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.215	20dB bandwidth	Compliant

## 6. TEST FACILITY

<b>Site</b>	Dongguan Precise Testing Service Co., Ltd.
<b>Location</b>	Building D, Baoding Technology Park, Guangming Road2, Dongcheng District, Dongguan, Guangdong, China.
<b>FCC Registration No.</b>	371540
<b>Description</b>	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2014.

## ALL TEST EQUIPMENT LIST

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 3, 2016	July 2, 2017
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 3, 2016	July 2, 2017
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 3, 2016	July 2, 2017
RF Cable	SCHWARZBECK	AK9515E	96221	July 3, 2016	July 2, 2017
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 2, 2017	June 1, 2018
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 2, 2017	June 1, 2018
Spectrum analyzer	Agilent	E4407B	MY46185649	June 2, 2017	June 1, 2018
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	June 2, 2017	June 1, 2018
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 2, 2017	June 1, 2018



## 7. RADIATED EMISSION

### 7.1 TEST LIMIT

#### Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

#### Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		$\mu$ V/m	dB( $\mu$ V)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other: 74.0 dB( $\mu$ V)/m (Peak) 54.0 dB( $\mu$ V)/m (Average)	

Remark:

- (1) Emission level dB $\mu$  V = 20 log Emission level  $\mu$  V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

## 7.2. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/10Hz for Average


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

7.3. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



7.4. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION 30MHz- 1GHZ

EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 1	Polarization :	Horizontal




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		144.7833	9.09	14.04	23.13	43.50	-20.37	peak			
2		219.1500	13.74	10.05	23.79	46.00	-22.21	peak			
3		351.7167	11.17	18.75	29.92	46.00	-16.08	peak			
4		460.0333	3.57	20.70	24.27	46.00	-21.73	peak			
5		634.6333	5.23	23.81	29.04	46.00	-16.96	peak			
6	*	893.3000	1.72	28.44	30.16	46.00	-15.84	peak			

RESULT: PASS

EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 1	Polarization :	Vertical

66.9 dBuV/m



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	144.7833	14.28	15.23	29.51	43.50	-13.99	peak			
2		217.5333	15.53	10.72	26.25	46.00	-19.75	peak			
3		325.8500	8.92	17.13	26.05	46.00	-19.95	peak			
4		460.0333	7.74	20.70	28.44	46.00	-17.56	peak			
5		663.7333	3.99	24.22	28.21	46.00	-17.79	peak			
6		794.6833	2.24	27.25	29.49	46.00	-16.51	peak			

**RESULT: PASS****Note:**

Factor=Antenna Factor + Cable loss, Margin=Result-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

The mode 1 is the worst case, and only the data of the worst case recorded in this test report.

## RADIATED EMISSION ABOVE 1GHZ

EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 1	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2407.013	98.52	-9.37	89.15	114	-24.85	peak
2407.013	96.74	-9.37	87.37	94	-6.63	AVG
4814.026	42.54	3.74	46.28	74	-27.72	peak
4814.026	40.78	3.74	44.52	54	-9.48	AVG
7221.039	40.35	8.14	48.49	74	-25.51	peak
7221.039	38.81	8.14	46.95	54	-7.05	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 1	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2407.013	96.49	-9.37	87.12	114	-26.88	peak
2407.013	94.68	-9.37	85.31	94	-8.69	AVG
4814.026	41.85	3.74	45.59	74	-28.41	peak
4814.026	40.08	3.74	43.82	54	-10.18	AVG
7221.039	40.15	8.14	48.29	74	-25.71	peak
7221.039	38.64	8.14	46.78	54	-7.22	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 2	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2439.016	98.15	-9.63	88.52	114	-25.48	peak
2439.016	96.64	-9.63	87.01	94	-6.99	AVG
4878.032	42.18	3.76	45.94	74	-28.06	peak
4878.032	40.37	3.76	44.13	54	-9.87	AVG
7317.048	40.94	8.17	49.11	74	-24.89	peak
7317.048	39.09	8.17	47.26	54	-6.74	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 2	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2439.016	97.24	-9.63	87.61	114	-26.39	peak
2439.016	95.71	-9.63	86.08	94	-7.92	AVG
4878.032	41.52	3.76	45.28	74	-28.72	peak
4878.032	39.64	3.76	43.4	54	-10.6	AVG
7317.048	40.75	8.17	48.92	74	-25.08	peak
7317.048	38.84	8.17	47.01	54	-6.99	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						



EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 3	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2477.021	98.36	-9.61	88.75	114	-25.25	peak
2477.021	96.54	-9.61	86.93	94	-7.07	AVG
4954.042	43.52	3.83	47.35	74	-26.65	peak
4954.042	41.84	3.83	45.67	54	-8.33	AVG
7431.063	41.12	8.21	49.33	74	-24.67	peak
7431.063	39.52	8.21	47.73	54	-6.27	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 3	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2477.021	96.41	-9.61	86.8	114	-27.2	peak
2477.021	94.57	-9.61	84.96	94	-9.04	AVG
4954.042	42.15	3.83	45.98	74	-28.02	peak
4954.042	40.54	3.83	44.37	54	-9.63	AVG
7431.063	41.24	8.21	49.45	74	-24.55	peak
7431.063	39.65	8.21	47.86	54	-6.14	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

**Note:** Other emissions from 8G to 25 GHz are considered as ambient noise. No recording in the test report.  
Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.  
The “Factor” value can be calculated automatically by software of measurement system.


## 8. BAND EDGE EMISSION

### 8.1. MEASUREMENT PROCEDURE

1. The EUT operates at transmitting mode. The operate channel is tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
2. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:  
(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO  
(b) AVERAGE: RBW=1MHz ; VBW=1/on time(1KHz) / Sweep=AUTO
3. Other procedures refer to clause 7.2.

### 8.2 TEST SETUP

#### RADIATED EMISSION TEST SETUP



### 8.3 RADIATED TEST RESULT

#### Note:


1. Factor=Antenna Factor + Cable loss - Amplifier gain. Field Strength=Factor + Reading level
2. The factor had been edited in the "Input Correction" of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB( $\mu$ V) to represent the Amplitude. Use the F dB( $\mu$ V/m) to represent the Field Strength. So A=F.

EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 1	Polarization :	Horizontal

PK Value



AV Value




EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 1	Polarization :	Vertical

## PK Value



## AV Value




EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 3	Polarization :	Horizontal

PK Value



AV Value



EUT :	QUADROTOR	Model Name. :	I3HW
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC3V
Test Mode :	Mode 3	Polarization :	Vertical

PK Value



AV Value




## 9. 20DB BANDWIDTH

### 9.1. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel  
The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

### 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)




### 9.3. MEASUREMENT RESULTS


TEST ITEM	20DB BANDWIDTH
TEST MODE	Mode1;Mode2;Mode3

Test Data (MHz)		Criteria
Low Channel	0.8027	PASS
Middle Channel	0.7940	PASS
High Channel	0.7963	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL






TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### FCC RADIATED EMISSION TEST SETUP



## APPENDIX B: PHOTOGRAPHS OF EUT

ALL VIEW OF EUT



TOP VIEW OF EUT





BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT







RIGHT VIEW OF EUT




OPEN VIEW OF EUT



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



-----END OF REPORT-----