

Test Report

FCC Part15 Subpart C

Product Name : Q Light Engine
Model No. : QPI-1
FCC ID : 2AA45-QPI-1

Applicant : Q-Point Technology Inc
Address : 4F., No.90, XinHu 1st Rd., NeiHu Dist., Taipei City
11494, Taiwan

Date of Receipt : Sep. 15, 2013
Test Date : Sep. 15, 2013~ Mar. 28, 2014
Issued Date : Apr. 02, 2014
Report No. : 1430403R-RF-US-P06V02
Report Version : V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.

Test Report Certification

Issued Date : Apr. 02, 2014

Report No. : 1430403R-RF-US-P06V02



Product Name : Q Light Engine

Applicant : Q-Point Technology Inc

Address : 4F., No.90, XinHu 1st Rd., NeiHu Dist., Taipei City 11494,
Taiwan

Manufacturer : Q-Point Technology Inc

Address : 4F., No.90, XinHu 1st Rd., NeiHu Dist., Taipei City 11494,
Taiwan

Model No. : QPI-1

FCC ID : 2AA45-QPI-1

EUT Voltage : DC 5V

Brand Name : Q-Point

Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2012
ANSI C63.4: 2009 ANSI C63.10:2009
KDB 558074 D01 DTS Meas Guidance v03r01

Test Result : Complied

Performed Location : Suzhou EMC Laboratory
No.99 Hongye Rd., Suzhou Industrial Park Loufeng
Hi-Tech Development Zone., Suzhou, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392

Documented By : Alice Ni

Reviewed By : James Yuan

Approved By : Jeff Chen

Laboratory Information

We, **Quietek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C.	:	BSMI, NCC, TAF
Germany	:	TUV Rheinland
Norway	:	Nemko, DNV
USA	:	FCC
Japan	:	VCCI
China	:	CNAS

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site :<http://www.quietek.com/tw/ctg/cts/accreditations.htm>

The address and introduction of Quietek Corporation's laboratories can be founded in our Web site :
<http://www.quietek.com/>

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yonghxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.
TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : service@quietek.com

Linkou Testing Laboratory :

No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451, Taiwan, R.O.C.
TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : service@quietek.com

Suzhou Testing Laboratory :

No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., SuZhou, China
TEL : +86-512-6251-5088 / FAX : 86-512-6251-5098 E-Mail : service@quietek.com

TABLE OF CONTENTS

Description	Page
1. General Information	6
1.1. EUT Description	6
1.2. Mode of Operation	8
1.3. Tested System Details	9
1.4. Configuration of Tested System	10
1.5. EUT Exercise Software	11
2. Technical Test	12
2.1. Summary of Test Result	12
2.2. Test Environment	13
3. Conducted Emission	14
3.1. Test Equipment	14
3.2. Test Setup	14
3.3. Limit	15
3.4. Test Procedure	15
3.5. Uncertainty	15
3.6. Test Result	16
4. Radiated Emission	18
4.1. Test Equipment	18
4.2. Test Setup	19
4.3. Limit	20
4.4. Test Procedure	20
4.5. Uncertainty	20
4.6. Test Result	21
5. RF Antenna Conducted Spurious	24
5.1. Test Equipment	24
5.2. Test Setup	24
5.3. Limit	24
5.4. Test Procedure	25
5.5. Uncertainty	25
5.6. Test Result	26
6. Radiated Emission Band Edge	27
6.1. Test Equipment	27
6.2. Test Setup	28
6.3. Limit	28
6.4. Test Procedure	28
6.5. Uncertainty	28
6.6. Test Result	29

7.	Operation Frequency Range of 20dB Bandwidth.....	37
7.1.	Test Equipment	37
7.2.	Test Setup	37
7.3.	Limit	37
7.4.	Test Procedure	37
7.5.	Uncertainty	37
7.6.	Test Result	38
8.	Occupied Bandwidth	39
8.1.	Test Equipment	39
8.2.	Test Setup	39
8.3.	Limit	39
8.4.	Test Procedure	39
8.5.	Uncertainty	39
8.6.	Test Result	40
9.	Power Output	42
9.1.	Test Equipment	42
9.2.	Test Setup	42
9.3.	Limit	42
9.4.	Test Procedure	42
9.5.	Uncertainty	43
9.6.	Test Result	44
10.	Power Spectral Density	45
10.1.	Test Equipment	45
10.2.	Test Setup	45
10.3.	Limit	45
10.4.	Test Procedure	45
10.5.	Uncertainty	46
10.6.	Test Result	47

1. General Information

1.1. EUT Description

Product Name	Q Light Engine
Brand Name	Q-Point
Model No.	QPI-1
Working Voltage	DC 5V
Antenna Type	PIFA antenna
Bluetooth	
Frequency Range	2402 - 2480 MHz
Channel Number	79
Type of Modulation	FHSS
Bluetooth Version	4.0+HS
Type of modulation	V3.0+HS: GFSK, Pi/4 DQPSK, 8DPSK V4.0: GFSK
Data Rate	V3.0+HS: 1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK) V4.0: 1Mbps(GFSK)
Antenna Gain	2.6dBi
Wi-Fi	
Frequency Range	802.11b/g/n(20MHz): 2412 ~ 2462 MHz 802.11n(40MHz): 2422 ~ 2452 MHz
Channel Number	802.11b/g/n(20MHz): 13 802.11n(40MHz): 9
Type of modulation	802.11b: DSSS; 802.11g/n: OFDM
Data Rate	802.11b: 1/2/5.5/11 Mbps
	802.11g: 6/9/12/18/24/36/48/54 Mbps
	802.11n: up to 150 Mbps
Channel Control	Auto
Antenna Gain	2.6dBi
Components	
Adapter	Brand Name: DVE M/N: DSA-20PFE-05 FUS 050300 Input: 100-240V~50/60Hz 0.7A Output: 5V, 3A

Bluetooth Working Frequency of Each Channel: (For V3.0+HS)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz	03	2405 MHz
04	2406 MHz	05	2407 MHz	06	2408 MHz	07	2409 MHz
08	2410 MHz	09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz	15	2417 MHz
16	2418 MHz	17	2419 MHz	18	2420 MHz	19	2421 MHz
20	2422 MHz	21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz	27	2429 MHz
28	2430 MHz	29	2431 MHz	30	2432 MHz	31	2433 MHz
32	2434 MHz	33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz	39	2441 MHz
40	2442 MHz	41	2443 MHz	42	2444 MHz	43	2445 MHz
44	2446 MHz	45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz	51	2453 MHz
52	2454 MHz	53	2455 MHz	54	2456 MHz	55	2457 MHz
56	2458 MHz	57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz	63	2465 MHz
64	2466 MHz	65	2467 MHz	66	2468 MHz	67	2469 MHz
68	2470 MHz	69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz	75	2477 MHz
76	2478 MHz	77	2479 MHz	78	2480 MHz	N/A	N/A

Bluetooth Working Frequency of Each Channel: (For V4.0)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz	03	2408 MHz
04	2410 MHz	05	2412 MHz	06	2414 MHz	07	2416 MHz
08	2418 MHz	09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz	15	2432 MHz
16	2434 MHz	17	2436 MHz	18	2438 MHz	19	2440 MHz
20	2442 MHz	21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz	27	2456 MHz
28	2458 MHz	29	2460 MHz	30	2462 MHz	31	2464 MHz
32	2466 MHz	33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz	39	2480 MHz

1.2. Mode of Operation

QuieTek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmit-1Mbps(GFSK_BLE)

Note:


1. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. For portable device, radiated spurious emission was verified over X, Y, Z Axis, and shown the worst case on this report.

1.3. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook	DELL	E520	N/A	Non-Shielded, 1.8m

1.4. Configuration of Tested System



1.5. EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of equipment.
3	Run the RF test software "REALTEK", and set the test mode and channel, then press OK to start continue transmit or receive.

2. Technical Test

2.1. Summary of Test Result

- ☒ No deviations from the test standards
- ☐ Deviations from the test standards as below description:

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.207	Yes	No
Radiated Emission	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.209	Yes	No
RF Antenna Conducted Spurious	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(d)	Yes	No
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2012 15.247(d)	Yes	No
Operation Frequency Range of 20dB Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2012 15.215(c)	Yes	No
Occupied Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(a)(2)	Yes	No
Power Output	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(b)(3)	Yes	No
Power Spectral Density	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(e)	Yes	No

2.2. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

3. Conducted Emission


3.1. Test Equipment

Conducted Emission / TR-1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
EMI Test Receiver	R&S	ESCI	100726	2015.03.30
Two-Line V-Network	R&S	ENV216	100043	2015.03.30
Two-Line V-Network	R&S	ENV216	100044	2014.09.16
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2015.03.01
50ohm Termination	SHX	TF2	07081401	2014.09.16
Temperature/Humidity Meter	zhicheng	ZC1-2	TR1-TH	2015.01.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 – 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

3.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2009 and tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs) Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.


The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.

3.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB


3.6. Test Result

Engineer: Toms	
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Line
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1		0.154	49.533	39.660	-16.248	65.781	9.873	QP
2		0.154	23.433	13.560	-32.348	55.781	9.873	AV
3	*	0.178	51.502	41.645	-13.076	64.578	9.857	QP
4		0.178	40.355	30.498	-14.223	54.578	9.857	AV
5		0.194	45.269	35.419	-18.595	63.864	9.850	QP
6		0.194	29.599	19.749	-24.265	53.864	9.850	AV
7		0.214	46.264	36.414	-16.785	63.049	9.850	QP
8		0.214	28.609	18.759	-24.440	53.049	9.850	AV
9		0.234	46.192	36.342	-16.115	62.307	9.850	QP
10		0.234	30.593	20.743	-21.714	52.307	9.850	AV
11		0.262	44.054	34.208	-17.314	61.368	9.846	QP
12		0.262	29.700	19.854	-21.668	51.368	9.846	AV

Engineer: Toms	
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Neutral
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.178	50.354	40.490	-14.224	64.578	9.864	QP
2		0.178	34.501	24.637	-20.077	54.578	9.864	AV
3		0.198	41.173	31.313	-22.521	63.694	9.860	QP
4		0.198	16.003	6.143	-37.691	53.694	9.860	AV
5		0.226	44.429	34.569	-18.166	62.595	9.860	QP
6		0.226	29.430	19.570	-23.165	52.595	9.860	AV
7		0.258	31.985	22.128	-29.511	61.496	9.857	QP
8		0.258	10.225	0.368	-41.271	51.496	9.857	AV
9		0.310	35.178	25.328	-24.792	59.970	9.850	QP
10		0.310	20.691	10.841	-29.279	49.970	9.850	AV
11		0.538	33.624	23.794	-22.376	56.000	9.830	QP
12		0.538	25.516	15.686	-20.484	46.000	9.830	AV

4. Radiated Emission

4.1. Test Equipment

Radiated Emission / AC-2


Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
EMI Test Receiver	R&S	ESCI	100573	2014.04.30
Loop Antenna	R&S	HFH2-Z2	833799/003	2015.11.25
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2014.10.15
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2015.03.01
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC2-TH	2015.01.08

Radiated Emission / AC-5


Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2015.03.30
Preamplifier	Miteq	NSP1800-25	1364185	2014.05.03
Preamplifier	QuieTek	AP-040G	CHM-0906001	2014.05.03
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2014.10.15
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2014.06.08
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2014.11.24
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2015.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2015.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2015.03.01
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC5-TH	2015.01.08

4.2. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2009 and tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2009 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the "cone of radiation" of EUT. The 3dB beamwidth is 10~60 degrees for H-plane and 10~90 degrees for E-plane.

4.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB
below 1G is defined as ± 3.8 dB

4.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;

Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Measure Level = Reading Level + Cable Loss + Antenna Factor - Preamplifier Gain

Mode 1: Transmitter-1Mbps(GFSK_BLE)


CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	4804.0	50.7	-6.2	44.5	54(Note2)	-9.5	PK
	V	4804.0	51.3	-6.3	45.0	54(Note2)	-9.0	PK
	H	7206.0	43.0	-1.7	41.3	54(Note2)	-12.7	PK
	V	7206.0	43.1	-1.7	41.4	54(Note2)	-12.6	PK
	H	9608.0	36.5	4.9	41.4	54(Note2)	-12.6	PK
	V	9608.0	36.8	4.9	41.7	54(Note2)	-12.3	PK
19	H	4880.0	50.6	-6.2	44.4	54(Note2)	-9.6	PK
	V	4880.0	51.2	-6.2	45.0	54(Note2)	-9.0	PK
	H	7320.0	41.3	-1.4	39.9	54(Note2)	-14.1	PK
	V	7320.0	41.3	-1.4	39.9	54(Note2)	-14.1	PK
	H	9760.0	36.0	5.1	41.1	54(Note2)	-12.9	PK
	V	9760.0	37.1	5.2	42.3	54(Note2)	-11.7	PK
39	H	4960.0	50.1	-6.3	43.8	54(Note2)	-10.2	PK
	V	4960.0	49.6	-6.1	43.5	54(Note2)	-10.5	PK
	H	7440.0	40.3	-0.8	39.5	54(Note2)	-14.5	PK
	V	7440.0	41.7	-0.8	40.9	54(Note2)	-13.1	PK
	H	9920.0	35.9	5.5	41.4	54(Note2)	-12.6	PK
	V	9920.0	35.7	5.5	41.2	54(Note2)	-12.8	PK

Note 1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.


The worst case of Radiated Emission below 1GHz:

Engineer: Toms	
Site: AC2	Time: 2013/09/23 - 20:00
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: CBL6112D_27613(30-1000MHz)	Polarity: Horizontal
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1: Transmit at channel 2480MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	192.960	27.853	17.501	-15.647	43.500	10.352	QP
2		355.920	29.445	13.020	-16.555	46.000	16.425	QP

Engineer: Toms	
Site: AC2	Time: 2013/09/23 - 20:00
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: CBL6112D_27613(30-1000MHz)	Polarity: Vertical
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1: Transmit at channel 2480MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		298.205	29.455	14.740	-16.545	46.000	14.715	QP
2	*	479.110	33.651	14.352	-12.349	46.000	19.299	QP

5. RF Antenna Conducted Spurious


5.1. Test Equipment

RF Antenna Conducted Spurious / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2015.01.07
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

5.2. Test Setup



5.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.


5.5. Uncertainty

The measurement uncertainty is defined as ± 1.27 dB

5.6. Test Result


Product	:	Q Light Engine
Test Item	:	RF Antenna Conducted Spurious
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmit-1Mbps(GFSK_BLE)

Channel 00 (2402MHz)




Note: The above test pattern is synthesized by multiple of the frequency range.

Channel 19 (2440MHz)



Note: The above test pattern is synthesized by multiple of the frequency range.

Channel 39 (2480MHz)



Note: The above test pattern is synthesized by multiple of the frequency range.

6. Radiated Emission Band Edge


6.1. Test Equipment

☒ Radiated Emission Band Edge / AC-5

Instrument	Manufacturer	Type No.	Serial No.	Cali. Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100159	2015.03.30
Preamplifier	Miteq	NSP1800-25	1364185	2014.05.03
Preamplifier	QuieTek	AP-040G	CHM-0906001	2014.05.03
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2014.10.15
DRG Horn	ETS-Lindgren	3117	00123988	2015.01.07
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2015.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2015.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2015.03.01
EMI Receiver	Agilent	N9038A	MY51210196	2014.06.09
Temperature/Humidity Meter	Zhichen	ZC1-2	AC5-TH	2015.01.08

Note 1: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

6.2. Test Setup



6.3. Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

6.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2009 and tested according to ANSI C63.10 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.


The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2009 on radiated measurement.

6.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB


6.6. Test Result

Engineer: Milo	
Site: AC5	Time: 2013/09/23 - 14:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1: Transmit at channel 2402MHz by BLE	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	52.128	14.969	-21.872	74.000	37.159	PK
2		*	2402.073	101.429	64.164	N/A	N/A	37.265	PK

Engineer: Milo	
Site: AC5	Time: 2013/09/23 - 14:37
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1: Transmit at channel 2402MHz by BLE	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	39.269	2.110	-14.731	54.000	37.159	AV
2		*	2402.073	79.043	41.778	N/A	N/A	37.265	AV

Engineer: Milo	
Site: AC5	Time: 2013/09/23 - 14:38
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1: Transmit at channel 2402MHz by BLE	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	51.380	14.881	-22.620	74.000	36.499	PK
2		*	2402.073	100.936	64.379	N/A	N/A	36.556	PK

Engineer: Milo	
Site: AC5	Time: 2013/09/23 - 14:40
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1: Transmit at channel 2402MHz by BLE	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	38.242	1.743	-15.758	54.000	36.499	AV
2		*	2402.073	78.647	42.090	N/A	N/A	36.556	AV

Engineer: Milo	
Site: AC5	Time: 2013/09/23 - 14:41
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1 Transmit at channel 2480MHz by BLE	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.738	103.087	65.150	N/A	N/A	37.937	PK
2			2483.500	56.014	18.044	-17.986	74.000	37.969	PK

Engineer: Milo	
Site: AC5	Time: 2013/09/23 - 14:44
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Horizontal
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1 Transmit at channel 2480MHz by BLE	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.046	80.213	42.274	N/A	N/A	37.939	AV
2			2483.500	42.125	4.155	-11.875	54.000	37.969	AV

Engineer: Milo	
Site: AC5	Time: 2013/09/23 - 14:45
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1 Transmit at channel 2480MHz by BLE	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	103.163	66.244	N/A	N/A	36.919	PK
2			2483.500	55.448	18.512	-18.552	74.000	36.935	PK

Engineer: Milo	
Site: AC5	Time: 2013/09/23 - 14:47
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: Q Light Engine	Power: AC 120V/60Hz
Note: Mode1 Transmit at channel 2480MHz by BLE	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.969	80.147	43.228	N/A	N/A	36.919	AV
2			2483.500	41.503	4.567	-12.497	54.000	36.935	AV

7. Operation Frequency Range of 20dB Bandwidth


7.1. Test Equipment

Operation Frequency Range of 20dB Bandwidth / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2015.01.07
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

7.2. Test Setup



7.3. Limit

20 dB bandwidth of the emission is contained within the operation frequency band.

7.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.



Set RBW = 100 kHz, Span greater than RBW.

7.5. Uncertainty

The measurement uncertainty is defined as ± 1 kHz

7.6. Test Result

Product	:	Q Light Engine
Test Item	:	Operation Frequency Range of 20dB Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmit-1Mbps(GFSK_BLE)



8. Occupied Bandwidth


8.1. Test Equipment

Occupied Bandwidth / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2015.01.07
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

8.2. Test Setup



8.3. Limit

The minimum 6dB bandwidth shall be at least 500 kHz.

8.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Span greater than RBW.

8.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

8.6. Test Result


Product	:	Q Light Engine
Test Item	:	6dB Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmit-1Mbps(GFSK_BLE)

Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)
00	2402	780
19	2440	770
39	2480	790


Channel 00 (2402MHz)



Channel 19 (2440MHz)



Channel 39 (2480MHz)



9. Power Output


9.1. Test Equipment

Power Output / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Wideband Peak Power Meter	Anritsu	ML2495A	0905006	2014.11.01
Power Sensor	Anritsu	MA2411B	0846014	2014.11.01
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

9.2. Test Setup



9.3. Limit

The maximum peak power shall be less 1 Watt (30dBm).

Note: the conducted output power limit specified above is based on the use the antennas with directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values above, as appropriate, by the amount in dB that the directional gain of antenna exceeds 6 dBi.

9.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Use the broadband peak RF power meter to test peak power and record the result.

9.5. Uncertainty

The measurement uncertainty is defined as ± 1.27 dB

9.6. Test Result

Product	:	Q Light Engine
Test Item	:	Power Output
Test Site	:	TR8
Test Mode	:	Mode 1: Transmit-1Mbps(GFSK_BLE)

Channel No.	Frequency (MHz)	Power Output (dBm)	Limit (dBm)	Result
00	2402	1.54	30.00	Pass
19	2440	1.21	30.00	Pass
39	2480	0.34	30.00	Pass

10. Power Spectral Density


10.1. Test Equipment

Power Spectral Density / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2015.01.07
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

10.2. Test Setup



10.3. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiated to the Antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

10.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Set analyzer center frequency to DTS channel center frequency, the span to 1.5 times the DTS channel bandwidth, $RBW \geq 3 \text{ kHz}$, Set $VBW \geq 3 * RBW$, Sweep time = auto couple, Detector = peak, Trace mode = max hold, Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level. If measured value exceed limit reduce

RBW (no less than 3kHz) and repeat.


10.5. Uncertainty

The measurement uncertainty is defined as ± 1.27 dB


10.6. Test Result

Product	:	Q Light Engine
Test Item	:	Power Spectral Density
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmit-1Mbps(GFSK_BLE)


Channel No.	Frequency (MHz)	Measurement PPSD (dBm)	Total PPSD (dBm)	Limit (dBm)	Result
00	2402	-13.66	-13.66	8	Pass
19	2440	-14.64	-14.64	8	Pass
39	2480	-15.52	-15.52	8	Pass



Channel 19 (2440MHz)



Channel 39 (2480MHz)



The End