



FCC Part15.247 Test Report

Product Name : Q TV Engine
Model No. : QP-168
FCC ID : 2AA45-QP168

Applicant : Q-Point Technology Inc
Address : 6F.-17, No.73, Sec. 2, Xinsheng N. Rd., Zhongshan
Dist., Taipei City 104, Taiwan

Date of Receipt : 13/09/2013
Test Date : 13/09/2013~28/09/2013
Issued Date : 11/10/2013
Report No. : 139S041R-RF-US-P06V01
Report Version : V 1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the Government.
The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

Test Report Certification

Issued Date : 11/10/2013

Report No. : 139S041R-RF-US-P06V01



Product Name : Q TV Engine

Applicant : Q-Point Technology Inc

Address : 6F.-17, No.73, Sec. 2, Xincheng N. Rd., Zhongshan Dist.,
Taipei City 104, Taiwan

Manufacturer : Kunshan Heisei Electronics Co.,Ltd.

Address : No.758 Zhenchuan East Rd.,Kunshan City, China

Model No. : QP-168

FCC ID : 2AA45-QP168

EUT Voltage : 5V --- 2A

Trade Name : Q-Point

Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2012
ANSI C63.4: 2009
ANSI C63.10: 2009

Test Result : Complied

Performed Location : Suzhou EMC Laboratory
No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech
Development Zone., Suzhou, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392

Documented By : Alice Mi

Reviewed By : Jackzhong

Approved By : Jame yuan

Laboratory Information

We, **Quietek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C.	:	BSMI, NCC, TAF
Germany	:	TUV Rheinland
Norway	:	Nemko, DNV
USA	:	FCC
Japan	:	VCCI
China	:	CNAS

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site :<http://www.quietek.com/tw/ctg/cts/accreditations.htm>

The address and introduction of Quietek Corporation's laboratories can be founded in our Web site :
<http://www.quietek.com/>

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yonghxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.

TEL:+886-3-592-8858 / FAX:+886-3-592-8859

E-Mail : service@quietek.com

LinKou Testing Laboratory :

No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451, Taiwan, R.O.C.

TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789

E-Mail : service@quietek.com

Suzhou Testing Laboratory :

No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., SuZhou, China

TEL : +86-512-6251-5088 / FAX : 86-512-6251-5098

E-Mail : service@quietek.com

TABLE OF CONTENTS

Description	Page
1. General Information	6
1.1. EUT Description	6
1.2. Mode of Operation	8
1.3. Tested System Details	10
1.4. Configuration of Tested System	11
1.5. EUT Exercise Software	12
2. Technical Test	13
2.1. Summary of Test Result	13
2.2. Test Environment	14
3. Conducted Emission	15
3.1. Test Equipment	15
3.2. Test Setup	15
3.3. Limit	16
3.4. Test Procedure	16
3.5. Uncertainty	16
3.6. Test Result	16
4. Radiated Emission	19
4.1. Test Equipment	19
4.2. Test Setup	20
4.3. Limit	21
4.4. Test Procedure	21
4.5. Uncertainty	22
4.6. Test Result	23
5. 20dB Bandwidth	28
5.1. Test Equipment	28
5.2. Test Setup	28
5.3. Limit	28
5.4. Test Procedure	29
5.5. Uncertainty	29
5.6. Test Result	30
6. Carrier Frequency Separation	36
6.1. Test Equipment	36
6.2. Test Setup	36
6.3. Limit	36
6.4. Test Procedure	37
6.5. Uncertainty	37
6.6. Test Result	38
7. Number of Hopping Frequencies	44
7.1. Test Equipment	44
7.2. Test Setup	44
7.3. Limit	44
7.4. Test Procedure	45
7.5. Uncertainty	45
7.6. Test Result	46
8. Time of Occupancy (Dwell Time)	55
8.1. Test Equipment	55
8.2. Test Setup	55
8.3. Limit	55
8.4. Test Procedure	56
8.5. Uncertainty	56
8.6. Test Result	57
9. Peak Output Power	63
9.1. Test Equipment	63
9.2. Test Setup	63
9.3. Limit	63

9.4.	Test Procedure	64
9.5.	Uncertainty	64
9.6.	Test Result	65
10.	Band-edge Compliance of RF Conducted Emissions	71
10.1.	Test Equipment	71
10.2.	Test Setup	71
10.3.	Limit.....	71
10.4.	Test Procedure	72
10.5.	Uncertainty	72
10.6.	Test Result	73
11.	Spurious RF Conducted Emissions.....	77
11.1.	Test Equipment	77
11.2.	Test Setup	77
11.3.	Limit.....	77
11.4.	Test Procedure	78
11.5.	Uncertainty	78
11.6.	Test Result	79
12.	Radiated Emission Band Edge	85
12.1.	Test Equipment	85
12.2.	Test Setup	86
12.3.	Limit.....	86
12.4.	Test Procedure	86
12.5.	Uncertainty	87
12.6.	Test Result	88

1. General Information

1.1. EUT Description

Product	Q TV Engine
Brand Name	Q-Point
Model No.	QP-168
Working Voltage	5V \pm 2A
Frequency Range	2402- 2480 MHz
Channel Number	79
Channel Separation	V3.0+HS: 1MHz V4.0: 2MHz
Type of Modulation	V3.0+HS: GFSK, Pi/4 DQPSK, 8DPSK V4.0: GFSK
Data Rate	V3.0+HS: 1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK) V4.0: 1Mbps(GFSK)
Antenna Type	Reference to Antenna List
Peak Antenna Gain	Reference to Antenna List

Component	
Car Charger	M/N: BX0502000 Input: 100V-240V -50/60Hz Output: 5V 2000mA DC

Bluetooth Working Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz	03	2405 MHz
04	2406 MHz	05	2407 MHz	06	2408 MHz	07	2409 MHz
08	2410 MHz	09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz	15	2417 MHz
16	2418 MHz	17	2419 MHz	18	2420 MHz	19	2421 MHz
20	2422 MHz	21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz	27	2429 MHz
28	2430 MHz	29	2431 MHz	30	2432 MHz	31	2433 MHz
32	2434 MHz	33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz	39	2441 MHz
40	2442 MHz	41	2443 MHz	42	2444 MHz	43	2445 MHz
44	2446 MHz	45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz	51	2453 MHz
52	2454 MHz	53	2455 MHz	54	2456 MHz	55	2457 MHz
56	2458 MHz	57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz	63	2465 MHz
64	2466 MHz	65	2467 MHz	66	2468 MHz	67	2469 MHz
68	2470 MHz	69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz	75	2477 MHz
76	2478 MHz	77	2479 MHz	78	2480 MHz	N/A	N/A

Bluetooth Working Frequency of Each Channel: (For V4.0)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz	03	2408 MHz
04	2410 MHz	05	2412 MHz	06	2414 MHz	07	2416 MHz
08	2418 MHz	09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz	15	2432 MHz
16	2434 MHz	17	2436 MHz	18	2438 MHz	19	2440 MHz
20	2442 MHz	21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz	27	2456 MHz
28	2458 MHz	29	2460 MHz	30	2462 MHz	31	2464 MHz
32	2466 MHz	33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz	39	2480 MHz

Bluetooth Antenna List

Antenna	Manufacturer	Model No.	Peak Gain
PCB antenna	ShenZhen Landy Antenna Technology Co.,Ltd	LY-WIFI-PCB90L	2.23dBi for 2.4GHz

1.2. Mode of Operation

QuieTek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmitter-1Mbps(GFSK_DH5)
Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)
Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Note:


1. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. For portable device, radiated spurious emission was verified over X, Y, Z axis, and shown the worst case on this report.
3. This portable device is accordance with Part 15 Subpart B regulations. The report number is 139S041R-RF-US-P01V02.

1.3. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	N/A	N/A	N/A	N/A	N/A

1.4. Configuration of Tested System



1.5. EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of equipment.
3	Run the RF test software “REALTEK” , and set the test mode and channel, then press OK to start continue Transmit or receive.

2. Technical Test

2.1. Summary of Test Result

☒ No deviations from the test standards

☐ Deviations from the test standards as below description:

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.207	Yes	No
Radiated Emission	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.209	Yes	No
20dB Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(a)(1)	Yes	No
Carrier Frequency Separation	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(a)(1)	Yes	No
Number of Hopping Frequencies	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(a)(1)(iii)	Yes	No
Time of Occupancy (Dwell Time)	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(a)(1)(iii)	Yes	No
Peak Output Power	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.247(b)(1)	Yes	No
Band-edge Compliance of RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2012 Section 15.215(c), 15.247(d)	Yes	No
Spurious RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2012 15.247(d)	Yes	No
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2012 15.247(d)	Yes	No

2.2. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

3. Conducted Emission


3.1. Test Equipment

Conducted Emission / TR-1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100726	2014.03.30
Two-Line V-Network	R&S	ENV216	100043	2014.03.30
Two-Line V-Network	R&S	ENV216	100044	2014.09.16
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2014.03.01
50ohm Termination	SHX	TF2	07081401	2014.09.16
Temperature/Humidity Meter	zhicheng	ZC1-2	TR1-TH	2014.01.10

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

3.4. Test Procedure

According to FCC ANSI C63.4: 2009 & ANSI C63.10: 2009.

The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)

Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.


Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

3.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB


3.6. Test Result

Engineer: Milo	
Site: TR1	Time: 2013/09/29 - 17:03
Limit: FCC_Part15.107_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Neutral
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1		0.211	40.362	30.448	-22.804	63.166	9.914	QP
2		0.211	28.462	18.548	-24.704	53.166	9.914	AV
3		0.270	43.254	33.319	-17.864	61.118	9.935	QP
4	*	0.270	35.266	25.331	-15.852	51.118	9.935	AV
5		0.342	39.632	29.661	-19.523	59.155	9.971	QP
6		0.342	32.666	22.695	-16.489	49.155	9.971	AV
7		0.610	31.992	22.031	-24.008	56.000	9.961	QP
8		0.610	29.021	19.060	-16.979	46.000	9.961	AV
9		3.790	30.849	20.805	-25.151	56.000	10.044	QP
10		3.790	13.960	3.916	-32.040	46.000	10.044	AV
11		11.650	26.444	16.126	-33.556	60.000	10.318	QP
12		11.650	15.914	5.596	-34.086	50.000	10.318	AV

Engineer: Milo	
Site: TR1	Time: 2013/09/29 - 17:04
Limit: FCC_Part15.107_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Line
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1		0.206	48.911	39.050	-14.454	63.365	9.861	QP
2	*	0.206	39.811	29.950	-13.554	53.365	9.861	AV
3		0.274	42.118	32.248	-18.878	60.996	9.870	QP
4		0.274	34.422	24.552	-16.574	50.996	9.870	AV
5		0.478	33.676	23.768	-22.698	56.374	9.908	QP
6		0.478	30.472	20.564	-15.902	46.374	9.908	AV
7		0.954	29.832	20.016	-26.168	56.000	9.816	QP
8		0.954	28.693	18.877	-17.307	46.000	9.816	AV
9		4.014	39.079	29.242	-16.921	56.000	9.837	QP
10		4.014	32.263	22.426	-13.737	46.000	9.837	AV
11		20.954	29.008	18.473	-30.992	60.000	10.535	QP
12		20.954	22.607	12.072	-27.393	50.000	10.535	AV

4. Radiated Emission

4.1. Test Equipment

Radiated Emission / AC-2


Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
EMI Test Receiver	R&S	ESCI	100573	2014.04.30
Loop Antenna	R&S	HFH2-Z2	833799/003	2013.11.17
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2013.10.15
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2014.03.01
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC2-TH	2014.05.08

Radiated Emission / AC-5


Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2014.03.30
Preamplifier	Miteq	NSP1800-25	1364185	2014.05.03
Preamplifier	QuieTek	AP-040G	CHM-0906001	2014.05.03
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2013.10.15
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2014.06.08
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2013.11.24
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2014.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2014.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2014.03.01
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC5-TH	2014.01.11

4.2. Test Setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level.

This is repeated for both horizontal and vertical polarization of the antenna. In order to find the

maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2009 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the “cone of radiation” of EUT. The 3dB beamwidth is 60~10 degrees for H-plane and 90~10 degrees for E-plane.

4.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB

below 1G is defined as ± 3.8 dB

4.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;

Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Measure Level = Reading Level + Cable Loss + Antenna Factor – Preamplifier Gain

Mode 1: Transmitter-1Mbps(GFSK_DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	4804.0	45.2	-6.2	39.0	54(Note2)	-15.0	PK
	V	4804.0	45.3	-6.3	39.0	54(Note2)	-15.0	PK
	H	7206.0	41.6	-1.7	39.9	54(Note2)	-14.1	PK
	V	7206.0	41.9	-1.7	40.2	54(Note2)	-13.8	PK
	H	9608.0	35.6	4.9	40.5	54(Note2)	-13.5	PK
	V	9608.0	35.5	4.9	40.4	54(Note2)	-13.6	PK
39	H	4882.0	44.9	-6.2	38.7	54(Note2)	-15.3	PK
	V	4882.0	45.4	-6.2	39.2	54(Note2)	-14.8	PK
	H	7323.0	42.1	-1.4	40.7	54(Note2)	-13.3	PK
	V	7323.0	42.3	-1.4	40.9	54(Note2)	-13.1	PK
	H	9764.0	35.9	5.1	41.0	54(Note2)	-13.0	PK
	V	9764.0	35.9	5.2	41.1	54(Note2)	-12.9	PK
78	H	4960.0	44.7	-6.3	38.4	54(Note2)	-15.6	PK
	V	4960.0	44.6	-6.1	38.5	54(Note2)	-15.5	PK
	H	7440.0	40.0	-0.8	39.2	54(Note2)	-14.8	PK
	V	7440.0	41.0	-0.8	40.2	54(Note2)	-13.8	PK
	H	9920.0	35.5	5.5	41.0	54(Note2)	-13.0	PK
	V	9920.0	36.3	5.5	41.8	54(Note2)	-12.2	PK

Note 1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

3: Measure Level = Reading Level + Factor.

Mode 2: Transmitter-2Mbps(Pi/4 DQPSK _DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	4804.0	44.6	-6.2	38.4	54(Note2)	-15.6	PK
	V	4804.0	44.5	-6.3	38.2	54(Note2)	-15.8	PK
	H	7206.0	41.9	-1.7	40.2	54(Note2)	-13.8	PK
	V	7206.0	41.6	-1.7	39.9	54(Note2)	-14.1	PK
	H	9608.0	35.8	4.9	40.7	54(Note2)	-13.3	PK
	V	9608.0	35.1	4.9	40.0	54(Note2)	-14.0	PK
39	H	4882.0	44.4	-6.2	38.2	54(Note2)	-15.8	PK
	V	4882.0	44.9	-6.2	38.7	54(Note2)	-15.3	PK
	H	7323.0	42.4	-1.4	41.0	54(Note2)	-13.0	PK
	V	7323.0	42.9	-1.4	41.5	54(Note2)	-12.5	PK
	H	9764.0	36.3	5.1	41.4	54(Note2)	-12.6	PK
	V	9764.0	35.9	5.2	41.1	54(Note2)	-12.9	PK
78	H	4960.0	45.4	-6.3	39.1	54(Note2)	-14.9	PK
	V	4960.0	43.9	-6.1	37.8	54(Note2)	-16.2	PK
	H	7440.0	41.2	-0.8	40.4	54(Note2)	-13.6	PK
	V	7440.0	40.2	-0.8	39.4	54(Note2)	-14.6	PK
	H	9920.0	36.1	5.5	41.6	54(Note2)	-12.4	PK
	V	9920.0	35.5	5.5	41.0	54(Note2)	-13.0	PK

Note 1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

3: Measure Level = Reading Level + Factor.

Mode 3: Transmitter-3Mbps(8DPSK_DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	4804.0	44.1	-6.2	37.9	54(Note2)	-16.1	PK
	V	4804.0	44.7	-6.3	38.4	54(Note2)	-15.6	PK
	H	7206.0	41.3	-1.7	39.6	54(Note2)	-14.4	PK
	V	7206.0	41.9	-1.7	40.2	54(Note2)	-13.8	PK
	H	9608.0	35.4	4.9	40.3	54(Note2)	-13.7	PK
	V	9608.0	35.3	4.9	40.2	54(Note2)	-13.8	PK
39	H	4882.0	44.6	-6.2	38.4	54(Note2)	-15.6	PK
	V	4882.0	44.9	-6.2	38.7	54(Note2)	-15.3	PK
	H	7323.0	41.9	-1.4	40.5	54(Note2)	-13.5	PK
	V	7323.0	42.5	-1.4	41.1	54(Note2)	-12.9	PK
	H	9764.0	36.3	5.1	41.4	54(Note2)	-12.6	PK
	V	9764.0	36.3	5.2	41.5	54(Note2)	-12.5	PK
78	H	4960.0	44.6	-6.3	38.3	54(Note2)	-15.7	PK
	V	4960.0	44.7	-6.1	38.6	54(Note2)	-15.4	PK
	H	7440.0	41.6	-0.8	40.8	54(Note2)	-13.2	PK
	V	7440.0	40.8	-0.8	40.0	54(Note2)	-14.0	PK
	H	9920.0	35.9	5.5	41.4	54(Note2)	-12.6	PK
	V	9920.0	36.2	5.5	41.7	54(Note2)	-12.3	PK

Note 1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

3: Measure Level = Reading Level + Factor.

The worst case of Radiated Emission below 1GHz:

Engineer: Toms

Site: AC2

Time: 2013/09/18 - 19:47

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: CBL6112D_27611(30-1000MHz)

Polarity: Vertical

EUT: Q TV Engine

Power: AC 120V/60Hz

Note: Mode1: Transmit at channel 2402MHz by DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	111.844	23.397	4.787	-20.103	43.500	18.610	QP
2		165.194	19.841	3.356	-23.659	43.500	16.485	QP

Engineer: Toms

Site: AC2

Time: 2013/09/18 - 19:50

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: CBL6112D_27611(30-1000MHz)

Polarity: Horizontal

EUT: Q TV Engine

Power: AC 120V/60Hz

Note: Mode1: Transmit at channel 2402MHz by DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	111.844	23.397	4.787	-20.103	43.500	18.610	QP
2		172.226	20.156	3.970	-23.344	43.500	16.186	QP

5. 20dB Bandwidth


5.1 Test Equipment

20dB Bandwidth / TR8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

5.2 Test Setup



5.3 Limit

- For frequency hopping systems operating in 2400-2483.5 MHz band, no limitation.
- For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

5.4 Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel

RBW \cong 1% of the 20dB bandwidth

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize.

Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

5.5 Uncertainty


The measurement uncertainty is defined as ± 1 kHz

5.6 Test Result


Product	:	Q TV Engine
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)
00	2402	1150
39	2441	1140
78	2480	1150


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Q TV Engine
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)
00	2402	1350
39	2441	1350
78	2480	1340


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Q TV Engine
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)
00	2402	1410
39	2441	1400
78	2480	1410


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



6. Carrier Frequency Separation


6.1. Test Equipment

Carrier Frequency Separation / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

6.2. Test Setup



6.3. Limit

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping

channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

6.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) \geq 1% of the span

Video (or Average) Bandwidth VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

6.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

6.6. Test Result


Product	:	Q TV Engine
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	: Q TV Engine
Test Item	: Carrier Frequency Separation
Test Site	: TR-8
Test Mode	: Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Q TV Engine
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



7. Number of Hopping Frequencies


7.1. Test Equipment

Number of Hopping Frequencies / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

7.2. Test Setup



7.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.
- For frequency hopping systems operating in 902-928 MHz band shall use at least 50 hopping frequencies.
- For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.

7.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW \cong 1% of the span

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to bread the span up to sections, in order to clearly show all of the hopping frequencies.

7.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

7.6. Test Result


Product	:	Q TV Engine
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz




2462 - 2480 MHz




Product	:	Q TV Engine
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz




2462 - 2480 MHz




Product	:	Q TV Engine
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz



2462 - 2480 MHz



8. Time of Occupancy (Dwell Time)


8.1. Test Equipment

Time of Occupancy (Dwell Time) / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

8.2. Test Setup



8.3. Limit

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75

hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

- Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1MHz

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

8.5. Uncertainty

The measurement uncertainty is defined as ± 0.1 us

8.6. Test Result


Product	:	Q TV Engine
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-3Mbps (8DPSK_DH1)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	124.80	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6$ sec, Hopping Times Within 1sec: $40/50$ msec=800 hops/sec.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(0.39\text{ms} \times 800)/79] \times 31.6 = 124.80$ msec

Channel 39 (2441MHz)-(3DH1)






Product	:	Q TV Engine
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-3Mbps (8DPSK_DH3)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	260.8	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6\text{sec}$, Hopping Times Within 1sec: $20/50\text{msec} = 400\text{hops/sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(1.63\text{ms} \times 400)/79] \times 31.6 = 260.8\text{msec}$

Channel 39 (2441MHz) - (3DH3)






Product	:	Q TV Engine
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-3Mbps (8DPSK_DH5)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	299.52	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6\text{sec}$, Hopping Times Within 1sec: $14/50\text{msec} = 280\text{ hops/sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(2.88\text{ms} \times 280)/79] \times 31.6 = 299.52\text{msec}$

Channel 39 (2441MHz) - (3DH5)





9. Peak Output Power


9.1. Test Equipment

Peak Output Power / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

9.2. Test Setup



9.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
- For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

Note: the conducted output power limit specified above is based on the use the antennas with

directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values above, as appropriate, by the amount in dB that the directional gain of antenna exceeds 6 dBi.

9.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel

RBW $>$ the 20 dB bandwidth of the emission being measured.

VBW \cong RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss).

9.5. Uncertainty


The measurement uncertainty is defined as ± 1.0 dB

9.6. Test Result


Product	:	Q TV Engine
Test Item	:	Power Output
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	7.38	30.00	Pass
39	2441	6.40	30.00	Pass
78	2480	5.41	30.00	Pass


DH5 2402MHz



DH5 2441MHz




DH5 2480MHz




Product	:	Q TV Engine
Test Item	:	Power Output
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	8.30	30.00	Pass
39	2441	7.63	30.00	Pass
78	2480	6.78	30.00	Pass


2DH5 2402MHz



2DH5 2441MHz




2DH5 2480MHz




Product	:	Q TV Engine
Test Item	:	Power Output
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	8.72	30.00	Pass
39	2441	7.92	30.00	Pass
78	2480	7.00	30.00	Pass


3DH5 2402MHz



3DH5 2441MHz



3DH5 2480MHz



10. Band-edge Compliance of RF Conducted Emissions


10.1. Test Equipment

Band-edge Compliance of RF Conducted Emissions / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

10.2. Test Setup



10.3. Limit

- Intentional radiators operating under the alternative provisions to the general emission limits as contained in 15.217 through 15.257 and in Subpart E of FCC part 15, must be designed to ensure that 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz

bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) of FCC part 15 is not required.

10.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation.

RBW \geq 1% of the span

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge.

Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.


10.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB


10.6. Test Result

Product	:	Q TV Engine
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel 00 (2402MHz)




Channel 78 (2480MHz)




Product	:	Q TV Engine
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel 00 (2402MHz)




Channel 78 (2480MHz)




Product	:	Q TV Engine
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)



Channel 00 (2402MHz)



Channel 78 (2480MHz)



Product	: Q TV Engine
Test Item	: Band-edge Compliance of RF Conducted Emissions
Test Mode	: Mode: Hopping Mode



11. Spurious RF Conducted Emissions


11.1. Test Equipment

Spurious RF Conducted Emissions / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2014.01.21
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2014.05.08

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

11.2. Test Setup



11.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in

Section 15.209(a) of FCC part 15 is not required.

11.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.

The level displayed must comply with the limit specified in this section.

11.5. Uncertainty


The measurement uncertainty is defined as ± 1.0 dB

11.6. Test Result


Product	:	Q TV Engine
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel 00 (2402MHz)


3



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Q TV Engine
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Q TV Engine
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)




12. Radiated Emission Band Edge

12.1. Test Equipment

☒ Radiated Emission Band Edge / AC-5

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2014.03.30
Preamplifier	Miteq	NSP1800-25	1364185	2014.05.03
Preamplifier	QuieTek	AP-040G	CHM-0906001	2014.05.03
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2013.10.15
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2014.06.08
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2013.11.24
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2014.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2014.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2014.03.01
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC5-TH	2014.01.11

12.2. Test Setup



12.3. Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) of FCC part 15.

12.4. Test Procedure

According to ANSI C63.10: 2009.

This test is required for any spurious emission or modulation product that falls in a Restricted Band, as defined in Section 15.205 of FCC part 15. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being

corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b) of FCC part 15.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209 of FCC Part 15. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit of FCC part 15.

If the emission on which a radiated measurement must be made is located at the edge of the authorized band of operation, then the alternative “marker-delta” method may be employed.

12.5. Uncertainty

The measurement uncertainty above 1G is defined as $\pm 3.9 \text{ dB}$

below 1G is defined as $\pm 3.8 \text{ dB}$


12.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;


Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:02
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Vertical
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode1: Transmit at channel 2402MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	51.792	24.110	-22.208	74.000	27.682	PK
2	*	2401.791	89.349	61.620	N/A	N/A	27.729	PK

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Vertical
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode1: Transmit at channel 2402MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	38.814	11.132	-15.186	54.000	27.682	AV
2	*	2401.885	75.441	47.712	N/A	N/A	27.729	AV

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:12
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Horizontal
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode1: Transmit at channel 2402MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	51.627	23.945	-22.373	74.000	27.682	PK
2	*	2401.885	86.583	58.854	N/A	N/A	27.729	PK

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:15
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Horizontal
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode1: Transmit at channel 2402MHz by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	38.782	11.100	-15.218	54.000	27.682	AV
2	*	2401.932	76.076	48.347	N/A	N/A	27.729	AV

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:16
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Vertical
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode1: Transmit at channel 2480MHz by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.057	88.197	60.153	N/A	N/A	28.044	PK
2		2483.500	60.246	32.189	-13.754	74.000	28.057	PK

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:20

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Vertical

EUT: Q TV Engine

Power: AC 120V/60Hz

Note: Mode1: Transmit at channel 2480MHz by DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.980	77.438	49.394	N/A	N/A	28.044	AV
2		2483.500	39.580	11.523	-14.420	54.000	28.057	AV

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:21

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Horizontal

EUT: Q TV Engine

Power: AC 120V/60Hz

Note: Mode1: Transmit at channel 2480MHz by DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.024	94.752	66.708	N/A	N/A	28.044	PK
2		2483.500	64.501	36.444	-9.499	74.000	28.057	PK

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:25

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Horizontal

EUT: Q TV Engine

Power: AC 120V/60Hz

Note: Mode1: Transmit at channel 2480MHz by DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.035	82.181	54.137	N/A	N/A	28.044	AV
2		2483.500	39.846	11.789	-14.154	54.000	28.057	AV

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:27

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Vertical

EUT: Q TV Engine


Power: AC 120V/60Hz

Note: Mode2: Transmit at channel 2402MHz by 2DH5




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	51.624	23.942	-22.376	74.000	27.682	PK
2	*	2402.120	89.465	61.735	N/A	N/A	27.730	PK

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:30
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Vertical
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode2: Transmit at channel 2402MHz by 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	38.837	11.155	-15.163	54.000	27.682	AV
2	*	2401.838	77.074	49.345	N/A	N/A	27.729	AV

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:30
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Horizontal
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode2: Transmit at channel 2402MHz by 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	52.075	24.393	-21.925	74.000	27.682	PK
2	*	2402.026	87.459	59.729	N/A	N/A	27.730	PK

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:33

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Horizontal

EUT: Q TV Engine

Power: AC 120V/60Hz

Note: Mode2: Transmit at channel 2402MHz by 2DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	38.753	11.071	-15.247	54.000	27.682	AV
2	*	2401.885	75.788	48.059	N/A	N/A	27.729	AV

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:34

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Vertical

EUT: Q TV Engine

Power: AC 120V/60Hz

Note: Mode2: Transmit at channel 2480MHz by 2DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.068	89.205	61.161	N/A	N/A	28.044	PK
2		2483.500	58.201	30.144	-15.799	74.000	28.057	PK

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:37

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Vertical

EUT: Q TV Engine

Power: AC 120V/60Hz

Note: Mode2: Transmit at channel 2480MHz by 2DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.947	77.020	48.976	N/A	N/A	28.044	AV
2		2483.500	39.569	11.512	-14.431	54.000	28.057	AV

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:38

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Horizontal

EUT: Q TV Engine

Power: AC 120V/60Hz

Note: Mode2: Transmit at channel 2480MHz by 2DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.123	95.677	67.633	N/A	N/A	28.044	PK
2		2483.500	64.984	36.927	-9.016	74.000	28.057	PK

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:41

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Horizontal

EUT: Q TV Engine

Power: AC 120V/60Hz

Note: Mode2: Transmit at channel 2480MHz by 2DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.958	82.089	54.045	N/A	N/A	28.044	AV
2		2483.500	39.813	11.756	-14.187	54.000	28.057	AV

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:42

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Horizontal

EUT: Q TV Engine


Power: AC 120V/60Hz

Note: Mode3: Transmit at channel 2402MHz by 3DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	51.894	24.212	-22.106	74.000	27.682	PK
2	*	2401.885	86.697	58.968	N/A	N/A	27.729	PK

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:45
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Horizontal
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode3: Transmit at channel 2402MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	38.844	11.162	-15.156	54.000	27.682	AV
2	*	2401.838	72.999	45.270	N/A	N/A	27.729	AV

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:47

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Vertical

EUT: Q TV Engine


Power: AC 120V/60Hz

Note: Mode3: Transmit at channel 2402MHz by 3DH5



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	53.269	25.587	-20.731	74.000	27.682	PK
2	*	2402.026	89.015	61.285	N/A	N/A	27.730	PK

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Vertical
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode3: Transmit at channel 2402MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	38.849	11.167	-15.151	54.000	27.682	AV
2	*	2401.744	73.901	46.173	N/A	N/A	27.729	AV

Engineer: Toms

Site: AC5

Time: 2013/09/17 - 14:51

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_3117_988(1-18GHz)(1-18GHz)

Polarity: Vertical

EUT: Q TV Engine


Power: AC 120V/60Hz

Note: Mode3: Transmit at channel 2480MHz by 3DH5




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.024	88.924	60.880	N/A	N/A	28.044	PK
2		2483.500	53.736	25.679	-20.264	74.000	28.057	PK

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:55
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Vertical
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode3: Transmit at channel 2480MHz by 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.969	75.558	47.514	N/A	N/A	28.044	AV
2		2483.500	39.639	11.582	-14.361	54.000	28.057	AV

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:55
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Horizontal
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode3: Transmit at channel 2480MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.914	95.022	66.979	N/A	N/A	28.043	PK
2		2483.500	64.855	36.798	-9.145	74.000	28.057	PK

Engineer: Toms	
Site: AC5	Time: 2013/09/17 - 14:59
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)(1-18GHz)	Polarity: Horizontal
EUT: Q TV Engine	Power: AC 120V/60Hz
Note: Mode3: Transmit at channel 2480MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.980	80.533	52.489	N/A	N/A	28.044	AV
2		2483.500	40.069	12.012	-13.931	54.000	28.057	AV

The End