

FCC PART 15.249
EMI MEASUREMENT AND TEST REPORT
For
CONVOY TECHNOLOGIES L.L.C.
3300 Irvine Ave, STE 310, Newport Beach, C.A, USA

FCC ID: 2AA4QCT-W1000KIT

Sep 27, 2013

This Report Concerns: Original Report	Equipment Type: Wireless video and audio transmitter
Test Engineer:	Lisa Chen <i>Lisa Chen</i>
Report No.:	BSL13095735Y-1ER-3
Receive EUT Date/Test Date:	Sep. 19, 2013 / Sep. 19-27, 2013
Reviewed By:	Sky Zhang <i>Sky Zhang</i>
Prepared By:	BSL Testing Co.,LTD. NO. 24, ZH Park, Nantou, Shenzhen, 518000 China Tel: 86- 755-26508703 Fax: 86- 755-26508703

Note: The test report is specially limited to the above company and this particular sample only.
It may not be duplicated without prior written consent of BSL Testing Co.,LTD.
This report must not be used by the client to claim product certification,approval,or
endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

1.	GENERAL INFORMATION	3
1.1.	Report information	3
1.2.	Measurement Uncertainty	3
2.	PRODUCT DESCRIPTION	4
2.1.	EUT Description	4
2.2.	Block Diagram of EUT Configuration.....	5
2.3.	Support Equipment List	5
2.4.	Test Conditions	5
3.	TEST RESULTS SUMMARY	6
	Modifications	6
4.	TEST EQUIPMENT USED	7
5.	ANTENNA REQUIREMENT	8
5.1.	Standard Applicable.....	8
5.2.	Antenna Connected Construction	8
5.3.	Result	8
6.	CONDUCTED POWER LINE TEST	9
6.1.	Test Equipment	9
6.2.	Test Procedure	9
6.3.	Test Setup.....	9
6.4.	Conducted Power line Emission Limits.....	9
6.5.	Conducted Power Line Test Result.....	10
7.	RADIATED EMISSION TEST	11
7.1.	Test Equipment	11
7.2.	Test Procedure	11
7.3.	Radiated Test Setup	11
7.4.	Radiated Emission Limit.....	13
7.5.	Radiated Emission Test Result	14
8.	BAND EDGE	19
8.1.	Test Equipment	19
8.2.	Test Procedure	19
8.3.	Band Edge FCC 15.249(d) Limit.....	19
8.4.	Band Edge Test Result.....	20
9.	20-DB BANDWIDTH	28
9.1.	Test Equipment	28
9.2.	Test Procedure	28
9.3.	Limit.....	28
9.4.	Test Result /Plots	28

1. GENERAL INFORMATION

1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BSL approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BSL in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BSL therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 1.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BSL, unless the applicant has authorized BSL in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of BSL Testing Co.,LTD.

(FCC Registered Test Site Number: 191509) on

NO. 24, ZH Park, Nantou, Shenzhen, 518000 China

The Test Site is constructed and calibrated to meet the FCC requirements.

1.2. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	+/-1.25dB
2	RF Power, Conducted	+/-0.20dB
3	Spurious emissions, conducted	+/-0.33dB
4	All emissions, radiated (<1G)	+/-3.47dB
5	All emissions, radiated (>1G)	+/-3.82dB
6	Temperature	+/-0.5°CdB
7	Humidity	+/-2%

2. PRODUCT DESCRIPTION

2.1. EUT Description

Description : Wireless video and audio transmitter
 Trade Name : Convoy Technologies
 Applicant : CONVOY TECHNOLOGIES L.L.C.
 3300 Irvine Ave, STE 310, Newport Beach, C.A, USA
 Manufacturer : INTEC INTERNATIONAL (H.K) LTD.
 Unit 2110, DiWang Apt, ShunHing Square, Luohu, Shenzhen, China
 Model Number : CT-W1000KIT, CT-W1000KIT-MCN, CT-W1000TX, CT-W1000RX, 1490159, 1490161
 Modulation type : 16QAM
 Antenna gain : 0dBi
 Antenna type : Integral Antenna
 Frequency : 2403-2478MHz
 Number of Channels : 26 Channels
 Power Supply : DC 12V By battery
 (the new battery is used during the measurement)

Channel List			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2403	14	2442
2	2406	15	2445
3	2409	16	2448
4	2412	17	2451
5	2415	18	2454
6	2418	19	2457
7	2421	20	2460
8	2424	21	2463
9	2427	22	2466
10	2430	23	2469
11	2433	24	2472
12	2436	25	2475
13	2439	26	2478

2.2. Block Diagram of EUT Configuration

Radiated emissions test




Figure 1 EUT Setup

2.3. Support Equipment List

Name	Model No	S/N	Manufacturer	Used “Yes/No”
--	--	--	--	--

2.4. Test Conditions

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-25
Humidity (%RH)	25-75	50-63
Barometric pressure (mbar)	860-1060	950-1000

3. TEST RESULTS SUMMARY

FCC 15 Subpart C, Paragraph 15.249

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.249(a)	The fundamental field strength and the harmonics	Compliant
Section 15.209 Section 15.249(d)	Radiated Emission	Compliant
Section 15.249(d)	Band Edge	Compliant
Section 15.203	Antenna Requirement	Compliant
Section 15.249	20dB Bandwidth	Compliant

Remark: "N/A" means "Not applicable".

Statement: All testing was performed using the test procedures found in ANSI C63.4-2003.

Standard:

FCC Part 15: 2012

Modifications

No modification was made.

4. TEST EQUIPMENT USED

EQUIPMENT/FACILITIES	MANUFACTURER	MODEL	SERIAL NO.	DATE OF CAL.	CAL. INTERVAL
3m Semi-Anechoic Chamber	Chengyu Electron	9 (L)*6 (W)* 6 (H)	BSL086	Aug. 23 2013	1 Year
EMI Test Receiver	Rohde & Schwarz	ESCI3	BSL001	Sep. 28 2012	1 Year
BiConiLog Antenna	Rohde & Schwarz	HL562	BSL009	Sep. 28 2012	1 Year
Double -ridged waveguide horn	Rohde & Schwarz	9120D	BSL008	Aug. 27 2013	1 Year
Horn Antenna	ETS-LINDGREN	3160	BSL072	Dec. 28 2012	1 Year
Cable	Rohde & Schwarz	N/A	BSL045	Aug. 27 2013	1 Year
Cable	Rohde & Schwarz	N/A	BSL046	Aug. 27 2013	1 Year
Cable	Rohde & Schwarz	N/A	BSL047	Aug. 27 2013	1 Year
Amplifier(100kHz-40G Hz)	R&S	SMR40	BSL007	Sep. 28 2012	1 Year
Band filter	Amindeon	82346	BSL049	Aug. 27 2013	1 Year
Active Loop Antenna	EMTES	EM15	BSL011	Sep. 28 2012	1 Year
Coaxial Switch	YUANFANG	TA218B	BSL004	Aug. 27 2013	1 Year
Spectrum analyzer	Rohde & Schwarz	FSP40	BSL049	Sep. 28 2012	1 Year

5. ANTENNA REQUIREMENT

5.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.2. Antenna Connected Construction

According to § 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The antenna used in this product is Integral Antenna. The antenna is permanently attached. Refer to the product photo.

5.3. Result

Compliance

6. CONDUCTED POWER LINE TEST

6.1. Test Equipment


Please refer to section 4 this report.

6.2. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.).This provides a 50ohm/50uh coupling inpedance for the measuring equipment.The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uh coupling inpedance with 50ohm termination.

Both sides of A.C. Line are check for maximum conducted interference.In order to find the maximum emission,the relative positions of equipment and all of the interface cables must be changed according to ASIN C63.4:2003 on conducted measurement .Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

6.3. Test Setup



For the actual test configuration,Please refer to the related items-Photos of testing

6.4. Conducted Power line Emission Limits

FCC Part 15 Paragraph 15.207 (dBuV)		
Frequency Range (MHZ)	Class A QP/AV	Class B QP/AV
0.15-0.5	79/66	65-56/56-46
0.5-5.0	73/60	56-46
5.0-3.0	73/60	60-50

Note: In the above table, the tighter limit applies at the band edges.

6.5. Conducted Power Line Test Result

N/A

This EUT is only powered by Car battery, therefore this test item is not applicable.

7. RADIATED EMISSION TEST

7.1. Test Equipment

Please refer to section 4 this report.

7.2. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level.

Calibrated Loop antenna is used as receiving antenna for frequencies below 30MHz, Calibrated Bilog antenna is used as receiving antenna for frequencies between 30 MHz and 1 GHz, Calibrated Horn antenna is used as receiving antenna for frequencies above 1000MHz. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver is set at 9kHz in below 30MHz. and set at 120kHz in 30-1000MHz, and 1MHz in above 1000MHz.


The frequency range from 9kHz to 25GHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Peak detector and Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.


Through three orthogonal axes to determine which attitude and equipment arrangement produces the highest emission relative to the limit. And X direction is worst mode

7.3. Radiated Test Setup


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.4. Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below :

A. Fundamental and Harmonics Radiated Emissions 15.249(a) Limit

Fundamental Frequency (MHZ)	Field as strength of Fundamental(3m)			Field as strength of Harmonics(3m)		
	mV/m	dBuV/m		uV/m	dBuV/m	
902-928	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)
2400-2483.5	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

(3) The emission limit in this paragraph is based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

B. Spurious Radiated Emissions.

Frequency (MHz)	Limit			
	Field Strength of Quasi-peak Value (microvolts/m)	Field Strength of Quasi-peak Value (dBμV/m)	Measurement distance (m)	The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
0.009 - 0.490	2400/F(kHz)	/	300	
0.490 - 1.705	24000/F(kHz)	/	30	
1.705-30	30	29.5	30	
30 - 88	100	40	3	
88 - 216	150	43.5	3	
216 - 960	200	46	3	
Above 960	500	54	3	

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

(2) In the Above Table, the tighter limit applies at the band edges.

(3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

7.5. Radiated Emission Test Result

Pass

A. Fundamental Radiated Emissions Data

CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2403	64.64/84.01	VERT	94/114	-29.36/-29.99
2403	66.80/85.09	HORIZ	94/114	-27.2/-28.91

CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2442	63.56/83.47	VERT	94/114	-30.44/-30.53
2442	65.32/84.59	HORIZ	94/114	-28.68/-29.41

CH High

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2478	62.04/81.30	VERT	94/114	-31.96/-32.7
2478	64.22/83.10	HORIZ	94/114	-29.78/-30.9

B. General Radiated Emissions Data

For below 9kHz-30MHz Spurious


Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
-	-	HORIZ	-	-
-	-	VERT	-	-

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.


For 30M-1000MHz Spurious

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain
Horizontal



Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV)	Margin (dB)	Detector
38.35	21.13	10.24	31.37	40.00	-8.63	Peak
107.89	21.78	10.26	32.04	43.50	-11.46	Peak
155.91	20.8	13.25	34.05	43.50	-9.45	Peak
227.04	22.36	14.53	36.89	46.00	-9.11	Peak
329.04	26.33	12.34	38.67	46.00	-7.33	Peak
691.99	31.38	11.25	42.63	46.00	-3.37	Peak

Vertical



Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV)	Margin (dB)	Detector
38.48	17.43	10.24	27.67	40.00	-12.33	Peak
107.89	18.56	10.26	28.82	43.50	-14.68	Peak
155.91	13.30	13.25	26.55	43.50	-16.95	Peak
239.99	13.09	14.41	27.50	46.00	-18.50	Peak
451.14	25.38	12.34	37.72	46.00	-8.28	Peak
570.61	27.09	11.32	38.41	46.00	-7.59	Peak

For 1000MHz-25000MHz Spurious**CH Low**

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4806.0	44.06/60.88	VERT	54.0/74.0	-9.94/-13.12
7209.0	43.54/61.43		54.0/74.0	-10.46/-12.57
9612.0	46.27/62.47		54.0/74.0	-7.73/-11.53
4806.0	45.32/62.35	HORIZ	54.0/74.0	-8.68/-11.65
7209.0	44.93/62.67		54.0/74.0	-9.07/-11.33
9612.0	46.37/63.55		54.0/74.0	-7.63/-10.45

CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4884.0	44.15/61.24	VERT	54.0/74.0	-9.85/-12.76
7326.0	44.12/61.57		54.0/74.0	-9.88/-12.43
9768.0	45.93/62.73		54.0/74.0	-8.07/-11.27
4884.0	45.12/62.49	HORIZ	54.0/74.0	-8.88/-11.51
7326.0	44.93/63.27		54.0/74.0	-9.07/-10.73
9768.0	46.21/63.87		54.0/74.0	-7.79/-10.13

CH High

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4956.0	44.52/62.34	VERT	54.0/74.0	-9.48/-11.66
7434.0	43.62/61.49		54.0/74.0	-10.38/-12.51
9912.0	44.87/62.78		54.0/74.0	-9.13/-11.22
4956.0	45.62/63.45	HORIZ	54.0/74.0	-8.38/-10.55
7434.0	45.02/62.98		54.0/74.0	-8.98/-11.02
9912.0	46.03/64.01		54.0/74.0	-7.97/-9.99

Note:

1. The average measurement was not performed when the peak measured data under the limit of average detection.
2. Emissions attenuated more than 20 dB below the permissible value are not reported.

8. BAND EDGE

8.1. Test Equipment

Please refer to Section 4 this report.

8.2. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement. The bandwidth setting below 1GHz and above 1GHz on the field strength meter is 120 kHz and 1MHz respectively.

8.3. Band Edge FCC 15.249(d) Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

8.4. Band Edge Test Result


Pass

Vertical Low channel PK




*RBW 100 kHz Marker 4 [T1]
 *VBW 300 kHz 34.60 dBμV
 Ref 96 dBμV Att 20 dB SWT 10 ms 2.379600000 GHz

1 PK
VIEW



Date: 27.SEP.2013 13:05:41

Vertical Low channel AV



Date: 27.SEP.2013 12:59:01

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Horizontal Low channel PK




*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz 85.09 dBμV
 Ref 96 dBμV Att 20 dB SWT 10 ms 2.402800000 GHz

1 PK
 VIEW



Date: 27.SEP.2013 13:02:56

Horizontal Low channel AV



Date: 27.SEP.2013 12:55:56


Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical High channel PK




*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz 61.30 dBμV
 Ref 96 dBμV Att 20 dB SWT 5 ms 2.477464000 GHz



Date: 27.SEP.2013 13:06:26

Vertical High channel AV



Date: 27.SEP.2013 13:14:26


Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Horizontal High channel PK



* RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz 63.10 dBμV
 Ref 96 dBμV Att 20 dB SWT 5 ms 2.477588000 GHz

1 PK
VIEW



Date: 27.SEP.2013 13:11:59

9. 20-DB BANDWIDTH

9.1. Test Equipment

Please refer to Section 4 this report.

9.2. Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set center frequency of spectrum analyzer = operating frequency.
3. The spectrum analyzer as RBW=30 KHz, VBW=100 KHz, Sweep=auto
4. Mark the peak frequency and -20dB (upper and lower) frequency.

9.3. Limit

Please refer section15.249


9.4. Test Result /Plots

Limit	Channel Frequency (MHz)	20dB Bandwidth (MHz)
/	2403	4.144
/	2442	4.116
/	2478	4.088



*RBW 30 kHz Marker 1 [T1]
 *VBW 100 kHz 84.43 dBμV
 Ref 96 dBμV Att 20 dB SWT 20 ms 2.403420000 GHz


1 PR
 VIEW



Date: 27.SEP.2013 13:17:53



1 PR
VIEW




Date: 27.SEP.2013 13:19:03



*RBW 30 kHz Marker 1 [T1]
 *VBW 100 kHz 80.78 dBμV
 Ref 96 dBμV Att 20 dB SWT 20 ms 2.478420000 GHz

1 PK
 VIEW



Date: 27.SEP.2013 13:20:36