

Standalone SAR test exclusion considerations

November 4, 2013

- Min. transmitting frequency = 2462 MHz
 - Min. test separation distance = 5 mm
 - Max. power with turn-up tolerance = 3.50 dBm = 3 mW
- Typical Power: 2.00 dBm + 1.50 dB & - 1.50 dB

These information are declared form applicant.

Measured Power: 2.88 dBm

This measured power is worst data in all AV power data

Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≤ 50 mm = **Used**

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

= $[3.00 / 5] * [\sqrt{ 2.462 }]$

= **0.94** ≤ 3 , for 1g SAR

Step 2-1) SAR test exclusion thresholds for 100MHz to 1500MHz at test separation distances > 50 mm = **N/A**

$[\text{Threshold at 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)] \text{ mW}$

Step 2-2) SAR test exclusion thresholds for 1500MHz to 6GHz at test separation distances > 50 mm = **N/A**

$[\text{Threshold at 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW}$