



Shenzhen Zoko Industry Development Co.,Ltd

Application
For
Certification

FCC ID: 2AA7I-U300

RFID data collector

Model: U300, U301, U302, U303

Brand Name: ZOKO

2.4GHz Transceiver

Report No.: 131018005SZN-002

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-12]

Prepared and Checked by:

Approved by:

Sign on file

Sen Lv
Project Engineer

Andy Yan
Project Engineer
Date: January 29, 2014

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_TX_b

Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch

6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751 Website: www.china.intertek-etlsemko.com

INTERTEK TESTING SERVICES

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Confidentiality Request
<i>EXHIBIT 10:</i>	Test Equipment List

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

Shenzhen Zoko Industry Development Co., Ltd
Model: U300, U301, U302, U303

FCC ID: 2AA7I-U300

This report concerns (check one :) Original Grant X Class II Change _____

Equipment Type: DXX - Part 15 Low Power Communication Device Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes _____ No X

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes _____ No X

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-12 Edition] provision.

Report prepared by:

Sen Lv
Intertek Testing Services Shenzhen Ltd.
Kejiyuan Branch
6F, Block D, Huahan Building, Langshan Road,
Nanshan District, Shenzhen, P. R. China
Phone: (86 755) 8601 0653
Fax: (86 755) 8601 6751

INTERTEK TESTING SERVICES

Table of Contents

1.0 General Description	2
1.1 Product Description	2
1.2 Related Submittal(s) Grants	2
1.3 Test Methodology	2
1.4 Test Facility	2
2.0 System Test Configuration	5
2.1 Justification	5
2.2 EUT Exercising Software	5
2.3 Special Accessories	5
2.4 Equipment Modification	5
2.5 Measurement Uncertainty	6
2.6 Support Equipment List and Description	6
3.0 Emission Results	8
3.1 Radiated Test Results	9
3.1.1 Field Strength Calculation	9
3.1.2 Radiated Emission Configuration Photograph	10
3.1.3 Radiated Emissions	10
3.1.4 Transmitter Spurious Emissions (Radiated)	12
3.2 Conducted Emission at Mains Terminal	16
3.2.1 Conducted Emissions Configuration Photograph	16
3.2.2 Conducted Emissions	16
4.0 Equipment Photographs	20
5.0 Product Labelling	22
6.0 Technical Specifications	24
7.0 Instruction Manual	26
8.0 Miscellaneous Information	28
8.1 20dB BW Plot	29
8.2 Discussion of Pulse Desensitization	30
8.3 Emissions Test Procedures	31
9.0 Confidentiality Request	34
10.0 Test Equipment List	36

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
Test Report	20dB BW Plot	bw.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

EXHIBIT 1

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a RFID data collector, it is able to read ID cards through 902.75-927.25MHz and transmit data through Bluetooth (4.0) function operating at 2402-2480MHz. The EUT was powered by a 3.7 VDC Li-ion rechargeable battery which is charged by USB Power Adapter with AC 120V, 60Hz input. For more detail information pls. refer to the user manual.

The Models: U301, U302, U303 are the same as the Model: U300 in hardware and electronic aspect. They are just different in appearance, model number and brand name for trading purpose.

Antenna Type: Integral antenna
Modulation Type: GFSK

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

1. This is an application for certification of the Bluetooth (4.0) Function operating at 2402-2480MHz.
2. RFID Function: Refer to report 131018005SZN-001
3. Transfer data function: this function has been completed in DoC.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

1.4 Test Facility

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC(Registration Number: 242492).

EXHIBIT 2
SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The EUT was powered by a 3.7 VDC fully charged Li-ion rechargeable battery which is charged by an USB Power Adapter with AC 120V, 60Hz input during the test.

The EUT has only BLE mode, and the mode reported in this report.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

The EUT engineering mode (provided by client) used during testing as similar to a typical use.

2.3 Special Accessories

One shielded USB cable with a ferrite core is used.

2.4 Equipment Modification

Any modifications installed previous to testing by Shenzhen Zoko Industry Development Co.,Ltd will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd Kejiyuan Branch.

INTERTEK TESTING SERVICES

2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

Description	Manufacturer	Model No.
110cm shielded USB Cable with a ferrite core	Shenzhen Zoko Industry Development Co.,Ltd	N/A
USB Power Adapter	Juxing Electronic (Huizhou) Co.,Ltd.	JXAS0050500100VU Input: AC 100-240V; 50/60Hz Output: DC 5V; 1000mA

INTERTEK TESTING SERVICES

EXHIBIT 3

EMISSION RESULTS

INTERTEK TESTING SERVICES

3.0 **Emission Results**

Data is included worst-case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

INTERTEK TESTING SERVICES

3.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

3.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where FS = Field Strength in dB μ V/m
 RA = Receiver Amplitude (including preamplifier) in dB μ V
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB
 PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 62.0 dB μ V
AF = 7.4 dB
CF = 1.6 dB
AG = 29.0 dB
PD = 0 dB
FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 dB μ V/m

Level in μ V/m = Common Antilogarithm [(42 dB μ V/m)/20] = 125.9 μ V/m

INTERTEK TESTING SERVICES

3.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

3.1.3 Radiated Emissions

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission
at
41.155 MHz

Judgement: Passed by 14.7 dB

TEST PERSONNEL:

Sign on file

Sen Lv, Project Engineer
Typed/Printed Name

December 3, 2013
Date

INTERTEK TESTING SERVICES

Applicant: Shenzhen Zoko Industry Development Co.,Ltd

Model: U300

Sample: 1/1

Worst Case Operating Mode: Transmit with charging

Table 1

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	82.865	34.1	20.0	6.1	20.2	40.0	-19.8
Horizontal	199.265	33.2	20.0	10.3	23.5	43.5	-20.0
Horizontal	297.235	33.3	20.0	13.9	27.2	46.0	-18.8
Vertical	41.155	35.5	20.0	9.8	25.3	40.0	-14.7
Vertical	86.260	38.3	20.0	6.8	25.1	40.0	-14.9
Vertical	518.395	31.3	20.0	16.3	27.6	46.0	-18.4

- NOTES: 1. Quasi-Peak detector is used except for others stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. All emissions are below the QP limit.

INTERTEK TESTING SERVICES

3.1.4 Transmitter Spurious Emissions (Radiated)

Worst Case Radiated Emission
at
2480.000 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 1.6 dB

TEST PERSONNEL:

Sign on file

Sen Lv, Project Engineer
Typed/Printed Name

December 3, 2013
Date

INTERTEK TESTING SERVICES

Applicant: Shenzhen Zoko Industry Development Co.,Ltd

Model: U300

Sample: 1/1

Worst Case Operating Mode: Transmit with charging

Table 2

Radiated Emissions

(2402MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	2402.000	104.9	36.7	28.5	96.7	114.0	-17.3
Horizontal	4804.000	54.9	36.7	35.0	53.2	74.0	-20.8
Horizontal	7206.000	52.6	36.1	37.0	53.5	74.0	-20.5
Horizontal	9608.000	55.3	36.2	37.5	56.6	74.0	-17.4
Horizontal	2390.000	68.1	36.7	28.5	59.9	74.0	-14.1
Horizontal	2399.156	68.5	36.7	28.5	60.3	74.0	-13.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	2402.000	99.3	36.7	28.5	91.1	94.0	-2.9
Horizontal	4804.000	48.6	36.7	35.0	46.9	54.0	-7.1
Horizontal	7206.000	39.5	36.1	37.0	40.4	54.0	-13.6
Horizontal	9608.000	47.0	36.2	37.5	48.3	54.0	-5.7
Horizontal	2390.000	60.0	36.7	28.5	51.8	54.0	-2.2
Horizontal	2399.156	60.3	36.7	28.5	52.1	54.0	-1.9

- Notes: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna is used for the emission over 1000MHz.

TRF No.: FCC 15C_TX_b

FCC ID: 2AA7I-U300

Report No.: 131018005SZN-002

INTERTEK TESTING SERVICES

Applicant: Shenzhen Zoko Industry Development Co.,Ltd

Model: U300

Sample: 1/1

Worst Case Operating Mode: Transmit with charging

Table 3

Radiated Emissions

(2440MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	2440.000	105.0	36.7	28.5	96.8	114.0	-17.2
Horizontal	4882.000	53.9	36.7	35.0	52.2	74.0	-21.8
Horizontal	7323.000	52.9	36.1	37.0	53.8	74.0	-20.2
Horizontal	9764.000	54.6	36.2	38.0	56.4	74.0	-17.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	2440.000	100.0	36.7	28.5	91.8	94.0	-2.2
Horizontal	4882.000	49.8	36.7	35.0	48.1	54.0	-5.9
Horizontal	7323.000	47.6	36.1	37.0	48.5	54.0	-5.5
Horizontal	9764.000	47.5	36.2	38.0	49.3	54.0	-4.7

- Notes:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: Shenzhen Zoko Industry Development Co.,Ltd

Model: U300

Sample: 1/1

Worst Case Operating Mode: Transmit with charging

Table 4

Radiated Emissions

(2480MHz)

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	2480.000	103.7	36.7	28.3	95.3	114.0	-18.7
Horizontal	4960.000	52.4	36.7	35.3	51.0	74.0	-23.0
Horizontal	7440.000	52.5	36.1	37.0	53.4	74.0	-20.6
Horizontal	9920.000	54.6	36.3	38.7	57.0	74.0	-17.0
Horizontal	2483.500	66.7	36.7	28.3	58.3	74.0	-15.7

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	2480.000	100.8	36.7	28.3	92.4	94.0	-1.6
Horizontal	4960.000	48.9	36.7	35.3	47.5	54.0	-6.5
Horizontal	7440.000	47.4	36.1	37.0	48.3	54.0	-5.7
Horizontal	9920.000	46.5	36.3	38.7	48.9	54.0	-5.1
Horizontal	2483.500	58.9	36.7	28.3	50.5	54.0	-3.5

- Notes:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

3.2 Conducted Emission at Mains Terminal

3.2.1 Conducted Emissions Configuration Photograph

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

3.2.2 Conducted Emissions

Worst Case Conducted Configuration
At

0.906 MHz

Judgement: Passed by 18.2 dB margin

TEST PERSONNEL:

Sign on file

Sen Lv, Project Engineer
Typed/Printed Name

November 29, 2013
Date

INTERTEK TESTING SERVICES


Applicant: Shenzhen Zoko Industry Development Co.,Ltd

Model: U300

Sample: 1/1

Worst Case Operating Mode: Transmit with charging

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.162000	47.0	L1	9.8	18.4	65.4
0.214000	41.0	L1	9.7	22.0	63.0
0.506000	37.7	L1	9.7	18.3	56.0
0.898000	36.5	L1	9.8	19.5	56.0
1.298000	34.6	L1	9.8	21.4	56.0
3.246000	33.8	L1	9.8	22.2	56.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.162000	32.0	L1	9.8	23.4	55.4
0.214000	27.0	L1	9.7	26.0	53.0
0.506000	26.5	L1	9.7	19.5	46.0
0.898000	26.6	L1	9.8	19.4	46.0
1.298000	23.4	L1	9.8	22.6	46.0
3.246000	20.9	L1	9.8	25.1	46.0

TRF No.: FCC 15C_TX_b

FCC ID: 2AA7I-U300

Report No.: 131018005SZN-002

INTERTEK TESTING SERVICES


Applicant: Shenzhen Zoko Industry Development Co.,Ltd

Model: U300

Sample: 1/1

Worst Case Operating Mode: Transmit with charging

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.162000	45.9	N	10.2	19.5	65.4
0.214000	40.5	N	10.2	22.5	63.0
0.502000	36.8	N	10.2	19.2	56.0
0.906000	37.8	N	10.3	18.2	56.0
1.182000	34.3	N	10.3	21.7	56.0
2.082000	33.4	N	10.4	22.6	56.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.162000	30.4	N	10.2	25.0	55.4
0.214000	26.5	N	10.2	26.5	53.0
0.502000	26.9	N	10.2	19.1	46.0
0.906000	26.5	N	10.3	19.5	46.0
1.182000	21.8	N	10.3	24.2	46.0
2.082000	22.0	N	10.4	24.0	46.0

TRF No.: FCC 15C_TX_b

FCC ID: 2AA7I-U300

Report No.: 131018005SZN-002

INTERTEK TESTING SERVICES

EXHIBIT 4

EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

4.0 Equipment Photographs

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 5

PRODUCT LABELLING

INTERTEK TESTING SERVICES

5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 6

TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

6.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

INTERTEK TESTING SERVICES

EXHIBIT 7

INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

EXHIBIT 8

MISCELLANEOUS INFORMATION

INTERTEK TESTING SERVICES

8.0 **Miscellaneous Information**

This miscellaneous information includes details of the measured bandedge, the test procedure and calculation of factor such as pulse desensitization.

INTERTEK TESTING SERVICES

8.1 20dB BW Plot

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

Figure 8.1 Bandwidth

INTERTEK TESTING SERVICES

8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device.

INTERTEK TESTING SERVICES

8.3 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2009.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Detector function for conducted emissions is in QP & AV mode and IFBW setting is 9 kHz from the frequency band 150 kHz to 30MHz.

INTERTEK TESTING SERVICES

8.3 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2009.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

INTERTEK TESTING SERVICES

EXHIBIT 9

CONFIDENTIALITY REQUEST

INTERTEK TESTING SERVICES

9.0 **Confidentiality Request**

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 10

TEST EQUIPMENT LIST

INTERTEK TESTING SERVICES

10.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-03	BiConiLog Antenna	ETS	3142C	00066460	20-Jul-13	20-Jan-14
SZ185-01	EMI Receiver	R&S	ESCI	100547	20-Jul-13	20-Jan-14
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	20-Jul-13	20-Jan-14
SZ061-08	Horn Antenna	ETS	3115	00092346	17-Oct-13	17-Apr-14
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	17-Oct-13	17-Apr-14
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	20-Jul-13	20-Jan-14
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	18-Oct-13	18-Apr-14
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	18-Oct-13	18-Apr-14
SZ062-02	RF Cable	RADIAL	RG 213U	--	20-Jul-13	20-Jan-14
SZ062-06	RF Cable	RADIAL	0.04-26.5GHz	--	17-Oct-13	17-Apr-14
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	--	17-Oct-13	17-Apr-14
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	18-Oct-13	18-Apr-14
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	18-Oct-13	18-Apr-14
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	18-Oct-13	18-Apr-14
SZ188-03	Shielding Room	ETS	RFD-100	4100	18-Oct-13	18-Apr-14