



Star Systems International Limited

**Application
For
Certification**

FCC ID: 2AA7KPLATINO-WF2014

RFID Handheld Reader

**Model: PLATINO
Brand Name: Star Systems**

902.75-927.25MHz Transceiver

Report No.: 140924018SZN-003

Prepared and Checked by:

Approved by:

Sign on file

Benson Wang
Assistant Engineer

Andy Yan
Senior Project Engineer
Date: 23 June, 2015

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_TX_b

Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch
6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751 Website: www.china.intertek-etlsemko.com

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Test Equipment List

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

Star Systems International Limited

Model: PLATINO

FCC ID: 2AA7KPLATINO-WF2014

This report concerns (check one): Original Grant ☒ Class II Change ☐

Equipment Type: DSS - Part 15 Spread Spectrum Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-13 Edition] provision.

Report prepared by:

Benson Wang
Intertek Testing Services Shenzhen Ltd.
Kejiyuan Branch
6F, Block D, Huahan Building, Langshan Road,
Nanshan District, Shenzhen, P. R. China
Phone: (86 755) 8601 0680
Fax: (86 755) 8601 6751

INTERTEK TESTING SERVICES

Table of Contents

1.0 General Description	2
1.1 Product Description	2
1.2 Related Submittal(s) Grants	2
1.3 Test Methodology	2
1.4 Test Facility	2
2.0 System Test Configuration	4
2.1 Justification	4
2.2 EUT Exercising Software	4
2.3 Special Accessories	4
2.4 Equipment Modification	4
2.5 Measurement Uncertainty	5
2.6 Support Equipment List and Description	5
3.0 Test Results	8
3.1 Radiated Test Result	8
3.1.1 Field Strength Calculation	8
3.1.2 Radiated Emission Data and Configuration Photograph	9
3.1.3 Transmitter Spurious Emissions (Radiated)	11
3.2 Conducted Emissions at Mains Terminal	15
3.2.1 Conducted Emissions and Data Configuration Photograph	15
3.3 Peak Power	18
3.4 20dB Bandwidth	21
3.5 Channel Number (Number of Hopping Frequencies)	23
3.6 Channel Separation (Carrier Frequency Separation)	24
3.7 Dwell Time (Time of Occupancy)	26
3.8 Band Edge	30
3.9 Transmitter Spurious Emissions (Conducted)	32
4.0 Equipment Photographs	37
5.0 Product Labelling	39
6.0 Technical Specifications	41
7.0 Instruction Manual	43
8.0 Miscellaneous Information	45
8.1 Discussion of Pulse Desensitization	46
8.2 Emissions Test Procedures	47
9.0 Test Equipment List	50

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	filename
Test Report	Test Report	report.pdf
Test Report	Test Report	sar report.pdf
Operational Description	Technical Description	descri.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
External Photos	External Photo	external photos.pdf
Internal Photos	Internal Photo	internal photos.pdf
ID Label/Location Info	Label Artwork and Location	label.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Users Manual	User Manual	manual.pdf
Cover Letter	Letter of Agency	letter of agency.pdf

INTERTEK TESTING SERVICES

EXHIBIT 1

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a RFID Handheld Reader, it is able to read ID cards through 902.75-927.25MHz and transmit data through WIFI function operating at 2412-2462MHz, 11channels with 5MHz separation, and in 2422-2452MHz, 7 channels with 5MHz separation. The EUT was powered by a 3.7 VDC Li-ion rechargeable battery which is charged by USB Power Adapter with AC 120V, 60Hz input. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna
Modulation Type: DSB-ASK

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

1. This is an application for certification of the RFID function operation at 902.75-927.25MHz.
2. WIFI Function: Refer to report 140924018SZN-004
3. Data Transfer function with PC: this function has been completed in DoC.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4: 2009 and DA 00-705. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

1.4 Test Facility

The Semi-Anechoic chamber and shield room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, Block D, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

EXHIBIT 2

SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

2.0 System Test Configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4: 2009.

The EUT was powered by a 3.7 VDC fully charged Li-ion rechargeable battery which is charged by USB Power Adapter with AC 120V, 60Hz input during the test.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

The EUT engineering mode (provided by client) used during testing as similar to a typical use.

2.3 Special Accessories

One shielded USB cable with a ferrite core attached with the EUT is used.

2.4 Equipment Modification

Any modifications installed previous to testing by STAR SYSTEMS INTERNATIONAL LIMITED will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

INTERTEK TESTING SERVICES

2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

Description	Manufacturer	Model No.
110cm shielded USB Cable with a ferrite core	Star Systems International Limited	N/A
USB Power Adapter	Juxing Electronic (Huizhou) Co.,Ltd.	JXAS0050500100VU, Input: AC 100-240V; 50/60Hz Output: DC 5V; 1000mA

EXHIBIT 3
TEST RESULTS

INTERTEK TESTING SERVICES

3.0 **Test Results**

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

INTERTEK TESTING SERVICES

3.1 **Radiated Test Results**

A sample calculation, configuration photographs and data tables of the emissions are included.

3.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB
- AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 62.0 dB μ V
AF = 7.4 dB
CF = 1.6 dB
AG = 29.0 dB
PD = 0 dB

AV = -10 dB

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.1.2 Radiated Emission Data and Configuration Photograph - FCC section 15.209

Worst Case Radiated Emission

At

86.230 MHz

Judgement: Passed by 11.9 dB

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos.pdf.

TEST PERSONNEL:

Sign on file

Benson Wang, Assistant Engineer

Typed / Printed Name

January 8, 2015

Date

INTERTEK TESTING SERVICES

Applicant: STAR SYSTEMS INTERNATIONAL LIMITED

Date of Test: January 8, 2015

Model: PLATINO

Worst Case Operating Mode: Transmit with charging

Table 1

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	30.920	22.6	20.0	18.6	21.2	40.0	-18.8
Horizontal	404.490	37.8	20.0	13.5	31.3	46.0	-14.7
Horizontal	486.448	32.3	20.0	17.0	29.3	46.0	-16.7
Vertical	32.410	22.4	20.0	18.2	20.6	40.0	-19.4
Vertical	86.230	41.0	20.0	7.1	28.1	40.0	-11.9
Vertical	315.250	23.1	20.0	22.1	25.2	46.0	-20.8

- NOTES: 1. Quasi-Peak detector is used except for others stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. All emissions are below the QP limit.

Test Engineer: Benson Wang

INTERTEK TESTING SERVICES

3.1.3 Transmitter Spurious Emissions (Radiated) - FCC section 15.209

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission
at
2708.250 MHz

Judgement: Passed by 6.7 dB

TEST PERSONNEL:

Sign on file

Benson Wang, Assistant Engineer
Typed/Printed Name

January 8, 2015
Date

INTERTEK TESTING SERVICES

Applicant: STAR SYSTEMS INTERNATIONAL LIMITED

Date of Test: January 8, 2015

Model: PLATINO

Mode: Transmit with charging (902.75MHz)

Table 2

Radiated Emissions

(902.75MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2708.250	61.7	36.8	26.5	51.4	74.0	-22.6
Horizontal	*3611.000	48.6	35.6	39.5	52.5	74.0	-21.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2708.250	57.6	36.8	26.5	47.3	54.0	-6.7
Horizontal	*3611.000	42.5	35.6	39.5	46.4	54.0	-7.6

- NOTES:
1. Peak detector is used except for others stated. Peak detector is used for spurious emission with RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Benson Wang

INTERTEK TESTING SERVICES

Applicant: STAR SYSTEMS INTERNATIONAL LIMITED

Date of Test: January 8, 2015

Model: PLATINO

Mode: Transmit with charging (914.75MHz)

Table 3

Radiated Emissions

(914.75MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2744.250	44.9	36.2	37.9	46.6	74.0	-27.4
Horizontal	*3659.000	44.9	35.6	39.5	48.8	74.0	-25.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2744.250	38.9	36.2	37.9	40.6	54.0	-13.4
Horizontal	*3659.000	37.6	35.6	39.5	41.5	54.0	-12.5

- NOTES:
1. Peak detector is used except for others stated. Peak detector is used for spurious emission with RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Benson Wang

TRF No.: FCC 15C_TX_b

FCC ID: 2AA7KPLATINO-WF2014

INTERTEK TESTING SERVICES

Applicant: STAR SYSTEMS INTERNATIONAL LIMITED

Date of Test: January 8, 2015

Model: PLATINO

Mode: Transmit with charging (927.25MHz)

Table 4

Radiated Emissions

(927.25MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2781.750	56.5	36.8	26.5	46.2	74.0	-27.8
Horizontal	*3709.000	44.1	35.6	39.5	48.0	74.0	-26.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*2781.750	52.5	36.8	26.5	42.2	54.0	-11.8
Horizontal	*3709.000	30.4	35.6	39.5	34.3	54.0	-19.7

- NOTES:
1. Peak detector is used except for others stated. Peak detector is used for spurious emission with RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Benson Wang

TRF No.: FCC 15C_TX_b

FCC ID: 2AA7KPLATINO-WF2014

INTERTEK TESTING SERVICES

3.2 Conducted Emission at Mains Terminal

3.2.1 Conducted Emissions and Data Configuration Photograph

Worst Case Conducted Configuration
at
0.906 MHz

Judgement: Passed by 6.8 dB

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

TEST PERSONNEL:

Sign on file

Benson Wang, Assistant Engineer
Typed/Printed Name

January 8, 2015
Date

INTERTEK TESTING SERVICES

Company: STAR SYSTEMS INTERNATIONAL LIMITED


Date of Test: January 8, 2015

Model: PLATINO

Worst Case Operating Mode: Transmit with charging

Conducted Emission Test – FCC

Pursuant to 15.207 Emissions Requirement



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.162000	45.0	L1	9.8	20.4	65.4
0.394000	44.5	L1	9.8	13.5	58.0
0.506000	48.1	L1	9.8	7.9	56.0
0.906000	48.7	L1	9.9	7.3	56.0
1.354000	47.4	L1	9.9	8.6	56.0
1.966000	47.3	L1	9.9	8.7	56.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.162000	36.5	L1	9.8	18.9	55.4
0.394000	36.2	L1	9.8	11.8	48.0
0.506000	38.6	L1	9.8	7.4	46.0
0.906000	39.2	L1	9.9	6.8	46.0
1.354000	36.3	L1	9.9	9.7	46.0
1.966000	37.5	L1	9.9	8.5	46.0

TRF No.: FCC 15C_TX_b

FCC ID: 2AA7KPLATINO-WF2014

INTERTEK TESTING SERVICES

Company: STAR SYSTEMS INTERNATIONAL LIMITED


Date of Test: January 8, 2015

Model: PLATINO

Worst Case Operating Mode: Transmit with charging

Conducted Emission Test – FCC

Pursuant to 15.207 Emissions Requirement



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.158000	48.2	N	10.0	17.4	65.6
0.210000	41.7	N	10.1	21.5	63.2
0.502000	43.4	N	10.1	12.6	56.0
0.946000	35.2	N	10.2	20.8	56.0
1.426000	33.9	N	10.3	22.1	56.0
1.738000	32.9	N	10.3	23.1	56.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.158000	33.8	N	10.0	21.8	55.6
0.210000	28.4	N	10.1	24.8	53.2
0.502000	29.6	N	10.1	16.4	46.0
0.946000	25.3	N	10.2	20.7	46.0
1.426000	22.9	N	10.3	23.1	46.0
1.738000	21.5	N	10.3	24.5	46.0

TRF No.: FCC 15C_TX_b

FCC ID: 2AA7KPLATINO-WF2014

INTERTEK TESTING SERVICES

3.3 **Peak Power**

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(1)

The antenna port of the EUT was connected to the input of a spectrum analyzer. The analyzer was set for RBW > 20dB bandwidth and power was read directly in dBm.


For frequency hopping systems operating in the 902–928 MHz band: 1 watt for systems employing at least 50 hopping channels.

Antenna Gain = 2.0dBi			
Modulation Type	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
DSB-ASK	902.75	21.86	153.46
	914.75	21.66	146.55
	927.25	21.38	137.40


INTERTEK TESTING SERVICES

Modulation Type: DSB-ASK

902.75 MHz




914.75 MHz



INTERTEK TESTING SERVICES

927.25 MHz



INTERTEK TESTING SERVICES


3.4 20dB Bandwidth

Maximum 20dB RF Bandwidth, FCC Rule 15.247(a) (1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.


Frequency (MHz)	20 dB Bandwidth (KHz)	Limit (KHz)
902.75	78.150	500
914.75	65.850	500
927.25	57.890	500

Modulation Type: DSB-ASK




INTERTEK TESTING SERVICES

914.75MHz



927.25MHz



INTERTEK TESTING SERVICES

3.5 Channel Number (Number of Hopping Frequencies)

Minimum Number of Hopping Frequencies, FCC Rule 15.247(a) (1) (iii):


The RF passband of the EUT was divided into 3 approximately equal bands. With the analyzer set to MAX HOLD readings were taken for 2-3 minutes. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

Note: For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies

Number of hopping channels =	50
------------------------------	----

Modulation Type: DSB-ASK

CH00-CH49



INTERTEK TESTING SERVICES

3.6 Channel Separation (Carrier Frequency Separation)

Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1):


Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit:

Limit: Not less than 20dB bandwidth: 78KHz

Channel	Channel Separation (KHz)	Limit (KHz)
Low	512.3	78
Mid	506.5	78
High	506.5	78


Modulation Type: DSB-ASK

Low Channel




INTERTEK TESTING SERVICES

Middle Channel



High Channel



INTERTEK TESTING SERVICES

3.7 Dwell Time (Time of Occupancy)

Average Channel Occupancy Time, FCC Ref: 15.247(a)(1)(iii):

The spectrum analyzer center frequency was set to one of the known hopping channels. The SWEEP was set to 20s, the SPAN was set to ZERO SPAN, and the TRIGGER was set to VIDEO. The time duration of the transmissions so captured was measured with the MARKER DELTA function.

Note: For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period.


The maximum number of hopping channels in 20s:

Frequency (MHz)	Dwell time Per Hop(s)	Number of hopping channels in 20s	Dwell time (s)	Limit (s)
902.75	0.33	1	0.33	0.4
914.75	0.33	1	0.33	0.4
927.25	0.33	1	0.33	0.4


Modulation Type: DSB-ASK

902.75MHz


The number of hopping channels in 20s:




TRF No.: FCC 15C_TX_b
FCC ID: 2AA7KPLATINO-WF2014




INTERTEK TESTING SERVICES



927.25MHz



INTERTEK TESTING SERVICES




3.8 Band Edge


Out of Band Conducted Emissions, FCC Rule 15.247(d):

In any 100 KHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission.

Modulation Type: DSB-ASK



INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES

3.9 Transmitter Spurious Emissions (Conducted)



Out of Band Conducted Spurious Emissions, FCC Rule 15.247(d):

All spurious emission and up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

INTERTEK TESTING SERVICES



Modulation Type: DSB-ASK

Low Channel:



INTERTEK TESTING SERVICES

Middle Channel:



INTERTEK TESTING SERVICES

High Channel:





EXHIBIT 4
EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

4.0 **Equipment Photographs**

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

EXHIBIT 5
PRODUCT LABELLING

INTERTEK TESTING SERVICES

5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

EXHIBIT 6

TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

6.0 **Technical Specifications**

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 7
INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

EXHIBIT 8

MISCELLANEOUS INFORMATION

INTERTEK TESTING SERVICES

8.0 **Miscellaneous Information**

This miscellaneous information includes details of the test procedure and calculation of factor such as pulse desensitization.

INTERTEK TESTING SERVICES

8.1 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device.

8.2 **Emissions Test Procedures**

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4: 2009.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

Detector function for conducted emissions is in QP & AV mode and IFBW setting is 9 kHz from the frequency band 150 kHz to 30MHz.

8.3 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4: 2009.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

EXHIBIT 9
TEST EQUIPMENT LIST

INTERTEK TESTING SERVICES

9.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-03	BiConiLog Antenna	ETS	3142C	00066460	28-Jun-14	28-Jun-15
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	3-Sep-14	3-Sep-15
SZ061-08	Horn Antenna	ETS	3115	00092346	19-Oct-14	19-Oct-15
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	29-Apr-14	29-Apr-15
EM031-03	Spectrum Analyzer	R&S	FSV40	101148	9-Jun-14	9-Jun-15
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	10-Mar-14	10-Mar-15
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	19-Apr-14	19-Apr-15
SZ062-02	RF Cable	RADIAL	RG 213U	--	8-Jan-15	8-Jul-15
SZ062-06	RF Cable	RADIAL	0.04-26.5GHz	--	8-Jan-15	8-Jul-15
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	--	17-Oct-14	17-Apr-15
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	--	21-May-14	21-May-15
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	1-Nov-14	1-Nov-15
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	1-Nov-14	1-Nov-15
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	1-Nov-14	1-Nov-15
SZ188-03	Shielding Room	ETS	RFD-100	4100	23-Aug-14	23-Aug-15