FCC RF Test Report

APPLICANT	**:**	**Eroad, Ltd.**
EQUIPMENT	**:**	**Ehubo**
BRAND NAME	**:**	**EROAD**
MODEL NAME	**:**	**Ehubo2.2**
FCC ID	**:**	**Contains FCC ID: 2AA93-1316**
STANDARD	**:**	**FCC Part 15 Subpart C §15.247**
CLASSIFICATION	**:**	**(DSS) Spread Spectrum Transmitter**

The product was received on Dec. 05, 2018 and testing was completed on Jan . 16, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

James Huang

NVLAP®
TESTING
NVLAP LAB CODE 600155-0

_____

Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province, China

TABLE OF CONTENTS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR8D0502A	Rev. 01	Initial issue of report	Feb. 18, 2019

Sporton International (Kunshan) Inc.
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number   : 3 of 55
Report Issued Date : Feb. 18, 2019
Report Version   : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.5	15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	≤ 20dBc	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 2.39 dB at 167.74 MHz
-	15.207	AC Conducted Emission	15.207(a)	Not Required	-
3.9	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

Sporton International (Kunshan) Inc.
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number   : 4 of 55
Report Issued Date : Feb. 18, 2019
Report Version   : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

1 General Description

1.1 Applicant

Eroad, Ltd.

Level 3, 260 Oteha Valley Road Albany, Auckland, 0757 New Zealand

1.2 Manufacturer

Eroad, Ltd.

Level 3, 260 Oteha Valley Road Albany, Auckland, 0757 New Zealand

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Ehubo
Brand Name	EROAD
Model Name	Ehubo2.2
FCC ID	Contains FCC ID: 2AA93-1316
EUT supports Radios application	WCDMA/HSPA/LTE
	Bluetooth BR/EDR/LE
HW Version	Rev E1
SW Version	1.46
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Sporton International (Kunshan) Inc.
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number : 5 of 55
Report Issued Date : Feb. 18, 2019
Report Version : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 8.92 dBm (0.0078 W) Bluetooth EDR (2Mbps) : 8.24 dBm (0.0067 W) Bluetooth EDR (3Mbps) : 8.25 dBm (0.0067 W)
Antenna Type / Gain	Chip Antenna with gain 0.90 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π /4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province, China TEL : 86-512-57900158 FAX : 86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC designation No.**	**FCC Test Firm Registration No.**
	TH01-KS 03CH05-KS	CN5013	630927

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ⬧ 47 CFR Part 15 Subpart C §15.247
- ⬧ FCC KDB 558074 D01 15.247 Meas Guidance v05
- ⬧ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2   Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
2400-2483.5 MHz	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the worst cases were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	**Data Rate / Modulation**		
	Bluetooth BR 1Mbps GFSK	**Bluetooth EDR 2Mbps π /4-DQPSK**	**Bluetooth EDR 3Mbps 8-DPSK**
Conducted Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated Test Cases	**Bluetooth BR 1Mbps GFSK**		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
	Mode 3: CH78_2480 MHz		
Remark: For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.			

2.3 Connection Diagram of Test System

This example is connection diagram of EUT test configurations.
For detail, please refer to test mode configuration and setup photographs for each test item.

2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	BT Base Station	R&S	CBT	N/A	N/A	Unshielded,1.8m

2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit/receive.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss

Following shows an offset computation example with cable loss 6.1dB.

Offset(dB) = RF cable loss(dB) .

$\qquad$ = 6.1 (dB)

3　Test Result

3.1　Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup

Spectrum Analyzer　　　　　　　　　　EUT

3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	1Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass

Sporton International (Kunshan) Inc.
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number　　　　: 12 of 55
Report Issued Date : Feb. 18, 2019
Report Version　　　: Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

Number of Hopping Channel Plot on Channel 00 - 78

Date: 13.JAN.2019 16:46:45

Date: 13.JAN.2019 16:48:19

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
   Span = wide enough to capture the peaks of two adjacent channels;
   RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup

Spectrum Analyzer   **EUT**

3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.6889	Pass
39	2441	1.002	0.6889	Pass
78	2480	1.002	0.6889	Pass

<1Mbps>

**Channel Separation Plot on Channel 00 - 01**


Date: 13.JAN.2019 16:43:41

Channel Separation Plot on Channel 39 - 40

Date: 14.JAN.2019 09:37:31

Channel Separation Plot on Channel 77 - 78

Date: 14.JAN.2019 09:42:10

Test Mode :	2Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.007	0.8249	Pass
39	2441	0.999	0.8191	Pass
78	2480	0.999	0.8191	Pass

<2Mbps>

Channel Separation Plot on Channel 00 - 01

Date: 14.JAN.2019 11:13:24

Sporton International (Kunshan) Inc.
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number : 17 of 55
Report Issued Date : Feb. 18, 2019
Report Version : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

Channel Separation Plot on Channel 39 - 40

Date: 14.JAN.2019 11:16:24

### Channel Separation Plot on Channel 77 - 78

Date: 14.JAN.2019 11:19:00

Test Mode :	3Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	0.994	0.7815	Pass
39	2441	1.012	0.7844	Pass
78	2480	1.012	0.7786	Pass

<3Mbps>

Channel Separation Plot on Channel 00 - 01

Date: 14.JAN.2019 11:27:19

Channel Separation Plot on Channel 39 - 40

Date: 14.JAN.2019 11:28:22

Channel Separation Plot on Channel 77 - 78

Date: 14.JAN.2019 11:25:40

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup

Spectrum Analyzer   **EUT**

3.3.5 Test Result of Dwell Time

Test Mode :	3DH5	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.8986	0.31	0.4	Pass
AFH	20	53.34	2.8986	0.15	0.4	Pass

Package Transfer Time Plot

Date: 13.JAN.2019 15:15:07

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.

   With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),

   Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.

2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.

   With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),

   Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.

3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

3.4 20dB Bandwidth Measurement

### 3.4.1 Limit of 20dB Bandwidth

Reporting only

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
   Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
   RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
   Trace = max hold.
5. Measure and record the results in the test report.

3.4.4 Test Setup

Spectrum Analyzer   EUT

3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

| Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.033
39	2441	1.033
78	2480	1.033

<1Mbps>

**20 dB Bandwidth Plot on Channel 00**

Date: 13.JAN.2019 16:11:22

20 dB Bandwidth Plot on Channel 39

Date: 13.JAN.2019 19:36:35

20 dB Bandwidth Plot on Channel 78

Date: 13.JAN.2019 19:30:08

Sporton International (Kunshan) Inc.

TEL : 86-512-57900158

FAX : 86-512-57900958

FCC ID: 2AA93-1316

Page Number   : 25 of 55

Report Issued Date : Feb. 18, 2019

Report Version   : Rev. 01

Report Template No.: BU5-FR15CBT Version 2.0

Test Mode :	2Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.237
39	2441	1.229
78	2480	1.229

<2Mbps>

20 dB Bandwidth Plot on Channel 00

Date: 14.JAN.2019 08:43:30

Sporton International (Kunshan) Inc.
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number   : 26 of 55
Report Issued Date : Feb. 18, 2019
Report Version   : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

20 dB Bandwidth Plot on Channel 39

Date: 14.JAN.2019 08:53:21

### 20 dB Bandwidth Plot on Channel 78

Date: 14.JAN.2019 08:15:32

Test Mode :	3Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.172
39	2441	1.177
78	2480	1.168

<3Mbps>

20 dB Bandwidth Plot on Channel 00

Date: 13.JAN.2019 18:38:29

Sporton International (Kunshan) Inc.

TEL : 86-512-57900158

FAX : 86-512-57900958

FCC ID: 2AA93-1316

Page Number   : 28 of 55

Report Issued Date : Feb. 18, 2019

Report Version   : Rev. 01

Report Template No.: BU5-FR15CBT Version 2.0

20 dB Bandwidth Plot on Channel 39

Date: 13.JAN.2019 19:17:16

20 dB Bandwidth Plot on Channel 78

Date: 13.JAN.2019 19:00:17

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup

3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

Channel	Frequency (MHz)	RF Power (dBm)		Pass/Fail
		GFSK 1 Mbps	Max. Limits (dBm)	
00	2402	8.08	20.97	Pass
39	2441	8.48	20.97	Pass
78	2480	8.92	20.97	Pass

Test Mode :	2Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

Channel	Frequency (MHz)	RF Power (dBm)		Pass/Fail
		π/4-DQPSK 2 Mbps	Max. Limits (dBm)	
00	2402	7.74	20.97	Pass
39	2441	8.24	20.97	Pass
78	2480	7.55	20.97	Pass

Test Mode :	3Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

Channel	Frequency (MHz)	RF Power (dBm)		Pass/Fail
		8-DPSK 3 Mbps	Max. Limits (dBm)	
00	2402	7.80	20.97	Pass
39	2441	8.25	20.97	Pass
78	2480	7.58	20.97	Pass

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup

Spectrum Analyzer   EUT

Sporton International (Kunshan) Inc.   Page Number   : 32 of 55
TEL : 86-512-57900158   Report Issued Date : Feb. 18, 2019
FAX : 86-512-57900958   Report Version   : Rev. 01
FCC ID: 2AA93-1316   Report Template No.: BU5-FR15CBT Version 2.0

3.6.5 Test Result of Conducted Band Edges

Test Mode :	1Mbps	Temperature :	21~24℃
Test Channel :	00 and 78	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

<1Mbps>

**Low Band Edge Plot on Channel 00**

Date: 13.JAN.2019 16:08:56

High Band Edge Plot on Channel 78

Date: 13.JAN.2019 19:26:51

Test Mode :	2Mbps	Temperature :	21~24℃
Test Channel :	00 and 78	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

<2Mbps>

Low Band Edge Plot on Channel 00

Date: 14.JAN.2019 08:31:01

High Band Edge Plot on Channel 78

Date: 14.JAN.2019 08:09:22

Test Mode :	3Mbps	Temperature :	21~24℃
Test Channel :	00 and 78	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

<3Mbps>

Low Band Edge Plot on Channel 00

Date: 13.JAN.2019 19:10:38

High Band Edge Plot on Channel 78

Date: 13.JAN.2019 18:54:06

3.6.6 Test Result of Conducted Hopping Mode Band Edges

Test Mode :	1Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

<1Mbps>

Hopping Mode Low Band Edge Plot

Date: 13.JAN.2019 16:52:00

Hopping Mode High Band Edge Plot

Date: 13.JAN.2019 16:52:42

Test Mode :	2Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

<2Mbps>

Hopping Mode Low Band Edge Plot

Date: 13.JAN.2019 19:08:50

Hopping Mode High Band Edge Plot

Date: 13.JAN.2019 17:00:23

Sporton International (Kunshan) Inc.

TEL : 86-512-57900158

FAX : 86-512-57900958

FCC ID: 2AA93-1316

Page Number   : 37 of 55

Report Issued Date : Feb. 18, 2019

Report Version   : Rev. 01

Report Template No.: BU5-FR15CBT Version 2.0

Test Mode :	3Mbps	Temperature :	21~24℃
Test Engineer :	Ivan Zhang	Relative Humidity :	49~51%

<3Mbps>

Hopping Mode Low Band Edge Plot

Date: 13.JAN.2019 17:02:52

Hopping Mode High Band Edge Plot

Date: 13.JAN.2019 17:01:44

*Sporton International (Kunshan) Inc.*
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number   : 38 of 55
Report Issued Date : Feb. 18, 2019
Report Version   : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup

3.7.5 Test Result of Conducted Spurious Emission

Test Mode :	1Mbps	Temperature :	21~24℃
Test Channel :	00	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

<1Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz

Date: 14.JAN.2019 09:19:06

1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz

Date: 14.JAN.2019 09:19:41

Sporton International (Kunshan) Inc.
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number　　　: 40 of 55
Report Issued Date : Feb. 18, 2019
Report Version　　: Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

Test Mode :	1Mbps	Temperature :	21~24℃
Test Channel :	39	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

CSE Plot on Ch 39 between 30MHz ~ 3 GHz

Date: 14.JAN.2019 09:26:09

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz

Date: 14.JAN.2019 09:26:37

Test Mode :	1Mbps	Temperature :	21~24℃
Test Channel :	78	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

CSE Plot on Ch 78 between 30MHz ~ 3 GHz

Date: 14.JAN.2019 09:24:24

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz

Date: 14.JAN.2019 09:24:54

| Test Mode :	2Mbps	Temperature :	21~24℃
Test Channel :	00	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

CSE Plot on Ch 00 between 30MHz ~ 3 GHz

Date: 14.JAN.2019 08:41:06

### CSE Plot on Ch 00 between 2 GHz ~ 25 GHz

Date: 14.JAN.2019 08:41:43

Test Mode :	2Mbps	Temperature :	21~24℃
Test Channel :	39	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

CSE Plot on Ch 39 between 30MHz ~ 3 GHz

Spectrum

Ref Level 16.10 dBm   Offset 6.10 dB   RBW 100 kHz
Att   20 dB   SWT   29.7 ms   VBW 300 kHz   Mode Auto Sweep

1Pk View

M2[1]   -58.18 dBm
10 dBm   814.40 MHz
M1[1]   M1   3.58 dBm
D1 3.580 dBm   2.44340 GHz
0 dBm

-10 dBm

D2 -16.420 dBm
-20 dBm

-30 dBm

-40 dBm

-50 dBm

M2
-60 dBm

-70 dBm

-80 dBm

Start 30.0 MHz   691 pts   Stop 3.0 GHz

Date: 14.JAN.2019 08:56:33

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz

Spectrum

Ref Level 16.10 dBm   Offset 6.10 dB   RBW 100 kHz
Att   20 dB   SWT   230 ms   VBW 300 kHz   Mode Auto Sweep

1Pk View

M2[1]   -40.39 dBm
10 dBm   14.6320 GHz
M1   M1[1]   4.02 dBm
D1 4.020 dBm   2.4490 GHz
0 dBm

-10 dBm

D2 -15.980 dBm
-20 dBm

-30 dBm

-40 dBm   M2

-50 dBm

-60 dBm

-70 dBm

-80 dBm

Start 2.0 GHz   691 pts   Stop 25.0 GHz

Date: 14.JAN.2019 08:57:07

Sporton International (Kunshan) Inc.   Page Number   : 44 of 55
TEL : 86-512-57900158   Report Issued Date : Feb. 18, 2019
FAX : 86-512-57900958   Report Version   : Rev. 01
FCC ID: 2AA93-1316   Report Template No.: BU5-FR15CBT Version 2.0

Test Mode :	2Mbps	Temperature :	21~24℃
Test Channel :	78	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

CSE Plot on Ch 78 between 30MHz ~ 3 GHz

Date: 14.JAN.2019 09:00:33

### CSE Plot on Ch 78 between 2 GHz ~ 25 GHz

Date: 14.JAN.2019 09:01:01

Sporton International (Kunshan) Inc.
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number   : 45 of 55
Report Issued Date : Feb. 18, 2019
Report Version   : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

Test Mode :	3Mbps	Temperature :	21~24℃
Test Channel :	00	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

CSE Plot on Ch 00 between 30MHz ~ 3 GHz

Date: 14.JAN.2019 09:06:45

CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 14.JAN.2019 09:07:17

Sporton International (Kunshan) Inc.
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number   : 46 of 55
Report Issued Date : Feb. 18, 2019
Report Version   : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

Test Mode :	3Mbps	Temperature :	21~24℃
Test Channel :	39	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

CSE Plot on Ch 39 between 30MHz ~ 3 GHz

Date: 14.JAN.2019 09:12:41

### CSE Plot on Ch 39 between 2 GHz ~ 25 GHz

Date: 14.JAN.2019 09:13:10

Test Mode :	3Mbps	Temperature :	21~24℃
Test Channel :	78	Relative Humidity :	49~51%
		Test Engineer :	Ivan Zhang

CSE Plot on Ch 78 between 30MHz ~ 3 GHz

Date: 14.JAN.2019 09:08:53

### CSE Plot on Ch 78 between 2 GHz ~ 25 GHz

Date: 14.JAN.2019 09:09:20

*Sporton International (Kunshan) Inc.*
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number   : 48 of 55
Report Issued Date : Feb. 18, 2019
Report Version   : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.

2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.

4. Set to the maximum power setting and enable the EUT transmit continuously.

5. Use the following spectrum analyzer settings:

    (1) Span shall wide enough to fully capture the emission being measured;

   (2) Set RBW=100 kHz for f < 1 GHz, RBW=1MHz for f>1GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak

    (3) For average measurement: use duty cycle correction factor method per 15.35(c).

    Duty cycle = On time/100 milliseconds

    On time = $N_1*L_1+N_2*L_2+...+N_{n-1}*LN_{n-1}+N_n*L_n$

    Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.

    Average Emission Level = Peak Emission Level + 20*log(Duty cycle)

6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.

8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from 20log (dwell time/100ms). This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup

For radiated emissions below 30MHz

For radiated emissions from 30MHz to 1GHz

For radiated emissions above 1GHz

3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A.

3.8.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A.

3.8.8 Duty cycle correction factor for average measurement

Please refer to Appendix B.

3.9 Antenna Requirements

3.9.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.9.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.9.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4   List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2018	Jan. 13, 2019~ Jan. 14, 2019	Aug. 06, 2019	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 11, 2018	Jan. 13, 2019~ Jan. 14, 2019	Oct. 10, 2019	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 18, 2018	Jan. 13, 2019~ Jan. 14, 2019	Jan. 17, 2019	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 18, 2018	Jan. 13, 2019~ Jan. 14, 2019	Jan. 17, 2019	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY57290151	3Hz~8.5GHz;Max 30dBm	Jun. 25, 2018	Jan. 16, 2019	Jun. 24, 2019	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44GHz	Apr. 17, 2018	Jan. 16, 2019	Apr. 16, 2019	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Jan. 16, 2019	Oct. 18, 2019	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Jun. 12, 2018	Jan. 16, 2019	Jun. 11, 2019	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 21, 2018	Jan. 16, 2019	Jan. 20, 2019	Radiation (03CH05-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Feb. 07, 2018	Jan. 16, 2019	Feb. 06, 2019	Radiation (03CH05-KS)
Amplifier	com-power	PA-103A	161069	1MHz ~1000MHz / 32 dB	Apr. 17, 2018	Jan. 16, 2019	Apr. 16, 2019	Radiation (03CH05-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18~40GHz	Feb. 08, 2018	Jan. 16, 2019	Feb. 07, 2019	Radiation (03CH05-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2025788	1Ghz-18Ghz	Apr. 17, 2018	Jan. 16, 2019	Apr. 16, 2019	Radiation (03CH05-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Apr. 18, 2018	Jan. 16, 2019	Apr. 17, 2019	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 16, 2019	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 16, 2019	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 16, 2019	NCR	Radiation (03CH05-KS)

NCR: No Calibration Required

Sporton International (Kunshan) Inc.
TEL : 86-512-57900158
FAX : 86-512-57900958
FCC ID: 2AA93-1316

Page Number   : 54 of 55
Report Issued Date : Feb. 18, 2019
Report Version   : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

5   Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB

Appendix A.   Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT **CH00** **2402MHz**		2377.6	53.11	-20.89	74	49.42	32.03	5.43	33.77	400	320	P	H
	*	2377.6	28.35	-25.65	54	-	-	-	-	-	-	A	H
		2402	94.52	-	-	90.81	32	5.48	33.77	400	320	P	H
		2402	69.76	-	-	-	-	-	-	-	-	A	H
		2381.5	57.38	-16.62	74	53.69	32.03	5.43	33.77	100	119	P	V
	*	2381.5	32.62	-21.38	54	-	-	-	-	-	-	A	V
		2402	101.17	-	-	97.46	32	5.48	33.77	100	119	P	V
		2402	76.41	-	-	-	-	-	-	-	-	A	V
BT **CH 78** **2480MHz**	*	2480	100.72	-	-	96.66	32.27	5.55	33.76	375	316	P	H
		2480	75.96	-	-	-	-	-	-	-	-	A	H
		2497.9	53.53	-20.47	74	49.53	32.2	5.55	33.75	375	316	P	H
		2497.9	28.77	-25.23	54	-	-	-	-	-	-	A	H
	*	2480	105.97	-	-	101.91	32.27	5.55	33.76	140	84	P	V
		2480	81.21	-	-	-	-	-	-	-	-	A	V
		2490.76	56.88	-17.12	74	52.89	32.2	5.55	33.76	140	84	P	V
		2490.76	32.12	-21.88	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15C 2.4GHz 2400~2483.5MHz
BT (Harmonic @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH 00 2402MHz		4806	57.26	-16.74	74	77.09	34.2	8.1	62.13	300	196	P	H
		4806	32.50	-21.50	54	-	-	-	-	-	-	A	H
		4806	55.67	-18.33	74	75.5	34.2	8.1	62.13	237	257	P	V
		4806	30.91	-23.09	54	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		4882	56.77	-17.23	74	76.68	34.13	8.07	62.11	296	189	P	H
		4882	32.01	-21.99	54	-	-	-	-	-	-	A	H
		7323	55.47	-18.53	74	71.89	36.6	9.75	62.77	236	196	P	H
		7323	30.71	-23.29	54	-	-	-	-	-	-	A	H
		4884	55.63	-18.37	74	75.54	34.13	8.07	62.11	285	246	P	V
		4884	30.87	-23.13	54	-	-	-	-	-	-	A	V
		7323	44.74	-29.26	74	61.16	36.6	9.75	62.77	100	360	P	V
		7323	19.98	-34.02	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4962	57.03	-16.97	74	76.96	34.1	8.05	62.08	270	191	P	H
		4962	32.27	-21.73	54	-	-	-	-	-	-	A	H
		7440	56.15	-17.85	74	72.69	36.4	9.84	62.78	236	195	P	H
		7440	31.39	-22.61	54	-	-	-	-	-	-	A	H
		4960	53.27	-20.73	74	73.2	34.1	8.05	62.08	289	189	P	V
		4960	28.51	-25.49	54	-	-	-	-	-	-	A	V
		7440	53.58	-20.42	74	70.12	36.4	9.84	62.78	189	147	P	V
		7440	28.82	-25.18	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15C Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		62.98	24.52	-15.48	40	43.49	12.56	0.81	32.34			P	H
		166.77	31.63	-11.87	43.5	46.71	15.63	1.36	32.07			P	H
		187.14	28.18	-15.32	43.5	43.36	15.41	1.44	32.03			P	H
		233.7	36.37	-9.63	46	49.8	16.77	1.67	31.87	100	214	P	H
		244.37	33.4	-12.6	46	45.54	17.97	1.71	31.82			P	H
		480.08	28.77	-17.23	46	34.95	23.14	2.32	31.64			P	H
		35.82	33.66	-6.34	40	44.99	20.62	0.63	32.58			P	V
		48.43	37.59	-2.41	40	54.67	14.7	0.69	32.47			P	V
		167.74	41.11	-2.39	43.5	56.2	15.61	1.36	32.06	100	260	P	V
		186.17	37.78	-5.72	43.5	52.99	15.39	1.43	32.03			P	V
		233.7	37.41	-8.59	46	50.84	16.77	1.67	31.87			P	V
		246.31	35.32	-10.68	46	47.22	18.2	1.72	31.82			P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

Appendix B.   Duty Cycle Plots

DH5 on time (One Pulse) Plot on Channel 39

DH5 on time (Count Pulses) Plot on Channel 39

Note:

1.   Worst case Duty cycle = on time/100 milliseconds = 2 * 2.89 / 100 = 5.78 %

2.   Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.76 dB

3.   DH5 has the highest duty cycle worst case and is reported.