

## ELECTRONICS TESTING CENTER, TAIWAN

NO. 8, LANE 29, WEN-MING RD.,  
LO-SHAN TSUN. KUI-SHAN  
HSIANG, TAOYUAN HSIEN  
333, TAIWAN, R. O. C.

Tel:(03)3280026  
Fax:(03)3280034

*According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation distance  $\leq 50$  mm are determined by:*

*$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$*

The max. average power of channel, including tune-up tolerance(mW) is  
**12.589mW @ 951.825MHz** (With Tune-up tolerance),

The min. test separation distance (mm) is **5 mm**,

So,  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = \mathbf{2.46 < 3.0}$  (With Tune-up tolerance).

Therefore, standalone SAR measurements are not required for both head and body.

Signature S S Liou

Name/Title: S. S. Liou / Section Manager, EMC Testing Department II

TEL: +886-2-2602-3052

Email: ssliou@etc.org.tw