

# FCC ID : 2AA9Y-DAIDT05

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in § 1.1307(b)

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>300-1500</b>	--	--	<b>F/300</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>300-1500</b>	--	--	<b>F/1500</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>1</b>	<b>30</b>

### 11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$ = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in mW

$G$ = Numeric gain of the antenna relative to isotropic antenna

$\pi$ =3.1416

$R$ = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### 11.2 Measurement Result

Antenna gain: 0 dBi

Mode	Max Output Peak power (dBm)	Output Peak power (mW)	Antenna Gain Numeric	Power density at 20cm (mW/ cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
GFSK	4.00	2.51	1.00	0.00050	1
GFSK	3.14	2.06	1.00	0.00041	1
GFSK	1.94	1.56	1.00	0.00031	1
$\pi$ /4DQPSK	2.89	1.95	1.00	0.00039	1
$\pi$ /4DQPSK	1.57	1.44	1.00	0.00029	1
$\pi$ /4DQPSK	0.08	1.02	1.00	0.00020	1
8DPSK	2.95	1.97	1.00	0.00039	1
8DPSK	1.92	1.56	1.00	0.00031	1
8DPSK	0.37	1.09	1.00	0.00022	1