



# FCC PART 15.247 TEST REPORT

For

# SENWA MEXICO,S.A.DE C.V

CARRETERA MEXICO-TOLUCA No. 5324, INT. PLANTA BAJA, COL. EL YAQUI, CUAJIMALPA DE MORELOS, CIUDAD DE MEXICO, Mexico

FCC ID: 2AAA6-LS5018FP

Report Type: Product Type:
Original Report Mobile Phone

**Report Number:** RSZ190619001-00C

**Report Date:** 2019-07-24

Nancy Wang

**Reviewed By:** RF Engineer

**Prepared By:** Bay Area Compliance Laboratories Corp. (Shenzhen)

6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone,

Nany Wang

Shenzhen, Guangdong, China Tel: +86-755-33320018

Fax: +86-755-33320008 www.baclcorp.com.cn

**Note**: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. \* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "\*".

The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

# **TABLE OF CONTENTS**

GENERAL INFORMATION	
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
OBJECTIVE	
RELATED SUBMITTAL(S)/GRANT(S)	
MEASUREMENT UNCERTAINTY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EQUIPMENT MODIFICATIONS	
EUT Exercise Software	
DUTY CYCLE	
EXTERNAL I/O CABLEBLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
TEST EQUIPMENT LIST	
FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE	
APPLICABLE STANDARD	
FCC §15.203 - ANTENNA REQUIREMENT	
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	
APPLICABLE STANDARDEUT SETUP	
EMI TEST RECEIVER SETUP.	
TEST PROCEDURE	
CORRECTED FACTOR & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	22
APPLICABLE STANDARDEUT SETUP	
EUT SETUP	
TEST PROCEDURE	23
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	
APPLICABLE STANDARD	
TEST PROCEDURE	
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	
APPLICABLE STANDARD	
TEST PROCEDURE	

Test Data	48
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	50
APPLICABLE STANDARD	50
TEST PROCEDURE	50
Test Data	50
FCC §15.247(e) - POWER SPECTRAL DENSITY	55
APPLICABLE STANDARD	55
Test Procedure	
TEST DATA	55

# **GENERAL INFORMATION**

# **Product Description for Equipment under Test (EUT)**

Product	Mobile Phone
Model	LS5018FP
Frequency Range	Bluetooth LE: 2402~2480MHz WI-FI: 2412~2462MHz
Transmit Power(Conducted)	BLE: -1.48 dBm WIFI: 802.11b: 10.53 dBm, 802.11G: 13.82 dBm, 802.11N20: 13.39 dBm
Modulation Technique	Bluetooth LE: GFSK WIFI: DSSS, OFDM
Antenna Specification	FPC Antenna Bluetooth/WIFI: 1.5dBi@2.4GHz
Voltage Range	DC 3.8V from battery or DC 5.0V from adapter
Date of Test	2019/06/21~2019/07/18
Sample serial number	LS5018FP201809000001
Received date	2019/06/19
Sample/EUT Status	Good condition
Adapter information	Model: LS5018FP Input: AC 100-240V, 50/60Hz, 0.2A Output: DC 5V, 1A

Report No.: RSZ190619001-00C

# **Objective**

This report is prepared on behalf of *SENWA MEXICO*, *S.A.DE C.V* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS and Part 22H /24E / 27 PCE submissions with FCC ID: 2AAA6-LS5018FP.

FCC Part 15.247 Page 4 of 62

### **Test Methodology**

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

Report No.: RSZ190619001-00C

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

# **Measurement Uncertainty**

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power	with Power meter	±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions,	Below 1GHz	±4.75dB
Radiated	Above 1GHz	±4.88dB
Temperature		±1℃
Humidity		±6%
Supply voltages		±0.4%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

### **Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

FCC Part 15.247 Page 5 of 62

# **SYSTEM TEST CONFIGURATION**

# **Description of Test Configuration**

For 802.11b, 802.11g and 802.11n-HT20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

Report No.: RSZ190619001-00C

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

For BLE Mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

FCC Part 15.247 Page 6 of 62

# **Equipment Modifications**

No modification was made to the EUT tested.

# **EUT Exercise Software**

BLE & Wi-Fi test in the engineer mode.

The device was tested with the worst case was performed as below:

Mada	Mode Data rate		Power level	
Mode	Data rate	Low channel	Middle channel	High channel
802.11b	1 Mbps	8	10	8
802.11g	6 Mbps	8	9	8
802.11n-HT20	MCS0	8	9	8
BLE	/	Default	Default	Default


Report No.: RSZ190619001-00C

Pre-scan with all the data rates, the above data rate is the worst case for Wi-Fi test.

FCC Part 15.247 Page 7 of 62


# **Duty cycle**





Date: 3.JUL.2019 16:43:52


# 802.11g mode



Date: 3.JUL.2019 16:44:19


FCC Part 15.247 Page 8 of 62

### 802.11n-HT20 Mode



Date: 3.JUL.2019 16:44:49

# **BLE Mode**



Date: 22.JUN.2019 00:40:25

FCC Part 15.247 Page 9 of 62


Report No.: RSZ190619001-00C

# **External I/O Cable**

Cable Description	Length (m)	From Port	То
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

# **Block Diagram of Test Setup**

For conducted emission



FCC Part 15.247 Page 10 of 62

# **SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Report No.: RSZ190619001-00C

FCC Part 15.247 Page 11 of 62

# TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
	Condu	cted Emissions	Test		
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2019-07-11	2020-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2019-01-25	2020-01-25
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2019-03-02	2020-03-02
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Un-known	Conducted Emission Cable	78652	UF A210B-1- 0720-504504	2018-11-12	2019-11-12
	Radia	ated Emission T	'est		
A.H. System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2018-07-22	2019-07-21
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
COM-POWER	Pre-amplifier	PA-122	181919	2018-11-12	2019-11-12
Sonoma Instrument	Amplifier	310N	186238	2018-11-12	2019-11-12
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2019-07-09	2020-07-08
Ducommun technologies	RF Cable	UFA147A- 2362-100100	MFR64639 231029-003	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	RG-214	1	2019-05-21	2019-11-19
Ducommun technologies	RF Cable	RG-214	2	2018-11-12	2019-11-12
Ducommun Technologies	Horn Antenna	ARH-4223- 02	1007726-04	2017-12-29	2020-12-28
Heatsink Required	Amplifier	QLW- 18405536-J0	15964001002	2018-11-12	2019-11-12
Sinoscite	Notch Filter	BSF2402- 2480MN- 0898-001	99632	2018-11-12	2019-11-12
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR

Report No.: RSZ190619001-00C

FCC Part 15.247 Page 12 of 62

Report No.: RSZ190619001-00C

FCC Part 15.247 Page 13 of 62

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

# FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

# **Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: RSZ190619001-00C

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

- 1. f(GHz) is the RF channel transmit frequency in GHz.
- 2. Power and distance are rounded to the nearest mW and mm before calculation.
- 3. The result is rounded to one decimal place for comparison.
- 4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

#### **Measurement Result**

#### For worst case:

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2480	-1.0	0.79	5	0.25	3.0	Yes
WIFI	2462	8.0	6.31	5	1.98	3.0	Yes

Result: No SAR test is required

FCC Part 15.247 Page 14 of 62

# FCC §15.203 - ANTENNA REQUIREMENT

# **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

Report No.: RSZ190619001-00C

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is 1.5 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

**Result:** Compliance.


FCC Part 15.247 Page 15 of 62

# FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

# **Applicable Standard**

FCC§15.207

### **EUT Setup**



Report No.: RSZ190619001-00C

Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

### **EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

FCC Part 15.247 Page 16 of 62

#### **Test Procedure**

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

# **Corrected Factor & Margin Calculation**

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Report No.: RSZ190619001-00C

Margin = Limit - Corrected Amplitude

# **Test Results Summary**

According to the EUT complied with the FCC Part 15.207.

### **Test Data**

### **Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa


The testing was performed by Haiguo Li on 2019-07-15.

EUT operation mode: Transmitting & Charging

FCC Part 15.247 Page 17 of 62

**BLE Mode:** 

# AC 120V/60 Hz, Line




Report No.: RSZ190619001-00C

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.506350	41.4	19.8	56.0	14.6	QP
0.624610	39.0	19.8	56.0	17.0	QP
0.801970	41.4	19.8	56.0	14.6	QP
0.892650	36.3	19.8	56.0	19.7	QP
1.006670	40.1	19.9	56.0	15.9	QP
1.012970	39.9	19.9	56.0	16.1	QP
0.506350	31.9	19.8	46.0	14.1	Ave.
0.624610	29.7	19.8	46.0	16.3	Ave.
0.801970	29.5	19.8	46.0	16.5	Ave.
0.892650	27.0	19.8	46.0	19.0	Ave.
1.006670	32.3	19.9	46.0	13.7	Ave.
1.012970	33.5	19.9	46.0	12.5	Ave.

FCC Part 15.247 Page 18 of 62

# AC 120V/60 Hz, Neutral




Report No.: RSZ190619001-00C

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.537870	43.3	19.8	56.0	12.7	QP
0.541990	42.7	19.8	56.0	13.3	QP
0.707290	42.4	19.8	56.0	13.6	QP
0.869010	43.8	19.7	56.0	12.2	QP
1.006670	42.5	19.8	56.0	13.5	QP
1.006910	42.6	19.8	56.0	13.4	QP
0.537870	29.9	19.8	46.0	16.1	Ave.
0.541990	31.3	19.8	46.0	14.7	Ave.
0.707290	29.7	19.8	46.0	16.3	Ave.
0.869010	33.3	19.7	46.0	12.7	Ave.
1.006670	32.0	19.8	46.0	14.0	Ave.
1.006910	32.0	19.8	46.0	14.0	Ave.

FCC Part 15.247 Page 19 of 62

Wi-Fi Mode:

# AC 120 V/60 Hz, Line:




Report No.: RSZ190619001-00C

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.510410	43.7	19.8	56.0	12.3	QP
0.616670	40.1	19.8	56.0	15.9	QP
0.727170	42.7	19.8	56.0	13.3	QP
0.798030	42.3	19.8	56.0	13.7	QP
0.943870	42.1	19.8	56.0	13.9	QP
1.030610	37.6	19.9	56.0	18.4	QP
0.510410	31.4	19.8	46.0	14.6	Ave.
0.616670	29.5	19.8	46.0	16.5	Ave.
0.727170	31.1	19.8	46.0	14.9	Ave.
0.798030	32.0	19.8	46.0	14.0	Ave.
0.943870	32.3	19.8	46.0	13.7	Ave.
1.030610	27.2	19.9	46.0	18.8	Ave.

FCC Part 15.247 Page 20 of 62

# **AC 120V/60 Hz, Neutral:**



Report No.: RSZ190619001-00C

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.541870	46.8	19.8	56.0	9.2	QP
0.652190	43.3	19.8	56.0	12.7	QP
0.715290	42.5	19.8	56.0	13.5	QP
0.865010	43.3	19.8	56.0	12.7	QP
1.022850	41.6	19.8	56.0	14.4	QP
1.089590	41.9	19.8	56.0	14.1	QP
0.541870	32.4	19.8	46.0	13.6	Ave.
0.652190	29.7	19.8	46.0	16.3	Ave.
0.715290	29.8	19.8	46.0	16.2	Ave.
0.865010	33.4	19.8	46.0	12.6	Ave.
1.022850	31.1	19.8	46.0	14.9	Ave.
1.089590	32.8	19.8	46.0	13.2	Ave.

#### Note:

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit Corrected Amplitude

FCC Part 15.247 Page 21 of 62


# FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

# **Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;


# **EUT Setup**

### **Below 1 GHz:**



Report No.: RSZ190619001-00C

#### Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

FCC Part 15.247 Page 22 of 62

# **EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Report No.: RSZ190619001-00C

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz Note 1	/	Average
	1MHz	>1/T Note 2	/	Average

Note 1: when duty cycle is no less than 98% Note 2: when duty cycle is less than 98%

### **Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

# **Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

# **Test Results Summary**

According to the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

FCC Part 15.247 Page 23 of 62

# **Test Data**

### **Environmental Conditions**

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa


The testing was performed by Baston Chen on 2019-07-18 and Alan He from on 2019-07-01.

Report No.: RSZ190619001-00C

EUT operation mode: Transmitting

### **BLE & Wi-Fi Mode:**

# 30 MHz~1 GHz (Worst case at 802.11b mode, Low channel)



FCC Part 15.247 Page 24 of 62

Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
119.507875	25.12	273.0	Н	222.0	-14.3	43.50	18.38
142.623375	26.12	233.0	Н	43.0	-14.2	43.50	17.38
147.791125	25.96	187.0	Н	37.0	-14.2	43.50	17.54
228.836375	25.89	110.0	Н	310.0	-14.0	46.00	20.11
826.967000	27.49	230.0	Н	278.0	4.6	46.00	18.51
955.833500	32.06	335.0	Н	223.0	9.5	46.00	13.94

Report No.: RSZ190619001-00C

# 1 GHz-25 GHz:

# **BLE Mode:**

Engguenav	Re	ceiver	Turntable	Rx An	tenna	Corrected	Corrected	Limit	Margin	
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Degree	Height (m)	Polar (H/V)	Factor (dB/m)	Amplitude (dBμV/m)	(dBµV/m)	(dB)	
	Low Channel (2402 MHz)									
2316.66	28.19	PK	24	1.7	V	31.64	59.83	74	14.17	
2316.66	13.56	Ave.	24	1.7	V	31.64	45.20	54	8.80	
2493.59	28.33	PK	144	1.7	V	32.13	60.46	74	13.54	
2493.59	13.72	Ave.	144	1.7	V	32.13	45.85	54	8.15	
4804.00	43.59	PK	358	2.1	V	6.28	49.87	74	24.13	
4804.00	28.68	Ave.	358	2.1	V	6.28	34.96	54	19.04	
			Middle C	hannel	(2440 N	/IHz)				
4880.00	43.41	PK	286	1.2	V	6.76	50.17	74	23.83	
4880.00	28.51	Ave.	286	1.2	V	6.76	35.27	54	18.73	
			High Ch	nannel (2	2480 M	Hz)				
2338.42	28.77	PK	3	1.6	V	31.64	60.41	74	13.59	
2338.42	13.64	Ave.	3	1.6	V	31.64	45.28	54	8.72	
2493.21	28.68	PK	185	2.5	V	32.13	60.81	74	13.19	
2493.21	13.73	Ave.	185	2.5	V	32.13	45.86	54	8.14	
4960.00	43.51	PK	173	1.1	V	6.80	50.31	74	23.69	
4960.00	28.56	Ave.	173	1.1	V	6.80	35.36	54	18.64	

FCC Part 15.247 Page 25 of 62

# Wi-Fi Mode:

# 802.11b Mode:

Enganomay	Re	eceiver	Turntable	Rx An	tenna	Corrected	Corrected	Limit	Mongin		
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Degree	Height (m)	Polar (H/V)	Factor (dB/m)	Amplitude (dBµV/m)	(dBµV/m)	Margin (dB)		
	Low Channel (2412 MHz)										
2383.34	27.97	PK	160	1.1	V	31.87	59.84	74	14.16		
2383.34	13.51	Ave.	160	1.1	V	31.87	45.38	54	8.62		
2497.82	28.07	PK	238	1.1	V	32.13	60.20	74	13.80		
2497.82	13.62	Ave.	238	1.1	V	32.13	45.75	54	8.25		
4824.00	45.43	PK	309	1.3	V	6.28	51.71	74	22.29		
4824.00	35.52	Ave.	309	1.3	V	6.28	41.80	54	12.20		
7236.00	46.90	PK	254	2.3	V	11.93	58.83	74	15.17		
7236.00	39.89	Ave.	254	2.3	V	11.93	51.82	54	2.18		
			Middle C	Channel	(2437N	IHz)					
4874.00	43.59	PK	91	1.3	V	6.76	50.35	74	23.65		
4874.00	32.34	Ave.	91	1.3	V	6.76	39.10	54	14.90		
7311.00	44.09	PK	348	2.5	V	11.56	55.65	74	18.35		
7311.00	32.53	Ave.	348	2.5	V	11.56	44.09	54	9.91		
			High Ch	annel (2	2462 M	Hz)					
2314.69	27.73	PK	10	1.1	V	31.64	59.37	74	14.63		
2314.69	13.52	Ave.	10	1.1	V	31.64	45.16	54	8.84		
2492.40	28.03	PK	190	1.9	V	32.13	60.16	74	13.84		
2492.40	13.59	Ave.	190	1.9	V	32.13	45.72	54	8.28		
4924.00	45.03	PK	100	2.2	V	6.76	51.79	74	22.21		
4924.00	34.66	Ave.	100	2.2	V	6.76	41.42	54	12.58		
7386.00	45.04	PK	33	2.1	V	12.29	57.33	74	16.67		
7386.00	36.17	Ave.	33	2.1	V	12.29	48.46	54	5.54		

Report No.: RSZ190619001-00C

FCC Part 15.247 Page 26 of 62

# 802.11g Mode:

E	Re	eceiver	T4-1-1-	Rx Ar	itenna	Corrected	Corrected	T ::4	Manain	
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Turntable Degree	Height (m)		Factor (dB/m)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)	
Low Channel (2412 MHz)										
2371.19	27.87	PK	266	2.0	V	31.87	59.74	74	14.26	
2371.19	13.54	Ave.	266	2.0	V	31.87	45.41	54	8.59	
2483.89	28.52	PK	20	1.1	V	32.13	60.65	74	13.35	
2483.89	13.59	Ave.	20	1.1	V	32.13	45.72	54	8.28	
4824.00	43.88	PK	348	1.4	V	6.28	50.16	74	23.84	
4824.00	29.06	Ave.	348	1.4	V	6.28	35.34	54	18.66	
7236.00	44.60	PK	56	1.8	V	11.93	56.53	74	17.47	
7236.00	28.53	Ave.	56	1.8	V	11.93	40.46	54	13.54	
			Middle C	Channel	(2437N	(IHz)				
4874.00	44.15	PK	339	1.3	V	6.76	50.91	74	23.09	
4874.00	28.35	Ave.	339	1.3	V	6.76	35.11	54	18.89	
7311.00	43.92	PK	235	1.4	V	11.56	55.48	74	18.52	
7311.00	28.18	Ave.	235	1.4	V	11.56	39.74	54	14.26	
			High Ch	annel (	2462 M	Hz)				
2382.30	28.36	PK	199	1.6	V	31.87	60.23	74	13.77	
2382.30	13.53	Ave.	199	1.6	V	31.87	45.40	54	8.60	
2483.75	29.31	PK	22	1.7	V	32.13	61.44	74	12.56	
2483.75	13.93	Ave.	22	1.7	V	32.13	46.06	54	7.94	
4924.00	44.47	PK	56	2.4	V	6.76	51.23	74	22.77	
4924.00	28.58	Ave.	56	2.4	V	6.76	35.34	54	18.66	
7386.00	45.38	PK	286	2.1	V	12.29	57.67	74	16.33	
7386.00	28.51	Ave.	286	2.1	V	12.29	40.80	54	13.20	

Report No.: RSZ190619001-00C

FCC Part 15.247 Page 27 of 62

### 802.11n-HT20 Mode:

E	Re	eceiver	T4-1-1-	Rx An	tenna	Corrected	Corrected	Limit	Manain	
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Turntable Degree	Height (m)	Polar (H/V)	Factor (dB/m)	Amplitude (dBμV/m)	(dBµV/m)	Margin (dB)	
	Low Channel (2412 MHz)									
2338.08	28.46	PK	320	2.3	V	31.64	60.10	74	13.90	
2338.08	13.54	Ave.	320	2.3	V	31.64	45.18	54	8.82	
2496.96	28.73	PK	21	1.3	V	32.13	60.86	74	13.14	
2496.96	13.62	Ave.	21	1.3	V	32.13	45.75	54	8.25	
4824.00	44.24	PK	30	2.3	V	6.28	50.52	74	23.48	
4824.00	28.76	Ave.	30	2.3	V	6.28	35.04	54	18.96	
7236.00	46.11	PK	112	1.6	V	11.93	58.04	74	15.96	
7236.00	29.13	Ave.	112	1.6	V	11.93	41.06	54	12.94	
			Middle C	Channel	(2437N	(IHz)				
4874.00	43.28	PK	289	1.5	V	6.76	50.04	74	23.96	
4874.00	28.18	Ave.	289	1.5	V	6.76	34.94	54	19.06	
7311.00	44.06	PK	294	2.0	V	11.56	55.62	74	18.38	
7311.00	27.58	Ave.	294	2.0	V	11.56	39.14	54	14.86	
			High Ch	annel (	2462 M	Hz)				
2379.29	27.90	PK	20	2.4	V	31.87	59.77	74	14.23	
2379.29	13.53	Ave.	20	2.4	V	31.87	45.40	54	8.60	
2483.56	29.41	PK	65	2.0	V	32.13	61.54	74	12.46	
2483.56	13.95	Ave.	335	2.3	V	32.13	46.08	54	7.92	
4924.00	43.18	PK	298	1.6	V	6.76	49.94	74	24.06	
4924.00	28.44	Ave.	298	1.6	V	6.76	35.20	54	18.80	
7386.00	46.17	PK	132	1.4	V	12.29	58.46	74	15.54	
7386.00	28.97	Ave.	132	1.4	V	12.29	41.26	54	12.74	

Report No.: RSZ190619001-00C

#### Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.


And for the pre-scan is performed with the 2400-2483.5MHz band filter.

FCC Part 15.247 Page 28 of 62


# Pre-scan with 802.11B Mode, Low channel

Report No.: RSZ190619001-00C

#### Horizontal




Date: 1.JUL.2019 17:30:09




FCC Part 15.247 Page 29 of 62

# Vertical

Report No.: RSZ190619001-00C



Date: 1.JUL.2019 17:37:23




Date: 1.JUL.2019 18:20:57


FCC Part 15.247 Page 30 of 62

# Pre-scan for Average Horizontal

Report No.: RSZ190619001-00C




Date: 1.JUL.2019 17:33:56




Date: 1.JUL.2019 18:39:27

FCC Part 15.247 Page 31 of 62




Date: 1.JUL.2019 17:50:19




Date: 1.JUL.2019 17:48:10

FCC Part 15.247 Page 32 of 62

Report No.: RSZ190619001-00C




Date: 1.JUL.2019 17:41:00




Date: 1.JUL.2019 18:27:04

FCC Part 15.247 Page 33 of 62



Date: 1.JUL.2019 17:53:11



Date: 1.JUL.2019 17:46:51

FCC Part 15.247 Page 34 of 62

# FCC $\S15.247(a)$ (2) – 6 dB EMISSION BANDWIDTH


### **Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Report No.: RSZ190619001-00C

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.



### **Test Data**

#### **Environmental Conditions**

Temperature:	25℃
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by George Zhong and Kieron Luo from 2019-06-22 to 2019-07-23.

Test Result: Pass.

Please refer to the following table and plots.


FCC Part 15.247 Page 35 of 62

Channel	Frequency (MHz)	6dB bandwidth (MHz)	99% OBW (MHz)	Limit (kHz)		
	802.11b mode					
Low	2412	8.654	11.795	≥500		
Middle	2437	9.103	11.474	≥500		
High	2462	8.654	11.603	≥500		
802.11g mode						
Low	2412	15.833	17.115	≥500		
Middle	2437	15.897	17.051	≥500		
High	2462	15.833	16.987	≥500		
802.11n-HT20 mode						
Low	2412	16.410	17.949	≥500		
Middle	2437	16.346	17.885	≥500		
High	2462	16.410	17.821	≥500		

Report No.: RSZ190619001-00C


Channel	Frequency (MHz)	6 dB Emission Bandwidth(MHz)	Limit (kHz)		
BLE Mode					
Low	2402	0.676	≥500		
Middle	2440	0.670	≥500		
High	2480	0.670	≥500		

FCC Part 15.247 Page 36 of 62



Date: 3.JUL.2019 16:06:39


## 6dB Bandwidth, 802.11b Middle Channel



Date: 3.JUL.2019 16:09:51


FCC Part 15.247 Page 37 of 62

## 6dB Bandwidth, 802.11b High Channel



Date: 3.JUL.2019 16:08:32


## 6dB Bandwidth, 802.11g Low Channel



Date: 3.JUL.2019 16:17:14


FCC Part 15.247 Page 38 of 62

## 6dB Bandwidth, 802.11g Middle Channel



Date: 3.JUL.2019 16:21:49

## 6dB Bandwidth, 802.11g High Channel




Date: 3.JUL.2019 16:15:50

FCC Part 15.247 Page 39 of 62


## 6dB Bandwidth, 802.11n-HT20 Low Channel

Report No.: RSZ190619001-00C



Date: 3.JUL.2019 16:26:10


## 6dB Bandwidth, 802.11n-HT20 Middle Channel



Date: 3.JUL.2019 16:24:41


FCC Part 15.247 Page 40 of 62

## 6dB Bandwidth, 802.11n-HT20 High Channel



Date: 3.JUL.2019 16:28:53

## 99% Occupied Bandwidth, 802.11b Low Channel




Date: 23.JUL.2019 10:33:28

FCC Part 15.247 Page 41 of 62


## 99% Occupied Bandwidth, 802.11b Middle Channel

Report No.: RSZ190619001-00C




Date: 23.JUL.2019 10:37:17

## 99% Occupied Bandwidth, 802.11b High Channel




Date: 23.JUL.2019 10:39:03

FCC Part 15.247 Page 42 of 62



Date: 23.JUL.2019 10:43:52

## 99% Occupied Bandwidth, 802.11g Middle Channel




Date: 23.JUL.2019 10:45:52

FCC Part 15.247 Page 43 of 62


## 99% Occupied Bandwidth, 802.11g High Channel

Report No.: RSZ190619001-00C




Date: 23.JUL.2019 10:47:56

## 99% Occupied Bandwidth, 802.11n-HT20 Low Channel




Date: 23.JUL.2019 10:51:05

FCC Part 15.247 Page 44 of 62



Date: 23.JUL.2019 10:52:51

## 99% Occupied Bandwidth, 802.11n-HT20 High Channel



Date: 23.JUL.2019 10:54:31


FCC Part 15.247 Page 45 of 62

#### **BLE Low Channel**



Date: 22.JUN.2019 00:48:09


#### **BLE Middle Channel**



Date: 22.JUN.2019 00:47:24

FCC Part 15.247 Page 46 of 62

## **BLE High Channel**



Date: 22.JUN.2019 00:46:32

FCC Part 15.247 Page 47 of 62

## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


#### **Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Report No.: RSZ190619001-00C

#### **Test Procedure**

- 1. Place the EUT on a bench and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.



#### **Test Data**

#### **Environmental Conditions**

Temperature:	25℃	
Relative Humidity:	50 %	
ATM Pressure:	101.0 kPa	

The testing was performed by George Zhong and Kieron Luo from 2019-06-22 to 2019-07-03.

EUT operation mode: Transmitting

FCC Part 15.247 Page 48 of 62

## Wi-Fi mode

Report No.: RSZ190619001-00C

Channel	Frequency (MHz)	Max Conducted Average Output Power (dBm)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	
		802.11b			
Low	2412	7.69	10.37	30	
Middle	2437	7.86	10.53	30	
High	2462	7.56	10.33	30	
	802.11g				
Low	2412	7.04	13.05	30	
Middle	2437	7.59	13.82	30	
High	2462	7.80	13.75	30	
802.11n HT20					
Low	2412	7.18	13.13	30	
Middle	2437	7.16	13.39	30	
High	2462	7.20	13.35	30	

## **BLE Mode**

Channel	Frequency (MHz)	Max Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	-6.63	30	Pass
Middle	2440	-1.48	30	Pass
High	2480	-3.70	30	Pass

FCC Part 15.247 Page 49 of 62

## FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Report No.: RSZ190619001-00C

#### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.



#### **Test Data**

#### **Environmental Conditions**

Temperature:	25℃	
Relative Humidity:	50 %	
ATM Pressure:	101.0 kPa	

The testing was performed by George Zhong and Kieron Luo from 2019-06-22 to 2019-07-03.


EUT operation mode: Transmitting

Test Result: Compliance

Please refer to the following plots.


FCC Part 15.247 Page 50 of 62

802.11b: Band Edge, Left Side



Date: 3.JUL.2019 16:11:15


802.11b: Band Edge, Right Side



Date: 3.JUL.2019 16:12:14


FCC Part 15.247 Page 51 of 62

## 802.11g: Band Edge, Left Side



Date: 3.JUL.2019 16:18:12


## 802.11g: Band Edge, Right Side



Date: 3.JUL.2019 16:14:49


FCC Part 15.247 Page 52 of 62

## 802.11n-HT20: Band Edge, Left Side



Date: 3.JUL.2019 16:26:51


## 802.11n-HT20: Band Edge, Right Side



Date: 3.JUL.2019 16:27:53


FCC Part 15.247 Page 53 of 62

**BLE: Band Edge, Left Side** 



Date: 22.JUN.2019 00:42:27

**BLE: Band Edge, Right Side** 



Date: 22.JUN.2019 00:43:43

FCC Part 15.247 Page 54 of 62

## FCC §15.247(e) - POWER SPECTRAL DENSITY

### **Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Report No.: RSZ190619001-00C

#### **Test Procedure**

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW to:  $3kHz \le RBW \le 100 \text{ kHz}$ .
- 3. Set the VBW  $> 3 \times RBW$ .
- 4. Set the span to 1.5 times the DTS bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



#### **Test Data**

#### **Environmental Conditions**

Temperature:	25℃	
Relative Humidity:	50 %	
ATM Pressure:	101.0 kPa	

The testing was performed by George Zhong and Kieron Luo from 2019-06-22 to 2019-07-23.

EUT operation mode: Transmitting


Test Result: Pass

FCC Part 15.247 Page 55 of 62

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)		
	802.11b mode				
Low	2412	-18.44	≤8		
Middle	2437	-18.92	≤8		
High	2462	-19.71	≤8		
	802.11g	mode			
Low	2412	-24.22	≤8		
Middle	2437	-21.09	≤8		
High	2462	-21.48	≤8		
	802.11n-HT20 mode				
Low	2412	-21.31	≤8		
Middle	2437	-21.88	≤8		
High	2462	-21.48	≤8		
BLE Mode					
Low	2402	-22.59	≤8		
Middle	2440	-17.18	≤8		
High	2480	-19.29	≤8		


FCC Part 15.247 Page 56 of 62

## Power Spectral Density, 802.11b Low Channel



Date: 23.JUL.2019 10:36:13


## Power Spectral Density, 802.11b Middle Channel



Date: 23.JUL.2019 10:38:20


FCC Part 15.247 Page 57 of 62

## Power Spectral Density, 802.11b High Channel



Date: 23.JUL.2019 10:40:29


## Power Spectral Density, 802.11g Low Channel



Date: 23.JUL.2019 10:44:38


FCC Part 15.247 Page 58 of 62

## Power Spectral Density, 802.11g Middle Channel



Date: 23.JUL.2019 10:46:35


## Power Spectral Density, 802.11g High Channel



Date: 23.JUL.2019 10:49:23


FCC Part 15.247 Page 59 of 62

## Power Spectral Density, 802.11n-HT20 Low Channel




Date: 23.JUL.2019 10:52:05

## Power Spectral Density, 802.11n-HT20 Middle Channel




Date: 23.JUL.2019 10:53:37

FCC Part 15.247 Page 60 of 62



Date: 23.JUL.2019 10:55:28

## **Power Spectral Density, BLE Low Channel**




Date: 22.JUN.2019 00:54:03

FCC Part 15.247 Page 61 of 62


## Power Spectral Density, BLE Middle Channel

Report No.: RSZ190619001-00C



Date: 22.JUN.2019 00:54:50

## Power Spectral Density, BLE High Channel



Date: 22.JUN.2019 00:55:22

\*\*\*\*\* END OF REPORT \*\*\*\*\*

FCC Part 15.247 Page 62 of 62