



FCC PART 27 FCC PART 22H, PART 24E TEST REPORT

For

SENWA MEXICO,S.A.DE C.V

CARRETERA MEXICO-TOLUCA No. 5324, INT. PLANTA BAJA COL. EL YAQUI, DELEGACION CUAJIMALPA DE MORELOS CIUDAD DE MEXICO, Mexico

FCC ID: 2AAA6-LS130PLUS

Report Type:
Original Report

Mobile Phone(Base Unit)

Report Number: RSZ181029004-00D

Report Date: 2018-11-19

Rocky Kang

Reviewed By: RF Engineer

Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen)

6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone,

Rocky Kang

Shenzhen, Guangdong, China Tel: +86-755-33320018

Fax: +86-755-33320018 www.baclcorp.com.cn

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "**".

TABLE OF CONTENTS

GENERAL INFORMATION	
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
OBJECTIVE	
RELATED SUBMITTAL(S)/GRANT(S)	
MEASUREMENT UNCERTAINTY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EQUIPMENT MODIFICATIONS	
SUPPORT EQUIPMENT LIST AND DETAILS	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
TEST EQUIPMENT LIST	,
FCC §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	
APPLICABLE STANDARD	
RESULT	
FCC §2.1047 - MODULATION CHARACTERISTIC	
•	
FCC § 2.1046, § 22.913 (A) & § 24.232 (C); §27.50(D)(H) - RF OUTPUT POWER	12
APPLICABLE STANDARD	12
TEST PROCEDURE	
TEST DATA	
FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH	40
APPLICABLE STANDARD	40
TEST PROCEDURE	
TEST DATA	40
FCC §2.1051, §22.917(A) & §24.238(A); §27.53 (H) (M) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	7'
APPLICABLE STANDARD	
TEST PROCEDURE	
Test Data	
FCC § 2.1053; § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) SPURIOUS RADIATED EMISSIONS	120
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST DATA	
FCC § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) - BAND EDGES	12
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST DATA	124
FCC § 2.1055; § 22.355; § 24.235; §27.54 - FREQUENCY STABILITY	18
APPLICABLE STANDARD	185
TEST PROCEDURE	
Test Data	180

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The SENWA MEXICO,S.A.DE C.V's product, model number: LS130PLUS (FCC ID: 2AAA6-LS130PLUS) or the "EUT" in this report was a Mobile Phone(Base Unit), which was measured approximately: 15.2 cm (L) \times 7.2 cm (W) \times 9.35 cm (H), rated with input voltage: DC 3.8V from battery or DC 5.0V from adapter.

Adapter Information: Model: SENWAC1AM

Input: AC 100-240V, 50/60Hz, 0.25 A

Output: DC 5.0V, 1000mA

*All measurement and test data in this report was gathered from production sample serial number: 1810290040. (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-10-29.

Objective

This test report is prepared on behalf of *SENWA MEXICO*, *S.A.DE C.V* in accordance with Part 2-Subpart J, Part 22-Subpart H and Part 24-Subpart E and Subpart 27 of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS & DTS submissions with FCC ID: 2AAA6-LS130PLUS and part of system FCC Part 15.247 DSS submissions with FCC ID: 2AAA6-LS130PLUS-BT.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2-Subpart J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Part 27 – Miscellaneous wireless communications services

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty	
Occupied Char	nnel Bandwidth	±5%	
RF output power, conducted		±1.5dB	
Unwanted Emis	ssion, conducted	±1.5dB	
Emissions,	Below 1GHz	±4.70dB	
radiated	Above 1GHz	±4.80dB	
Temperature		±1°C	
Supply	voltages	±0.4%	

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.

The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50- 116218-UY
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§2.1091	Maximum Permissible Exposure(MPE)	Compliance
\$2.1046; \$ 22.913 (a); \$ 24.232 (c); \$27.50(d) (h)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905; § 22.917; § 24.238; §27.53	Occupied Bandwidth	Compliance
§ 2.1051; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; §27.54;	Frequency stability	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
		Radiated Emission	on Test		
Sunol Sciences	Sunol Sciences Horn Antenna		A052604	2017-12-22	2020-12-21
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2018-06-23	2019-06-23
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
COM-POWER	Pre-amplifier	PA-122	181919	2018-05-22	2018-11-22
Sonoma instrument	Amplifier	310N	186238	2018-05-12	2018-11-12
Sonoma instrument	Amplifier	310N	186238	2018-11-12	2019-05-12
Anritsu	Signal Generator	68369B	004114	2017-12-24	2018-12-24
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2018-01-11	2019-01-11
COM POWER	Dipole Antenna	AD-100	41000	NCR	NCR
A.H. System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31
Ducommun technologies	RF Cable	UFA147A-2362- 100100	MFR64639 231029-003	2018-08-01	2019-02-01
Ducommun technologies	RF Cable	104PEA	218124002	2018-05-21	2018-11-21
Ducommun technologies	RF Cable	RG-214	1	2018-05-21	2018-11-19
Ducommun technologies	RF Cable	RG-214	2	2018-05-22	2018-11-22
Ducommun Technologies	Horn Antenna		1007726-04	2017-12-29	2020-12-28
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-03	2017-12-29	2020-12-28
Heatsink Required	Amplifier	QLW-18405536-J0	15964001002	2018-08-01	2019-02-01

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
		RF Conducted	Test		
Rohde & Schwarz	Spectrum Analyzer	FSU26	200120	2017-12-24	2018-12-24
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2017-12-21	2018-12-21
Long Wei	DC Power Supply	TPR-6420D	398363	NCR	NCR
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2017-12-14	2018-12-14
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50- 146520-wh	2018-06-23	2019-06-23
Ducommun technologies	RF Cable	RG-214	3	Each Time	
WEINSCHEL	10dB Attenuator	5324	AU 3842	Each Time	
Un-known	Power Splitter	1620	129	Each	Time

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure							
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)			
0.3-1.34	614	1.63	*(100)	30			
1.34-30	824/f	2.19/f	$*(180/f^2)$	30			
30-300	27.5	0.073	0.2	30			
300-1500	/	/	f/1500	30			
1500-100,000	/	/	1.0	30			

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Operation			Antenna Gain		Max Conducted Power		Power Density	MPE Limit
mode	(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm ²)
Wifi	2412-2462	1.5	1.41	21.0	125.89	20	0.0353	1.0
BLE	2402-2480	1.5	1.41	0	1	20	0.0003	1.0
Bluetooth	2402-2480	1.5	1.41	8.0	6.31	20	0.0018	1.0
GSM	824-849	-1.09	0.78	32.5	1778.28	20	0.2761	0.55
PCS	1850-1910	0.38	1.09	29.5	891.25	20	0.1934	1.0
WCDMA B2	1850-1910	0.38	1.09	22.0	158.49	20	0.0344	1.0
WCDMA B5	824-849	-1.09	0.78	22.5	177.83	20	0.0276	0.55
LTE B2	1850-1910	0.38	1.09	23.5	223.87	20	0.0486	1.0
LTE B4	1710-1755	0.54	1.13	23.5	223.87	20	0.0504	1.0
LTE B5	824-849	-1.09	0.78	23.5	223.87	20	0.0348	0.55
LTE B7	2500-2570	1.20	1.32	23.0	199.53	20	0.0524	1.0
LTE B66	1710-1780	0.54	1.13	23.0	199.53	20	0.0449	1.0

Simultaneously consider: The worst case is wifi and Bluetooth and GSM cellular band transmitting simultaneously:

The rate=0.0353/1.0+0.0018/1.0+0.2761/0.55=0.5392<1

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: compliance.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC \S 2.1047(d), Part 22H & 24E & 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c); §27.50(d)(h) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB.


According to §27.50(d), Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

According to §27.50(h), Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the CMW500/CMU200 through sufficient attenuation.



Radiated method:

TIA 603-D section 2.2.17

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2018-11-10.

Conducted Power

Cellular Band (Part 22H)

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
	128	824.2	32.24	38.45
GSM	190	836.6	32.37	38.45
	251	848.8	32.40	38.45

Mode	Channel	Channel Frequency		Average Output Power (dBm)			
		(MHz)	1 slot	2 slots	3 slots	4 slots	(dBm)
	128	824.2	32.21	30.07	28.34	26.14	38.45
GPRS	190	836.6	32.33	30.30	28.65	26.46	38.45
	251	848.8	32.40	30.41	28.75	26.63	38.45

Mode	Test	Test Test	3GPP Sub	Average Output Power (dBm)		
Mode	Condition	Mode	Test	Low Frequency	Middle Frequency	High Frequency
		RMC	12.2k	21.98	22.06	22.07
			1	21.24	21.43	21.48
		HSDPA	2	21.17	21.38	21.43
			3	21.32	21.51	21.59
WCDMA	Normal		4	21.17	21.36	21.35
(Band V)	Normai		1	21.33	21.52	21.58
			2	21.30	21.40	21.51
		HSUPA	3	21.40	21.55	21.62
			4	21.21	21.40	21.51
			5	21.39	21.61	21.62

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
	512	1850.2	29.14	33
GSM	661	1880.0	28.84	33
	810	1909.8	28.33	33

Mode	Channel	Channel Frequency		Average Output Power (dBm)					
	i, rout	(MHz)	1 slot	2 slots	3 slots	4 slots	(dBm)		
	512	1850.2	29.21	27.56	25.71	24.33	33		
GPRS	661	1880.0	28.78	27.48	25.62	24.31	33		
	810	1909.8	28.45	27.32	25.23	24.20	33		

Mode	Test	Test	3GPP Sub	Average Output Power (dBm)					
Mode	Condition	Mode	Test	Low Frequency	Middle Frequency	(dBm) Middle High			
		RMC	12.2k	21.55	21.35	21.19			
			1	20.42	20.46	20.35			
		HSDPA	2	20.31	20.39	20.26			
		пзрга	3	20.46	20.53	20.44			
WCDMA			4	20.31	20.33	20.30			
(Band II)	Normal		1	20.51	20.47	20.45			
			2	20.45	20.37	20.36			
		HSUPA	3	20.61	20.51	20.53			
			4	20.44	20.44	20.35			
			5	20.60	20.54	20.51			

Peak-to-average ratio (PAR)

Cellular Band

Mode	Channel	PAR (dB)	Limit (dB)	
	Low	1.39	13	
GSM	Middle	1.42	13	
	High	1.37	13	

Mode	Channel	PAR (dB)	Limit (dB)	
2110	Low	3.47	13	
RMC (BPSK)	Middle	3.31	13	
(BPSK)	High	3.33	13	
Habby	Low	3.51	13	
HSDPA (16QAM)	Middle	3.70	13	
(10Q/111)	High	3.39	13	
Haliby	Low	3.60	13	
HSUPA (BPSK)	Middle	3.36	13	
(BI SIK)	High	3.56	13	

PCS Band

Mode	Channel	PAR (dB)	Limit (dB)
	Low	1.41	13
GSM	Middle	1.47	13
	High	1.45	13

Mode	Channel	PAR (dB)	Limit (dB)
	Low	4.43	13
RMC (BPSK)	Middle	4.62	13
(BI SII)	High	4.43	13
*******	Low	4.46	13
HSDPA (16QAM)	Middle	4.39	13
(10Q/11/1)	High	4.57	13
*******	Low	4.69	13
HSUPA (BPSK)	Middle	4.33	13
(BI SIK)	High	4.47	13

Radiated Power

GSM Mode:

	Receiver	Turntable	Rx An	tenna	S	ubstitut	ed	Absolute		
Frequency (MHz)	Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
ERP for Cellular Band (Part 22H), Middle Channel										
836.6	92.34	102	1.5	Н	33.0	1.9	0.0	31.10	38.45	7.35
836.6	87.66	295	1.3	V	27.7	1.9	0.0	25.80	38.45	12.65
		EII	RP for PC	S Band	(Part 24E)	, Middle	Channel			
1880.00	92.33	336	1.1	Н	22.3	1.30	9.40	30.40	33	2.6
1880.00	91.00	16	1.2	V	20.7	1.30	9.40	28.80	33	4.2

WCDMA Mode:

	Receiver	Turntable	Rx An	tenna	S	Substitut	ed	Absolute		
Frequency (MHz)	Reading (dBµV)		Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
	ERP for WCDMA Band V (Part 22H), Middle Channel									
836.6	86.93	164	1.6	Н	27.6	1.9	0.0	25.70	38.45	12.75
836.6	81.06	250	2.1	V	21.1	1.9	0.0	19.20	38.45	19.25
		EIRP	for WCD	MA Ban	d II (Part	24E), M	iddle Chan	nel		
1880.00	87.02	245	1.0	Н	17.0	1.30	9.40	25.10	33.00	7.9
1880.00	86.40	242	1.8	V	16.1	1.30	9.40	24.20	33.00	8.8

Note

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

Maximum Output Power

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
		RB Size=1, RB Offset=0	22.48	22.43	22.39
		RB Size=1, RB Offset=2	21.74	21.73	21.62
		RB Size=1, RB Offset=5	21.94	21.92	21.88
	QPSK	RB Size=3, RB Offset=0	22.52	22.51	22.40
		RB Size=3, RB Offset=1	22.52	22.47	22.37
		RB Size=3, RB Offset=2	21.81	21.76	21.68
1.4		RB Size=6, RB Offset=0	22.91	22.88	22.76
1.4		RB Size=1, RB Offset=0	22.34	22.22	22.10
		RB Size=1, RB Offset=2	21.58	21.52	21.40
		RB Size=1, RB Offset=5	21.78	21.73	21.63
	16QAM	RB Size=3, RB Offset=0	22.36	22.24	22.16
		RB Size=3, RB Offset=1	22.25	22.14	22.05
		RB Size=3, RB Offset=2	21.61	21.57	21.49
		RB Size=6, RB Offset=0	22.72	22.68	22.59
		RB Size=1, RB Offset=0	22.70	22.70	22.57
		RB Size=1, RB Offset=7	22.56	22.55	22.44
		RB Size=1, RB Offset=14	22.99	22.98	22.92
	QPSK	RB Size=8, RB Offset=0	22.54	22.56	22.50
		RB Size=8, RB Offset=4	22.55	22.49	22.37
		RB Size=8, RB Offset=7	22.62	22.62	22.53
3.0		RB Size=15, RB Offset=0	22.21	22.16	22.04
3.0		RB Size=1, RB Offset=0	22.54	22.49	22.44
		RB Size=1, RB Offset=7	22.34	22.25	22.14
		RB Size=1, RB Offset=14	22.88	22.82	22.78
	16QAM	RB Size=8, RB Offset=0	22.47	22.40	22.29
		RB Size=8, RB Offset=4	22.25	22.16	22.07
		RB Size=8, RB Offset=7	22.46	22.43	22.33
		RB Size=15, RB Offset=0	21.94	21.83	21.77

RB Size=50, RB Offset=0

21.45

21.86

21.57

RB Size=100, RB Offset=0

21.54

21.83

21.45

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	6.95	13	Pass
QPSK (100RB Size)	7.66	13	Pass
16QAM (1RB Size)	7.75	13	Pass
16QAM (100RB Size)	7.38	13	Pass

QPSK:

	Receiver	Turn	Rx An	tenna	S	Substitut	ed	Absolute	
Frequency (MHz)	Reading (dBµV)	table Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)
				Middle	Channel				
			1	.4 MHz	Bandwidth				
1880.00	80.17	39	1.7	Н	10.1	1.30	9.40	18.20	33
1880.00	82.32	337	1.3	V	12.1	1.30	9.40	20.20	33
				3 MHz B	andwidth				
1880.00	80.22	325	2.4	Н	10.2	1.30	9.40	18.30	33
1880.00	82.36	301	1.6	V	12.1	1.30	9.40	20.20	33
				5 MHz B	andwidth				
1880.00	79.94	4	1.7	Н	9.9	1.30	9.40	18.00	33
1880.00	81.86	43	1.6	V	11.6	1.30	9.40	19.70	33
			. 1	10 MHz I	Bandwidth				
1880.00	80.12	136	2.1	Н	10.1	1.30	9.40	18.20	33
1880.00	82.54	31	1.2	V	12.3	1.30	9.40	20.40	33
			1	12 MHz I	Bandwidth			,	
1880.00	79.64	158	1.5	Н	9.6	1.30	9.40	17.70	33
1880.00	82.14	232	1.9	V	11.9	1.30	9.40	20.00	33
			2	20 MHz I	Bandwidth				
1880.00	80.38	218	2.2	Н	10.3	1.30	9.40	18.40	33
1880.00	82.98	5	1.7	V	12.7	1.30	9.40	20.80	33

16QAM:

	Receiver	Turn	Rx An	tenna	5	Substitut	ed	Absolute		
Frequency (MHz)	Reading (dBµV)	table Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	
	Middle Channel									
	1.4 MHz Bandwidth									
1880.00	79.11	138	2.4	Н	9.1	1.30	9.40	17.20	33	
1880.00	82.23	75	2.1	V	12.0	1.30	9.40	20.10	33	
				3 MHz B	andwidth					
1880.00	78.76	3	2.1	Н	8.7	1.30	9.40	16.80	33	
1880.00	81.66	155	1.6	V	11.4	1.30	9.40	19.50	33	
				5 MHz B	andwidth					
1880.00	78.89	243	2.4	Н	8.8	1.30	9.40	16.90	33	
1880.00	81.86	89	1.9	V	11.6	1.30	9.40	19.70	33	
]	10 MHz I	Bandwidth					
1880.00	79.19	68	1.9	Н	9.1	1.30	9.40	17.20	33	
1880.00	82.13	90	2.0	V	11.9	1.30	9.40	20.00	33	
			1	15 MHz I	Bandwidth					
1880.00	79.58	117	1.2	Н	9.5	1.30	9.40	17.60	33	
1880.00	81.96	283	1.6	V	11.7	1.30	9.40	19.80	33	
	20 MHz Bandwidth									
1880.00	79.81	99	2.3	Н	9.8	1.30	9.40	17.90	33	
1880.00	82.53	342	1.4	V	12.3	1.30	9.40	20.40	33	

Maximum Output Power

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
		RB Size=1, RB Offset=0	22.38	22.32	22.25
		RB Size=1, RB Offset=2	22.29	22.24	22.15
		RB Size=1, RB Offset=5	21.99	21.93	21.85
	QPSK	RB Size=3, RB Offset=0	22.59	22.53	22.46
		RB Size=3, RB Offset=1	22.71	22.66	22.58
		RB Size=3, RB Offset=2	21.87	21.87	21.83
1.4		RB Size=6, RB Offset=0	22.53	22.49	22.39
1.4		RB Size=1, RB Offset=0	22.22	22.14	22.02
		RB Size=1, RB Offset=2	22.12	22.03	21.93
		RB Size=1, RB Offset=5	21.72	21.62	21.54
	16QAM	RB Size=3, RB Offset=0	22.34	22.21	22.08
		RB Size=3, RB Offset=1	22.49	22.36	22.29
		RB Size=3, RB Offset=2	21.77	21.67	21.59
		RB Size=6, RB Offset=0	22.26	22.21	22.10
		RB Size=1, RB Offset=0	22.30	22.31	22.23
		RB Size=1, RB Offset=7	22.09	22.10	22.00
		RB Size=1, RB Offset=14	22.72	22.72	22.60
	QPSK	RB Size=8, RB Offset=0	22.32	22.25	22.17
		RB Size=8, RB Offset=4	21.84	21.85	21.74
		RB Size=8, RB Offset=7	21.52	21.53	21.46
3.0		RB Size=15, RB Offset=0	21.62	21.57	21.51
3.0		RB Size=1, RB Offset=0	22.38	22.32	22.43
		RB Size=1, RB Offset=7	22.93	22.25	22.56
		RB Size=1, RB Offset=14	22.89	22.11	22.73
	16QAM	RB Size=8, RB Offset=0	22.91	21.84	22.61
		RB Size=8, RB Offset=4	22.78	21.94	22.62
		RB Size=8, RB Offset=7	22.51	22.21	23.02
		RB Size=15, RB Offset=0	22.49	22.31	22.86

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	6.73	13	Pass
QPSK (100RB Size)	6.84	13	Pass
16QAM (1RB Size)	7.30	13	Pass
16QAM (100RB Size)	7.32	13	Pass

QPSK:

	Receiver	Turn	Rx An	tenna	S	Substitut	ed	Absolute		
Frequency (MHz)	Reading (dBµV)	table Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	
	Middle Channel									
	1.4 MHz Bandwidth									
1732.50	79.88	31	2.1	Н	6.7	1.30	8.90	14.30	30	
1732.50	85.19	341	1.7	V	12.6	1.30	8.90	20.20	30	
				3 MHz B	andwidth					
1732.50	79.97	10	1.9	Н	6.8	1.30	8.90	14.40	30	
1732.50	86.21	249	1.4	V	13.6	1.30	8.90	21.20	30	
				5 MHz B	andwidth					
1732.50	80.11	357	1.7	Н	6.9	1.30	8.90	14.50	30	
1732.50	86.76	225	2.1	V	14.2	1.30	8.90	21.80	30	
			1	0 MHz I	Bandwidth					
1732.50	79.84	105	2.3	Н	6.7	1.30	8.90	14.30	30	
1732.50	86.96	360	1.6	V	14.4	1.30	8.90	22.00	30	
			1	5 MHz I	Bandwidth					
1732.50	79.63	146	1.2	Н	6.5	1.30	8.90	14.10	30	
1732.50	87.26	92	1.2	V	14.7	1.30	8.90	22.30	30	
	20 MHz Bandwidth									
1732.50	80.14	297	2.5	Н	7.0	1.30	8.90	14.60	30	
1732.50	87.47	310	1.1	V	14.9	1.30	8.90	22.50	30	

16QAM:

	Receiver	Turn	Rx An	tenna	5	Substitut	ed	Absolute	
Frequency (MHz)	Receiver Reading (dBµV)	table Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)
Middle Channel									
			1	.4 MHz	Bandwidth				
1732.50	79.26	324	1.2	Н	6.1	1.30	8.90	13.70	30
1732.50	86.19	309	1.8	V	13.6	1.30	8.90	21.20	30
				3 MHz B	andwidth				
1732.50	79.62	246	1.3	Н	6.5	1.30	8.90	14.10	30
1732.50	86.52	334	1.1	V	14.0	1.30	8.90	21.60	30
			_	5 MHz B	andwidth	_			
1732.50	79.13	166	1.4	Н	6.0	1.30	8.90	13.60	30
1732.50	86.33	173	1.8	V	13.8	1.30	8.90	21.40	30
				10 MHz 1	Bandwidth				
1732.50	78.66	313	1.7	Н	5.5	1.30	8.90	13.10	30
1732.50	86.43	85	2.4	V	13.9	1.30	8.90	21.50	30
				15 MHz I	Bandwidth				
1732.50	79.49	284	1.5	Н	6.3	1.30	8.90	13.90	30
1732.50	86.96	262	1.3	V	14.4	1.30	8.90	22.00	30
	20 MHz Bandwidth								
1732.50	79.86	173	1.8	Н	6.7	1.30	8.90	14.30	30
1732.50	87.21	171	1.9	V	14.6	1.30	8.90	22.20	30

LTE Band 5:

Maximum Output Power

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
		RB Size=1, RB Offset=0	22.05	22.22	22.07
		RB Size=1, RB Offset=2	21.98	22.13	21.99
		RB Size=1, RB Offset=5	22.11	22.31	22.12
	QPSK	RB Size=3, RB Offset=0	22.78	23.02	22.81
		RB Size=3, RB Offset=1	22.74	22.98	22.72
		RB Size=3, RB Offset=2	22.89	23.09	22.88
1.4		RB Size=6, RB Offset=0	20.78	21.00	20.74
1.4		RB Size=1, RB Offset=0	22.09	22.26	22.03
		RB Size=1, RB Offset=2	22.05	22.14	21.90
		RB Size=1, RB Offset=5	22.19	22.33	22.06
	16QAM	RB Size=3, RB Offset=0	21.56	21.84	21.61
		RB Size=3, RB Offset=1	21.50	21.73	21.55
		RB Size=3, RB Offset=2	21.64	21.94	21.71
		RB Size=6, RB Offset=0	21.26	21.54	21.28
		RB Size=1, RB Offset=0	22.07	22.3	22.08
		RB Size=1, RB Offset=7	21.94	22.18	22.00
		RB Size=1, RB Offset=14	22.15	22.42	22.18
	QPSK	RB Size=8, RB Offset=0	21.67	21.91	21.64
		RB Size=8, RB Offset=4	21.56	21.80	21.59
		RB Size=8, RB Offset=7	21.76	21.99	21.73
3.0		RB Size=15, RB Offset=0	21.32	21.60	21.24
3.0		RB Size=1, RB Offset=0	22.01	22.28	22.03
		RB Size=1, RB Offset=7	21.91	22.16	21.93
		RB Size=1, RB Offset=14	22.13	22.33	22.12
	16QAM	RB Size=8, RB Offset=0	21.64	21.97	21.69
		RB Size=8, RB Offset=4	21.55	21.85	21.62
		RB Size=8, RB Offset=7	21.71	22.05	21.80
		RB Size=15, RB Offset=0	21.35	21.62	21.42

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	6.73	13	Pass
QPSK (50RB Size)	7.14	13	Pass
16QAM (1RB Size)	7.08	13	Pass
16QAM (50RB Size)	7.82	13	Pass

QPSK:

	Receiver	Turn	Rx An	tenna	5	Substitut	ed	Absolute	
Frequency (MHz)	Reading (dBµV)	table Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)
				Middle	Channel				
			1	.4 MHz	Bandwidth				
836.5	83.18	153	2.4	Н	23.8	1.9	0.0	21.90	38.45
836.5	84.61	202	2.3	V	24.6	1.9	0.0	22.70	38.45
				3 MHz B	andwidth				
836.5	83.49	238	2.3	Н	24.1	1.9	0.0	22.20	38.45
836.5	84.22	343	2.3	V	24.2	1.9	0.0	22.30	38.45
			_	5 MHz B	andwidth				
836.5	83.57	293	1.6	Н	24.2	1.9	0.0	22.30	38.45
836.5	84.19	164	2.3	V	24.2	1.9	0.0	22.30	38.45
	10 MHz Bandwidth								
836.5	83.16	0	1.2	Н	23.8	1.9	0.0	21.90	38.45
836.5	84.14	351	1.9	V	24.1	1.9	0.0	22.20	38.45

16QAM:

	Receiver	Turn	Rx An	tenna		Substitut	ed	Absolute	
Frequency (MHz)	Reading (dBµV)	table Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)
				Middle	Channel				
			1	.4 MHz	Bandwidth				
836.5	82.64	182	2.0	Н	23.3	1.9	0.0	21.40	38.45
836.5	83.77	272	1.2	V	23.8	1.9	0.0	21.90	38.45
				3 MHz B	Bandwidth				
836.5	83.29	100	1.1	Н	23.9	1.9	0.0	22.00	38.45
836.5	84.27	178	1.0	V	24.3	1.9	0.0	22.40	38.45
				5 MHz B	andwidth				
836.5	83.49	224	1.5	Н	24.1	1.9	0.0	22.20	38.45
836.5	84.54	254	2.0	V	24.5	1.9	0.0	22.60	38.45
	10 MHz Bandwidth								
836.5	83.28	133	1.7	Н	23.9	1.9	0.0	22.00	38.45
836.5	84.65	241	2.3	V	24.7	1.9	0.0	22.80	38.45

LTE Band 7:

Maximum Output Power

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
		RB Size=1, RB Offset=0	22.29	22.22	22.11
		RB Size=1, RB Offset=12	21.35	21.33	21.25
		RB Size=1, RB Offset=24	21.39	21.37	21.26
	QPSK	RB Size=12, RB Offset=0	22.51	22.48	22.43
		RB Size=12, RB Offset=6	22.36	22.32	22.29
		RB Size=12, RB Offset=11	22.12	22.14	22.01
5.0		RB Size=25, RB Offset=0	22.72	22.73	22.60
3.0		RB Size=1, RB Offset=0	22.02	21.96	21.86
		RB Size=1, RB Offset=12	21.14	21.04	20.97
		RB Size=1, RB Offset=24	21.19	21.14	21.04
	16QAM	RB Size=12, RB Offset=0	22.38	22.27	22.15
		RB Size=12, RB Offset=6	22.17	22.04	21.98
		RB Size=12, RB Offset=11	21.96	21.89	21.84
		RB Size=25, RB Offset=0	22.53	22.47	22.35
		RB Size=1, RB Offset=0	22.54	22.48	22.39
		RB Size=1, RB Offset=24	22.13	22.10	22.05
		RB Size=1, RB Offset=49	22.93	22.95	22.90
	QPSK	RB Size=25, RB Offset=0	22.44	22.40	22.34
		RB Size=25, RB Offset=12	22.41	22.36	22.28
		RB Size=25, RB Offset=24	21.81	21.80	21.75
10.0		RB Size=50, RB Offset=0	22.57	22.55	22.46
10.0		RB Size=1, RB Offset=0	22.29	22.17	22.08
		RB Size=1, RB Offset=24	21.94	21.86	21.78
		RB Size=1, RB Offset=49	22.82	22.76	22.70
	16QAM	RB Size=25, RB Offset=0	22.24	22.11	22.01
		RB Size=25, RB Offset=12	22.15	22.07	22.01
		RB Size=25, RB Offset=24	21.63	21.52	21.47
		RB Size=50, RB Offset=0	22.41	22.33	22.23

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
		RB Size=1, RB Offset=0	21.76	21.74	21.61
		RB Size=1, RB Offset=37	21.41	21.38	21.32
		RB Size=1, RB Offset=74	21.26	21.27	21.20
	QPSK	RB Size=36, RB Offset=0	22.02	21.98	21.92
		RB Size=36, RB Offset=18	22.16	22.10	22.02
		RB Size=36, RB Offset=37	21.61	21.57	21.54
15.0		RB Size=75, RB Offset=0	22.14	22.13	22.05
15.0		RB Size=1, RB Offset=0	21.52	21.45	21.33
		RB Size=1, RB Offset=37	21.27	21.18	21.10
		RB Size=1, RB Offset=74	21.11	21.05	21.00
	16QAM	RB Size=36, RB Offset=0	21.87	21.81	21.77
		RB Size=36, RB Offset=18	21.92	21.86	21.82
		RB Size=36, RB Offset=37	21.49	21.42	21.31
		RB Size=75, RB Offset=0	21.94	21.90	21.86
		RB Size=1, RB Offset=0	22.13	22.13	22.05
		RB Size=1, RB Offset=49	22.07	22.07	21.97
		RB Size=1, RB Offset=99	22.40	22.34	22.26
	QPSK	RB Size=50, RB Offset=0	21.76	21.78	21.68
		RB Size=50, RB Offset=24	21.47	21.42	21.33
		RB Size=50, RB Offset=49	21.26	21.23	21.16
20.0		RB Size=100, RB Offset=0	21.28	21.26	21.15
20.0		RB Size=1, RB Offset=0	22.00	21.97	21.92
		RB Size=1, RB Offset=49	21.88	21.83	21.78
		RB Size=1, RB Offset=99	22.15	22.06	21.99
	16QAM	RB Size=50, RB Offset=0	21.64	21.54	21.45
		RB Size=50, RB Offset=24	21.25	21.16	21.04
		RB Size=50, RB Offset=49	21.13	21.06	21.02
		RB Size=100, RB Offset=0	21.04	20.97	20.93

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	6.76	13	Pass
QPSK (100RB Size)	6.17	13	Pass
16QAM (1RB Size)	7.15	13	Pass
16QAM (100RB Size)	7.89	13	Pass

QPSK:

	Receiver Reading (dBµV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute	
Frequency (MHz)			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)
	Middle Channel								
	5 MHz Bandwidth								
2535.00	77.69	1	1.5	Н	8.8	2.60	10.20	16.40	33
2535.00	84.62	228	2.3	V	15.1	2.60	10.20	22.70	33
	10 MHz Bandwidth								
2535.00	77.73	250	1.8	Н	8.9	2.60	10.20	16.50	33
2535.00	84.56	138	2.4	V	15.1	2.60	10.20	22.70	33
15 MHz Bandwidth									
2535.00	77.43	144	1.3	Н	8.6	2.60	10.20	16.20	33
2535.00	84.29	123	1.7	V	14.8	2.60	10.20	22.40	33
20 MHz Bandwidth									
2535.00	77.98	220	1.1	Н	9.1	2.60	10.20	16.70	33
2535.00	84.91	78	2.1	V	15.4	2.60	10.20	23.00	33

16QAM:

		Turn	Rx Antenna		Substituted			Absolute	
Frequency (MHz)	Receiver Reading (dBµV)	table Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)
	Middle Channel								
5 MHz Bandwidth									
2535.00	77.43	248	1.2	Н	8.6	2.60	10.20	16.20	33
2535.00	84.12	210	1.6	V	14.6	2.60	10.20	22.20	33
10 MHz Bandwidth									
2535.00	77.52	9	1.8	Н	8.6	2.60	10.20	16.20	33
2535.00	84.31	78	1.2	V	14.8	2.60	10.20	22.40	33
15 MHz Bandwidth									
2535.00	77.49	43	2.1	Н	8.6	2.60	10.20	16.20	33
2535.00	84.36	62	1.1	V	14.9	2.60	10.20	22.50	33
20 MHz Bandwidth									
2535.00	77.73	277	1.3	Н	8.9	2.60	10.20	16.50	33
2535.00	84.52	345	1.5	V	15.0	2.60	10.20	22.60	33

LTE Band 66:

Maximum Output Power

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
	QPSK	RB Size=1, RB Offset=0	22.36	22.36	22.28
		RB Size=1, RB Offset=2	22.24	22.17	22.09
		RB Size=1, RB Offset=5	22.00	22.02	21.98
		RB Size=3, RB Offset=0	22.56	22.57	22.50
		RB Size=3, RB Offset=1	22.44	22.42	22.30
		RB Size=3, RB Offset=2	22.32	22.30	22.20
1 /		RB Size=6, RB Offset=0	22.75	22.71	22.60
1.4		RB Size=1, RB Offset=0	22.25	22.20	22.14
		RB Size=1, RB Offset=2	21.99	21.95	21.88
		RB Size=1, RB Offset=5	21.91	21.87	21.80
	16QAM	RB Size=3, RB Offset=0	22.38	22.34	22.24
		RB Size=3, RB Offset=1	22.26	22.20	22.16
		RB Size=3, RB Offset=2	22.13	22.02	21.94
		RB Size=6, RB Offset=0	22.53	22.41	22.30
	QPSK	RB Size=1, RB Offset=0	22.75	22.78	22.73
		RB Size=1, RB Offset=7	22.12	22.11	22.08
		RB Size=1, RB Offset=14	22.91	22.88	22.79
		RB Size=8, RB Offset=0	22.44	22.42	22.35
		RB Size=8, RB Offset=4	22.41	22.41	22.30
3		RB Size=8, RB Offset=7	21.89	21.86	21.73
		RB Size=15, RB Offset=0	21.94	21.93	21.87
	16QAM	RB Size=1, RB Offset=0	22.62	22.56	22.50
		RB Size=1, RB Offset=7	22.04	22.01	21.94
		RB Size=1, RB Offset=14	22.75	22.71	22.64
		RB Size=8, RB Offset=0	22.30	22.27	22.17
		RB Size=8, RB Offset=4	22.25	22.17	22.09
		RB Size=8, RB Offset=7	21.60	21.56	21.52
		RB Size=15, RB Offset=0	21.84	21.80	21.73

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
	QPSK	RB Size=1, RB Offset=0	22.18	22.19	22.07
		RB Size=1, RB Offset=12	21.21	21.14	21.10
		RB Size=1, RB Offset=24	21.59	21.60	21.54
		RB Size=12, RB Offset=0	22.55	22.49	22.44
		RB Size=12, RB Offset=6	22.54	22.52	22.45
		RB Size=12, RB Offset=11	22.16	22.10	22.04
5		RB Size=25, RB Offset=0	22.40	22.34	22.28
3	16QAM	RB Size=1, RB Offset=0	21.97	21.86	21.76
		RB Size=1, RB Offset=12	20.97	20.94	20.91
		RB Size=1, RB Offset=24	21.44	21.34	21.26
		RB Size=12, RB Offset=0	22.40	22.34	22.28
		RB Size=12, RB Offset=6	22.37	22.29	22.21
		RB Size=12, RB Offset=11	21.96	21.84	21.72
		RB Size=25, RB Offset=0	20.75	20.73	20.79
	QPSK	RB Size=1, RB Offset=0	22.42	22.38	22.32
		RB Size=1, RB Offset=24	22.26	22.29	22.18
		RB Size=1, RB Offset=49	21.92	21.87	21.75
		RB Size=25, RB Offset=0	22.62	22.60	22.50
		RB Size=25, RB Offset=12	22.52	22.53	22.42
		RB Size=25, RB Offset=24	22.09	22.08	21.96
10		RB Size=50, RB Offset=0	22.68	22.68	22.56
10	16QAM	RB Size=1, RB Offset=0	21.70	21.66	21.66
		RB Size=1, RB Offset=24	21.63	21.55	21.67
		RB Size=1, RB Offset=49	21.44	21.42	21.72
		RB Size=25, RB Offset=0	22.64	20.69	20.78
		RB Size=25, RB Offset=12	22.55	20.51	20.57
		RB Size=25, RB Offset=24	22.63	20.30	20.36
		RB Size=50, RB Offset=0	20.51	20.52	20.56

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
		RB Size=1, RB Offset=0	22.15	22.07	22.39
		RB Size=1, RB Offset=37	22.05	21.95	22.24
		RB Size=1, RB Offset=74	22.06	22.04	22.26
	QPSK	RB Size=36, RB Offset=0	22.03	22.04	22.04
15		RB Size=36, RB Offset=18	22.10	21.99	21.93
		RB Size=36, RB Offset=37	22.12	21.69	21.63
		RB Size=75, RB Offset=0	21.91	21.94	22.04
		RB Size=1, RB Offset=0	22.19	22.14	22.04
		RB Size=1, RB Offset=37	22.05	21.98	21.89
		RB Size=1, RB Offset=74	21.64	21.54	21.46
	16QAM	RB Size=36, RB Offset=0	22.38	22.27	22.21
		RB Size=36, RB Offset=18	22.33	22.27	22.17
		RB Size=36, RB Offset=37	21.91	21.85	21.76
		RB Size=75, RB Offset=0	22.53	22.50	22.41
		RB Size=1, RB Offset=0	22.49	22.50	22.43
		RB Size=1, RB Offset=49	22.56	22.53	22.44
		RB Size=1, RB Offset=99	22.70	22.64	22.54
	QPSK	RB Size=50, RB Offset=0	22.53	22.49	22.44
		RB Size=50, RB Offset=24	22.27	22.29	22.22
		RB Size=50, RB Offset=49	21.93	21.88	21.80
20		RB Size=100, RB Offset=0	21.89	21.85	21.73
20		RB Size=1, RB Offset=0	22.32	22.20	22.17
		RB Size=1, RB Offset=49	22.40	22.35	22.29
		RB Size=1, RB Offset=99	22.42	22.35	22.29
	16QAM	RB Size=50, RB Offset=0	22.36	22.33	22.27
		RB Size=50, RB Offset=24	22.10	21.98	21.94
		RB Size=50, RB Offset=49	21.76	21.67	21.55
		RB Size=100, RB Offset=0	21.68	21.65	21.59

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	6.66	13	Pass
QPSK (100RB Size)	6.44	13	Pass
16QAM (1RB Size)	7.10	13	Pass
16QAM (100RB Size)	7.25	13	Pass

EIRP:

QPSK:

	Receiver	Turn	Rx An	tenna	\$	Substitut	ed	Absolute	
Frequency (MHz)	Reading (dBµV)	table Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)
				Middle	Channel				
			1	.4 MHz 1	Bandwidth	_			
1745.00	82.43	273	1.8	Н	9.9	1.30	8.90	17.50	30
1745.00	88.86	90	2.5	V	15.7	1.30	8.90	23.30	30
				3 MHz B	andwidth				
1745.00	82.86	109	1.4	Н	10.3	1.30	8.90	17.90	30
1745.00	88.94	31	1.5	V	15.8	1.30	8.90	23.40	30
				5 MHz B	andwidth				
1745.00	82.65	327	2.4	Н	10.1	1.30	8.90	17.70	30
1745.00	88.79	230	2.2	V	15.6	1.30	8.90	23.20	30
			1	0 MHz I	Bandwidth	_			
1745.00	82.66	173	2.2	Н	10.1	1.30	8.90	17.70	30
1745.00	89.09	23	1.6	V	15.9	1.30	8.90	23.50	30
			1	5 MHz I	Bandwidth				
1745.00	82.84	189	1.7	Н	10.3	1.30	8.90	17.90	30
1745.00	88.73	249	1.7	V	15.6	1.30	8.90	23.20	30
	20 MHz Bandwidth								
1745.00	83.04	43	2.1	Н	10.5	1.30	8.90	18.10	30
1745.00	89.44	286	1.1	V	16.3	1.30	8.90	23.90	30

16QAM:

	Dagaiyay	Turn	Rx An	tenna		Substitut	ed	Absolute	
Frequency (MHz)	Receiver Reading (dBµV)	table Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)
				Middle	Channel				
			. 1	.4 MHz	Bandwidth				
1745.00	82.55	147	2.2	Н	10.0	1.30	8.90	17.60	30
1745.00	88.72	1	1.4	V	15.6	1.30	8.90	23.20	30
				3 MHz B	andwidth				
1745.00	82.37	117	2.0	Н	9.8	1.30	8.90	17.40	30
1745.00	87.54	305	1.3	V	14.4	1.30	8.90	22.00	30
				5 MHz B	andwidth				
1745.00	82.32	123	1.2	Н	9.8	1.30	8.90	17.40	30
1745.00	88.61	121	2.2	V	15.4	1.30	8.90	23.00	30
				10 MHz I	Bandwidth				
1745.00	82.27	102	2.4	Н	9.7	1.30	8.90	17.30	30
1745.00	88.46	267	2.5	V	15.3	1.30	8.90	22.90	30
	15 MHz Bandwidth								
1745.00	82.62	179	2.5	Н	10.1	1.30	8.90	17.70	30
1745.00	88.67	151	1.8	V	15.5	1.30	8.90	23.10	30
	20 MHz Bandwidth								
1745.00	82.98	148	2.4	Н	10.4	1.30	8.90	18.00	30
1745.00	89.26	290	1.2	V	16.1	1.30	8.90	23.70	30

Note:

All above data were tested with no amplifier

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH


Applicable Standard

FCC 47 §2.1049, §22.917, §22.905, §24.238 and §27.53.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 1% to 5% of the anticipated emission bandwidth and the 26 dB & 99% bandwidth was recorded.



Test Data

Environmental Conditions

Temperature:	24~25 °C
Relative Humidity:	50~52 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Kiki Kong from 2018-11-06 to 2018-11-10.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	836.6	248.40	317.31

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	836.6	4.160	4.679
HSUPA (BPSK)	836.6	4.160	4.696
HSDPA (16QAM)	836.6	4.160	4.679


PCS Band (Part 24E)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	1880.0	245.19	315.71

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1880.0	4.160	4.696
HSUPA (BPSK)	1880.0	4.160	4.696
HSDPA (16QAM)	1880.0	4.160	4.712


Report No.: RSZ181029004-00D

Cellular Band (Part 22H) 26 dB Emissions &99% Occupied Bandwidth for GSM (GMSK) Mode




Date: 10.NOV.2018 19:18:03

26 dB Emissions &99% Occupied Bandwidth for RMC (BPSK) Mode




Date: 6.NOV.2018 22:10:00

26 dB Emissions &99% Occupied Bandwidth for HSUPA (BPSK) Mode




Date: 6.NOV.2018 22:33:14

26 dB Emissions &99% Occupied Bandwidth for HSDPA (16QAM) Mode




Date: 6.NOV.2018 22:21:23

PCS Band (Part 24E)
26 dB Emissions &99% Occupied Bandwidth for GSM (GMSK) Mode




Date: 10.NOV.2018 19:07:24

26 dB Emissions &99% Occupied Bandwidth for RMC (BPSK) Mode




Date: 6.NOV.2018 21:50:34

26 dB Emissions &99% Occupied Bandwidth for HSUPA (BPSK) Mode



Date: 6.NOV.2018 22:35:06

26 dB Emissions &99% Occupied Bandwidth for HSDPA (16QAM) Mode




Date: 6.NOV.2018 22:16:29

LTE Band 2: (Middle Channel)


Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.109	1.348
1.4	16QAM	1.114	1.337
2.0	QPSK	2.712	3.019
3.0	16QAM	2.700	3.048
5.0	QPSK	4.560	5.449
5.0	16QAM	4.540	5.326
10.0	QPSK	8.960	9.857
10.0	16QAM	8.960	9.867
15.0	QPSK	13.500	15.048
15.0	16QAM	13.500	14.904
20.0	QPSK	18.000	19.685
20.0	16QAM	18.000	19.817

QPSK (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:20:03

16-QAM (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:23:41

QPSK (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:25:53

16-QAM (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:27:22

QPSK (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:29:50

16-QAM (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:31:24

QPSK (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:33:05

16-QAM (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:34:39

QPSK (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:36:29

16-QAM (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:37:58

QPSK (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel



Date: 6.NOV.2018 23:40:38

16-QAM (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:42:29

LTE Band 4: (Middle Channel)


Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1 4	QPSK	1.113	1.396
1.4	16QAM	1.117	1.324
2.0	QPSK	2.702	3.019
3.0	16QAM	2.702	3.019
5.0	QPSK	4.540	5.511
5.0	16QAM	4.580	5.369
10.0	QPSK	9.000	9.816
10.0	16QAM	9.000	9.808
15.0	QPSK	13.500	15.037
15.0	16QAM	13.440	14.871
20.0	QPSK	17.920	19.492
20.0	16QAM	18.000	19.808

QPSK (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 23:49:40

16-QAM (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 23:47:50

QPSK (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 23:51:05

16-QAM (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 23:52:05

QPSK (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:49:40

16-QAM (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:47:30

QPSK (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:52:18

16-QAM (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:50:57

QPSK (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:55:47

16-QAM (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:53:34

QPSK (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel



Date: 6.NOV.2018 23:57:49

16-QAM (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 6.NOV.2018 23:56:52

LTE Band 5: (Middle Channel)


Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.108	1.346
1.4	16QAM	1.117	1.297
2.0	QPSK	2.702	3.038
3.0	16QAM	2.692	3.058
5.0	QPSK	4.551	5.337
5.0	16QAM	4.535	5.304
10.0	QPSK	8.974	9.936
10.0	16QAM	8.974	9.904

QPSK (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:13:03

16-QAM (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:14:47

QPSK (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:08:07

16-QAM (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:09:09

QPSK (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:03:49

16-QAM (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:06:35

QPSK (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel



Date: 7.NOV.2018 19:56:47

16-QAM (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 19:58:29

LTE Band 7: (Middle Channel)


Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
5.0	QPSK	4.535	5.513
	16QAM	4.567	5.529
10.0	QPSK	8.974	9.744
	16QAM	8.942	9.808
15.0	QPSK	13.462	15.048
	16QAM	13.462	14.904
20.0	QPSK	17.949	19.551
	16QAM	17.949	19.487

QPSK (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:22:12

16-QAM (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:19:10

QPSK (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:24:06

16-QAM (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:25:51

QPSK (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:28:31

16-QAM (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:30:17

QPSK (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel



Date: 7.NOV.2018 20:32:54

16-QAM (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 20:36:00

LTE Band 66: (Middle Channel)


Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.113	1.427
	16QAM	1.117	1.373
3.0	QPSK	2.702	3.038
	16QAM	2.702	3.010
5.0	QPSK	4.551	5.369
	16QAM	4.520	5.321
10.0	QPSK	8.974	9.872
	16QAM	8.974	9.808
15.0	QPSK	13.462	15.064
	16QAM	13.462	14.872
20.0	QPSK	17.885	19.551
	16QAM	17.949	19.487

QPSK (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 21:25:32

16-QAM (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 21:30:13

QPSK (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 21:23:11

16-QAM (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 21:21:47

QPSK (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 21:18:27

16-QAM (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 21:20:29

QPSK (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 21:15:26

16-QAM (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 21:16:30

QPSK (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 21:14:11

16-QAM (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 7.NOV.2018 21:12:50

QPSK (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel



Date: 7.NOV.2018 21:10:05

16-QAM (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel



Date: 7.NOV.2018 21:11:33

FCC §2.1051, §22.917(a) & §24.238(a); §27.53 (h) (m) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a) and §27.53(h) (m).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Data

Environmental Conditions

Temperature:	24~25 °C
Relative Humidity:	50~52 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Kiki Kong from 2018-11-06 to 2018-11-12.

Test result: Compliance.


EUT operation mode: transmitting

Please refer to the following plots.

Report No.: RSZ181029004-00D


Cellular Band (Part 22H)

30 MHz – 1 GHz (GSM Mode)




Date: 10.NOV.2018 19:14:50

1 GHz – 10 GHz (GSM Mode)




Date: 10.NOV.2018 19:13:06

30 MHz – 1 GHz (WCDMA Mode)



Date: 6.NOV.2018 22:03:15


1 GHz – 10 GHz (WCDMA Mode)



Date: 6.NOV.2018 22:04:13


PCS Band (Part 24E)

30 MHz – 1 GHz (GSM Mode)




Date: 10.NOV.2018 19:08:40

1 GHz – 2 GHz (GSM Mode)




Date: 10.NOV.2018 19:09:47

2 GHz - 20 GHz (GSM Mode)




Date: 10.NOV.2018 19:10:46

30 MHz – 1 GHz (WCDMA Mode)




Date: 6.NOV.2018 22:01:47

1 GHz – 2 GHz (WCDMA Mode)



Date: 6.NOV.2018 21:57:17


2 GHz - 20 GHz (WCDMA Mode)



Date: 6.NOV.2018 21:59:59

LTE Band 2:

30 MHz - 1 GHz (1.4 MHz, Middle Channel)




Date: 12.NOV.2018 19:36:59

1 GHz – 2 GHz (1.4 MHz, Middle Channel)




Date: 12.NOV.2018 19:23:05

2 GHz - 20 GHz (1.4 MHz, Middle Channel)




Date: 12.NOV.2018 19:35:38

30 MHz - 1 GHz (3.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:37:33

1 GHz - 2 GHz (3.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:22:13

2 GHz - 20 GHz (3.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:35:24

30 MHz - 1 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:37:50

1 GHz - 2 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:21:18

2 GHz - 20 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:35:06

30 MHz - 1 GHz (10.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:38:05

1 GHz – 2 GHz (10.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:27:06

2 GHz - 20 GHz (10.0 MHz, Middle Channel)



Date: 12.NOV.2018 19:34:44

30 MHz - 1 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:39:55

1 GHz – 2 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:28:41

2 GHz - 20 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:34:28

30 MHz - 1 GHz (20.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:40:18

1 GHz – 2 GHz (20.0 MHz, Middle Channel)



Date: 12.NOV.2018 19:29:33

2 GHz - 20 GHz (20.0 MHz, Middle Channel)




Date: 12.NOV.2018 19:33:52

Report No.: RSZ181029004-00D


LTE Band 4:

30 MHz - 1 GHz (1.4 MHz, Middle Channel)




Date: 12.NOV.2018 20:57:48

1 GHz – 2 GHz (1.4 MHz, Middle Channel)




Date: 12.NOV.2018 20:51:33

2 GHz - 20 GHz (1.4 MHz, Middle Channel)




Date: 12.NOV.2018 20:52:48

30 MHz - 1 GHz (3.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:57:17

1 GHz – 2 GHz (3.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:50:38

2 GHz - 20 GHz (3.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:54:15

30 MHz - 1 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:57:06

1 GHz - 2 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:49:29

2 GHz - 20 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:54:36

30 MHz - 1 GHz (10.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:56:51

1 GHz – 2 GHz (10.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:48:01

2 GHz - 20 GHz (10.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:55:00

30 MHz - 1 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:56:28

1 GHz – 2 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:47:08

2 GHz - 20 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:55:19

30 MHz - 1 GHz (20.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:56:05

1 GHz - 2 GHz (20.0 MHz, Middle Channel)



Date: 12.NOV.2018 20:45:38


2 GHz - 20 GHz (20.0 MHz, Middle Channel)



Date: 12.NOV.2018 20:55:36


LTE Band 5:

30 MHz - 1 GHz (1.4 MHz, Middle Channel)




Date: 12.NOV.2018 20:59:49

1 GHz – 10 GHz (1.4 MHz, Middle Channel)




Date: 12.NOV.2018 21:01:06

30 MHz - 1 GHz (3.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:59:30

1 GHz – 10 GHz (3.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:01:25

30 MHz - 1 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 20:58:35

1 GHz – 10 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:01:47

30 MHz - 1 GHz (10.0 MHz, Middle Channel)



Date: 12.NOV.2018 20:59:04


1 GHz – 10 GHz (10.0 MHz, Middle Channel)



Date: 12.NOV.2018 21:02:05


LTE Band 7:

30 MHz - 1 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:11:48

1 GHz – 3 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:06:09

3 GHz – 26 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:10:15

30 MHz - 1 GHz (10.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:11:10

1 GHz - 3 GHz (10.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:04:47

3 GHz - 26 GHz (10.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:09:59

30 MHz - 1 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:12:09

1 GHz - 3 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:06:35

3 GHz - 26 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:09:41

30 MHz - 1 GHz (20.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:12:23

1 GHz - 3 GHz (20.0 MHz, Middle Channel)



Date: 12.NOV.2018 21:06:54


3 GHz – 26 GHz (20.0 MHz, Middle Channel)



Date: 12.NOV.2018 21:09:20


LTE Band 66:

30 MHz - 1 GHz (1.4 MHz, Middle Channel)




Date: 12.NOV.2018 21:51:56

1 GHz – 2 GHz (1.4 MHz, Middle Channel)




Date: 12.NOV.2018 21:45:30

2 GHz - 20 GHz (1.4 MHz, Middle Channel)




Date: 12.NOV.2018 21:51:13

30 MHz - 1 GHz (3.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:52:18

1 GHz - 2 GHz (3.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:47:08

2 GHz - 20 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:50:56

30 MHz - 1 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:52:36

1 GHz – 2 GHz (5.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:47:47

2 GHz - 20 GHz (20.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:50:42

30 MHz - 1 GHz (10.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:52:50

1 GHz – 2 GHz (10.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:48:26

2 GHz - 20 GHz (10.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:50:25

30 MHz - 1 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:53:02

1 GHz – 2 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:48:55

2 GHz - 20 GHz (15.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:50:11

30 MHz - 1 GHz (20.0 MHz, Middle Channel)




Date: 12.NOV.2018 21:53:11

1 GHz - 2 GHz (20.0 MHz, Middle Channel)



Date: 12.NOV.2018 21:49:21

2 GHz – 20 GHz (20.0 MHz, Middle Channel)



Date: 12.NOV.2018 21:49:51

FCC § 2.1053; § 22.917 (a); § 24.238 (a); §27.53 (h)(m) SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917(a) and § 24.238(a) and § 27.53(h)(m)

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Test Data

Environmental Conditions

Temperature:	24~25 ℃				
Relative Humidity:	50~52 %				
ATM Pressure:	100.0~101.0 kPa				

The testing was performed by Kiki Kong from 2018-11-08 to 2018-11-13.

EUT operation mode: Transmitting

Pre-scan with Low, Middle and High channel, the worst case as below:

30 MHz ~ **10 GHz**:

Cellular Band (Part 22H)

Receiver		Townstable	Rx Antenna		Substituted			A la salasta	FCC Part 22H	
Frequency (MHz)	Receiver Reading (dBµV)	Turntable Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
GSM Mode, middle channel										
436.25	32.15	253	1.7	Н	-64.9	0.44	0	-65.34	-13	52.34
436.25	31.24	232	1.7	V	-65.8	0.44	0	-66.24	-13	53.24
1673.20	58.31	246	2.0	Н	-48.8	1.30	8.90	-41.20	-13	28.20
1673.20	67.66	234	1.0	V	-38.8	1.30	8.90	-31.20	-13	18.20
2509.80	49.71	285	2.5	Н	-53.8	2.60	10.20	-46.20	-13	33.20
2509.80	48.04	189	1.4	V	-54.9	2.60	10.20	-47.30	-13	34.30
3346.40	47.23	282	1.4	Н	-53.1	1.50	11.70	-42.90	-13	29.90
3346.40	50.52	136	1.1	V	-49.9	1.50	11.70	-39.70	-13	26.70
WCDMA Mode, Middle channel										
436.25	33.01	69	2.4	Н	-64.0	0.44	0	-64.44	-13	51.44
436.25	32.12	120	2.5	V	-64.9	0.44	0	-65.34	-13	52.34
1673.20	47.65	179	1.4	Н	-59.4	1.30	8.90	-51.80	-13	38.80
1673.20	48.38	15	1.8	V	-58.1	1.30	8.90	-50.50	-13	37.50
2509.80	46.1	11	2.1	Н	-57.4	2.60	10.20	-49.80	-13	36.80
2509.80	47.59	340	1.8	V	-55.3	2.60	10.20	-47.70	-13	34.70
3346.40	47.71	224	1.2	Н	-52.6	1.50	11.70	-42.40	-13	29.40
3346.40	50.64	84	1.9	V	-49.7	1.50	11.70	-39.50	-13	26.50

30 MHz ~ 20 GHz:

PCS Band (Part 24E)

	Dogoison	Receiver Turntable Reading Angle (dBµV) Degree	Rx Antenna		Substituted			Absolute	FCC Part 24E	
Frequency (MHz)	Reading		Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
GSM Mode, middle channel										
436.25	32.98	308	2.0	Н	-64.0	0.44	0	-64.44	-13	51.44
436.25	31.75	71	1.2	V	-65.3	0.44	0	-65.74	-13	52.74
3760.00	49.85	31	2.3	Н	-51.4	1.50	11.80	-41.10	-13	28.10
3760.00	52.28	240	2.1	V	-48.5	1.50	11.80	-38.20	-13	25.20
WCDMA Mode Band II, Middle channel										
436.25	32.47	86	1.0	Н	-64.5	0.44	0	-64.94	-13	51.94
436.25	31.24	299	1.9	V	-65.8	0.44	0	-66.24	-13	53.24
3760.00	45.56	119	1.6	Н	-54.8	1.50	11.80	-44.50	-13	31.50
3760.00	44.85	312	1.2	V	-56.3	1.50	11.80	-46.00	-13	33.00

LTE Band: (Pre-scan with all the bandwidth, and worse case as below)

Frequency	Receiver	Turntable	Rx An	x Antenna Substituted			Absolute			
(MHz)	Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
				Band 2	QPSK 20	MHz				
Test frequency range:30 MHz ~ 20 GHz										
436.25	33.01	119	1.7	Н	-64.0	0.44	0	-64.44	-13	51.44
436.25	32.14	243	1.0	V	-64.9	0.44	0	-65.34	-13	52.34
3760.00	44.53	229	1.2	Н	-56.7	1.50	11.80	-46.40	-13	33.40
3760.00	45.24	342	2.4	V	-55.5	1.50	11.80	-45.20	-13	32.20
	Band 4 QPSK 20MHz									
Test frequency range:30 MHz ~ 20 GHz										
436.25	32.75	140	2.2	Н	-64.3	0.44	0	-64.74	-13	51.74
436.25	31.95	101	2.2	V	-65.1	0.44	0	-65.54	-13	52.54
3465.00	45.05	239	1.7	Н	-55.3	1.50	12.00	-44.80	-13	31.80
3465.00	45.19	158	2.4	V	-56.0	1.50	12.00	-45.50	-13	32.50
Band 5 QPSK 10MHz										
Test frequency range:30 MHz ~ 10 GHz										
436.25	32.47	196	1.3	Н	-64.5	0.44	0	-64.94	-13	51.94
436.25	31.58	341	1.7	V	-65.4	0.44	0	-65.84	-13	52.84
1673.00	44.83	114	2.5	Н	-62.2	1.30	8.90	-54.60	-13	41.60
1673.00	43.92	264	1.9	V	-62.6	1.30	8.90	-55.00	-13	42.00
2509.50	47.21	61	1.1	Н	-56.3	2.60	10.20	-48.70	-13	35.70
2509.50	46.8	51	1.4	V	-56.1	2.60	10.20	-48.50	-13	35.50
3346.00	44.15	161	1.3	Н	-56.2	1.50	11.70	-46.00	-13	33.00
3346.00	46.91	158	2.5	V	-53.5	1.50	11.70	-43.30	-13	30.30
					QPSK 20					
	.	•	Test fr	<u> </u>	range:30 N			.	1	
436.25	32.86	304	1.6	Н	-64.1	0.44	0	-64.54	-25	39.54
436.25	31.17	135	1.5	V	-65.8	0.44	0	-66.24	-25	41.24
5070.00	48.9	330	1.9	Н	-49.0	1.60	12.10	-38.50	-25	13.5
5070.00	54.89	215	1.0	V	-43.0	1.60	12.10	-32.50	-25	7.5
Band 66 QPSK 20MHz										
Test frequency range: 30 MHz ~ 20GHz										
436.25	32.01	88	1.1	Н	-65.0	0.44	0	-65.44	-13	52.44
436.25	31.24	230	2.4	V	-65.8	0.44	0	-66.24	-13	53.24
3490.00	47.91	326	1.0	Н	-52.5	1.50	12.00	-42.00	-13	29.00
3490.00	48.35	101	1.7	V	-52.8	1.50	12.00	-42.30	-13	29.30

Note:

¹⁾ Absolute Level = Substituted Level - Cable loss + Antenna Gain

²⁾ Margin = Limit- Absolute Level

FCC § 22.917 (a); § 24.238 (a); §27.53 (h)(m) - BAND EDGES

Applicable Standard

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to \$24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) \, dB$.

According to FCC §27.53 (h)(m), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency



Test Data

Environmental Conditions


Temperature:	24~25 ℃				
Relative Humidity:	50~52 %				
ATM Pressure:	100.0~101.0 kPa				

The testing was performed by Kiki Kong from 2018-11-06 to 2018-11-12.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to the following plots.

Cellular Band, Left Band Edge for GSM (GMSK) Mode




Date: 10.NOV.2018 19:22:45

Cellular Band, Right Band Edge for GSM (GMSK) Mode




Date: 10.NOV.2018 19:23:41

Cellular Band, Left Band Edge for WCDMA (BPSK) Mode




Date: 6.NOV.2018 22:06:22

Cellular Band, Right Band Edge for WCDMA (BPSK) Mode




Date: 6.NOV.2018 22:07:47

Cellular Band, Left Band Edge for HSDPA (16QAM) Mode




Date: 6.NOV.2018 22:22:34

Cellular Band, Right Band Edge for HSDPA (16QAM) Mode




Date: 6.NOV.2018 22:23:44

Cellular Band, Left Band Edge for HSUPA (BPSK) Mode




Date: 6.NOV.2018 22:31:18

Cellular Band, Right Band Edge for HSUPA (BPSK) Mode




Date: 6.NOV.2018 22:30:14

PCS Band, Left Band Edge for GSM (GMSK) Mode




Date: 10.NOV.2018 19:04:08

PCS Band, Right Band Edge for GSM (GMSK) Mode




Date: 10.NOV.2018 19:04:51

PCS Band, Left Band Edge for WCDMA (BPSK) Mode




Date: 6.NOV.2018 21:53:08

PCS Band, Right Band Edge for WCDMA (BPSK) Mode




Date: 6.NOV.2018 21:54:20

PCS Band, Left Band Edge for HSDPA (16QAM) Mode




Date: 6.NOV.2018 22:24:53

PCS Band, Right Band Edge for HSDPA (16QAM) Mode




Date: 6.NOV.2018 22:25:48

PCS Band, Left Band Edge for HSUPA (BPSK) Mode



Date: 6.NOV.2018 22:29:23


PCS Band, Right Band Edge for HSUPA (BPSK) Mode



Date: 6.NOV.2018 22:28:33


Band 2:






Date: 7.NOV.2018 21:40:21

QPSK (1.4 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 21:41:35

16-QAM (1.4 MHz, FULL RB) - Left Band Edge



Date: 7.NOV.2018 21:37:47


16-QAM (1.4 MHz, FULL RB) - Right Band Edge



Date: 7.NOV.2018 21:42:30


Report No.: RSZ181029004-00D

QPSK (3.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 21:46:24

QPSK (3.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 21:44:16

16-QAM (3.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 21:45:42

16-QAM (3.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 21:44:58

QPSK (5.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 21:48:28

QPSK (5.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 21:49:39

16-QAM (5.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 21:47:29

16-QAM (5.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 21:50:12

QPSK (10.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 21:53:17

QPSK (10.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 21:52:25

16-QAM (10.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 21:54:01

16-QAM (10.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 21:51:34

QPSK (15.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 21:55:59

QPSK (15.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 21:57:42

16-QAM (15.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 21:55:16

16-QAM (15.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 21:56:56

QPSK (20.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:01:11

QPSK (20.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:00:07

16-QAM (20.0 MHz, FULL RB) - Left Band Edge



Date: 7.NOV.2018 22:02:02


16-QAM (20.0 MHz, FULL RB) - Right Band Edge



Date: 7.NOV.2018 21:59:13


Band 4:






Date: 7.NOV.2018 22:22:29

QPSK (1.4 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:23:15

16-QAM (1.4 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:21:38

16-QAM (1.4 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:23:49

QPSK (3.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:27:50

QPSK (3.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:24:50

16-QAM (3.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:27:08

16-QAM (3.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:25:41

QPSK (5.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:05:40

QPSK (5.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:09:38

16-QAM (5.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:04:51

16-QAM (5.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:10:18

QPSK (10.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:13:16

QPSK (10.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:12:17

16-QAM (10.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:13:50

16-QAM (10.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:11:28

QPSK (15.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:15:48

QPSK (15.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:17:16

16-QAM (15.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:15:12

16-QAM (15.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:16:43

QPSK (20.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:19:56

QPSK (20.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:18:49

16-QAM (20.0 MHz, FULL RB) - Left Band Edge



Date: 7.NOV.2018 22:20:18


16-QAM (20.0 MHz, FULL RB) - Right Band Edge



Date: 7.NOV.2018 22:18:12


Band 5:






Date: 7.NOV.2018 22:31:17

QPSK (1.4 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:32:28

16-QAM (1.4 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:30:08

16-QAM (1.4 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:32:53

QPSK (3.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:35:55

QPSK (3.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:34:01

16-QAM (3.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:35:23

16-QAM (3.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:34:45

QPSK (5.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:37:31

QPSK (5.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:38:15

16-QAM (5.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:36:55

16-QAM (5.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:38:46

QPSK (10.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 22:41:02

QPSK (10.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 22:40:24

16-QAM (10.0 MHz, FULL RB) - Left Band Edge



Date: 7.NOV.2018 22:41:30


16-QAM (10.0 MHz, FULL RB) - Right Band Edge



Date: 7.NOV.2018 22:39:49


Band 7:






Date: 12.NOV.2018 18:44:39

QPSK (5.0 MHz, FULL RB) - Right Band Edge




Date: 12.NOV.2018 18:48:28

16-QAM (5.0 MHz, FULL RB) - Left Band Edge




Date: 12.NOV.2018 18:46:22

16-QAM (5.0 MHz, FULL RB) - Right Band Edge




Date: 12.NOV.2018 18:49:25

QPSK (10.0 MHz, FULL RB) - Left Band Edge




Date: 12.NOV.2018 18:53:59

QPSK (10.0 MHz, FULL RB) - Right Band Edge




Date: 12.NOV.2018 18:56:28

16-QAM (10.0 MHz, FULL RB) - Left Band Edge




Date: 12.NOV.2018 18:55:03

16-QAM (10.0 MHz, FULL RB) - Right Band Edge




Date: 12.NOV.2018 18:55:57

QPSK (15.0 MHz, FULL RB) - Left Band Edge




Date: 12.NOV.2018 19:00:09

QPSK (15.0 MHz, FULL RB) - Right Band Edge




Date: 12.NOV.2018 18:58:34

16-QAM (15.0 MHz, FULL RB) - Left Band Edge




Date: 12.NOV.2018 18:59:44

16-QAM (15.0 MHz, FULL RB) - Right Band Edge




Date: 12.NOV.2018 18:58:57

QPSK (20.0 MHz, FULL RB) - Left Band Edge




Date: 12.NOV.2018 19:01:09

QPSK (20.0 MHz, FULL RB) - Right Band Edge




Date: 12.NOV.2018 19:04:09

16-QAM (20.0 MHz, FULL RB) - Left Band Edge



Date: 12.NOV.2018 19:02:00


16-QAM (20.0 MHz, FULL RB) - Right Band Edge



Date: 12.NOV.2018 19:03:04


Band 66:

QPSK (1.4 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 23:21:51

QPSK (1.4 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 23:24:48

16-QAM (1.4 MHz, FULL RB) - Left Band Edge



Date: 7.NOV.2018 23:22:55


16-QAM (1.4 MHz, FULL RB) - Right Band Edge



Date: 7.NOV.2018 23:24:19


Report No.: RSZ181029004-00D

QPSK (3.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 23:28:05

QPSK (3.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 23:26:18

16-QAM (3.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 23:27:37

16-QAM (3.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 23:26:56

QPSK (5.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 23:29:35

QPSK (5.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 23:30:26

16-QAM (5.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 23:29:00

16-QAM (5.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 23:30:51

QPSK (10.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 23:32:48

QPSK (10.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 23:32:15

16-QAM (10.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 23:33:07

16-QAM (10.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 23:31:45

QPSK (15.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 23:42:17

QPSK (15.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 23:44:09

16-QAM (15.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 23:42:45

16-QAM (15.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 23:43:45

QPSK (20.0 MHz, FULL RB) - Left Band Edge




Date: 7.NOV.2018 23:41:27

QPSK (20.0 MHz, FULL RB) - Right Band Edge




Date: 7.NOV.2018 23:40:02

16-QAM (20.0 MHz, FULL RB) - Left Band Edge



Date: 7.NOV.2018 23:41:04

16-QAM (20.0 MHz, FULL RB) - Right Band Edge



Date: 7.NOV.2018 23:40:30

FCC § 2.1055; § 22.355; § 24.235; §27.54 - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055, §22.355, §24.235 and & §27.54.

According to FCC §2.1055, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance	for Transm	itters in th	e Public	Mobile Services
---------------------	------------	--------------	----------	-----------------

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile > 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2018-11-17.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

Cellular Band (Part 22H)

GSM Mode

	Middle Channel, f ₀ =836.6MHz						
Temperature (°C)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)			
-30		-15	-0.017930	2.5			
-20		-12	-0.014344	2.5			
-10		-11	-0.013148	2.5			
0		-8	-0.009563	2.5			
10	3.8	-6	-0.007172	2.5			
20		-7	-0.008367	2.5			
30		-4	-0.004781	2.5			
40		-2	-0.002391	2.5			
50		1	0.001195	2.5			
20	V min.= 3.6	4	0.004781	2.5			
20	V max.= 4.35	7	0.008367	2.5			

WCDMA Mode

	Middle Channel, f _o =836.6MHz						
Temperature (°C)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)			
-30		1	0.001195	2.5			
-20		-3	-0.003586	2.5			
-10		-4	-0.004781	2.5			
0		-2	-0.002391	2.5			
10	3.8	-5	-0.005977	2.5			
20		-1	-0.001195	2.5			
30		0	0.000000	2.5			
40		2	0.002391	2.5			
50		4	0.004781	2.5			
20	V min.= 3.6	3	0.003586	2.5			
20	V max.= 4.35	-6	-0.007172	2.5			

PCS Band (Part 24E)

Report No.: RSZ181029004-00D

GSM Mode

	Middle Channel, f _o =1880.0 MHz						
Temperature (°C)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result			
-30		-9	-0.004787	pass			
-20		-6	-0.003191	pass			
-10		-8	-0.004255	pass			
0		-7	-0.003723	pass			
10	3.8	-5	-0.002660	pass			
20		-3	-0.001596	pass			
30		-1	-0.000532	pass			
40		2	0.001064	pass			
50		3	0.001596	pass			
20	V min.= 3.6	5	0.002660	pass			
	V max.= 4.35	8	0.004255	pass			

WCDMA Mode

	Middle Channel, f _o =1880.0 MHz						
Temperature (°C)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result			
-30		3	0.001596	pass			
-20		2	0.001064	pass			
-10	3.8	-1	-0.000532	pass			
0		-5	-0.002660	pass			
10		-4	-0.002128	pass			
20		-2	-0.001064	pass			
30		-1	-0.000532	pass			
40		-8	-0.004255	pass			
50		-7	-0.003723	pass			
20	V min.= 3.6	1	0.000532	pass			
	V max.= 4.35	-3	-0.001596	pass			

LTE: QPSK:

Band 2:

10.0 MHz Middle Channel						
Temperature (°C)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result		
-30		-4	-0.0021	pass		
-20		-2	-0.0011	pass		
-10		-3	-0.0016	pass		
0		-2	-0.0011	pass		
10	3.8	-3	-0.0016	pass		
20		-2	-0.0011	pass		
30		-1	-0.0005	pass		
40		-2	-0.0011	pass		
50		-2	-0.0011	pass		
20	V min.= 3.6	-3	-0.0016	pass		
20	V max.= 4.35	-1	-0.0005	pass		

Band 4(5MHz Band width):

Temperature (°C)	Power Supplied (V _{DC})	F _L (MHz)	F _H (MHz)	F _L Limit (MHz)	F _H Limit (MHz)
-30		1710.1125	1754.8717	1710.0000	1755.0000
-20		1710.0647	1754.8564	1710.0000	1755.0000
-10		1710.1127	1754.8714	1710.0000	1755.0000
0		1710.0436	1754.8032	1710.0000	1755.0000
10	3.8	1710.0432	1754.7580	1710.0000	1755.0000
20		1710.1128	1754.8728	1710.0000	1755.0000
30		1710.0790	1754.8758	1710.0000	1755.0000
40		1710.0677	1754.8315	1710.0000	1755.0000
50		1710.1125	1754.8718	1710.0000	1755.0000
20	V min.= 3.6	1710.0896	1754.8836	1710.0000	1755.0000
20	V max.= 4.35	1710.1025	1754.8485	1710.0000	1755.0000

Band 5:

	10.0 MHz Middle Channel, f _o = 836.5MHz						
Temperature (°C)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)			
-30		-6	-0.0072	2.5			
-20		-4	-0.0048	2.5			
-10	3.8	-1	-0.0012	2.5			
0		-4	-0.0048	2.5			
10		-3	-0.0036	2.5			
20		-3	-0.0036	2.5			
30		-3	-0.0036	2.5			
40		-3	-0.0036	2.5			
50		-4	-0.0048	2.5			
20	V min.= 3.6	-1	-0.0012	2.5			
20	V max.= 4.35	-3	-0.0036	2.5			

Band 7:

	5 MHz Bandwidth						
Temperature (°C)	Power Supplied (V _{DC})	F _L (MHz)	F _H (MHz)	F _L Limit (MHz)	F _H Limit (MHz)		
-30		2500.128335	2569.85568	2500	2570		
-20		2500.128337	2569.855671	2500	2570		
-10		2500.128331	2569.855678	2500	2570		
0		2500.128337	2569.855676	2500	2570		
10	3.8	2500.12833	2569.85567	2500	2570		
20		2500.128325	2569.855665	2500	2570		
30		2500.128323	2569.855659	2500	2570		
40		2500.128319	2569.855658	2500	2570		
50		2500.128314	2569.85565	2500	2570		
20	V min.= 3.6	2500.128335	2569.85568	2500	2570		
20	V max.= 4.35	2500.128337	2569.855671	2500	2570		

Band 66:

5 MHz Bandwidth						
Temperature (°C)	Power Supplied (V _{DC})	F _L (MHz)	F _H (MHz)	F _L Limit (MHz)	F _H Limit (MHz)	
-30		1710.128549	1779.855082	1710	1780	
-20		1710.128541	1779.855081	1710	1780	
-10		1710.128543	1779.855084	1710	1780	
0		1710.128550	1779.855086	1710	1780	
10	3.8	1710.128540	1779.855080	1710	1780	
20		1710.128538	1779.855074	1710	1780	
30		1710.128534	1779.855073	1710	1780	
40		1710.128533	1779.855071	1710	1780	
50		1710.128525	1779.855064	1710	1780	
20	V min.= 3.6	1710.128549	1779.855082	1710	1780	
20	V max.= 4.35	1710.128541	1779.855081	1710	1780	

16QAM:

Band 2:

10.0 MHz Middle Channel					
Temperature (℃)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result	
-30		-5	-0.0027	pass	
-20	3.8	-2	-0.0011	pass	
-10		-3	-0.0016	pass	
0		-6	-0.0032	pass	
10		-3	-0.0016	pass	
20		-2	-0.0011	pass	
30		-2	-0.0011	pass	
40		-2	-0.0011	pass	
50		-1	-0.0005	pass	
20	V min.= 3.6	3	0.003586	pass	
	V max.= 4.35	7	0.008368	pass	

Band 4(5MHz Band width):

Temperature (°C)	Power Supplied (V_{DC})	F _L (MHz)	F _H (MHz)	F _L Limit (MHz)	F _H Limit (MHz)
-30		1710.1125	1754.8717	1710.0000	1755.0000
-20	3.8	1710.0647	1754.8564	1710.0000	1755.0000
-10		1710.1127	1754.8717	1710.0000	1755.0000
0		1710.0438	1754.8032	1710.0000	1755.0000
10		1710.0431	1754.7580	1710.0000	1755.0000
20		1710.1122	1754.8718	1710.0000	1755.0000
30		1710.0790	1754.8758	1710.0000	1755.0000
40		1710.0687	1754.8313	1710.0000	1755.0000
50		1710.1120	1754.8718	1710.0000	1755.0000
20	V min.= 3.6	1710.0295	1754.7905	1710.0000	1755.0000
	V max.= 4.35	1710.0299	1754.7822	1710.0000	1755.0000

Band 5:

10.0 MHz Middle Channel, f _o =836.5MHz					
Temperature (°C)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	
-30		-6	-0.0072	2.5	
-20	3.8	-4	-0.0048	2.5	
-10		-1	-0.0012	2.5	
0		-4	-0.0048	2.5	
10		-3	-0.0036	2.5	
20		-3	-0.0036	2.5	
30		-5	-0.0060	2.5	
40		-3	-0.0036	2.5	
50		-1	-0.0012	2.5	
20	V min.= 3.6	-5	-0.0060	2.5	
	V max.= 4.35	-6	-0.0072	2.5	

Band 7:

5 MHz Bandwidth					
Temperature (°C)	Power Supplied (V _{DC})	F _L (MHz)	F _H (MHz)	F _L Limit (MHz)	F _H Limit (MHz)
-30		2500.128219	2569.855776	2500	2570
-20	3.8	2500.128220	2569.855779	2500	2570
-10		2500.128212	2569.855777	2500	2570
0		2500.128213	2569.855775	2500	2570
10		2500.128210	2569.85577	2500	2570
20		2500.128204	2569.855764	2500	2570
30		2500.128199	2569.855756	2500	2570
40		2500.128195	2569.855749	2500	2570
50		2500.128185	2569.855741	2500	2570
20	V min.= 3.6	2500.128219	2569.855776	2500	2570
	V max.= 4.35	2500.128220	2569.855779	2500	2570

Band 66:

5 MHz Bandwidth					
Temperature (°C)	$\begin{array}{c} \textbf{Power} \\ \textbf{Supplied} \\ \textbf{(V}_{DC)} \end{array}$	F _L (MHz)	F _H (MHz)	F _L Limit (MHz)	F _H Limit (MHz)
-30		1710.128211	1779.855789	1710	1780
-20		1710.128213	1779.855782	1710	1780
-10	3.8	1710.128216	1779.855787	1710	1780
0		1710.128215	1779.855789	1710	1780
10		1710.12821	1779.85578	1710	1780
20		1710.128205	1779.855772	1710	1780
30		1710.128202	1779.855768	1710	1780
40		1710.128195	1779.85576	1710	1780
50		1710.128189	1779.855758	1710	1780
20	V min.= 3.6	1710.128211	1779.855789	1710	1780
	V max.= 4.35	1710.128213	1779.855782	1710	1780

***** END OF REPORT *****