Contact us. info@vivint.com 800.216.5232

Visit us online. vivint.com

47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091 Maximum Permissible Exposure Calculations

For Vivint M/N: CP04

908.4 / 908.42 / 916.0 MHz Z-Wave Transceiver

EUT Device Category = General Population/Uncontrolled Exposure

EUT consists of one Z-Wave radio transmitting at one of three possible frequencies: **908.4MHz**, **908.42MHz**, **916.0MHz**

MPE Summary:

According subpart 1.1307 (b)(1) and 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure								
		Magnetic Field Strength (A/m)	_	Averaging Time (Minutes)				
0.3-1.34	614	1.63	*(100)	30				
1.34-30	824/f	2.19/f	*(180/f2)	30				
30-300	27.5	0.073	0.2	30				
300-1500	/	/	f/1500	30				
1500-100,000	/	/	1.0	30				

f = frequency in MHz; * = Plane-wave equivalent power density



Contact us. info@vivint.com 800.216.5232

Visit us online. vivint.com

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

PG = EIRP

MPE and Limit are calculated as follows:

f (MHz)	Field Strength (dBuV/m [@3m])	EIRP (mW)	Power Density (mW/cm^2)	Limit (mW/cm^2)	Δ
908.40	93.2	0.63	0.000125	0.6056	0.6055
908.42	93.0	0.60	0.000119	0.6056	0.6055
916.00	92.9	0.58	0.000115	0.6107	0.6106

Result: The device meets FCC MPE limit at 20 cm for General Population/Uncontrolled Exposure as specified in 47 CRF §1.1310 and §2.1091.

