Contact us. info@vivint.com 800.216.5232

Visit us online. vivint.com

47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091 Maximum Permissible Exposure Calculations

For Vivint M/N: CP04

## 908.4 / 908.42 / 916.0 MHz Z-Wave Transceiver

EUT Device Category = General Population/Uncontrolled Exposure

EUT consists of one Z-Wave radio transmitting at one of three possible frequencies: **908.4MHz**, **908.42MHz**, **916.0MHz** 

## MPE Summary:

According subpart 1.1307 (b)(1) and 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)			_	Averaging Time (Minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30					
30-300	27.5	0.073	0.2	30					
300-1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

f = frequency in MHz; \* = Plane-wa

\* = Plane-wave equivalent power density





Minnesota 2854 Highway 55, Suite 200 Eagan, MN 55121 USA 651.450.4853



Contact us. Visit us on info@vivint.com vivint.com 800.216.5232

Visit us online.

## **Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

PG = EIRP

MPE and Limit are calculated as follows:

f (	(MHz)	Field Strength (dBuV/m [@3m])	EIRP (mW)	Power Density (mW/cm^2)	Limit (mW/cm^2)	Δ
1	13.56	55.5	0.0001064	0.000000021	1.00846	1.00846

Result: The device meets FCC MPE limit at 20 cm for General Population/Uncontrolled Exposure as specified in 47 CRF §1.1310 and §2.1091.

