







ISO/IEC17025Accredited Lab.

Report No: FCC 1308121 File reference No: 2013-09-05

Applicant: TAE Electronics Co., Ltd.

Product: Tablet PC

Model No: 2330C, M703, M704, M706, M711, M712, M713, MA711, MA712, MA717, MR712,

MR713, MA801, MA802, M812, M813, M901, M902, MA911, MA912, MA9701, MA9702, M1001, MA1001, MA1002, 7260, 7270, 2330, 7250, 5110, 5111, 5112, 5113, 5115, 7260 (A), 7260C, 7260D, 2330D, 2330E, 7250 (A), 7250A, 7250B, 5110C, 5110D (A), 8215, 8216, 8210, 8212, 7710, 7780, 7180, 7810, 5MINI, TS-5244, TS-5254, 3MINI, 3MINI(A), TAB4, 9010, 9011, 9012, 9020, 9021, 9022, 1090, 1080, 1070, 1060, 1050, 1030, A-PAD 113, MIDM-1001, V1003, NAT07,

NAT-07, NAT-08, NAT-09, NAT-10, NAT-6, NAT-06

Trademark: N/A

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4,FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung Manager

Dated: Sep 05, 2013

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District, Shenzhen,CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 1308121 Page 2 of 98

Date: 2013-09-05



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAL-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC- Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-02.

Page 3 of 98

Report No: 1308121 Date: 2013-09-05



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details.	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	6
3.0	Technical Details	9
3.1	Summary of Test Results	9
3.2	Test Standards.	9
4.0	EUT Modification.	9
5.0	Power Line Conducted Emission Test.	10
5.1	Schematics of the Test.	10
5.2	Test Method and Test Procedure.	10
5.3	Configuration of the EUT	10
5.4	EUT Operating Condition.	11
5.5	Conducted Emission Limit.	11
5.6	Test Result.	11
6.0	Radiated Emission test	14
5.1	Test Method and Test Procedure.	14
6.2	Configuration of the EUT	14
6.3	EUT Operation Condition.	14
6.4	Radiated Emission Limit.	15
7.0	6dB Bandwidth Measurement	39
8.0	Maximum Peak Output Power	58
9.0	Power Spectral Density Measurement.	61
10.0	Out of Band Measurement.	79
11.0	Antenna Requirement.	88
12.0	FCC ID Label.	89
13.0	Photo of Test Setup and EUT View.	90

Date: 2013-09-05



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-01

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: TAE Electronics Co., Ltd.

Address: NO.8 Area D Xiongxing Industrial Park, Gaoxing District, Qingyuan, Guangdong Province,

China

Telephone: 0763-3113009 Fax: 0763-3118652

1.3 Description of EUT

Product: Tablet PC

Manufacturer: TAE Electronics Co., Ltd.

Address: NO.8 Area D Xiongxing Industrial Park, Gaoxing District, Qingyuan,

Guangdong Province, China

Brand Name: N/A
Additional Brand Name: N/A
Model Number: 2330C

Additional Model Number: M703, M704, M706, M711, M712, M713, MA711, MA712, MA717, MR712, MR713, MA801, MA802, M812, M813, M901, M902, MA911, MA912, MA9701, MA9702, M1001, MA1001, MA1002, 7260, 7270, 2330, 7250, 5110, 5111, 5112, 5113, 5115, 7260 (A), 7260C, 7260D, 2330D, 2330E, 7250 (A), 7250A, 7250B, 5110C, 5110D (A), 8215, 8216, 8210, 8212, 7710, 7780, 7180, 7810, 5MINI, TS-5244, TS-5254, 3MINI, 3MINI(A), TAB4, 9010, 9011, 9012, 9020, 9021, 9022, 1090, 1080, 1070, 1060, 1050, 1030, A-PAD 113, MIDM-1001, V1003, NAT07, NAT-07, NAT-08, NAT-09, NAT-10, NAT-6, NAT-06

Type of Modulation IEEE 802.11b : DSSS (CCK, QPSK, DBPSK)

IEEE 802.11g/n (HT20/HT40) : OFDM(64QAM, 16QAM, QPSK, BPSK)

Frequency range IEEE 802.11b/g/n (HT20) : 2412-2462MHz;

IEEE 802.11n HT40: 2422MHz-2452MHz

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1308121 Page 5 of 98

TIMEWAY FESTIVO LABS

Channel Spacing IEEE 802.11b/g/n (HT20/HT40) : 5MHz

Air Data Rate IEEE 802.11b : 11, 5.5, 2, 1 Mbps

IEEE 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps

IEEE 802.11n HT20: 150, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6 Mbps IEEE 802.11n HT40: 150, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6 Mbps

Frequency Selection By software

Channel Number IEEE 802.11b/g/n (HT20): 11 Channels

IEEE 802.11n HT40: 7 Channels

Input Voltage: DC3.7V 1600mAh powered by Lion-Battery

Power Supply: Model No.: SK02G-0500150U

Input: AC100-240V~50/60Hz, 0.2A Max; Output: 5V, 1.5A

Antenna: Integral Antenna with maximum gain 2.1dBi

1.4 Submitted Sample: 2 Samples

1.5 Test Duration

Date: 2013-09-05

2013-08-26 to 2013-09-05

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty = 4.7dB

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 98

Report No: 1308121 Date: 2013-09-05



2.0		Test Equip	ments		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2013-08-23	2014-08-22
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2013-08-23	2014-08-22
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2013-08-23	2014-08-22
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2013-08-25	2014-08-24
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2013-08-23	2014-08-22
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2013-08-24	2014-08-23
System Controller	CT	SC100	-		
Printer	EPSON	РНОТО ЕХЗ	CFNH234850		
Computer	IBM	8434	1S8434KCE99BLXL O*	-	-
Loop Antenna	EMCO	6502	00042960	2013-08-23	2014-08-22
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2013-08-23	2014-08-22
3m OATS			N/A	2013-08-22	2014-08-21
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2013-08-24	2014-08-23
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2013-08-24	2014-08-23
Power meter	Anritsu	ML2487A	6K00003613	2013-08-24	2014-08-23
Power sensor	Anritsu	MA2491A	32263	2013-08-24	2014-08-23
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2012-08-21	2013-08-20
LISN	AFJ	LS16C	10010947251	2012-08-21	2013-08-20
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-23	2014-08-22
9*6*6 Anechoic			N/A	2013-08-22	2014-08-21
EMI Test Receiver	RS	ESCS30	100139	2013-08-23	2014-08-22
LISN	AFJ	LS16C	10010947251	2013-08-23	2014-08-22
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-23	2014-08-22

Report No: 1308121 Page 7 of 98

Date: 2013-09-05



2.1 Auxiliary Equipment

Name	Model No.	Serial No.	Manufacturer	Cable	FCC ID/DOC
TF Card			Kingston		
Passive Earphone					

Report No: 1308121 Page 8 of 98

Date: 2013-09-05



3. DESCRIPTION OF TEST MODES

IEEE 802.11b, 802.11g, 802.11n (HT20) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 11Mbps data rate (worst case) was chosen for full testing. IEEE 802.11g mode: 6Mbps data rate (worst case) was chosen for full testing. IEEE 802.11n (HT20) mode: 65Mbps data rate (worst case) were chosen for full testing

IEEE 802.11n HT40

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2422
Mid	2437
High	2452

IEEE 802.11n HT40 mode: 65Mbps data rate (worst case) was chosen for full testing.

The worst-case data rates are determined according to the description above, based on the investigations by measuring the PSD and average power across all the data rates, bandwidths, modulations and spatial stream modes.



3.0 **Technical Details**

3.1 **Summary of test results**

Standard	Test Type	Result	Notes
CCC Part 15, Paragraph 15.107	Conducted Emission Test	PASS	Complies
& 15.207 & RSS-210 Issue 8			
	Spectrum bandwidth of a		Complies
FCC Part 15 Subpart C	Orthogonal Frequency		
Paragraph 15.247(a)(2) Limit &	Division Multiplex System	PASS	
RSS-210 Issue 8	Limit: 6dB		
	bandwidth>500kHz		
FCC Part 15, Paragraph	Maximum peak output		
15.247(b) & RSS-210 Issue 8	power	PASS	Complies
13.247(0) & 1055 210 13546 0	Limit: max. 30dBm		
FCC Part 15, Paragraph	Transmitter Radiated	PASS	Complies
15.109,15.205 & 15.209 &	Emission		
RSS-210 Issue 8	Limit: Table 15.209		
FCC Part 15, Paragraph	Power Spectral Density	PASS	Complies
15.247(e) & RSS-210 Issue 8	Limit: max. 8dBm		
FCC Part 15, Paragraph	Out of Band Emission and	PASS	Complies
15.247(d) & RSS-210 Issue 8	Restricted Band		
	Radiation		
	Limit: 20dB less than		
	peak value of fundamental		
	frequency		
	Restricted band limit:		
	Table 15.209		

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

EUT Modification 4.0

No modification by Shenzhen Timeway Technology Consulting Co., Ltd


Report No: 1308121 Page 10 of 98

Date: 2013-09-05



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm/50 uH as specified by section 5.1 of ANSI C63.4 - 2003.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the

appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Device Manufacturer		FCC
Tablet PC	Tablet PC TAE Electronics Co., Ltd.		2AAB3V703C

Report No: 1308121 Page 11 of 98

Date: 2013-09-05



B. Internal Device

Device	Manufacturer	Model	Rating

C. Peripherals

Device	Manufacturer	Model	Rating

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107 and RSS-210

	<u> </u>				
Frequency	, ,		Class B Lim	nits (dB µ V)	
(MHz)			Quasi-peak Level	Average Level	i l
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
5.00 ~ 30.00	73.0	60.0	60.0	50.0	Ì

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Report No: 1308121 Page 12 of 98

Date: 2013-09-05



A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Charging and Keep Transmitting

Equipment Level: Class B

Results: PASS

Please refer to following diagram for individual



Frequency	Line	Reading(dBμV)	Limit(dBμV)
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.428	Live	54.90	34.90	57.28	47.28
0.841	Live	47.63	31.03	56.00	46.00
1.283	Live	46.91	30.11	56.00	46.00
1.979	Live	46.69	32.39	56.00	46.00
3.011	Live	46.20	32.20	56.00	46.00
4.157	Live	46.96	32.16	56.00	46.00

Report No: 1308121 Page 13 of 98

Date: 2013-09-05



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Charging and Keep Transmitting

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



Frequency	Lina	Line Reading(dBµV)		Limit(dBµV)	
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.384	Neutral	51.95	25.35	58.18	48.18
0.649	Neutral	48.83	19.93	56.00	46.00
1.053	Neutral	48.02	20.72	56.00	46.00
2.318	Neutral	47.63	22.63	56.00	46.00
3.824	Neutral	49.93	25.03	56.00	46.00
4.572	Neutral	48.43	23.13	56.00	46.00

Report No: 1308121 Page 14 of 98


Date: 2013-09-05



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup



- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

Report No: 1308121 Page 15 of 98



6.4 Radiated Emission Limit

Date: 2013-09-05

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209

	<u> </u>	8 1
Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Report No: 1308121 Page 16 of 98

Date: 2013-09-05



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Transmitting

Results: Pass


Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
117.000	35.87	Н	43.50
641.160	40.86	Н	46.00
78.000	29.57	Н	40.00
291.440	37.32	Н	46.00
117.000	37.88	V	43.50
111.160	34.05	V	43.50
78.000	30.28	V	40.00
90.250	29.91	V	43.50

Report No: 1308121 Page 17 of 98

Date: 2013-09-05



Test Figure:




Date: 26.AUG.2013 11:30:29

Report No: 1308121 Page 18 of 98

Date: 2013-09-05



Test Figure:



Date: 26.AUG.2013 11:25:43

Report No: 1308121 Page 19 of 98

Date: 2013-09-05



Operation Mode: Keeping Transmitting under CH01 for 11g at 6Mbps

Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
92.95 (PK)	Н	Fundamental Frequency
92.66 (PK)	V	Fundamental Frequency
46.72 (PK)	Н	74(Peak)/ 54(AV)
47.11 (PK)	V	74(Peak)/ 54(AV)
	H/V	74(Peak)/ 54(AV)
	92.95 (PK) 92.66 (PK) 46.72 (PK)	92.95 (PK) H 92.66 (PK) V 46.72 (PK) H 47.11 (PK) V H/V H/V H/V H/V H/V H/V H/V H/V

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 6Mbps

Report No: 1308121 Page 20 of 98

Date: 2013-09-05



Operation Mode: Keeping Transmitting under CH06 for 11g at 6Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
2437.00	93.10 (PK)	Н	Fundamental Frequency
2437.00	92.66 (PK)	V	rundamentai riequency
4874.00	44.92 (PK)	Н	74(Peak)/ 54(AV)
4874.00	47.93 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 6 Mbps

Operation Mode: Transmitting under CH11 for 11g at 6Mbps

Frequency (MHz)	Level@3m (dB \u03ba V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2462.00	92.97 (PK)	Н	Fundamental Frequency
2462.00	93.17 (PK)	V	Fundamental Frequency
4924	48.70 (PK)	Н	74(Peak)/ 54(AV)
4924	48.66 (PK)	V	74(Peak)/ 54(AV)
7368	-	H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310	-	H/V	74(Peak)/ 54(AV)
14772	-	H/V	74(Peak)/ 54(AV)
17234	-	H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24650		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 6 Mbps


The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Please refer to the following test plots for details:

CH01 for 11g at 6Mbps: Horizontal



CH01 for 11g at 6Mbps: Vertical




The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



CH06 for 11g at 6Mbps: Vertical



CH06 for 11g at 6Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



CH11 for 11g at 6Mbps: Vertical



CH11 for 11g at 6Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Report No: 1308121 Page 24 of 98

Date: 2013-09-05



Operation Mode: Keeping Transmitting under CH01 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
2412.00	93.11 (PK)	V	Fundamental Frequency
2412.00	93.88 (PK)	Н	Fundamental Frequency
4824.00	45.10 (PK)	Н	74(Peak)/ 54(AV)
4824.00	47.04 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

Operation Mode: Keeping Transmitting under CH06 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \) V/m)
2437.00	93.46 (PK)	Н	Fundamental Frequency
2437.00	94.76 (PK)	V	Fundamental Frequency
4874.00	48.55 (PK)	Н	74(Peak)/ 54(AV)
4874.00	46.02 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1308121 Page 25 of 98

Date: 2013-09-05



Operation Mode: Keeping Transmitting under CH11 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2462.00	94.38 (PK)	Н	Even do ma out of Euro aven ave
2462.00	95.06 (PK)	V	Fundamental Frequency
4924	47.79 (PK)	Н	74(Peak)/ 54(AV)
4924	49.63 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24650		H/V	74(Peak)/ 54(AV)


Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode at 11Mbps




Please refer to the following test plots for details:

CH01 for 11b at 11Mbps: Horizontal



CH01 for 11b at 11Mbps: Vertical




The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



CH06 for 11b at 11Mbps: Vertical



CH06 for 11b at 11Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



CH11 for 11b at 11Mbps: Vertical



CH11 for 11b at 11Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2013-09-05



Operation Mode: Keeping Transmitting under CH01 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
2412.00	92.86 (PK)	Н	Fundamental Frequency
2412.00	93.42 (PK)	V	Fundamental Frequency
4824.00	47.60 (PK)	Н	74(Peak)/ 54(AV)
4824.00	48.43 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

Operation Mode: Keeping Transmitting under CH06 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2437.00	92.05 (PK)	Н	Fundamental Frequency
2437.00	93.51 (PK)	V	Fundamental Frequency
4874.00	46.14 (PK)	Н	74(Peak)/ 54(AV)
4874.00	45.88 (PK)	V	74(Peak)/ 54(AV)
7311.00	-	H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185	-	H/V	74(Peak)/ 54(AV)
14622	-	H/V	74(Peak)/ 54(AV)
17059	-	H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1308121 Page 30 of 98

Date: 2013-09-05



Operation Mode: Keeping Transmitting under CH11 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
2462.00	93.75 (PK)	Н	P 11P
2462.00	93.84 (PK)	V	Fundamental Frequency
4924	46.62 (PK)	Н	74(Peak)/ 54(AV)
4924	47.64 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24650		H/V	74(Peak)/ 54(AV)


Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps




Please refer to the following test plots for details:

CH01 for 11n HT20 at 65Mbps: Horizontal



CH01 for 11n HT20 at 65Mbps: Vertical




The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



CH06 for 11n HT20 at 65Mbps: Vertical



CH06 for 11n HT20 at 65Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



CH11 for 11n HT20 at 65Mbps: Vertical



CH11 for 11n HT20 at 65Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Report No: 1308121 Page 34 of 98

Date: 2013-09-05



Operation Mode: Transmitting under CH01 for 11n HT40 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2422.00	90.88 (PK)	Н	Eundomontal Engagonov
2422.00	91.56 (PK)	V	Fundamental Frequency
4844.00	46.05 (PK)	Н	74(Peak)/ 54(AV)
4844.00	47.64 (PK)	V	74(Peak)/ 54(AV)
7266.00		H/V	74(Peak)/ 54(AV)
9688.00		H/V	74(Peak)/ 54(AV)
12110		H/V	74(Peak)/ 54(AV)
14532		H/V	74(Peak)/ 54(AV)
16954		H/V	74(Peak)/ 54(AV)
19376		H/V	74(Peak)/ 54(AV)
21798		H/V	74(Peak)/ 54(AV)
24220		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 65Mbps

Operation Mode: Transmitting under CH04 for 11n HT40 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2437.00	91.25 (PK)	Н	Fundamental Frequency
2437.00	91.52 (PK)	V	
4874.00	46.09 (PK)	Н	74(Peak)/ 54(AV)
4874.00	45.11 (PK)	V	74(Peak)/ 54(AV)
7311.00	-	H/V	74(Peak)/ 54(AV)
9748.00	-	H/V	74(Peak)/ 54(AV)
12185	-	H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496	-1	H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 65Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1308121 Page 35 of 98

Date: 2013-09-05



Operation Mode: Transmitting under CH7 for 11n HT40 at 65Mbps

	-		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2452.00	90.82 (PK)	Н	Fundamental Frequency
2452.00	92.02 (PK)	V	
4904	46.38 (PK)	Н	74(Peak)/ 54(AV)
4904		V	74(Peak)/ 54(AV)
7356		H/V	74(Peak)/ 54(AV)
9808		H/V	74(Peak)/ 54(AV)
12260		H/V	74(Peak)/ 54(AV)
14712		H/V	74(Peak)/ 54(AV)
17164		H/V	74(Peak)/ 54(AV)
19616		H/V	74(Peak)/ 54(AV)
22068		H/V	74(Peak)/ 54(AV)
24520		H/V	74(Peak)/ 54(AV)


Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 65Mbps




Please refer to the following test plots for details:

CH01 for 11n HT40 at 65Mbps: Vertical



CH01 for 11n HT40 at 65Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Report No: 1308121 Date: 2013-09-05



CH04 for 11n HT40 at 65Mbps: Vertical



CH04 for 11n HT40 at 65Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Report No: 1308121 Date: 2013-09-05



CH07 for 11n HT40 at 65Mbps: Vertical



CH07 for 11n HT40 at 65Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Report No: 1308121 Page 39 of 98

Date: 2013-09-05



7.0 6dB Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW) \geq 3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 Test Result

Report No: 1308121 Page 40 of 98

Date: 2013-09-05



6dB Occupied Bandwidth


EUT		Tablet PC Model				2330C		
Mode		8	302.11b		Input Vol	tage		DC3.7V
Temperati	ure	24	4 deg. C,		Humidity			56% RH
Channel	Channel Frequency (MHz) Trans		Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)			mum Limit MHz)	Pass/ Fail
1		2412 1		10.08			0.5	Pass
6		2437	1	10.08			0.5	Pass
11		2462	1	10	.08		0.5	Pass
1		2412	11	9.	30		0.5	Pass
6		2437	11 9.30		30		0.5	Pass
11		2462 11 9		9.	.30		0.5	Pass

Report No: 1308121 Page 41 of 98

Date: 2013-09-05



1. 802.11b at 1Mbps of CH01




Date: 5.SEP.2013 15:13:16

Report No: 1308121 Page 42 of 98

Date: 2013-09-05



2. 802.11b at 1Mbps of CH06




Date: 5.SEP.2013 15:15:14

Report No: 1308121 Page 43 of 98

Date: 2013-09-05



3. 802.11b at 1Mbps of CH11




Date: 5.SEP.2013 15:16:53

Report No: 1308121 Page 44 of 98

Date: 2013-09-05



4. 802.11b at 11Mbps of CH01




Date: 5.SEP.2013 15:21:49

Report No: 1308121 Page 45 of 98

Date: 2013-09-05



5. 802.11b at 11Mbps of CH06




Date: 5.SEP.2013 15:24:00

Report No: 1308121 Page 46 of 98

Date: 2013-09-05



6. 802.11b at 11Mbps of CH11



Date: 5.SEP.2013 15:26:06

Report No: 1308121 Page 47 of 98

Date: 2013-09-05



6dB Occupied Bandwidth

EUT		Tablet PC Model			2330C			
Mode		8	302.11g		Input Vol	tage	DC3.7V	
Temperati	ure	24	l deg. C,		Humidity			56% RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)				num Limit MHz)	Pass/ Fail
1		2412	6	16	.38		0.5	Pass
6		2437	6	16	.38		0.5	Pass
11		2462	6	16	.38	38 0.5		Pass


Report No: 1308121 Page 48 of 98

Date: 2013-09-05



Test Plots:

1. 802.11g at 6Mbps of CH01




Date: 5.SEP.2013 15:20:42

Report No: 1308121 Page 49 of 98

Date: 2013-09-05



2. 802.11g at 6Mbps of CH06




Date: 5.SEP.2013 15:19:32

Report No: 1308121 Page 50 of 98

Date: 2013-09-05



3. 802.11g at 6Mbps of CH11



Date: 5.SEP.2013 15:18:10

Report No: 1308121 Page 51 of 98

Date: 2013-09-05



6dB Occupied Bandwidth

EUT		T	ablet PC		Model			2330C
Mode		802	.11n HT20	and HT40	Input Vol	tage		DC3.7V
Temperati	erature 24 deg. C, Humidity			56% RH				
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)			mum Limit MHz)	Pass/ Fail
1	2412		HT20	17.34		0.5		Pass
6		2437	HT20	17.34			0.5	Pass
11		2462	HT20	17	.34		0.5	Pass
1		2422	HT40	35	.12	0.5		Pass
4	2437		HT40	35.12		0.5		Pass
7		2452	HT40	35	.22	0.5		Pass


Report No: 1308121 Page 52 of 98

Date: 2013-09-05



Test Plots:

1. 802.11n at HT20 of CH01




Date: 5.SEP.2013 15:29:50

Report No: 1308121 Page 53 of 98

Date: 2013-09-05



2. 802.11n at HT20 of CH06




Date: 5.SEP.2013 15:28:36

Report No: 1308121 Page 54 of 98

Date: 2013-09-05



3. 802.11n at HT20 of CH11




Date: 5.SEP.2013 15:27:24

Report No: 1308121 Page 55 of 98

Date: 2013-09-05



4. 802.11n at HT40 of CH01




Date: 5.SEP.2013 15:31:12

Report No: 1308121 Page 56 of 98

Date: 2013-09-05



5. 802.11n at HT40 of CH04




Date: 5.SEP.2013 15:32:49

Report No: 1308121 Page 57 of 98

Date: 2013-09-05



6. 802.11n at HT40 of CH07



Date: 5.SEP.2013 15:34:25


Report No: 1308121 Page 58 of 98



8. Maximum Peak Output Power

8.1 Test Setup

Date: 2013-09-05



8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the peak power was measured

Report No: 1308121 Date: 2013-09-05



8.4Test Results

EUT	Tablet PC	Model	2330C			
Mode	802.11b	Input Voltage	DC3.7V			
Temperature	24 deg. C,	Humidity	56% RH			
Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm) Pass/ Fail			
1	2412	8.54	30	Pass		
6	2437	8.64	30	Pass		
11	2462	8.35	30	Pass		

Note: 1. At finial test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT	EUT Tablet		PC Mo		odel		2330C
Mode 802.1		1g	Input	Input Voltage		DC3.7V	
Temperati	emperature 24 deg. C, Humidity			56% RH			
Channel	Channel Frequency (MHz)		Peak Power Output (dBm)		Peak Power Limit (dBm)		Pass/ Fail
1		2412	5.36		30		Pass
6	2437		5.45		30		Pass
11		2462	5.27		30)	Pass

Note: 1. At finial test to get the worst-case emission at 6Mbps for CH01, CH06 and CH11

- The result basic equation calculation as follow:
 Peak Power Output = Peak Power Reading + Cable loss + Attenuator
- 3. The worse case was recorded

Report No: 1308121 Page 60 of 98

Date: 2013-09-05



EUT	EUT Tablet		PC Mo		odel		2330C
Mode 802.11n		(HT20) Inj		Input Voltage		DC3.7V	
Temperati	Temperature 24 deg. C,		g. C,	Humidity			56% RH
Channel	Channel Frequency (MHz)		Peak Power Output (dBm)		Peak Power Limit (dBm)		Pass/ Fail
1	2412		5.51		30		Pass
6		2437	5.53		30		Pass
11		2462	5.43		30)	Pass

Note: 1. At finial test to get the worst-case emission at 11n HT20 for CH01, CH06 and CH11

2. The result basic equation calculation as follow:Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT	EUT Tablet		PC N		odel		2330C
Mode 802.11n		HT40)	Input Voltage		DC3.7V		
Temperati	Temperature 24 de		g. C, Hu		midity		56% RH
Channel	Cha	• •		Peak Power Output (dBm)		Power nit m)	Pass/ Fail
1		2422 5.22		30)	Pass
4		2437 5.04			30		Pass
7		2452 5.03			30)	Pass

Note: 1. At finial test to get the worst-case emission at 11n HT40 for CH01, CH04 and CH07

2. The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded


Report No: 1308121 Page 61 of 98

Date: 2013-09-05



9. Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW \geq 30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be ≤ 8 dBm.

Report No: 1308121 Page 62 of 98

Date: 2013-09-05



9.4Test Result

EUT		Tablet	PC	M	odel		2330C
Mode	Mode 8		802.11b 11Mbps		Input Voltage		DC3.7V
Temperature		24 deg. C,		Humidity		56% RH	
Channel	Channel Fr (MH		Final Power Sponsity (dBm)		Maximum Limit (dBm)		Pass/ Fail
			11M	[bps			
1		2412	-14.61		8		Pass
6	2437		-14.20		8		Pass
11		2462	-15.07		8		Pass

EUT		Tablet	PC	M	odel		2330C
Mode		802.11b	802.11b 1Mbps		Input Voltage		DC3.7V
Temperat	ure	24 deg. C,		Humidity			56% RH
Channel	Ch	annel Frequency (MHz)	Final Power S Density (dBm)		Maximum Limit (dBm)		Pass/ Fail
			1M	bps			
1		2412		-13.30			Pass
6	2437		-14.51		8		Pass
11		2462	-14.68		8		Pass

Report No: 1308121 Page 63 of 98

Date: 2013-09-05



EUT		Tablet	PC	M	odel		2330C
Mode	Mode 802.11g		6Mbps	Input Voltage			DC3.7V
Temperat	Temperature 24 de		g. C, Hun		nidity		56% RH
Channel	Channel Frequency (MHz)		Final Power S Density (dBm		Maximur (dB		Pass/ Fail
			6M	bps			
1		2412	-24.38		8		Pass
6	2437		-23.95		8		Pass
11		2462	-24.28		8		Pass

EUT	Tablet		PC	M	odel		2330C
Mode	Mode 802.11n HT2		20 65Mbps	Input Voltage		DC3.7V	
Temperat	Temperature 24 deg		g. C, Hum		nidity		56% RH
Channel	Channel Frequency (MHz)		Final Power Spectral Density (dBm)		Maximur (dB		Pass/ Fail
			НТ	20			
1		2412	-24.87		8		Pass
6	2437		-23.68		8		Pass
11		2462	-24.52		8		Pass

EUT		Tablet	PC	M	odel		2330C
Mode	Mode 802.11n HT		0 65Mbps	Input	Input Voltage		DC3.7V
Temperati	Temperature		24 deg. C,		Humidity		56% RH
Channel	Channel Frequency (MHz)		Final Power S Density (dBm		Maximur (dB		Pass/ Fail
			НТ	740			
1		2422	-26.40		8		Pass
4		2437	-26.65		8		Pass
7		2452	-26.81		8		Pass


Report No: 1308121 Page 64 of 98

Date: 2013-09-05



9.5 Photo of Power Spectral Density Measurement

1.802.11b at 11Mbps of CH01




Date: 6.SEP.2013 10:49:55

Report No: 1308121 Page 65 of 98

Date: 2013-09-05



2. 802.11b at 11Mbps at CH06




Date: 6.SEP.2013 10:49:27

Report No: 1308121 Page 66 of 98

Date: 2013-09-05



3. 802.11b at 11Mbps of CH11




Date: 6.SEP.2013 10:48:57

Report No: 1308121 Page 67 of 98

Date: 2013-09-05



4. 802.11b at 1Mbps of CH1




Date: 6.SEP.2013 10:41:49

Report No: 1308121 Page 68 of 98

Date: 2013-09-05



5. 802.11b at 1Mbps of CH6




Date: 6.SEP.2013 10:44:05

Report No: 1308121 Page 69 of 98

Date: 2013-09-05



6. 802.11b at 1Mbps of CH11




Date: 6.SEP.2013 10:44:28

Report No: 1308121 Page 70 of 98

Date: 2013-09-05



7. 802.11g at 6Mbps of CH1




Date: 6.SEP.2013 10:46:54

Report No: 1308121 Page 71 of 98

Date: 2013-09-05



8. 802.11g at 6 Mbps of CH6




Date: 6.SEP.2013 10:46:11

Report No: 1308121 Page 72 of 98

Date: 2013-09-05



9. 802.11g at 6 Mbps of CH11




Date: 6.SEP.2013 10:47:20

Report No: 1308121 Page 73 of 98

Date: 2013-09-05



10. 802.11n at HT20 of CH01




Date: 6.SEP.2013 10:50:58

Report No: 1308121 Page 74 of 98

Date: 2013-09-05



11. 802.11n at HT20 of CH06




Date: 6.SEP.2013 10:51:44

Report No: 1308121 Page 75 of 98

Date: 2013-09-05



12. 802.11n at HT20 of CH11




Date: 6.SEP.2013 10:52:33

Report No: 1308121 Page 76 of 98

Date: 2013-09-05



13. 802.11n at HT40 of CH01




Date: 6.SEP.2013 10:53:24

Report No: 1308121 Page 77 of 98

Date: 2013-09-05



14. 802.11n at HT40 of CH04




Date: 6.SEP.2013 10:54:18

Report No: 1308121 Page 78 of 98

Date: 2013-09-05



15. 802.11n at HT40 of CH07



Date: 6.SEP.2013 10:55:13


Report No: 1308121 Page 79 of 98

Date: 2013-09-05



10 Out of Band Measurement

10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test.(Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measurement used

10.4 Test Result

Please see next pages

Note: 1. this is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), after pre-test. It was found that the worse radiated emission was get at the lying position. the worse case was recorded

2. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Report No: 1308121 Date: 2013-09-05




For 802.11b mode

CH01 at 11Mbps

10.4 Band-edge and Restricted band Measurement

Total Daniel Vago und Itoparotte Canad Internation							
EUT	Tablet PC		Model	2330C			
Mode	Keeping Transmitting		Input Voltage	DC3.7V			
Temperature	24 deg. C,		Humidity	56% RH			
Test Result:	Pass		Detector	PK			
2400	PK (dBμV/m)	42.7	T ::4	$74(dB\mu V/m)$			
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$			
2390	PK (dBμV/m)	37.6	Limit	$74(dB\mu V/m)$			
	AV (dBμV/m)		Limit	54(dBμV/m)			

Test Figure:



Date: 6.SEP.2013 11:00:05

Page 81 of 98

Report No: 1308121 Date: 2013-09-05




CH11 at 11Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	2330C
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m) 38.9		T,	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Date: 6.SEP.2013 11:07:12

Page 82 of 98

Report No: 1308121 Date: 2013-09-05




For 802.11g mode

CH01 at 6Mbps

10.4 Band-edge and Restricted band Measurement

Total Sund Guge and House Sund House Sund House						
EUT	Tablet Po	C I		Iodel	2330C	
Mode	Keeping Trans	mitting Inpu		t Voltage	DC3.7V	
Temperature	24 deg. (C, Hu		midity	56% RH	
Test Result:	Pass	Do		etector	PK	
2400	PK (dBμV/m)	43.8		T ' '	74(dBμV/m)	
	AV (dBμV/m)			Limit	54(dBμV/m)	
2390	PK (dBμV/m)	39.2		Limit	74(dBμV/m)	
	AV (dBμV/m)			Lillill	54(dBμV/m)	

Test Figure:



Date: 6.SEP.2013 10:59:30

Page 83 of 98

Report No: 1308121 Date: 2013-09-05




CH11 at 6Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	2330C
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBµV/m)	38.5	T * */	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Date: 6.SEP.2013 11:06:44

Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

Page 84 of 98

Report No: 1308121 Date: 2013-09-05




For 802.11n (HT20) mode

CH01 at 65Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	2330C	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:	Pass		Detector	PK	
2400	PK (dBµV/m)	44.1	Limit	$74(dB\mu V/m)$	
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$	
2390	PK (dBµV/m)	38.3	Limit	74(dBμV/m)	
	$AV (dB\mu V/m)$		Lillit	$54(dB\mu V/m)$	

Test Figure:



Date: 6.SEP.2013 11:00:51

Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 85 of 98

Report No: 1308121 Date: 2013-09-05




CH11 at 65Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	2330C
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBµV/m)	(dBμV/m) 38.7		74(dBμV/m)
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Date: 6.SEP.2013 11:04:54

Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

Page 86 of 98

Report No: 1308121 Date: 2013-09-05




For 802.11n (HT40) mode

CH01 at 65Mbps

10.4 Band-edge and Restricted band Measurement

2011 2010 4084 with 1140001414 county 1140001411411							
EUT	Tablet PC		Model	2330C			
Mode	Keeping Transmitting		Input Voltage	DC3.7V			
Temperature	24 deg. C,		Humidity	56% RH			
Test Result:	Pass		Detector	PK			
2400	PK (dBμV/m)	44.5	T ::4	$74(dB\mu V/m)$			
	AV (dBμV/m)		Limit	54(dBμV/m)			
2390	PK (dBμV/m)	37.8	Limit	$74(dB\mu V/m)$			
	AV (dBμV/m)		Lillit	$54(dB\mu V/m)$			

Test Figure:



Date: 6.SEP.2013 11:01:51

Page 87 of 98

Report No: 1308121 Date: 2013-09-05




CH11 at 65Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	2330C
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m)	PK (dBμV/m) 37.9		$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Date: 6.SEP.2013 11:03:14

Report No: 1308121 Page 88 of 98

Date: 2013-09-05



11.0 Antenna Requirement

11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

Integral Antenna used. The maximum Gain of the antennas is 2.1dBi.

Page 89 of 98

Report No: 1308121 Date: 2013-09-05



12.0 FCC Label

FCC ID: 2AAB3V703C

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



The report refers only to the sample tested and does not apply to the bulk.

Report No: 1308121 Page 90 of 98

Date: 2013-09-05



13.0 Photo of testing

Conducted Emission Test Setup:




Page 91 of 98

Report No: 1308121 Date: 2013-09-05



Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1308121 Page 92 of 98

Date: 2013-09-05



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 93 of 98

Report No: 1308121 Date: 2013-09-05



Photos of EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Page 94 of 98

Report No: 1308121 Date: 2013-09-05



Photos of EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 95 of 98

Report No: 1308121 Date: 2013-09-05



Photos of EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 96 of 98

Report No: 1308121 Date: 2013-09-05



Photos of EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 97 of 98

Report No: 1308121 Date: 2013-09-05



Photos of EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 98 of 98

Report No: 1308121 Date: 2013-09-05



Photos of EUT





End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.