

RF EXPOSURE **EVALUATION REPORT**

APPLICANT

: TECH-AUDIO CO LTD

PRODUCT NAME

Bluetooth receiver

MODEL NAME

: BTR

TRADE NAME

N/A

BRAND NAME

N/A

FCC ID

2AABM-BT101

47CFR 2.1093

STANDARD(S)

KDB 447498 D01 General RF Exposure

Guidance v06

ISSUE DATE

2016-07-05

SHENZHEN MORLAB

STECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample is results apply on the particular sample is results apply ton validation and information confirmed at our website.

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Http://www.morlab.com
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China



DIRECTORY

TEST REPORT DECLARATION		•••••	3
1. TECHNICAL INFORMATION	•••••		4
1.1. IDENTIFICATION OF APPLICANT	•••••	••••••	4
1.2. IDENTIFICATION OF MANUFACTURER			4
1.3. EQUIPMENT UNDER TEST (EUT)			4
1.3.1. PHOTOGRAPHS OF THE EUT			5
1.3.2. IDENTIFICATION OF ALL USED EUT 1.4. APPLIED REFERENCE DOCUMENTS			6
1.4. APPLIED REFERENCE DOCUMENTS	••••••	•••••	6
2. DEVICE CATEGORY AND RF EXPOSU	JRE LIMIT		7
3. MEASUREMENT OF CONDUCTED PEA	K OUTPUT POWER	•••••	8
E CLAS MORE MO. AE	QLAB 110F	Mo	IE SLAB
4. RF EXPOSURE EVALUATION			8
ANNEX A GENERAL INFORMATION	•••••		9

	Change History		
Issue	Date	Reason for change	
1.0 2016-07-05 First edition			
MORE	We I	3 SELAT MORE ME AE SELAT MORE	



TEST REPORT DECLARATION

Applicant	TECH-AUDIO CO LTD
Applicant Address	NO,3 Tungshih ,PingCheng TaoYuan ,Taiwan .
Manufacturer	Xiamen Tech-Sound Co.,Ltd
Manufacturer Address	NO.170,Ji Yin Road, Tong An District , Xiamen , China.
Product Name	Bluetooth receiver
Model Name	BTR
Brand Name	N/A
HW Version	N/A
SW Version	N/A
Test Standards	47CFR 2.1093; KDB 447498 D01 General RF Exposure Guidance v06
Issue Date	2016-07-05
SAR Evaluation	Not Required

Tested by	:	Chen Shengkui
		Chen Shengkui
Reviewed by		Liu Jun
		Liu Jun

Approved by



1. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

1.1. Identification of Applicant

Company Name:	TECH-AUDIO CO LTD
Address:	NO,3 Tungshih ,PingCheng TaoYuan ,Taiwan .

1.2. Identification of Manufacturer

Company Name:	Xiamen Tech-Sound Co.,Ltd
Address:	NO.170,Ji Yin Road, Tong An District , Xiamen , China.

1.3. Equipment Under Test (EUT)

Model Name:	BTR NO.
Trade Name:	N/A
Brand Name:	N/A
Hardware Version:	N/A
Software Version:	N/A
Frequency Bands:	Bluetooth 4.0:2402MHz - 2480MHz.;
Modulation Mode:	GFSK;
Antenna type:	Ceramic Antenna
Antenna Gain:	1dBi Maria M




1.3.1. Photographs of the EUT

EUT front view



2. EUT rear view





1.3.2. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version	
1#	N/A	N/A	

1.4. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1 OPLAE	47 CFR§2.1093	Radiofrequency Radiation Exposure Evaluation: portable devices
2	KDB 447498 D01v06	General RF Exposure Guidance



2. DEVICE CATEGORY AND RF EXPOSURE LIMIT

Per user manual. Based on 47CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

Portable Devices:

47CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

47CFR 2.1093(d) (2)

Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.



3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER

1. Average output power

61,	A-	· Pr	
Band	Channel Frequency (MHz)	Output Power(dBm)	
24		(MHz)	GFSK
QLAB.	0	2402	-2.76
BT 4.0	19	2440	0.83
LAB JOR	39	2480	2.16

4. RF EXPOSURE EVALUATION

The device only incorporates a Bluetooth transmitter, so standalone SAR evaluation is required for Bluetooth and simultaneous SAR is not required.

Standalone transmission SAR evaluation

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation Distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)}$] ≤ 3.0

The maximum tune-up limit power is 1.58mW @ 2.480GHz

so use 5mm as the most conservative minimum test separation distance,

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)}$] =0.628 \leq 3.0

So SAR evaluation is not required for this device.



ANNEX A GENERAL INFORMATION

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang
	Road, Block 67, BaoAn District, ShenZhen, GuangDong
	Province, P. R. China

