

FCC RF EXPOSURE REPORT

FCC ID: 2AACP-0BK1

Project No. : 1408C163
Equipment : Transit XS
Model : BK1
Applicant : Strata Audio LLC
Address : 31368 Via Colinas, Suite 106, Westlake Village,
California 91362, United States

According: : FCC Guidelines for Human Exposure IEEE
C95.1

BTL Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL : (0769) 8318-3000 FAX : (0769) 8319-6000

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Printed	N/A	-1.72

GENERAL CONCLUSION:

Maximum measured transmitter power:

Output Power (dBm)	Output Power (mW)	Limit (mW)
5.45	3.5	10

According to FCC KDB447498 V05, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 3.5 mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold