



# TEST REPORT

Report Reference No..... : TRE1405020702 R/C.....: 58890  
FCC ID..... : 2AADR-HSG1279A  
Applicant's name..... : Hannstar Display Corp.  
Address..... : 4F., No.48, Wuquan Rd., Wugu Dist., New Taipei City 248, Taiwan, R.O.C.  
Manufacturer..... : Foxda Technology Industrial(Shenzhen) Co.,Ltd  
Address..... : 1F of 1st Building&1F-3F of 2nd Building, Foxda Industrial Zone,North of Lanzhu Road,Pingshan New District,Shenzhen City,Guangdong Province,P.R.China  
Test item description ..... : Tablet PC  
Trade Mark ..... : HANNspree  
Model/Type reference..... : HSG1279  
List Model ..... : /  
Standard ..... : FCC CFR Title 47 Part 15 Subpart C Section 15.247  
Date of receipt of test sample..... : May 29, 2014  
Date of testing ..... : May 29, 2014- Jul 04, 2014  
Date of issue..... : Jul 04, 2014  
Result..... : PASS

Compiled by  
( position+printed name+signature)... : File administrators Jerome Luo  
Supervised by  
( position+printed name+signature)... : Project Engineer Yuchao Wang  
Approved by  
( position+printed name+signature)... : RF Manager Hans Hu

Jerome Luo

yuchao.wang

Hans Hu

Testing Laboratory Name ..... : Shenzhen Huatongwei International Inspection Co., Ltd  
Address..... : Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

## Contents

<b><u>1.</u></b>	<b><u>TEST STANDARDS AND TEST DESCRIPTION</u></b>	<b><u>3</u></b>
1.1.	Test Standards	3
1.2.	Test Description	3
<b><u>2.</u></b>	<b><u>SUMMARY</u></b>	<b><u>4</u></b>
2.1.	Client Information	4
2.2.	Product Description	4
2.3.	EUT operation mode	5
2.4.	EUT configuration	5
2.5.	Modifications	5
<b><u>3.</u></b>	<b><u>TEST ENVIRONMENT</u></b>	<b><u>6</u></b>
3.1.	Address of the test laboratory	6
3.2.	Test Facility	6
3.3.	Environmental conditions	7
3.4.	Statement of the measurement uncertainty	7
3.5.	Equipments Used during the Test	8
<b><u>4.</u></b>	<b><u>TEST CONDITIONS AND RESULTS</u></b>	<b><u>9</u></b>
4.1.	Antenna requirement	9
4.2.	Conducted Emission (AC Main)	10
4.3.	Conducted Peak Output Power	13
4.4.	20dB Emission Bandwidth	17
4.5.	Carrier Frequencies Separation	21
4.6.	Hopping Channel Number	25
4.7.	Dwell Time	27
4.8.	Pseudorandom Frequency Hopping Sequence	31
4.9.	Band Edge	32
4.10.	Spurious Emission (conducted)	39
4.11.	Spurious Emission (radiated)	42
<b><u>5.</u></b>	<b><u>TEST SETUP PHOTOS OF THE EUT</u></b>	<b><u>48</u></b>
<b><u>6.</u></b>	<b><u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u></b>	<b><u>49</u></b>

## 1. TEST STANDARDS AND TEST DESCRIPTION

### 1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2009](#): American National Standard for Testing Unlicensed Wireless Devices

### 1.2. Test Description

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)	Pass
Dwell Time	15.247 (a)(1)	Pass
Pseudorandom Frequency Hopping Sequence	15.247(b)(4)&TCB Exclusion List (7 July 2002)	Pass
Band Edge	15.247(d)	Pass
Radiated Emission	15.205/15.209	Pass

Remark: The measurement uncertainty is not included in the test result.

## 2. SUMMARY

### 2.1. Client Information

Applicant:	Hannstar Display Corp.
Address:	4F., No.48, Wuquan Rd., Wugu Dist., New Taipei City 248, Taiwan, R.O.C.
Manufacturer:	Foxda Technology Industrial(Shenzhen) Co.,Ltd
Address:	1F of 1st Building&1F-3F of 2nd Building, Foxda Industrial Zone,North of Lanzhu Road,Pingshan New District,Shenzhen City,Guangdong Province,P.R.China

### 2.2. Product Description

Name of EUT	Tablet PC
Trade Mark:	HANNspree
Model No.:	HSG1279
List Model:	/
Power supply:	DC 3.7V From Internal Battery
Adapter information:	Mode:SYS1357-1305 INPUT:AC 100-240V 50/60Hz 1.0A OUTPUT:DC 5V 2.6A
<b>Bluetooth</b>	
Version:	Supported BT3.0+EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Internal Antenna
Antenna gain:	2.35dBi

#### Operation Frequency List:

Channel	Frequency (MHz)
<b>1</b>	<b>2402</b>
2	2403
⋮	⋮
39	2440
<b>40</b>	<b>2441</b>
41	2442
⋮	⋮
78	2479
<b>79</b>	<b>2480</b>

#### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

### 2.3. EUT operation mode

The EUT has been tested under typical operating condition. The Applicant provides software to control the EUT for staying in continuous transmitting and receiving mode for testing.

### 2.4. EUT configuration

**The following peripheral devices and interface cables were connected during the measurement:**

● - supplied by the manufacturer

○ - supplied by the lab

<input type="radio"/>	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

### 2.5. Modifications

No modifications were implemented to meet testing criteria.

### **3. TEST ENVIRONMENT**

#### **3.1. Address of the test laboratory**

Shenzhen Huatongwei International Inspection Co., Ltd.  
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China  
Phone: 86-755-26748019 Fax: 86-755-26748089

#### **3.2. Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

##### **CNAS-Lab Code: L1225**

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: Mar. 01, 2012. Valid time is until February 28, 2015.

##### **A2LA-Lab Cert. No. 2243.01**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until Sept 30, 2015.

##### **FCC-Registration No.: 662850**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 662850, Renewal date Jul. 01, 2012, valid time is until Jun. 01, 2015.

##### **IC-Registration No.: 5377A**

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

##### **ACA**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

##### **VCCI**

The 3m Semi-anechoic chamber (12.2m×7.95m×6.7m) of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.:R-2484. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 29, 2015.

Radiated disturbance above 1GHz measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-292. Date of Registration: Dec. 24, 2013. Valid time is until Dec. 23, 2016.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 19, 2015.

Telecommunication Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-1837. Date of Registration: May 07, 2013. Valid time is until May 06, 2016.

##### **DNV**

Shenzhen Huatongwei International Inspection Co., Ltd. has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025 (2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until Aug. 24, 2016.

### 3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

### 3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Radiated spurious emission 9KHz-40 GHz	2.20 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emission 1~18GHz	5.16 dB	(1)
Radiated Emission 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .

### 3.5. Equipments Used during the Test

AC Power Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Due
1	Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2014/10/25
2	EMI Test Receiver	Rohde&Schwarz	ESCI3	100038	2014/10/25
3	Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2014/10/25
4	EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	N/A

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Due
1	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2014/10/25
2	EMI TEST RECEIVER	Rohde&Schwarz	ESI 26	100009	2014/10/25
3	EMI TEST Software	Audix	E3	N/A	N/A
4	TURNTABLE	ETS	2088	2149	N/A
5	ANTENNA MAST	ETS	2075	2346	N/A
6	EMI TEST Software	Rohde&Schwarz	ESK1	N/A	N/A
7	HORN ANTENNA	ShwarzBeck	9120D	1011	2014/10/25
8	Amplifer	Sonoma	310N	E009-13	2014/10/25
9	JS amplifer	Rohde&Schwarz	JS4-00101800-28-5A	F201504	2014/10/25
10	High pass filter	Compliance Direction systems	BSU-6	34202	2014/10/25
11	HORN ANTENNA	ShwarzBeck	9120D	1012	2014/10/25
12	Amplifer	Compliance Direction systems	PAP1-4060	120	2014/10/25
13	Loop Antenna	Rohde&Schwarz	HFH2-Z2	100020	2014/10/25
14	TURNTABLE	MATURO	TT2.0	----	N/A
15	ANTENNA MAST	MATURO	TAM-4.0-P	----	N/A
16	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2014/10/25
17	ULTRA-BROADBAND ANTENNA	Rohde&Schwarz	HL562	100015	2014/10/25

Maximum Peak Output Power / Power Spectral Density / 6dB Bandwidth / Band Edge Compliance of RF Emission / Spurious RF Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Due
1	Spectrum Analyzer	Rohde&Schwarz	FSP	1164.4391.40	2014/10/25

The Cal.Interval was one year



## 4. TEST CONDITIONS AND RESULTS

### 4.1. Antenna requirement

#### Requirement

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):**

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

#### Test Result:

The antenna is integral antenna, the best case gain of the antenna is 2.35dBi



## 4.2. Conducted Emission (AC Main)


### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST CONFIGURATION




### TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2009.
2. Support equipment, if needed, was placed as per ANSI C63.10-2009
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2009
4. The EUT received DC5V power from the adapter, the adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

### TEST RESULTS

Test mode:	Bluetooth mode	Polarization	L
------------	----------------	--------------	---



### MEASUREMENT RESULT: "HTW0530202\_fin"

5/30/2014 9:26AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.163500	56.00	10.1	65	9.3	QP	L1	GND
0.501000	34.40	10.1	56	21.6	QP	L1	GND
1.828500	26.90	10.2	56	29.1	QP	L1	GND
3.876000	24.30	10.2	56	31.7	QP	L1	GND
10.252500	38.80	10.5	60	21.2	QP	L1	GND
21.133500	26.80	11.0	60	33.2	QP	L1	GND

### MEASUREMENT RESULT: "HTW0530202\_fin2"

5/30/2014 9:26AM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.168000	37.40	10.1	55	17.7	AV	L1	GND
0.501000	28.10	10.1	46	17.9	AV	L1	GND
1.671000	21.60	10.2	46	24.4	AV	L1	GND
2.715000	21.40	10.2	46	24.6	AV	L1	GND
10.239000	24.10	10.5	50	25.9	AV	L1	GND
20.998500	21.10	10.9	50	28.9	AV	L1	GND

Test mode:

Bluetooth mode

Polarization

N

**MEASUREMENT RESULT: "HTW0530201\_fin"**

5/30/2014 9:19AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.154500	59.20	10.1	66	6.6	QP	N	GND
0.370500	36.10	10.1	59	22.4	QP	N	GND
1.567500	32.00	10.2	56	24.0	QP	N	GND
3.592500	30.70	10.2	56	25.3	QP	N	GND
10.315500	40.20	10.5	60	19.8	QP	N	GND
13.960500	27.60	10.6	60	32.4	QP	N	GND

**MEASUREMENT RESULT: "HTW0530201\_fin2"**

5/30/2014 9:19AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.154500	41.70	10.1	56	14.1	AV	N	GND
0.186000	37.30	10.1	54	16.9	AV	N	GND
0.496500	27.60	10.1	46	18.5	AV	N	GND
1.639500	26.50	10.2	46	19.5	AV	N	GND
3.322500	25.50	10.2	46	20.5	AV	N	GND

### 4.3. Conducted Peak Output Power

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1) or (b)(1): **30dBm or 21dBm**

#### TEST CONFIGURATION



#### TEST PROCEDURE


Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum.

#### TEST RESULTS

Modulation type	Channel	Output power (dBm)	Limit (dBm)	Result
GFSK	01	-0.43	30	Pass
	40	-0.22		
	79	-0.64		
$\pi/4$ DQPSK	01	-1.62	21	Pass
	40	-1.25		
	79	-1.16		
8DPSK	01	-1.34	21	Pass
	40	-0.94		
	79	-0.85		


Test plot as follows:

GFSK Modulation




Date: 6.JUN.2014 21:02:12

CH01



Date: 6.JUN.2014 21:02:29


CH40



Date: 6.JUN.2014 21:02:44


CH79

$\pi/4$ DQPSK Modulation




Date: 6.JUN.2014 21:04:08

CH01



Date: 6.JUN.2014 21:04:26


CH40



Date: 6.JUN.2014 21:04:44


CH79

8DPSK Modulation




Date: 6.JUN.2014 21:05:02

CH01



Date: 6.JUN.2014 21:05:18

CH40



Date: 6.JUN.2014 21:05:34

CH79



#### 4.4. 20dB Emission Bandwidth

##### LIMIT

N/A

##### TEST CONFIGURATION



##### TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=30 KHz and VBW=100KHz.
3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

##### TEST RESULTS

Modulation type	Channel	20dB Bandwidth (MHz)	Limit (MHz)	Result
GFSK	01	0.844	/	Pass
	40	0.836		
	79	0.844		
$\pi/4$ DQPSK	01	1.216	/	Pass
	40	1.216		
	79	1.216		
8DPSK	01	1.208	/	Pass
	40	1.208		
	79	1.208		


Test plot as follows:

GFSK Modulation




Date: 6.JUN.2014 21:28:48

CH01



Date: 6.JUN.2014 21:29:08


CH40



Date: 6.JUN.2014 21:29:30


CH79

$\pi/4$ DQPSK Modulation




Date: 6.JUN.2014 21:30:00

CH01



Date: 6.JUN.2014 21:30:24


CH40



Date: 6.JUN.2014 21:30:47


CH79

8DPSK Modulation




Date: 6.JUN.2014 21:31:11

CH01



Date: 6.JUN.2014 21:31:31

CH40



Date: 6.JUN.2014 21:31:52

CH79

#### 4.5. Carrier Frequencies Separation

##### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):  
frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the  $2/3 \times 20\text{dB}$  bandwidth of the hopping channel, whichever is greater.

##### TEST CONFIGURATION



##### TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=30 KHz and VBW=100KHz.

##### TEST RESULTS

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (MHz)	Result
GFSK	01	1.004	0.844	Pass
	40	1.004		
	79	1.004		
$\pi/4$ DQPSK	01	1.004	0.811	Pass
	40	1.004		
	79	1.004		
8DPSK	01	1.004	0.805	Pass
	40	1.004		
	79	1.004		


Test plot as follows:

GFSK Modulation




Date: 6.JUN.2014 21:06:55

CH01



Date: 6.JUN.2014 21:07:26


CH40



Date: 6.JUN.2014 21:08:04


CH79

$\pi/4$ DQPSK Modulation




Date: 6.JUN.2014 21:09:53

CH01



Date: 6.JUN.2014 21:10:28


CH40



Date: 6.JUN.2014 21:08:56


CH79

8DPSK Modulation




Date: 6.JUN.2014 21:12:06

CH01



Date: 6.JUN.2014 21:11:14

CH40



Date: 6.JUN.2014 21:12:44

CH79



#### 4.6. Hopping Channel Number

##### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

##### TEST CONFIGURATION




##### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=30 KHz and VBW=100KHz.

##### TEST RESULTS


Modulation type	Channel number	Limit (MHz)	Result
GFSK	79	15	Pass
$\pi/4$ DQPSK	79		
8DPSK	79		

Test plot as follows:




Date: 6.JUN.2014 20:58:12

GFSK



Date: 6.JUN.2014 20:57:00

$\pi/4$ DQPSK



Date: 6.JUN.2014 21:00:24

8DPSK

## 4.7. Dwell Time

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

*The average time of occupancy on any channel shall not be greater than 0.4 seconds within a pe-riod of 0.4 seconds multiplied by the number of hopping channels employed.*

### TEST CONFIGURATION



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set center frequency of spectrum analyzer=operating frequency with RBW=1MHz and VBW=3MHz,Span=0Hz.

### TEST RESULTS


Modulation type	Channel	Dwell time (Second)	Limit (Second)	Result
GFSK	DH1	0.134	0.40	Pass
	DH3	0.271		
	DH5	0.315		
$\pi/4$ DQPSK	2-DH1	0.138	0.40	Pass
	2-DH3	0.270		
	2-DH5	0.317		
8DPSK	3-DH1	0.138	0.40	Pass
	3-DH3	0.270		
	3-DH5	0.315		

Note:

1. We have tested all mode at high,middle and low channel,and recoreded worst case at middle channel.
2. Dwell time=Pulse time (ms)  $\times$  (1600  $\div$  2  $\div$  79)  $\times$ 31.6 Second for DH1, 2-DH1, 3-DH1  
 Dwell time=Pulse time (ms)  $\times$  (1600  $\div$  4  $\div$  79)  $\times$ 31.6 Second for DH3, 2-DH3, 3-DH3  
 Dwell time=Pulse time (ms)  $\times$  (1600  $\div$  6  $\div$  79)  $\times$ 31.6 Second for DH5, 2-DH5, 3-DH5


Test plot as follows:

GFSK Modulation




Date: 6.JUN.2014 21:14:10

DH1



Date: 6.JUN.2014 21:14:33


DH3



Date: 6.JUN.2014 21:14:56


DH5

$\pi/4$ DQPSK Modulation




Date: 6.JUN.2014 21:15:28

2-DH1



Date: 6.JUN.2014 21:15:55


2-DH3



Date: 6.JUN.2014 21:16:22


2-DH5

8DPSK Modulation




Date: 6.JUN.2014 21:15:28

3-DH1



Date: 6.JUN.2014 21:15:55

3-DH3



3-DH5

#### 4.8. Pseudorandom Frequency Hopping Sequence

##### LIMIT


FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

##### TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5<sup>th</sup> and 9<sup>th</sup> stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally on the average by each transmitter.

The system receiver has input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shifts frequencies in synchronization with the transmitted signals.


## 4.9. Band Edge

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

*In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.*

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The receiver set as follow  
Peak Vaule: RBW=1MHz, VBW=1MHz, Detector=Peak  
Average Vaule: RBW=1MHz, VBW=10Hz, Detector=Peak.

### TEST RESULTS

Noted:

Have pre-scan all modulation mode, found the 8DPSK modulation which it was worst case, so only the worst case's data on the test report.




## For Radiated Bandedge Measurement

Worst mode:	GFSK Modulation	Test Channel:	01
Detector:	Peak	Polarization:	Horizontal

Data: 94

File: D:\E3\HTW\0822.EM6 (94)




Mark	Frequency MHz	Level dBuV/m	Factor dB	Reading dBuV/m	Limit dBuV/m	Margin dB	Polarization
1	2390.00	39.35	-5.28	44.63	74.00	34.65	HORIZONTAL
2	2402.25	95.75	-5.31	101.06	74.00	-21.75	HORIZONTAL

Worst mode:	GFSK Modulation	Test Channel:	01
Detector:	Peak	Polarization:	Vertical

Data: 95

File: D:\E3\HTW\0822.EM6 (95)




Mark	Frequency MHz	Level dBuV/m	Factor dB	Reading dBuV/m	Limit dBuV/m	Margin dB	Polarization
1	2390.00	40.17	-5.28	45.45	74.00	33.83	VERTICAL
2	2402.05	95.59	-5.31	100.90	74.00	-21.59	VERTICAL

Worst mode:	GFSK Modulation	Test Channel:	01
Detector:	Peak	Polarization:	Horizontal

Data: 92

File: D:\E3\HTW\0822.EM6 (92)




Mark	Frequency MHz	Level dBuV/m	Factor dB	Reading dBuV/m	Limit dBuV/m	Margin dB	Polarization
1	2390.00	27.98	-5.28	33.26	54.00	26.02	HORIZONTAL
2	2402.05	83.54	-5.31	88.85	54.00	-29.54	HORIZONTAL

Worst mode:	GFSK Modulation	Test Channel:	01
Detector:	Peak	Polarization:	Vertical

Data: 93

File: D:\E3\HTW\0822.EM6 (93)




Mark	Frequency MHz	Level dBuV/m	Factor dB	Reading dBuV/m	Limit dBuV/m	Margin dB	Polarization
1	2390.00	26.03	-5.28	31.31	54.00	27.97	VERTICAL
2	2402.05	82.24	-5.31	87.55	54.00	-28.24	VERTICAL

Worst mode:	GFSK Modulation	Test Channel:	79
Detector:	Peak	Polarization:	Horizontal

Data: 110

File: D:\E3\HTW\0822.EM6 (110)




Mark	Frequency MHz	Level dBuV/m	Factor dB	Reading dBuV/m	Limit dBuV/m	Margin dB	Polarization
1	2480.01	93.78	-5.22	99.00	74.00	-19.78	VERTICAL
2	2483.50	54.58	-5.22	59.80	74.00	19.42	VERTICAL

Worst mode:	GFSK Modulation	Test Channel:	79
Detector:	Peak	Polarization:	Vertical

Data: 111

File: D:\E3\HTW\0822.EM6 (111)




Mark	Frequency MHz	Level dBuV/m	Factor dB	Reading dBuV/m	Limit dBuV/m	Margin dB	Polarization
1	2480.01	91.38	-5.22	96.60	74.00	-17.38	VERTICAL
2	2483.50	51.92	-5.22	57.14	74.00	22.08	VERTICAL

Worst mode:	GFSK Modulation	Test Channel:	79
Detector:	Peak	Polarization:	Horizontal

Data: 108

File: D:\E3\HTW\0822.EM6 (108)




Mark	Frequency MHz	Level dBuV/m	Factor dB	Reading dBuV/m	Limit dBuV/m	Margin dB	Polarization
1	2480.01	81.97	-5.22	87.19	54.00	-27.97	HORIZONTAL
2	2483.50	41.17	-5.22	46.39	54.00	12.83	HORIZONTAL

Worst mode:	GFSK Modulation	Test Channel:	79
Detector:	Peak	Polarization:	Vertical


Data: 109

File: D:\E3\HTW\0822.EM6 (109)




Mark	Frequency MHz	Level dBuV/m	Factor dB	Reading dBuV/m	Limit dBuV/m	Margin dB	Polarization
1	2480.01	81.58	-5.22	86.80	54.00	-27.58	VERTICAL
2	2483.50	40.96	-5.22	46.18	54.00	13.04	VERTICAL

For Conducted Bandedge Measurement




GFSK Modulation(Worst mode)



Date: 6.JUN.2014 21:40:10

CH79



Date: 6.JUN.2014 21:40:46

CH79

#### 4.10. Spurious Emission (conducted)

##### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

*In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.*

##### TEST CONFIGURATION



##### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz.
3. Below -20dB of the highest emission level in operating band.


##### TEST RESULTS

*Noted:*

*Have pre-scan all modulation mode, found the 8DPSK modulation which it was worst case, so only the worst case's data on the test report.*


Test plot as follows:

Test channel




Date: 6.JUN.2014 21:19:13

01



Date: 6.JUN.2014 21:19:25

30MHz~1GHz




Date: 6.JUN.2014 21:19:34

10GHz~15GHz


15GHz~25GHz

Test channel



Date: 6.JUN.2014 21:20:03

40




Date: 6.JUN.2014 21:20:12

30MHz~1GHz

1GHz~15GHz






Date: 6.JUN.2014 21:20:20

15GHz~25GHz


Test channel

79




Date: 6.JUN.2014 21:20:45

30MHz~1GHz



Date: 6.JUN.2014 21:20:53

1GHz~15GHz



Date: 6.JUN.2014 21:21:02

15GHz~25GHz

#### 4.11. Spurious Emission (radiated)


##### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

##### TEST CONFIGURATION


- Below 30MHz



- 30MHz~1000MHz



- Above 1GHz



**TEST PROCEDURE**

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Frequency range	RBW	VBW	Detector
9K~150KHz	200Hz	600Hz	Quasi-Peak
150K~30MHz	200Hz	600Hz	Quasi-Peak
30MHz~1GHz	120KHz	300KHz	Quasi-Peak
Above 1GHz	1MHz	1MHz	Peak for peak value
	1MHz	10Hz	Peak for average value

**TEST RESULTS**

*Noted:*

*Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.*

***For 9KHz to 30MHz***

Frequency (MHz)	Level (dBuV/m)@3m	Limit Line (dBuV/m)@3m	Margin (dB)	Detector	Result
12.00	42.93	69.54	26.61	QP	PASS
24.00	40.87	69.54	28.67	QP	PASS


## Measurement data:

## ■ Below 1GHz

Test mode:

Polarization

Horizontal



## MEASUREMENT RESULT: "HTW0604412\_red"


6/4/2014 8:59AM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
55.270541	27.00	-22.4	40.0	13.0	Pk	300.0	125.00	HORIZONTAL
675.370741	34.60	-7.5	46.0	11.4	Pk	100.0	166.00	HORIZONTAL
720.080160	35.50	-7.2	46.0	10.5	Pk	100.0	53.00	HORIZONTAL
805.611222	40.90	-5.9	46.0	5.1	Pk	100.0	71.00	HORIZONTAL
840.601202	42.50	-5.2	46.0	3.5	Pk	100.0	291.00	HORIZONTAL
879.478958	40.30	-4.4	46.0	5.7	Pk	100.0	118.00	HORIZONTAL

Test mode:

Polarization

Vertical



## MEASUREMENT RESULT: "HTW0604411\_red"

6/4/2014 8:56AM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
41.663327	37.00	-16.2	40.0	3.0	Pk	100.0	45.00	VERTICAL
140.801603	35.30	-20.1	43.5	8.2	Pk	100.0	144.00	VERTICAL
675.370741	35.30	-7.5	46.0	10.7	Pk	100.0	175.00	VERTICAL
720.080160	34.40	-7.2	46.0	11.6	Pk	100.0	269.00	VERTICAL
803.667335	41.40	-6.1	46.0	4.6	Pk	100.0	103.00	VERTICAL
842.545090	39.20	-5.2	46.0	6.8	Pk	100.0	26.00	VERTICAL

■ Above 1GHz

Test channel:	01
---------------	----

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	46.53	31.28	5.66	35.29	48.18	74.00	25.82	Vertical
7206.00	52.75	36.22	6.87	35.15	60.69	74.00	13.31	Vertical
9608.00	45.13	37.85	8.8	35.55	56.23	74.00	17.77	Vertical
12010.00						74.00		Vertical
14412.00						74.00		Vertical
4804.00	45.21	31.28	5.66	35.29	46.86	74.00	27.14	Horizontal
7206.00	48.67	36.22	6.87	35.15	56.61	74.00	17.39	Horizontal
9608.00	43.33	37.85	8.8	35.55	54.43	74.00	19.57	Horizontal
12010.00						74.00		Horizontal
14412.00						74.00		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	26.26	31.28	5.66	35.29	27.91	54.00	26.09	Vertical
7206.00	32.07	36.22	6.87	35.15	40.01	54.00	13.99	Vertical
9608.00	29.29	37.85	8.8	35.55	40.39	54.00	13.61	Vertical
12010.00						54.00		Vertical
14412.00						54.00		Vertical
4804.00	25.78	31.28	5.66	35.29	27.43	54.00	26.57	Horizontal
7206.00	32.53	36.22	6.87	35.15	40.47	54.00	13.53	Horizontal
9608.00	26.29	37.85	8.8	35.55	37.39	54.00	16.61	Horizontal
12010.00						54.00		Horizontal
14412.00						54.00		Horizontal

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	40
---------------	----

**Peak value:**

Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	Polarization
4882.00	44.64	31.26	5.65	35.27	46.28	74.00	27.72	Vertical
7323.00	50.86	36.2	6.86	35.13	58.79	74.00	15.21	Vertical
9764.00	43.24	37.83	8.79	35.53	54.33	74.00	19.67	Vertical
12205.00						74.00		Vertical
14646.00						74.00		Vertical
4882.00	43.32	31.26	5.65	35.27	44.96	74.00	29.04	Horizontal
7323.00	46.78	36.2	6.86	35.13	54.71	74.00	19.29	Horizontal
9764.00	41.44	37.83	8.79	35.53	52.53	74.00	21.47	Horizontal
12205.00						74.00		Horizontal
14646.00						74.00		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	Polarization
4960.00	24.59	31.26	5.65	35.27	26.23	27.77	26.58	Vertical
7440.00	30.40	36.2	6.86	35.13	38.33	15.67	14.48	Vertical
9620.00	27.62	37.83	8.79	35.53	38.71	15.29	14.10	Vertical
12400.00						54.00		Vertical
14880.00						54.00		Vertical
4960.00	24.11	31.26	5.65	35.27	25.75	54.00	28.25	Horizontal
7440.00	30.86	36.2	6.86	35.13	38.79	54.00	15.21	Horizontal
9620.00	24.62	37.83	8.79	35.53	35.71	54.00	18.29	Horizontal
12400.00						54.00		Horizontal
14880.00						54.00		Horizontal

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	79
---------------	----

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	45.23	31.23	5.64	35.22	46.88	74.00	27.12	Vertical
7206.00	51.45	36.17	6.85	35.08	59.39	74.00	14.61	Vertical
9608.00	43.83	37.8	8.78	35.48	54.93	74.00	19.07	Vertical
12010.00						74.00		Vertical
14412.00						74.00		Vertical
4804.00	43.91	31.23	5.64	35.22	45.56	74.00	28.44	Horizontal
7206.00	47.37	36.17	6.85	35.08	55.31	74.00	18.69	Horizontal
9608.00	42.03	37.8	8.78	35.48	53.13	74.00	20.87	Horizontal
12010.00						74.00		Horizontal
14412.00						74.00		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	24.96	31.23	5.64	35.22	26.61	54.00	27.39	Vertical
7206.00	30.77	36.17	6.85	35.08	38.71	54.00	15.29	Vertical
9608.00	27.99	37.8	8.78	35.48	39.09	54.00	14.91	Vertical
12010.00						54.00		Vertical
14412.00						54.00		Vertical
4804.00	24.48	31.23	5.64	35.22	26.13	54.00	27.87	Horizontal
7206.00	31.23	36.17	6.85	35.08	39.17	54.00	14.83	Horizontal
9608.00	24.99	37.8	8.78	35.48	36.09	54.00	17.91	Horizontal
12010.00						54.00		Horizontal
14412.00						54.00		Horizontal

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 5. Test Setup Photos of the EUT

Radiated Emission (Below 30MHz)



Radiated Emission (30MHz-1GHz)



Radiated Emission (above 1GHz)





Conducted Emission (AC Mains)



## 6. External and Internal Photos of the EUT

Reference to the test report No. TRE1405020701

.....End of Report.....