



**FCC Part 1 Subpart I
FCC Part 2 Subpart J
INDUSTRY CANADA RSS 102 ISSUE 5**

RF EXPOSURE REPORT

FOR

Intelligent Backhaul Radio

MODEL NUMBERS: IBR-1300-NA and IBR-1301-NA

**FCC ID: 2AAEH-107
IC ID: 11158A-107**

REPORT NUMBER: 15U21741-E7V1

ISSUE DATE: February 15, 2016

Prepared for
**CBF NETWORKS, INC., DBA FASTBACK NETWORKS
2460 N. FIRST STREET, SUITE 200
SAN JOSE, CA 95131**

Prepared by
**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 100255-0

Revision History

| Rev. | Issue Date | Revisions | Revised By |
|------|------------|---------------|------------|
| -- | 2/15/16 | Initial Issue | F. de Anda |

TABLE OF CONTENTS

| | |
|---|-----------|
| 1. ATTESTATION OF TEST RESULTS | 4 |
| 2. TEST METHODOLOGY | 5 |
| 3. REFERENCES | 5 |
| 4. FACILITIES AND ACCREDITATION | 5 |
| 5. MAXIMUM PERMISSIBLE RF EXPOSURE | 6 |
| 5.1. <i>FCC RULES</i> | 6 |
| 5.2. <i>IC RULES</i> | 7 |
| 5.3. <i>EQUATIONS</i> | 8 |
| 5.4. <i>LIMITS AND IC EXEMPTION</i> | 9 |
| 6. RF EXPOSURE RESULTS | 10 |

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: CBF NETWORKS, INC., DBA FASTBACK NETWORKS
2460 N. FIRST STREET, SUITE 200
SAN JOSE, CA 95131

EUT DESCRIPTION: Intelligent Backhaul Radio

MODELS: IBR-1300-NA and IBR-1301-NA

SERIAL NUMBER: Proto 1

| APPLICABLE STANDARDS | |
|---|--------------|
| STANDARD | TEST RESULTS |
| FCC PART 1 SUBPART I & PART 2 SUBPART J | Pass |
| INDUSTRY CANADA RSS 102 ISSUE 5 | Pass |

UL Verification Services Inc. calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.


Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:



Francisco de Anda
PROGRAM MANAGER
UL VERIFICATION SERVICES INC.

Tested By:



Chris Xiong
EMC ENGINEER
UL VERIFICATION SERVICES INC.

2. TEST METHODOLOGY

All calculations were made in accordance with FCC OET Bulletin 65 Edition 97-01 and IC Safety Code 6.

3. REFERENCES

All measurements were made as documented in test report UL Verification Services Inc. document 15U21741-E3V1 for operation in the 5.3 GHz band and 15U21741-E4V1 for operation in the 5.6 GHz band.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports.

Antenna gain data is excerpted from product documentation provided by the applicant.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

| 47173 Benicia Street | 47266 Benicia Street |
|------------------------------------|---|
| <input type="checkbox"/> Chamber A | <input type="checkbox"/> Chamber D |
| <input type="checkbox"/> Chamber B | <input type="checkbox"/> Chamber E |
| <input type="checkbox"/> Chamber C | <input type="checkbox"/> Chamber F |
| | <input type="checkbox"/> Chamber G |
| | <input checked="" type="checkbox"/> Chamber H |

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

5. MAXIMUM PERMISSIBLE RF EXPOSURE

5.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3–3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0–30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1500 | | | f/300 | 6 |
| 1500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|-----------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | | | f/1500 | 30 |
| 1500–100,000 | | | 1.0 | 30 |

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

5.2. IC RULES

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

Table 5
Exposure Limits for Persons Not Classified As RF and Microwave Exposed Workers (Including the General Public)

| 1 Frequency (MHz) | 2 Electric Field Strength; rms (V/m) | 3 Magnetic Field Strength; rms (A/m) | 4 Power Density (W/m ²) | 5 Averaging Time (min) |
|-------------------------|---|---|--|---------------------------------|
| 0.003–1 | 280 | 2.19 | | 6 |
| 1–10 | $280/f$ | $2.19/f$ | | 6 |
| 10–30 | 28 | $2.19/f$ | | 6 |
| 30–300 | 28 | 0.073 | 2* | 6 |
| 300–1 500 | $1.585f^{0.5}$ | $0.0042f^{0.5}$ | $f/150$ | 6 |
| 1 500–15 000 | 61.4 | 0.163 | 10 | 6 |
| 15 000–150 000 | 61.4 | 0.163 | 10 | $616\,000/f^{1.2}$ |
| 150 000–300 000 | $0.158f^{0.5}$ | $4.21 \times 10^{-4}f^{0.5}$ | $6.67 \times 10^{-5}f$ | $616\,000/f^{1.2}$ |

* Power density limit is applicable at frequencies greater than 100 MHz.

Notes: 1. Frequency, f , is in MHz.
2. A power density of 10 W/m² is equivalent to 1 mW/cm².
3. A magnetic field strength of 1 A/m corresponds to 1.257 microtesla (μT) or 12.57 milligauss (mG).

5.3. EQUATIONS

POWER DENSITY

Power density is given by:

$$S = \text{EIRP} / (4 * \text{Pi} * D^2)$$

Where

S = Power density in mW/cm²

EIRP = Equivalent Isotropic Radiated Power in mW

D = Separation distance in cm

Power density in units of mW/cm² is converted to units of W/m² by multiplying by 10.

DISTANCE

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

Where

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power in mW

S = Power density in mW/cm²

SOURCE-BASED DUTY CYCLE

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

$$\text{Source-based time-averaged EIRP} = (\text{DC} / 100) * \text{EIRP}$$

Where

DC = Duty Cycle in %, as applicable

EIRP = Equivalent Isotropic Radiated Power in W

MIMO AND COLOCATED TRANSMITTERS

For multiple colocated transmitters operating simultaneously in frequency bands where different limits apply:

The Power Density at the specified separation distance is calculated for each transmitter chain or transmitter.

The fraction of the exposure limit is calculated for each chain or transmitter as
(Power Density of chain or transmitter) / (Limit applicable to that chain or transmitter).

The fractions are summed.

Compliance is established if the sum of the fractions is less than or equal to one.

5.4. LIMITS AND IC EXEMPTION

FIXED LIMITS

For operation in the 5 GHz band:

From FCC §1.1310 Table 1 (B), the maximum value of $S = 1.0 \text{ mW/cm}^2$

From IC Safety Code 6, Section 2.2 Table 5 Column 4, $S = 10 \text{ W/m}^2$

INDUSTRY CANADA EXEMPTION

RSS-102 Clause 2.5.2 RF exposure evaluation is required if the separation distance between the user and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 1.5 GHz and the maximum e.i.r.p. of the device is equal to or less than 2.5 W;
- at or above 1.5 GHz and the maximum e.i.r.p. of the device is equal to or less than 5 W.

6. RF EXPOSURE RESULTS

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

(MIMO and/or Colocated transmitters all with same Power Density limit, MPE distance > 20 cm)

Note. the minimum 33cm separation distance is derived from the 5.8 GHz band MPE calculations report(15U21741-E2V3).

Multiple chain or colocated transmitters- **BW 40MHz**

| Band | (GHz) | 5 | 5 |
|-------------------------|-----------------------|---------|---------|
| Mode | | WLAN | WLAN |
| Transmitter | | Chain 0 | Chain 1 |
| Separation Distance | (cm) | 33 | 33 |
| Output Power | (dBm) | 12.06 | 12.64 |
| Antenna Gain | (dBi) | 15.0 | 15.0 |
| Duty Cycle | (%) | 98.5 | 98.5 |
| Source Based EIRP | (mW) | 500.5 | 572.1 |
| FCC Power Density | (mW/cm ²) | 0.04 | 0.04 |
| FCC Power Density Limit | (mW/cm ²) | 1 | 1 |
| IC Power Density | (W/m ²) | 0.366 | 0.418 |
| IC Power Density Limit | (W/m ²) | 10 | 10 |
| Fraction of Limit | (%) | 3.7 | 4.2 |
| Sum of Fractions (%) | 7.8 | | |

Multiple chain or colocated transmitters- **BW 20MHz**

| | | | |
|--------------------------------|------------------|---------|---------|
| Band | (GHz) | 5 | 5 |
| Mode | | WLAN | WLAN |
| Transmitter | | Chain 0 | Chain 1 |
| Separation Distance | (cm) | 33 | 33 |
| Output Power | (dBm) | 10.99 | 11.26 |
| Antenna Gain | (dBi) | 15.0 | 15.0 |
| Duty Cycle | (%) | 98.5 | 98.5 |
| Source Based EIRP | (mW) | 391.2 | 416.3 |
| FCC Power Density | (mW/cm^2) | 0.03 | 0.03 |
| FCC Power Density Limit | (mW/cm^2) | 1 | 1 |
| IC Power Density | (W/m^2) | 0.286 | 0.304 |
| IC Power Density Limit | (W/m^2) | 10 | 10 |
| Fraction of Limit | (%) | 2.9 | 3.0 |
| Sum of Fractions (%) | 5.9 | | |

Multiple chain or colocated transmitters- **BW 10MHz**

| | | | |
|--------------------------------|------------------|---------|---------|
| Band | (GHz) | 5 | 5 |
| Mode | | WLAN | WLAN |
| Transmitter | | Chain 0 | Chain 1 |
| Separation Distance | (cm) | 33 | 33 |
| Output Power | (dBm) | 8.02 | 8.46 |
| Antenna Gain | (dBi) | 15.0 | 15.0 |
| Duty Cycle | (%) | 98.5 | 98.5 |
| Source Based EIRP | (mW) | 197.4 | 218.5 |
| FCC Power Density | (mW/cm^2) | 0.01 | 0.02 |
| FCC Power Density Limit | (mW/cm^2) | 1 | 1 |
| IC Power Density | (W/m^2) | 0.144 | 0.160 |
| IC Power Density Limit | (W/m^2) | 10 | 10 |
| Fraction of Limit | (%) | 1.4 | 1.6 |
| Sum of Fractions (%) | 3.0 | | |

Calculated using the worst case measured power also a tolerance of 0.5 was added to worst case measured power.

Notes:

- 1) For MPE the new KDB 447498 requires the calculations to use the maximum rated power; that power should be declared by the manufacturer, and should not be lower than the measured power. If the power has a tolerance then we also need to check that the measured power is within the tolerance.
- 2) A tolerance value of +/- 0.5 dB was included in the output power values above to cover the output power tolerance of +/-0.5dB under extreme conditions in the real filed as declared by the client.
- 3) The manufacturer configures output power so that the maximum power, after accounting for manufacturing tolerances, will never exceed the maximum power level measured.
- 4) The output power in the tables above is the maximum power per chain among various channels and various modes within the specific band.
- 5) The antenna gain in the tables above is the maximum antenna gain among various channels within the specified band.

END OF REPORT