



Neutron Engineering Inc.

FCC RF EXPOSURE REPORT

FCC ID: 2AAGJDHTS514A

Project No. : 1310C090
Equipment : HOME THEATER SYSTEM
Model : DSW-S514
Applicant : Tymphany HK Limited
Address : Room 1307-8 Dominion Centre 43-59 Queens Road East, WanChai,
Hong Kong, China

According: : **FCC Guidelines for Human Exposure IEEE C95.1**

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL : (0769) 8318-3000 FAX : (0769) 8319-6000



Neutron Engineering Inc.

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Ant.	Brand name	Model Name	Antenna Type	Connector	Gain (dBi)
A	SMSC	DWAM83-TB	Printed	N/A	2.0
B	SMSC	DWAM83-TB	Printed	N/A	2.0

TEST RESULTS

EUT:	HOME THEATER SYSTEM	Model Name :	DSW-S514
Temperature: 24	°C	Relative Humidity:	60 %
Pressure:	1016 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX MODE /CH01, CH02, CH03		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2	1.5849	15.12	32.5087	0.01025535	1	Complies
2	1.5849	14.78	30.0608	0.00948310	1	Complies
2	1.5849	14.25	26.6073	0.00839364	1	Complies

The calculated distance is 20cm