

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057 Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM170900945103

Page: 1 of 8

RF Exposure Evaluation Report

Application No.: SZEM1709009451CR

Applicant: ZHENCHENG TOYS FACTORY

Address of Applicant: CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, China

Manufacturer: ZHENCHENG TOYS FACTORY

Address of Manufacturer: CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, China

Factory: ZHENCHENG TOYS FACTORY

Address of Factory: CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, China

Equipment Under Test (EUT):

EUT Name: R/C CAR

Model No.: Please refer to section 2 ♣

Please refer to section 2 of this report which indicates which model was actually

tested and which were electrically identical.

FCC ID: 2AAGP172801B

Trade mark: CARZON

Standard(s): 47 CFR Part 1.1307

47 CFR Part 1.1310

Date of Receipt: 2017-09-05

Date of Test: 2017-09-05 to 2017-09-14

Date of Issue: 2017-09-14

Test Result: Pass*



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM170900945103

Page: 2 of 8

2 Version

Revision Record						
Version	Chapter	Date	Modifier	Remark		
01		2017-09-14		Original		

Authorized for issue by:		
	(eo ti	
	Leo Li /Project Engineer	
	Eric Fu	
	Eric Fu /Reviewer	



Report No.: SZEM170900945103

Page: 3 of 8

3 Contents

		Page
1	COVER PAGE	1
2	VERSION	2
3	CONTENTS	3
4	GENERAL INFORMATION	4
	4.1 GENERAL DESCRIPTION OF EUT	4
	4.2 TEST LOCATION	5
	4.3 Test Facility	5
	4.4 DEVIATION FROM STANDARDS	6
	4.5 ABNORMALITIES FROM STANDARD CONDITIONS	6
	4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5	RF EXPOSURE EVALUATION	7
	5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	
	5.1.1 Limits	7
	5.1.2 Test Procedure	7
	4.1.3 EUT RF EXPOSURE EVALUATION.	8



Report No.: SZEM170900945103

Page: 4 of 8

4 General Information

4.1 General Description of EUT

Power supply:	Nickel-chromium Battery: 3.7V 380mAh rechargeable battery which charged by USB port for car
Test voltage	DC 3.7V
Cable:	USB cable: 60cm unshielded
Type of Modulation:	IEEE for 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE for 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11nHT20: OFDM (64QAM, 16QAM, QPSK, BPSK)
Operating Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Number:	IEEE 802.11b/g, IEEE 802.11n(HT20): 11 Channels
Channels Step:	Channels with 5MHz step
Antenna Type:	Integral
Antenna Gain:	2.5 dBi
EIRP:	13.21dBm(20.94mW)*
*	The EIRP data refer to the report SZEM170900945101.

Remark:

Model No.: 172801,172802,333-P011A,333-P012A,333-P013A,333-P014A,333-P015A,333-SL01B,333-SL01A,171801B,171802B,171801A,171802A,171803,171804,171605A,171605B,333-MT01B,333-MT01A,333-GS01A,333-GS02B,333-GS03B,333-GS04B,333-GS05B,333-GS06B,333-GS07B,333-GS08B,333-GS09B,,333-GS02A,333-GS03A,333-GS04A,333-GS05A,333-GS06A,333-GS07A,333-GS08A,333-GS09A,333-G02,333-G03,333-G04,333-G05,333-G06,333-G07,333-G08,333-G09

Only the model 172801 was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for all the above models, with only difference on the shell's colour.



Report No.: SZEM170900945103

Page: 5 of 8

4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

FCC –Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



Report No.: SZEM170900945103

Page: 6 of 8

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None

4.6 Other Information Requested by the Customer

None.



Report No.: SZEM170900945103

Page: 7 of 8

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34 1.34–30 30–300 300–1500 1500–100,000	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30 30 30			

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4*Pi*R2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Report No.: SZEM170900945103

Page: 8 of 8

4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 2.5dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.78 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Wifi2.4G:

Test Mode	Frequency (MHz)	Max. Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm²)	MPE Ratios	Result
11B	2462	9.49	8.89	0.0031	1.0	0.0031	PASS
11G	2462	13.20	20.89	0.0074	1.0	0.0074	PASS
11N20 SISO	2462	13.21	20.94	0.0074	1.0	0.0074	PASS

Note: Refer to report No. SZEM170900945101 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.