



# FCC 47 CFR PART 15 SUBPART C

## TEST REPORT

*For*

**Applicant:** Shenzhen Wanchuangbo Industry Development Co., Ltd.

**Address:** 3rd Floor, No. 20, Yangmei Road, Bantian Street, Longgang,  
Shenzhen, China

**Product Name:** Tablet PC

**Model Name:** CT720

**Brand Name:** iDeaUSA

**FCC ID:** 2AAGRCT720

**Report No.:** DPH20130920F02

**Date of Issue:** September 23, 2013

**Issued by:** Shenzhen Top-cert Service Co., Ltd.

**Address:** Room 506, Hongyu Commercial Building, Gushu 2nd Road,  
Baoan District, Shenzhen, China

**Tel:** 0755-61196328

**Fax:** 0755-61196328

**E-mail:** [service@top-cert.com](mailto:service@top-cert.com)

**Web:** [www.top-cert.com](http://www.top-cert.com)

*The report consists 60 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by Top-cert. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.*

## TABLE OF CONTENTS

|   |           |
|---|-----------|
| <b>1. VERIFICATION OF CONFORMITY .....</b>              | <b>3</b>  |
| <b>2. GENERAL INFORMATION.....</b>                      | <b>4</b>  |
| 2.1 Product Information .....                           | 4         |
| 2.2 Objective .....                                     | 5         |
| 2.3 Test Standards and Results.....                     | 5         |
| <b>2.4 Environmental Conditions.....</b>                | <b>5</b>  |
| <b>3. TEST FACILITY .....</b>                           | <b>6</b>  |
| 3.1 Test Facility.....                                  | 6         |
| 3.2 General Test Procedures.....                        | 6         |
| 3.3 FCC Part 15.205 Restricted Bands of Operations..... | 7         |
| <b>4. TEST EQUIPMENT LIST .....</b>                     | <b>8</b>  |
| <b>5. 47 CFR Part 15 C 15.247 Requirements.....</b>     | <b>9</b>  |
| 5.1 6dB Bandwidth .....                                 | 9         |
| 5.2 Peak Output Power .....                             | 13        |
| 5.3 Conducted Spurious Emission .....                   | 17        |
| 5.4 Band Edge .....                                     | 21        |
| 5.5 Power Spectral Density (PSD) .....                  | 24        |
| 5.6 Conducted Emission .....                            | 28        |
| 5.7 Radiated Emission .....                             | 31        |
| <b>APPENDIX 1 .....</b>                                 | <b>48</b> |
| <b>PHOTOGRAPHS OF TEST SETUP .....</b>                  | <b>48</b> |
| <b>APPENDIX 2.....</b>                                  | <b>52</b> |
| <b>PHOTOGRAPHS OF EUT .....</b>                         | <b>52</b> |

| Revision History |                    |                     |
|------------------|--------------------|---------------------|
| Issue            | Date               | Reason for Revision |
| 1.0              | September 23, 2013 | First edition       |
|                  |                    |                     |

## 1. VERIFICATION OF CONFORMITY

|                                  |   |
|----------------------------------|---|
| <b>Equipment Under Test:</b>     | Tablet PC   |
| <b>Brand Name:</b>               | iDeaUSA   |
| <b>Model Number:</b>             | CT720   |
| <b>Series Model Name:</b>        | CT720X(X=A-Z)   |
| <b>Difference description:</b>   | Only the difference in model name.  |
| <b>FCC ID:</b>                   | 2AAGRCT720  |
| <b>Applicant:</b>                | Shenzhen Wanchuangbo Industry Development Co., Ltd.<br>3rd Floor, No. 20, Yangmei Road, Bantian Street, Longgang, Shenzhen, China |
| <b>Manufacturer:</b>             | Shenzhen Wanchuangbo Industry Development Co., Ltd.<br>3rd Floor, No. 20, Yangmei Road, Bantian Street, Longgang, Shenzhen, China |
| <b>Technical Standards:</b>      | 47 CFR Part 15 Subpart C  |
| <b>File Number:</b>              | DPH20130920F02  |
| <b>Date of test:</b>             | September 10, 2013- September 23, 2013  |
| <b>Date of issue:</b>            | September 23, 2013  |
| <b>Condition of Test Sample:</b> | Normal  |
| <b>Test Result:</b>              | PASS  |

The above equipment was tested by Top-cert. For compliance with the requirements set forth in FCC rules and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Tested by (+ signature):

*Rex Luo*

Rex Luo  
Test Engineer



Approved by (+ signature):

*Joe Jia*

Joe Jia  
Manager

## 2. GENERAL INFORMATION

### 2.1 Product Information

|                       |  |
|-----------------------|--|
| Description:          | Tablet PC  |
| Brand Name:           | iDeaUSA  |
| Model Name:           | CT720  |
| Frequency Range:      | 2412MHz-2462MHz                                    |
| Test Frequency:       | Low: 2412MHz, Mid: 2437MHz, High: 2462MHz          |
| Number of Channels:   | 11 Channels  |
| Modulation Technique: | IEEE 802.11b mode: DSSS<br>IEEE 802.11g mode: OFDM |
| Antenna Type:         | Internal   |
| Antenna Gain:         | 0 dBi  |
| Power Supply:         | DC 3.7V by Battery<br>DC 5V by AC/DC adapter       |
| Temperature Range:    | -20°C ~ +50°C                                      |

**NOTE:**

1. For more detailed features description about the EUT, please refer to User's Manual.

## 2.2 Objective

The objective of the report is to perform tests according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

| No. | Identity                        | Document Title          |
|-----|---------------------------------|-------------------------|
| 1   | 47 CFR Part 15(10-1-09 Edition) | Radio Frequency Devices |

## 2.3 Test Standards and Results

Test items and the results are as bellow:

| No. | Section                       | Description                 | Result | Date of Test |
|-----|-------------------------------|-----------------------------|--------|--------------|
| 1   | 15.247(a)(2)                  | 6dB Bandwidth               | PASS   | 2013-09-21   |
| 2   | 15.247(b)(3)                  | Peak Output Power           | PASS   | 2013-09-21   |
| 3   | 15.247(d)                     | conducted spurious emission | PASS   | 2013-09-21   |
| 4   | 15.247(d)                     | Band Edge                   | PASS   | 2013-09-21   |
| 5   | 15.247(e)                     | Power Spectral Density      | PASS   | 2013-09-21   |
| 6   | 15.207                        | Conducted Emission          | PASS   | 2013-09-21   |
| 7   | 15.247(d)<br>15.205<br>15.209 | Radiated Emission           | PASS   | 2013-09-23   |

Note: 1. The test result judgment is decided by the limit of measurement standard  
2. The information of measurement uncertainty is available upon the customer's request.

## 2.4 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 kPa

### 3. TEST FACILITY

#### 3.1 Test Facility

|                       |  |
|-----------------------|--|
| Test Site:            | BZT Testing Technology Co., Ltd.   |
| Location:             | 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.   |
| Description:          | There is one 3m semi-anechoic an area test sites and two line conducted labs for final test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009 and CISPR 16 requirements.<br>The FCC Registration Number is <b>701733</b>  |
| Site Filing:          | The site description is on file with the Federal Communications Commission, 7435 Oakland Mills Road, Columbia, MD 21046.   |
| Instrument Tolerance: | All measuring equipment is in accord with ANSI C63.4 and CISPR 16 requirements that meet industry regulatory agency and accreditation agency requirement.  |
| Ground Plane:         | Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna. It has no holes or gaps having longitudinal dimensions larger than one-tenth of a wavelength at the highest frequency of measurement up to 1GHz. |

#### 3.2 General Test Procedures

##### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4:2009, Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4:2009.

### **3.3 FCC Part 15.205 Restricted Bands of Operations**

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz                      | MHz                   | MHz             | GHz              |
|--------------------------|-----------------------|-----------------|------------------|
| 0.090 0.110              | 16.42 - 16.423        | 399.9 - 410     | 4.5 - 5.15       |
| <sup>1</sup> 0.495 0.505 | 16.69475 - 16.69525   | 608 - 614       | 5.35 - 5.46      |
| 2.1735 2.1905            | 16.80425 - 16.80475   | 960 - 1240      | 7.25 - 7.75      |
| 4.125 - 4.128            | 25.5 - 25.67          | 1300 - 1427     | 8.025 - 8.5      |
| 4.17725 - 4.17775        | 37.5 - 38.25          | 1435 - 1626.5   | 9.0 - 9.2        |
| 4.20725 - 4.20775        | 73 - 74.6             | 1645.5 - 1646.5 | 9.3 - 9.5        |
| 6.215 - 6.218            | 74.8 - 75.2           | 1660 - 1710     | 10.6 - 12.7      |
| 6.26775 - 6.26825        | 108 - 121.94          | 1718.8 - 1722.2 | 13.25 - 13.4     |
| 6.31175 - 6.31225        | 123 - 138             | 2200 - 2300     | 14.47 - 14.5     |
| 8.291 - 8.294            | 149.9 - 150.05        | 2310 - 2390     | 15.35 - 16.2     |
| 8.362 8.366              | 156.52475 - 156.52525 | 2483.5 - 2500   | 17.7 - 21.4      |
| 8.37625 - 8.38675        | 156.7 - 156.9         | 2655 - 2900     | 22.01 - 23.12    |
| 8.41425 - 8.41475        | 162.0125 - 167.17     | 3260 - 3267     | 23.6 - 24.0      |
| 12.29 - 12.293           | 167.72 - 173.2        | 3332 - 3339     | 31.2 - 31.8      |
| 12.51975 - 12.52025      | 240 - 285             | 3345.8 - 3358   | 36.43 - 36.5     |
| 12.57675 - 12.57725      | 322 - 335.4           | 3600 - 4400     | ( <sup>2</sup> ) |
| 13.36 13.41              |                       |                 |                  |

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasipeak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

#### 4. TEST EQUIPMENT LIST

**Instrumentation:** The following list contains equipment used at MOST for testing. The equipment conforms to the CISPR 16-1/ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

| No. | Equipment                      | Manufacturer | Model No.   | S/N          | Calibration due date |
|-----|--------------------------------|--------------|-------------|--------------|----------------------|
| 1   | Spectrum Analyzer              | Agilent      | E4407B      | 160400005    | Jul. 06. 2014        |
| 2   | Test Receiver                  | R&S          | ESPI        | 101318       | Jul. 06. 2014        |
| 3   | Bilog Antenna                  | TESEQ        | CBL6111D    | 31216        | Jul. 06. 2014        |
| 4   | 50Ω Coaxial Switch             | Anritsu      | MP59B       | 6200264416   | Jul. 06. 2014        |
| 5   | Spectrum Analyzer              | ADVANTEST    | R3132       | 150900201    | Jul. 06. 2014        |
| 6   | Horn Antenna                   | EM           | EM-AH-20180 | 2011071402   | Jul. 06. 2014        |
| 7   | Horn Ant                       | Schwarzbeck  | BBHA 9170   | 9170-181     | Jul. 06. 2014        |
| 8   | Amplifier                      | EM           | EM-30180    | 060538       | Jul. 06. 2014        |
| 9   | Loop Antenna                   | ARA          | PLA-2030/B  | 1029         | Jul. 06. 2014        |
| 10  | Power Meter                    | R&S          | NRVS        | 100696       | Jul. 06. 2014        |
| 11  | Signal Generator               | R&S          | SMT 06      | 832080/007   | Jul. 31, 2014        |
| 12  | Temperature & Humidity Chamber | GIANT FORCE  | GTH-056P    | GF-94454-1   | Jul. 22, 2014        |
| 13  | Power Sensor (AV)              | R&S          | URV5-Z4     | 0395.1619.05 | Feb. 09, 2014        |
| 14  | EMI Test Receiver              | R&S          | ESCI-7      | 101318       | Jul. 06, 2014        |
| 15  | Antenna Mast                   | EM           | SC100_1     | N/A          | N/A                  |
| 16  | Turn Table                     | EM           | SC100       | 060531       | N/A                  |
|     |                                |              |             |              |                      |

**NOTE:** Equipments listed above have been calibrated and are in the period of validation.



## 5. 47 CFR Part 15 C 15.247 Requirements

### 5.1 6dB Bandwidth

#### 5.1.1 Definition

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### 5.1.2 Test Description

The EUT is powered by the Battery, is coupled to the Spectrum Analyzer (SA) through the Attenuator/DC Block. The path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and is set to operate at maximum power. The RF load attached to the EUT antenna terminal is 50Ohm.





Figure 1: RF Test Setup

#### 5.1.3 Test Result


The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.

## 802.11b Test Mode


| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Limits (kHz) | Result |
|---------|-----------------|----------------------|--------------|--------|
| 1       | 2412            | 6.059                | ≥500         | PASS   |
| 6       | 2437            | 7.074                | ≥500         | PASS   |
| 11      | 2462            | 7.074                | ≥500         | PASS   |



(CH Low)




(CH Mid)




(CH High)

## 802.11g Test Mode


| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Limits (kHz) | Result |
|---------|-----------------|----------------------|--------------|--------|
| 1       | 2412            | 15.133               | ≥500         | PASS   |
| 6       | 2437            | 15.975               | ≥500         | PASS   |
| 11      | 2462            | 15.137               | ≥500         | PASS   |



(CH Low)



(CH Mid)



(CH High)

## 5.2 Peak Output Power

### 5.2.1 Definition

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

### 5.2.2 Test Description


See section 5.1.2 of this report.

### 5.2.3 Test Result


The lowest and highest data rate are selected to perform testing to verify the conducted RF output peak power of the Module. Only the maximum conducted RF output peak power recorded in the report.

#### 802.11b Test Mode


| Channel | Frequency (MHz) | Rate (Mbps) | Measured Output Peak Power |          | Limit |   | Verdict |
|---------|-----------------|-------------|----------------------------|----------|-------|---|---------|
|         |                 |             | dBm                        | W        | dBm   | W |         |
| 1       | 2412            | 1Mbps       | 8.61                       | 0.007261 | 30    | 1 | PASS    |
| 6       | 2437            | 1Mbps       | 9.21                       | 0.008337 |       |   | PASS    |
| 11      | 2462            | 1Mbps       | 9.07                       | 0.008072 |       |   | PASS    |



(CH Low)




(CH Mid)




(CH High)

## 802.11g Test Mode


| Channel | Frequency (MHz) | Rate (Mbps) | Measured Output Peak Power |          | Limit |   | Verdict |
|---------|-----------------|-------------|----------------------------|----------|-------|---|---------|
|         |                 |             | dBm                        | W        | dBm   | W |         |
| 1       | 2412            | 6Mbps       | 9.14                       | 0.008204 | 30    | 1 | PASS    |
| 6       | 2437            | 6Mbps       | 8.85                       | 0.007674 |       |   | PASS    |
| 11      | 2462            | 6Mbps       | 9.04                       | 0.008017 |       |   | PASS    |



(CH Low)



(CH Mid)



(CH High)



### 5.3 Conducted Spurious Emission

#### 5.3.1 Definition

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.


#### 5.3.2 Test Description

See section 5.1.2 of this report.


#### 5.3.3 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.


#### 802.11b Test Mode



(CH Low, 30MHz to 25GHz)




(CH Mid, 30MHz to 25GHz)




(CH High, 30MHz to 25GHz)

Note: The power of the Module transmitting frequency should be ignored.


## 802.11g Test Mode



(CH Low, 30MHz to 25GHz)



(CH Mid, 30MHz to 25GHz)



(CH High, 30MHz to 25GHz)

Note: The power of the Module transmitting frequency should be ignored.

## 5.4 Band Edge

### 5.4.1 Definition

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.


### 5.4.2 Test Description

See section 5.1.2 of this report.


### 5.4.3 Test Result

The EUT operates at continuous transmit test mode. The test data of the lowest and highest channels are tested to verify the band edge emissions.

#### 802.11b Test Mode




(CH Low)




(CH High)

802.11g Test Mode



(CH Low)



(CH High, Peak)

## 5.5 Power Spectral Density (PSD)

### 5.5.1 Definition

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.5.2 Test Description


See section 5.1.2 of this report.

### 5.5.3 Test Result

The lowest, middle and highest channels are tested to verify the power spectral density.


#### 802.11b Test Mode

| Channel | Frequency (MHz) | PSD (dBm) | Limits(dBm) | Result |
|---------|-----------------|-----------|-------------|--------|
| 1       | 2412            | -5.16     | $\leq 8$    | PASS   |
| 6       | 2437            | -5.11     | $\leq 8$    | PASS   |
| 11      | 2462            | -5.79     | $\leq 8$    | PASS   |




(CH Low)






(CH Mid)




(CH High)

## 802.11g Test Mode


| Channel | Frequency (MHz) | PSD (dBm) | Limits(dBm) | Result |
|---------|-----------------|-----------|-------------|--------|
| 1       | 2412            | -8.23     | $\leq 8$    | PASS   |
| 6       | 2437            | -8.92     | $\leq 8$    | PASS   |
| 11      | 2462            | -8.44     | $\leq 8$    | PASS   |



(CH Low)



(CH Mid)



(CH High)

## 5.6 Conducted Emission

### 5.6.1 Definition

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN).


| Frequency     | Maximum RF Line Voltage |                |
|---------------|-------------------------|----------------|
|               | Q.P.( dBuV)             | Average( dBuV) |
| 150kHz-500kHz | 66-56                   | 56-46          |
| 500kHz-5MHz   | 56                      | 46             |
| 5MHz-30MHz    | 60                      | 50             |

**Note:**

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz


### 5.6.2 Test Description

The EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and is set to operate at maximum power.



### 5.6.3 Test Result

#### Conducted Emission Measurement



Site site #1

Phase: **N**

Temperature: 26

Limit: FCC Part 15 Class B QP

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Tablet PC

M/N: CT720


Mode: WIFI

Note:

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   | *   | 0.2232       | 36.43                    | 11.85                   | 48.28                    | 62.70         | -14.42     | QP       |         |
| 2   |     | 1.7220       | 30.48                    | 9.28                    | 39.76                    | 56.00         | -16.24     | QP       |         |
| 3   |     | 3.3620       | 27.37                    | 10.36                   | 37.73                    | 56.00         | -18.27     | QP       |         |
| 4   |     | 5.2820       | 14.97                    | 11.83                   | 26.80                    | 60.00         | -33.20     | QP       |         |
| 5   |     | 10.7540      | 9.49                     | 9.00                    | 18.49                    | 60.00         | -41.51     | QP       |         |

\*:Maximum data    x:Over limit    !:over margin

## Conducted Emission Measurement



Site site #1

Phase: **L1**

Temperature: 26

Limit: FCC Part 15 Class B QP

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Tablet PC

M/N: CT720

Mode: WIFI

Note:

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.1900       | 38.80                    | 11.40                   | 50.20                    | 64.04         | -13.84     | QP       |         |
| 2   | *   | 1.5660       | 36.26                    | 9.43                    | 45.69                    | 56.00         | -10.31     | QP       |         |
| 3   |     | 2.7980       | 29.51                    | 9.80                    | 39.31                    | 56.00         | -16.69     | QP       |         |
| 4   |     | 3.6220       | 24.98                    | 10.62                   | 35.60                    | 56.00         | -20.40     | QP       |         |
| 5   |     | 7.7940       | 17.41                    | 10.32                   | 27.73                    | 60.00         | -32.27     | QP       |         |

\*:Maximum data    x:Over limit    !:over margin

## 5.7 Radiated Emission

### 5.7.1 Definition

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).


According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength ( $\mu\text{V}/\text{m}$ ) | Measurement Distance (m) |
|-----------------|---|--------------------------|
| 0.009 - 0.490   | $2400/F(\text{kHz})$                      | 300                      |
| 0.490 - 1.705   | $24000/F(\text{kHz})$                     | 30                       |
| 1.705 - 30.0    | 30  | 30                       |
| 30 - 88         | 100                                       | 3                        |
| 88 - 216        | 150                                       | 3                        |
| 216 - 960       | 200                                       | 3                        |
| Above 960       | 500                                       | 3                        |


As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

### 5.7.2 Test Description


#### A. Test Setup:



#### Blow 1GHz:





**Above 1GHz:****B. Test procedures**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:  
Below 1GHz: RBW=100 kHz / VBW=300 kHz / Sweep=AUTO  
Above 1GHz : (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO  
(b) AVERAGE: RBW=1MHz / VBW=1MHz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.


**5.7.3 Test Result****Form 9 KHz to 30MHz:**

| Freq.<br>(MHz) | Ant. Pol<br>H/V | Peak<br>Reading<br>(dBuV) | Ant. / CL<br>CF<br>(dB) | Actual Fs<br>Peak<br>(dBuV/m) | Peak<br>Limit<br>(dBuV/m) | Peak<br>Margin<br>(dB) |
|----------------|-----------------|---------------------------|-------------------------|-------------------------------|---------------------------|------------------------|
|                | H               |                           |                         |                               |                           |                        |
|                | H               |                           |                         |                               |                           |                        |
|                | H               |                           |                         |                               |                           |                        |
| N/A            |                 |                           |                         |                               |                           | >20                    |
|                | V               |                           |                         |                               |                           |                        |
|                | V               |                           |                         |                               |                           |                        |
|                | V               |                           |                         |                               |                           |                        |
| N/A            |                 |                           |                         |                               |                           | >20                    |

**-Note: No test data was detected in below 30MHz.**

## Below 1 GHz

## Radiated Emission Measurement



Site site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Part15 B 3M Radiation

Power: AC 120V/60Hz

Humidity: 61 %

EUT: Tablet PC

Distance:

M/N: CT720


Mode: WIFI

Note:

| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   | Antenna Height | Table Degree |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dBuV/m | dB     | cm             | degree       | Comment |
| 1   |     | 166.7700 | 15.49         | 17.20          | 32.69       | 43.50  | -10.81 | peak           |              |         |
| 2   |     | 500.4500 | 16.07         | 21.40          | 37.47       | 46.00  | -8.53  | peak           |              |         |
| 3   | *   | 566.4099 | 14.94         | 22.79          | 37.73       | 46.00  | -8.27  | peak           |              |         |
| 4   |     | 633.3400 | 8.86          | 23.80          | 32.66       | 46.00  | -13.34 | peak           |              |         |
| 5   |     | 865.1700 | 4.44          | 27.05          | 31.49       | 46.00  | -14.51 | peak           |              |         |

\*:Maximum data    x:Over limit    !:over margin

## Radiated Emission Measurement



Site site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Part15 B 3M Radiation

Power: AC 120V/60Hz

Humidity: 61 %

EUT: Tablet PC

Distance:

M/N: CT720

Mode: WIFI

Note:

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Antenna<br>Height<br>cm | Table<br>Degree<br>degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|-------------------------|---------------------------|---------|
| 1   | *   | 71.7100      | 24.20                    | 11.68                   | 35.88                      | 40.00           | -4.12      | peak     |                         |                           |         |
| 2   |     | 184.2300     | 18.81                    | 16.62                   | 35.43                      | 43.50           | -8.07      | peak     |                         |                           |         |
| 3   |     | 500.4500     | 10.90                    | 21.40                   | 32.30                      | 46.00           | -13.70     | peak     |                         |                           |         |
| 4   |     | 834.1300     | 7.68                     | 27.08                   | 34.76                      | 46.00           | -11.24     | peak     |                         |                           |         |
| 5   |     | 960.2300     | 7.78                     | 28.00                   | 35.78                      | 54.00           | -18.22     | peak     |                         |                           |         |

\*:Maximum data    x:Over limit    !:over margin

**Above 1 GHz****Operation Mode:** TX/ IEEE 802.11b/CH Low**Test Date:** 2013-09-21**Temperature:** 20°C**Humidity:** 65 % RH

| Freq. | Ant. Pol | Peak    | AV      | Ant. / CL | Actual Fs |        | Peak   | AV     | AV     |
|-------|----------|---------|---------|-----------|-----------|--------|--------|--------|--------|
| (MHz) | H/V      | Reading | Reading | CF        |           |        | Limit  | Limit  | Margin |
|       |          | dBuV    | dBuV    | dB        | Peak      | AV     | dBuV/m | dBuV/m | dB     |
|       |          |         |         |           | dBuV/m    | dBuV/m |        |        |        |
| 4824  | V        | 43.53   | 21.84   | 21.24     | 64.77     | 43.08  | 74     | 54     | -10.92 |
| N/A   | H        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
| 4824  | H        | 42.15   | 20.71   | 21.24     | 63.39     | 41.95  | 74     | 54     | -12.05 |
| N/A   | H        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11b/CH Mid**Test Date:** 2013-09-21**Temperature:** 20°C**Humidity:** 65 % RH

| Freq. | Ant. Pol | Peak    | AV      | Ant. / CL | Actual Fs |        | Peak   | AV     | AV     |
|-------|----------|---------|---------|-----------|-----------|--------|--------|--------|--------|
| (MHz) | H/V      | Reading | Reading | CF        |           |        | Limit  | Limit  | Margin |
|       |          | dBuV    | dBuV    | dB        | Peak      | AV     | dBuV/m | dBuV/m | dB     |
|       |          |         |         |           | dBuV/m    | dBuV/m |        |        |        |
| 4874  | V        | 43.83   | 21.86   | 22.11     | 65.94     | 43.97  | 74     | 54     | -10.03 |
| N/A   | V        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
| 4874  | H        | 43.4    | 23.29   | 22.11     | 65.51     | 45.4   | 74     | 54     | -8.60  |
| N/A   | H        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11b/CH High**Test Date:** 2013-09-21**Temperature:** 20°C**Humidity:** 65 % RH

| Freq. | Ant. Pol | Peak    | AV      | Ant. / CL | Actual Fs |        | Peak   | AV     | AV     |
|-------|----------|---------|---------|-----------|-----------|--------|--------|--------|--------|
| (MHz) | H/V      | Reading | Reading | CF        |           |        | Limit  | Limit  | Margin |
|       |          | dBuV    | dBuV    | dB        | Peak      | AV     | dBuV/m | dBuV/m | dB     |
|       |          |         |         |           | dBuV/m    | dBuV/m |        |        |        |
| 4924  | V        | 42.02   | 20.1    | 22.56     | 64.58     | 42.66  | 74     | 54     | -11.34 |
| N/A   | V        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
| 4924  | H        | 44.75   | 22.88   | 22.56     | 67.31     | 45.44  | 74     | 54     | -8.56  |
| N/A   | H        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11g/CH Low**Test Date:** 2013-09-21**Temperature:** 20°C**Humidity:** 65 % RH

| Freq. | Ant. Pol | Peak    | AV      | Ant. / CL | Actual Fs |        | Peak   | AV     | AV     |
|-------|----------|---------|---------|-----------|-----------|--------|--------|--------|--------|
| (MHz) | H/V      | Reading | Reading | CF        |           |        | Limit  | Limit  | Margin |
|       |          | dBuV    | dBuV    | dB)       | Peak      | AV     | dBuV/m | dBuV/m | dB     |
|       |          |         |         |           | dBuV/m    | dBuV/m |        |        |        |
| 4824  | V        | 44.66   | 23.61   | 21.24     | 65.9      | 44.85  | 74     | 54     | -9.15  |
| N/A   | V        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
| 4824  | H        | 44.24   | 23.91   | 21.24     | 65.48     | 45.15  | 74     | 54     | -8.85  |
| N/A   | H        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



**Operation Mode:** TX/ IEEE 802.11g/CH Mid**Test Date:** 2013-09-21**Temperature:** 20°C**Humidity:** 65 % RH

| Freq. | Ant. Pol | Peak    | AV      | Ant. / CL | Actual Fs |        | Peak   | AV     | AV     |
|-------|----------|---------|---------|-----------|-----------|--------|--------|--------|--------|
| (MHz) | H/V      | Reading | Reading | CF        |           |        | Limit  | Limit  | Margin |
|       |          | dBuV    | dBuV    | dB)       | Peak      | AV     | dBuV/m | dBuV/m | dB     |
|       |          |         |         |           | dBuV/m    | dBuV/m |        |        |        |
| 4874  | V        | 43.77   | 23.36   | 22.11     | 65.88     | 45.47  | 74     | 54     | -8.53  |
| N/A   | V        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
| 4874  | H        | 44.09   | 23.07   | 22.11     | 66.2      | 45.18  | 74     | 54     | -8.82  |
| N/A   | H        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11g/CH High**Test Date:** 2013-09-21**Temperature:** 20°C**Humidity:** 65 % RH

| Freq. | Ant. Pol | Peak    | AV      | Ant. / CL | Actual Fs |        | Peak   | AV     | AV     |
|-------|----------|---------|---------|-----------|-----------|--------|--------|--------|--------|
| (MHz) | H/V      | Reading | Reading | CF        |           |        | Limit  | Limit  | Margin |
|       |          | dBuV    | dBuV    | dB)       | Peak      | AV     | dBuV/m | dBuV/m | dB     |
|       |          |         |         |           | dBuV/m    | dBuV/m |        |        |        |
| 4924  | V        | 43.84   | 23.33   | 22.56     | 66.4      | 45.89  | 74     | 54     | -8.11  |
| N/A   | V        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
| 4924  | H        | 42.48   | 21.88   | 22.56     | 65.04     | 44.44  | 74     | 54     | -9.56  |
| N/A   | H        |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |
|       |          |         |         |           |           |        |        |        |        |


**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).


# Test Restricted Range of "2.31GHz to 2.390GHz" and "2.4835GHz to 2.500GHz"

## 802.11b Test Mode


| Fre. (MHz) | Measured Level (dBuV) | Limit (dBuV) | Margin (dB) | Height (cm) | Azimuth (deg) | Polarization | Detector |
|------------|-----------------------|--------------|-------------|-------------|---------------|--------------|----------|
| 2390.00    | 48.72                 | 74.00        | 25.28       | 100.00      | 90.00         | Vertical     | Peak     |
|            | 40.52                 | 54.00        | 13.48       | 100.00      | 90.00         | Vertical     | Average  |
| 2483.50    | 49.76                 | 74.00        | 24.24       | 100.00      | 90.00         | Vertical     | Peak     |
|            | 41.86                 | 54.00        | 12.14       | 100.00      | 90.00         | Vertical     | Average  |




(CH Low, Peak)



(CH Low, Average)




(CH High, Peak)




(CH High, Average)

## 802.11g Test Mode


| Fre. (MHz) | Measured Level (dBuV) | Limit (dBuV) | Margin (dB) | Height (cm) | Azimuth (deg) | Polarization | Detector |
|------------|-----------------------|--------------|-------------|-------------|---------------|--------------|----------|
| 2390.00    | 57.28                 | 74.00        | 16.72       | 100.00      | 90.00         | Vertical     | Peak     |
|            | 46.90                 | 54.00        | 7.10        | 100.00      | 90.00         | Vertical     | Average  |
| 2483.50    | 60.18                 | 74.00        | 13.82       | 100.00      | 90.00         | Vertical     | Peak     |
|            | 47.64                 | 54.00        | 6.36        | 100.00      | 90.00         | Vertical     | Average  |




(CH Low, Peak)



(CH Low, Average)



(CH High, Peak)



(CH High, Average)


**APPENDIX 1**  
**PHOTOGRAPHS OF TEST SETUP**



CE TEST SETUP



RE TEST SETUP



CONDUCTED TEST SETUP



**APPENDIX 2  
PHOTOGRAPHS OF EUT**



FRONT VIEW OF SAMPLE



BACK VIEW OF SAMPLE



LEFT VIEW OF SAMPLE



RIGHT VIEW OF SAMPLE





UP VIEW OF SAMPLE



DOWN VIEW OF SAMPLE



PHOTO OF FULL VIEW






INTERNAL PHOTO OF SAMPLE -1




INTERNAL PHOTO OF SAMPLE - 2



INTERNAL PHOTO OF SAMPLE - 3




INTERNAL PHOTO OF SAMPLE - 4






INTERNAL PHOTO OF SAMPLE - 5



INTERNAL PHOTO OF SAMPLE - 5



TOP VIEW OF MODUEL



BACK VIEW OF MODUEL



-----END OF REPORT-----