

FCC RF Test Report


APPLICANT : Paden LLC
EQUIPMENT : Electronic Display Device
MODEL NAME : DP75SDI
FCC ID : 2AAIE-0610
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was completely tested on Jun. 06, 2013. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Feature of Equipment Under Test.....	5
1.3 Product Specification of Equipment Under Test	5
1.4 Modification of EUT	5
1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	6
1.6 Testing Site.....	6
1.7 Applied Standards	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Test Mode.....	7
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration and system.....	9
2.4 Measurement Results Explanation Example	9
3 TEST RESULT	10
3.1 Conducted Output Power Measurement.....	10
3.2 Peak-to-Average Ratio	12
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	26
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	32
3.5 Band Edge Measurement.....	52
3.6 Conducted Spurious Emission Measurement	65
3.7 Field Strength of Spurious Radiation Measurement	81
3.8 Frequency Stability Measurement.....	95
4 LIST OF MEASURING EQUIPMENT	100
5 UNCERTAINTY OF EVALUATION	101

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG332112-04	Rev. 01	Initial issue of report	Jul. 24, 2013
FG332112-04	Rev. 02	Update report for revising description of conducted output power measurement and measuring equipment	Aug. 01, 2013

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	RSS-132 (5.4) RSS-133 (6.4)	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	RSS-132 (5.4) RSS-133(6.4)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	RSS-132(5.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(b)	RSS-GEN(4.6.1) RSS-133(2.3)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Band Edge Measurement	< $43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Conducted Spurious Emission	< $43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Field Strength of Spurious Radiation	< $43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 16.55 dB at 13160.000 MHz
3.8	§2.1055 §22.355 §24.235	RSS-132(5.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

Paden LLC

699 Walnut Street, Suite 400, 4th Floor, Des Moines, Iowa, 50309

1.2 Feature of Equipment Under Test

Product Feature	
Equipment	Electronic Display Device
Model Name	DP75SDI
FCC ID	2AAIE-0610
EUT supports Radios application	GSM/EGPRS/WCDMA/HSDPA/ WLAN 11bgn

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.3 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 32.10 dBm GSM1900 : 29.76 dBm WCDMA Band V : 22.13 dBm WCDMA Band II : 22.00 dBm
Antenna Type	Fixed Internal Antenna
Type of Modulation	GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink)

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (% , Hz, ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	1.1885	0.04 ppm	246KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.3802	0.05 ppm	246KG7W
Part 22	WCDMA Band V RMC 12.2kbps	QPSK	0.0693	0.04 ppm	4M20F9W
Part 24	GSM1900 GPRS class 8	GMSK	1.4928	0.03 ppm	250KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.6109	0.04 ppm	250KG7W
Part 24	WCDMA Band II RMC 12.2kbps	QPSK	0.3243	0.02 ppm	4M18F9W

1.6 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH02-HY	03CH07-HY	722060/4086B-1

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes in Tablet PC configurations and one test plane in Laptop PC configuration to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 8 Link	■ GPRS class 8 Link
	■ EDGE class 8 Link	■ EDGE class 8 Link
GSM 1900	■ GPRS class 8 Link	■ GPRS class 8 Link
	■ EDGE class 8 Link	■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2kbps Link	■ RMC 12.2kbps Link
WCDMA Band II	■ RMC 12.2kbps Link	■ RMC 12.2kbps Link


Note: The maximum power levels are GPRS multi-slot class 8 mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2kbps mode for WCDMA band V, and RMC 12.2kbps mode for WCDMA band II, only these modes were used for all tests.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	32.09	32.10	32.03	29.17	29.51	29.76
GPRS class 10	31.03	31.05	31.00	28.09	28.43	28.69
EGPRS class 8	26.14	26.15	26.07	25.18	25.50	25.72
EGPRS class 10	26.13	26.14	26.06	25.15	25.47	25.70

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
RMC 12.2k	22.08	22.13	21.87	21.93	22.00	21.91
HSDPA Subtest-1	22.05	22.07	21.84	21.91	21.98	21.88
HSDPA Subtest-2	22.06	22.08	21.86	21.92	21.99	21.90
HSDPA Subtest-3	22.06	22.10	21.86	21.91	21.97	21.86
HSDPA Subtest-4	22.05	22.09	21.85	21.90	21.96	21.84

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	USB Cable	N/A	VR47XW	N/A	Unshielded, 1.6 m	N/A
3.	Adapter	N/A	PE98ED	Verification	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.09	32.10	32.03	26.14	26.15	26.07	22.08	22.13	21.87
Conducted Power (Watts)	1.62	1.62	1.60	0.41	0.41	0.40	0.16	0.16	0.15

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.17	29.51	29.76	25.18	25.50	25.72	21.93	22.00	21.91
Conducted Power (Watts)	0.83	0.89	0.95	0.33	0.35	0.37	0.16	0.16	0.16

Note: maximum burst average power for GPRS, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
2. For GSM/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
3. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio


Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Peak-to-Average Ratio (dB)	0.17	0.16	0.16	2.77	2.82	2.74	3.04	3.24	3.00

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.15	0.16	0.15	2.84	2.69	2.86	3.12	3.08	3.08

3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

Peak-to-Average Ratio on Channel 128 (824.2 MHz)




Date: 6.JUN.2013 10:42:42

Peak-to-Average Ratio on Channel 189 (836.4 MHz)



Date: 6.JUN.2013 10:46:15


Peak-to-Average Ratio on Channel 251 (848.8 MHz)




Date: 6.JUN.2013 10:44:28

Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------


Peak-to-Average Ratio on Channel 128 (824.2 MHz)



Peak-to-Average Ratio on Channel 189 (836.4 MHz)




Peak-to-Average Ratio on Channel 251 (848.8 MHz)




Date: 6.JUN.2013 10:57:42

Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
---------------	----------	--------------------	--------------------------


Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Peak-to-Average Ratio on Channel 661 (1880.0 MHz)




Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 6.JUN.2013 11:27:40

Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------


Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Peak-to-Average Ratio on Channel 661 (1880.0 MHz)




Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 6.JUN.2013 11:44:17


Band :	WCDMA Band V	Test Mode :	RMC 12.2kbps Link (QPSK)
--------	--------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 4132 (826.4 MHz)




Date: 5.JUN.2013 20:01:50

Peak-to-Average Ratio on Channel 4182 (836.4 MHz)



Date: 5.JUN.2013 20:03:40


Peak-to-Average Ratio on Channel 4233 (846.6 MHz)



Date: 5.JUN.2013 20:04:39


Band :	WCDMA Band II	Test Mode :	RMC 12.2kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)




Date: 5.JUN.2013 19:42:25

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 5.JUN.2013 19:43:05

Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 5.JUN.2013 19:43:46

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.3.2 Measuring Instruments


See list of measuring instruments of this test report.

3.3.3 Test Procedures


1. The EUT was placed on an non-conductive rotating platform with 0.8 meter height in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RBW= 1MHz, VBW= 3MHz for GSM, RBW= 100 kHz, VBW= 300 kHz, used channel power option with bandwidth=5MHz for WCDMA, and RMS detector settings per KDB 971168 D01.
2. During the measurement, the EUT was enforced in maximum power and linked with a base station. The highest emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by dipole antenna (substitution antenna) at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$.

3.3.4 Test Setup

<Test configuration for EUT operating frequency below 1GHz>



<Test configuration for EUT operating frequency above 1GHz>



3.3.5 Test Result of ERP

GSM850 (GPRS class 8) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-0.92	31.54	28.47	0.7031
836.4	-0.51	32.04	29.38	0.8670
848.8	0.31	32.59	30.75	1.1885
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-8.37	32.93	22.41	0.1742
836.4	-6.96	32.82	23.71	0.2350
848.8	-5.84	33.62	25.63	0.3656

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15

GSM850 (EDGE class 8) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-6.15	31.54	23.24	0.2109
836.4	-5.41	32.04	24.48	0.2805
848.8	-4.64	32.59	25.80	0.3802
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-13.23	32.93	17.55	0.0569
836.4	-11.99	32.82	18.68	0.0738
848.8	-10.83	33.62	20.64	0.1159

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15

WCDMA Band V (RMC 12.2kbps) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
826.40	-11.19	31.44	18.10	0.0646
836.40	-12.67	32.04	17.22	0.0527
846.60	-12.07	32.63	18.41	0.0693
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
826.40	-18.52	32.78	12.11	0.0163
836.40	-19.47	32.82	11.20	0.0132
846.60	-17.94	33.4	13.31	0.0214

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15

3.3.6 Test Result of EIRP

GSM1900 (GPRS class 8) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-11.95	43.69	31.74	1.4928
1880.0	-13.38	44.79	31.41	1.3836
1909.8	-16.43	43.59	27.16	0.5200
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-20.57	45.72	25.15	0.3273
1880.0	-21.22	46.78	25.56	0.3597
1909.8	-23.40	46.77	23.37	0.2173

* EIRP = LVL (dBm) + Correction Factor (dB)

GSM1900 (EDGE class 8) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-17.48	43.69	26.21	0.4178
1880.0	-17.33	44.79	27.46	0.5572
1909.8	-15.73	43.59	27.86	0.6109
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-23.95	45.72	21.77	0.1503
1880.0	-23.31	46.78	23.47	0.2223
1909.8	-23.77	46.77	23.00	0.1995

* EIRP = LVL (dBm) + Correction Factor (dB)

WCDMA Band II (RMC 12.2kbps) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1852.40	-21.31	44.15	22.84	0.1923
1880.00	-19.68	44.79	25.11	0.3243
1907.60	-20.31	44.21	23.90	0.2455
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1852.40	-29.37	45.73	16.36	0.0433
1880.00	-28.33	46.78	18.45	0.0700
1907.60	-26.94	46.49	19.55	0.0902

* EIRP = LVL (dBm) + Correction Factor (dB)

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	244.00	246.00	246.00	246.00	246.00	246.00
26dB BW (kHz)	310.00	320.00	314.00	304.00	308.00	310.00

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	250.00	242.00	246.00	250.00	244.00	250.00
26dB BW (kHz)	316.00	314.00	310.00	308.00	310.00	304.00


Cellular Band			
Modes	WCDMA Band V (RMC 12.2kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.18	4.20	4.16
26dB BW (MHz)	4.68	4.68	4.68

PCS Band			
Modes	WCDMA Band II (RMC 12.2kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.18	4.16	4.18
26dB BW (MHz)	4.68	4.68	4.68

3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 5.JUN.2013 14:19:18

26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 5.JUN.2013 13:55:39

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 5.JUN.2013 13:57:24

26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 5.JUN.2013 13:56:05

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 5.JUN.2013 13:57:49


26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 5.JUN.2013 13:56:31


Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 5.JUN.2013 14:39:50

26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 5.JUN.2013 14:38:31

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 5.JUN.2013 14:40:16

26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 5.JUN.2013 14:38:57

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 5.JUN.2013 14:40:42


26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 5.JUN.2013 14:39:23


Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 5.JUN.2013 15:00:03

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 5.JUN.2013 14:58:44

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 5.JUN.2013 15:00:28

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 5.JUN.2013 14:59:10

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 5.JUN.2013 15:00:54


26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 5.JUN.2013 14:59:36


Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 5.JUN.2013 15:26:41

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 5.JUN.2013 15:25:23

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 5.JUN.2013 15:27:07

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 5.JUN.2013 15:25:49

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 5.JUN.2013 15:33:42


26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 5.JUN.2013 15:26:15


Band :	WCDMA Band V	Test Mode :	RMC 12.2kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)




Date: 5.JUN.2013 19:54:09

26dB Bandwidth Plot on Channel 4132 (826.4 MHz)




Date: 5.JUN.2013 19:52:50

99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)




Date: 5.JUN.2013 19:54:34

26dB Bandwidth Plot on Channel 4182 (836.4 MHz)




Date: 5.JUN.2013 19:53:16

99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 5.JUN.2013 19:55:00


26dB Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 5.JUN.2013 19:58:21


Band :	WCDMA Band II	Test Mode :	RMC 12.2kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 5.JUN.2013 19:34:29

26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 5.JUN.2013 19:33:10

99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 5.JUN.2013 19:34:54

26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 5.JUN.2013 19:33:36

99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 5.JUN.2013 19:35:20

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 5.JUN.2013 19:34:02

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly $BW/100$.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.28dB	Maximum 26dB Bandwidth :	0.320MHz
Band Edge :	-15.89dBm	Measurement Value :	-16.17dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 5.JUN.2013 13:58:16

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
 2. Band Edge= Measurement Value + Correction Factor(dB)
- For example, $-16.17\text{dBm} + 0.28\text{dB} = -15.89\text{dBm}$

Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.28dB	Maximum 26dB Bandwidth :	0.320MHz
Band Edge :	-18.38dBm	Measurement Value :	-18.66dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 5.JUN.2013 13:58:42

1. $Correction\ Factor(dB) = 10\log(1\% \text{ Emission } BW/RBW)$
2. $Band\ Edge = Measurement\ Value + Correction\ Factor(dB)$

Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.14dB	Maximum 26dB Bandwidth :	0.310MHz
Band Edge :	-22.37dBm	Measurement Value :	-22.51dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 5.JUN.2013 14:41:08

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.14dB	Maximum 26dB Bandwidth :	0.310MHz
Band Edge :	-26.39dBm	Measurement Value :	-26.53dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 5.JUN.2013 14:41:35

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-19.98dBm	Measurement Value :	-20.21dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 5.JUN.2013 15:01:21

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-20.13dBm	Measurement Value :	-20.36dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 5.JUN.2013 15:01:47

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.14dB	Maximum 26dB Bandwidth :	0.310MHz
Band Edge :	-23.00dBm	Measurement Value :	-23.14dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 5.JUN.2013 15:30:15

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.14dB	Maximum 26dB Bandwidth :	0.310MHz
Band Edge :	-23.87dBm	Measurement Value :	-24.01dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 5.JUN.2013 15:28:26

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band V	Test Mode :	RMC 12.2kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.68MHz
Band Edge :	-32.82dBm	Measurement Value :	-29.52dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)




Date: 5.JUN.2013 19:55:27

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band V	Test Mode :	RMC 12.2kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.68MHz
Band Edge :	-33.43dBm	Measurement Value :	-30.13dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 5.JUN.2013 19:55:53

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band II	Test Mode :	RMC 12.2kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.68MHz
Band Edge :	-31.25dBm	Measurement Value :	-27.95dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)




Date: 5.JUN.2013 19:35:47

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band II	Test Mode :	RMC 12.2kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.68MHz
Band Edge :	-32.94dBm	Measurement Value :	-29.64dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 5.JUN.2013 19:36:13

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm


3.6.4 Test Setup




3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 5.JUN.2013 13:42:59


Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 5.JUN.2013 13:43:12


Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 5.JUN.2013 14:29:26

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 5.JUN.2013 14:29:42

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 5.JUN.2013 14:29:55


Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 5.JUN.2013 14:30:07


Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 5.JUN.2013 14:53:49

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 5.JUN.2013 14:54:02

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 5.JUN.2013 14:54:19

Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 5.JUN.2013 14:54:31


Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 5.JUN.2013 14:54:44


Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 5.JUN.2013 15:20:03

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 5.JUN.2013 15:20:15

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 5.JUN.2013 15:20:32

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 5.JUN.2013 15:20:45


Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 5.JUN.2013 15:20:57


Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 5.JUN.2013 19:50:42

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 5.JUN.2013 19:50:59

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 5.JUN.2013 19:51:11


Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 5.JUN.2013 19:51:24


Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 5.JUN.2013 19:29:17

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 5.JUN.2013 19:29:29

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 5.JUN.2013 19:29:46

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 5.JUN.2013 19:29:59

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 5.JUN.2013 19:30:11

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


7. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
8. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
9. The table was rotated 360 degrees to determine the position of the highest spurious emission.
10. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
11. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
12. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
13. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
14. Taking the record of output power at antenna port.
15. Repeat step 7 to step 8 for another polarization.
16. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
17. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$
18. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
19. $\text{ERP (dBm)} = \text{EIRP} - 2.15$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz




3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	21~23°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-47.11	-13	-34.11	-56.03	-48.83	1.62	5.49	H	Pass
2509	-41.68	-13	-28.68	-54.97	-43.65	2.1	6.22	H	Pass
3345	-52.75	-13	-39.75	-66.85	-55.64	3.03	8.07	H	Pass

Band :	GSM850	Temperature :	21~23°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-51.94	-13	-38.94	-63.1	-53.66	1.62	5.49	V	Pass
2509	-47.42	-13	-34.42	-61.16	-49.39	2.1	6.22	V	Pass
3345	-51.36	-13	-38.36	-66.95	-54.25	3.03	8.07	V	Pass

Band :	GSM850	Temperature :	21~23°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-57.30	-13	-44.30	-66.22	-59.02	1.62	5.49	H	Pass
2509	-53.95	-13	-40.95	-67.24	-55.92	2.1	6.22	H	Pass
3345	-52.69	-13	-39.69	-66.79	-55.58	3.03	8.07	H	Pass

Band :	GSM850	Temperature :	21~23°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-54.66	-13	-41.66	-65.82	-56.38	1.62	5.49	V	Pass
2509	-52.91	-13	-39.91	-66.65	-54.88	2.1	6.22	V	Pass
3345	-51.87	-13	-38.87	-67.46	-54.76	3.03	8.07	V	Pass

Band :	GSM1900	Temperature :	21~23°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-51.13	-13	-38.13	-66.48	-57.43	2.51	8.81	H	Pass
5640	-46.00	-13	-33.00	-66.76	-53.71	2.99	10.70	H	Pass
7520	-40.31	-13	-27.31	-67.58	-48.84	3.59	12.12	H	Pass
13160	-29.55	-13	-16.55	-62.98	-39.07	4.27	13.79	H	Pass

Band :	GSM1900	Temperature :	21~23°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-47.14	-13	-34.14	-63.44	-53.44	2.51	8.81	V	Pass
5640	-44.64	-13	-31.64	-65.21	-52.35	2.99	10.70	V	Pass
7520	-39.59	-13	-26.59	-66.64	-48.12	3.59	12.12	V	Pass
13160	-34.47	-13	-21.47	-65.92	-43.99	4.27	13.79	V	Pass

Band :	GSM1900	Temperature :	21~23°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-49.90	-13	-36.90	-65.25	-56.2	2.51	8.81	H	Pass
5640	-45.82	-13	-32.82	-66.58	-53.53	2.99	10.70	H	Pass
7520	-40.90	-13	-27.90	-68.17	-49.43	3.59	12.12	H	Pass
13160	-30.15	-13	-17.15	-63.48	-39.67	4.27	13.79	H	Pass

Band :	GSM1900	Temperature :	21~23°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-47.37	-13	-34.37	-63.67	-53.67	2.51	8.81	V	Pass
5640	-45.09	-13	-32.09	-65.66	-52.8	2.99	10.70	V	Pass
7520	-38.97	-13	-25.97	-66.02	-47.5	3.59	12.12	V	Pass
13160	-33.65	-13	-20.65	-65.1	-43.17	4.27	13.79	V	Pass

Band :	WCDMA Band V	Temperature :	21~23°C
Test Mode :	RMC 12.2kbps Link (QPSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-52.28	-13	-39.28	-61.2	-54	1.62	5.49	H	Pass
2509	-53.72	-13	-40.72	-67.01	-55.69	2.1	6.22	H	Pass
3346	-53.07	-13	-40.07	-67.17	-55.96	3.03	8.07	H	Pass

Band :	WCDMA Band V	Temperature :	21~23°C
Test Mode :	RMC 12.2kbps Link (QPSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-54.57	-13	-41.57	-65.73	-56.29	1.62	5.49	V	Pass
2509	-53.30	-13	-40.30	-67.04	-55.27	2.1	6.22	V	Pass
3345	-51.70	-13	-38.70	-67.29	-54.59	3.03	8.07	V	Pass

Band :	WCDMA Band II	Temperature :	21~23°C
Test Mode :	RMC 12.2kbps Link (QPSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-52.93	-13	-39.93	-68.28	-59.23	2.51	8.81	H	Pass
5640	-48.30	-13	-35.30	-69.06	-56.01	2.99	10.70	H	Pass
7520	-41.50	-13	-28.50	-68.77	-50.03	3.59	12.12	H	Pass

Band :	WCDMA Band II	Temperature :	21~23°C
Test Mode :	RMC 12.2kbps Link (QPSK)	Relative Humidity :	51~53%
Test Engineer :	Beer Chang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-50.72	-13	-37.72	-67.02	-57.02	2.51	8.81	V	Pass
5640	-47.37	-13	-34.37	-67.94	-55.08	2.99	10.70	V	Pass
7520	-41.52	-13	-28.52	-68.57	-50.05	3.59	12.12	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-30	-0.04	-36	-0.04	PASS
-20	-38	-0.04	-34	-0.04	
-10	-29	-0.03	-30	-0.04	
0	-27	-0.03	-29	-0.03	
10	-25	-0.03	-27	-0.03	
20	-23	-0.03	-29	-0.03	
30	-22	-0.03	-34	-0.04	
40	-24	-0.03	-40	-0.05	
50	-33	-0.04	-39	-0.05	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-53	-0.03	-69	-0.04	PASS
-20	-49	-0.03	-58	-0.03	
-10	-47	-0.02	-61	-0.03	
0	-45	-0.02	-60	-0.03	
10	-40	-0.02	-62	-0.03	
20	-44	-0.02	-65	-0.03	
30	-43	-0.02	-64	-0.03	
40	-49	-0.03	-67	-0.04	
50	-63	-0.03	-72	-0.04	

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	30	0.04	PASS
-20	26	0.03	
-10	23	0.03	
0	-18	-0.02	
10	15	0.02	
20	17	0.02	
30	19	0.02	
40	21	0.02	
50	20	0.02	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	45	0.02	PASS
-20	39	0.02	
-10	-32	-0.02	
0	31	0.02	
10	-34	-0.02	
20	-30	-0.02	
30	29	0.02	
40	-38	-0.02	
50	36	0.02	

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS class 8	3.7	-26	-0.03	2.5	PASS
		BEP	-23	-0.03		
		4.2	-22	-0.03		
	EDGE class 8	3.7	-26	-0.03		
		BEP	-29	-0.03		
		4.2	-28	-0.03		
GSM 1900 CH661	GPRS class 8	3.7	-36	-0.02		
		BEP	-31	-0.02		
		4.2	-47	-0.02		
	EDGE class 8	3.7	-55	-0.03		
		BEP	-53	-0.03		
		4.2	-59	-0.03		
WCDMA Band V CH4182	RMC 12.2kbps	3.7	28	0.03		
		BEP	21	0.02		
		4.2	-19	-0.02		
WCDMA Band II CH9400	RMC 12.2kbps	3.7	-39	-0.02		
		BEP	42	0.02		
		4.2	-40	-0.02		

Note:

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.4 V.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
System Simulator (with power meter function)	Rohde & Schwarz	CMU200	117995	N/A	Jul. 30, 2012	Jun. 05, 2013 ~ Jun.06, 2013	Jul. 29, 2013	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz~40GHz	Oct. 29, 2012	Jun. 05, 2013 ~ Jun.06, 2013	Oct. 28, 2013	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D3SP	TBN-930701	N/A	Jul. 23, 2012	Jun. 05, 2013 ~ Jun.06, 2013	Jul. 22, 2013	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9k~30G	Nov. 30, 2012	May 31, 2013~ Jun. 26, 2013	Nov. 29, 2013	Radiation (03CH07-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30M~1G	Oct. 06, 2012	May 31, 2013~ Jun. 26, 2013	Oct. 05, 2013	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1G~18G	Aug. 22, 2012	May 31, 2013~ Jun. 26, 2013	Aug. 21, 2013	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	30M~1G	Feb. 26, 2013	May 31, 2013~ Jun. 26, 2013	Feb. 25, 2014	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1G~26.5G	Dec. 01, 2012	May 31, 2013~ Jun. 26, 2013	Nov. 30, 2013	Radiation (03CH07-HY)
Turn Table	ChainTek	ChainTek 3000	N/A	0 ~ 360 degree	N/A	May 31, 2013~ Jun. 26, 2013	N/A	Radiation (03CH07-HY)
Antenna Mast	ChainTek	ChainTek 3000	N/A	N/A	N/A	May 31, 2013~ Jun. 26, 2013	N/A	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	18G~40G	Sep. 28, 2012	May 31, 2013~ Jun. 26, 2013	Sep. 27, 2013	Radiation (03CH07-HY)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54
--	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72
--	------