

# FCC REPORT

**Applicant:** HI-SKY INTERNATIONAL S.A.S

**Address of Applicant:** Via 40 NO.54-58 Oficina 4 Parque Industrial La Maria,  
Barranquilla, Colombia

**Equipment Under Test (EUT)**

Product Name: Smart Phone

Model No.: BLESS

Trade mark: Hi Sky

**FCC ID:** 2AAIWBLESS

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart B

**Date of sample receipt:** 30 Jun. 2014

**Date of Test:** 01 Jul. to 16 Jul., 2014

**Date of report issued:** 17 Jul., 2014

**Test Result:** Pass \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	17 Jul., 2014	Original

Prepared by:

*Sera Xiang*

Report Clerk

Date:

17 Jul., 2014

Reviewed by:

*Atomb Yang*

Project Engineer

Date:

17 Jul., 2014

## 3 Contents

Page

<b>1</b>	<b>COVER PAGE .....</b>	<b>1</b>
<b>2</b>	<b>VERSION .....</b>	<b>2</b>
<b>3</b>	<b>CONTENTS .....</b>	<b>3</b>
<b>4</b>	<b>TEST SUMMARY .....</b>	<b>4</b>
<b>5</b>	<b>GENERAL INFORMATION .....</b>	<b>5</b>
5.1	CLIENT INFORMATION .....	5
5.2	GENERAL DESCRIPTION OF E.U.T. ....	5
5.3	TEST MODE.....	5
5.4	DESCRIPTION OF SUPPORT UNITS .....	6
5.5	LABORATORY FACILITY .....	6
5.6	LABORATORY LOCATION .....	6
5.7	TEST INSTRUMENTS LIST.....	7
<b>6</b>	<b>TEST RESULTS AND MEASUREMENT DATA .....</b>	<b>8</b>
6.1	CONDUCTED EMISSION.....	8
6.2	RADIATED EMISSION .....	11
<b>7</b>	<b>TEST SETUP PHOTO.....</b>	<b>17</b>
<b>8</b>	<b>EUT CONSTRUCTIONAL DETAILS.....</b>	<b>19</b>

## 4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	Pass
Radiated Emission	Part15.109	Pass

*Pass: The EUT complies with the essential requirements in the standard.*

## 5 General Information

### 5.1 Client Information

Applicant:	HI-SKY INTERNATIONAL S.A.S
Address of Applicant:	Via 40 NO.54-58 Oficina 4 Parque Industrial La Maria, Barranquilla, Colombia
Manufacturer :	Shenzhen Kleadtone Technology Co., Limited
Address of Manufacturer:	Room B201,Garden City Cyber Port,NO.1079 Nanhai Road Nanshan District Shenzhen,China

### 5.2 General Description of E.U.T.

Product Name:	Smart Phone
Model No.:	BLESS
Power supply:	Rechargeable Li-ion Battery DC3.7V-1800mAh
AC adapter :	MODEL:BLESS Input: AC 100-240V 50/60Hz 0.15A Output: DC 5V, 650mA

### 5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging & recording mode	Keep the EUT in Charging & recording mode
Charging & palying mode	Keep the EUT in Charging & palying mode
The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

## 5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC

## 5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

● **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

## 5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.  
Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,  
Bao'an District, Shenzhen, Guangdong, China  
Tel: 0755-23118282  
Fax: 0755-23116366

## 5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	July 09 2014	Jul 08 2015
2	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	June 25 2014	June 24 2015
3	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	June 25 2014	June 24 2015
4	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
5	Coaxial Cable	CCIS	N/A	CCIS0016	Apr. 01 2014	Mar. 31 2015
6	Coaxial Cable	CCIS	N/A	CCIS0017	Apr. 01 2014	Mar. 31 2015
7	Coaxial cable	CCIS	N/A	CCIS0018	Apr. 01 2014	Mar. 31 2015
8	Coaxial Cable	CCIS	N/A	CCIS0019	Apr. 01 2014	Mar. 31 2015
9	Coaxial Cable	CCIS	N/A	CCIS0087	Apr. 01 2014	Mar. 31 2015
10	Amplifier(10kHz-1.3GHz)	HP	8447D	CCIS0003	Apr. 01 2014	Mar. 31 2015
11	Amplifier(1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	July 09 2014	July 08 2015
12	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	Apr. 01 2014	Mar. 31 2015
13	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 30 2014	Mar. 29 2015
14	Printer	HP	HP LaserJet P1007	N/A	N/A	N/A
15	Positioning Controller	UC	UC3000	CCIS0015	N/A	N/A
16	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP	CCIS0023	June. 25 2014	June. 24 2015
17	EMI Test Receiver	Rohde & Schwarz	ESPI	CCIS0022	Apr 01 2014	Mar. 31 2015
18	Loop antenna	Laplace instrument	RF300	EMC0701	Aug. 12 2013	Aug. 11 2014
19	Universal radio communication tester	Rhode & Schwarz	CMU200	CCIS0069	June. 25 2014	June. 24 2015
20	Signal Analyzer	Rohde & Schwarz	FSIQ3	CCIS0088	June. 25 2014	June. 24 2015

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	July 09 2014	July 08 2015
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	June 25 2014	June. 24 2015
3	LISN	CHASE	MN2050D	CCIS0074	Apr. 01 2014	Mar. 31 2015
4	Coaxial Cable	CCIS	N/A	CCIS0086	Apr. 01 2014	Mar. 31 2015

## 6 Test results and Measurement Data

### 6.1 Conducted Emission


Test Requirement:	FCC Part15 B Section 15.107																		
Test Method:	ANSI C63.4:2003																		
Test Frequency Range:	150kHz to 30MHz																		
Class / Severity:	Class B																		
Receiver setup:	RBW=9kHz, VBW=30kHz																		
Limit:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBμV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>0.5-30</td><td>60</td><td>50</td></tr></table>					Frequency range (MHz)	Limit (dBμV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	0.5-30	60	50
Frequency range (MHz)	Limit (dBμV)																		
	Quasi-peak	Average																	
0.15-0.5	66 to 56*	56 to 46*																	
0.5-5	56	46																	
0.5-30	60	50																	
Test setup:	<div><p style="text-align: center;"><b>Reference Plane</b></p><p style="text-align: center;">40cm      80cm</p><p style="text-align: center;">LISN      LISN      Filter — AC power</p><p style="text-align: center;">AUX Equipment      E.U.T</p><p style="text-align: center;">EMI Receiver</p><p style="text-align: center;">Test table/Insulation plane</p><p><i>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</i></p></div>																		
Test procedure	<div><div>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment.</div><div>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs).</div><div>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.</div></div>																		
Test environment:	Temp.:	23 °C	Humid.:	56%	Press.: 1 01kPa														
Measurement Record:	Uncertainty: 3.28dB																		
Test Instruments:	Refer to section 5.7 for details																		
Test mode:	Refer to section 5.3 for details																		
Test results:	Pass																		



**Measurement data:**

PC mode :

Line:




**Trace: 5**

Site : CCIS Shielding Room  
 Condition : FCC PART15 B QP LISN LINE  
 Job No. : 504RF  
 EUT : Smartphone  
 Model : BLESS  
 Test Mode : PC Mode  
 Power Rating : AC120V/60Hz  
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa  
 Test Engineer: Carey

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.162	32.09	0.27	10.77	43.13	65.34	-22.21	QP
2	0.258	20.77	0.27	10.75	31.79	51.51	-19.72	Average
3	0.322	28.21	0.26	10.73	39.20	59.66	-20.46	QP
4	0.322	21.58	0.26	10.73	32.57	49.66	-17.09	Average
5	0.381	21.55	0.28	10.72	32.55	48.25	-15.70	Average
6	0.385	29.67	0.28	10.72	40.67	58.17	-17.50	QP
7	0.447	18.14	0.28	10.74	29.16	46.93	-17.77	Average
8	0.582	26.24	0.26	10.77	37.27	56.00	-18.73	QP
9	0.601	16.91	0.25	10.77	27.93	46.00	-18.07	Average
10	0.771	16.31	0.23	10.80	27.34	46.00	-18.66	Average
11	1.082	25.15	0.25	10.88	36.28	56.00	-19.72	QP
12	2.066	24.71	0.26	10.96	35.93	56.00	-20.07	QP

Neutral:



Trace: 7



Site : CCIS Shielding Room  
 Condition : FCC PART15 B QP LISN NEUTRAL  
 Job No. : 504RF  
 EUT : Smartphone  
 Model : BLESS  
 Test Mode : PC Mode  
 Power Rating : AC120V/60Hz  
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa  
 Test Engineer: Carey

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.318	21.01	0.26	10.74	32.01	49.75	-17.74	Average
2	0.322	31.78	0.26	10.73	42.77	59.66	-16.89	QP
3	0.373	32.28	0.25	10.73	43.26	58.43	-15.17	QP
4	0.377	18.66	0.25	10.72	29.63	48.34	-18.71	Average
5	0.442	17.39	0.27	10.74	28.40	47.02	-18.62	Average
6	0.579	29.09	0.24	10.77	40.10	56.00	-15.90	QP
7	0.739	28.75	0.19	10.79	39.73	56.00	-16.27	QP
8	0.759	14.59	0.19	10.80	25.58	46.00	-20.42	Average
9	2.099	30.13	0.29	10.96	41.38	56.00	-14.62	QP
10	2.121	15.51	0.29	10.95	26.75	46.00	-19.25	Average
11	3.293	14.12	0.29	10.91	25.32	46.00	-20.68	Average
12	3.417	27.33	0.29	10.91	38.53	56.00	-17.47	QP

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

## 6.2 Radiated Emission


Test Requirement:	FCC Part15 B Section 15.109				
Test Method:	ANSI C63.4:2003				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
			74.0		Peak Value
Test setup:	Below 1GHz				
					
Test setup:	Above 1GHz				
					

Test Procedure:	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>
Test environment:	Temp.: 25 °C Humid.: 55% Press.: 1 01kPa
Measurement Record:	Uncertainty: 4.88dB
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

## Measurement Data

Below 1GHz


Horizontal:



Site : 3m chamber  
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) HORIZONTAL  
 Pro : 504RF  
 EUT : Smartphone  
 Model : BLESS  
 Test mode : PC mode  
 Power Rating : 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Carey  
 REMARK :

	Freq	ReadAntenna	Cable Preamp			Limit	Over	
		Level Factor	Loss Factor	Level	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	61.132	40.14	12.29	0.70	29.77	23.36	40.00	-16.64 QP
2	107.134	40.40	12.49	1.02	29.48	24.43	43.50	-19.07 QP
3	213.763	46.37	11.00	1.45	28.74	30.08	43.50	-13.42 QP
4	245.090	48.55	12.08	1.60	28.57	33.66	46.00	-12.34 QP
5	369.405	43.14	14.51	2.01	28.65	31.01	46.00	-14.99 QP
6	721.726	46.04	19.10	2.97	28.58	39.53	46.00	-6.47 QP

Vertical:




Site : 3m chamber  
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL  
 Pro : 504RF  
 EUT : Smartphone  
 Model : B1ESS  
 Test mode : PC mode  
 Power Rating : 120W/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Carey  
 REMARK :

	ReadAntenna	Cable	Preamp		Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	61.132	44.78	12.29	0.70	29.77	28.00	40.00 -12.00 QP
2	104.536	40.48	12.73	1.00	29.50	24.71	43.50 -18.79 QP
3	174.424	43.89	9.29	1.35	29.02	25.51	43.50 -17.99 QP
4	245.090	42.98	12.08	1.60	28.57	28.09	46.00 -17.91 QP
5	345.595	39.99	14.20	1.92	28.55	27.56	46.00 -18.44 QP
6	962.162	43.29	21.49	3.47	27.65	40.60	54.00 -13.40 QP

Above 1GHz

Horizontal:




Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL  
 Pro : 504RF  
 EUT : Smartphone  
 Model : BLESS  
 Test mode : PC mode  
 Power Rating : 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Carey  
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Limit	Over	
	Level	Factor	Loss	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m dB
1	1868.851	47.34	25.60	4.72	40.93	36.73	74.00 -37.27 Peak
2	1868.851	37.57	25.60	4.72	40.93	26.96	54.00 -27.04 Average
3	3393.901	47.59	28.46	6.44	38.84	43.65	74.00 -30.35 Peak
4	3393.901	37.36	28.46	6.44	38.84	33.42	54.00 -20.58 Average
5	5264.368	48.95	31.73	9.14	40.13	49.69	74.00 -24.31 Peak
6	5264.368	38.16	31.73	9.14	40.13	38.90	54.00 -15.10 Average



Vertical:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL  
 Pro : 504RF  
 EUT : Smartphone  
 Model : BLESS  
 Test mode : PC mode  
 Power Rating : 120W/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Carey  
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Limit	Over	
		Level	Factor	Loss	Factor	Level	Line
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m
1	1889.051	49.14	25.75	4.74	40.92	38.71	74.00
2	1889.051	38.22	25.75	4.74	40.92	27.79	54.00
3	3517.727	48.25	29.01	6.24	39.71	43.79	74.00
4	3517.727	38.59	29.01	6.24	39.71	34.13	54.00
5	5115.591	48.31	32.10	9.13	40.05	49.49	74.00
6	5115.591	38.14	32.10	9.13	40.05	39.32	54.00