



FCC PART 15.247


TEST REPORT

For

MOIMSTONE CO., LTD

16, sapyeong-daero, Seocho-gu, Seoul, South Korea

FCC ID: 2AAKFAIPHONE

Report Type: Original Report	Product Type: AI Phone
Report Number: RSZ180723002-00C	
Report Date: 2018-08-17	
Rocky Kang 	
Reviewed By: RF Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "**".

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	8
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS	12
TEST EQUIPMENT LIST	13
FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	15
APPLICABLE STANDARD	15
RESULT	15
FCC §15.203 - ANTENNA REQUIREMENT.....	17
APPLICABLE STANDARD	17
ANTENNA CONNECTOR CONSTRUCTION	17
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE	18
CORRECTED FACTOR & MARGIN CALCULATION	19
TEST RESULTS SUMMARY	19
TEST DATA	19
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	24
APPLICABLE STANDARD	24
EUT SETUP	24
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	25
TEST PROCEDURE	25
CORRECTED AMPLITUDE & MARGIN CALCULATION	25
TEST RESULTS SUMMARY	25
TEST DATA	26
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST DATA	38
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	48
APPLICABLE STANDARD	48

TEST PROCEDURE	48
TEST DATA	48
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	50
APPLICABLE STANDARD	50
TEST PROCEDURE	50
TEST DATA	50
FCC §15.247(e) - POWER SPECTRAL DENSITY	56
APPLICABLE STANDARD	56
TEST PROCEDURE	56
TEST DATA	56

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *MOIMSTONE CO., LTD*'s product, model number: *AI-PHONE (FCC ID: 2AAKFAIPHONE)* or the "EUT" in this report was an *AI Phone*, which was measured approximately: 224 mm (L) * 170 mm (W) * 144 mm (H), rated with input voltage: DC 5 V from adapter.

Adapter Information:

Model: KT241050300US

Input: 100-240V ~ 50/60Hz, 0.8A

Output: 5V, 3A

**All measurement and test data in this report was gathered from production sample serial number: 180723002 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-07-23.*

Objective

This report is prepared on behalf of *MOIMSTONE CO., LTD* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP, Part 15.247 DSS and Part 15.407 NII submissions with FCC ID: 2AAKFAIPHONE.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 DTS Meas Guidance v04 .

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.5dB
RF conducted test with spectrum		±1.5dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±3°C
Humidity		±6%
Supply voltages		±0.4%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

For 802.11n-HT40 mode, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	/	/
4	2437	/	/
5	2442	/	/

EUT was tested with Channel 1, 4 and 7.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

CMD command was used for BLE & Wi-Fi testing.


The device was tested with the worst case was performed as below:

Mode	Data rate	Power level		
		Low channel	Middle channel	High channel
802.11b	1 Mbps	12	12	12
802.11g	6 Mbps	9	9	9
802.11n-HT20	MCS0	9	9	9
802.11n-HT40	MCS0	9	9	9
BLE	/	Default	Default	Default

Pre-scan with all the data rates, the above data rate is the worst case for Wi-Fi test.


Duty cycle

802.11b mode




Date: 3.AUG.2018 10:07:27

802.11g mode




Date: 3.AUG.2018 10:08:15

802.11n-HT20 Mode




Date: 3.AUG.2018 10:08:37

802.11n-HT40 Mode



Date: 3.AUG.2018 10:09:00

BLE Mode



Date: 10.AUG.2018 14:32:44


Mode	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting	10log(1/ Duty Cycle)
802.11b	100	-	-	10Hz	-
802.11g	100	-	-	10Hz	-
802.11n-HT20	100	-	-	10Hz	-
802.11n-HT40	100	-	-	10Hz	-
BLE	70	437	2.29	3kHz	1.55

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding Un-detachable DC Cable	1.5	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1091	Maximum Permissible Exposure(MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2018-07-11	2019-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2017-12-21	2018-12-21
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2018-05-21	2018-11-19
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
N/A	Conducted Emission Cable	N/A	UF A210B-1-0720-504504	2018-05-12	2018-11-12
Radiated Emission Test					
A.H.System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2018-06-23	2019-06-23
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2018-05-21	2019-05-21
HP	Amplifier	HP8447E	1937A01046	2018-05-21	2018-11-19
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2018-01-11	2019-01-11
UTiFLEX MICRO-C0AX	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-04-01	2018-10-01
Ducommun technologies	RF Cable	104PEA	218124002	2018-05-21	2018-11-19
Ducommun technologies	RF Cable	RG-214	1	2018-05-21	2018-11-19
Ducommun technologies	RF Cable	RG-214	2	2018-05-22	2018-11-22
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2017-12-06	2020-12-05
Ducommun Technologies	Pre-amplifier	ALN-22093530-01	991373-01	2018-08-03	2019-08-03
Sinoscite	Notch Filter	BSF2402-2480MN-0898-001	N/A	2018-05-21	2019-05-21
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Agilent	USB Wideband Power Meter	U2021XA	MY54250003	2018-03-21	2019-03-21
WEINSCHTEL	3dB Attenuator	N/A	N/A	Each Time	
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2017-12-24	2018-12-24
Ducommun technologies	RF Cable	RG-214	3	Each Time	

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Turn up conducted power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2402-2480	0.46	1.11	2.5	1.78	20	0.0004	1
2412-2462	0.46	1.11	19	79.43	20	0.0175	1

Simultaneous transmitting consideration: (referring to the DSS report, the highest MPE for Bluetooth is 0.002mW/cm²)

The ratio= $MPE/limit_{DSS}+MPE/limit_{DTS}=0.002+0.0175=0.0195<1.0$, simultaneous exposure is not required.

Note: 2.4GHz and 5GHz WiFi can't transmit simultaneously for this device.

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is 0.46 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2018-08-11.


EUT operation mode: Transmitting

BLE Mode:**AC 120V/60 Hz, Line**


Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.983030	44.2	20.0	56.0	11.8	QP
1.030670	42.5	20.0	56.0	13.5	QP
1.944810	38.1	20.0	56.0	17.9	QP
2.433490	41.0	20.0	56.0	15.0	QP
2.922170	41.8	20.0	56.0	14.2	QP
3.406910	42.2	20.0	56.0	13.8	QP
0.983030	34.3	20.0	46.0	11.7	Ave.
1.030670	34.4	20.0	46.0	11.6	Ave.
1.944810	32.6	20.0	46.0	13.4	Ave.
2.433490	36.5	20.0	46.0	9.5	Ave.
2.922170	37.7	20.0	46.0	8.3	Ave.
3.406910	38.2	20.0	46.0	7.8	Ave.

AC 120V/60 Hz, Neutral

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.209500	41.6	20.1	63.2	21.6	QP
0.229500	44.3	20.1	62.5	18.2	QP
0.249500	41.3	20.1	61.8	20.5	QP
0.257500	37.3	20.1	61.5	24.2	QP
0.526170	37.5	20.1	56.0	18.5	QP
2.918170	34.7	20.0	56.0	21.3	QP
0.209500	34.9	20.1	53.2	18.3	Ave.
0.229500	33.0	20.1	52.5	19.5	Ave.
0.249500	35.2	20.1	51.8	16.6	Ave.
0.257500	33.1	20.1	51.5	18.4	Ave.
0.526170	31.1	20.1	46.0	14.9	Ave.
2.918170	31.6	20.0	46.0	14.4	Ave.

Wi-Fi Mode:**AC 120 V/60 Hz, Line:**

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.868890	30.0	20.0	56.0	26.0	QP
0.999090	40.7	20.0	56.0	15.3	QP
1.101530	37.5	20.0	56.0	18.5	QP
1.152690	34.9	20.0	56.0	21.1	QP
2.437490	37.3	20.0	56.0	18.7	QP
2.922170	38.5	20.0	56.0	17.5	QP
0.868890	26.0	20.0	46.0	20.0	Ave.
0.999090	31.8	20.0	46.0	14.2	Ave.
1.101530	28.1	20.0	46.0	17.9	Ave.
1.152690	26.3	20.0	46.0	19.7	Ave.
2.437490	32.8	20.0	46.0	13.2	Ave.
2.922170	34.5	20.0	46.0	11.5	Ave.

AC 120V/ 60 Hz, Neutral:

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.153500	47.5	20.1	65.8	18.3	QP
0.177500	45.6	20.1	64.6	19.0	QP
0.205500	47.1	20.1	63.4	16.3	QP
0.225500	46.0	20.1	62.6	16.6	QP
0.253500	40.0	20.1	61.6	21.6	QP
2.803490	15.8	20.0	56.0	40.2	QP
0.153500	33.2	20.1	55.8	22.6	Ave.
0.177500	33.9	20.1	54.6	20.7	Ave.
0.205500	41.9	20.1	53.4	11.5	Ave.
0.225500	40.7	20.1	52.6	11.9	Ave.
0.253500	29.6	20.1	51.6	22.0	Ave.
2.803490	10.0	20.0	46.0	36.0	Ave.

Note:


- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$


In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2018-08-08.


EUT operation mode: Transmitting

BLE Mode:**30 MHz~1 GHz:**

Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.609291	22.45	198.0	V	167.0	0.3	40.00	17.55
450.012500	34.35	109.0	V	281.0	0.2	46.00	11.65
584.773125	26.92	297.0	V	161.0	4.9	46.00	19.08
699.648500	28.50	302.0	H	218.0	7.0	46.00	17.50
758.130375	30.54	263.0	H	328.0	8.7	46.00	15.46
858.175875	31.41	165.0	V	54.0	9.7	46.00	14.59

1 GHz-25 GHz (BLE):

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2402.00	62.11	PK	111	2.3	H	33.92	96.03	/	/
2402.00	60.46	Ave.	111	2.3	H	33.92	94.38	/	/
2402.00	60.33	PK	8	1.4	V	33.92	94.25	/	/
2402.00	58.02	Ave.	8	1.4	V	33.92	91.94	/	/
2352.32	27.91	PK	285	1.1	H	33.92	61.83	74	12.17
2352.32	13.66	Ave.	285	1.1	H	33.92	47.58	54	6.42
2486.23	27.44	PK	102	2.2	H	34.08	61.52	74	12.48
2486.23	13.45	Ave.	102	2.2	H	34.08	47.53	54	6.47
4804.00	45.47	PK	142	2.0	H	5.84	51.31	74	22.69
4804.00	34.02	Ave.	142	2.0	H	5.84	39.86	54	14.14
Middle Channel (2440 MHz)									
2440.00	62.41	PK	225	1.7	H	33.92	96.33	/	/
2440.00	60.71	Ave.	225	1.7	H	33.92	94.63	/	/
2440.00	59.71	PK	29	1.5	V	33.92	93.63	/	/
2440.00	56.47	Ave.	29	1.5	V	33.92	90.39	/	/
4880.00	44.73	PK	313	2.5	H	6.21	50.94	74	23.06
4880.00	31.77	Ave.	313	2.5	H	6.21	37.98	54	16.02
High Channel (2480 MHz)									
2480.00	63.22	PK	274	1.7	H	33.92	97.14	/	/
2480.00	61.11	Ave.	274	1.7	H	33.92	95.03	/	/
2480.00	61.70	PK	335	1.1	V	33.92	95.62	/	/
2480.00	59.63	Ave.	335	1.1	V	33.92	93.55	/	/
2387.65	27.63	PK	284	2.0	H	33.92	61.55	74	12.45
2387.65	13.57	Ave.	284	2.0	H	33.92	47.49	54	6.51
2486.23	28.35	PK	265	1.3	H	34.08	62.43	74	11.57
2486.23	16.85	Ave.	265	1.3	H	34.08	50.93	54	3.07
4960.00	42.28	PK	69	2.4	H	7.82	50.10	74	23.9
4960.00	30.29	Ave.	69	2.4	H	7.82	38.11	54	15.89

Wi-Fi 802.11b Mode low channel:**30 MHz~1 GHz:**

Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
30.446500	22.53	277.0	H	0.0	0.4	40.00	17.47
449.995250	34.63	100.0	V	304.0	0.2	46.00	11.37
549.987125	32.53	107.0	V	237.0	5.3	46.00	13.47
691.443750	28.66	257.0	H	207.0	6.4	46.00	17.34
783.692500	31.11	229.0	H	338.0	9.0	46.00	14.89
855.807250	31.19	332.0	H	117.0	9.6	46.00	14.81

1 GHz-25 GHz (WIFI):**802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2412.00	71.77	PK	49	1.2	H	33.92	105.69	/	/
2412.00	66.61	Ave.	49	1.2	H	33.92	100.53	/	/
2412.00	71.75	PK	342	2.2	V	33.92	105.67	/	/
2412.00	66.59	Ave.	342	2.2	V	33.92	100.51	/	/
2359.64	28.18	PK	57	1.8	H	33.92	62.10	74	11.90
2359.64	13.36	Ave.	57	1.8	H	33.92	47.28	54	6.72
2489.43	27.15	PK	337	1.9	H	34.08	61.23	74	12.77
2489.43	13.24	Ave.	337	1.9	H	34.08	47.32	54	6.68
4824.00	43.37	PK	131	1.3	H	5.84	49.21	74	24.79
4824.00	29.04	Ave.	131	1.3	H	5.84	34.88	54	19.12
Middle Channel (2437 MHz)									
2437.00	71.52	PK	175	1.6	H	33.92	105.44	/	/
2437.00	66.43	Ave.	175	1.6	H	33.92	100.35	/	/
2437.00	69.74	PK	143	1.8	V	33.92	103.66	/	/
2437.00	64.51	Ave.	143	1.8	V	33.92	98.43	/	/
4874.00	42.61	PK	161	1.9	H	6.21	48.82	74	25.18
4874.00	28.17	Ave.	161	1.9	H	6.21	34.38	54	19.62
High Channel (2462 MHz)									
2462.00	71.66	PK	245	1.8	H	34.08	105.74	/	/
2462.00	66.94	Ave.	245	1.8	H	34.08	101.02	/	/
2462.00	69.05	PK	302	1.0	V	34.08	103.13	/	/
2462.00	64.21	Ave.	302	1.0	V	34.08	98.29	/	/
2387.00	27.61	PK	11	1.8	H	33.92	61.53	74	12.47
2387.00	13.25	Ave.	11	1.8	H	33.92	47.17	54	6.83
2483.50	27.54	PK	18	1.8	H	34.08	61.62	74	12.38
2483.50	13.31	Ave.	18	1.8	H	34.08	47.39	54	6.61
4924.00	42.44	PK	22	1.2	H	6.21	48.65	74	25.35
4924.00	28.96	Ave.	22	1.2	H	6.21	35.17	54	18.83

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2412.00	70.71	PK	244	1.0	H	33.92	104.63	/	/
2412.00	58.06	Ave.	244	1.0	H	33.92	91.98	/	/
2412.00	66.08	PK	308	1.3	V	33.92	100.00	/	/
2412.00	53.71	Ave.	308	1.3	V	33.92	87.63	/	/
2390.00	27.65	PK	321	1.8	H	33.92	61.57	74	12.43
2390.00	13.95	Ave.	321	1.8	H	33.92	47.87	54	6.13
2483.50	26.54	PK	91	2.1	H	34.08	60.62	74	13.38
2483.50	13.24	Ave.	91	2.1	H	34.08	47.32	54	6.68
4824.00	42.32	PK	205	2.0	H	5.84	48.16	74	25.84
4824.00	28.51	Ave.	205	2.0	H	5.84	34.35	54	19.65
Middle Channel (2437MHz)									
2437.00	69.74	PK	26	1.4	H	33.92	103.66	/	/
2437.00	57.13	Ave.	26	1.4	H	33.92	91.05	/	/
2437.00	66.41	PK	211	1.2	V	33.92	100.33	/	/
2437.00	54.21	Ave.	211	1.2	V	33.92	88.13	/	/
4874.00	42.56	PK	32	2.0	H	6.21	48.77	74	25.23
4874.00	28.49	Ave.	32	2.0	H	6.21	34.70	54	19.30
High Channel (2462 MHz)									
2462.00	69.92	PK	265	1.1	H	34.08	104.00	/	/
2462.00	57.46	Ave.	265	1.1	H	34.08	91.54	/	/
2462.00	66.83	PK	84	1.5	V	34.08	100.91	/	/
2462.00	54.26	Ave.	84	1.5	V	34.08	88.34	/	/
2387.54	27.02	PK	168	2.5	H	33.92	60.94	74	13.06
2387.54	13.19	Ave.	168	2.5	H	33.92	47.11	54	6.89
2483.50	27.15	PK	150	2.0	H	34.08	61.23	74	12.77
2483.50	13.26	Ave.	150	2.0	H	34.08	47.34	54	6.66
4924.00	42.79	PK	266	1.3	H	6.21	49.00	74	25.00
4924.00	28.31	Ave.	266	1.3	H	6.21	34.52	54	19.48

802.11n-HT20 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2412.00	69.95	PK	326	1.3	H	33.92	103.87	/	/
2412.00	57.38	Ave.	326	1.3	H	33.92	91.30	/	/
2412.00	66.45	PK	271	1.9	V	33.92	100.37	/	/
2412.00	54.16	Ave.	271	1.9	V	33.92	88.08	/	/
2389.96	27.21	PK	110	1.4	H	33.92	61.13	74	12.87
2389.96	13.15	Ave.	110	1.4	H	33.92	47.07	54	6.93
2489.40	26.14	PK	160	1.0	H	34.08	60.22	74	13.78
2489.40	13.25	Ave.	160	1.0	H	34.08	47.33	54	6.67
4824.00	42.54	PK	275	1.7	H	5.84	48.38	74	25.62
4824.00	28.39	Ave.	275	1.7	H	5.84	34.23	54	19.77
Middle Channel (2437MHz)									
2437.00	69.75	PK	29	2.2	H	33.92	103.67	/	/
2437.00	57.27	Ave.	29	2.2	H	33.92	91.19	/	/
2437.00	65.49	PK	46	1.2	V	33.92	99.41	/	/
2437.00	53.28	Ave.	46	1.2	V	33.92	87.20	/	/
4874.00	42.89	PK	208	1.8	H	6.21	49.10	74	24.90
4874.00	28.61	Ave.	208	1.8	H	6.21	34.82	54	19.18
High Channel (2462 MHz)									
2462.00	69.93	PK	216	2.1	H	34.08	104.01	/	/
2462.00	57.64	Ave.	216	2.1	H	34.08	91.72	/	/
2462.00	65.77	PK	128	2.3	V	34.08	99.85	/	/
2462.00	53.36	Ave.	128	2.3	V	34.08	87.44	/	/
2312.00	27.80	PK	261	2.1	H	33.83	61.63	74	12.37
2312.00	13.24	Ave.	261	2.1	H	33.83	47.07	54	6.93
2487.00	27.12	PK	93	2.2	H	34.08	61.20	74	12.80
2487.00	13.32	Ave.	93	2.2	H	34.08	47.40	54	6.60
4924.00	42.87	PK	104	2.0	H	6.21	49.08	74	24.92
4924.00	28.39	Ave.	104	2.0	H	6.21	34.60	54	19.40

802.11n-HT40 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2422 MHz)									
2422.00	67.76	PK	11	1.4	H	33.92	101.68	/	/
2422.00	55.12	Ave.	11	1.4	H	33.92	89.04	/	/
2422.00	62.15	PK	358	2.1	V	33.92	96.07	/	/
2422.00	49.67	Ave.	358	2.1	V	33.92	83.59	/	/
2388.57	36.49	PK	98	1.9	H	33.92	70.41	74	3.59
2388.57	15.82	Ave.	98	1.9	H	33.92	49.74	54	4.26
2489.70	27.25	PK	237	1.4	H	34.08	61.33	74	12.67
2489.70	13.34	Ave.	237	1.4	H	34.08	47.42	54	6.58
4844.00	42.25	PK	340	1.2	H	5.84	48.09	74	25.91
4844.00	28.71	Ave.	340	1.2	H	5.84	34.55	54	19.45
Middle Channel (2437 MHz)									
2437.00	67.13	PK	217	2.0	H	33.92	101.05	/	/
2437.00	54.68	Ave.	217	2.0	H	33.92	88.60	/	/
2437.00	62.94	PK	337	1.7	V	33.92	96.86	/	/
2437.00	50.25	Ave.	337	1.7	V	33.92	84.17	/	/
4874.00	43.87	PK	25	1.4	H	6.21	50.08	74	23.92
4874.00	28.96	Ave.	25	1.4	H	6.21	35.17	54	18.83
High Channel (2452 MHz)									
2452.00	66.93	PK	266	2.4	H	34.08	101.01	/	/
2452.00	54.57	Ave.	266	2.4	H	34.08	88.65	/	/
2452.00	63.28	PK	273	2.3	V	34.08	97.36	/	/
2452.00	50.61	Ave.	273	2.3	V	34.08	84.69	/	/
2390.00	27.24	PK	38	1.7	H	33.92	61.16	74	12.84
2390.00	13.15	Ave.	38	1.7	H	33.92	47.07	54	6.93
2486.40	31.25	PK	47	1.4	H	34.08	65.33	74	8.67
2486.40	14.11	Ave.	47	1.4	H	34.08	48.19	54	5.81
4904.00	42.85	PK	243	1.1	H	6.21	49.06	74	24.94
4904.00	28.96	Ave.	243	1.1	H	6.21	35.17	54	18.83

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor



Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude



The other spurious emission which is 20dB to the limit was not recorded.

And for the pre-scan is performed with the 2400-2483.5MHz band filter.



**Pre-scan with 802.11b Mode, High channel
Horizontal**





Vertical



Pre-scan for Average Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH**Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Data****Environmental Conditions**

Temperature:	24~25 °C
Relative Humidity:	51~52 %
ATM Pressure:	100.6~101.0 kPa

The testing was performed by Kiki Kong from 2018-08-03 to 2018-08-10.

Test Result: Pass.


Please refer to the following tables and plots.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode			
Low	2412	8.013	≥ 500
Middle	2437	8.013	≥ 500
High	2462	8.013	≥ 500
802.11g			
Low	2412	15.321	≥ 500
Middle	2437	15.128	≥ 500
High	2462	15.385	≥ 500
802.11n-HT20 mode			
Low	2412	15.128	≥ 500
Middle	2437	15.449	≥ 500
High	2462	15.449	≥ 500
802.11n-HT40 mode			
Low	2422	35.000	≥ 500
Middle	2437	35.000	≥ 500
High	2452	35.128	≥ 500


Channel	Frequency (MHz)	6 dB Emission Bandwidth(MHz)	Limit (kHz)
BLE mode			
Low	2402	0.663	≥ 500
Middle	2440	0.673	≥ 500
High	2480	0.696	≥ 500

802.11b Low Channel




Date: 3.AUG.2018 09:28:16

802.11b Middle Channel




Date: 10.AUG.2018 14:37:56

802.11b High Channel




Date: 3.AUG.2018 09:34:50

802.11g Low Channel




Date: 3.AUG.2018 09:41:34

802.11g Middle Channel




Date: 3.AUG.2018 09:39:59

802.11g High Channel




Date: 3.AUG.2018 09:43:21

802.11n-HT20 Low Channel




Date: 3.AUG.2018 09:45:17

802.11n-HT20 Middle Channel




Date: 3.AUG.2018 09:46:40

802.11n-HT20 High Channel




Date: 3.AUG.2018 09:48:15

802.11n-HT40 Low Channel




Date: 3.AUG.2018 09:50:27

802.11n-HT40 Middle Channel




Date: 3.AUG.2018 09:51:45

802.11n-HT40 High Channel




Date: 3.AUG.2018 09:54:44

BLE Low Channel




Date: 5.AUG.2018 21:44:00

BLE Middle Channel



Date: 5.AUG.2018 21:45:58

BLE High Channel



Date: 5.AUG.2018 21:47:50


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100.0 kPa

The testing was performed by Kiki Kong on 2018-08-05.

EUT operation mode: Transmitting

Wi-Fi mode

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)
802.11b			
Low	2412	17.33	30
Middle	2437	17.10	30
High	2462	17.19	30
802.11g			
Low	2412	18.15	30
Middle	2437	18.03	30
High	2462	18.30	30
802.11n HT20			
Low	2412	18.36	30
Middle	2437	18.00	30
High	2462	18.09	30
802.11n HT40			
Low	2422	18.52	30
Middle	2437	17.89	30
High	2452	18.33	30

BLE mode

Channel	Frequency (MHz)	Max Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	1.40	30	Pass
Middle	2440	2.09	30	Pass
High	2480	2.16	30	Pass

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	24~25 °C
Relative Humidity:	51~52 %
ATM Pressure:	100.5~101.0 kPa


The testing was performed by Kiki Kong from 2018-08-03 to 2018-08-10.

EUT operation mode: Transmitting

Test Result: Compliance


Please refer to the following plots.

802.11b: Band Edge, Left Side




Date: 3.AUG.2018 09:57:36

802.11b: Band Edge, Right Side




Date: 3.AUG.2018 09:59:16

802.11g: Band Edge, Left Side




Date: 3.AUG.2018 10:01:11

802.11g: Band Edge, Right Side




Date: 3.AUG.2018 10:00:13

802.11n-HT20: Band Edge, Left Side




Date: 3.AUG.2018 10:02:24

802.11n-HT20: Band Edge, Right Side




Date: 3.AUG.2018 10:03:57

802.11n-HT40: Band Edge, Left Side




Date: 3.AUG.2018 10:05:48

802.11n-HT40: Band Edge, Right Side




Date: 10.AUG.2018 14:35:48

BLE: Band Edge, Left Side



Date: 5.AUG.2018 22:04:48

BLE: Band Edge, Right Side



Date: 5.AUG.2018 22:03:17


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa


The testing was performed by Kiki Kong on 2018-08-03 and 2018-08-05.

EUT operation mode: Transmitting

Test Result: Pass


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-11.77	≤ 8
Middle	2437	-10.78	≤ 8
High	2462	-9.53	≤ 8
802.11g mode			
Low	2412	-15.41	≤ 8
Middle	2437	-16.39	≤ 8
High	2462	-15.64	≤ 8
802.11n-HT20 mode			
Low	2412	-17.23	≤ 8
Middle	2437	-16.23	≤ 8
High	2462	-15.31	≤ 8
802.11n-HT40 mode			
Low	2422	-19.40	≤ 8
Middle	2437	-19.73	≤ 8
High	2452	-19.36	≤ 8
BLE mode			
Low	2402	-13.36	≤ 8
Middle	2440	-12.62	≤ 8
High	2480	-12.67	≤ 8

Power Spectral Density, 802.11b Low Channel




Date: 3.AUG.2018 10:13:27

Power Spectral Density, 802.11b Middle Channel




Date: 3.AUG.2018 10:14:12

Power Spectral Density, 802.11b High Channel




Date: 3.AUG.2018 10:14:39

Power Spectral Density, 802.11g Low Channel




Date: 3.AUG.2018 10:16:28

Power Spectral Density, 802.11g Middle Channel




Date: 3.AUG.2018 10:17:37

Power Spectral Density, 802.11g High Channel




Date: 3.AUG.2018 10:20:18

Power Spectral Density, 802.11n-HT20 Low Channel




Date: 3.AUG.2018 10:21:40

Power Spectral Density, 802.11n-HT20 Middle Channel




Date: 3.AUG.2018 10:22:38

Power Spectral Density, 802.11n-HT20 High Channel




Date: 3.AUG.2018 10:24:18

Power Spectral Density, 802.11n-HT40 Low Channel




Date: 3.AUG.2018 10:25:29

Power Spectral Density, 802.11n-HT40 Middle Channel




Date: 3.AUG.2018 10:26:16

Power Spectral Density, 802.11n-HT40 High Channel




Date: 3.AUG.2018 10:27:14

Power Spectral Density, BLE Low Channel




Date: 5.AUG.2018 21:49:47

Power Spectral Density, BLE Middle Channel



Date: 5.AUG.2018 21:50:46

Power Spectral Density, BLE High Channel



Date: 5.AUG.2018 21:51:58

***** END OF REPORT *****