BT-5003B Instruction Manual

Parameters:

1. 3.0 Bluetooth speaker

2. Bluetooth specification: 3.0 + EDR

3. Bluetooth profile: A2DP AVRCP

4. Range: 10M

5. Amplifier output power: 3W x2 (RMS)6. Frequency Response: 120HZ-20KHZ

7. SNR: ≥65db

8. Degree of Distortion: thd≤10%

9. Powered supply: 100-240V AC adaptor

10. 3.5mm audio cable & AC adaptor


11. Material: ABS+Injection

12. Unit size: 26x11x12.2cm (WxHxD)

Operation:

- 1. Connect the speaker with the power
- 2. Power on the speaker
- Turn on the Bluetooth of the player, and search the speaker, signal identification is 2Boom
- 4. Connect the signals between the player and speaker
- 5. Play the speaker as the above diagram (1~5)
- 6. Be noted that only buttons 1,3,5 can be worked when you play through the audio input.

Diagram:



- 0 DDEM
- 2、PREV
- 3 · Pause/Play
- 4 · Next
- 5 · Volume+
- 6 · On/Off
- 7 · DC Input
- 8 · Audio Input

Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

1. Volume-

NOTE:

1. Changes or Modifications not expressly approved by the party responsible could void the user's authority to operate this device.

This device complies with Industry Canada licence-exempt RSS standard(s).

2. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -- Reorient or relocate the receiving antenna.
- -- Increase the separation between the equipment and receiver.
- -- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- -- Consult the dealer or an experienced radio/TV technician for help.

Warning:

 The battery pack shall not be exposed to excessive heat such as sunshine, fire or the like.