

# FCC Part 15C

## Measurement and Test Report

For

**OLIVESKY INTERNATIONAL ELECTRONIC CO., LTD**

**5C11 Huafeng Times Plaza Bao'an 25 Area, Shenzhen, 518101 Guangdong**

**China.**

**FCC ID: 2AAL9M730DIQO**

**FCC Rules:** FCC Part 15C

**Product Description:** PCBA

**Tested Model:** M730

**Report No.:** STR13078098I-2

**Tested Date:** 2013-07-04 to 2013-07-25

**Issued Date:** 2013-07-26

**Tested By:** Seven Song / Engineer

*Seven Song*

**Reviewed By:** Lahm Peng / EMC Manager

*Lahm peng*

**Approved & Authorized By:** Jandy so / PSQ Manager

*Jandyso*

**Prepared By:**

**SEM.Test Compliance Service Co., Ltd**

3/F, Jinbao Commerce Building, Xin'an Fanshen Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd

**TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND TEST MODE.....	5
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>6</b>
<b>3. ANTENNA REQUIREMENT .....</b>	<b>7</b>
3.1 STANDARD APPLICABLE.....	7
3.2 EVALUATION INFORMATION .....	7
<b>4. POWER SPECTRAL DENSITY .....</b>	<b>8</b>
4.1 STANDARD APPLICABLE.....	8
4.2 TEST EQUIPMENT LIST AND DETAILS .....	8
4.3 TEST PROCEDURE.....	8
4.4 ENVIRONMENTAL CONDITIONS .....	8
4.5 SUMMARY OF TEST RESULTS/PLOTS .....	9
<b>5. 6DB BANDWIDTH .....</b>	<b>15</b>
5.1 STANDARD APPLICABLE.....	15
5.2 TEST EQUIPMENT LIST AND DETAILS .....	15
5.3 TEST PROCEDURE.....	15
5.4 ENVIRONMENTAL CONDITIONS .....	15
5.5 SUMMARY OF TEST RESULTS/PLOTS .....	16
<b>6. RF OUTPUT POWER.....</b>	<b>21</b>
6.1 STANDARD APPLICABLE.....	21
6.2 TEST EQUIPMENT LIST AND DETAILS .....	21
6.3 TEST PROCEDURE.....	21
6.4 ENVIRONMENTAL CONDITIONS .....	21
6.5 SUMMARY OF TEST RESULTS/PLOTS .....	22
<b>7. FIELD STRENGTH OF SPURIOUS EMISSIONS .....</b>	<b>32</b>
7.1 MEASUREMENT UNCERTAINTY .....	32
7.2 STANDARD APPLICABLE.....	32
7.3 TEST EQUIPMENT LIST AND DETAILS .....	32
7.4 TEST PROCEDURE.....	33
7.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	33
7.6 ENVIRONMENTAL CONDITIONS .....	34
7.7 SUMMARY OF TEST RESULTS/PLOTS .....	34
<b>8. OUT OF BAND EMISSIONS.....</b>	<b>56</b>
8.1 STANDARD APPLICABLE.....	56
8.2 TEST EQUIPMENT LIST AND DETAILS .....	56
8.3 TEST PROCEDURE.....	56
8.4 ENVIRONMENTAL CONDITIONS .....	57
8.5 SUMMARY OF TEST RESULTS/PLOTS .....	57
<b>9. CONDUCTED EMISSIONS .....</b>	<b>69</b>
9.1 MEASUREMENT UNCERTAINTY .....	69
9.2 TEST EQUIPMENT LIST AND DETAILS .....	69
9.3 TEST PROCEDURE.....	69
9.4 BASIC TEST SETUP BLOCK DIAGRAM.....	69
9.5 ENVIRONMENTAL CONDITIONS .....	70
9.6 TEST RECEIVER SETUP .....	70
9.7 SUMMARY OF TEST RESULTS/PLOTS .....	70
9.8 CONDUCTED EMISSIONS TEST DATA.....	70

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: OLIVESKY INTERNATIONAL ELECTRONIC CO., LTD  
Address of applicant: 5C11 Huafeng Times Plaza Bao'an 25 Area, Shenzhen, 518101 Guangdong, China.

Manufacturer: OLIVESKY INTERNATIONAL ELECTRONIC CO., LTD  
Address of manufacturer: 5C11 Huafeng Times Plaza Bao'an 25 Area, Shenzhen, 518101 Guangdong, China.

General Description of EUT	
Product Name:	PCBA
Brand Name:	N/A
Model No.:	M730
Adding Models:	M730A, M730B, M730C, M730D
Rated Voltage:	DC 12V
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The other model listed in the report has different appearance only of M730 without circuit and electronic construction changed, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b/g/n
Frequency Range:	2412-2462MHz
RF Output Power:	16.30dBm (Conducted)
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Modulation:	CCK, BPSK, QPSK, 16QAM, 64QAM
Quantity of Channels:	11
Channel Separation:	5MHz
Antenna Type:	Integral Antenna
Antenna Gain:	2 dBi
Lowest Internal Frequency:	32.768KHz
Device Category:	Fixed Device

## 1.2 Test Standards

The following report is prepared on behalf of the OLIVESKY INTERNATIONAL ELECTRONIC CO., LTD in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The public notice KDB 558074 D01 V02 for digital transmission systems shall be performed also.

## 1.4 Test Facility

- **FCC – Registration No.: 994117**

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

- **Industry Canada (IC) Registration No.: 7673A**

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz
TM2	802.11g	2412MHz, 2437MHz, 2462MHz
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC Power Cable	1.0	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
DC Power	LW	Apr-03	/

## 2. SUMMARY OF TEST RESULTS

<b>FCC Rules</b>	<b>Description of Test Item</b>	<b>Result</b>
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)(d)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

### **3. Antenna Requirement**

---

#### **3.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### **3.2 Evaluation Information**

This product has a special Antenna, fulfill the requirement of this section.

## 4. Power Spectral Density

### 4.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 4.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2013-05-07	2014-05-06
Attenuator	ATTEN	ATS100-4-20	/	2013-05-07	2014-05-06

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

### 4.3 Test Procedure

According to the KDB 558074 D01 V03, the test method of power spectral density as below:

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \text{ RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 4.4 Environmental Conditions

Temperature:	20° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar




#### 4.5 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b	2412	-13.05	8
	2437	-13.55	8
	2462	-14.67	8
802.11g	2412	-12.59	8
	2437	-13.52	8
	2462	-12.35	8
802.11n HT20	2412	-11.99	8
	2437	-14.99	8
	2462	-13.98	8

Please refer to the following test plots:


## 802.11b-Low Channel




## 802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




## 802.11g-Middle Channel




## 802.11g-High Channel




## 802.11n-HT20-Low Channel



## 802.11n-HT20-Middle Channel



802.11n-HT20-High Channel



## 5. 6dB Bandwidth

### 5.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 5.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2013-05-07	2014-05-06
Attenuator	ATTEN	ATS100-4-20	/	2013-05-07	2014-05-06

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

### 5.3 Test Procedure

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 5.4 Environmental Conditions


Temperature:	24° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

### 5.5 Summary of Test Results/Plots

Test Mode	Test Channel MHz	6 dB Bandwidth kHz	Limit kHz
802.11b	2412	9.404	500
	2437	9.138	500
	2462	9.056	500
802.11g	2412	15.212	500
	2437	15.386	500
	2462	15.180	500
802.11n-HT20	2412	17.561	500
	2437	17.135	500
	2462	16.691	500


Please refer to the following test plots:

#### 802.11b-Low Channel







## 802.11b-Middle Channel




## 802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




## 802.11g-High Channel




## 802.11n-HT20-Low Channel



802.11n-HT20-Middle Channel



802.11n-HT20-High Channel



## 6. RF Output Power

### 6.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 6.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2013-05-07	2014-05-06
Attenuator	ATTEN	ATS100-4-20	/	2013-05-07	2014-05-06

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

### 6.3 Test Procedure

According to section 15.247(b)-power output of the KDB-558074 D01 V03 (2013), 9.1.2 Option 2 (Integrated band Power method) this procedure should only be used when the maximum available RBW of the spectrum/signal

analyzer is less than the DTS bandwidth.

1. Set the RBW = 1 MHz.
2. Set the VBW  $\geq$  3 RBW
3. Set the span  $\geq$  1.5 x DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function,

### 6.4 Environmental Conditions

Temperature:	21° C
Relative Humidity:	55%
ATM Pressure:	1011 mbar


**6.5 Summary of Test Results/Plots**

Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b_1Mbps	2412	12.41	17.42	1000
	2437	11.59	14.42	1000
	2462	10.77	11.94	1000
802.11b_11Mbps	2412	12.45	17.58	1000
	2437	11.79	15.10	1000
	2462	10.76	11.91	1000
802.11g_6Mbps	2412	16.27	42.36	1000
	2437	15.62	36.48	1000
	2462	15.62	36.48	1000
802.11g_54Mbps	2412	16.30	42.66	1000
	2437	15.94	39.26	1000
	2462	15.65	36.73	1000
802.11n HT20_MCS0	2412	15.78	37.84	1000
	2437	15.13	32.58	1000
	2462	15.06	32.06	1000
802.11n HT20_MCS7	2412	15.54	35.81	1000
	2437	14.98	31.48	1000
	2462	14.98	31.48	1000


*Note: the antenna gain of 2dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.*

Please refer to the following test plots:


## 802.11b-1Mbps-Low Channel




## 802.11b-1Mbps-Middle Channel



## 802.11b-1Mbps-High Channel




## 802.11b-11Mbps-Low Channel







## 802.11b-11Mbps-Middle Channel




## 802.11b-11Mbps-High Channel




## 802.11g-6Mbps-Low Channel



## 802.11g-6Mbps-Middle Channel




802.11g-6Mbps-High Channel




802.11g-54Mbps-Low Channel




## 802.11g-54Mbps-Middle Channel




## 802.11g-54Mbps-High Channel




## 802.11n HT20\_MCS0-Low Channel




## 802.11n-HT20\_MCS0-Middle Channel




802.11n-HT20\_ MCS0-High Channel




802.11n-HT20\_ MCS7-Low Channel



802.11n-HT20\_ MCS7-Middle Channel



802.11n-HT20\_ MCS7-High Channel



## 7. Field Strength of Spurious Emissions

### 7.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 5.10$  dB.

### 7.2 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 7.3 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2013-05-07	2014-05-06
EMI Test Receiver	R&S	ESVB	825471/005	2013-05-07	2014-05-06
Pre-amplifier	Agilent	8447F	3113A06717	2013-05-07	2014-05-06
Pre-amplifier	Compliance Direction	PAP-0118	24002	2013-05-07	2014-05-06
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2013-04-20	2014-04-19
Horn Antenna	ETS	3117	00086197	2013-04-20	2014-04-19
Horn Antenna	ETS	3116B	00088203	2013-04-20	2014-04-19
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2013-04-20	2014-04-19

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.




## 7.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Detector function = peak

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Detector function = peak, AV

## 7.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

## 7.6 Environmental Conditions


Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

## 7.7 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst margin of:


**-7.87 dB at 32.4059 MHz in the Vertical polarization for 802.11n-HT20 Transmitting Low Channel, 9kHz to 25 GHz, 3 Meters**

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

**Plot of Radiated Emissions Test Data (30MHz to 1GHz)***EUT:* PCBA*Tested Model:* M370*Operating Condition:* 802.11b Transmitting Low Channel-2412MHz*Comment:* DC 12V*Test Specification:* Horizontal

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( ° )	Height (cm)	Remark
1	40.5591	15.26	9.51	24.77	40.00	-15.23	360	100	peak
2	99.5281	15.60	6.72	22.32	43.50	-21.18	116	200	peak
3	168.4138	16.59	3.69	20.28	43.50	-23.22	254	100	peak
4	263.8190	17.87	8.00	25.87	46.00	-20.13	113	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	46.6664	14.93	7.64	22.57	40.00	-17.43	270	100	peak
2	99.5281	14.58	6.72	21.30	43.50	-22.20	360	100	peak
3	330.1949	15.74	10.28	26.02	46.00	-19.98	116	100	peak
4	750.1083	16.03	17.78	33.81	46.00	-12.19	54	100	peak
5	869.1302	15.55	18.54	34.09	46.00	-11.91	113	100	peak

Operating Condition: 802.11b Transmitting Middle Channel-2437MHz


Comment: DC 12V

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	36.5092	14.69	9.13	23.82	40.00	-16.18	160	100	peak
2	100.2286	13.48	6.81	20.29	43.50	-23.21	290	100	peak
3	428.0193	15.54	10.93	26.47	46.00	-19.53	178	100	peak
4	760.7036	16.14	17.15	33.29	46.00	-12.71	224	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	40.2757	15.09	9.60	24.69	40.00	-15.31	256	100	peak
2	99.5281	15.08	6.72	21.80	43.50	-21.70	360	100	peak
3	297.2241	15.23	10.04	25.27	46.00	-20.73	360	100	peak
4	372.0045	16.46	10.65	27.11	46.00	-18.89	360	100	peak

Operating Condition: 802.11b Transmitting High Channel-2462MHz


Comment: DC 12V

Test Specification: Horizontal




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	36.0007	15.78	9.04	24.82	40.00	-15.18	360	100	peak
2	53.6932	15.24	6.28	21.52	40.00	-18.48	178	100	peak
3	99.5281	14.81	6.72	21.53	43.50	-21.97	176	100	peak
4	312.1794	16.07	10.36	26.43	46.00	-19.57	255	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	33.0950	16.41	8.56	24.97	40.00	-15.03	360	100	peak
2	99.5281	14.92	6.72	21.64	43.50	-21.86	225	100	peak
3	297.2241	15.73	10.04	25.77	46.00	-20.23	160	100	peak
4	586.8437	14.85	14.39	29.24	46.00	-16.76	310	100	peak



**Plot of Radiated Emissions Test Data (30MHz to 1GHz)***EUT:* PCBA*Tested Model:* M370*Operating Condition:* 802.11g Transmitting Low Channel-2412MHz*Comment:* DC 12V*Test Specification:* Horizontal

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	32.4059	21.23	8.44	29.67	40.00	-10.33	174	100	peak
2	110.5687	15.56	5.80	21.36	43.50	-22.14	160	100	peak
3	465.5994	16.02	11.69	27.71	46.00	-18.29	320	100	peak
4	893.8567	16.34	19.27	35.61	46.00	-10.39	360	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	36.2541	17.45	9.09	26.54	40.00	-13.46	177	100	peak
2	98.1419	14.98	6.39	21.37	43.50	-22.13	90	100	peak
3	679.9600	15.48	15.55	31.03	46.00	-14.97	336	100	peak
4	893.8567	16.13	19.27	35.40	46.00	-10.60	360	100	peak

Operating Condition: 802.11g Transmitting Middle Channel-2437MHz


Comment: DC 12V

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	32.4059	21.23	8.44	29.67	40.00	-10.33	270	100	peak
2	110.5687	15.56	5.80	21.36	43.50	-22.14	164	100	peak
3	341.9787	16.40	10.16	26.56	46.00	-19.44	228	200	peak
4	729.3583	17.11	17.31	34.42	46.00	-11.58	130	200	peak
5	887.6099	18.21	19.15	37.36	46.00	-8.64	360	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	37.0249	18.59	9.21	27.80	40.00	-12.20	360	100	peak
2	316.5890	16.84	10.44	27.28	46.00	-18.72	255	100	peak
3	739.6605	16.54	18.07	34.61	46.00	-11.39	270	100	peak
4	906.4824	16.47	19.15	35.62	46.00	-10.38	180	100	peak

Operating Condition: 802.11g Transmitting High Channel-2462MHz


Comment: DC 12V

Test Specification: Horizontal




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	32.4059	21.23	8.44	29.67	40.00	-10.33	270	100	peak
2	104.5361	15.27	6.39	21.66	43.50	-21.84	51	200	peak
3	218.3085	16.82	5.81	22.63	46.00	-23.37	360	200	peak
4	887.6099	18.21	19.15	37.36	46.00	-8.64	360	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	36.5092	19.47	9.13	28.60	40.00	-11.40	360	100	peak
2	98.1419	14.98	6.39	21.37	43.50	-22.13	180	100	peak
3	316.5890	16.84	10.44	27.28	46.00	-18.72	225	100	peak
4	875.2470	17.15	18.80	35.95	46.00	-10.05	67	100	peak

**Plot of Radiated Emissions Test Data (30MHz to 1GHz)***EUT:* PCBA*Tested Model:* M370*Operating Condition:* 802.11n-HT20 Transmitting Low Channel-2412MHz*Comment:* DC 12V*Test Specification:* Horizontal

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	39.4372	14.37	9.60	23.97	40.00	-16.03	260	100	peak
2	102.3597	14.14	6.61	20.75	43.50	-22.75	131	200	peak
3	744.8661	15.61	17.95	33.56	46.00	-12.44	285	200	peak
4	919.2866	16.27	18.70	34.97	46.00	-11.03	224	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	32.4059	23.69	8.44	32.13	40.00	-7.87	155	100	peak
2	105.2718	16.25	6.32	22.57	43.50	-20.93	197	100	peak
3	495.9344	17.25	12.04	29.29	46.00	-16.71	310	100	peak
4	744.8661	15.46	17.95	33.41	46.00	-12.59	229	100	peak
5	887.6099	16.71	19.15	35.86	46.00	-10.14	130	100	peak



Operating Condition: 802.11n-HT20 Transmitting Middle Channel-2437MHz


Comment: DC 12V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	100.9340	15.68	6.75	22.43	43.50	-21.07	274	100	peak
2	312.1794	15.59	10.36	25.95	46.00	-20.05	116	100	peak
3	744.8661	15.61	17.95	33.56	46.00	-12.44	82	100	peak
4	887.6099	15.93	19.15	35.08	46.00	-10.92	134	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	37.2855	16.21	9.25	25.46	40.00	-14.54	78	100	peak
2	102.3597	15.58	6.61	22.19	43.50	-21.31	136	100	peak
3	318.8170	15.51	10.46	25.97	46.00	-20.03	284	100	peak
4	739.6605	16.31	18.07	34.38	46.00	-11.62	60	100	peak

Operating Condition: 802.11n-HT20 Transmitting High Channel-2462MHz


Comment: DC 12V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( ° )	Height (cm)	Remark
1	39.7147	16.86	9.64	26.50	40.00	-13.50	360	100	peak
2	102.3597	15.89	6.61	22.50	43.50	-21.00	112	100	peak
3	724.2611	18.01	16.93	34.94	46.00	-11.06	180	200	peak
4	881.4067	17.84	19.03	36.87	46.00	-9.13	270	200	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	37.8121	21.98	9.33	31.31	40.00	-8.69	267	100	peak
2	316.5890	16.84	10.44	27.28	46.00	-18.72	116	100	peak
3	452.7197	16.27	11.58	27.85	46.00	-18.15	360	100	peak
4	739.6605	16.81	18.07	34.88	46.00	-11.12	228	100	peak
5	986.0717	17.36	19.17	36.53	54.00	-17.47	270	100	peak

*Spurious Emissions Above 1GHz**Test Mode: 802.11b*

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	58.22	-3.87	54.35	74.00	-19.65	H	PK
4824.000	42.52	-3.87	38.65	54.00	-15.35	H	AV
7236.000	55.60	1.14	56.74	74.00	-17.26	H	PK
7236.000	39.16	1.19	40.35	54.00	-13.65	H	AV
4824.000	54.02	-3.86	50.16	74.00	-23.84	V	PK
4824.000	41.40	-3.86	37.54	54.00	-16.46	V	AV
7236.000	52.48	1.10	53.58	74.00	-20.42	V	PK
7236.000	39.22	1.10	40.32	54.00	-13.68	V	AV
Middle Channel-2437MHz							
4874.000	54.95	-3.74	51.21	74.00	-22.79	H	PK
4874.000	40.95	-3.74	37.21	54.00	-16.79	H	AV
7311.000	46.85	1.47	48.32	74.00	-25.68	H	PK
7311.000	33.10	1.47	34.57	54.00	-19.43	H	AV
4874.000	53.97	-3.74	50.23	74.00	-23.77	V	PK
4874.000	40.89	-3.74	37.15	54.00	-16.85	V	AV
7311.000	47.98	1.47	49.45	74.00	-24.55	V	PK
7311.000	34.08	1.47	35.55	54.00	-18.45	V	AV
High Channel-2462MHz							
4924.000	54.94	-3.59	51.35	74.00	-22.65	H	PK
4924.000	42.04	-3.59	38.45	54.00	-15.55	H	AV
7386.000	47.99	1.79	49.78	74.00	-24.22	H	PK
7386.000	35.18	1.79	36.97	54.00	-17.03	H	AV
4924.000	55.82	-3.59	52.23	74.00	-21.77	V	PK
4924.000	41.76	-3.59	38.17	54.00	-15.83	V	AV
7386.000	46.38	1.79	48.17	74.00	-25.83	V	PK
7386.000	34.83	1.79	36.62	54.00	-17.38	V	AV

*Test Mode: 802.11g*

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	55.99	-3.86	52.13	74.00	-21.87	H	PK
4824.000	42.65	-3.86	38.79	54.00	-15.21	H	AV
7236.000	49.22	1.10	50.32	74.00	-23.68	H	PK
7236.000	35.54	1.10	36.64	54.00	-17.36	H	AV
4824.000	55.50	-3.86	51.64	74.00	-22.36	V	PK
4824.000	42.23	-3.86	38.37	54.00	-15.63	V	AV
7236.000	48.42	1.10	49.52	74.00	-24.48	V	PK
7236.000	34.40	1.10	35.50	54.00	-18.50	V	AV
Middle Channel-2437MHz							
4874.000	55.10	-3.74	51.36	74.00	-22.64	H	PK
4874.000	43.28	-3.74	39.54	54.00	-14.46	H	AV
7311.000	47.38	1.47	48.85	74.00	-25.15	H	PK
7311.000	35.27	1.47	36.74	54.00	-17.26	H	AV
4874.000	57.07	-3.74	53.33	74.00	-20.67	V	PK
4874.000	43.86	-3.74	40.12	54.00	-13.88	V	AV
7311.000	48.40	1.47	49.87	74.00	-24.13	V	PK
7311.000	35.33	1.47	36.80	54.00	-17.20	V	AV
High Channel-2462MHz							
4924.000	56.11	-3.59	52.52	74.00	-21.48	H	PK
4924.000	42.69	-3.59	39.10	54.00	-14.90	H	AV
7386.000	47.18	1.79	48.97	74.00	-25.03	H	PK
7386.000	34.73	1.79	36.52	54.00	-17.48	H	AV
4924.000	54.00	-3.59	50.41	74.00	-23.59	V	PK
4924.000	40.75	-3.59	37.16	54.00	-16.84	V	AV
7386.000	48.58	1.79	50.37	74.00	-23.63	V	PK
7386.000	35.95	1.79	37.74	54.00	-16.26	V	AV

Test Mode: 802.11n-HT20

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	56.71	-3.86	52.85	74.00	-21.15	H	PK
4824.000	43.18	-3.86	39.32	54.00	-14.68	H	AV
7236.000	49.21	1.10	50.31	74.00	-23.69	H	PK
7236.000	35.77	1.10	36.87	54.00	-17.13	H	AV
4824.000	55.60	-3.86	51.74	74.00	-22.26	V	PK
4824.000	40.54	-3.86	36.68	54.00	-17.32	V	AV
7236.000	47.26	1.10	48.36	74.00	-25.64	V	PK
7236.000	34.44	1.10	35.54	54.00	-18.46	V	AV
Middle Channel-2437MHz							
4874.000	54.05	-3.74	50.31	74.00	-23.69	H	PK
4874.000	41.63	-3.74	37.89	54.00	-16.11	H	AV
7311.000	48.87	1.47	50.34	74.00	-23.66	H	PK
7311.000	36.42	1.47	37.89	54.00	-16.11	H	AV
4874.000	55.85	-3.74	52.11	74.00	-21.89	V	PK
4874.000	43.38	-3.74	39.64	54.00	-14.36	V	AV
7311.000	48.63	1.47	50.10	74.00	-23.90	V	PK
7311.000	35.68	1.47	37.15	54.00	-16.85	V	AV
High Channel-2462MHz							
4924.000	54.77	-3.59	51.18	74.00	-22.82	H	PK
4924.000	42.47	-3.59	38.88	54.00	-15.12	H	AV
7386.000	48.42	1.79	50.21	74.00	-23.79	H	PK
7386.000	32.78	1.79	34.57	54.00	-19.43	H	AV
4924.000	54.01	-3.59	50.42	74.00	-23.58	V	PK
4924.000	42.33	-3.59	38.74	54.00	-15.26	V	AV
7386.000	48.17	1.79	49.96	74.00	-24.04	V	PK
7386.000	34.88	1.79	36.67	54.00	-17.33	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz and the data is not display.

## 8. Out of Band Emissions

### 8.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 8.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2013-05-07	2014-05-06
EMI Test Receiver	R&S	ESVB	825471/005	2013-05-07	2014-05-06
Pre-amplifier	Agilent	8447F	3113A06717	2013-05-07	2014-05-06
Pre-amplifier	Compliance Direction	PAP-0118	24002	2013-05-07	2014-05-06
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2013-04-20	2014-04-19
Horn Antenna	ETS	3117	00086197	2013-04-20	2014-04-19

### 8.3 Test Procedure

According to the KDB 558074 D01 V02, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.



According to the KDB 558074 D01 V03, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW  $\geq$  300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

#### 8.4 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar


#### 8.5 Summary of Test Results/Plots

Test Mode	Test Frequency MHz	Limit dBuV / dBc	Result
802.11b	2390.00	<54 dBuV	Pass
	2400.00	<54 dBuV	Pass
	2483.50	<54 dBuV	Pass
802.11g	2390.00	<54 dBuV	Pass
	2400.00	<54 dBuV	Pass
	2483.50	<54 dBuV	Pass
802.11n-HT20	2390.00	<54 dBuV	Pass
	2400.00	<54 dBuV	Pass
	2483.50	<54 dBuV	Pass

The edge emissions are below the FCC 15.209 Limits or complies with the 15.247(d) requirements.


Please refer to the test plots as below.

## 802.11b-Lowest Bandedge




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	33.08	-3.71	29.37	54.00	-24.63	Average Detector
	2310.000	45.79	-3.71	42.08	74.00	-31.92	Peak Detector
2	2390.000	37.38	-3.54	33.84	54.00	-20.16	Average Detector
	2390.000	53.27	-3.54	49.73	74.00	-24.27	Peak Detector
3	2397.840	51.24	-3.51	47.73	54.00	-6.27	Average Detector
	2397.840	68.80	-3.51	65.29	74.00	-8.71	Peak Detector
4	2400.000	48.25	-3.51	44.74	54.00	-9.26	Average Detector
	2400.000	62.88	-3.51	59.37	74.00	-14.63	Peak Detector

802.11b-Highest Bandedge




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2461.200	94.34	-3.37	90.97	/	/	Average Detector
	2461.200	106.36	-3.37	102.99	/	/	Peak Detector
2	2483.500	Delta = 55.77 dBc		35.20	54.00	-18.80	Average Detector
	2483.500			47.22	74.00	-26.78	Peak Detector
3	2500.000	35.74	-3.28	32.46	54.00	-21.54	Average Detector
	2500.000	48.62	-3.28	45.34	74.00	-28.66	Peak Detector

802.11g-Lowest Bandedge




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.000	33.06	-3.71	29.35	54.00	-24.65	Average Detector
	2310.000	46.17	-3.71	42.46	74.00	-31.54	Peak Detector
2	2390.000	46.62	-3.54	43.08	54.00	-10.92	Average Detector
	2390.000	60.68	-3.54	57.14	74.00	-16.86	Peak Detector
3	2400.000	49.02	-3.51	45.51	54.00	-8.49	Average Detector
	2400.000	69.56	-3.51	66.05	74.00	-7.95	Peak Detector

802.11g-Highest Bandedge




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2461.100	83.44	-3.37	80.07	/	/	Average Detector
	2461.100	101.62	-3.37	98.25	/	/	Peak Detector
2	2483.500	Delta = 40.88 dBc		39.19	54.00	-14.81	Average Detector
	2483.500			57.37	74.00	-16.63	Peak Detector
3	2500.000	39.00	-3.28	35.72	54.00	-18.28	Average Detector
	2500.000	54.45	-3.28	51.17	74.00	-22.83	Peak Detector

802.11n-HT20-Lowest Bandedge





No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.000	33.12	-3.71	29.41	54.00	-24.59	Average Detector
	2310.000	45.63	-3.71	41.92	74.00	-32.08	Peak Detector
2	2390.000	45.54	-3.54	42.00	54.00	-12.00	Average Detector
	2390.000	61.09	-3.54	57.55	74.00	-16.45	Peak Detector
3	2400.000	45.88	-3.51	42.37	54.00	-11.63	Average Detector
	2400.000	65.93	-3.51	62.42	74.00	-11.58	Peak Detector

802.11n-HT20-Highest Bandedge




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2461.000	82.07	-3.37	78.70	/	/	Average Detector
	2461.000	101.42	-3.37	98.05	/	/	Peak Detector
2	2483.500	Delta = 40.00 dBc		38.70	54.00	-15.30	Average Detector
	2483.500			58.05	74.00	-15.95	Peak Detector
3	2500.000	38.74	-3.28	35.46	54.00	-18.54	Average Detector
	2500.000	53.55	-3.28	50.27	74.00	-23.73	Peak Detector


**Conducted Spurious Emissions****802.11b Low Bandedge****802.11b Middle Bandedge**




802.11b High Bandedge




802.11g Low Bandedge




802.11g Middle Bandedge




802.11g High Bandedge




## 802.11n-HT20 Low Bandedge



## 802.11n-HT20 Middle Bandedge



802.11n-HT20 High Bandedge



## 9. Conducted Emissions

### 9.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is  $\pm 2.88$  dB.

### 9.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2013-05-07	2014-05-06
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2013-05-07	2014-05-06
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2013-05-07	2014-05-06


### 9.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### 9.4 Basic Test Setup Block Diagram



## 9.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

## 9.6 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency ..... 150 kHz  
Stop Frequency..... 30 MHz  
Sweep Speed ..... Auto  
IF Bandwidth..... 10 kHz  
Quasi-Peak Adapter Bandwidth ..... 9 kHz  
Quasi-Peak Adapter Mode ..... Normal

## 9.7 Summary of Test Results/Plots

According to the data in section 9.8, the EUT complied with the FCC Part 15.207 Conducted margin for a Class B device, with the *worst* margin reading of:

**-16.83 dB at 0.154 MHz in the Line mode, Peak detector, 0.15-30MHz**

## 9.8 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT:PCBA

Tested Model:M730

Operating Condition:Transmitting


Comment:Input AC 120V/60Hz adapter; Output DC 12V

Test Specification:Neutral



EDIT PEAK LIST (Prescan Results)			
Trace1:	-QP		
Trace2:	-AV		
Trace3:	---		
TRACE	FREQUENCY	LEVEL dBµV	DELTA LIMIT dB
1 Max Peak	174 kHz	46.62	-18.14
1 Max Peak	494 kHz	32.83	-23.26
2 Average	778 kHz	23.81	-22.18
1 Max Peak	886 kHz	31.53	-24.46

Test Specification: Line



EDIT PEAK LIST (Prescan Results)			
Trace1:	-QP		
Trace2:	-AV		
Trace3:	---		
TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1 Max Peak	154 kHz	48.94	-16.83
1 Max Peak	602 kHz	33.92	-22.07
2 Average	778 kHz	24.35	-21.64

\*\*\*\*\* END OF REPORT \*\*\*\*\*