

---

# FCC Test Report

---

Report No.: AGC04025151201FE03

**FCC ID** : 2AALP-HXHP400  
**APPLICATION PURPOSE** : Original Equipment  
**PRODUCT DESIGNATION** : Bluetooth headphone  
**BRAND NAME** : Jam  
**MODEL NAME** : HX-HP400  
**CLIENT** : Shenzhen XSOUND Innovation Technologies Co.,Ltd.  
**DATE OF ISSUE** : Jan.23,2016  
**STANDARD(S)** : FCC Part 15 Rules  
**TEST PROCEDURE(S)**  
**REPORT VERSION** : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jan.23,2016	Valid	Original Report

## TABLE OF CONTENTS


<b>1. VERIFICATION OF CONFORMITY .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
2.1. PRODUCT DESCRIPTION .....	5
2.2. TABLE OF CARRIER FREQUENCYS .....	5
<b>3. MEASUREMENT UNCERTAINTY .....</b>	<b>7</b>
<b>4. DESCRIPTION OF TEST MODES.....</b>	<b>7</b>
<b>5. SYSTEM TEST CONFIGURATION .....</b>	<b>9</b>
5.1. CONFIGURATION OF EUT SYSTEM.....	9
5.2. EQUIPMENT USED IN EUT SYSTEM.....	9
5.3. SUMMARY OF TEST RESULTS.....	9
<b>6. TEST FACILITY .....</b>	<b>10</b>
<b>7.ALL TEST EQUIPMENT LIST .....</b>	<b>10</b>
<b>8. RADIATED EMISSION .....</b>	<b>12</b>
8.1TEST LIMIT.....	12
8.2. MEASUREMENT PROCEDURE.....	13
8.3. TEST SETUP .....	15
8.4. TEST RESULT .....	17
<b>9. BAND EDGE EMISSION .....</b>	<b>43</b>
9.1. MEASUREMENT PROCEDURE.....	43
9.2 TEST SETUP.....	43
9.3 RADIATED TEST RESULT .....	44
<b>10. 20DB BANDWIDTH.....</b>	<b>52</b>
10.1. MEASUREMENT PROCEDURE.....	52
10.2. TEST SET-UP .....	52
10.3. LIMITS AND MEASUREMENT RESULTS.....	52
<b>11. FCC LINE CONDUCTED EMISSION TEST .....</b>	<b>62</b>
11.1. LIMITS OF LINE CONDUCTED EMISSION TEST .....	62
11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST .....	62
11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST .....	63
11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST .....	63
11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST .....	64
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>	<b>68</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>71</b>


## 1. VERIFICATION OF CONFORMITY

<b>Applicant</b>	Shenzhen XSOUND Innovation Technologies Co.,Ltd.
<b>Address</b>	Building C, Junxing industrial zone B, Haoye Road, Heping, Fuyong , Baoan, Shenzhen, 518103, China
<b>Manufacturer</b>	Shenzhen XSOUND Innovation Technologies Co.,Ltd.
<b>Address</b>	Building C, Junxing industrial zone B, Haoye Road, Heping, Fuyong , Baoan, Shenzhen, 518103, China
<b>Product Designation</b>	Bluetooth headphone
<b>Brand Name</b>	Jam
<b>Test Model</b>	HX-HP400
<b>Date of test</b>	Jan.04,2016 to Jan.06,2016
<b>Deviation</b>	None
<b>Condition of Test Sample</b>	Normal
<b>Report Template</b>	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Tested By   
Time Huang(Huang Nanhui) Jan.23,2016

Reviewed By   
Forrest Lei(Lei Yonggang) Jan.23,2016

Approved By   
Solger Zhang(Zhang Hongyi)  
Authorized Officer Jan.23,2016

## 2. GENERAL INFORMATION

### 2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

<b>Operation Frequency</b>	2.402 GHz to 2.480GHz
<b>RF Output Power</b>	1.90dBm(Max)
<b>Bluetooth Version</b>	V4.0
<b>Modulation</b>	GFSK, $\pi/4$ -DQPSK, 8DPSK GFSK
<b>Number of channels</b>	79 for BR/EDR, 40 for BLE
<b>Hardware Version</b>	HX-HP400-R2
<b>Software Version</b>	REV-2
<b>Antenna Designation</b>	PCB antenna (Met 15.203 Antenna requirement)
<b>Antenna Gain</b>	1.95dBi
<b>Power Supply</b>	DC 3.7V by battery
Note: The USB port only used for charging and can't be used to transfer data with PC.	

### 2.2. TABLE OF CARRIER FREQUENCIES

BR/EDR channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

BLE Channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2404MHZ
	:	:
	38	2478 MHZ
	39	2480 MHZ

### 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.18\text{dB}$
2	All emissions, radiated	$\pm 3.91\text{dB}$
3	Temperature	$\pm 0.5^\circ\text{C}$
4	Humidity	$\pm 2\%$


### 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel $\pi/4$ -DQPSK
5	Middle channel $\pi/4$ -DQPSK
6	High channel $\pi/4$ -DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	BT Link with charging
11	BT Link without charging

Note:

1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. The EUT used fully-charged battery when tested

## Software Setting






## 5. SYSTEM TEST CONFIGURATION


### 5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



**Note:** Owing to the EUT has own battery, Testing will be performed while PC or adapter remove.

Configure 2: (Control continuous TX)



### 5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Bluetooth headphone	Jam	HX-HP400	EUT
2	PC	SONY	E1412AYCW	A.E
3	Control box	N/A	N/A	A.E
4	USB Cable	N/A	0.6m, unshielded	A.E
5	Adapter	ETPCA-050100U3W	N/A	A.E
6	Temporary Antenna Connector	T10	N/A	A.E

### 5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
N/A	BANDWIDTH	Compliant

## 6. TEST FACILITY

<b>Site</b>	Dongguan Precise Testing Service Co., Ltd.
<b>Location</b>	Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan, Guangdong, China,
<b>FCC Registration No.</b>	371540
<b>Description</b>	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009.

## 7. ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2015	July 3, 2016
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2015	July 3, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2015	June 5, 2016
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2015	June 5, 2016
Radiation Cable 1	MXT	RS1	R005	June 6, 2015	June 5, 2016
Radiation Cable 2	MXT	RS1	R006	June 6, 2015	June 5, 2016

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2015	July 10, 2016
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2015	July 6, 2016
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2015	July 7, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2015	June 5, 2016
Radiation Cable 1	MXT	RS1	R005	June 6, 2015	June 5, 2016
Radiation Cable 2	MXT	RS1	R006	June 6, 2015	June 5, 2016

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	- Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Artificial Mains Network	Narda	L2-16B	000WX31025	July 8, 2015	July 7, 2016
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 8, 2015	July 7, 2016
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2015	July 3, 2016
Shielded Room	CHENGYU	843	PTS-002	June 6,2015	June 5,2016
Conduction Cable	MXT	SE1	S003	June 6,2015	June 5,2016

## 8. RADIATED EMISSION

### 8.1 TEST LIMIT

#### Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

#### Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		$\mu$ V/m	dB( $\mu$ V)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other: 74.0 dB( $\mu$ V)/m (Peak) 54.0 dB( $\mu$ V)/m (Average)	

Remark: (1) Emission level  $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$   
 (2) The smaller limit shall apply at the cross point between two frequency bands.  
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

## 8.2. MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1.5MHz VBW and RBW for peak reading. Then 1.5MHz RBW and 10Hz VBW for average reading in spectrum analyzer.

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1.5MHz/1.5MHz for Peak, 1.5MHz/10Hz for Average


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

### 8.3. TEST SETUP


#### Radiated Emission Test-Setup Frequency Below 30MHz



#### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



## RADIATED EMISSION TEST SETUP ABOVE 1000MHz





8.4. TEST RESULT


(Worst modulation:GFSK)  
FOR BR/EDR

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL




Site: Conduction	Polarization: <i>Horizontal</i>	Temperature: 23.1
Limit: FCC Class B 3M Radiation	Power:	Humidity: 54.1 %
EUT: Bluetooth Headphone	Distance:	
M/N: HX-HP400		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		136.7000	13.41	13.66	27.07	43.50	-16.43	peak			
2	*	196.5166	23.07	11.84	34.91	43.50	-8.59	peak			
3		296.7500	20.71	14.86	35.57	46.00	-10.43	peak			
4		387.2832	16.43	18.99	35.42	46.00	-10.58	peak			
5		563.5000	12.36	22.82	35.18	46.00	-10.82	peak			
6		728.4000	6.34	26.01	32.35	46.00	-13.65	peak			

RESULT: PASS

## RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: Conduction

Polarization: *Vertical*

Temperature: 23.1

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.1 %

EUT: Bluetooth Headphone

Distance:

M/N: HX-HP400

Mode: Low Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		68.7999	24.77	4.73	29.50	40.00	-10.50	peak			
2	*	141.5500	21.46	15.21	36.67	43.50	-6.83	peak			
3		215.9167	25.45	10.56	36.01	43.50	-7.49	peak			
4		298.3667	16.60	15.36	31.96	46.00	-14.04	peak			
5		503.6833	13.30	21.23	34.53	46.00	-11.47	peak			
6		665.3500	5.34	24.26	29.60	46.00	-16.40	peak			

**RESULT: PASS****Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

## RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: Conduction

Polarization: *Horizontal*

Temperature: 23.1

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.1 %

EUT: Bluetooth Headphone

Distance:

M/N: HX-HP400


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		136.7000	17.91	13.66	31.57	43.50	-11.93	peak			
2		183.5833	23.22	11.24	34.46	43.50	-9.04	peak			
3		296.7500	20.21	14.86	35.07	46.00	-10.93	peak			
4		384.0500	16.89	18.96	35.85	46.00	-10.15	peak			
5	*	563.5000	14.36	22.82	37.18	46.00	-8.82	peak			
6		728.4000	5.84	26.01	31.85	46.00	-14.15	peak			

**RESULT: PASS**

## RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: Conduction

Polarization: **Vertical**

Temperature: 23.1

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.1 %

EUT: Bluetooth Headphone

Distance:

M/N: HX-HP400

Mode: Middle Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	151.2500	21.01	15.27	36.28	43.50	-7.22	peak			
2		215.9167	24.95	10.56	35.51	43.50	-7.99	peak			
3		298.3667	18.10	15.36	33.46	46.00	-12.54	peak			
4		398.6000	15.82	19.06	34.88	46.00	-11.12	peak			
5		599.0667	8.89	22.73	31.62	46.00	-14.38	peak			
6		799.5333	3.14	27.31	30.45	46.00	-15.55	peak			

**RESULT: PASS****Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL




Site: Conduction Polarization: *Horizontal* Temperature: 23.1  
Limit: FCC Class B 3M Radiation Power: Humidity: 54.1 %  
EUT: Bluetooth Headphone Distance:  
M/N: HX-HP400  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		136.7000	13.91	13.66	27.57	43.50	-15.93	peak			
2	*	215.9167	25.40	10.38	35.78	43.50	-7.72	peak			
3		296.7500	21.21	14.86	36.07	46.00	-9.93	peak			
4		384.0500	17.39	18.96	36.35	46.00	-9.65	peak			
5		555.4167	14.11	22.62	36.73	46.00	-9.27	peak			
6		799.5333	6.55	27.31	33.86	46.00	-12.14	peak			

RESULT: PASS

## RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: Conduction

Polarization: **Vertical**

Temperature: 23.1

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.1 %

EUT: Bluetooth Headphone

Distance:

M/N: HX-HP400

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		68.8000	23.27	4.73	28.00	40.00	-12.00	peak			
2	!	141.5500	22.46	15.21	37.67	43.50	-5.83	peak			
3	*	215.9167	27.45	10.56	38.01	43.50	-5.49	peak			
4		398.6000	17.82	19.06	36.88	46.00	-9.12	peak			
5		432.5500	10.54	20.06	30.60	46.00	-15.40	peak			
6		599.0667	11.39	22.73	34.12	46.00	-11.88	peak			

**RESULT: PASS****Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.


FOR BLE

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL




Site: Conduction Polarization: **Horizontal** Temperature: 23.1  
Limit: FCC Class B 3M Radiation Power: Humidity: 54.1 %  
EUT: Bluetooth Headphone Distance:  
M/N: HX-HP400  
Mode: Low Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	175.5000	23.37	10.90	34.27	43.50	-9.23	peak			
2		296.7500	20.21	14.86	35.07	46.00	-10.93	peak			
3		411.5332	15.61	19.42	35.03	46.00	-10.97	peak			
4		555.4166	12.11	22.62	34.73	46.00	-11.27	peak			
5		699.3000	6.40	25.17	31.57	46.00	-14.43	peak			
6		799.5333	5.05	27.31	32.36	46.00	-13.64	peak			

RESULT: PASS

## RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: Conduction

Polarization: **Vertical**

Temperature: 23.1

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.1 %

EUT: Bluetooth Headphone

Distance:

M/N: HX-HP400

Mode: Low Channel TX

Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	151.2500	20.51	15.27	35.78	43.50	-7.72	peak			
2		215.9167	23.45	10.56	34.01	43.50	-9.49	peak			
3		299.9833	16.95	15.41	32.36	46.00	-13.64	peak			
4		398.6000	14.32	19.06	33.38	46.00	-12.62	peak			
5		503.6833	11.80	21.23	33.03	46.00	-12.97	peak			
6		665.3500	4.84	24.26	29.10	46.00	-16.90	peak			

**RESULT: PASS****Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



## RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: Conduction

Polarization: *Horizontal*

Temperature: 23.1

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.1 %

EUT: Bluetooth Headphone

Distance:

M/N: HX-HP400


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		136.7000	20.41	13.66	34.07	43.50	-9.43	peak			
2	*	215.9167	24.40	10.38	34.78	43.50	-8.72	peak			
3		296.7500	19.71	14.86	34.57	46.00	-11.43	peak			
4		479.4333	14.53	20.91	35.44	46.00	-10.56	peak			
5		555.4166	13.61	22.62	36.23	46.00	-9.77	peak			
6		983.8333	3.58	29.68	33.26	54.00	-20.74	peak			

**RESULT: PASS**

## RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: Conduction

Polarization: **Vertical**

Temperature: 23.1

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.1 %

EUT: Bluetooth Headphone

Distance:

M/N: HX-HP400

Mode: Middle Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	139.9333	18.92	15.17	34.09	43.50	-9.41	peak			
2		215.9167	22.95	10.56	33.51	43.50	-9.99	peak			
3		298.3667	19.10	15.36	34.46	46.00	-11.54	peak			
4		451.9500	10.55	20.61	31.16	46.00	-14.84	peak			
5		597.4500	8.25	22.72	30.97	46.00	-15.03	peak			
6		896.5333	0.90	28.52	29.42	46.00	-16.58	peak			

**RESULT: PASS****Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL




Site: Conduction	Polarization: <i>Horizontal</i>	Temperature: 23.1
Limit: FCC Class B 3M Radiation	Power:	Humidity: 54.1 %
EUT: Bluetooth Headphone	Distance:	
M/N: HX-HP400		
Mode: High Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		199.7500	22.13	11.99	34.12	43.50	-9.38	peak			
2	*	387.2832	18.43	18.99	37.42	46.00	-8.58	peak			
3		408.3000	17.81	19.32	37.13	46.00	-8.87	peak			
4		568.3500	12.42	22.94	35.36	46.00	-10.64	peak			
5		728.4000	5.34	26.01	31.35	46.00	-14.65	peak			
6		799.5333	5.05	27.31	32.36	46.00	-13.64	peak			

RESULT: PASS

## RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: Conduction

Polarization: *Vertical*

Temperature: 23.1

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.1 %

EUT: Bluetooth Headphone

Distance:

M/N: HX-HP400

Mode: High Channel TX

Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	183.5833	22.81	13.16	35.97	43.50	-7.53	peak			
2		398.6000	16.32	19.06	35.38	46.00	-10.62	peak			
3		432.5500	14.54	20.06	34.60	46.00	-11.40	peak			
4		599.0667	10.39	22.73	33.12	46.00	-12.88	peak			
5		665.3500	7.34	24.26	31.60	46.00	-14.40	peak			
6		799.5333	3.64	27.31	30.95	46.00	-15.05	peak			

**RESULT: PASS****Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION ABOVE 1GHZ  
FOR BR/EDR

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL




Site: Conduction	Polarization: <i>Horizontal</i>	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-	Power:	Humidity: 60 %
EUT: Bluetooth Headphone	Distance: 3m	
M/N: HX-HP400		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	104.70	-9.68	95.02	114.00	-18.98	peak			
2		3633.333	50.39	-7.07	43.32	74.00	-30.68	peak			
3		4516.667	47.56	-3.07	44.49	74.00	-29.51	peak			
4	*	2402.000	93.09	-9.68	83.41	94.00	-10.59	AVG	100	191	

RESULT: PASS

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: Conduction

Polarization: **Vertical**

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance: 3m

M/N: HX-HP400


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	104.74	-9.68	95.06	114.00	-18.94	peak			
2		4075.000	48.91	-4.55	44.36	74.00	-29.64	peak			
3		5250.000	46.52	-1.81	44.71	74.00	-29.29	peak			
4	*	2402.000	92.84	-9.68	83.16	94.00	-10.84	AVG	100	241	

**RESULT: PASS**

# RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL




Site: Conduction Polarization: **Horizontal** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: Bluetooth Headphone Distance: 3m  
M/N: HX-HP400  
Mode: Middle Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	108.77	-9.63	99.14	114.00	-14.86	peak			
2		3900.000	48.98	-5.43	43.55	74.00	-30.45	peak			
3		4883.333	45.54	-2.11	43.43	74.00	-30.57	peak			
4	*	2441.000	94.46	-9.63	84.83	94.00	-9.17	AVG	100	187	

**RESULT: PASS**

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: Conduction

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance: 3m

M/N: HX-HP400

Mode: Middle Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	108.67	-9.63	99.04	114.00	-14.96	peak			
2		3800.000	50.69	-6.04	44.65	74.00	-29.35	peak			
3		5250.000	46.60	-1.81	44.79	74.00	-29.21	peak			
4	*	2441.000	95.86	-9.63	86.23	94.00	-7.77	AVG	100	243	

**RESULT: PASS**



## RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: Conduction

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance: 3m

M/N: HX-HP400


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	107.88	-9.59	98.29	114.00	-15.71	peak			
2		3750.000	50.56	-6.35	44.21	74.00	-29.79	peak			
3		5150.000	46.65	-1.80	44.85	74.00	-29.15	peak			
4	*	2480.000	92.88	-9.59	83.29	94.00	-10.71	AVG	100	193	

**RESULT: PASS**

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: Conduction

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance: 3m

M/N: HX-HP400

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	107.85	-9.59	98.26	114.00	-15.74	peak			
2		3425.000	52.50	-7.96	44.54	74.00	-29.46	peak			
3		4750.000	47.13	-2.45	44.68	74.00	-29.32	peak			
4	*	2480.000	92.78	-9.59	83.19	94.00	-10.81	AVG	100	245	

**RESULT: PASS****Note:** 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.


### Field strength of the fundamental signal

#### Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	104.70	-9.68	95.02	114	-18.98	Horizontal
2402	104.74	-9.68	95.06	114	-18.94	Vertical
2441	108.77	-9.63	99.14	114	-14.86	Horizontal
2441	108.67	-9.63	99.04	114	-14.96	Vertical
2480	107.88	-9.59	98.29	114	-15.71	Horizontal
2480	107.85	-9.59	98.26	114	-15.74	Vertical

#### Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	93.09	-9.68	83.41	94	-10.59	Horizontal
2402	92.84	-9.68	83.16	94	-10.84	Vertical
2441	94.46	-9.63	84.83	94	-9.17	Horizontal
2441	95.86	-9.63	86.23	94	-7.77	Vertical
2480	92.88	-9.59	83.29	94	-10.71	Horizontal
2480	92.78	-9.59	83.19	94	-10.81	Vertical

**FOR BLE****RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL**

Site: Conduction

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance: 3m

M/N: HX-HP400


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	104.26	-9.68	94.58	114.00	-19.42	peak			
2		3658.333	51.00	-6.91	44.09	74.00	-29.91	peak			
3		4583.333	46.65	-2.89	43.76	74.00	-30.24	peak			
4	*	2402.000	91.71	-9.68	82.03	94.00	-11.97	AVG	100	71	

**RESULT: PASS**

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: Conduction

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance: 3m

M/N: HX-HP400


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	104.22	-9.68	94.54	114.00	-19.46	peak			
2		3183.333	52.11	-8.19	43.92	74.00	-30.08	peak			
3		4883.333	47.46	-2.11	45.35	74.00	-28.65	peak			
4	*	2402.000	92.24	-9.68	82.56	94.00	-11.44	AVG	100	304	

**RESULT: PASS**

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: Conduction

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance: 3m

M/N: HX-HP400


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2440.000	105.77	-9.64	96.13	114.00	-17.87	peak			
2		3750.000	50.69	-6.35	44.34	74.00	-29.66	peak			
3		4825.000	46.39	-2.26	44.13	74.00	-29.87	peak			
4	*	2440.000	91.95	-9.64	82.31	94.00	-11.69	AVG	100	73	

**RESULT: PASS**

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: Conduction

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance: 3m

M/N: HX-HP400


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2440.000	105.70	-9.64	96.06	114.00	-17.94	peak			
2		3541.667	51.81	-7.63	44.18	74.00	-29.82	peak			
3		4466.667	47.91	-3.22	44.69	74.00	-29.31	peak			
4	*	2440.000	93.28	-9.64	83.64	94.00	-10.36	AVG	100	301	

**RESULT: PASS**

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: Conduction

Polarization: Horizontal

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance: 3m

M/N: HX-HP400

Mode: High Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	103.85	-9.59	94.26	114.00	-19.74	peak			
2		3233.333	52.61	-8.14	44.47	74.00	-29.53	peak			
3		4525.000	47.45	-3.04	44.41	74.00	-29.59	peak			
4	*	2480.000	91.84	-9.59	82.25	94.00	-11.75	AVG	100	78	

**RESULT: PASS**



## RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: Conduction

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance: 3m

M/N: HX-HP400

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	103.88	-9.59	94.29	114.00	-19.71	peak			
2		3716.667	50.91	-6.56	44.35	74.00	-29.65	peak			
3		4666.667	46.44	-2.67	43.77	74.00	-30.23	peak			
4	*	2480.000	91.96	-9.59	82.37	94.00	-11.63	AVG	100	299	

**RESULT: PASS**

**Note:** 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

### Field strength of the fundamental signal

#### Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	104.26	-9.68	94.58	114	-19.42	Horizontal
2402	104.22	-9.68	94.54	114	-19.46	Vertical
2440	105.77	-9.64	96.13	114	-17.87	Horizontal
2440	105.70	-9.64	96.06	114	-17.94	Vertical
2480	103.85	-9.59	94.26	114	-19.74	Horizontal
2480	103.88	-9.59	94.29	114	-19.71	Vertical

#### Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	91.71	-9.68	82.03	94	-11.97	Horizontal
2402	92.24	-9.68	82.56	94	-11.44	Vertical
2440	91.95	-9.64	82.31	94	-11.69	Horizontal
2440	93.28	-9.64	83.64	94	-10.36	Vertical
2480	91.84	-9.59	82.25	94	-11.75	Horizontal
2480	91.96	-9.59	82.37	94	-11.63	Vertical

## 9. BAND EDGE EMISSION

### 9.1. MEASUREMENT PROCEDURE

1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.


2Max hold the trace of the setp 1,and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.

3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=VBW=1.5MHz / Sweep=AUTO

(b) AVERAGE: RBW=1.5MHz ; VBW=1/on time(1KHz) / Sweep=AUTO

### 9.2 TEST SETUP

RADIATED EMISSION TEST SETUP




9.3 RADIATED TEST RESULT

(Worst modulation: GFSK)

FOR BR/EDR


TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: Conduction	Polarization: <i>Horizontal</i>	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: Bluetooth Headphone	Distance:	
M/N: HX-HP400		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2305.917	30.20	10.22	40.42	74.00	-33.58	peak			
2		2390.000	30.50	10.31	40.81	74.00	-33.19	peak			
3	*	2402.000	84.72	10.32	95.04	74.00	21.04	peak			


TEST PLOT OF BAND EDGE FOR LOW CHANNEL –Vertical



Site: Conduction	Polarization: <i>Vertical</i>	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: Bluetooth Headphone	Distance:	
M/N: HX-HP400		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2275.850	30.52	10.18	40.70	74.00	-33.30	peak			
2		2390.000	29.71	10.31	40.02	74.00	-33.98	peak			
3	*	2402.000	84.59	10.32	94.91	74.00	20.91	peak			

## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: Conduction

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance:


M/N: HX-HP400

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	88.05	10.41	98.46	74.00	24.46	peak			
2		2483.500	30.19	10.41	40.60	74.00	-33.40	peak			
3		2496.407	31.71	10.43	42.14	74.00	-31.86	peak			

## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: Conduction

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance:

M/N: HX-HP400

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	87.82	10.41	98.23	74.00	24.23	peak			
2		2483.500	29.76	10.41	40.17	74.00	-33.83	peak			
3		2492.117	31.24	10.42	41.66	74.00	-32.34	peak			

**RESULT: PASS****Note:** The other modes radiation emission have enough 20dB margin.


Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.

FOR BLE

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal




Site: Conduction	Polarization: <i>Horizontal</i>	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: Bluetooth Headphone	Distance:	
M/N: HX-HP400		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2248.517	32.41	10.15	42.56	74.00	-31.44	peak			
2		2390.000	31.00	10.31	41.31	74.00	-32.69	peak			
3	*	2402.000	84.22	10.32	94.54	74.00	20.54	peak			



## TEST PLOT OF BAND EDGE FOR LOW CHANNEL –Vertical



Site: Conduction

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance:


M/N: HX-HP400

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2279.608	30.98	10.19	41.17	74.00	-32.83	peak			
2		2390.000	32.21	10.31	42.52	74.00	-31.48	peak			
3	*	2402.000	84.59	10.32	94.91	74.00	20.91	peak			

## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: Conduction

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance:


M/N: HX-HP400

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	83.55	10.41	93.96	74.00	19.96	peak			
2		2483.500	30.19	10.41	40.60	74.00	-33.40	peak			
3		2492.410	30.44	10.42	40.86	74.00	-33.14	peak			

## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: Conduction

Polarization: **Vertical**

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Headphone

Distance:

M/N: HX-HP400

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	83.82	10.41	94.23	74.00	20.23	peak			
2		2483.500	30.26	10.41	40.67	74.00	-33.33	peak			
3		2492.080	30.11	10.42	40.53	74.00	-33.47	peak			

**RESULT: PASS****Note:** The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.


## 10. 20DB BANDWIDTH

### 10.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel  
RBW  $\geq$  1% of the 20 dB bandwidth, VBW  $\geq$  RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

### 10.2. TEST SET-UP

(BLOCK DIAGRAM OF CONFIGURATION)




Note: The EUT has been used temporary antenna connector for testing.

### 10.3. LIMITS AND MEASUREMENT RESULTS


FOR BR/EDR

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.095	PASS
	Middle Channel	1.104	PASS
	High Channel	1.090	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




BLUETOOTH 2Mbps LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.358	PASS
	Middle Channel	1.359	PASS
	High Channel	1.346	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL






BLUETOOTH 3Mbps LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.374	PASS
	Middle Channel	1.369	PASS
	High Channel	1.366	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




FOR BLE

BLUETOOTH LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.203	PASS
	Middle Channel	1.193	PASS
	High Channel	1.221	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



## 11. FCC LINE CONDUCTED EMISSION TEST


### 11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.( dBuV)	Average( dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



### **11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST**

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by PC or by adapter which received 120V/60Hz power by a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

### **11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST**

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

**11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST**  
**BY ADAPTER (WORST CASE)**  
**FOR BR/EDR**

Line Conducted Emission Test Line 1-L




Site: Conduction Phase: **L1** Temperature: 24.1  
Limit: FCC Class B Conduction(QP) Power: Humidity: 55.1 %  
EUT: Bluetooth Headphone  
M/N: HX-HP400  
Mode: BT Link with charging  
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.5660	18.24		4.96	10.34	28.58		15.30	56.00	46.00	-27.42	-30.70	P	
2	0.6820	19.84		6.29	10.34	30.18		16.63	56.00	46.00	-25.82	-29.37	P	
3	1.1100	16.72		2.79	10.37	27.09		13.16	56.00	46.00	-28.91	-32.84	P	
4	1.9340	17.61		4.01	10.24	27.85		14.25	56.00	46.00	-28.15	-31.75	P	
5	6.5339	25.41		13.47	10.30	35.71		23.77	60.00	50.00	-24.29	-26.23	P	
6	17.3699	25.97		12.79	10.13	36.10		22.92	60.00	50.00	-23.90	-27.08	P	



Line Conducted Emission Test Line 2-N




Site: Conduction Phase: **N** Temperature: 24.1  
Limit: FCC Class B Conduction(QP) Power: Humidity: 55.1 %  
EUT: Bluetooth Headphone  
M/N: HX-HP400  
Mode: BT Link with charging  
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.4540	20.94		10.37	10.37	31.31		20.74	56.80	46.80	-25.49	-26.06	P	
2	0.6500	24.17		11.26	10.33	34.50		21.59	56.00	46.00	-21.50	-24.41	P	
3	0.9540	16.48		7.46	10.39	26.87		17.85	56.00	46.00	-29.13	-28.15	P	
4	1.5140	14.52		6.00	10.38	24.90		16.38	56.00	46.00	-31.10	-29.62	P	
5	6.4820	19.14		10.21	10.30	29.44		20.51	60.00	50.00	-30.56	-29.49	P	
6	17.0500	15.21		1.52	10.13	25.34		11.65	60.00	50.00	-34.66	-38.35	P	

## FOR BLE

## Line Conducted Emission Test Line 1-L



Site: Conduction

Phase: L1

Temperature: 24.1

Limit: FCC Class B Conduction(QP)

Power:

Humidity: 55.1 %

EUT: Bluetooth Headphone


M/N: HX-HP400

Mode: BT Link with charging

Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.4940	19.44		7.26	10.40	29.84		17.66	56.10	46.10	-26.26	-28.44	P	
2	0.6740	18.45		5.70	10.34	28.79		16.04	56.00	46.00	-27.21	-29.96	P	
3	1.4260	15.82		4.04	10.38	26.20		14.42	56.00	46.00	-29.80	-31.58	P	
4	3.3540	16.67		4.97	10.52	27.19		15.49	56.00	46.00	-28.81	-30.51	P	
5	6.6460	23.93		11.75	10.32	34.25		22.07	60.00	50.00	-25.75	-27.93	P	
6	17.1820	23.48		11.58	10.13	33.61		21.71	60.00	50.00	-26.39	-28.29	P	

### Line Conducted Emission Test Line 2-N




Site: Conduction Phase: **N** Temperature: 24.1  
Limit: FCC Class B Conduction(QP) Power: Humidity: 55.1 %  
EUT: Bluetooth Headphone  
M/N: HX-HP400  
Mode: BT Link with charging  
Note:


No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.4540	22.92		14.29	10.37	33.29		24.66	56.80	46.80	-23.51	-22.14	P	
2	0.6700	22.65		8.44	10.34	32.99		18.78	56.00	46.00	-23.01	-27.22	P	
3	0.9540	18.50		9.75	10.39	28.89		20.14	56.00	46.00	-27.11	-25.86	P	
4	1.3460	14.92		2.36	10.38	25.30		12.74	56.00	46.00	-30.70	-33.26	P	
5	6.8140	20.16		10.76	10.34	30.50		21.10	60.00	50.00	-29.50	-28.90	P	
6	16.9180	17.09		5.76	10.13	27.22		15.89	60.00	50.00	-32.78	-34.11	P	



## APPENDIX A: PHOTOGRAPHS OF TEST SETUP


### FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP









## APPENDIX B: PHOTOGRAPHS OF EUT

All VIEW OF EUT



TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT





BACK VIEW OF EUT




LEFT VIEW OF EUT



RIGHT VIEW OF EUT




VIEW OF EUT (OPEN)



VIEW OF EUT (PORT)




INTERNAL VIEW OF EUT-1







INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3



INTERNAL VIEW OF EUT-4




INTERNAL VIEW OF EUT-5





INTERNAL VIEW OF EUT-6



INTERNAL VIEW OF EUT-7



**ADAPTER VIEW(AE)**



**Note: The adapter above was provided by AGC Lab**

**----END OF REPORT----**