







ISO/IEC17025 Accredited Lab.

Report No: FCC 1307021 File reference No: 2013-07-31

Applicant: Shenzhen Zhihuang Technology Co., Ltd

Product: Radio Transmitter

Model No: ZC105A; ZC106A; ZC107A; ZC108A.

Trademark: Zhihuang

Test Standards: FCC Part 15 Subpart C, Paragraph 15.231

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4&FCC Part 15 Subpart C, Paragraph 15.231 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung Manager

Dated: July 31, 2013

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District, Shenzhen,CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 1307021 Page 2 of 28

Date: 2013-07-31



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meets with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.:899988.

IC- Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration No.: IC 5205A-02.

Page 3 of 28

Report No: 1307021 Date: 2013-07-31



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details.	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	5
3.0	Technical Details	6
3.1	Summary of Test Results	6
3.2	Test Standards	6
4.0	EUT Modification.	6
5.0	Power Line Conducted Emission Test.	7
5.1	Schematics of the Test.	7
5.2	Test Method and Test Procedure.	7
5.3	Configuration of the EUT	7
5.4	EUT Operating Condition.	7
5.5	Conducted Emission Limit.	7
5.6	Test Result	8
6.0	Radiated Emission test.	9
6.1	Test Method and Test Procedure.	9
6.2	Configuration of the EUT	9
6.3	EUT Operation Condition.	9
6.4	Radiated Emission Limit.	9
6.5	Test Result	11
7.0	20dB Bandwidth Test.	15
8.0	Deactivate Test	17
9.0	FCC ID Label	19
10.0	Photo of Testing.	20

Report No: 1307021 Page 4 of 28

Date: 2013-07-31



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-01

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: Shenzhen Zhihuang Technology Co., Ltd

Address: 4F, 3 Building, Yongxin Industrial Park, 89 No., Hengping Road, Henggang Town,

LongGang District, ShenZhen, China

Telephone: 0755-33291908/33291906

Fax: 0755-89233053

1.3 Description of EUT

Product: Radio Transmitter

Manufacturer: Shenzhen Zhihuang Technology Co., Ltd

Address: 4F, 3 Building, Yongxin Industrial Park, 89 No., Hengping Road, Henggang

Town, LongGang District, ShenZhen, China

Brand Name: Zhihuang Model Number: ZC105A;

Additional Model Name ZC106A; ZC107A; ZC108A.

Additional Trade Name N/A

Rating: 3VDC (2pcs AA batteries)

Operation Frequency 433.92MHz

Antenna Designation PCB Printed Antenna

1.4 Submitted Sample

2 Sample

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1307021 Page 5 of 28
Date: 2013-07-31

TIMEWAY TESTROLAS

1.5 Test Duration

2013-06-21 to 2013-07-31

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty = 4.7dB

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

2.0	Test Equipments						
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date		
Loop Antenna	EMCO	6502	00042960	2012-08-21	2013-08-20		
Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2012-08-21	2013-08-20		
3m OATS			N/A	2012-08-21	2013-08-20		
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2012-08-21	2013-08-20		
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2012-08-21	2013-08-20		
9*6*6 Anechoic			N/A	2012-08-21	2013-08-20		

Report No: 1307021 Page 6 of 28

Date: 2013-07-31



The EUT has been tested according to the following specifications:

3.0 Technical Details

3.1 Summary of test results

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.207	Conducted	N/A	N/A
	Emission Test		
FCC P	General	DACC	C1:1
FCC Part 15, Paragraph 15.209	Requirement	PASS	Compliant
	Radiated		
FCC Part 15, Paragraph 15.231 (b)	Emission Test	PASS	Compliant
FCC Part 15, Paragraph 15.231 (c)	20dB	PASS	Compliant
	Bandwidth		
	Testing		
FCC Part 15, Paragraph 15.231 (a) (1)	Deactivate	PASS	Compliant
	Testing		

3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.231

4.0 EUT Modification


No modification by Shenzhen Timeway Technology Consulting Co.,Ltd

Report No: 1307021 Date: 2013-07-31



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 500hm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model	FCC ID
Radio Transmitter	Shenzhen Zhihuang Technology	ZC105A; ZC106A; ZC107A;	2AALU105T108
	Co.,Ltd	ZC108A.	

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

Device	Manufacturer	Model	FCC	Cable
			ID/DOC	
N/A				

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1307021 Page 8 of 28

Date: 2013-07-31



5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

	Frequency Class A Limi		mits (dB μ V) Class B Limits (dB μ		nits (dB µ V)
	(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level
0.1	5 ~ 0.50	79.0	66.0	66.0~56.0*	56.0~46.0*
0.5	$50 \sim 5.00$	73.0	60.0	56.0	46.0
5.0	00 ~ 30.00	73.0	60.0	60.0	50.0

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Note: Owing to DC operation of EUT, this test item is not performed

Report No: 1307021 Page 9 of 28


Date: 2013-07-31



6 **Radiated Emission Test**

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 -2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
- The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency. (4)
- Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with (5) all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- The antenna polarization: Vertical polarization and Horizontal polarization. (6)

Distance = 3mComputer Pre -Amplifier



6.2 Configuration of The EUT Same as section 5.3 of this report

Block diagram of Test setup

EUT Operating Condition 6.3 Same as section 5.4 of this report. Report No: 1307021 Date: 2013-07-31



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

A FCC Part 15 Subpart C Paragraph 15.231 Limit

11 1 CC 1 and 13 Subpart C 1				
Fundamental Frequency (MHz)	Field Strength of		Field Strength of Spurious	
	Fundamental		Em	ission
	uV/m	dBuV/m	uV/m	dBuV/m
40.66-40.70	2250	67.04	225	47.04
70-130	1250	61.94	125	41.94
130-174	1250-3370	61.94-70.55	125-375	41.94-51.48
174-260	3750	71.48	375	51.48
260-470	3750-12500	71.48-81.94	375-1250	51.48-61.94
Above 470	12500	81.94	1250	61.94

Note:

- 1. RF Field Strength $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.
- 4. Linear interpolations for frequency ranges 130-174MHz and 260-470MHz
- 5.the above field strength limits are specified at a distance of 3-meters and the tighter limits apply at the band edges

B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-5G, the final emission level got using PK detector. And Average = peak(dBuV/m) duty cycle(dB)
- 6. New batteries were installed in the equipment under test for radiated emission testing.
- 7. Model ZC107A was the selected for the final test and it was the worst case.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1307021 Page 11 of 28

Date: 2013-07-31



6.5 Test result

A Fundamental and Harmonic Radiated Emission Data

Product:	Radio Transmitter	Test Mode:	Keeping Tx transmitting
Test Item:	Fundamental Radiated Emission and Spurious Emission Data	Temperature:	25℃
Test Voltage:	DC3V	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
434.00	54.35(PK)	Horizontal	100.82/80.82	-26.47
434.04	56.39(PK)	Vertical	100.82/80.82	-24.43
868.00	41.62(PK)	Horizontal	80.82/60.82	-19.20
868.00	44.86(PK)	Vertical	80.82/60.82	-15.96
1301.76	46.41(PK)	Horizontal	74/54	-7.59
1301.76	43.91(PK)	Vertical	74/54	-10.09
1735.68	44.51(PK)	Horizontal	80.82/60.82	-16.31
1735.68	42.01(PK)	Vertical	80.82/60.82	-18.81
2196.60	45.41(PK)	Horizontal	80.82/60.82	-15.41
2196.60		Vertical	80.82/60.82	-
2630.52		Horizontal	80.82/60.82	
2630.52		Vertical	80.82/60.82	
3037.44		Horizontal	80.82/60.82	
3037.44		Vertical	80.82/60.82	
3471.36		Horizontal	80.82/60.82	
3471.36		Vertical	80.82/60.82	
3905.28		Horizontal	80.82/60.82	
3905.28		Vertical	80.82/60.82	
4339.200		Horizontal	80.82/60.82	
4339.200		Vertical	80.82/60.82	


Note: Average value was not recorded because the PK value was less than the AV limit value.


Report No: 1307021 Date: 2013-07-31



Test Plot above 1G

Horizontal





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1307021 Date: 2013-07-31




Test Plot below 1GHz

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Tx Transmitting

Results: Pass

Please refer to following diagram for individual



Date: 15.JUL.2013 18:16:55

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
	-	Н	-
	-	Н	

The report refers only to the sample tested and does not apply to the bulk.

Page 14 of 28

Report No: 1307021 Date: 2013-07-31




Test Plot below 1GHz

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Tx Transmitting

Results: Pass

Please refer to following diagram for individual



Date: 15.JUL.2013 18:15:34

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
		V	

Report No: 1307021 Page 15 of 28

Date: 2013-07-31



7.0 20dB Bandwidth Testing

7.1 Requirement

Per 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

7.2 Test Procedure

With the EUT's antenna attached, the EUT's 20dB Bandwidth power was received by the test antenna which was connected to the spectrum analyzer with the START and STOP frequencies set to the EUT's operation band.

7.3 Test Data

Frequency (MHz)	20dB Bandwidth Emission (kHz)	Limit (MHz)	Result
433.92	58	1.08	Pass


Limit=Frequency x 0.25%=433.92x 0.25%=1.08MHz

Refer to attached plots:

Report No: 1307021 Page 16 of 28

Date: 2013-07-31





Date: 17.JUL.2013 15:34:47

Report No: 1307021 Page 17 of 28

Date: 2013-07-31




8.0 Deactivate Test

8.1 Requirement

Per 15.231(a) (1), a manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

8. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing The deactivation test was performed in the 3 meters chamber B test site, using the setup accordance with the ANSI C63.4 - 2003. The specification used was the FCC 15.231(a) limits.

8.3 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.


8.4 Test Data

Refer to attached plots:

Report No: 1307021 Page 18 of 28

Date: 2013-07-31





Date: 17.JUL.2013 15:44:23

Report No: 1307021 Page 19 of 28

Date: 2013-07-31




9.0 FCC ID Label

FCC ID: 2AALU105T108

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 20 of 28

Report No: 1307021 Date: 2013-07-31



10.0. Photo of testing

10.1 Conducted test View—N/A

10.2 Radiated emission test view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1307021 Date: 2013-07-31



10.3 Photo for the EUT

Outside View (ZC105A)





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1307021 Page 22 of 28

Date: 2013-07-31



Outside View (ZC105A)





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1307021 Page 23 of 28

Date: 2013-07-31



Inside View (ZC105A)





The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Report No: 1307021 Page 24 of 28

Date: 2013-07-31



Inside View (ZC105A)





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co .,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 25 of 28

Report No: 1307021 Date: 2013-07-31



Outside View (ZC107A)





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1307021 Page 26 of 28

Date: 2013-07-31



Outside View (ZC107A)




Report No: 1307021 Page 27 of 28

Date: 2013-07-31



Inside View (ZC107A)






Page 28 of 28

Report No: 1307021 Date: 2013-07-31



Inside View (ZC107A)





End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.