



FCC Part 15C Test Report

FCC ID: 2AAMDTX-3CH

Product Name:	Silent Symphony Headphone / Transmitter
Trademark:	N/A
Model Name :	TX-3CH
Prepared For :	MICA ELECTRONIC CORP /DBA VOCOPRO
Address :	1728 CURTISS COURT. LA VERNE, CA 91750, USA
Prepared By :	Shenzhen BCTC Technology Co., Ltd.
Address :	No.101,Yousong Road,Longhua New District, Shenzhen,China
Test Date:	Sep. 02 - Sep. 10, 2015
Date of Report :	Sep. 10, 2015
Report No.:	BCTC-15090251



TEST RESULT CERTIFICATION

Applicant's name..... : MICA ELECTRONIC CORP /DBA VOCOPRO

Address..... : 1728 CURTISS COURT. LA VERNE, CA 91750, USA

Manufacture's Name..... : **Shenzhen Changyin Electronic co.,Ltd**

Address..... : 4/F, Bldg1, Guanfeng Industrial Park, Jiuwei New Village, Xixiang,
Bao'an District, Shenzhen, 518126, China

Product description

Product name..... : Silent Symphony Headphone / Transmitter

Model and/or type reference : TX-3CH

Serial Model..... : N/A

Standards..... : FCC Part15.249

Test procedure..... ANSI C63.10-2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Testing Engineer : _____

Eric Yang

(Eric Yang)

Technical Manager : _____

Sophie Lu

(Sophia Lee)

Authorized Signatory : _____

Casey Wang

(Casey Wang)



**Table of Contents**

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	11
3.1.2 TEST PROCEDURE	11
3.1.3 DEVIATION FROM TEST STANDARD	11
3.1.4 TEST SETUP	12
3.1.5 EUT OPERATING CONDITIONS	12
3.1.6 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 RADIATED EMISSION LIMITS	15
3.2.2 TEST PROCEDURE	16
3.2.3 DEVIATION FROM TEST STANDARD	16
3.2.4 TEST SETUP	17
3.2.5 EUT OPERATING CONDITIONS	18
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	19
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	20
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	26
4 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	28
4.1 DEVIATION FROM STANDARD	29
4.2 TEST SETUP	29
4.3 EUT OPERATION CONDITIONS	29
4.4 TEST RESULTS	29
5 . BANDWIDTH TEST	30
5.1 APPLIED PROCEDURES / LIMIT	30



Table of Contents

	Page
5.1.1 TEST PROCEDURE	30
5.1.2 DEVIATION FROM STANDARD	30
5.1.3 TEST SETUP	30
5.1.4 EUT OPERATION CONDITIONS	30
5.1.5 TEST RESULTS	31
6 . ANTENNA REQUIREMENT	33
6.1 STANDARD REQUIREMENT	33
6.2 EUT ANTENNA	33
7 . EUT TEST PHOTO	34
8 . PHOTO OF THE EUT	36



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.249 (a)(2)	20dB Bandwidth	PASS	
15.249	Fundamental &Radiated Spurious Emission Measurement	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



1.1 TEST FACILITY

Shenzhen BCTC Technology Co., Ltd.

Add. : No.101,Yousong Road,Longhua New District, Shenzhen,China

FCC Registered No.: 187086

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Silent Symphony Headphone / Transmitter	
Trade Name	N/A	
Model Name	TX-3CH	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a Silent Symphony Headphone / Transmitter	
	Operation Frequency:	908.7-926.3MHz
	Modulation Type:	FM
	Number Of Channel	3CH
	Antenna Designation:	Please see Note 3.
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Power	DC 9V from adapter input AC 120V/60Hz	
Battery	DC3.7V	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	908.7	01	917	02	926.3

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	R - SMA Antenna	N/A	5	



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode
Mode 2	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 2	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode


Note:

(1) The measurements are performed at the highest, middle, lowest available channels.



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Silent Symphony Headphone / Transmitter	N/A	TX-3CH	N/A	EUT
E-2	Adapter	N/A	YHSW-090100U	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	1.8M	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	1166.5950K03-101165-ha	2015.06.05	2016.06.05	1 year
2	LISN	R&S	NSLK8126	8126466	2015.08.24	2016.08.23	1 year
3	LISN	R&S	NSLK8126	8126487	2015.08.24	2016.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.05	2016.06.05	1 year
5	RF cables	R&S	R204	R20X	2015.06.05	2016.06.05	1 year

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45109572	2015.08.25	2016.08.24	1 year
2	Test Receiver	R&S	ESPI	101396	2015.08.25	2016.08.24	1 year
3	Bilog Antenna	SCHWARZBECK	VULB9160	VULB9160-3369	2015.08.25	2016.08.24	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.07	2016.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.07	2016.06.06	1 year
6	Horn Antenna	SCHWARZBECK	9120D	9120D-1275	2015.08.25	2016.08.24	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	SCHWARZBECK	BBV9718	9718-270	2015.08.25	2016.08.24	1 year
9	Amplifier	SCHWARZBECK	BBV9743	9743-119	2015.08.25	2016.08.24	1 year
10	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
11	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
12	Power Sensor	R&S	URV5-Z4	0395.1619.05	2015.07.06	2016.07.05	1 year
13	RF cables	R&S	N/A	N/A	2015.07.06	2016.07.05	1 year



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.



3.1.6 TEST RESULTS


EUT :	Silent Symphony Headphone / Transmitter	Model Name. :	TX-3CH
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	AC120V/60Hz	Test Mode :	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.3180	32.91	10.10	43.01	59.76	-16.75	QP	
2		0.3180	21.50	10.10	31.60	49.76	-18.16	AVG	
3		0.6300	26.40	10.13	36.53	56.00	-19.47	QP	
4		0.6300	16.29	10.13	26.42	46.00	-19.58	AVG	
5		1.1539	25.63	10.17	35.80	56.00	-20.20	QP	
6		1.1539	15.36	10.17	25.53	46.00	-20.47	AVG	
7		1.6060	24.78	10.18	34.96	56.00	-21.04	QP	
8		1.6060	14.13	10.18	24.31	46.00	-21.69	AVG	
9		2.1340	24.20	10.18	34.38	56.00	-21.62	QP	
10		2.1340	14.14	10.18	24.32	46.00	-21.68	AVG	
11		3.4700	23.91	10.18	34.09	56.00	-21.91	QP	
12		3.4700	14.03	10.18	24.21	46.00	-21.79	AVG	



EUT :	Silent Symphony Headphone / Transmitter	Model Name. :	TX-3CH
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	AC120V/60Hz	Test Mode :	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.3100	34.81	10.09	44.90	59.97	-15.07	QP	
2	*	0.3100	25.39	10.09	35.48	49.97	-14.49	AVG	
3		0.5540	26.26	10.12	36.38	56.00	-19.62	QP	
4		0.5540	16.12	10.12	26.24	46.00	-19.76	AVG	
5		0.9900	26.24	10.16	36.40	56.00	-19.60	QP	
6		0.9900	15.57	10.16	25.73	46.00	-20.27	AVG	
7		1.3460	25.85	10.17	36.02	56.00	-19.98	QP	
8		1.3460	15.41	10.17	25.58	46.00	-20.42	AVG	
9		1.7580	24.51	10.18	34.69	56.00	-21.31	QP	
10		1.7580	13.97	10.18	24.15	46.00	-21.85	AVG	
11		2.4380	24.70	10.18	34.88	56.00	-21.12	QP	
12		2.4380	14.12	10.18	24.30	46.00	-21.70	AVG	



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

EUT:	Silent Symphony Headphone / Transmitter	Model Name. :	TX-3CH
Temperature:	20°C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

**3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)**

EUT :	Silent Symphony Headphone / Transmitter	Model Name :	TX-3CH
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC120V/60Hz		
Test Mode :	TX 00		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
34.1561	27.45	-8.45	19.00	40.00	-21.00	QP
51.1209	34.38	-10.48	23.90	40.00	-16.10	QP
82.3588	38.00	-18.12	19.88	40.00	-20.12	QP
138.3873	46.73	-13.50	33.23	43.50	-10.27	QP
284.7457	49.07	-13.72	35.35	46.00	-10.65	QP
377.0935	45.95	-13.22	32.73	46.00	-13.27	QP
908.7	104.45	-3.16	101.29	114	-12.71	PK
908.7	92.71	-3.16	89.55	94	-4.45	AV

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All interfaces was connected, and TX mode was link.



EUT :	Silent Symphony Headphone / Transmitter	Model Name :	TX-3CH
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	AC120V/60Hz		
Test Mode :	TX 00		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
31.9546	43.04	-8.29	34.75	40.00	-5.25	
51.6616	41.59	-10.57	31.02	40.00	-8.98	QP
80.9275	50.03	-18.10	31.93	40.00	-8.07	QP
141.3298	44.14	-13.32	30.82	43.50	-12.68	QP
226.0680	41.38	-13.23	28.15	43.50	-15.35	QP
458.3264	44.16	-13.98	30.18	46.00	-15.82	QP
908.7	103.55	-3.16	100.39	114	-13.61	PK
908.7	91.85	-3.16	88.69	94	-5.31	AV

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All interfaces was connected, and TX mode was link.



EUT :	Silent Symphony Headphone / Transmitter	Model Name :	TX-3CH
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC120V/60Hz		
Test Mode :	TX 01		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
43.2017	30.95	-9.25	21.70	40.00	-18.30	
76.2442	43.02	-16.76	26.26	40.00	-13.74	QP
92.7871	45.72	-17.23	28.49	43.50	-15.01	QP
125.4457	46.83	-14.39	32.44	43.50	-11.06	QP
199.2855	51.08	-16.16	34.92	43.50	-8.58	QP
416.1791	34.80	-9.83	24.97	46.00	-21.03	QP
917	103.36	-3.18	100.18	114	-13.82	PK
917	92.21	-3.18	89.03	94	-4.97	AV

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All interfaces was connected, and TX mode was link.



EUT :	Silent Symphony Headphone / Transmitter	Model Name :	TX-3CH
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	AC120V/60Hz		
Test Mode :	TX 01		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
53.8817	30.40	-10.93	19.47	40.00	-20.53	
71.8319	32.59	-15.19	17.40	40.00	-22.60	QP
129.9225	36.70	-14.11	22.59	43.50	-20.91	QP
194.4533	46.78	-15.86	30.92	43.50	-12.58	QP
325.5957	50.23	-11.92	38.31	46.00	-7.69	QP
625.0779	33.16	-5.52	27.64	46.00	-18.36	QP
917	103.55	-3.23	100.32	114	-13.68	PK
917	91.85	-3.23	88.62	94	-5.38	AV

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All interfaces was connected, and TX mode was link.



EUT :	Silent Symphony Headphone / Transmitter	Model Name :	TX-3CH
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC120V/60Hz		
Test Mode :	TX 02		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
35.1561	27.56	-8.45	19.11	40	-20.89	QP
50.1209	35.21	-10.48	24.73	40	-15.27	QP
82.3588	38.83	-18.12	20.71	40	-19.29	QP
139.3854	46.76	-13.5	33.26	43.5	-10.24	QP
264.9455	49.65	-13.72	35.93	46	-10.07	QP
278.0935	46.43	-13.22	33.21	46	-12.79	QP
926.3	104.06	-3.23	100.83	114	-13.17	PK
926.3	92.79	-3.23	89.56	94	-4.44	AV

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All interfaces was connected, and TX mode was link.



EUT :	Silent Symphony Headphone / Transmitter	Model Name :	TX-3CH
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	AC120V/60Hz		
Test Mode :	TX 02		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
32.2543	43.04	-8.29	34.75	40	-5.25	
50.5678	41.59	-10.57	31.02	40	-8.98	QP
81.7272	50.03	-18.1	31.93	40	-8.07	QP
142.5641	44.14	-13.32	30.82	43.5	-12.68	QP
165.1682	41.38	-13.23	28.15	43.5	-15.35	QP
259.6544	44.16	-13.98	30.18	46	-15.82	QP
926.3	104.25	-3.23	101.02	114	-12.98	PK
926.3	93.85	-3.23	90.62	94	-3.38	AV

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All interfaces was connected, and TX mode was link.

**3.2.8 TEST RESULTS (ABOVE 1000 MHZ)**

Normal Voltage

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
908.7MHz							
V	1817.4	65.35	-3.57	61.78	74	-12.22	Pk
V	1817.4	52.89	-3.57	49.32	54	-4.68	AV
V	2726.1	64.61	-3.84	60.77	74	-13.23	Pk
V	2726.1	53.02	-3.84	49.18	54	-4.82	AV
V	3634.8	64.45	-4.59	59.86	74	-14.14	Pk
V	3634.8	53.34	-4.59	48.75	54	-5.25	AV
H	1817.4	65.21	-3.62	61.59	74	-12.41	Pk
H	1817.4	52.75	-3.62	49.13	54	-4.87	AV
H	2726.1	64.34	-3.93	60.41	74	-13.59	Pk
H	2726.1	53.82	-3.93	49.89	54	-4.11	AV
H	3634.8	65.02	-3.57	61.45	74	-12.55	Pk
H	3634.8	53.09	-3.57	49.52	54	-4.48	AV

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Limit- Absolute Level

Normal Voltage

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
917MHz							
V	1834	63.63	-3.57	60.06	74	-13.94	Pk
V	1834	52.76	-3.57	49.19	54	-4.81	AV
V	2751	64.02	-3.84	60.18	74	-13.82	Pk
V	2751	53.14	-3.84	49.3	54	-4.7	AV
V	3668	63.25	-4.59	58.66	74	-15.34	Pk
V	3668	53.87	-4.59	49.28	54	-4.72	AV
H	1834	64.21	-3.62	60.59	74	-13.41	Pk
H	1834	53.89	-3.62	50.27	54	-3.73	AV
H	2751	63.78	-3.93	59.85	74	-14.15	Pk
H	2751	53.96	-3.93	50.03	54	-3.97	AV
H	3668	63.27	-3.57	59.7	74	-14.3	Pk
H	3668	53.72	-3.57	50.15	54	-3.85	AV

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Limit- Absolute Level



Normal Voltage

Normal Voltage							
Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
926.3MHz							
V	1847.2	64.92	-3.57	61.35	74	-12.65	Pk
V	1847.2	53.19	-3.57	49.62	54	-4.38	AV
V	2770.8	64.35	-3.84	60.51	74	-13.49	Pk
V	2770.8	53.61	-3.84	49.77	54	-4.23	AV
V	3694.4	64.45	-4.59	59.86	74	-14.14	Pk
V	3694.4	54.05	-4.59	49.46	54	-4.54	AV
H	1847.2	65.21	-3.62	61.59	74	-12.41	Pk
H	1847.2	53.23	-3.62	49.61	54	-4.39	AV
H	2770.8	64.34	-3.93	60.41	74	-13.59	Pk
H	2770.8	53.82	-3.93	49.89	54	-4.11	AV
H	3694.4	65.37	-3.57	61.8	74	-12.2	Pk
H	3694.4	54.02	-3.57	50.45	54	-3.55	AV
Remark:							
Absolute Level= ReadingLevel+ Factor, Margin= Limit- Absolute Level							



4. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 1.5 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported



4.1 DEVIATION FROM STANDARD

No deviation.

4.2 TEST SETUP

4.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.4 TEST RESULTS

EUT :	Balight	Model Name :	LK152001-RD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX Mode		

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)	Limit (dBuV/m)	Result
				Pass
902	H	40.32	46.00	Pass
902	V	40.25	46.00	Pass
928	H	40.43	46.00	Pass
928	V	40.14	46.00	Pass

If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.



5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.249	Bandwidth	902~928	PASS

5.1.1 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) \geq 300 kHz.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.





5.1.5 TEST RESULTS

EUT :	Silent Symphony Headphone / Transmitter	Model Name :	TX-3CH
Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX Mode		

Channel	Frequency (MHz)	20dB bandwidth (MHz)
00	908.7	0.368
01	917	0.365
02	926.3	0.368







6. ANTENNA REQUIREMENT

6.1 STANDARD REQUIREMENT



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2 EUT ANTENNA

The EUT antenna is R - SMA antenna. It comply with the standard requirement.

7. EUT TEST PHOTO

R E



C E



8. PHOTO OF THE EUT

