

Page: 1 of 25

# **FCC Test Report**

**Application No.**: HKES141200244801 **Applicant**: S.E.M. INDUSTRIES

Address: 35/F., Tower A, Billion Centre

No.1 Wang Kwong Road, Kowloon Bay, Kowloon

Hong Kong

**Product Information:** 

Product Description: Portable Stereo Speaker

Model: GB-3600-BTHFM3UC, GB-3600-BTLFM3UC, GB-3600-BT, GB-3600-BT,

3600, GB3600, GB-3601-BTHFM3UC, GB-3601-BTLFM3UC, GB-3601-BTF, GB-

3601-BT, GB-3601, GB3601 &

Please refer to section 2 of this report which indicates which item was actually

tested and which were electrically identical.

Brand Name: S.E.M/ S-LOGO/ NIL/ S-DIGITAL/ SDIGITAL/ S.E.M. AUDIO LABORATORIES

Product Class: Low Power Communication Device – Transmitter (2.4 GHz)

FCC ID: 2AANA-SEM-GB3600

Requirement: CFR 47 FCC PART 15 SUBPART C, 2014

- Intentional Radiators (Section 15.249)

**Date of Receipt**: 2014-12-12

**Date of Test**: 2014-12-24 to 2015-01-02

**Date of Issue**: 2015-01-09

Test Result : PASS\*

In the configuration tested, the EUT complied with the requirements for the relevant clauses of Federal Communications Commission Rules as specified above.

Authorized Signature:

CHEN Jian-feng, Jeffrey

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS IECC Limited or testing done by SGS IECC Limited in connection with, distribution or use of the product described in this report must be approved by SGS IECC Limited in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

FCC ID: 2AANA-SEM-GB3600



Page: 2 of 25

# 2 Test Summary

Test	Test Requirement Test Method		Result
Conducted Emission (150KHz to 30MHz)	FCC PART 15, SUBPART C: 2014	ANSI C63.4:2003	PASS
Radiated Emission (9kMHz to 1GHz)	FCC PART 15, SUBPART C: 2014	ANSI C63.4:2003	PASS
Radiated Emission above 1 GHz	FCC PART 15, SUBPART C: 2014	ANSI C63.4:2003	PASS
Band edge / 20 dB Bandwidth	FCC PART 15, SUBPART C: 2014	ANSI C63.4:2003 Marker-Detla measurement	PASS

**\* Item no.:** GB-3600-BTHFM3UC, GB-3600-BTLFM3UC, GB-3600-BTF, GB-3600-BT, GB-3600, GB-3601-BTHFM3UC, GB-3601-BTLFM3UC, GB-3601-BTF, GB-3601-BT, GB-3601, GB3601

According to the confirmation from the applicant, the above models are identical in all electrical aspects in relating to the circuit design, PCB layout and construction. The differences are the model no. trade name, color, cosmetic outlook and silkscreen.

Therefore only the item GB-3600-BTHFM3UC was tested in this report.



Page: 3 of 25

# 3 Contents

		Page
1	COVER PAGE	1
2	2 TEST SUMMARY	2
3	CONTENTS	3
4	GENERAL INFORMATION	4
	4.1 GENERAL DESCRIPTION OF EUT	4
	4.2 DETAILS OF EUT	4
	4.3 CONDITIONS OF EUT	
	4.4 DESCRIPTION OF SUPPORT UNITS	
	4.5STANDARDS APPLICABLE FOR TESTING	
	4.6 TEST LOCATION	
	4.7 TEST FACILITY	
	4.8 DEVIATION FROM STANDARDS	
	4.10 DECLARATION OF FAMILY GROUPING	
	4.11 ABBREVIATIONS	
_		
5	EQUIPMENTS USED DURING TEST	6
6	5 TEST RESULTS	3
Ŭ		
	CONDUCTED EMISSIONS MAINS TERMINALS, 150KHZ TO 30MHZ	
	6.1.1 EUT Operation	
	6.1.3 Measurement Data	
	6.2 RADIATED EMISSIONS, 9KHZ TO1GHZ	
	6.2.1 EUT Operation	
	6.2.2 Test Setup and Procedure	
	6.2.3 Measurement Data	
	6.3 RADIATED EMISSIONS ABOVE 1 GHz	
	6.3.1 EUT Operation	
	6.3.2 Test Setup and Procedure	
	6.3.3 Measurement Data	
	6.4 BAND EDGE / 20 DB BANDWIDTH	
7	PHOTOGRAPHS	22
	7.1 CONDUCT EMISSION TEST SETUP	22
	7.2 RADIATD EMISSION TEST SETUP	
	FUT CONSTRUCTIONAL DETAILS	23



Page: 4 of 25

## 4 General Information

## 4.1 General Description of EUT

Product Description: Portable Stereo Speaker Model No: GB-3600-BTHFM3UC

Serial No.: --

## 4.2 Details of EUT

Power Supply: AC 120V 60Hz to DC 5V

Adaptor: AS050-050-UA100

DC 3.7V (Rechargeable battery x1)

Operating Frequency 2402-2480MHz
Antenna Type: Integral antenna
Bluetooth version V2.1+EDR

Modulation Type: GFSK, Π/4-DQPSK and 8DPSK

Modulation	Packet	Packet Type	Packet Size
	DH1	4	24
GFSK	DH3	11	183
	DH5	15	339
	2DH1	20	54
(π/4)DQPSK	2DH3	26	367
	2DH5	30	379
	3DH1	24	83
8DPSK	3DH3	27	552
	3DH5	31	1021

## 4.3 Conditions of EUT

FCC ID: 2AANA-SEM-GB3600

The received sample was under good condition.

## 4.4 Description of Support Units

Description	Manufacturer Model No. Serial No.				
Notebook	HP	HP OmniBook 6000 series (			
BT test board	Supported by cilent				
Test software	BK3256 RF Test_V1.3				
Cable	Aux in cable (3.5mm jack) with 22k Ohms Terminator				
Cable	Headphone cable (3.5mm jack) with 32 Ohms Terminator				

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.ses.com/terms">www.ses.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.ses.com/terms">www.ses.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction form cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

 $Unless otherwise stated the results shown in this test report refer only to the sample(s) \ tested \ and \ such \ sample(s) \ are \ retained \ for \ 90 \ days \ only.$ 



Page: 5 of 25

Cable USB cable with 10 Ohms Terminator

All field strength measures in this test report were done by the aid of test software which places the device in continuous transmission under different package type and the test software above allowed to set the frequency fixed and hopping stopped.

## 4.5Standards Applicable for Testing

CFR 47, FCC Part 15, 2014 ANSI C63.4:2003

#### 4.6 Test Location

All tests were performed at:

SGS IECC Limited (Member of the SGS Group (SGS SA))

Units 303-305, 3/F., 31 Lok Yip Road, On Lok Tsuen, Fanling, N.T., Hong Kong

Tel: +852 2305 2570 Fax: +852 2756 4480

## 4.7 Test Facility

Measurement facility located at Fanling (Hong Kong), placed on file with the FCC Pursuant to Section 2.948 of the FCC Rules (FCC Registration No.: 97774).

The test facility is recognized, certified, or accredited by the following organizations:

FCC - CAB Registration No.: 446297

Measurement facility located at Fanling (Hong Kong), accredited as a Conformity Assessment Body (CAB) and was designated by FCC to perform compliance testing on equipment subject to Declaration Of Conformity (DOC) and Certification under Part 15 and 18 of the Commission's Rules.

## 4.8 Deviation from Standards

None.

#### 4.9 Abnormalities from Standard Conditions

None.

## 4.10 Declaration of Family Grouping

None.

## 4.11 Abbreviations

N/A: Not Applicable

**EUT: Equipment Under Test** 

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms and conditions.htm">www.sgs.com/terms and conditions.htm</a> and, for electronic Documents at <a href="https://www.sgs.com/terms e-document.htm">www.sgs.com/terms e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's soole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

FCC ID: 2AANA-SEM-GB3600



Page: 6 of 25

# 5 Equipments Used during Test

Conducted Emission				
Equipment	Manufacturer	Model / Serial No.	Cal. Date	Cal. Due Date
Test Receiver	Rohde & Schwarz	ESHS 30 / 839667/002	2014/10/17	2015/10/16
Artificial Mains Network (LISN)	Schwarzbeck	NSLK 8127 / 8127312	2014/4/8	2015/4/7
Impulse Limiter	Rohde & Schwarz	ESH-3-Z2 / 375881052	2013/1/21	2015/1/20

Radiated Emission				
Equipment	Manufacturer	Model / Serial No.	Cal. Date	Cal. Due Date
3m Semi-Anechoic Chamber (pre-test)				
3m / 10m Open Aera Test Site			2012-3-17	2015-3-16
Test Receiver	Rohde & Schwarz	ESCS 30 / 100388	2014/10/17	2015/10/16
Spectrum Analyzer	Rohde & Schwarz	FSP 30 / 101474	2014/6/16	2015/6/15
Loop antenna	Rohde & Schwarz	HFH2-Z2 / 871336/48	2012/12/27	2015/12/26
Antenna 30-1000MHz	Schaffner	CBL6111C / 2791	2014/10/19	2016/10/18
Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D / 9120D-1070	2014/1/13	2016/1/12
Horn Antenna 15-26.5GHz	Schwarzbeck	BBHA9170 / 9170-492	2014/11/24	2016/11/23
Preamplifier 10MHz – 6GHz	Schwarzbeck	BBV9743 / 9743-052	2014/1/13	2016/1/12
Preamplifier 1-18GHz	Schwarzbeck	BBV9718 / 9718-223	2014/1/13	2016/1/12
Preamplifier 18- 26.5GHz	Schwarzbeck	BBV9719 / 9719-019	2014/11/19	2016/11/18
Coaxial Cable		E167	2014/06/25	2015/06/24
RF Cable	HUBER+SUHNER	E207	2014/11/17	2016/11/16
Antenna Mast System	Schwarzbeck	AM9104 / -		

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 7 of 25

Turntable with Controller	Drehtisch	DT312/-		
---------------------------	-----------	---------	--	--

General Use Equipment					
Equipment	Manufacturer	Model / Serial No.	Cal. Date	Cal. Due Date	
Digital Multimeter	Fluke	189 / 83640020	2014/4/8	2015/4/7	
Temperature / Humidity meter	-	E158	2014-11-14	2015/11/13	



Page: 8 of 25

## 6 Test Results

## Conducted Emissions Mains Terminals, 150kHz to 30MHz

Test Requirement: FCC Part15 C
Test Method: ANSI C63.4
Test Date: 2014-12-24

Frequency Range: 150kHz to 30MHz

Class / Severity: Class B

Detector: Peak for pre-scan (9kHz Resolution Bandwidth)

Quasi-Peak if maximised peak within 6dB of Quasi-Peak limit

#### Limit:

Frequency range MHz	Class B Limits dB (μV)			
	Quasi-peak	Average		
0.15 to 0.50	66 to 56	56 to 46		
0.50 to 5	56	46		
5 to 30	60	50		

#### Note:

- 1) The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.
- 2) The lower limit is applicable at the transition frequency.

## 6.1.1 EUT Operation

Operating Environment:

Temperature: 21°C Humidity: 42% RH

EUT Operation: Pre-test with adaptor or battery operate and Peak detector with the following

mode(s):

1: Transmission with GFSK (packet DH1/DH3/DH5)

2: Transmimssion with Π/4-DQPSK (packet 2DH1/2DH3/2DH5)

3: Transmission with 8DPSK (packet 3DH1/3DH3/3DH5)


Final test with adaptor and Quasi-Peak detector with the following mode(s):

1: Transmission with GFSK (packet DH5)



Page: 9 of 25

### 6.1.2 Test Setup and Procedure



- 1. The mains terminal conducted emission test was conducted in a shielded room.
- 2. The EUT was connected to AC power source through a LISN (Line Impedance Stabilization Network) which provides a  $50\Omega/50\mu H + 5\Omega$  linear impedance. For Load terminal voltage measurement, a voltage probe was used on the load terminals. Measurement at control terminals were carried out by means of an impedance stabilization network (ISN). The ISN was bounded to ground.
- 3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
- 4. The EUT kept a distance of at least 0.8m from any other earthed conducting surface. The Artificial Mains Network was situated at a distance of 0.8m from the EUT. The mains lead of EUT excess 0.8m was folded back and forth parallel to the lead so as to form a horizontal bundle with a length between 0.3m and 0.4m.




Page: 10 of 25

#### 6.1.3 Measurement Data

Live Line:

#### BT mode

Quasi-peak/ Average measurement:



Freq	Read Level		LISN Factor		Limit Line	Over Limit	Remark
MHz	dBu∀	<u>dB</u>	dB	dBu∇	dBuV	$\phantom{aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa$	
0.3560 0.3560 1.0710 1.0710 1.7905 1.7905 2.5101 2.5101 10.7038 10.7038 26.1826 26.1826	52.66 45.64 51.74 42.18 53.12 44.79 52.74 44.33 48.46 32.71 33.97 54.34	0.30 0.30 0.01 0.01 0.08 0.08 0.10 0.12 0.12 0.20 0.20	0.23 0.23 0.26 0.26 0.30 0.30 0.54	53.07 46.05 51.98 42.42 53.46 45.13 53.14 44.73 49.11 33.36 34.99 55.36	56.00 46.00 60.00	-4.02 -3.58 -2.54 -0.87 -2.86 -1.27 -10.89 -16.64	AVERAGE QP AVERAGE QP AVERAGE QP AVERAGE QP AVERAGE QP AVERAGE AVERAGE


Level = Read Level + LISN Factor + Cable Loss.



Page: 11 of 25

#### **Neutral Line:**

#### Quasi-peak/ Average measurement:



Freq	Read Level		LISN Factor	Level	Limit Line	Over Limit	Remark
MHz	dBuV	āB	dB	dBuV	dBuV	$-\overline{dB}$	
0.3555 0.3615 1.0679 1.0731 3.2049 3.2205 10.7070 10.7070 16.4928 16.4996 27.6056 27.6056	43.37 47.68 51.10 45.34 48.00 44.54 31.78 29.56 34.87 39.96 52.14 32.97	0.30 0.30 0.01 0.01 0.10 0.12 0.12 0.20 0.20 0.2	0.19 0.19 0.27 0.27 0.38 0.38 0.59 0.59 0.76 0.76 0.87	43.86 48.17 51.38 45.62 48.48 45.02 32.48 30.26 35.83 40.92 53.21 34.04	46.00 56.00 46.00 50.00 60.00 60.00 60.00	-10.52 -4.62 -0.38 -7.52 -0.98 -17.52 -29.74 -14.17 -19.08 -6.79	QP AVERAGE QP AVERAGE AVERAGE QP AVERAGE QP

Level = Read Level + LISN Factor + Cable Loss.

Remark: Aux in, headphone and usb port are terminated by resistor during test.



Page: 12 of 25

## 6.2 Radiated Emissions, 9kHz to1GHz

Test Requirement: FCC Part15 Subpart C Section 15.209 and 15.249(d)

Test Method: ANSI C63.4:2003

Test Date: 2015-01-02

Frequency Range: The lowest frequency generated by EUT, 12MHz to 1GHz

Measurement Distance: 3m

Detector: Peak for pre-scan

(200Hz resolution bandwidth and 1kHz video bandwidth for measurement

between 9kHz - 150kHz)

(9kHz resolution bandwidth and 100kHz video bandwidth for

measurement between 150kHz - 30MHz)

120kHz resolution bandwidth and 1MHz video bandwidth for

measurement between 30MHz to 1GHz)

Quasi-Peak if maximised peak within 6dB of limit

#### Limit:

Frequency range MHz	Quasi-peak limits dB (μV/m)
0.009 - 0.490	-72.4 – 20logF(MHz)
0.490 - 1.705	-12.4 – 20logF(MHz)
1.705 – 30.0	-10.5
30 to 88	40
88 to 216	43.5
216 to 960	46
Above 960	54

Note: 1) At transitional frequencies the lower limit applies.

2) F is the frequency of the spurious emission measured in MHz.

3) Limit from 0.009 – 30 MHz is converted from measuring distance 300m or 30m to 3m with the formulat provided in FCC Part 15, section 15.31(f)(2)

#### 6.2.1 EUT Operation

Operating Environment:

Temperature: 23 °C Humidity: 45%

EUT Operation: Pre-test with adaptor or battery operate and Peak detector with the following

mode(s):

1: Transmission with GFSK (packet DH1/DH3/DH5)

2: Transmimssion with Π/4-DQPSK (packet 2DH1/2DH3/2DH5)

3: Transmission with 8DPSK (packet 3DH1/3DH3/3DH5)


Final test with adaptor and Quasi-Peak detector with the following mode(s):

1: Transmission with GFSK (packet DH5)



Page: 13 of 25

#### 6.2.2 Test Setup and Procedure



- 1. The pre-test of the radiated emissions test was conducted in a semi-anechoic chamber and the final measurement was conducted in the open area test site.
- 2. The EUT was connected to AC power source through a mains power outlet which was bonded to the ground reference plane. The EUT was placed upon a non-metallic table 0.8m above the ground reference plane.
- 3. Loop antennat and Bilog antenna was used for the frequency range from the lowest generated frequency to 30MHz and 30MHz to 1GHz respectively
- 4. Before final measurements of radiated emissions, a pre-scan was performed in the spectrum mode with the peak detector to find out the maximum emissions spectrum plots of the EUT with located frequencies.
- 5. The actual frequencies of maximum emission were confirmed in the final radiated emissions measurement. At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters for Bilog antenna (Loop antenna is still maintain in 1m hight) in order to determine the maximum disturbance. Measurements were performed for both horizontal and vertical antenna polarization.



Page: 14 of 25

#### 6.2.3 Measurement Data

An initial pre-scan was performed in the 3m chamber using the spectrum analyser in peak detection mode. The EUT was measured by Bilog antenna with 2 orthogonal polarities and frequencies of peak emissions from the EUT were detected within 6dB of the limit line. Final measurement was conducted in the open area test site with data as follows:

#### Test results:

## (1) Operation Frequency: 2402MHz

Frequency	Antenna	Correction	Receiver	Emission	Limit	Over Limit
(MHz)	Polarization	Factor (dB/m)	QP Reading (dBμV)	Level (dBµV/m)	(dBµV/m)	(dB)
30.000	V	19.1	10.2	29.3	40.0	-10.7
42.571	V	14.2	19.4	33.6	40.0	-6.4
61.125	V	9.6	12.4	22.0	40.0	-18.0
120.000	V	11.3	18.4	29.7	43.5	-13.8
149.875	Н	11.2	14.8	26.0	43.5	-17.5
477.688	V	18.2	5.4	23.6	46.0	-22.4

#### Test results:

#### (2) Operation Frequency: 2441MHz

Frequency (MHz)	Antenna Polarization	Correction Factor (dB/m)	Receiver QP Reading (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Over Limit (dB)
30.750	V	18.8	12.0	30.8	40.0	-9.2
44.000	V	13.7	20.6	34.3	40.0	-5.7
61.875	V	9.6	11.1	20.7	40.0	-19.3
120.063	V	11.3	18.7	30.0	43.5	-13.5
148.813	Н	11.2	13.8	25.0	43.5	-18.5
568.313	V	19.5	4.9	24.4	46.0	-21.6



Page: 15 of 25

#### Test results:

#### (3) Operation Frequency: 2480MHz

Frequency (MHz)	Antenna Polarization	Correction Factor (dB/m)	Receiver QP Reading (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/ m)	Over Limit (dB)
30.000	V	19.1	5.3	24.4	40.0	-15.6
46.250	V	13.0	19.5	32.5	40.0	-7.5
85.188	Н	9.2	7.3	16.5	40.0	-23.5
120.125	V	11.3	15.9	27.2	43.5	-16.3
149.500	Н	11.2	13.9	25.1	43.5	-18.4
551.875	V	19.4	4.1	23.5	46.0	-22.5

#### Note:

- 1) All readings are Quasi-Peak values.
- 2) Correction Factor = Antenna Factor + Cable Loss.
- 3) The above results were the worst case results with the EUT positioned in all 3 axis during the test. The EUT was positioned vertically and horizontally on the table for vertical and horizontal measurement respectively.
- 4) Other emissions more than 20dB below the limit are not shown on the above table and only worst six emissions below 1GHz are listed.
- 5) Aux in, headphone and USB port are terminated by resistor during test.



Page: 16 of 25

#### 6.3 Radiated Emissions above 1 GHz

Test Requirement: FCC Part15 Subpart C Section 15.209 & 15.249(a) & (d)

Test Method: ANSI C63.4:2003

Test Date: 2014-12-24 Frequency Range: 1GHz – 26GHz

Measurement Distance: 3m

Detector: Peak for pre-scan (≥ 1MHz resolution bandwidth, ≥ 1MHz video

bandwidth)

Average and Peak detector for final test

Limit:

Fundamental Frequency:

Frequency range MHz	Limits (Peak) dB (μV/m)	Limits (Average) dB (μV/m)
2400 to 2483.5	114	94

## Spurious Emission:

Frequency range	Limits (Peak)	Limits (Average)
MHz	dB (μV/m)	dB (μV/m)
Over 1000	74	54

## 6.3.1 EUT Operation

Operating Environment:

Temperature: 22 °C Humidity: 42 %

EUT Operation: Pre-test with adaptor or battery operate and Peak detector with the following

mode(s):

1: Transmission with GFSK (packet DH1/DH3/DH5)

2: Transmimssion with Π/4-DQPSK (packet 2DH1/2DH3/2DH5)

3: Transmission with 8DPSK (packet 3DH1/3DH3/3DH5)


Final test with adaptor and Peak and Avearge detector with the following mode(s):

1: Transmission with GFSK (packet DH5)



Page: 17 of 25

#### 6.3.2 Test Setup and Procedure



- 1. The pre-test of the radiated emissions test was conducted in a semi-anechoic chamber and the final measurement was conducted in the open area test site.
- The EUT was connected to AC power source through a mains power outlet which was bonded to the ground reference plane. The EUT was placed upon a non-metallic table 0.8m above the ground reference plane.
- 3. Horn antenna was used for the frequency over 1GHz
- 4. Before final measurements of radiated emissions, a pre-scan was performed in the spectrum mode with the peak detector to find out the maximum emissions spectrum plots of the EUT with located frequencies.
- 5. The actual frequencies of maximum emission were confirmed in the final radiated emissions measurement. At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum disturbance. Measurements were performed for both horizontal and vertical antenna polarization.



Page: 18 of 25

#### 6.3.3 Measurement Data

An initial pre-scan was performed in the 3m chamber using the spectrum analyser in peak detection mode. The EUT was measured with 2 orthogonal polarities and frequencies of average emissions from the EUT were measured as follows:

## Test results:

## (1) Fundmental Frequency

Frequency	Antenna	Emission Lev	vel (dBμV/m)	Limit (d	BμV/m)	Domostic
(MHz)	Polarization	Peak	Average	Peak	Average	Remark
2402.0	Н	93.94	91.54	114	94	Pass
2402.0	V	93.19	92.28	114	94	Pass
2441.0	Н	91.46	89.51	114	94	Pass
2441.0	V	92.85	91.75	114	94	Pass
2480.0	Н	91.05	90.70	114	94	Pass
2480.0	V	94.19	89.37	114	94	Pass

## (2) Spurious Emission

Operation Frequency: 2402.0 MHz

Frequency	Antenna	Emission Le	vel (dBμV/m)	Limit (d	BμV/m)	Remark
(MHz)	Polarization	Peak	Average	Peak	Average	nemark
4804	V	50.71	41.00	74	54	Pass
4877	V	52.43	38.04	74	54	Pass
7206	V	53.51	39.64	74	54	Pass
8687	Н	58.38	44.63	74	54	Pass
9608	V	55.93	42.46	74	54	Pass
10878	Н	62.53	48.94	74	54	Pass



Page: 19 of 25

### Operation Frequency: 2441.0 MHz

Frequency	Antenna	Emission Level (dBµV/m)		Limit (dBµV/m)		Remark
(MHz)	Polarization	Peak	Average	Peak	Average	nemark
4882	Н	60.42	52.78	74	54	Pass
7323	V	65.88	50.44	74	54	Pass
8907	Н	58.63	45.09	74	54	Pass
9763	V	57.26	46.05	74	54	Pass
11082	Н	62.14	48.31	74	54	Pass
12205	Н	57.56	44.33	74	54	Pass

## Operation Frequency: 2480.0 MHz

Frequency	Antenna	Emission Lev	vel (dBμV/m)	Limit (d	BμV/m)	Damadi	
(MHz)	Polarization	Peak	Average	Peak	Average	Remark	
4923.6	Н	54.52	46.00	74	54	Pass	
4960.2	Н	56.35	47.36	74	54	Pass	
7439.3	V	63.97	52.00	74	54	Pass	
9920.0	V	58.05	49.91	74	54	Pass	
10696	V	63.33	50.51	74	54	Pass	
12400	Н	58.26	46.77	74	54	Pass	

#### Note:

- 1) The above results were the worst case results with the EUT positioned in all 3 axis during the test. The EUT was positioned vertically and horizontally on the table for vertical and horizontal measurement respectively.
- 2) Other emissions more than 20dB below the limit are not shown on the above table and only worst six emissions below 1GHz are listed.
- 3) Aux, headphone and USB port are terminated by resistor during test.



Page: 20 of 25

## 6.4 Band Edge / 20 dB Bandwidth

Test Requirement: FCC Part15 Subpart C Section 15.215, 15.249(d)

Test Method: ANSI C63.4:2003 and Marker-Delta Method

Test Date: 2014-12-24


EUT Operation: 1: Transmission with GFSK

2: Transmission with Π/4-DQPSK;3: Transmission with 8DPSK;

Result: Pass

<u>Test Plot</u>: (Worst case: Transmission with 8DPSK)

Operation frequency: 2402.0 MHz



Date: 21.JAN.2015 10:30:33

According to the page 18 of this report, the emission of the fundamental frequency 2402MHz is 93.94dBuV/m for peak level respectively. Based on the delta method, the emission at the bandedge, 2400MHz, is more than 40dB below the fundamental and 20dB bandwidth falls in assigned band. It is deemed to comply with section 15.215. Besides, it is below the limit of 74dBuV/m and 54dBuV/m for peak and average level under 15.209. It is deemed to comply with section 15.249(d).

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


FCC ID: 2AANA-SEM-GB3600



Page: 21 of 25

Test Plot : (Worst case: Transmission with 8DPSK)

Operation frequency: 2480.0 MHz



Date: 22.JAN.2015 09:08:24

According to the page 18 of this report, the emission of the fundamental frequency 2480MHz is 94.19dBuV/m for peak level respectively. Based on the delta method, the emission at the bandedge, 2483.5MHz, is more than 40dB below the fundamental and 20dB bandwidth falls in the assigned band. It is deemed to comply with section 15.215. Besides, it is below the limit of 74dBuV/m and 54dBuV/m for peak and average level under 15.209. It is deemed to comply with section 15.249(d).



Page: 22 of 25

# 7 Photographs

# 7.1 Conduct Emission Test Setup



## 7.2 Radiatd Emission Test Setup





Page: 23 of 25

## **EUT Constructional Details**







Page: 24 of 25







Page: 25 of 25



-- END OF REPORT --