



Shenzhen CTL Electromagnetic Technology Co., Ltd.
Tel: +86-755-89486194 Fax: +86-755-89486194-805

FCC PART 22 AND PART 24 TEST REPORT

FCC Part 22 Subpart H / Part 24 Subpart E

Report Reference No.....: CTL1306281042-WU

Compiled by

(position+printed name+signature)...: File administrators Jacky Chen

Jacky Chen

Name of the organization performing the tests

Test Engineer Tracy Qi

Tracy Qi

(position+printed name+signature)...:

Approved by

(position+printed name+signature)...: Manager Tracy Qi

Tracy Qi

Date of issue.....: August 15, 2013

Representative Laboratory Name : Shenzhen CTL Electromagnetic Technology Co., Ltd.

Address.....: Zone B, 4/F, Block 20, Guangqian Industrial Park, Longzhu Road, Nanshan, Shenzhen 518055 China.

Test Firm.....: Bontek Compliance Testing Laboratory Ltd

Address.....: 1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China

Applicant's name.....: SHENZHEN GOLD EAST ELETRONIC CO., LTD

Address.....: 6F, Bldg #11, Yusheng Industry Area, #467 Gushu, Xixiang, Bao'an District, Shenzhen, China 518000

Test specification:

Standard: **FCC CFR Title 47 Part 2, Part 22H and Part 24E**

EIA/TIA 603-C: 2004

Master TRF.....: Dated 2011-01

Shenzhen CTL Electromagnetic Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Electromagnetic Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Electromagnetic Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description : Tablet PC

FCC ID.....: 2AANTL001-30

Trade Mark: /

Model/Type reference.....: L001-30, L002-6, L097-5, L010-13, L011-1, L001-30S, L002-6S, L002-9S, L097-5S, L010-13S, L011-1S, L013-3S, L001-40, L001-40S, L002-10, L002-10S, L097-6, L097-6S, L010-16, L010-16S, L011-2, L011-2S

GSM/WCDMA

Transmit: 2G:GSM 850: 824~849MHz, PCS 1900: 1850~1910MHz

3G:WCDMA Band II: 1850-1910MHz,

WCDMA Band V: 824~849MHz

Receive: 2G:GSM 850: 869~894MHz, PCS 1900: 1930~1990MHz
3G:WCDMA Band II: 1930~1990MHz,
WCDMA Band V: 869~894MHz

Release Version: 2G:R99
3G:UMTS FDD: Rel-5

Type of modulation: 2G: GMSK for GSM/GPRS/EDGE
3G: QPSK

GPRS Type: Class B

GPRS Class: Class 12

GPS

work frequency: 1575.42MHz

Type of modulation: BPSK

Bluetooth

Work frequency: 2402~2480MHz

Version.....: V3.0

Type of modulation: FHSS

Data Rate.....: 1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps(8DPSK)

Wi-Fi

Work frequency: 802.11b/g/n(20MHz): 2412~2462MHz

Type of modulation: 802.11b DSSS, 802.11g/n: OFDM

Data Rate.....: 802.11b: 1/2/5.5/11 Mbps
802.11g: 6/9/12/18/24/36/48/54 Mbps
802.11n: up to 65 Mbps

Antenna Gain: -0.5 dBi for GSM850 and WCDMA Band V
-1.0 dBi for PCS1900 and WCDMA Band II
-2.0 dBi for Bluetooth and Wi-Fi

Antenna type: Internal

IMEI: 357619049208958

Result.....: **Positive**

TEST REPORT

Test Report No. :	CTL1306281042-WU	August 15, 2013
		Date of issue

Equipment under Test : **Tablet PC**

Model /Type : **L001-30**

Listed Models : L002-6, L097-5, L010-13, L011-1, L001-30S, L002-6S, L002-9S, L097-5S, L010-13S, L011-1S, L013-3S, L001-40, L001-40S, L002-10, L002-10S, L097-6, L097-6S, L010-16, L010-16S, L011-2, L011-2S

Difference Description **Only the model's name is different**

Applicant : **SHENZHEN GOLD EAST ELETRONIC CO., LTD**

Address : 6F, Bldg #11, Yusheng Industry Area, #467 Gushu, Xixiang, Bao'an District, Shenzhen, China 518000

Manufacturer **SHENZHEN GOLD EAST ELETRONIC CO., LTD**

Address 6F, Bldg #11, Yusheng Industry Area, #467 Gushu, Xixiang, Bao'an District, Shenzhen, China 518000

Test Result according to the standards on page 5:	Positive
--	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. TEST STANDARDS	5
2. SUMMARY	6
2.1. General Remarks	6
2.2. Equipment Under Test	6
2.3. Short description of the Equipment under Test (EUT)	6
2.4. EUT operation mode	6
2.5. EUT configuration	7
2.6. Related Submittal(s) / Grant (s)	7
2.7. Modifications	7
3. TEST ENVIRONMENT	8
3.1. Address of the test laboratory	8
3.2. Test Facility	8
3.3. Environmental conditions	8
3.4. Configuration of Tested System	8
3.5. EUT Exercise Software	9
3.6. Statement of the measurement uncertainty	9
3.7. Equipments Used during the Test	10
3.8. Summary of Test Result	11
4. TEST CONDITIONS AND RESULTS	12
4.1. Peak Output Power	12
4.2. Modulation Characteristic	19
4.3. Occupied Bandwidth	20
4.4. Spurious Emission At Antenna Terminals (+/- 1MHz)	33
4.5. Spurious Emission	40
4.6. Frequency Stability under Temperature & Voltage Variations	66
5. TEST SETUP PHOTOS OF THE EUT	73
6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	74

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Part 22 Subpart H:](#) Public Mobile Services

[FCC Part 24 Subpart E:](#) Personal Communications Services

[EIA/TIA 603-C: 2004](#)

[FCC CFR Title 47 Part 2](#)



2. SUMMARY

2.1. General Remarks

Date of receipt of test sample : July 22, 2013

Testing commenced on : July 22, 2013

Testing concluded on : August 15, 2013

2.2. Equipment Under Test

Power supply system utilised

Power supply voltage : ☒ 120V / 60 Hz ☐ 115V / 60Hz
☐ 12 V DC ☐ 24 V DC
☒ Other (specified in blank below)

DC 3.7V from battery

2.3. Short description of the Equipment under Test (EUT)

A Tablet PC (L001-30) with UMTS/GSM, Bluetooth, GPS and wifi function.

For more details, refer to the user's manual of the EUT.

Serial number: Prototype

2.4. EUT operation mode

CTL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: GSM850
Mode 2: PCS1900
Mode 3: GPRS850
Mode 4: GPRS1900
Mode 5: WCDMA Band II
Mode 6: WCDMA Band V
Mode 7: HSDPA Band II
Mode 8: HSUPA Band II
Mode 9: HSDPA Band V
Mode 10: HSUPA Band V

Note:

1. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. For the ERP/EIRP and radiated emission test, every axis (X, Y, Z) was verified, and show the worst result on this report.
3. Radiated power output working at GSM link was higher than that working at GPRS link, so all of test items were done working at GSM mode. Refer to peak power output for more details.
4. This device is a composite device in accordance with Part 15 Subpart B regulations. The report number is CTL1306281042-WD.

2.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

o - supplied by the manufacturer

o - supplied by the lab

o
Manufacturer :
Model No. :


o
Manufacturer :
Model No. :

2.6. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **2AANTL001-30** filing to comply with of the FCC Part 22 and Part 24 Rules.

2.7. Modifications

No modifications were implemented to meet testing criteria.



3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Bontek Compliance Testing Laboratory Ltd
1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2003) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 7631A

The 3m alternate test site of Bontek Compliance Testing Laboratory Ltd EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 7631A on March, 2011.

FCC-Registration No.: 338263

Bontek Compliance Testing Laboratory Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 338263, March 24, 2008.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:


Temperature: 15-35 ° C

Humidity: 30-60 %

Atmospheric pressure: 950-1050mbar

3.4. Configuration of Tested System

Fig. 2-1 Configuration of Tested System



3.5. EUT Exercise Software

1. Setup the EUT and simulators as shown on above.
2. Turn on the power of all equipment.
3. EUT Communicate with CMU200, then select channel to test.


3.6. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Bontek Compliance Testing Laboratory Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Bontek laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



3.7. Equipments Used during the Test

Item	Test Equipment	Manufacturer	Model No.	Last Cal.	Due. Date
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	2013/04/14	2014/04/13
2	Radio Communication Tester	ROHDE & SCHWARZ	CMU200	2013/04/14	2014/04/13
3	Dual Directional Coupler	Agilent	778D	2013/04/14	2014/04/13
4	10dB attenuator	SCHWARZBECK	MTAIMP-136	2013/04/14	2014/04/13
5	Tunable Bandreject filter	K&L	3TNF-800	2013/04/14	2014/04/13
6	Tunable Bandreject filter	K&L	5TNF-1700	2013/04/14	2014/04/13
7	High-Pass Filter	K&L	9SH10-2700/X12750-O/O	2013/04/14	2014/04/13
8	High-Pass Filter	K&L	41H10-1375/U12750-O/O	2013/04/14	2014/04/13
9	Coaxial Cable	Huber+Suhner	AC4-RF-H	2013/04/14	2014/04/13
10	AC Power Supply	IDRC	CF-500TP	2013/04/14	2014/04/13
11	DC Power Supply	IDRC	CD-035-020PR	2013/04/14	2014/04/13
12	RF Current Probe	FCC	F-33-4	2013/04/14	2014/04/13
13	Temperature /Humidity Meter	zhicheng	ZC1-2	2013/04/14	2014/04/13
14	MICROWAVE AMPLIFIER	HP	8349B	2013/04/14	2014/04/13
15	Amplifier	HP	8447D	2013/04/14	2014/04/13
16	SIGNAL GENERATOR	HP	8647A	2013/04/14	2014/04/13
17	Log Periodic Antenna	ELECTRO-METRICS	EM-6950	2013/04/14	2014/04/13
18	Horn Antenna	Schwarzbeck	BBHA9120A	2013/04/14	2014/04/13
19	EMI Test Receiver	R&S	ESPI	2013/04/14	2014/04/13
20	Loop Antenna	ZHINAN	ZN30900A	2013/04/14	2014/04/13
21	Horn Antenna	Schwarzbeck	BBHA9120D	2013/04/14	2014/04/13
22	Horn Antenna	Schwarzbeck	BBHA9170	2013/04/14	2014/04/13
23	Spectrum Analyzer	Agilent	E4446A	2013/04/14	2014/04/13
24	Wideband Peak Power Meter	Anritsu	ML2495A	2013/04/14	2014/04/13
25	Power Sensor	Anritsu	MA2411B	2013/04/14	2014/04/13
26	Climate Chamber	ESPEC	EL-10KA	2013/04/14	2014/04/13

3.8. Summary of Test Result

No deviations from the test standards

For GSM 850/WCDMA Band V (FCC Part 22H & Part 2)

Emission			
Performed Item	Normative References	Test Performed	Deviation
Peak Output Power	FCC Part 22.913(a)(2) and Part 2.1046 EIA/TIA 603-C	Yes	No
Modulation Characteristic	FCC Part 2.1047(d)	Yes	No
Occupied Bandwidth	FCC Part 2.1049	Yes	No
Spurious Emission At Antenna Terminals (+/- 1MHz)	FCC Part 22.917(a) and Part 2.1049	Yes	No
Spurious Emission	FCC Part 22.917(b) and Part 2.1051, 2.1053 EIA/TIA 603-C	Yes	No
Frequency Stability Under Temperature & Voltage Variations	FCC Part 22.355 and 2.1055 EIA/TIA 603-C	Yes	No

For PCS 1900/WCDMA Band II (FCC Part 24E & Part 2)


Emission			
Performed Item	Normative References	Test Performed	Deviation
Peak Output Power	FCC Part 24.232(b) and Part 2.1046 EIA/TIA 603-C	Yes	No
Modulation Characteristic	FCC Part 2.1047(d)	Yes	No
Occupied Bandwidth	FCC Part 24.238(b) and Part 2.1049	Yes	No
Spurious Emission At Antenna Terminals (+/- 1MHz)	FCC Part 24.238(a) and Part 2.1049	Yes	No
Spurious Emission	FCC Part 24.238(b) and Part 2.1051, 2.1053 EIA/TIA 603-C	Yes	No
Frequency Stability Under Temperature & Voltage Variations	FCC Part 24.235 and 2.1055 EIA/TIA 603-C	Yes	No

4. TEST CONDITIONS AND RESULTS


4.1. Peak Output Power

TEST CONFIGURATION

Conducted Power Measurement:



Radiated Power Measurement:



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603C

Conducted Power Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMU200 by a Directional Couple.
- EUT Communicate with CMU200, then select a channel for testing.
- Add a correction factor to the display of spectrum, and then test.

Radiated Power Measurement:

- a) The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b) The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- c) The output of the test antenna shall be connected to the measuring receiver.
- d) The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e) The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g) The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h) The maximum signal level detected by the measuring receiver shall be noted.
- i) The transmitter shall be replaced by a substitution antenna.
- j) The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k) The substitution antenna shall be connected to a calibrated signal generator.
- l) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m) The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n) The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o) The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p) The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q) Test site anechoic chamber refer to ANSI C63.4: 2003.

Base station simulator settings for each test mode:

1. For GSM/GPRS/EDGE
Configure R&S CMU200 to support GMSK and 8PSK call respectively, and set one timeslot transmission for GMSK GSM/GPRS and 8PSK EDGE.
Measure and record power outputs for both modulations.
2. For WCDMA
Configure the CMU-200 to support all WCDMA tests in respect to the 3GPP 34.121.
Measure the EUT output power at 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V and 1852.4MHz, 1880MHz and 1907.6MHz for WCDMA Band II.

For Rel 99

- Set a Test Mode 1 loop back with a 12.2kbps Reference Measurement Channel (RMC)
- Set and send continuously Up power control commands to the Gobi2000
- Measure the power at the Gobi2000 Module antenna connector by using CMU-200.

LIMIT

For FCC Part 22.913(a)(2):

The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

For FCC Part 24.232(b):

The EIRP of mobile transmitters and auxiliary test transmitters must not exceed 2 Watts.

TEST RESULTS**Conducted Power Measurement**

Mode	Frequency (MHz)	Avg. Burst Power (dBm)	Duty Cycle Factor (dB)	Frame Power (dBm)	Max. Power (dBm)	Scaling Factor
GSM850	824.2	32.84	-9	23.84	33	1.038
	836.4	32.94	-9	23.94	33	1.014
	848.8	32.96	-9	23.96	33	1.009
GPRS850(1 Slot)	824.2	32.80	-9	23.80	33	1.047
	836.4	32.89	-9	23.89	33	1.026
	848.8	32.94	-9	23.94	33	1.014
GPRS850(2 Slot)	824.2	30.41	-6	24.41	31	1.146
	836.4	30.55	-6	24.55	31	1.109
	848.8	30.59	-6	24.59	31	1.099
GPRS850(3 Slot)	824.2	28.30	-4.25	24.05	29	1.175
	836.4	28.38	-4.25	24.13	29	1.153
	848.8	28.42	-4.25	24.17	29	1.143
GPRS850(4 Slot)	824.2	27.56	-3	24.56	28	1.107
	836.4	27.62	-3	24.62	28	1.091
	848.8	27.78	-3	24.78	28	1.052
EDGE850(1 Slot)	824.2	27.16	-9	18.16	27.5	1.081
	836.4	27.19	-9	18.19	27.5	1.074
	848.8	27.43	-9	18.43	27.5	1.016
EDGE850(2 Slot)	824.2	26.10	-6	20.10	26.5	1.096
	836.4	26.15	-6	20.15	26.5	1.084
	848.8	26.46	-6	20.46	26.5	1.009
EDGE 850(3 Slot)	824.2	25.28	-4.25	21.03	26	1.180
	836.4	25.30	-4.25	21.05	26	1.175
	848.8	25.61	-4.25	21.36	26	1.094
EDGE 850(4 Slot)	824.2	24.71	-3	21.71	25	1.069
	836.4	24.87	-3	21.87	25	1.030
	848.8	24.94	-3	21.94	25	1.014
PCS1900	1850.2	30.95	-9	21.95	31	1.012
	1880.0	30.89	-9	21.89	31	1.026
	1909.8	30.83	-9	21.83	31	1.040
GPRS1900(1 Slot)	1850.2	30.76	-9	21.76	31	1.057
	1880.0	30.57	-9	21.57	31	1.104
	1909.8	30.37	-9	21.37	31	1.156

GPRS1900(2 Slot)	1850.2	28.69	-6	22.69	29	1.074
	1880.0	28.54	-6	22.54	29	1.112
	1909.8	28.52	-6	22.52	29	1.117
GPRS1900(3 Slot)	1850.2	26.47	-4.25	22.22	26.5	1.007
	1880.0	26.38	-4.25	22.13	26.5	1.028
	1909.8	26.31	-4.25	22.06	26.5	1.045
GPRS1900(4 Slot)	1850.2	25.78	-3	22.78	26	1.052
	1880.0	25.72	-3	22.72	26	1.067
	1909.8	25.69	-3	22.69	26	1.074
EDGE 1900(1 Slot)	1850.2	26.76	-9	17.76	27	1.057
	1880.0	26.59	-9	17.59	27	1.099
	1909.8	26.13	-9	17.13	27	1.222
EDGE 1900(2 Slot)	1850.2	26.26	-6	20.26	26.5	1.057
	1880.0	26.14	-6	20.14	26.5	1.086
	1909.8	26.05	-6	20.05	26.5	1.109
EDGE 1900(3 Slot)	1850.2	26.14	-4.25	21.89	26.5	1.086
	1880.0	26.02	-4.25	21.77	26.5	1.117
	1909.8	25.97	-4.25	21.72	26.5	1.130
EDGE 1900(4 Slot)	1850.2	25.52	-3	22.52	26	1.117
	1880.0	25.41	-3	22.41	26	1.146
	1909.8	25.37	-3	22.37	26	1.156

Note: 1. All conducted measurements are based on a peak detector.

2. The maximum PAR for GPRS1900 is 7.8dB less than 13 dB, and the maximum PAR for EDGE1900 is 7.9dB less than 13 dB.




WCDMA/HSDPA

Mode	3GPP Subtest	Band II (1900MHz) Channel			MPR
		Conducted Power (dBm)			
		9262	9400	9538	
WCDMA R99	1	23.46	23.43	23.54	N/A
Rel5 HSDPA	1	22.47	22.49	22.54	0
	2	22.43	22.40	22.45	0
	3	21.96	21.87	21.99	0.5
	4	21.92	21.83	21.97	0.5

Note: The maximum PAR for WCDMA Band II is 8.9dB less than 13 dB.

Mode	3GPP Subtest	Band V (850MHz) Channel			MPR
		Conducted Power (dBm)			
		4132	4182	4233	
WCDMA R99	1	23.32	23.21	23.29	N/A
Rel5 HSDPA	1	22.17	22.13	22.15	0
	2	22.14	22.09	22.11	0
	3	21.59	21.54	21.56	0.5
	4	21.07	20.96	20.99	0.5

Note: All conducted measurements are based on a RMS detector.



Radiated Measurement

GSM850

Frequency (MHz)	SA Reading (dBm)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 128 (824.20MHz)								
824.2	-16.67	H	17.09	1.75	-0.03	15.31	38.5	-23.19
824.2	-2.3	V	32.28	1.75	-0.03	30.50	38.5	-8.00
Middle Channel 189 (836.40MHz)								
836.4	-16.72	H	17.18	1.74	0.09	15.53	38.5	-22.97
836.4	-3.14	V	32.20	1.74	0.09	30.55	38.5	-7.95
High Channel 251 (848.80MHz)								
848.8	-15.80	H	18.22	1.77	0.12	16.57	38.5	-21.93
848.8	-2.30	V	32.31	1.77	0.12	30.66	38.5	-7.84

GSM1900

Frequency (MHz)	SA Reading (dBm)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 512 (1850.20MHz)								
1850.2	23.24	H	21.83	2.68	10.4	29.55	33.00	-3.45
1850.2	6.12	V	4.52	2.68	10.4	12.24	33.00	-20.76
Middle Channel 661 (1880.00MHz)								
1880	22.36	H	20.85	2.68	10.43	28.60	33.00	-4.40
1880	3.52	V	1.67	2.68	10.43	9.42	33.00	-23.58
High Channel 810 (1909.80MHz)								
1909.8	22.19	H	20.83	2.7	10.44	28.57	33.00	-4.43
1909.8	3.78	V	1.97	2.7	10.44	9.71	33.00	-23.29

EDGE 850

Frequency (MHz)	SA Reading (dBm)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 128 (824.20MHz)								
824.2	-17.9	H	15.86	1.75	-0.02	14.08	38.50	-24.42
824.2	-6.6	V	27.89	1.75	-0.02	26.11	38.50	-12.39
Middle Channel 189 (836.40MHz)								
836.4	-19.1	H	14.78	1.74	0.09	13.13	38.50	-25.37
836.4	-6.85	V	27.90	1.74	0.09	26.25	38.50	-12.25
High Channel 251 (848.80MHz)								
848.8	-20.12	H	13.88	1.77	0.12	12.23	38.50	-26.27
848.8	-6.4	V	28.20	1.77	0.12	26.55	38.50	-11.95

EDGE1900

Frequency (MHz)	SA Reading (dBm)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 512 (1850.20MHz)								
1850.2	19.34	H	17.93	2.68	10.4	25.65	33.00	-7.35
1850.2	3.66	V	2.06	2.68	10.4	9.78	33.00	-23.29
Middle Channel 661 (1880.00MHz)								
1880	19.27	H	17.76	2.68	10.43	25.51	33.00	-7.49
1880	4.14	V	2.29	2.68	10.43	10.04	33.00	-22.96
High Channel 810 (1909.80MHz)								
1909.8	18.65	H	17.29	2.7	10.44	25.03	33.00	-7.97
1909.8	1.91	V	0.11	2.7	10.44	7.85	33.00	-25.15

WCDMA Band II

Frequency (MHz)	SA Reading (dBm)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	ERIP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 9262 (1852.40MHz)								
1852.4	16.08	H	15.54	3.55	10.4	22.39	33.00	-10.61
1852.4	-0.41	V	-1.15	3.55	10.4	5.70	33.00	-27.30
Middle Channel 9400 (1880.00MHz)								
1880	16.11	H	15.45	3.53	10.43	22.35	33.00	-10.65
1880	-0.97	V	-1.97	3.53	10.43	4.93	33.00	-28.07
High Channel 9538 (1907.60MHz)								
1907.6	16.18	H	15.65	3.56	10.44	22.53	33.00	-10.47
1907.6	-1.73	V	-2.74	3.56	10.44	4.14	33.00	-28.86

WCDMA Band V


Frequency (MHz)	SA Reading (dBm)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 4132 (826.40MHz)								
826.4	-21.86	H	12.69	2.56	-0.02	10.11	38.50	-28.39
826.4	-10.51	V	24.81	2.56	-0.02	22.23	38.50	-16.27
Middle Channel 4182 (836.40MHz)								
836.4	-24.69	H	10.14	2.59	0.1	7.65	38.50	-30.85
836.4	-11.13	V	24.53	2.59	0.1	22.04	38.50	-16.46
High Channel 4233 (846.60MHz)								
846.6	-23.35	H	11.35	2.54	0.13	8.94	38.50	-29.56
846.6	-10.86	V	24.52	2.54	0.13	22.11	38.50	-16.39

Calculation formula: ERP/EIRP=SG Reading - Cable loss + Gain



4.2. Modulation Characteristic

TEST CONFIGURATION



LIMIT

N/A

TEST PROCEDURE

GMSK is a form of binary signaling schemes which represent digital states as a shift between discrete sinusoidal frequencies called Frequency Shift Keying (FSK). Minimum Shift Keying (MSK) is continuous phase FSK with the smallest possible modulation index h . Modulation index is defined as:
 $h = 2 \cdot F \cdot T_b$
where F = Peak frequency deviation in Hz and T_b = Bit period in seconds

Two discrete frequencies, representing two distinct digital states, with equal phases at switch time $t = 0$ requires a minimum value of $h = 0.5$. The Gaussian part of GMSK describes the fact that the digital pulses are filtered in the time domain. This results in bits which are sinusoidal rather than square. The effective spectrum is then compressed with the average carrier frequency in the center of the passband. This is a great advantage because of the significantly reduced bandwidth. GMSK is utilized because of these bandwidth conservation properties.

The bandwidth for GSM is a 60 MHz up-link at 1850-1910 MHz and down-link at 1930-1990 MHz. The 65 MHz is divided into 299 channels, each of which is 200 kHz wide. Slight spectral spillage is allowed into neighboring channels (which is minimized by GMSK). This separated transmit/receive frequencies scheme under GSM enables easier duplex filtering.


Within the bandwidth, individual channels are subdivided into multiframes (made of 26 frames), frames (made of 8 time slots), and time slots (made of 8 fields). The time slots are 0.57 ms long allowing 156.25 bits of information including overhead.

TEST RESULTS

The modulation of GSM/WCDMA was verified and confirmed compliance with requirement.

4.3. Occupied Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

Using Occupied Bandwidth measurement function of spectrum analyzer, and setting as follows:

For GPRS/EDGE 850/1900 test --- RBW = 3 kHz and VBW = 10 kHz

For WCDMA FDD Band II/V test --- RBW = 50 kHz and VBW = 200 kHz

LIMIT

N/A

TEST RESULTS

Product	Tablet PC
Test Item	Occupied Bandwidth
Test Mode	Mode 1: GSM 850 Link
Date of Test	2013/07/23

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
128	824.20	310.804	247.047
189	836.40	311.159	242.935
251	848.80	316.492	245.071

Figure Channel 128 (824.20MHz)




Figure Channel 189 (836.40MHz)




Figure Channel 251 (848.80MHz)



Product	Tablet PC
Test Item	Occupied Bandwidth
Test Mode	Mode 2: GSM 1900 Link
Date of Test	2013/07/23

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
512	1850.20	317.059	245.557
661	1880.00	320.895	246.669
810	1909.80	312.582	245.677

Figure Channel 512 (1850.20MHz)




Figure Channel 661 (1880.00MHz)





Figure Channel 810 (1909.80MHz)



Product	Tablet PC
Test Item	Occupied Bandwidth
Test Mode	Mode 3: EDGE 850 Link
Date of Test	2013/07/23

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
128	824.20	313.979	241.002
189	836.40	312.365	240.520
251	848.80	313.945	243.228

Figure Channel 128 (824.20MHz)




Figure Channel 189 (836.40MHz)




Figure Channel 251 (848.80MHz)



Product	Tablet PC
Test Item	Occupied Bandwidth
Test Mode	Mode 4: EDGE 1900 Link
Date of Test	2013/07/23

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
512	1850.20	312.469	244.236
661	1880.00	312.416	241.751
810	1909.80	310.131	240.571

Figure Channel 512 (1850.20MHz)




Figure Channel 661 (1880.00MHz)





Figure Channel 810 (1909.80MHz)



Product	Tablet PC
Test Item	Occupied Bandwidth
Test Mode	Mode 5: WCDMA Band II Link
Date of Test	2013/07/23

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
9262	1852.4	4668	4144.3
9400	1880.0	4660	4154.8
9538	1907.6	4683	4141.4

Figure Channel 9262 (1852.40MHz)




Figure Channel 9400 (1880.0MHz)





Figure Channel 9538 (1907.60MHz)



Product	Tablet PC
Test Item	Occupied Bandwidth
Test Mode	Mode 6: WCDMA Band V Link
Date of Test	2013/07/23

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
4132	826.4	4658	4144.2
4182	836.4	4665	4157.4
4233	846.6	4657	4147.2

Figure Channel 4132 (826.40MHz)




Figure Channel 4182 (836.40MHz)






Figure Channel 4233(846.60MHz)



4.4. Spurious Emission At Antenna Terminals (+/- 1MHz)

TEST CONFIGURATION



TEST PROCEDURE



In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.

LIMIT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

TEST RESULTS

Product	Tablet PC
Test Item	Spurious Emission At Antenna Terminals (+/- 1MHz)
Test Mode	Mode 1: GSM 850 Link
Date of Test	2013/07/23

Figure Channel 128 (824.20MHz)**Figure Channel 251 (848.80MHz)**

Product	Tablet PC
Test Item	Spurious Emission At Antenna Terminals (+/- 1MHz)
Test Mode	Mode 2: GSM1900 Link
Date of Test	2013/07/23

Figure Channel 512 (1850.20MHz)





Figure Channel 810 (1909.80MHz)



Product	Tablet PC
Test Item	Spurious Emission At Antenna Terminals (+/- 1MHz)
Test Mode	Mode 3: EDGE 850 Link
Date of Test	2013/07/23

Figure Channel 128 (824.20MHz)





Figure Channel 251 (848.80MHz)



Product	Tablet PC
Test Item	Spurious Emission At Antenna Terminals (+/- 1MHz)
Test Mode	Mode 4: EDGE1900 Link
Date of Test	2013/07/23

Figure Channel 512 (1850.20MHz)





Figure Channel 810 (1909.80MHz)



Product	Tablet PC
Test Item	Spurious Emission At Antenna Terminals (+/- 1MHz)
Test Mode	Mode 5: WCDMA Band II Link
Date of Test	2013/07/23

Figure Channel 9262 (1852.40MHz)





Figure Channel 9538 (1907.60MHz)



Product	Tablet PC
Test Item	Spurious Emission At Antenna Terminals (+/- 1MHz)
Test Mode	Mode 6: WCDMA Band V Link
Date of Test	2013/07/23

Figure Channel 4132 (826.40MHz)






Figure Channel 4233 (846.60MHz)




4.5. Spurious Emission

TEST CONFIGURATION

Conducted Spurious Measurement:



Radiated Spurious Measurement:



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603C

Conducted Spurious Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMU200 by a Directional Couple.
- EUT Communicate with CMU200, then select a channel for testing.
- Add a correction factor to the display of spectrum, and then test.
- The resolution bandwidth of the spectrum analyzer was set at 100 kHz for Part 22 and 1MHz for Part 24, sufficient scans were taken to show the out of band Emission if any up to 10th harmonic.

Radiated Spurious Measurement:



- a) The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b) The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- c) The output of the test antenna shall be connected to the measuring receiver.
- d) The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e) The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g) The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- q) The maximum signal level detected by the measuring receiver shall be noted.
- h) The transmitter shall be replaced by a substitution antenna.
- i) The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- j) The substitution antenna shall be connected to a calibrated signal generator.
- k) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- l) The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- m) The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- n) The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- o) The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- p) The resolution bandwidth of the spectrum analyzer was set at 100 kHz for Part 22 and 1MHz for Part 24. The frequency range was checked up to 10th harmonic.
- q) Test site anechoic chamber refer to ANSI C63.4: 2009

LIMIT



The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

TEST RESULTS



Product	Tablet PC
Test Item	Conducted Spurious Emission
Test Mode	Mode 1: GSM 850 Link
Date of Test	2013/07/23

Low Channel 128(824.20MHz)



Mid Channel 189(836.40MHz)





High Channel 251(848.80MHz)





Product	Tablet PC
Test Item	Conducted Spurious Emission
Test Mode	Mode 2: GSM1900 Link
Date of Test	2013/07/23

Low Channel 512(1850.20MHz)

Mid Channel 661(1880.00MHz)





High Channel 810(1909.80MHz)





Product	Tablet PC
Test Item	Conducted Spurious Emission
Test Mode	Mode 3: EDGE 850 Link
Date of Test	2013/07/23



Low Channel 128(824.20MHz)



Mid Channel 189(836.40MHz)





High Channel 251(848.80MHz)







Product	Tablet PC
Test Item	Conducted Spurious Emission
Test Mode	Mode 4: EDGE1900 Link
Date of Test	2013/07/23

Low Channel 512(1850.20MHz)







Mid Channel 661(1880.00MHz)







Product	Tablet PC
Test Item	Conducted Spurious Emission
Test Mode	Mode 5: WCDMA Band II Link
Date of Test	2013/07/23

Low Channel 9262(1852.40MHz)







High Channel 9538(1907.60MHz)





Product	Tablet PC
Test Item	Conducted Spurious Emission
Test Mode	Mode 6: WCDMA Band V Link
Date of Test	2013/07/23

Low Channel 4132(826.40MHz)








Product	Tablet PC
Test Item	Radiated Spurious Emission
Test Mode	Mode 1: GSM 850 Link
Date of Test	2013/07/23

Frequency (MHz)	SA Reading (dBm)	Ant.Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 128 (824.20MHz)								
1646.00	-50.72	V	-53.29	2.50	9.75	-46.04	-13.00	-33.04
2470.50	-47.49	V	-46.53	3.12	10.48	-39.17	-13.00	-26.17
1646.00	-56.82	H	-59.48	2.50	9.75	-52.23	-13.00	-39.23
2470.50	-48.22	H	-47.11	3.12	10.48	-39.75	-13.00	-26.75
Middle Channel 189 (836.40MHz)								
1671.50	-48.09	V	-50.76	2.52	9.95	-43.33	-13.00	-30.33
2513.00	-48.13	V	-47.45	3.18	10.62	-40.01	-13.00	-27.01
1671.50	-52.67	H	-55.09	2.52	9.95	-47.66	-13.00	-34.66
2513.00	-46.17	H	-45.10	3.18	10.62	-37.66	-13.00	-24.66
High Channel 251 (848.80MHz)								
1697.00	-54.16	V	-56.89	2.54	10.06	-49.37	-13.00	-36.37
2547.00	-43.58	V	-42.01	3.14	10.68	-34.47	-13.00	-21.47
1697.00	-54.43	H	-56.43	2.54	10.06	-48.91	-13.00	-35.91
2547.00	-46.23	H	-44.41	3.14	10.68	-36.87	-13.00	-23.87



Product	Tablet PC
Test Item	Radiated Spurious Emission
Test Mode	Mode 2: GSM 1900 Link
Date of Test	2013/07/23

Frequency (MHz)	SA Reading (dBm)	Ant.Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 512 (1850.20MHz)								
3700.00	-61.11	V	-57.65	3.84	12.69	-48.80	-13.00	-35.80
5550.00	-55.67	V	-47.16	4.82	13.15	-38.83	-13.00	-25.83
3700.00	-62.67	H	-59.30	3.84	12.69	-50.45	-13.00	-37.45
5550.00	-58.03	H	-50.15	4.82	13.15	-41.82	-13.00	-28.82
Middle Channel 661 (1880.00MHz)								
3760.00	-58.05	V	-54.83	3.73	12.72	-45.84	-13.00	-32.84
5640.00	-53.74	V	-45.81	4.93	13.14	-37.60	-13.00	-24.60
3760.00	-60.73	H	-57.43	3.73	12.72	-48.44	-13.00	-35.44
5640.00	-56.71	H	-49.11	4.93	13.14	-40.90	-13.00	-27.90
High Channel 810 (1909.80MHz)								
3818.00	-55.73	V	-52.01	4.02	12.73	-43.30	-13.00	-30.30
5727.00	-53.15	V	-44.54	4.87	13.11	-36.30	-13.00	-23.30
3818.00	-60.01	H	-56.14	4.02	12.73	-47.43	-13.00	-34.43
5727.00	-54.36	H	-46.12	4.87	13.11	-37.88	-13.00	-24.88



Product	Tablet PC
Test Item	Radiated Spurious Emission
Test Mode	Mode 3: EDGE S850 Link
Date of Test	2013/07/23

Frequency (MHz)	SA Reading (dBm)	Ant.Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 128 (824.20MHz)								
1646.00	-60.03	V	-62.59	2.50	9.75	-55.34	-13.00	-42.34
2470.50	-55.18	V	-54.21	3.12	10.48	-46.85	-13.00	-33.85
1646.00	-57.87	H	-60.53	2.50	9.75	-53.28	-13.00	-40.28
2470.50	-59.79	H	-58.68	3.12	10.48	-51.32	-13.00	-38.32
Middle Channel 189 (836.40MHz)								
1671.50	-59.63	V	-62.30	2.52	9.95	-54.87	-13.00	-41.87
2513.00	-50.20	V	-49.51	3.18	10.62	-42.07	-13.00	-29.07
1671.50	-57.41	H	-59.83	2.52	9.95	-52.40	-13.00	-39.40
2513.00	-57.67	H	-56.60	3.18	10.62	-49.16	-13.00	-36.16
High Channel 251 (848.80MHz)								
1697.00	-58.69	V	-61.43	2.54	10.06	-53.91	-13.00	-40.91
2547.00	-46.57	V	-45.00	3.14	10.68	-37.46	-13.00	-24.46
1697.00	-57.86	H	-59.86	2.54	10.06	-52.34	-13.00	-39.34
2547.00	-55.79	H	-53.97	3.14	10.68	-46.43	-13.00	-33.43




Product	Tablet PC
Test Item	Radiated Spurious Emission
Test Mode	Mode 4: EDGE 1900 Link
Date of Test	2013/07/23

Frequency (MHz)	SA Reading (dBm)	Ant.Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 512 (1850.20MHz)								
3700.00	-64.22	V	-60.78	3.84	12.69	-51.93	-13.00	-38.93
5550.00	-64.97	V	-56.46	4.82	13.15	-48.13	-13.00	-35.13
3700.00	-65.06	H	-61.69	3.84	12.69	-52.84	-13.00	-39.84
5550.00	-65.49	H	-57.60	4.82	13.15	-49.27	-13.00	-36.27
Middle Channel 661 (1880.00MHz)								
3760.00	-61.66	V	-58.44	3.73	12.72	-49.45	-13.00	-36.45
5640.00	-56.32	V	-48.39	4.93	13.14	-40.18	-13.00	-27.18
3760.00	-61.54	H	-58.24	3.73	12.72	-49.25	-13.00	-36.25
5640.00	-62.90	H	-55.29	4.93	13.14	-47.08	-13.00	-34.08
High Channel 810 (1909.80MHz)								
3818.00	-63.36	V	-59.64	4.02	12.73	-50.93	-13.00	-37.93
5727.00	-65.72	V	-57.05	4.87	13.11	-48.81	-13.00	-35.81
3818.00	-65.04	H	-61.17	4.02	12.73	-52.46	-13.00	-39.46
5727.00	-66.31	H	-58.04	4.87	13.11	-49.80	-13.00	-36.80



Product	Tablet PC
Test Item	Radiated Spurious Emission
Test Mode	Mode5: WCDMA Band II Link
Date of Test	2013/07/23

Frequency (MHz)	SA Reading (dBm)	Ant.Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 9262 (1852.40MHz)								
3704.80	-61.42	V	-57.03	4.78	12.69	-49.12	-13.00	-36.12
5557.20	-58.47	V	-45.50	4.82	13.15	-37.17	-13.00	-24.17
3704.80	-61.16	H	-56.85	4.78	12.69	-48.94	-13.00	-35.94
5557.20	-58.04	H	-45.34	4.82	13.15	-37.01	-13.00	-24.01
Middle Channel 9400 (1880.00MHz)								
3760.00	-60.57	V	-56.05	5.03	12.72	-48.36	-13.00	-35.36
5640.00	-60.90	V	-46.89	5.93	13.14	-39.68	-13.00	-26.68
3760.00	-59.81	H	-55.21	5.03	12.72	-47.52	-13.00	-34.52
5640.00	-59.39	H	-45.30	5.93	13.14	-38.09	-13.00	-25.09
High Channel 9538 (1907.60MHz)								
3815.20	-59.88	V	-55.15	5.03	12.73	-47.45	-13.00	-34.45
5722.80	-58.37	V	-45.60	4.87	13.11	-37.36	-13.00	-24.36
3815.20	-56.95	H	-52.04	5.03	12.73	-44.34	-13.00	-31.34
5722.80	-58.63	H	-46.18	4.87	13.11	-37.94	-13.00	-24.94




Product	Tablet PC
Test Item	Radiated Spurious Emission
Test Mode	Mode 6: WCDMA Band V Traffic
Date of Test	2013/07/23

Frequency (MHz)	SA Reading (dBm)	Ant.Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 4132 (826.40MHz)								
1654.50	-61.01	V	-62.76	3.28	9.75	-56.29	-13.00	-43.29
2479.20	-56.30	V	-54.51	4.10	10.48	-48.13	-13.00	-35.13
1654.50	-62.10	H	-63.88	3.28	9.75	-57.41	-13.00	-44.41
2479.00	-59.74	H	-57.73	4.10	10.48	-51.35	-13.00	-38.35
Middle Channel 4182 (836.40MHz)								
1671.50	-59.64	V	-61.50	3.32	9.95	-54.87	-13.00	-41.87
2513.00	-63.82	V	-62.07	4.31	10.62	-55.76	-13.00	-42.76
1671.50	-59.36	H	-60.98	3.32	9.95	-54.35	-13.00	-41.35
2513.00	-63.63	H	-61.49	4.31	10.62	-55.18	-13.00	-42.18
High Channel 4233 (846.60MHz)								
1697.00	-57.34	V	-59.26	3.35	10.06	-52.55	-13.00	-39.55
2539.80	-58.47	V	-56.03	3.91	10.33	-49.61	-13.00	-36.61
1697.00	-60.09	H	-61.06	4.19	10.68	-54.57	-13.00	-41.57
2538.50	-63.24	H	-60.34	4.33	10.79	-53.88	-13.00	-40.88



4.6. Frequency Stability under Temperature & Voltage Variations

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603C

Frequency Stability Under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

LIMIT

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Limit < ± 2.5 ppm

TEST RESULTS

Product	Tablet PC
Test Item	Frequency Stability Under Temperature & Voltage Variations
Test Mode	Mode 1: GSM 850 Link
Date of Test	2013/07/23

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
-30	836.40	51	± 2091
-20	836.40	33	± 2091
-10	836.40	-23	± 2091
0	836.40	-15	± 2091
10	836.40	-20	± 2091
20	836.40	18	± 2091
30	836.40	36	± 2091
40	836.40	-31	± 2091
50	836.40	28	± 2091

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
3.5	836.40	-20	± 2091
3.7	836.40	31	± 2091
4.2	836.40	-34	± 2091

Product	Tablet PC
Test Item	Frequency Stability Under Temperature & Voltage Variations
Test Mode	Mode 2: GSM1900 Link
Date of Test	2013/07/23

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
-30	1880.00	-21	± 4700
-20	1880.00	56	± 4700
-10	1880.00	21	± 4700
0	1880.00	-32	± 4700
10	1880.00	51	± 4700
20	1880.00	28	± 4700
30	1880.00	-35	± 4700
40	1880.00	41	± 4700
50	1880.00	56	± 4700

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
3.5	1880.00	-21	± 4700
3.7	1880.00	31	± 4700
4.2	1880.00	-19	± 4700

Product	Tablet PC
Test Item	Frequency Stability Under Temperature & Voltage Variations
Test Mode	Mode 3: EDGE 850 Link
Date of Test	2013/07/23

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
-30	836.40	20	± 2091
-20	836.40	-25	± 2091
-10	836.40	56	± 2091
0	836.40	-23	± 2091
10	836.40	28	± 2091
20	836.40	-40	± 2091
30	836.40	31	± 2091
40	836.40	-56	± 2091
50	836.40	41	± 2091

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
3.5	836.40	36	± 2091
3.7	836.40	-21	± 2091
4.2	836.40	62	± 2091

Product	Tablet PC
Test Item	Frequency Stability Under Temperature & Voltage Variations
Test Mode	Mode 4: EDGE1900 Link
Date of Test	2013/07/23

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
-30	1880.00	-39	± 4700
-20	1880.00	51	± 4700
-10	1880.00	-21	± 4700
0	1880.00	-44	± 4700
10	1880.00	34	± 4700
20	1880.00	-36	± 4700
30	1880.00	-21	± 4700
40	1880.00	24	± 4700
50	1880.00	-17	± 4700

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
3.5	1880.00	-15	± 4700
3.7	1880.00	-28	± 4700
4.2	1880.00	36	± 4700

Product	Tablet PC
Test Item	Frequency Stability Under Temperature & Voltage Variations
Test Mode	Mode 5: WCDMA Band II Link
Date of Test	2013/07/23

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
-30	1880.00	-30	± 4700
-20	1880.00	62	± 4700
-10	1880.00	26	± 4700
0	1880.00	31	± 4700
10	1880.00	41	± 4700
20	1880.00	-54	± 4700
30	1880.00	-23	± 4700
40	1880.00	-34	± 4700
50	1880.00	34	± 4700

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
3.5	1880.00	-56	± 4700
3.7	1880.00	-14	± 4700
4.2	1880.00	32	± 4700

Product	Tablet PC
Test Item	Frequency Stability Under Temperature & Voltage Variations
Test Mode	Mode 6: WCDMA Band V Link
Date of Test	2013/07/23

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
-30	836.40	62	± 2091
-20	836.40	-34	± 2091
-10	836.40	-26	± 2091
0	836.40	56	± 2091
10	836.40	45	± 2091
20	836.40	36	± 2091
30	836.40	-43	± 2091
40	836.40	35	± 2091
50	836.40	40	± 2091

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
3.5	836.40	21	± 2091
3.7	836.40	-28	± 2091
4.2	836.40	32	± 2091


5. Test Setup Photos of the EUT




6. External and Internal Photos of the EUT


External Photos of EUT









Internal Photos of EUT







.....End of Report.....