

## FCC - TEST REPORT

Report Number : **68.920.15.059.01** Date of Issue: April 12, 2016

Model : **W800BTR, W800BT/XX, W800BTYY/XX, (X=0 to 9 for marketing purpose representing different counties, Y=A to Z or Blank for different color).**

Product Type : True Wireless Headphones and Charging Case

Applicant : Gibson Innovations Limited

Address : 5/F Philips Electronics Building, 5 Science Park East Ave,  
HK Science Park, Shatin, NT, Hong Kong

Production Facility : Sheng Hai Electronics ( Shenzhen) Ltd.

Address : Block 17-19, Hui Ming Ying Industry, Yan Chuan, Song Gang  
Bao'an District, 518105 Shenzhen,  
PEOPLE'S REPUBLIC OF CHINA

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including Appendices : 37

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.*

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval*

## 1 Table of Contents

1	Table of Contents .....	2
2	Details about the Test Laboratory .....	3
3	Description of the Equipment Under Test .....	4
4	Summary of Test Standards .....	5
5	Summary of Test Results .....	6
6	General Remarks .....	7
7	Test Setups .....	8
8	Systems test configuration .....	9
9	Technical Requirement .....	10
9.1	Conducted peak output power .....	10
9.2	20 dB bandwidth and 99% Occupied Bandwidth .....	12
9.3	Carrier Frequency Separation .....	19
9.4	Number of hopping frequencies .....	22
9.5	Dwell Time .....	24
9.6	Spurious RF conducted emissions .....	27
9.7	Band edge testing .....	31
9.8	Spurious radiated emissions for transmitter .....	34
10	Test Equipment List .....	36
11	System Measurement Uncertainty .....	37

## 2 Details about the Test Laboratory

### Details about the Test Laboratory

#### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch  
Building 12&13, Zhiheng Wisdomland Business Park,  
Nantou Checkpoint Road 2, Nanshan District,  
Shenzhen City, 518052,  
P. R. China

FCC Registration  
Number: 502708

Telephone: 86 755 8828 6998  
Fax: 86 755 8828 5299

### 3 Description of the Equipment Under Test

Product:	True Wireless Headphones and Charging Case
Model no.:	W800BTR
FCC ID:	2AANUW800BTR
Options and accessories:	NIL
Rating:	3.7VDC (Supplied by the internal Li-ion rechargeable battery) 5.0VDC, 0.5A (Charging by USB Port)
RF Transmission Frequency:	2402MHz-2480MHz
No. of Operated Channel:	79
Duty Cycle	34.8%
Modulation:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	Integrated Antenna
Antenna Gain:	-1.0dBi
Description of the EUT:	The Equipment Under Test (EUT) is a Bluetooth headphone operated at 2.4GHz

## 4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2014 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to Public Notice DA 00-705 -Frequency Hopper Spread Spectrum Test Procedure released by FCC on March 30, 2000 and C63.10 (2013).

## 5 Summary of Test Results

Technical Requirements			
FCC Part 15 Subpart C			
Test Condition		Pages	Test Result
§15.207	Conducted emission AC power port	--	N/A
§15.247(b)(1)	Conducted peak output power	10	Pass
§15.247(e)	Power spectral density*	--	N/A
§15.247(a)(2)	6dB bandwidth	--	N/A
§15.247(a)(1)	20dB bandwidth and 99% Occupied Bandwidth	12	Pass
§15.247(a)(1)	Carrier frequency separation	19	Pass
§15.247(a)(1)(iii)	Number of hopping frequencies	22	Pass
§15.247(a)(1)(iii)	Dwell Time	24	Pass
§15.247(d)	Spurious RF conducted emissions	27	Pass
§15.247(d)	Band edge	31	Pass
§15.247(d) & §15.209 &	Spurious radiated emissions for transmitter and receiver	34	Pass
§15.203	Antenna requirement	See note 1	Pass

Note 1: N/A=Not Applicable.

Note 2: The EUT uses an Integrated Antenna, which gain is -1.0dBi. In accordance to §15.203, it is considered sufficiently to comply with the provisions of this section.

## 6 General Remarks

### Remarks

This submittal(s) (test report) is intended for FCC ID: 2AANUW800BTR complies with Section 15.209, 15.247 of the FCC Part 15, Subpart C.

All models are identical with W800BTR except model name, so full testing was applied on W800BTR, the other models were deemed to fulfill the EMC test requirement without further testing.

This report is for the BT3.0 part.

### SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment Under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: 10 December 2015

Testing Start Date: 04 January 2016

Testing End Date: 07 January 2016

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

Reviewed by:



Phoebe Hu  
EMC Project Manager

Prepared by:



Aaron Lai  
EMC Project Engineer


Tested by:




Leon Zhang  
EMC Test Engineer

## 7 Test Setups

### 7.1 Radiated test setups



### 7.2 Conducted RF test setups





## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
---	---	---	---

Test software: Blue test 3.0, which used to control the EUT in continues transmitting mode

The system was configured to hopping mode and non-hopping mode.

Hopping mode: typical working mode (normal hopping status)

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power

## 9 Technical Requirement

### 9.1 Conducted peak output power

#### Test Method

1. Use the following spectrum analyzer settings:  
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel  
RBW > the 20 dB bandwidth of the emission being measured, VBW $\geq$ RBW,  
Sweep = auto, Detector function = peak, Trace = max hold
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power

#### Limits

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	$\leq 1$	$\leq 30$

## Conducted peak output power

### BT 3.0 Bluetooth Mode GFSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	9.54	Pass
Middle channel 2441MHz	9.82	Pass
High channel 2480MHz	9.68	Pass

### BT3.0 Bluetooth Mode $\pi/4$ -DQPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	7.85	Pass
Middle channel 2441MHz	8.28	Pass
High channel 2480MHz	8.10	Pass

### BT3.0 Bluetooth Mode 8DPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	8.11	Pass
Middle channel 2441MHz	8.53	Pass
High channel 2480MHz	8.34	Pass

## 9.2 20 dB bandwidth and 99% Occupied Bandwidth

### Test Method

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### Limit

Limit [kHz]


---

N/A

## 20 dB bandwidth and 99% Occupied Bandwidth


### Bluetooth Mode GFSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	903.0	842.25	--	Pass
2441	881.3	881.30	--	Pass
2480	877.0	842.25	--	Pass




Date: 5.JAN.2016 16:46:05

2402MHz



Date: 5.JAN.2016 16:47:25

2441MHz




Date: 5.JAN.2016 16:48:34

2480MHz

## 20 dB bandwidth and 99% Occupied Bandwidth


Bluetooth Mode  $\pi/4$ -DQPSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	1220.0	1167.87	--	Pass
2441	1215.0	1167.87	--	Pass
2480	1215.0	1167.87	--	Pass




Date: 5.JAN.2016 16:44:06

2402MHz



Date: 5.JAN.2016 16:42:42

2441MHz



Date: 5.JAN.2016 16:41:01


2480MHz



## 20 dB bandwidth and 99% Occupied Bandwidth


### Bluetooth Mode 8DPSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	1228.7	1150.50	--	Pass
2441	1221.3	1150.50	--	Pass
2480	1211.3	1146.16	--	Pass




Date: 5.JAN.2016 16:53:09

2402MHz



Date: 5.JAN.2016 16:51:39

2441MHz



Date: 5.JAN.2016 16:50:04

2480MHz

### 9.3 Carrier Frequency Separation

#### Test Method

1. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels,  $RBW \geq 1\%$  of the span,  $VBW \geq RBW$ , Sweep = auto, Detector function = peak
2. By using the Max-Hold function record the separation of two adjacent channels.
3. Measure the frequency difference of these two adjacent channels by spectrum analyzer marker function.
4. Repeat above procedures until all frequencies measured were complete.

#### Limit

Limit  
kHz

≥25KHz or 2/3 of the 20 dB bandwidth which is greater

#### GFSK Modulation Limit

Frequency MHz	2/3 of 20 dB Bandwidth kHz
2402	602.00
2441	587.53
2480	584.66


## Carrier Frequency Separation

Test result: The measurement was performed with the typical configuration (normal hopping status), here GFSK modulation mode was used to show compliance.

### GFSK Modulation test result


Frequency MHz	Carrier Frequency Separation kHz	Result
2402	1000.0	Pass
2441	1000.0	Pass
2480	1000.0	Pass

### Low Channel




Date: 5.JAN.2016 17:20:46

## Middle channel



Date: 5.JAN.2016 17:21:57

## High Channel



Date: 5.JAN.2016 17:23:36

## 9.4 Number of hopping frequencies

### Test Method

1. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels,  $RBW \geq 1\%$  of the span,  $VBW \geq RBW$ , Sweep = auto, Detector function = peak
2. Set the spectrum analyzer on Max-Hold Mode, and then keep the EUT in hopping mode.
3. Record all the signals from each channel until each one has been recorded.
4. Repeat above procedures until all frequencies measured were complete.

### Limit

**Limit  
number**


---

$\geq 15$

Number of hopping frequencies

Test result: The measurement was performed with the typical configuration (normal hopping status), and the total hopping channels is constant for the all modulation mode according with the Bluetooth Core Specification. Here GFSK modulation mode was used to show compliance.

Number of hopping frequencies	Result
79	Pass



Date: 5.JAN.2016 17:19:06

## 9.5 Dwell Time

### Test Method

1. Connect EUT antenna terminal to the spectrum analyzer with a low loss cable.  
Equipment mode: Spectrum analyzer
2. RBW: 1MHz; VBW: 1MHz; SPAN: Zero Span
3. Adjust the center frequency of spectrum analyzer on any frequency be measured.
4. Measure the Dwell Time by spectrum analyzer Marker function.
5. Repeat above procedures until all frequencies measured were complete.

### Limit

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.



## Dwell Time

### Dwell time

The maximum dwell time shall be 0.4 s.

According to the Bluetooth Core Specification, the worse result (DH5 mode) was reported to show compliance.

The Dwell Time = Burst Width \* Total Hops. The detailed calculations are showed as follows:

The duration for dwell time calculation: 0.4 [s] \* hopping number = 0.4 [s] \* 79 [ch] = 31.6 [s\*ch];


The burst width, which is directly measured, refers to the duration on one channel hop.

The maximum number of hopping channels in 31.6s for DH5=1600 / 6 / 79 \*31.6=106.67

### Test Result

Modulation	Mode	Reading (ms)	Total Hops	Test Result (ms)	Limit (ms)	Result
GFSK	DH5	2.8986	107.44	311.43	< 400	Pass
$\pi/4$ -DQPSK	2DH5	2.9130	107.44	312.97	< 400	Pass
8-DPSK	3DH5	2.8986	107.44	311.43	< 400	Pass


### GFSK Modulation



Date: 5.JAN.2016 17:31:11

DH5


## $\pi/4$ -DQPSK Modulation



Date: 5.JAN.2016 17:30:00

2DH5

## 8-DPSK Modulation



Date: 5.JAN.2016 17:25:21

3DH5

## 9.6 Spurious RF conducted emissions

### Test Method

1. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10<sup>th</sup> harmonic. Typically, several plots are required to cover this entire span.  
RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
3. The level displayed must comply with the limit specified in this Section. Submit these plots.
4. Repeat above procedures until all frequencies measured were complete.



### Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20


Remark: Only the worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.

## Spurious RF conducted emissions


BT3.0 GFSK Modulation:  
2402MHz



## 2441MHz




Date: 5.JAN.2016 16:22:28




Date: 5.JAN.2016 16:21:43

2480MHz



Date: 5.JAN.2016 16:24:37



Date: 5.JAN.2016 16:23:57

## 9.7 Band edge testing

### Test Method


- 1 Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 100 kHz, VBW  $\geq$  RBW, Sweep = auto, Detector function = peak, Trace = max hold
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section. .
- 4 Repeat the test at the hopping off and hopping on mode, submit all the plots.

### Limit:


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

## Band edge testing

### BT3.0 GFSK Modulation Test Result: Hopping on mode:




Date: 5.JAN.2016 17:10:13




Date: 5.JAN.2016 17:06:46



## Hopping off mode:



Date: 5.JAN.2016 17:08:40



Date: 5.JAN.2016 17:07:44

## 9.8 Spurious radiated emissions for transmitter

### Test Method

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
3. Use the following spectrum analyzer settings:  
Span = wide enough to fully capture the emission being measured, RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz, VBW  $\geq$  RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Follow the guidelines in ANSI C63.4-2009 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc.  
The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the duty cycle per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{duty cycle}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

### Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Field Strength dBuV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

## Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.

### Transmitting spurious emission test result as below:

#### BT3.0 GFSK Modulation 2402MHz Test Result

Frequency Band	Frequency MHz	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Margin dBuV/m	Result
30-1000MHz	885.91	31.47	H	46	QP	14.53	Pass
	877.99	34.81	V	46	QP	11.19	Pass
1000-25000MHz	4804.00	50.98	H	74	PK	23.02	Pass
	7206.00	41.63	H	74	PK	32.37	Pass
	4804.50	50.42	V	74	PK	23.58	Pass
	7206.00	42.34	V	74	PK	31.66	Pass

#### BT3.0 GFSK Modulation 2441MHz Test Result

Frequency Band	Frequency MHz	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Margin dBuV/m	Result
30-1000MHz	--	--	--	--	--	--	Pass
	--	--	--	--	--	--	Pass
1000-25000MHz	4881.50	54.37	H	74	PK	19.63	Pass
	4881.50	45.23	H	54	AV	8.77	Pass
	7322.50	41.50	H	74	PK	32.50	Pass
	4882.00	51.67	V	74	PK	22.33	Pass
	7323.50	46.81	V	74	PK	27.19	Pass

#### BT3.0 GFSK Modulation 2480MHz Test Result

Frequency Band	Frequency MHz	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Margin dBuV/m	Result
30-1000MHz	--	--	--	--	--	--	Pass
	--	--	--	--	--	--	Pass
1000-25000MHz	4959.50	50.81	H	74	PK	23.19	Pass
	7400.00	40.82	H	74	PK	33.18	Pass
	4959.50	49.12	V	74	PK	24.88	Pass
	7439.50	45.48	V	74	PK	28.32	Pass

Remark:

- (1) AV Emission Level= PK Emission Level+20log(dutycycle)
- (2) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.
- (3) "\*" means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.

## 10 Test Equipment List

**List of Test Instruments**

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
C	Signal Generator	Rohde & Schwarz	SMB100A	108272	2016-7-24
	Signal Analyzer	Rohde & Schwarz	FSV40	101030	2016-7-24
	Vector Signal Generator	Rohde & Schwarz	SMU 200A	105324	2016-7-24
	RF Switch Module	Rohde & Schwarz	OSP120/OS P-B157	101226/100851	2016-7-24
RE	EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2016-7-24
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	2016-8-14
	Horn Antenna	Rohde & Schwarz	HF907	102294	2016-7-24
	Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2016-7-24
	3m Semi-anechoic chamber	TDK	9X6X6	----	2019-5-29

### C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth
- 20dB bandwidth and 99% Occupied Bandwidth
- Carrier frequency separation
- Number of hopping frequencies
- Dwell Time
- Power spectral density\*
- Spurious RF conducted emissions
- Band edge

## 11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.83dB; Vertical: 4.91dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-18000MHz	Horizontal: 4.89dB; Vertical: 4.88dB;
Uncertainty for Conducted Emission 150KHz-30MHz	U=3.5dB(k=2)