

FCC Test Report

Report No.: AGC01665180502FE03

FCC ID : 2AAPK-MAJH007

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: WIRELESS LOCATOR TAG

BRAND NAME : N/A

MODEL NAME : AZ50001, F01, F03, F04, F05

CLIENT: Shenzhen Kingsun Enterprises Co., Ltd.

DATE OF ISSUE : May 28, 2018

STANDARD(S)

TEST PROCEDURE(S)

: FCC Part 15 Subpart C Section 15.249

REPORT VERSION V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



The results spowed this jest eport refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago-gent.com.

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



Page 2 of 52

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	pliance / State	May 28, 2018	Valid	Initial release

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.gett.com.



TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	5 5
3. MEASUREMENT UNCERTAINTY	6
4. DESCRIPTION OF TEST MODES	
5. SYSTEM TEST CONFIGURATION	8
5.1. CONFIGURATION OF EUT SYSTEM	8 8 9
6. TEST FACILITY	10
7.TEST METHOD	
8. TEST EQUIPMENT LIST	11
9. RADIATED EMISSION	12
9.1TEST LIMIT 9.2. MEASUREMENT PROCEDURE 9.3. TEST SETUP 9.4. TEST RESULT	12 13
10. BAND EDGE EMISSION	36
10.1. MEASUREMENT PROCEDURE 10.2 TEST SETUP 10.3 RADIATED TEST RESULT	36
11. 20DB BANDWIDTH	41
11.1. MEASUREMENT PROCEDURE	41 41
12. FCC LINE CONDUCTED EMISSION TEST	
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	45 45 45
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	46
APPENDIX B. PHOTOGRAPHS OF FUT	48



age 4 of 52

1. VERIFICATION OF CONFORMITY

Applicant	Shenzhen Kingsun Enterprises Co., Ltd.			
Address	25/F, CEC Information Building, Xinwen Rd., Shenzhen, Guangdong, China			
Manufacturer	Shenzhen Jiehongwei Tednology Co.,Ltd			
Address	3F, Building B, Shengjingyuan Industrial Park, Fuqian Road, Guanlan Town, Shenzhen City			
Product Designation	WIRELESS LOCATOR TAG			
Brand Name	N/A			
Test Model	AZ50001			
Series Model	F01, F03, F04, F05			
Difference description	All the same except for the appearance shape			
Date of test	May 10, 2018 to May 26, 2018			
Deviation	None Sand Comment of the Comment of			
Condition of Test Sample	Normal			
Report Template	AGCRT-US-BR/RF			

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249. The test results of this report relate only to the tested sample identified in this report.

Tested By	Jorden Wang	
C C	Jonhen Wang(Wang Yonghuan)	May 26, 2018
Reviewed By	and change	
	Cool Cheng(Cheng Mengguo)	May 28, 2018
Approved By	Fowert cen	
CC TOWN	Forrest Lei(Lei Yonggang) Authorized Officer	May 28, 2018

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a try. //www.agc.webt.com



Page 5 of 52

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	-2.59dBm(Max EIRP Power=Max radiation field-95.2)
Bluetooth Version	V4.0
Modulation	BR □GFSK, EDR □π /4-DQPSK, □8DPSK BLE ☑GFSK
Number of channels	40
Hardware Version	V1 _x
Software Version	V1
Antenna Designation	PCB Antenna
Antenna Gain	-3dBi
Power Supply	DC 3V by battery

2.2. TABLE OF CARRIER FREQUENCYS

BLE Channel List

Frequency Band	Channel Number	Frequency		
	0	2402MHz		
	The state of the s	2404MHz		
2400~2483.5MHz				
	38	2478 MHz		
	39	2480 MHz		

The results specified this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by (CC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the confirmed at a



Page 6 of 52

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB


4. DESCRIPTION OF TEST MODES

NO.		TEST MODE DESCRIPTION			
8 4	Martinesia Inol Globa	Low channel GFSK			
CO	2	Middle channel GFSK			
	3	High channel GFSK			
10 mms	4 Karajane	BT Link			

Note:

- 1. Transmitting duty cycle >98%, The average correction factor is about -0.1
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.





The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



age 8 of 52

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)

EUT

Configure 2: (Control continuous TX)

			KET.	
EUT	station o	Control box	Da.	PC

5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	WIRELESS LOCATOR	Jiehongwei	AZ50001	EUT A
2	Battery	CR	2032	Accessory
3	PC	APPLE	A1465	A.E
4	Control box	SERIAL	N/A	A.E
5	USB Cable	N/A	1m unshielded	A.E
6	Mobile phone	Xiaomi	MAX 2S	A.E



Page 9 of 52

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249(a) §15.209	Radiated Emission	Compliant
§15.249(d)	Band Edges	Compliant
§15.207	Conduction Emission	N/A
§15.215	Bandwidth	Compliant

Note: N/A means it's not applicable to this item.



Page 10 of 52

6. TEST FACILITY

Tite.	
Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2F., Bldg.2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District B112-B113, Bldg.12, Baoan Bldg Materials Center, No.1 of Xixiang Inner Ring Road, Baoan District, Shenzhen 518012
NVLAP Lab Code	600153-0
Designation Number	CN5028
Test Firm Registration Number	682566
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by National Voluntary Laboratory Accreditation program, NVLAP Code 600153-0



age 11 of 52

7. TEST METHOD

All measurements contained in this report were conducted with ANSI C63.10-2013

8. TEST EQUIPMENT LIST

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun.20, 2017	Jun.19, 2018
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec.08, 2017	Dec.07, 2018
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep.20, 2017	Sep.19, 2018
preamplifier	ChengYi	EMC184045SE	980508	Sep.15, 2017	Sep.14, 2018
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May 18, 2017	May 17, 2019
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun.20, 2017	Jun.19, 2018
ANTENNA	SCHWARZBECK	VULB9168	D69250	Sep.28, 2017	Sep.27, 2018
Radiation Cable 1	MXT	RS1	R005	June 6, 2017	June 5, 2018
Radiation Cable 2	MXT	RS1	R006	June 6, 2017	June 5, 2018
Loop Antenna	A.H.Systems,Inc	SAS-562B	station of Country	Mar. 01, 2018	Feb. 28, 2019
Filter (2.4-2.483GHz)	Micro-tronics	087		Jun.20, 2017	Jun.19, 2018



Page 12 of 52

9. RADIATED EMISSION

9.1TEST LIMIT

Standard FCC15.249

Fundamental	Field Strength of Fundamental	Field Strength of Harmonics
Frequency	(millivolts/meter)	(microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency	Distance	Field Strengths Limit					
(MHz)	Meters	μ V/m	dB(μV)/m				
0.009 ~ 0.490	300	2400/F(kHz)					
0.490 ~ 1.705	30	24000/F(kHz)	电视 不是心				
1.705 ~ 30	30	30	Company of Circumstance of Cir				
30 ~ 88	3	100	40.0				
88 ~ 216	3	150	43.5				
216 ~ 960	3	200	46.0				
960 ~ 1000	3	500	54.0				
Above 1000	3 F. F. Standard Community	Other:74.0 dB(µV)/m (Average)	(Peak) 54.0 dB(μV)/m				

Remark:

- (1) Emission level dB μ V = 20 log Emission level μ V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.



Page 13 of 52

9.2. MEASUREMENT PROCEDURE

- 1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
- 2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
- The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
- 4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- 5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
- 6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 14 of 52


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	Fundamental: 2.4~2.483GHz RBW 2MHz/ VBW 6MHz for Peak, RBW 2MHz/ VBW 10Hz for Average Harmonics: 1GHz~25GHz RBW 1MHz/ VBW 3MHz for Peak, RBW 1MHz/ VBW 10Hz for Average
Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP





9.3. TEST SETUP

RADIATED EMISSION TEST-SETUP FREQUENCY BELOW 30MHz




RADIATED EMISSION TEST SETUP 30MHz-1000MHz







RADIATED EMISSION TEST SETUP ABOVE 1000MHz



Page 17 of 52


9.4. TEST RESULT

RADIATED EMISSION BELOW 30MHz

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHz

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL-HORIZONTAL




A. Suspected List:

	Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Marqin dB	Pass/Fail	Height cm	Angle deg
	38.730	Н	6.7	17.3	24.0	40.0	16.0	Pass	100.0	70.5
	150.280	Н	5.8	16.6	22.4	43.5	21.1	Pass	100.0	358.1
Γ	462.620	Н	5.0	22.3	27.3	46.0	18.7	Pass	100.0	70.5
	651.770	Н	6.6	25.6	32.2	46.0	13.8	Pass	150.0	327.0
	855.955	Н	5.9	29.7	35.6	46.0	10.4	Pass	100.0	70.5
	971.385	Н	6.7	30.9	37.6	54.0	16.4	Pass	150.0	254.3

RESULT: PASS



RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL -VERTICAL



A. Suspected List:

	Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
	47.460	v	5.2	17.2	22.4	40.0	17.6	Pass	150.0	180.4
	141.550	V	5.6	16.6	22.2	43.5	21.3	Pass	200.0	71.6
	530.035	v	6.6	23.4	30.0	46.0	16.0	Pass	200.0	71.6
	666.805	V	6.3	25.8	32.1	46.0	13.9	Pass	100.0	343.6
34	741.495	v	6.8	27.3	34.1	46.0	11.9	Pass	150.0	144.3
	966.050	v	6.2	30.8	37.0	54.0	17.0	Pass	150.0	108.8


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.



RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL-HORIZONTAL




A. Suspected List:

	Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(u√/m) PK	Limit dB(u\//m) QP	Marqin dB	Pass/Fail	Height cm	Angle deg
	46.490	H	6.1	17.2	23.3	40.0	16.7	Pass	100.0	339.2
	138.155	Н	5.6	16.6	22.2	43.5	21.3	Pass	100.0	267.3
	477.655	Н	6.2	22.5	28.7	46.0	17.3	Pass	100.0	232.6
	529.065	Н	5.7	23.4	29.1	46.0	16.9	Pass	100.0	159.9
3	889.905	Н	5.4	30.1	35.5	46.0	10.5	Pass	150.0	72.1
	934.040	Н	6.7	30.5	37.2	46.0	8.8	Pass	100.0	302.8

RESULT: PASS



RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL -VERTICAL



A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Marqin dB	Pass/Fail	Height cm	Angle deg
41.155	V	5.6	17.4	23.0	40.0	17.0	Pass	100.0	287.8
67.830	V	6.4	15.0	21.4	40.0	18.6	Pass	100.0	37.0
143.490	V	6.7	16.6	23.3	43.5	20.2	Pass	150.0	216.2
697.845	V	6.4	26.3	32.7	46.0	13.3	Pass	150.0	34.2
810.365	V	6.8	28.9	35.7	46.0	10.3	Pass	150.0	216.2
965.080	V	6.2	30.8	37.0	54.0	17.0	Pass	100.0	37.0


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.



RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL-HORIZONTAL



A. Suspected List:


	Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Marqin dB	Pass/Fail	Height cm	Angle deg
	36.790	H	6.0	16.8	22.8	40.0	17.2	Pass	200.0	127.2
Г	53.765	Н	5.6	16.8	22.4	40.0	17.6	Pass	200.0	267.4
	159.980	H	5.7	16.6	22.3	43.5	21.2	Pass	150.0	181.4
	494.145	Н	5.2	22.8	28.0	46.0	18.0	Pass	200.0	308.1
	855.955	Н	5.9	29.7	35.6	46.0	10.4	Pass	200.0	308.1
	951.500	Н	6.2	30.7	36.9	46.0	9.1	Pass	200.0	344.7

RESULT: PASS



Page 22 of 52

RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL -VERTICAL



A. Suspected List:

	Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Marqin dB	Pass/Fail	Height cm	Angle deg
Γ	40.670	V	6.4	17.4	23.8	40.0	16.2	Pass	200.0	72.0
ſ	54.735	V	6.1	16.7	22.8	40.0	17.2	Pass	200.0	217.9
	152.220	v	5.2	16.6	21.8	43.5	21.7	Pass	100.0	339.9
	486.870	V	6.5	22.7	29.2	46.0	16.8	Pass	200.0	325.5
311	858.380	V	6.2	29.7	35.9	46.0	10.1	Pass	200.0	72.0
	989.815	V	5.6	31.0	36.6	54.0	17.4	Pass	100.0	267.8

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.




Page 23 of 52

RADIATED EMISSION ABOVE 1GHz

For Fundamental

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1		2402.000	82.29	10.32	92.61	114.00	-21.39	peak			
2	*	2402.000	74.06	10.32	84.38	94.00	-9.62	AVG	100	133	

RESULT: PASS



Page 24 of 52

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




RESULT: PASS



Page 25 of 52

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL




RESULT: PASS

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 26 of 52

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
*	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2440.000	81.13	10.36	91.49	114.00	-22.51	peak			
2	*	2440.000	72.78	10.36	83.14	94.00	-10.86	AVG	100	314	


RESULT: PASS

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 27 of 52

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL




RESULT: PASS

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.agc.gett.com.



Page 28 of 52

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



RESULT: PASS

2480.000

72.31

10.41

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

82.72

The "Factor" value can be calculated automatically by software of measurement system.

94.00

-11.28

AVG

311

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 29 of 52

Field strength of the fundamental signal

1Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	82.29	10.32	92.61	114	-21.39	Horizontal	
2402	81.79	10.32	92.11	114	-21.89	Vertical	
2440	81.63	10.36	91.99	114	-22.01	Horizontal	
2440	81.13	10.36	91.49	114	-22.51	Vertical	
2480	80.75	10.41	91.16	114	-22.84	Horizontal	
2480	80.25	10.41	90.66	114	-23.34	Vertical	

Average value


Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	74.06	10.32	84.38	94	-9.62	Horizontal	
2402	73.62	10.32	83.94	94	-10.06	Vertical	
2440	73.09	10.36	83.45	94	-10.55	Horizontal	
2440	72.78	10.36	83.14	94	-10.86	Vertical	
2480	72.57	10.41	82.98	94	-11.02	Horizontal	
2480	72.31	10.41	82.72	94	-11.28	Vertical	



Page 30 of 52

For Harmonics

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL



74.00

-21.60

RESULT: PASS

4804.000

7.69


52.40

44.71



Page 31 of 52

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




RESULT: PASS

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago.gent.com.



Page 32 of 52

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL




RESULT: PASS



Page 33 of 52

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL



74.00

-21.72

peak

RESULT: PASS

4882.000

44.39

7.89

52.28


3

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 34 of 52

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL



RESULT: PASS


The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 💢 €, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc-cert.com.

\GC ? Attestation of Global Compliance peak



Page 35 of 52

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
i i		MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2325.000	36.14	10.24	46.38	74.00	-27.62	peak			
2		4108.333	35.91	13.39	49.30	74.00	-24.70	peak			
3	*	4960.000	45.41	8.09	53.50	74.00	-20.50	peak			

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.



Page 36 of 52

10. BAND EDGE EMISSION


10.1. MEASUREMENT PROCEDURE

- The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2. Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission.

	Start frequenc	y(MHz)		Stop frequency(MHz)			
	2200	Kimplence	The Committee	@ ## glation of G	2405	100	
(S) ### (1)	2478	3lobal C	Allestation of Glob	·,O *	2500		

10.2 TEST SETUP

RADIATED EMISSION TEST SETUP





age 37 of 52

10.3 RADIATED TEST RESULT

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
100	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2363.317	33.71	10.28	43.99	74.00	-30.01	peak			
2		2390.000	34.00	10.31	44.31	74.00	-29.69	peak			
3		2400.000	33.97	10.32	44.29	74.00	-29.71	peak			
4	*	2402.000	82.22	10.32	92.54	74.00	18.54	peak			
5	Х	2402.000	74.09	10.32	84.41	74.00	10.41	AVG	100	139	

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Page 38 of 52

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
€	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2372.542	31.78	10.29	42.07	74.00	-31.93	peak			
2		2390.000	32.71	10.31	43.02	74.00	-30.98	peak			
3		2400.000	38.56	10.32	48.88	74.00	-25.12	peak			
4	*	2402.000	82.09	10.32	92.41	74.00	18.41	peak			
5	Х	2402.000	73.76	10.32	84.08	74.00	10.08	AVG	100	301	

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Page 39 of 52

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
ă	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2480.000	81.05	10.41	91.46	74.00	17.46	peak			
2	Х	2480.000	72.86	10.41	83.27	74.00	9.27	AVG	100		
3		2483.500	34.19	10.41	44.60	74.00	-29.40	peak			
4		2486.543	33.15	10.42	43.57	74.00	-30.43	peak			

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Page 40 of 52

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



No	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
§	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1	*	2480.000	80.82	10.41	91.23	74.00	17.23	peak			
2	Х	2480.000	72.56	10.41	82.97	74.00	8.97	AVG	100	315	
3		2483.500	34.76	10.41	45.17	74.00	-28.83	peak			
4		2486.800	34.22	10.42	44.64	74.00	-29.36	peak			

RESULT: PASS

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 41 of 52

11. 20DB BANDWIDTH

11.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 2. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ 3RBW; Sweep = auto; Detector function = peak
- 3. Set SPA Trace 1 Max hold, then View.

11.2. TEST SET-UP



11.3. LIMITS AND MEASUREMENT RESULTS

		LD: " 78	The salls	-100					
BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT									
		Measure	ement Result						
Applicable Limits		D							
		99%OBW (MHz)	-20dB BW(MHz)	Result					
The state of the s	Low Channel	1.115	1.318	PASS					
N/A	Middle Channel	1.131	1.325	PASS					
	High Channel	1.160	1.356	PASS					


The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.




TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.





TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 44 of 52

12. FCC LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

F	Maximum RF Line Voltage							
Frequency	Q.P.(dBuV)	Average(dBuV)						
150kHz~500kHz	66-56	56-46						
500kHz~5MHz	8 Age 12	46/						
5MHz~30MHz	60	50						

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 45 of 52

12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- The test data of the worst case condition(s) was reported on the Summary Data page.

12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

N/A

Note: The EUT EUT is power supplied by button cell.

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a trp://www.ago.go.tt.com.





APPENDIX A: PHOTOGRAPHS OF TEST SETUP


FCC RADIATED EMISSION TEST SETUP






The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attr://www.agc.gett.com.

Attestation of Global Compliance










The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.




APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT




The results shows if this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by (CC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by (CC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by (CC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by (CC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by (CC, this document cannot be reported except in full with our prior written permission.


Attestation of Global Compliance



FRONT VIEW OF EUT



BACK VIEW OF EUT




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc-gett.com.


Attestation of Global Compliance



LEFT VIEW OF EUT



RIGHT VIEW OF EUT




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.


Attestation of Global Compliance



OPEN VIEW OF EUT



INTERNAL VIEW OF EUT-1




The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission.


Attestation of Global Compliance



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



----END OF REPORT----

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attr://www.agc-gett.com.

Attestation of Global Compliance