

APPLICATION CERTIFICATION FCC Part 15C

On Behalf of
Shenzhen Kingsun Enterprises Co., Ltd.

Flashing Bluetooth Speaker
Model No.: DC-1428

FCC ID: 2AAPK-DC1428

Prepared for : Shenzhen Kingsun Enterprises Co., Ltd.
Address : 25/F, CEC Information Building, Xinwen Rd., Shenzhen,
Guangdong, China

Prepared by : Shenzhen Accurate Technology Co., Ltd.
Address : 1/F., Building A, Changyuan New Material Port, Science & Industry
Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report No. : ATE20190972
Date of Test : July 1-2, 2019
Date of Report : July 3, 2019

TABLE OF CONTENTS

Description	Page
Test Report Certification	
TABLE OF CONTENTS.....	2
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. Accessory and Auxiliary Equipment	5
1.3. Description of Test Facility	6
1.4. Measurement Uncertainty	6
2. MEASURING DEVICE AND TEST EQUIPMENT	7
3. OPERATION OF EUT DURING TESTING	8
3.1. Operating Mode	8
3.2. Configuration and peripherals	8
4. FREQUENCY HOPPING SYSTEM REQUIREMENTS.....	9
4.1. Standard and Limit	9
4.2. EUT Pseudorandom Frequency Hopping Sequence.....	9
5. TEST PROCEDURES AND RESULTS	10
6. 20DB BANDWIDTH TEST.....	11
6.1. Block Diagram of Test Setup.....	11
6.2. The Requirement For Section 15.247(a)(1).....	11
6.3. EUT Configuration on Measurement	11
6.4. Operating Condition of EUT	11
6.5. Test Procedure	11
6.6. Test Result	12
7. CARRIER FREQUENCY SEPARATION TEST.....	16
7.1. Block Diagram of Test Setup.....	16
7.2. The Requirement For Section 15.247(a)(1).....	16
7.3. EUT Configuration on Measurement	16
7.4. Operating Condition of EUT	16
7.5. Test Procedure	17
7.6. Test Result	17
8. NUMBER OF HOPPING FREQUENCY TEST	21
8.1. Block Diagram of Test Setup.....	21
8.2. The Requirement For Section 15.247(a)(1)(iii).....	21
8.3. EUT Configuration on Measurement	21
8.4. Operating Condition of EUT	21
8.5. Test Procedure	21
8.6. Test Result	22
9. DWELL TIME TEST	24
9.1. Block Diagram of Test Setup.....	24
9.2. The Requirement For Section 15.247(a)(1)(iii).....	24
9.3. EUT Configuration on Measurement	24
9.4. Operating Condition of EUT	24
9.5. Test Procedure	24

9.6.	Test Result	25
10.	MAXIMUM PEAK OUTPUT POWER TEST	29
10.1.	Block Diagram of Test Setup.....	29
10.2.	The Requirement For Section 15.247(b)(1).....	29
10.3.	EUT Configuration on Measurement	29
10.4.	Operating Condition of EUT	29
10.5.	Test Procedure	29
10.6.	Test Result	30
11.	RADIATED EMISSION TEST	34
11.1.	Block Diagram of Test Setup.....	34
11.2.	The Limit For Section 15.247(d)	35
11.3.	Restricted bands of operation	36
11.4.	Configuration of EUT on Measurement	36
11.5.	Operating Condition of EUT	37
11.6.	Test Procedure	37
11.7.	Data Sample.....	38
11.8.	The Field Strength of Radiation Emission Measurement Results	38
12.	BAND EDGE COMPLIANCE TEST	51
12.1.	Block Diagram of Test Setup.....	51
12.2.	The Requirement For Section 15.247(d)	51
12.3.	EUT Configuration on Measurement	51
12.4.	Operating Condition of EUT	51
12.5.	Test Procedure	52
12.6.	Test Result	52
13.	AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A) ..	62
13.1.	Block Diagram of Test Setup.....	62
13.2.	Power Line Conducted Emission Measurement Limits.....	63
13.3.	Configuration of EUT on Measurement	63
13.4.	Operating Condition of EUT	63
13.5.	Test Procedure	63
13.6.	Data Sample.....	64
13.7.	Power Line Conducted Emission Measurement Results	64
14.	ANTENNA REQUIREMENT.....	67
14.1.	The Requirement	67
14.2.	Antenna Construction	67

Test Report Certification

Applicant : Shenzhen Kingsun Enterprises Co., Ltd.
Manufacturer : Shenzhen MiaoMiao Digital Technology Co., Ltd
EUT Description : Flashing Bluetooth Speaker
Model No. : DC-1428
Brand Name : n.a.


Measurement Procedure Used:


FCC Rules and Regulations Part 15 Subpart C Section 15.247: 2018
ANSI C63.10: 2013


The device described above is tested by Shenzhen Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and Shenzhen Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Shenzhen Accurate Technology Co., Ltd.

Date of Test : July 1-2, 2019
Date of Report : July 3, 2019

Test Engineer : 
(Frank, Engineer)

Prepared by : 
(Bob Wang, Engineer)

Approved & Authorized Signer : 
(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Model Number	: DC-1428
Bluetooth version	: V 5.0
Frequency Range	: 2402MHz-2480MHz
Number of Channels	: 79
Antenna Gain(Max)	: -0.58dBi
Antenna type	: Integral Antenna
Adapter Input Voltage	: DC 3.7V (Powered by Lithium battery) or DC 5V (Powered by USB port)
Modulation mode	: GFSK, $\pi/4$ DQPSK
Hardware version	: V1.0
Software version	: V1.0
Applicant	: Shenzhen Kingsun Enterprises Co., Ltd.
Address	: 25/F, CEC Information Building, Xinwen Rd., Shenzhen, Guangdong, China
Manufacturer	: Shenzhen MiaoMiao Digital Technology Co., Ltd
Address	: Building 6, No.279, Dabutou Road, Guanlan District, Longhua District, Shenzhen City, Guangdong Province, China

1.2. Accessory and Auxiliary Equipment

Adapter:	Model: BEK-QC-001 INPUT: 120V~60Hz OUTPUT: 5V/1A
----------	--

1.3. Description of Test Facility

EMC Lab	:	Recognition of accreditation by Federal Communications Commission (FCC) The Designation Number is CN1189 The Registration Number is 708358 Listed by Innovation, Science and Economic Development Canada (ISED) The Registration Number is 5077A-2 Accredited by China National Accreditation Service for Conformity Assessment (CNAS) The Registration Number is CNAS L3193 Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01
Name of Firm	:	Shenzhen Accurate Technology Co., Ltd.
Site Location	:	1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

1.4. Measurement Uncertainty

Radiated emission expanded uncertainty (9kHz-30MHz)	:	U=2.66dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	:	U=4.28dB, k=2
Radiated emission expanded uncertainty (1G-18GHz)	:	U=4.98dB, k=2
Radiated emission expanded uncertainty (18G-26.5GHz)	:	U=5.06dB, k=2
Conduction Emission Expanded Uncertainty (Mains ports, 9kHz-30MHz)	:	U=2.72dB, k=2
Conduction Emission Expanded Uncertainty (Telecommunication ports, 150kHz-30MHz)	:	U=2.94dB, k=2
Power disturbance Expanded Uncertainty	:	U=2.92dB, k=2
Harmonic current expanded uncertainty	:	U=0.512%, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 05, 2019	1 Year
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 05, 2019	1 Year
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 05, 2019	1 Year
Pre-Amplifier	Rohde&Schwarz	CBLU1183540-01	3791	Jan. 05, 2019	1 Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 05, 2019	1 Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 05, 2019	1 Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 05, 2019	1 Year
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 05, 2019	1 Year
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 05, 2019	1 Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 05, 2019	1 Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18G-10SS	N/A	Jan. 05, 2019	1 Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2485-2375/2510-60/11SS	N/A	Jan. 05, 2019	1 Year
RF COAXIAL CABLE	SUHNER	N-5m(Frequency range:9KHz-26.5GHz)	NO.3	Jan. 05, 2019	1 Year
RF COAXIAL CABLE	SUHNER	N-5m(Frequency range:9KHz-26.5GHz)	NO.4	Jan. 05, 2019	1 Year
RF COAXIAL CABLE	SUHNER	N-1m(Frequency range:9KHz-26.5GHz)	NO.5	Jan. 05, 2019	1 Year
RF COAXIAL CABLE	SUHNER	N-1m(Frequency range:9KHz-26.5GHz)	NO.6	Jan. 05, 2019	1 Year
Temporary antenna connector	NTGS	14AE	N/A	March 20, 2019	N/A

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: Transmitting mode

Low Channel: 2402MHz


Middle Channel: 2441MHz

High Channel: 2480MHz

Hopping

Note: The equipment under test (EUT) was tested under fully-charged battery.
The Bluetooth has been tested under continuous transmission mode.

3.2.Configuration and peripherals



4. FREQUENCY HOPPING SYSTEM REQUIREMENTS

4.1. Standard and Limit

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

4.2. EUT Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 08, 24, 40, 56, 34, 51, 72, 09, 01, 64, 22, 33, 41, 32, 47, 65, 73, 53, 69, 06, 17, 04, 20, 36, 52, 38, 66, 70, 78, 68, 76, 21, 29, 10, 26, 49, 00, 58, 44, 59, 75, 13, 03, 14, 11, 35, 43, 37, 50, 61, 77, 55, 71, 02, 23, 07, 27, 39, 54, 46, 48, 15, 63, 62, 67, 25, 31, 12, 28, 19, 60, 42, 57, 74, 16, 05, 18, 30, 45, etc.


The system receiving have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

5. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission Test	Compliant
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d) Section 15.209	Radiated Emission Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.203	Antenna Requirement	Compliant

6. 20DB BANDWIDTH TEST

6.1. Block Diagram of Test Setup



(EUT: Flashing Bluetooth Speaker)

6.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

6.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 5.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

6.5. Test Procedure

6.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz.

6.5.3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

6.6. Test Result


Test Lab: Shielding room

Test Engineer: Frank

Channel	Frequency (MHz)	GFSK 20dB Bandwidth (MHz)	$\Pi/4$ -DQPSK 20dB Bandwidth (MHz)	Result
Low	2402	0.062	1.434	Pass
Middle	2441	1.056	1.398	Pass
High	2480	1.098	1.380	Pass


The spectrum analyzer plots are attached as below.

GFSK Mode




Date: 2.JUL.2019 11:38:28

Middle channel



Date: 2.JUL.2019 11:34:59


High channel



Date: 2.JUL.2019 15:46:10


Π/4-DQPSK Mode

Low channel




Date: 2.JUL.2019 11:37:17

Middle channel



Date: 2.JUL.2019 11:35:52


High channel



Date: 2.JUL.2019 11:27:52

7. CARRIER FREQUENCY SEPARATION TEST

7.1. Block Diagram of Test Setup



(EUT: Flashing Bluetooth Speaker)

7.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

7.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 6.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

7.5. Test Procedure

7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz. Adjust Span to 2MHz.

7.5.3. Set the adjacent channel of the EUT Maxhold another trace.

7.5.4. Measurement the channel separation

7.6. Test Result

Test Lab: Shielding room

Test Engineer: Frank

GFSK


Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.002	25KHz or 2/3*20dB bandwidth	PASS
	2403			
Middle	2440	1.008	25KHz or 2/3*20dB bandwidth	PASS
	2441			
High	2479	1.002	25KHz or 2/3*20dB bandwidth	PASS
	2480			

Π/4-DQPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	0.996	25KHz or 2/3*20dB bandwidth	PASS
	2403			
Middle	2440	1.008	25KHz or 2/3*20dB bandwidth	PASS
	2441			
High	2479	1.002	25KHz or 2/3*20dB bandwidth	PASS
	2480			


GFSK Mode

Low channel




Date: 2.JUL.2019 11:41:41

Middle channel



Date: 2.JUL.2019 11:52:17


High channel



Date: 2.JUL.2019 11:54:11


Π/4-DQPSK Mode

Low channel




Date: 2.JUL.2019 11:45:38

Middle channel



Date: 2.JUL.2019 11:49:02


High channel



Date: 2.JUL.2019 11:55:31

8. NUMBER OF HOPPING FREQUENCY TEST

8.1. Block Diagram of Test Setup



(EUT: Flashing Bluetooth Speaker)

8.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

8.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 7.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX (Hopping on) modes measure it.

8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Set the spectrum analyzer as RBW=100 kHz, VBW=300 kHz.

8.5.3. Max hold, view and count how many channel in the band.


8.6.Test Result

Test Lab: Shielding room

Test Engineer: Frank


Total number of hopping channel	Measurement result(CH)	Limit(CH)
	79	≥ 15

Number of hopping channels(GFSK)



Date: 2..JUL.2019 15:24:57


Number of hopping channels($\Pi/4$ -DQPSK)



Date: 2.JUL.2019 15:26:45

9. DWELL TIME TEST

9.1. Block Diagram of Test Setup



(EUT: Flashing Bluetooth Speaker)

9.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

9.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 8.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

9.5. Test Procedure

9.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2. Set center frequency of spectrum analyzer = operating frequency.

9.5.3. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz, Adjust Sweep=5ms, 10ms, 15ms. Get the pulse time.

9.5.4. Repeat above procedures until all frequency measured were complete.

9.6. Test Result

Test Lab: Shielding room

Test Engineer: Frank

GFSK Mode (Worst case)

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.43	137.6	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2 \times 79)) \times 31.6$				
DH3	2441	1.71	273.6	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4 \times 79)) \times 31.6$				
DH5	2441	2.97	36.8	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6 \times 79)) \times 31.6$				

Π/4-DQPSK (Worst case)


Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.44	140.8	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2 \times 79)) \times 31.6$				
DH3	2441	1.72	275.2	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4 \times 79)) \times 31.6$				
DH5	2441	3.00	320.0	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6 \times 79)) \times 31.6$				

Note: We tested GFSK mode and Π/4-DQPSK mode the low, middle and high channel and recorded the worst case data for all test mode.

The spectrum analyzer plots are attached as below.


GFSK Mode

DH1 Middle channel




Date: 2.JUL.2019 15:16:14

DH3 Middle channel



Date: 2.JUL.2019 15:17:08


DH5 Middle channel



Date: 2.JUL.2019 15:17:49


II/4-DQPSK

2DH1 Middle channel




Date: 2.JUL.2019 15:21:57

2DH3 Middle channel



Date: 2.JUL.2019 15:20:51


2DH5 Middle channel



Date: 2.JUL.2019 15:20:02

10. MAXIMUM PEAK OUTPUT POWER TEST

10.1. Block Diagram of Test Setup



(EUT: Flashing Bluetooth Speaker)

10.2. The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

10.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.4. Operating Condition of EUT

10.4.1. Setup the EUT and simulator as shown as Section 9.1.

10.4.2. Turn on the power of all equipment.

10.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

10.5. Test Procedure

10.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

10.5.2. Set RBW of spectrum analyzer to 3MHz and VBW to 10MHz.

10.5.3. Measurement the maximum peak output power.

10.6.Test Result

Test Lab: Shielding room

Test Engineer: Frank

GFSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	-3.78/0.0004	21 / 0.125
Middle	2441	-1.86/0.0007	21 / 0.125
High	2480	-1.49/0.0007	21 / 0.125


II/4-DQPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	-2.19/0.0006	21 / 0.125
Middle	2441	-2.16/0.0006	21 / 0.125
High	2480	-3.99/0.0004	21 / 0.125

The spectrum analyzer plots are attached as below.


GFSK Mode

Low channel




Date: 2.JUL.2019 11:08:31

Middle channel



Date: 2.JUL.2019 11:22:12


High channel



Date: 2.JUL.2019 11:23:22


Π/4-DQPSK Mode

Low channel




Date: 2.JUL.2019 11:10:47

Middle channel



Date: 2.JUL.2019 11:12:19

High channel




Date: 2.JUL.2019 11:25:06

11.RADIATED EMISSION TEST


11.1.Block Diagram of Test Setup

11.1.1.Block diagram of connection between the EUT and peripherals




11.1.2.Semi-Anechoic Chamber Test Setup Diagram


(A)Radiated Emission Test Set-Up, Frequency below 30MHz



(B)Radiated Emission Test Set-Up, Frequency 30MHz-1GHz



(C) Radiated Emission Test Set-Up, Frequency above 1GHz



11.2.The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

11.3.Restricted bands of operation

11.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

11.4.Configuration of EUT on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.5. Operating Condition of EUT

11.5.1. Setup the EUT and simulator as shown as Section 10.1.

11.5.2. Turn on the power of all equipment.

11.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

11.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground(Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground(Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. This EUT was tested in 3 orthogonal positions and the worst case position data was reported.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

11.7.Data Sample

Frequency (MHz)	Reading (dB μ v)	Factor (dB/m)	Result (dB μ v/m)	Limit (dB μ v/m)	Margin (dB)	Remark
X.XX	48.69	-13.35	35.34	46	-10.66	QP

Frequency(MHz) = Emission frequency in MHz

Reading(dB μ v) = Uncorrected Analyzer/Receiver reading

Factor (dB/m) = Antenna factor + Cable Loss – Amplifier gain

Result(dB μ v/m) = Reading(dB μ v) + Factor(dB/m)

Limit (dB μ v/m) = Limit stated in standard

Margin (dB) = Result(dB μ v/m) - Limit (dB μ v/m)

QP = Quasi-peak Reading

Calculation Formula:

Margin(dB) = Result (dB μ V/m)–Limit(dB μ V/m)

Result(dB μ V/m)= Reading(dB μ V)+ Factor(dB/m)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit.

11.8.The Field Strength of Radiation Emission Measurement Results

PASS.

Test Lab: 3m Anechoic chamber

Test Engineer: Frank

Note: 1.We tested GFSK mode, $\Pi/4$ -DQPSK Mode and recorded the worst case data (GFSK mode) for all test mode.

2. Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured. The measurements greater than 20dB below the limit from 9kHz to 30MHz and 18 to 26.5GHz.

The spectrum analyzer plots are attached as below.

Below 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #445

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2402MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Vertical

Power Source: DC 3.7V


Date: 19/07/01/

Time: 13/38/03

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	46.8721	35.08	-25.08	10.00	40.00	-30.00	QP	100	123	
2	72.7203	40.20	-27.60	12.60	40.00	-27.40	QP	100	156	
3	94.9788	38.22	-27.42	10.80	43.50	-32.70	QP	100	198	
4	175.0404	40.21	-26.51	13.70	43.50	-29.80	QP	100	216	
5	295.4623	39.66	-21.39	18.27	46.00	-27.73	QP	100	265	
6	590.3511	40.28	-13.88	26.40	46.00	-19.60	QP	100	316	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #446

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2402MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Horizontal

Power Source: DC 3.7V


Date: 19/07/01/

Time: 13/41/06

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.5270	33.82	-21.32	12.50	40.00	-27.50	QP	200	106	
2	236.7928	40.38	-23.78	16.60	46.00	-29.40	QP	200	165	
3	298.5932	40.58	-21.28	19.30	46.00	-26.70	QP	200	185	
4	354.6912	36.14	-19.14	17.00	46.00	-29.00	QP	200	216	
5	415.4486	34.35	-18.05	16.30	46.00	-29.70	QP	200	265	
6	637.7947	33.20	-12.90	20.30	46.00	-25.70	QP	200	306	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #447

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2441MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Horizontal

Power Source: DC 3.7V


Date: 19/07/01/

Time: 13/42/50

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	76.9256	34.98	-27.58	7.40	40.00	-32.60	QP	200	136	
2	137.3565	35.29	-27.89	7.40	43.50	-36.10	QP	200	168	
3	236.7928	39.18	-23.78	15.40	46.00	-30.60	QP	200	196	
4	298.5932	41.28	-21.28	20.00	46.00	-26.00	QP	200	215	
5	354.6912	36.24	-19.14	17.10	46.00	-28.90	QP	200	236	
6	548.3600	33.15	-14.85	18.30	46.00	-27.70	QP	200	302	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #448

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2441MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Vertical

Power Source: DC 3.7V


Date: 19/07/01/

Time: 13/44/00

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972





ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #449

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2480MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Vertical

Power Source: DC 3.7V


Date: 19/07/01/

Time: 13/45/05

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	118.0957	37.30	-27.40	9.90	43.50	-33.60	QP	100	123	
2	163.7366	40.38	-26.68	13.70	43.50	-29.80	QP	100	136	
3	193.1366	36.21	-24.81	11.40	43.50	-32.10	QP	100	175	
4	266.8395	37.28	-22.68	14.60	46.00	-31.40	QP	100	196	
5	518.3832	35.04	-15.74	19.30	46.00	-26.70	QP	100	203	
6	658.2854	35.24	-12.44	22.80	46.00	-23.20	QP	100	285	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #450

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2480MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Horizontal

Power Source: DC 3.7V


Date: 19/07/01/

Time: 13/47/09

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	166.0540	37.12	-26.42	10.70	43.50	-32.80	QP	200	136	
2	236.7928	39.88	-23.78	16.10	46.00	-29.90	QP	200	162	
3	298.5932	41.28	-21.28	20.00	46.00	-26.00	QP	200	195	
4	354.6912	39.24	-19.14	20.10	46.00	-25.90	QP	200	215	
5	531.2910	33.17	-15.37	17.80	46.00	-28.20	QP	200	263	
6	662.9276	33.21	-12.31	20.90	46.00	-25.10	QP	200	315	

Above 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #451

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2402MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:13:28

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	99.22	-6.27	92.95			peak	200	126	
2	4804.000	55.92	1.00	56.92	74.00	-17.08	peak	200	136	
3	4804.000	49.20	1.00	50.20	54.00	-3.80	AVG	200	136	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #452

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2402MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Vertical

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:20:27

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	98.23	-6.27	91.96			peak	150	111	
2	4804.000	54.19	1.00	55.19	74.00	-18.81	peak	150	165	
3	4804.000	47.40	1.00	48.40	54.00	-5.60	AVG	150	165	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #453

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2441MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Vertical

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:22:31

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.000	99.17	-6.10	93.07			peak	150	154	
2	4882.000	54.04	1.36	55.40	74.00	-18.60	peak	150	236	
3	4882.000	46.24	1.36	47.60	54.00	-6.40	AVG	150	236	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #454

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2441MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:23:37

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.000	101.21	-6.10	95.11			peak	200	146	
2	4882.000	56.05	1.36	57.40	74.00	-16.60	peak	200	215	
3	4882.000	47.94	1.36	49.30	54.00	-4.70	AVG	200	215	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #455

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2480MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:27:02

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	101.83	-5.90	95.93			peak	200	211	
2	4960.000	56.42	1.68	58.10	74.00	-15.90	peak	200	236	
3	4960.000	48.92	1.68	50.60	54.00	-3.40	AVG	200	236	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #456

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2480MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Vertical

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:30:50

Engineer Signature: Frank

Distance: 3m


Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	98.81	-5.90	92.91			peak	150	26	
2	4960.000	54.01	1.68	55.69	74.00	-18.31	peak	150	185	
3	4960.000	47.02	1.68	48.70	54.00	-5.30	AVG	150	185	

12.BAND EDGE COMPLIANCE TEST

12.1.Block Diagram of Test Setup



(EUT: Flashing Bluetooth Speaker)

12.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

12.3.EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

12.4.Operating Condition of EUT

12.4.1.Setup the EUT and simulator as shown as Section 11.1.

12.4.2.Turn on the power of all equipment.

12.4.3.Let the EUT work in TX (Hopping off, Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

12.5. Test Procedure

12.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

12.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz with convenient frequency span including 100 kHz bandwidth from band edge.

12.5.3. The band edges was measured and recorded.

12.6. Test Result

Test Lab: Shielding room


Test Engineer: Frank

Note: Both hopping-on mode and hopping-off mode had been pre-tested, and only the worst case was recorded in the test report.


Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
GFSK Mode		
2400.00	40.57	> 20dBc
2483.50	39.91	> 20dBc
Π/4-DQPSK Mode		
2400.00	39.01	> 20dBc
2483.50	39.23	> 20dBc

The spectrum analyzer plots are attached as below.

GFSK Mode




Date: 2.JUL.2019 12:46:26




Date: 2.JUL.2019 14:18:08

Π/4-DQPSK Mode



Date: 2.JUL.2019 14:07:25



Date: 2.JUL.2019 14:21:06

Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

3. Display the measurement of peak values.

Test Procedure:

The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground(Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

Let the EUT work in TX (Hopping off, Hopping on) modes measure it.

We select 2402MHz, 2480MHz TX frequency to transmit(Hopping off mode).

We select 2402-2480MHz TX frequency to transmit(Hopping on mode).

During the radiated emission test, the spectrum analyzer was set with the following configurations:

- 1.The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
- 2.The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
- 3.All modes of operation were investigated and the worst case (GFSK mode) emissions are reported.

Test Lab: 3m Anechoic chamber

Test Engineer: Frank

Non-hopping mode



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #460

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2402MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Vertical

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:40:18

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	40.56	-6.32	34.24	74.00	-39.76	peak	150	168	
2	2390.000	31.82	-6.32	25.50	54.00	-28.50	AVG	150	168	
3	2400.000	60.04	-6.27	53.77	74.00	-20.23	peak	150	195	
4	2400.000	51.67	-6.27	45.40	54.00	-8.60	AVG	150	195	

Note: Average measurement with peak detection at No.2&4



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #459

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2402MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:35:42

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	40.31	-6.32	33.99	74.00	-40.01	peak	200	163	
2	2390.000	31.52	-6.32	25.20	54.00	-28.80	AVG	200	163	
3	2400.000	56.93	-6.27	50.66	74.00	-23.34	peak	200	245	
4	2400.000	47.87	-6.27	41.60	54.00	-12.40	AVG	200	245	

Note: Average measurement with peak detection at No.2&4



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #458

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2480MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:33:16

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	44.42	-5.89	38.53	74.00	-35.47	peak	200	236	
2	2483.500	35.99	-5.89	30.10	54.00	-23.90	AVG	200	236	
3	2500.000	42.25	-5.81	36.44	74.00	-37.56	peak	200	196	
4	2500.000	33.81	-5.81	28.00	54.00	-26.00	AVG	200	196	

Note: Average measurement with peak detection at No.2&4



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #457

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: TX 2480MHz

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Vertical

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:32:05

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	43.90	-5.89	38.01	74.00	-35.99	peak	150	186	
2	2483.500	34.89	-5.89	29.00	54.00	-25.00	AVG	150	186	
3	2500.000	41.94	-5.81	36.13	74.00	-37.87	peak	150	265	
4	2500.000	32.91	-5.81	27.10	54.00	-26.90	AVG	150	265	

Note: Average measurement with peak detection at No.2&4

Hopping mode



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #462

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: HOPPING

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Vertical

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:44:01

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	42.02	-6.32	35.70	74.00	-38.30	peak	150	125	
2	2390.000	33.62	-6.32	27.30	54.00	-26.70	AVG	150	125	
3	2400.000	58.56	-6.27	52.29	74.00	-21.71	peak	150	165	
4	2400.000	49.27	-6.27	43.00	54.00	-11.00	AVG	150	165	
5	2483.500	47.68	-5.89	41.79	74.00	-32.21	peak	150	185	
6	2483.500	37.59	-5.89	31.70	54.00	-22.30	AVG	150	185	
7	2500.000	42.95	-5.81	37.14	74.00	-36.86	peak	150	236	
8	2500.000	33.21	-5.81	27.40	54.00	-26.60	AVG	150	236	

Note: Average measurement with peak detection at No.2&4&6&8



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #461

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Flashing Bluetooth Speaker

Mode: HOPPING

Model: DC-1428

Manufacturer: MiaoMiao Digital

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2019/07/01

Time: 15:43:23

Engineer Signature: Frank

Distance: 3m

Note: Report NO.:ATE20190972



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	41.85	-6.32	35.53	74.00	-38.47	peak	200	136	
2	2390.000	32.82	-6.32	26.50	54.00	-27.50	AVG	200	136	
3	2400.000	56.56	-6.27	50.29	74.00	-23.71	peak	200	168	
4	2400.000	47.37	-6.27	41.10	54.00	-12.90	AVG	200	168	
5	2483.500	48.18	-5.89	42.29	74.00	-31.71	peak	200	195	
6	2483.500	39.29	-5.89	33.40	54.00	-20.60	AVG	200	195	
7	2500.000	42.22	-5.81	36.41	74.00	-37.59	peak	200	275	
8	2500.000	33.21	-5.81	27.40	54.00	-26.60	AVG	200	275	


Note: Average measurement with peak detection at No.2&4&6&8

13.AC POWER LINE CONDUCTED EMISSION FOR FCC PART

15 SECTION 15.207(A)


13.1.Block Diagram of Test Setup

13.1.1.Block diagram of connection between the EUT and simulators



(EUT: Flashing Bluetooth Speaker)

13.1.2.Test System Setup



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

13.2.Power Line Conducted Emission Measurement Limits

Frequency (MHz)	Limit dB(μ V)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0
NOTE1: The lower limit shall apply at the transition frequencies.		
NOTE2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.		

13.3.Configuration of EUT on Measurement

The equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

13.4.Operating Condition of EUT

13.4.1.Setup the EUT and simulator as shown as Section 12.1.

13.4.2.Turn on the power of all equipment.

13.4.3.Let the EUT work in test mode and measure it.

13.5.Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Measurement. The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

13.6.Data Sample

Frequency (MHz)	Transducer value (dB)	QuasiPeak Level (dBμV)	Average Level (dBμV)	QuasiPeak Limit (dBμV)	Average Limit (dBμV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
X.XX	10.5	51.1	34.2	56.0	46.0	4.9	11.8	Pass

Frequency(MHz) = Emission frequency in MHz

Transducer value(dB) = Insertion loss of LISN + Cable Loss

Level(dBμV) = Quasi-peak Reading/Average Reading + Transducer value

Limit (dBμV) = Limit stated in standard

Margin = Limit (dBμV) - Level (dBμV)

Calculation Formula:

Margin = Limit (dBμV) - Level (dBμV)

13.7.Power Line Conducted Emission Measurement Results

PASS.

Test Lab: Shielding room

Test Engineer: Frank

The frequency range from 150kHz to 30MHz is checked.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.
Emissions attenuated more than 20 dB below the permissible value are not reported.

All data was recorded in the Quasi-peak and average detection mode.

The spectral diagrams are attached as below.


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Flashing Bluetooth Speaker M/N:DC-1428
 Manufacturer: MiaoMiao Digital
 Operating Condition: Charging and operating
 Test Site: 1#Shielding Room
 Operator: Frank
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20190972
 Start of Test: 7/1/2019 / 11:36:09AM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 Average
 150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "ZR-0701-02_fin"

7/1/2019 11:39AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	43.20	10.5	66	22.8	QP	L1	GND
0.610000	40.70	10.6	56	15.3	QP	L1	GND
1.220000	30.90	10.7	56	25.1	QP	L1	GND
4.660000	27.40	10.8	56	28.6	QP	L1	GND
9.610000	35.10	10.9	60	24.9	QP	L1	GND
15.385000	30.20	10.9	60	29.8	QP	L1	GND

MEASUREMENT RESULT: "ZR-0701-02_fin2"

7/1/2019 11:39AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.295000	23.50	10.5	50	26.9	AV	L1	GND
0.610000	36.30	10.6	46	9.7	AV	L1	GND
1.565000	22.60	10.7	46	23.4	AV	L1	GND
2.520000	21.40	10.8	46	24.6	AV	L1	GND
12.340000	20.00	10.9	50	30.0	AV	L1	GND
18.070000	17.00	11.0	50	33.0	AV	L1	GND


ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Flashing Bluetooth Speaker M/N:DC-1428
 Manufacturer: MiaoMiao Digital
 Operating Condition: Charging and operating
 Test Site: 1#Shielding Room
 Operator: Frank
 Test Specification: N 120V/60Hz
 Comment: Report NO.:ATE20190972
 Start of Test: 7/1/2019 / 11:31:56AM

SCAN TABLE: "V 9K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 Average
 150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "ZR-0701-01_fin"

7/1/2019 11:35AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.230000	38.90	10.5	62	23.5	QP	N	GND
0.615000	39.60	10.6	56	16.4	QP	N	GND
1.205000	26.20	10.7	56	29.8	QP	N	GND
2.450000	24.60	10.8	56	31.4	QP	N	GND
10.555000	30.60	10.9	60	29.4	QP	N	GND
20.335000	29.90	11.0	60	30.1	QP	N	GND

MEASUREMENT RESULT: "ZR-0701-01_fin2"

7/1/2019 11:35AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.320000	21.20	10.6	50	28.5	AV	N	GND
0.610000	33.40	10.6	46	12.6	AV	N	GND
1.590000	20.90	10.7	46	25.1	AV	N	GND
2.890000	20.40	10.8	46	25.6	AV	N	GND
11.395000	18.80	10.9	50	31.2	AV	N	GND
17.170000	23.40	10.9	50	26.6	AV	N	GND


14.ANTENNA REQUIREMENT

14.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

14.2.Antenna Construction

Device is equipped with permanent attached antenna, which isn't displaced by other antenna. The Max Antenna gain of EUT is -0.58dBi. Therefore, the equipment complies with the antenna requirement of Section 15.203.



***** End of Test Report *****