

TEST REPORT

Reference No. : WTF15S0831496E
FCC ID : 2AAPV-X620
Applicant : Foshan Xincode Electronics Technology Co., Ltd.
Address : 3rd Floor, 4th Block, Yuxi Industrial Zone, Shi Hu Zhou, Sanshui District, Foshan, Guangdong, China
Manufacturer : The same as above.
Address : The same as above.
Product Name : wireless barcode scanner
Model No. : X-620, X-620D, X-600, X-630A, X-988, X-4600W, X-7200W, X-9700W, GT-730W, GT-750W, X-660, X-9700B, X-620C
Standards : FCC CFR47 Part 15 Section 15.249: 2015
Date of Receipt sample : Aug. 07, 2015
Date of Test : Aug. 08 – Dec. 16, 2015
Date of Issue : Dec. 16, 2015
Test Result : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.


Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China
Tel :+86-755-83551033
Fax:+86-755-83552400

Compiled by:



Zero Zhou / Test Engineer

Approved by:



Philo Zhong / Manager

2 Test Summary

| Test Items | Test Requirement | Result |
|--------------------------|----------------------------------|--------|
| Conducted Emissions | 15.207 | PASS |
| Radiated Emission | 15.249(a) 15.209 15.205(a) | PASS |
| Periodic Operation | 15.35(c) | PASS |
| Outside of Band Emission | 15.249 15.205 15.209 | PASS |
| 20dB Bandwidth | 15:215(c) | PASS |
| Antenna Requirement | 15.203 | PASS |

3 Contents

| | Page |
|-----------------------------------------------------------------------|-----------|
| 1 COVER PAGE | 1 |
| 2 TEST SUMMARY | 2 |
| 3 CONTENTS | 3 |
| 4 GENERAL INFORMATION | 4 |
| 4.1 GENERAL DESCRIPTION OF E.U.T. | 4 |
| 4.2 DETAILS OF E.U.T. | 4 |
| 4.3 TEST FACILITY | 4 |
| 5 EQUIPMENT USED DURING TEST | 5 |
| 5.1 EQUIPMENTS LIST | 5 |
| 5.2 DESCRIPTION OF SUPPORT UNITS | 5 |
| 5.3 MEASUREMENT UNCERTAINTY | 5 |
| 5.4 TEST EQUIPMENT CALIBRATION | 5 |
| 6 CONDUCTED EMISSION | 6 |
| 6.1 E.U.T. OPERATION | 6 |
| 6.2 EUT SETUP | 6 |
| 6.3 MEASUREMENT DESCRIPTION | 6 |
| 6.4 TEST RESULT | 7 |
| 7 RADIATION EMISSION TEST | 9 |
| 7.1 EUT OPERATION | 9 |
| 7.2 TEST SETUP | 10 |
| 7.3 SPECTRUM ANALYZER SETUP | 11 |
| 7.4 TEST PROCEDURE | 12 |
| 7.5 TEST RESULT | 13 |
| 8 PERIODIC OPERATION | 16 |
| 9 OUTSIDE OF BAND EMISSION | 18 |
| 9.1 TEST PROCEDURE | 18 |
| 9.2 TEST RESULT | 18 |
| 10 20 DB BANDWIDTH MEASUREMENT | 20 |
| 10.1 TEST PROCEDURE | 20 |
| 10.2 TEST RESULT | 20 |
| 11 ANTENNA REQUIREMENT | 22 |
| 12 PHOTOGRAPHS- MODEL X-620 TEST SETUP | 23 |
| 12.1 PHOTOGRAPH – CONDUCTED EMISSION TEST SETUP AT TEST SITE 1# | 23 |
| 12.2 RADIATION EMISSION | 23 |
| 13 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS | 25 |
| 13.1 MODEL X-620- EXTERNAL PHOTOS | 25 |
| 13.2 MODEL X-620- INTERNAL PHOTOS | 28 |

4 General Information

4.1 General Description of E.U.T.

| | |
|-----------------------|-----------------------------------------------------------------------------------------------------------------|
| Product Name | : wireless barcode scanner |
| Model No. | : X-620, X-620D, X-600, X-630A, X-988, X-4600W, X-7200W, X-9700W, GT-730W, GT-750W, X-660, X-9700B, X-620C |
| Model Differences | :All the models are the same circuit and RF module, There only difference is product appearance and model name. |
| Type of Modulation | : GFSK |
| Frequency Range | : 2402-2478MHz |
| The Lowest Oscillator | : 12MHz |
| Antenna installation | : whip antenna |
| Remark | :The test sample model is X-620. |

4.2 Details of E.U.T.

| | |
|----------------|------------------------------|
| Technical Data | : DC 3.7V, 700mAh by battery |
|----------------|------------------------------|

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **IC – Registration No.:7760A-1**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A-1, Oct 15, 2015.

- **FCC Test Site 1#– Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

- **FCC Test Site 2#– Registration No.: 328995**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014.

4.3.1 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

| Test mode | Lower channel | Middle channel | Upper channel |
|--------------|---------------|----------------|---------------|
| Transmitting | 2402MHz | 2440MHz | 2478MHz |

5 Equipment Used during Test

5.1 Equipments List

| Conducted Emissions Test Site 1# | | | | | | |
|----------------------------------------|----------------------------|----------------------|---------------|----------------|-----------------------|----------------------|
| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Calibration Date | Calibration Due Date |
| 1. | EMI Test Receiver | R&S | ESCI | 100947 | Sep.15,2015 | Sep.14,2016 |
| 2. | LISN | R&S | ENV216 | 101215 | Sep.15,2015 | Sep.14,2016 |
| 3. | Cable | Top | TYPE16(3.5 M) | - | Sep.15,2015 | Sep.14,2016 |
| 3m Semi-anechoic Chamber for Radiation | | | | | | |
| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Calibration Date | Calibration Due Date |
| 1 | EMC Analyzer | Agilent | E7405A | MY4511494 3 | Sep.15,2015 | Sep.14,2016 |
| 2 | Active Loop Antenna | Beijing Dazhi | ZN30900A | - | Sep.15,2015 | Sep.14,2016 |
| 3 | Trilog Broadband Antenna | SCHWARZBECK | VULB9163 | 336 | Apr.19,2015 | Apr.18,2016 |
| 4 | Coaxial Cable (below 1GHz) | Top | TYPE16(13M) | - | Sep.15,2015 | Sep.14,2016 |
| 5 | Broad-band Horn Antenna | SCHWARZBECK | BBHA 9120 D | 667 | Apr.19,2015 | Apr.18,2016 |
| 6 | Broad-band Horn Antenna | SCHWARZBECK | BBHA 9170 | 335 | Apr.19,2015 | Apr.18,2016 |
| 7 | Broadband Preamplifier | COMPLIANCE DIRECTION | PAP-1G18 | 2004 | Mar.17,2015 | Mar.16,2016 |
| 8 | Coaxial Cable (above 1GHz) | Top | 25MHz-18GHz | EW02014-7 | Apr.10,2015 | Apr.09,2016 |

5.2 Description of Support Units

| Equipment | Manufacturer | Model No. |
|-------------|--------------|-----------|
| MacBook Air | Apple | A1465 |

5.3 Measurement Uncertainty

| Parameter | Uncertainty |
|----------------------------------|------------------------------------------------|
| Radio Frequency | $\pm 1 \times 10^{-6}$ |
| RF Power | ± 1.0 dB |
| RF Power Density | ± 2.2 dB |
| Radiated Spurious Emissions test | ± 5.03 dB (Bilog antenna 30M~1000MHz) |
| | ± 5.47 dB (Horn antenna 1000M~25000MHz) |

5.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

6 Conducted Emission

| | |
|-------------------|------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC CFR 47 Part 15 Section 15.207 |
| Test Method: | ANSI C63.4:2003 |
| Test Result: | PASS |
| Frequency Range: | 150kHz to 30MHz |
| Class/Severity: | Class B |
| Limit: | 66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz |
| Detector: | Peak for pre-scan (9kHz Resolution Bandwidth) |

6.1 E.U.T. Operation

Operating Environment :


| | |
|-----------------------|----------|
| Temperature: | 25.5 °C |
| Humidity: | 51 % RH |
| Atmospheric Pressure: | 101.2kPa |

EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.

6.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.4:2003.




6.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


6.4 Test Result

Live line:



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit dBuV | Margin (dB) | Detector | Remark |
|-----|----------------|-------------------|----------------|------------------|---------------|----------------|----------|--------|
| 1 | 0.1539 | 35.35 | 11.18 | 46.53 | 65.78 | -19.25 | QP | |
| 2 | 0.1539 | 21.07 | 11.18 | 32.25 | 55.78 | -23.53 | AVG | |
| 3 | 0.3980 | 26.43 | 11.31 | 37.74 | 57.89 | -20.15 | QP | |
| 4 | 0.3980 | 15.47 | 11.31 | 26.78 | 47.89 | -21.11 | AVG | |
| 5 | 0.6580 | 26.08 | 11.33 | 37.41 | 56.00 | -18.59 | QP | |
| 6 | 0.6580 | 13.92 | 11.33 | 25.25 | 46.00 | -20.75 | AVG | |
| 7 | 1.4700 | 24.90 | 11.19 | 36.09 | 56.00 | -19.91 | QP | |
| 8 | 1.4700 | 13.79 | 11.19 | 24.98 | 46.00 | -21.02 | AVG | |
| 9 | 2.2820 | 22.98 | 11.20 | 34.18 | 56.00 | -21.82 | QP | |
| 10 | 2.2820 | 11.20 | 11.20 | 22.40 | 46.00 | -23.60 | AVG | |
| 11 | 3.0059 | 21.35 | 11.21 | 32.56 | 56.00 | -23.44 | QP | |
| 12 | 3.0059 | 9.98 | 11.21 | 21.19 | 46.00 | -24.81 | AVG | |

Neutral line:



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit dBuV | Margin (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|------------|-------------|----------|--------|
| 1 | 0.1539 | 35.35 | 11.18 | 46.53 | 65.78 | -19.25 | QP | |
| 2 | 0.1539 | 21.07 | 11.18 | 32.25 | 55.78 | -23.53 | AVG | |
| 3 | 0.4060 | 28.43 | 11.31 | 39.74 | 57.73 | -17.99 | QP | |
| 4 | 0.4060 | 17.55 | 11.31 | 28.86 | 47.73 | -18.87 | AVG | |
| 5 | 0.6820 | 27.07 | 11.34 | 38.41 | 56.00 | -17.59 | QP | |
| 6 | 0.6820 | 15.36 | 11.34 | 26.70 | 46.00 | -19.30 | AVG | |
| 7 | 1.5339 | 26.72 | 11.19 | 37.91 | 56.00 | -18.09 | QP | |
| 8 | 1.5339 | 16.72 | 11.19 | 27.91 | 46.00 | -18.09 | AVG | |
| 9 | 2.8540 | 23.35 | 11.21 | 34.56 | 56.00 | -21.44 | QP | |
| 10 | 2.8540 | 13.18 | 11.21 | 24.39 | 46.00 | -21.61 | AVG | |
| 11 | 5.8460 | 22.68 | 11.25 | 33.93 | 60.00 | -26.07 | QP | |
| 12 | 5.8460 | 11.39 | 11.25 | 22.64 | 50.00 | -27.36 | AVG | |

7 Radiation Emission Test

Test Requirement: FCC Part15 Paragraph 15.249&15.209&15.205

Test Method: ANSI 63.4: 2003

Measurement Distance: 3m

Test Result: PASS

15.249(a)Limit:

| Fundamental frequency | Field strength of fundamental | | Field strength of harmonics | |
|-----------------------|-------------------------------|--------|-----------------------------|--------|
| | mV/m | dBuV/m | uV/m | dBuV/m |
| 902-928 MHz | 50 | 94 | 500 | 54 |
| 2400-2483.5 MHz | 50 | 94 | 500 | 54 |
| 5725-5875 MHz | 50 | 94 | 500 | 54 |
| 24.0-24.25 GHz | 250 | 108 | 2500 | 68 |

15.209 Limit:

| Frequency (MHz) | Field Strength | | Field Strength Limit at 3m Measurement Dist | |
|--------------------|----------------|-----------------|---------------------------------------------|--------------------------------|
| | uV/m | Distance (m) | uV/m | dBuV/m |
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 | 10000 * 2400/F(kHz) | $20\log^{(2400/F(kHz))} + 80$ |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 | 100 * 24000/F(kHz) | $20\log^{(24000/F(kHz))} + 40$ |
| 1.705 ~ 30 | 30 | 30 | 100 * 30 | $20\log^{(30)} + 40$ |
| 30 ~ 88 | 100 | 3 | 100 | $20\log^{(100)}$ |
| 88 ~ 216 | 150 | 3 | 150 | $20\log^{(150)}$ |
| 216 ~ 960 | 200 | 3 | 200 | $20\log^{(200)}$ |
| Above 960 | 500 | 3 | 500 | $20\log^{(500)}$ |

Note: RF Voltage(dBuV)=20 log₁₀ RF Voltage(uV)

7.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 51.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4: 2003.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Below 30MHz

Sweep SpeedAuto
 IF Bandwidth10kHz
 Video Bandwidth10kHz
 Resolution Bandwidth10kHz

30MHz ~ 1GHz

Sweep SpeedAuto
 DetectorPK
 Resolution Bandwidth100kHz
 Video Bandwidth300kHz

Above 1GHz

Sweep SpeedAuto
 DetectorPK
 Resolution Bandwidth1MHz
 Video Bandwidth3MHz
 DetectorAve.
 Resolution Bandwidth1MHz
 Video Bandwidth10Hz

7.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

7.5 Test Result

Test Frequency :12MHz~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 18GHz

Test Mode: Low channel Transmitting

| Frequency | Receiver Reading (PK) | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude (PK) | FCC Part 15.249/209/205 | |
|-----------|-----------------------|------------------|------------|-------|------------------|--------------------------|-------------------------|--------|
| | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dBμV) | Degree | (m) | (H/V) | (dB) | (dBμV/m) | (dBμV/m) | (dB) |
| 2402.00 | 87.36 | 356 | 1.8 | H | -13.08 | 74.28 | 114.00 | -39.72 |
| 2402.00 | 98.24 | 87 | 1.7 | V | -13.08 | 85.16 | 114.00 | -28.84 |
| 4804.00 | 51.36 | 89 | 1.9 | H | 0.09 | 51.45 | 74.00 | -22.55 |
| 4804.00 | 42.36 | 127 | 1.0 | V | 0.09 | 42.45 | 74.00 | -31.55 |
| 7206.00 | 50.14 | 166 | 1.2 | H | 3.01 | 53.15 | 74.00 | -20.85 |
| 7206.00 | 46.98 | 127 | 1.6 | V | 3.01 | 49.99 | 74.00 | -24.01 |
| 2484.37 | 52.65 | 150 | 1.7 | H | -13.08 | 39.57 | 74.00 | -34.43 |
| 2484.37 | 45.41 | 219 | 1.6 | V | -13.08 | 32.33 | 74.00 | -41.67 |
| 2389.80 | 50.28 | 102 | 1.2 | H | -13.14 | 37.14 | 74.00 | -36.86 |
| 2389.80 | 45.12 | 327 | 1.4 | V | -13.14 | 31.98 | 74.00 | -42.02 |

AV = Peak +20Log10(duty cycle) =Peak+(-13.57)[refer to section 8 for more detail]

| Frequency | PK | RX Antenna Polar | Duty cycle Factor | Calculated AV | FCC Part 15.249/209/205 | |
|-----------|----------|------------------|-------------------|---------------|-------------------------|--------|
| | | | | | Limit | Margin |
| (MHz) | (dBμV/m) | (H/V) | (dB) | (dBμV/m) | (dBμV/m) | (dB) |
| 2402.00 | 74.28 | H | -13.57 | 60.71 | 94.00 | -33.29 |
| 2402.00 | 85.16 | V | -13.57 | 71.59 | 94.00 | -22.41 |
| 4804.00 | 51.45 | H | -13.57 | 37.88 | 54.00 | -16.12 |
| 4804.00 | 42.45 | V | -13.57 | 28.88 | 54.00 | -25.12 |
| 7206.00 | 53.15 | H | -13.57 | 39.58 | 54.00 | -14.42 |
| 7206.00 | 19.99 | V | -13.57 | 6.42 | 54.00 | -47.58 |
| 2484.37 | 39.57 | H | -13.57 | 26.00 | 54.00 | -28.00 |
| 2484.37 | 32.33 | V | -13.57 | 18.76 | 54.00 | -35.24 |
| 2389.80 | 37.14 | H | -13.57 | 23.57 | 54.00 | -30.43 |
| 2389.80 | 31.98 | V | -13.57 | 18.41 | 54.00 | -35.59 |

Test Mode: Middle channel Transmitting

| Frequency | Receiver Reading (PK) | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude (PK) | FCC Part 15.249/209/205 | |
|-----------|-----------------------|------------------|------------|-------|------------------|--------------------------|-------------------------|--------|
| | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dBμV) | Degree | (m) | (H/V) | (dB) | (dBμV/m) | (dBμV/m) | (dB) |
| 2440.00 | 86.54 | 107 | 1.9 | H | -13.12 | 73.42 | 114.00 | -40.58 |
| 2440.00 | 98.74 | 252 | 1.5 | V | -13.12 | 85.62 | 114.00 | -28.38 |
| 4880.00 | 50.23 | 170 | 1.2 | H | 0.12 | 50.35 | 74.00 | -23.65 |
| 4880.00 | 43.39 | 291 | 1.6 | V | 0.12 | 43.51 | 74.00 | -30.49 |
| 7320.00 | 51.47 | 276 | 1.7 | H | 3.06 | 54.53 | 74.00 | -19.47 |
| 7320.00 | 46.97 | 158 | 1.1 | V | 3.06 | 50.03 | 74.00 | -23.97 |
| 2483.75 | 51.25 | 107 | 1.4 | H | -13.08 | 38.17 | 74.00 | -35.83 |
| 2483.75 | 44.17 | 63 | 1.8 | V | -13.08 | 31.09 | 74.00 | -42.91 |
| 2389.60 | 51.04 | 72 | 2.0 | H | -13.14 | 37.90 | 74.00 | -36.10 |
| 2389.60 | 44.36 | 350 | 1.4 | V | -13.14 | 31.22 | 74.00 | -42.78 |

AV = Peak +20Log10(duty cycle) =Peak+(-13.15)[refer to section 8 for more detail]

| Frequency | PK | RX Antenna Polar | Duty cycle Factor | Calculated AV | FCC Part 15.249/209/205 | |
|-----------|----------|------------------|-------------------|---------------|-------------------------|--------|
| | | | | | Limit | Margin |
| (MHz) | (dBμV/m) | (H/V) | (dB) | (dBμV/m) | (dBμV/m) | (dB) |
| 2440.00 | 73.42 | H | -13.15 | 60.27 | 94.00 | -33.73 |
| 2440.00 | 85.62 | V | -13.15 | 72.47 | 94.00 | -21.53 |
| 4880.00 | 50.35 | H | -13.15 | 37.20 | 54.00 | -16.80 |
| 4880.00 | 43.51 | V | -13.15 | 30.36 | 54.00 | -23.64 |
| 7320.00 | 54.53 | H | -13.15 | 41.38 | 54.00 | -12.62 |
| 7320.00 | 50.03 | V | -13.15 | 36.88 | 54.00 | -17.12 |
| 2483.75 | 38.17 | H | -13.15 | 25.02 | 54.00 | -28.98 |
| 2483.75 | 31.09 | V | -13.15 | 17.94 | 54.00 | -36.06 |
| 2389.60 | 37.90 | H | -13.15 | 24.75 | 54.00 | -29.25 |
| 2389.60 | 31.22 | V | -13.15 | 18.07 | 54.00 | -35.93 |

Test Mode: High channel Transmitting

| Frequency | Receiver Reading (PK) | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude (PK) | FCC Part 15.249/209/205 | |
|-----------|-----------------------|------------------|------------|-------|------------------|--------------------------|-------------------------|--------|
| | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dBμV) | Degree | (m) | (H/V) | (dB) | (dBμV/m) | (dBμV/m) | (dB) |
| 2478.00 | 85.97 | 7 | 1.0 | H | -8.54 | 77.43 | 114.00 | -36.57 |
| 2478.00 | 94.52 | 231 | 1.1 | V | -8.54 | 85.98 | 114.00 | -28.02 |
| 4956.00 | 51.34 | 104 | 1.9 | H | 0.24 | 51.58 | 74.00 | -22.42 |
| 4956.00 | 42.64 | 232 | 1.7 | V | 0.24 | 42.88 | 74.00 | -31.12 |
| 7434.00 | 52.71 | 95 | 1.3 | H | 3.13 | 55.84 | 74.00 | -18.16 |
| 7434.00 | 45.06 | 291 | 2.0 | V | 3.13 | 48.19 | 74.00 | -25.81 |
| 2483.79 | 52.28 | 210 | 1.5 | H | -13.08 | 39.20 | 74.00 | -34.80 |
| 2483.79 | 43.67 | 41 | 1.5 | V | -13.08 | 30.59 | 74.00 | -43.41 |
| 2389.38 | 51.62 | 140 | 1.4 | H | -13.14 | 38.48 | 74.00 | -35.52 |
| 2389.38 | 43.99 | 70 | 1.5 | V | -13.14 | 30.85 | 74.00 | -43.15 |

AV = Peak +20Log10(duty cycle)=Peak+(-14.50) [refer to section 8 for more detail]

| Frequency | PK | RX Antenna Polar | Duty cycle Factor | Calculated AV | FCC Part 15.249/209/205 | |
|-----------|----------|------------------|-------------------|---------------|-------------------------|--------|
| | | | | | Limit | Margin |
| (MHz) | (dBμV/m) | (H/V) | (dB) | (dBμV/m) | (dBμV/m) | (dB) |
| 2478.00 | 77.43 | H | -14.50 | 62.93 | 94.00 | -31.07 |
| 2478.00 | 85.98 | V | -14.50 | 71.48 | 94.00 | -22.52 |
| 4956.00 | 51.58 | H | -14.50 | 37.08 | 54.00 | -16.92 |
| 4956.00 | 42.88 | V | -14.50 | 28.38 | 54.00 | -25.62 |
| 7434.00 | 55.84 | H | -14.50 | 41.34 | 54.00 | -12.66 |
| 7434.00 | 48.19 | V | -14.50 | 33.69 | 54.00 | -20.31 |
| 2483.79 | 39.20 | H | -14.50 | 24.70 | 54.00 | -29.30 |
| 2483.79 | 30.59 | V | -14.50 | 16.09 | 54.00 | -37.91 |
| 2389.38 | 38.48 | H | -14.50 | 23.98 | 54.00 | -30.02 |
| 2389.38 | 30.85 | V | -14.50 | 16.35 | 54.00 | -37.65 |

Test Frequency :From 18GHz to 25GHz

The measurements were more than 20 dB below the limit and not reported.

8 Periodic Operation

The duty cycle was determined by the following equation:


To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion



Duty Cycle(%)=Total On interval in a complete pulse train/ Length of a complete pulse train * %

Duty Cycle Correction Factor(dB)=20 * Log₁₀(Duty Cycle)

| Test Channel | Low Channel | Middle Channel | High Channel |
|----------------------------------------------|-------------|----------------|--------------|
| Total transmission time(us) | 76.8 | 81.6 | 69.6 |
| Length of a complete transmission period(us) | 367.2 | 370.8 | 369.6 |
| Duty Cycle(%) | 20.92 | 22.01 | 18.83 |
| Duty Cycle Correction Factor(dB) | -13.57 | -13.15 | -14.50 |

Refer to the duty cycle plot (as below)





9 Outside of Band Emission

| | |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 15.249(d):Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation. |
| Test Method: | ANSI C63.4:2003 |
| Test Mode: | Transmitting |


9.1 Test Procedure


Refer to section 7.4 of this test report.

9.2 Test Result

Test plots

Left band





10 20 dB Bandwidth Measurement

Test Requirement:

FCC CFR47 Part 15 Section 15.215(c)

Test Method:

ANSI C63.4:2003

Test Mode:

Transmitting

10.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz



10.2 Test Result

| Test Channel | Bandwidth |
|--------------|-----------|
| low | 1.627MHz |
| Middle | 1.627MHz |
| high | 1.627MHz |

Test plots

Low Channel





11 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has a whip antenna, fulfil the requirement of this section.


12 Photographs- Model X-620 Test Setup

12.1 Photograph – Conducted Emission Test Setup at Test Site 1#




12.2 Radiation Emission

Test frequency 12MHz to 30MHz at test site 2#



Test frequency from 30MHz to 1GHz at test site 2#



Test frequency above 1GHz at test site 1#



13 Photographs - Constructional Details


13.1 Model X-620- External Photos














13.2 Model X-620- Internal Photos






















=====End of Report=====