



FCC PART 15.247
EMI MEASUREMENT AND TEST REPORT
For

KBX GROUP

2525 PONCE De Leon Blvd. Suite 300 Coral Gables, FL 333134,
Coral Gables, Florida, United States

FCC ID: 2AAPW-QD-705GR-TV

2014-03-23


| | | | |
|--|--|------------------------|--|
| This Report Concerns: Original Report | | Equipment Type: MID | |
| Test Engineer: | Simon | | |
| Report No.: | TMC13071011 | | |
| Receive EUT Date/Test Date: | 2014-03-12 / 2014-03-12 ~ 2014-03-23 | | |
| Reviewed By: |  Michal Ling | | |
| Prepared By: | Shenzhen WST Testing Technology Co., Ltd. 1F, No.9 Building, TGK Science & Technology Park, Shenzhen Tel: 86-755-86642861 Fax: 86-755-86642996 | | |

TABLE OF CONTENTS

| | | |
|-----------|--|-----------|
| 1. | GENERAL INFORMATION | 4 |
| 1.1. | Report information | 4 |
| 1.2. | Measurement Uncertainty | 4 |
| 2. | PRODUCT DESCRIPTION | 5 |
| 2.1. | EUT Description | 5 |
| 2.2. | Block Diagram of EUT Configuration..... | 6 |
| 2.3. | Support Equipment List | 6 |
| 2.4. | Test Conditions | 6 |
| 3. | TEST RESULTS SUMMARY | 7 |
| | Modifications | 7 |
| 4. | TEST EQUIPMENT USED | 8 |
| 5. | §15.203 - ANTENNA REQUIREMENT | 9 |
| 5.1. | Standard Applicable..... | 9 |
| 5.2. | Antenna Connector Construction..... | 9 |
| 6. | §15.207 - CONDUCTED EMISSIONS..... | 10 |
| 6.1. | Applicable Standard..... | 10 |
| 6.2. | Test Procedure | 10 |
| 6.3. | Conducted Power line Emission Limits..... | 10 |
| 6.4. | Block Diagram of Test Setup..... | 10 |
| 6.5. | Conducted Power Line Test Result..... | 11 |
| 7. | §15.209, §15.205, §15.247(D) - SPURIOUS EMISSIONS | 13 |
| 7.1. | Test Equipment | 13 |
| 7.2. | Test Procedure | 13 |
| 7.3. | Radiated Test Setup | 13 |
| 7.4. | Radiated Emission Limit..... | 15 |
| 7.5. | Radiated Emission Test Result | 16 |
| 7.6. | Conducted Emission Method..... | 24 |
| 7.7. | Test Requirement: | 25 |
| 7.8. | Limit:..... | 25 |
| 7.9. | Test Setup..... | 25 |
| 7.10. | Test Result | 25 |
| 8. | §15.247(A) (2) – 6DB BANDWIDTH TESTING..... | 35 |
| 8.1. | Test Equipment | 35 |
| 8.2. | Test Procedure | 35 |
| 8.3. | Applicable Standard..... | 35 |
| 8.4. | Test Result:Pass. | 35 |
| 9. | §15.247(B) (3) - MAXIMUM PEAK OUTPUT POWER..... | 45 |
| 9.1. | Test Equipment | 45 |
| 9.2. | Test Procedure | 45 |

9.3. Applicable Standard.....45

9.4. Test Result46

10. §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE47

10.1. Test Equipment47

10.2. Test Procedure47

10.3. Applicable Standard.....47

10.4. Test Result47

11. §15.247(E) - POWER SPECTRAL DENSITY55

11.1. Test Equipment55

11.2. Test Procedure55

11.3. Applicable Standard.....55

11.4. Test Result55

1. GENERAL INFORMATION

1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that **WST** approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that **WST** in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, **WST** therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 1.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through **WST**, unless the applicant has authorized **WST** in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of

Shenzhen WST Testing Technology Co., Ltd.

(FCC Registered Test Site Number: 939433) on

1F, No.9 Building, TGK Science & Technology Park, Shenzhen, China

The Test Site is constructed and calibrated to meet the FCC requirements.

1.2. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| No. | Item | Uncertainty |
|-----|-------------------------------|-------------|
| 1 | Conducted Emission Test | +/-1.26dB |
| 2 | RF Power, Conducted | +/-0.21dB |
| 3 | Spurious emissions, conducted | +/-0.34dB |
| 4 | All emissions, radiated (<1G) | +/-3.42dB |
| 5 | All emissions, radiated (>1G) | +/-3.72dB |
| 6 | Temperature | +/-0.5°CdB |
| 7 | Humidity | +/-2% |

2. PRODUCT DESCRIPTION

2.1. EUT Description

| | | |
|----------------------|---|---|
| Applicant | : | KBX GROUP |
| Address | : | 2525 PONCE De Leon Blvd. Suite 300 Coral Gables, FL 333134, Coral Gables,Florida, United States |
| Manufacturer | : | KBX GROUP |
| Address | : | 2525 PONCE De Leon Blvd. Suite 300 Coral Gables, FL 333134, Coral Gables,Florida, United States |
| EUT Description | : | MID |
| Trade Name | : | QUO |
| Modulation | : | 802.11b: DSSS(11/5.5/2/1Mbps) 802.11g: OFDM(54/48/36/24/18/12/9/6Mbps) 802.11n@20M:OFDM (up to 72.2 Mbps) |
| Wi-fi Frequency Band | : | IEEE 802.11b/g/n(20M): 2412-2462MHz |
| Number of Channels | : | IEEE 802.11 b/g/n: 11 Channels |
| Model Number | : | QD-705GR-TV,QD-705WT-TV |
| Power Supply | : | DC 5V By Adapter |
| Antenna gain | : | 0dBi |
| Antenna type | : | Internal Welding permanent Antenna |

The series products, model name: QD-705GR-TV,QD-705WT-TV have the same circuit diagram,PCB layout, software, RF Module, Features and functionality. The differences are the model name, so, we select MID QD-705GR-TV to test.

2.2. Block Diagram of EUT Configuration




Figure 1 EUT Setup

2.3. Support Equipment List

Table 2 Ancillary Equipment

| Name | Model No | S/N | Manufacturer | Used (Y/N) |
|---------|-----------|-----|--------------|------------|
| Adapter | CW0502000 | N/A | KBX | Y |
| | | | | |

2.4. Test Conditions

Temperature: 23~25℃

Relative Humidity: 50~63 %

After the preliminary test, we found to emit the worst emissions and therefore had been tested under operating condition.

IEEE 802.11b:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE 802.11g:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n(20M):

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6.5Mbps data rate were chosen for full testing.

3. TEST RESULTS SUMMARY

FCC 15 Subpart C, Paragraph 15.247 :2013

| FCC Rules | Description of Test | Result |
|---------------------------------|--|------------|
| §15.203 | Antenna Requirement | Compliance |
| §15.207 (a) | AC Line Conducted Emissions | Compliance |
| §15.247(d) | Spurious Emissions at Antenna Port | Compliance |
| §15.205, §15.209, §15.247(d) | Spurious Emissions | Compliance |
| §15.247 (a)(2) | 6 dB Emission Bandwidth | Compliance |
| §15.247(b)(3) | Maximum Peak Output Power | Compliance |
| §15.247(d) | 100 kHz Bandwidth of Frequency Band Edge | Compliance |
| §15.247(e) | Power Spectral Density | Compliance |

Modifications

No modification was made.

4. TEST EQUIPMENT USED

| EQUIPMENT/FACILITIES | MANUFACTURER | MODEL | SERIAL NO. | DATE OF CAL. | CAL. INTERVAL |
|-------------------------------|------------------|----------------------|------------|--------------|---------------|
| 3m Semi-Anechoic Chamber | Chengyu Electron | 9 (L)*6 (W)* 6 (H) | BSL086 | Aug. 23 2013 | 1 Year |
| EMI Test Receiver | Rohde & Schwarz | ESCI3 | BSL001 | Sep. 28 2013 | 1 Year |
| BiConiLog Antenna | Rohde & Schwarz | HL562 | BSL009 | Sep. 28 2013 | 1 Year |
| Double -ridged waveguide horn | Rohde & Schwarz | 9120D | BSL008 | Aug. 27 2013 | 1 Year |
| Horn Antenna | ETS-LINDGREN | 3160 | BSL072 | Dec. 28 2013 | 1 Year |
| Cable | Rohde & Schwarz | N/A | BSL045 | Aug. 27 2013 | 1 Year |
| Cable | Rohde & Schwarz | N/A | BSL046 | Aug. 27 2013 | 1 Year |
| Cable | Rohde & Schwarz | N/A | BSL047 | Aug. 27 2013 | 1 Year |
| Amplifier(100kHz-40G Hz) | R&S | SMR40 | BSL007 | Sep. 28 2013 | 1 Year |
| Band filter | Amindeon | 82346 | BSL049 | Aug. 27 2013 | 1 Year |
| Active Loop Antenna | EMTES | EM15 | BSL011 | Sep. 28 2013 | 1 Year |
| Coaxial Switch | YUANFANG | TA218B | BSL004 | Aug. 27 2013 | 1 Year |
| Spectrum analyzer | Rohde & Schwarz | FSP40 | BSL049 | Sep. 28 2013 | 1 Year |
| Shielding Room | zhongyu Electron | 7.0(L)x3.0(W)x3.0(H) | BSL085 | Sep. 28 2013 | 1 Year |
| EMI Test Receiver | R&S | ESPI | BSL002 | Sep. 28 2013 | 1 Year |
| 10dB Pulse Limita | R&S | N/A | BSL003 | Sep. 28 2013 | 1 Year |
| Coaxial Switch | YUANFANG | TA218B | BSL004 | Aug. 27 2013 | 1 Year |
| LISN | Rohde & Schwarz | ESH3-Y5 | BSL005 | Sep. 28 2013 | 1 Year |
| Coaxial Cable | YUANFANG | N/A | BSL048 | Aug. 27 2013 | 1 Year |
| EMI TEST SOFTWARE | AUDIX | E3 | N/A | N/A | N/A |
| Power Meter | R&S | NRVS | GTS216 | Apr. 6, 2013 | 1 Year |
| Power Sensor | R&S | NRV-Z33 | GTS220 | Apr. 6, 2013 | 1 Year |

5. §15.203 - ANTENNA REQUIREMENT

5.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2. Antenna Connector Construction

The antenna used for this product is a built-in Welding Antenna. The antenna is permanently attached. Refer to the product photo.

5.3. Result

Compliance

6. §15.207 - CONDUCTED EMISSIONS

6.1. Applicable Standard

The specification used was with the FCC Part 15.207 limits.

6.2. Test Procedure


During the conducted emission test, the EUT was connected to the outlet of the LISN. Maximizing procedure was performed on the six (6) highest emissions of the EUT. All data was recorded in the Quasi-peak and average detection mode.

6.3. Conducted Power line Emission Limits

| FCC Part 15 Paragraph 15.207 (dBuV) | | |
|-------------------------------------|---------------|---------------|
| Frequency Range (MHz) | Class A QP/AV | Class B QP/AV |
| 0.15-0.5 | 79/66 | 65-56/56-46 |
| 0.5-5.0 | 73/60 | 56-46 |
| 5.0-3.0 | 73/60 | 60-50 |

Note: In the above table, the tighter limit applies at the band edges.


6.4. Block Diagram of Test Setup



6.5. Conducted Power Line Test Result

Pass.

Link Mode



Condition:


: RBW:9.000KHz VBW:30.000KHz

| | Freq | Level | Limit | Over | Remark | Pol/Phase |
|-------|------|-------|-------|--------|---------|-----------|
| | MHz | dBuV | Line | Limit | dB | |
| 1 max | 0.17 | 45.93 | 54.77 | -8.84 | Average | LINE |
| 2 | 0.23 | 38.93 | 52.35 | -13.42 | Average | LINE |
| 3 | 0.35 | 32.30 | 48.91 | -16.61 | Average | LINE |
| 4 | 0.52 | 31.48 | 46.00 | -14.52 | Average | LINE |
| 5 | 0.93 | 33.06 | 46.00 | -12.94 | Average | LINE |
| 6 | 1.93 | 31.78 | 46.00 | -14.22 | Average | LINE |

Condition:

: RBW:9.000KHz VBW:30.000KHz

| | Freq | Level | Limit | Over | Remark | Pol/Phase |
|-------|------|-------|-------|--------|--------|-----------|
| | MHz | dBuV | Line | Limit | dB | |
| 1 max | 0.15 | 59.69 | 66.00 | -6.31 | QP | LINE |
| 2 | 0.18 | 57.70 | 64.68 | -6.98 | QP | LINE |
| 3 | 0.23 | 48.47 | 62.35 | -13.88 | QP | LINE |
| 4 | 0.30 | 40.57 | 60.37 | -19.80 | QP | LINE |
| 5 | 0.35 | 38.75 | 58.91 | -20.16 | QP | LINE |
| 6 | 1.93 | 38.23 | 56.00 | -17.77 | QP | LINE |



Condition:

: RBW:9.000KHz VBW:30.000KHz

| | Freq | Level | Limit | Over | Remark | Pol/Phase |
|-------|------|-------|-------|--------|---------|-----------|
| | MHz | dBuV | dBuV | dB | | |
| 1 max | 0.18 | 43.55 | 54.68 | -11.13 | Average | NEUTRAL |
| 2 | 0.23 | 38.69 | 52.30 | -13.61 | Average | NEUTRAL |
| 3 | 0.29 | 34.05 | 50.46 | -16.41 | Average | NEUTRAL |
| 4 | 0.70 | 29.53 | 46.00 | -16.47 | Average | NEUTRAL |
| 5 | 0.93 | 29.63 | 46.00 | -16.37 | Average | NEUTRAL |
| 6 | 1.74 | 26.91 | 46.00 | -19.09 | Average | NEUTRAL |

Condition:

: RBW:9.000KHz VBW:30.000KHz

| | Freq | Level | Limit | Over | Remark | Pol/Phase |
|-------|-------|-------|-------|--------|--------|-----------|
| | MHz | dBuV | dBuV | dB | | |
| 1 max | 0.15 | 57.80 | 66.00 | -8.20 | QP | NEUTRAL |
| 2 | 0.18 | 54.71 | 64.68 | -9.97 | QP | NEUTRAL |
| 3 | 0.23 | 47.92 | 62.30 | -14.38 | QP | NEUTRAL |
| 4 | 0.29 | 40.89 | 60.46 | -19.57 | QP | NEUTRAL |
| 5 | 0.35 | 35.06 | 58.91 | -23.85 | QP | NEUTRAL |
| 6 | 0.76 | 32.75 | 56.00 | -23.25 | QP | NEUTRAL |
| 7 | 12.65 | 33.18 | 60.00 | -26.82 | QP | NEUTRAL |

7. §15.209, §15.205, §15.247(D) - Spurious Emissions

7.1. Test Equipment

Please refer to section 5 this report.

7.2. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level.

Calibrated Loop antenna is used as receiving antenna for frequencies below 30MHz, Calibrated Bilog antenna is used as receiving antenna for frequencies between 30 MHz and 1 GHz, Calibrated Horn antenna is used as receiving antenna for frequencies above 1000MHz. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver is set at 9kHz in below 30MHz. and set at 120kHz in 30-1000MHz, and 1MHz in above 1000MHz.


The frequency range from 9kHz to 25GHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Peak detector and Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.


Through three orthogonal axes to determine which attitude and equipment arrangement produces the highest emission relative to the limit. And X direction is worst mode

7.3. Radiated Test Setup


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.4. Radiated Emission Limit

| Frequency (MHz) | Limit | | | The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector. |
|--------------------|---|---|-----------------------------|--|
| | Field Strength of Quasi-peak Value (microvolts/m) | Field Strength of Quasi-peak Value (dB μ V/m) | Measurement distance (m) | |
| 0.009 - 0.490 | 2400/F(kHz) | / | 300 | |
| 0.490 - 1.705 | 24000/F(kHz) | / | 30 | |
| 1.705-30 | 30 | 29.5 | 30 | |
| 30 - 88 | 100 | 40 | 3 | |
| 88 - 216 | 150 | 43.5 | 3 | |
| 216 - 960 | 200 | 46 | 3 | |
| Above 960 | 500 | 54 | 3 | |

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

(2) In the Above Table,the tighter limit applies at the band edges.

(3) Distancce refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

7.5. Radiated Emission Test Result

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst margin of:

-4.98 dB at 7236MHz in the Horizon polarization, with 9KHz to 25 GHz, 3Meters Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

For below 9kHz-30MHz Spurious

| Freq. (MHz) | Emission(dBuV/m) PK / AV | Limits(dBuV/m) PK / AV | Margin (dB) |
|----------------|-----------------------------|---------------------------|----------------|
| - | - | - | - |
| - | - | - | - |


Note:


1. Emissions attenuated more than 20 dB below the permissible value are not reported.

For 30M-1000MHz Spurious

The worst test mode: WiFi Tx 802.11g 2412MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain





Condition : FCC15 CLASS-B 3m HORIZONTAL
 : RBW:120.000KHz VBW:300.000KHz SWT:Auto

| | Freq | Level | Limit | Over | | |
|-------|--------|--------|-------|-------|--------|------------|
| | MHz | dBuV/m | Line | Limit | Remark | Pol/Phase |
| 1 max | 191.75 | 39.46 | 43.50 | -4.04 | QP | HORIZONTAL |
| 2 | 216.02 | 39.97 | 46.00 | -6.03 | QP | HORIZONTAL |
| 3 | 325.60 | 40.84 | 46.00 | -5.16 | QP | HORIZONTAL |
| 4 | 336.04 | 41.25 | 46.00 | -4.75 | QP | HORIZONTAL |
| 5 | 361.71 | 40.58 | 46.00 | -5.42 | QP | HORIZONTAL |
| 6 | 906.48 | 39.84 | 46.00 | -6.16 | QP | HORIZONTAL |

For 1000MHz-25000MHz Spurious**Test mode 802.11b**

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB) | Corrected Amplitude (dBμV/m) | FCC Part 15.247/205/209 | |
|------------------------|-------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
| | Reading (dBμV) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | | | Limit (dBμV/m) | Margin (dB) |
| Low Channel (2412 MHz) | | | | | | | | | |
| 9648.0 | 21.53 | Ave. | 12 | 1.0 | V | 19.29 | 40.82 | 54 | 13.18 |
| 7236.0 | 22.02 | Ave. | 3206 | 1.3 | V | 16.62 | 38.64 | 54 | 15.36 |
| 4824.0 | 25.04 | Ave. | 234 | 1.1 | H | 12.40 | 37.44 | 54 | 16.56 |
| 9648.0 | 34.05 | PK | 12 | 1.0 | V | 19.29 | 53.34 | 74 | 20.66 |
| 4824.0 | 40.68 | PK | 234 | 1.1 | H | 12.40 | 53.08 | 74 | 20.92 |
| 7236.0 | 35.47 | PK | 320 | 1.3 | V | 16.62 | 52.09 | 74 | 21.91 |
| 2365.1 | 24.08 | Ave. | 74 | 1.3 | H | 5.48 | 29.56 | 54 | 24.44 |
| 2485.6 | 22.32 | Ave. | 111 | 1.2 | V | 7.21 | 29.53 | 54 | 24.47 |
| 2338.5 | 22.05 | Ave. | 88 | 1.0 | V | 5.48 | 27.53 | 54 | 26.47 |
| 2485.6 | 36.13 | PK | 1116 | 1.2 | V | 7.21 | 43.34 | 74 | 30.66 |
| 2365.1 | 37.24 | PK | 74 | 1.3 | H | 5.48 | 42.72 | 74 | 31.28 |
| 2338.5 | 35.47 | PK | 88 | 1.0 | V | 5.48 | 40.95 | 74 | 33.05 |

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB) | Corrected Amplitude (dBμV/m) | FCC Part 15.247/205/209 | |
|---------------------------|-------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
| | Reading (dBμV) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | | | Limit (dBμV/m) | Margin (dB) |
| Middle Channel (2437 MHz) | | | | | | | | | |
| 9748.0 | 19.8 | Ave. | 32 | 1.1 | V | 19.40 | 39.2 | 54 | 14.8 |
| 7311.0 | 21.69 | Ave. | 22 | 1.2 | V | 16.49 | 38.18 | 54 | 15.82 |
| 9748.0 | 38.72 | PK | 32 | 1.1 | V | 19.40 | 58.12 | 74 | 15.88 |
| 4874.0 | 24.23 | Ave. | 201 | 1.3 | H | 12.46 | 36.69 | 54 | 17.31 |
| 4874.0 | 41.8 | PK | 201 | 1.3 | H | 12.46 | 54.26 | 74 | 19.74 |
| 7311.0 | 37.23 | PK | 22 | 1.2 | V | 16.49 | 53.72 | 74 | 20.28 |
| 2488.3 | 23.72 | Ave. | 187 | 1.1 | H | 7.21 | 30.93 | 54 | 23.07 |
| 2386.1 | 22.18 | Ave. | 98 | 1.2 | V | 6.13 | 28.31 | 54 | 25.69 |
| 2368.4 | 21.94 | Ave. | 25 | 1.3 | V | 5.48 | 27.42 | 54 | 26.58 |
| 2386.1 | 38.8 | PK | 98 | 1.2 | V | 6.13 | 44.93 | 74 | 29.07 |
| 2488.3 | 36.35 | PK | 187 | 1.1 | H | 7.21 | 43.56 | 74 | 30.44 |
| 2368.4 | 37.13 | PK | 25 | 1.3 | V | 5.48 | 42.61 | 74 | 31.39 |
| High Channel (2462 MHz) | | | | | | | | | |
| 9848.0 | 20.04 | Ave. | 177 | 1.2 | H | 19.39 | 39.43 | 54 | 14.57 |
| 7386.0 | 21.05 | Ave. | 333 | 1.3 | V | 15.91 | 36.96 | 54 | 17.04 |
| 4924.0 | 22.01 | Ave. | 207 | 1.1 | H | 12.50 | 34.51 | 54 | 19.49 |
| 9848.0 | 33.37 | PK | 177 | 1.2 | H | 19.39 | 52.76 | 74 | 21.24 |
| 7386.0 | 36.02 | PK | 333 | 1.3 | V | 15.91 | 51.93 | 74 | 22.07 |
| 4924.0 | 38.69 | PK | 207 | 1.1 | H | 12.50 | 51.19 | 74 | 22.81 |
| 2491.3 | 23.8 | Ave. | 326 | 1.5 | H | 7.21 | 31.01 | 54 | 22.99 |
| 2368.7 | 24.52 | Ave. | 74 | 1.1 | V | 5.48 | 30 | 54 | 24 |
| 2488.5 | 22.75 | Ave. | 11 | 1.3 | V | 7.21 | 29.96 | 54 | 24.04 |
| 2488.5 | 37.13 | PK | 11 | 1.3 | V | 7.21 | 44.34 | 74 | 29.66 |
| 2491.3 | 36.33 | PK | 326 | 1.5 | H | 7.21 | 43.54 | 74 | 30.46 |
| 2368.7 | 36.02 | PK | 74 | 1.1 | V | 5.48 | 41.5 | 74 | 32.5 |

Note:

1. The average measurement was not performed when the peak measured data under the limit of average detection.
2. Emissions attenuated more than 20 dB below the permissible value are not reported.

Test mode 802.11g

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB) | Corrected Amplitude (dBμV/m) | FCC Part 15.247/205/209 | |
|---------------------------|-------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
| | Reading (dBμV) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | | | Limit (dBμV/m) | Margin (dB) |
| Low Channel (2412 MHz) | | | | | | | | | |
| 9648.0 | 23.05 | Ave. | 77 | 1.1 | V | 19.29 | 42.34 | 54 | 11.66 |
| 7236.0 | 20.39 | Ave. | 161 | 1.5 | V | 16.62 | 37.01 | 54 | 16.99 |
| 4824.0 | 22.05 | Ave. | 87 | 1.3 | V | 12.40 | 34.45 | 54 | 19.55 |
| 7236.0 | 36.23 | PK | 161 | 1.5 | V | 16.62 | 52.85 | 74 | 21.15 |
| 9648.0 | 33.21 | PK | 77 | 1.1 | V | 19.29 | 52.5 | 74 | 21.5 |
| 4824.0 | 38.92 | PK | 87 | 1.3 | V | 12.40 | 51.32 | 74 | 22.68 |
| 2353.4 | 24.17 | Ave. | 22 | 1.5 | V | 5.48 | 29.65 | 54 | 24.35 |
| 2485.1 | 22.1 | Ave. | 113 | 1.1 | V | 7.21 | 29.31 | 54 | 24.69 |
| 2344.7 | 22.68 | Ave. | 32 | 1.3 | H | 5.48 | 28.16 | 54 | 25.84 |
| 2344.7 | 38.8 | PK | 32 | 1.3 | H | 5.48 | 44.28 | 74 | 29.72 |
| 2485.1 | 35.42 | PK | 113 | 1.1 | V | 7.21 | 42.63 | 74 | 31.37 |
| 2353.4 | 37.07 | PK | 22 | 1.5 | V | 5.48 | 42.55 | 74 | 31.45 |
| Middle Channel (2437 MHz) | | | | | | | | | |
| 7311.0 | 22.26 | Ave. | 85 | 1.3 | V | 16.49 | 38.75 | 54 | 15.25 |
| 9748.0 | 18.68 | Ave. | 73 | 1.2 | V | 19.40 | 38.08 | 54 | 15.92 |
| 4874.0 | 22.18 | Ave. | 101 | 1.1 | V | 12.46 | 34.64 | 54 | 19.36 |
| 9748.0 | 33.97 | PK | 73 | 1.2 | V | 19.40 | 53.37 | 74 | 20.63 |
| 7311.0 | 36.47 | PK | 85 | 1.3 | V | 16.49 | 52.96 | 74 | 21.04 |
| 2364.5 | 22.92 | Ave. | 71 | 1.3 | V | 5.48 | 28.4 | 54 | 25.6 |
| 4874.0 | 35.8 | PK | 101 | 1.1 | V | 12.46 | 48.26 | 74 | 25.74 |
| 2318.2 | 22.05 | Ave. | 36 | 1.1 | H | 5.48 | 27.53 | 54 | 26.47 |
| 2383.9 | 21.35 | Ave. | 32 | 1.2 | V | 6.13 | 27.48 | 54 | 26.52 |
| 2383.9 | 37.1 | PK | 32 | 1.2 | V | 6.13 | 43.23 | 74 | 30.77 |
| 2364.5 | 37.13 | PK | 71 | 1.3 | V | 5.48 | 42.61 | 74 | 31.39 |
| 2318.2 | 36.16 | PK | 36 | 1.1 | H | 5.48 | 41.64 | 74 | 32.36 |

| Frequency (MHz) | Receiver | Turntable Degree | Rx Antenna | Corrected Factor | Corrected Amplitude | FCC Part 15.247/205/209 |
|--------------------|----------|---------------------|------------|---------------------|------------------------|----------------------------|
|--------------------|----------|---------------------|------------|---------------------|------------------------|----------------------------|

| | Reading (dBμV) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | (dB) | (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-------------------------|-------------------|--------------------------|-----|---------------|----------------|-------|----------|-------------------|----------------|
| High Channel (2462 MHz) | | | | | | | | | |
| 9848.0 | 18.39 | Ave. | 36 | 1.6 | V | 19.39 | 37.78 | 54 | 16.22 |
| 7386.0 | 21.72 | Ave. | 21 | 1.7 | H | 15.91 | 37.63 | 54 | 16.37 |
| 4924.0 | 21.53 | Ave. | 123 | 1.6 | V | 12.50 | 34.03 | 54 | 19.97 |
| 9848.0 | 33.24 | PK | 36 | 1.6 | V | 19.39 | 52.63 | 74 | 21.37 |
| 7386.0 | 34.94 | PK | 21 | 1.7 | H | 15.91 | 50.85 | 74 | 23.15 |
| 2485.6 | 21.49 | Ave. | 101 | 1.4 | H | 7.21 | 28.7 | 54 | 25.3 |
| 2493.5 | 21.23 | Ave. | 33 | 1.3 | V | 7.21 | 28.44 | 54 | 25.56 |
| 4924.0 | 35.8 | PK | 123 | 1.6 | V | 12.50 | 48.3 | 74 | 25.7 |
| 2333.4 | 21.45 | Ave. | 32 | 1.0 | V | 5.48 | 26.93 | 54 | 27.07 |
| 2485.6 | 36.23 | PK | 101 | 1.4 | H | 7.21 | 43.44 | 74 | 30.56 |
| 2493.5 | 35.24 | PK | 33 | 1.3 | V | 7.21 | 42.45 | 74 | 31.55 |
| 2333.4 | 36.51 | PK | 32 | 1.0 | V | 5.48 | 41.99 | 74 | 32.01 |

Note:

1. The average measurement was not performed when the peak measured data under the limit of average detection.
2. Emissions attenuated more than 20 dB below the permissible value are not reported.

Test mode 802.11n(20M)

| Frequency (MHz) | Receiver | Turntable Degree | Rx Antenna | Corrected Factor | Corrected Amplitude | FCC Part 15.247/205/209 |
|--------------------|----------|---------------------|------------|---------------------|------------------------|----------------------------|
|--------------------|----------|---------------------|------------|---------------------|------------------------|----------------------------|

| | Reading (dBμV) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | (dB) | (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|---------------------------|-------------------|--------------------------|-----|---------------|----------------|-------|----------|-------------------|----------------|
| Low Channel (2412 MHz) | | | | | | | | | |
| 2389.5 | 57.62 | PK | 168 | 1.1 | H | 6.13 | 63.75 | 74 | 10.25 |
| 2389.5 | 33.63 | Ave. | 168 | 1.1 | H | 6.13 | 39.76 | 54 | 14.24 |
| 9648.0 | 19.3 | Ave. | 77 | 1.0 | V | 19.28 | 38.58 | 54 | 15.42 |
| 7236.0 | 20.89 | Ave. | 36 | 1.2 | V | 16.62 | 37.51 | 54 | 16.49 |
| 4824.0 | 23.27 | Ave. | 74 | 1.0 | V | 12.40 | 35.67 | 54 | 18.33 |
| 4824.0 | 42.19 | PK | 74 | 1.0 | V | 12.40 | 54.59 | 74 | 19.41 |
| 2492.3 | 24.73 | Ave. | 83 | 1.2 | H | 7.21 | 31.94 | 54 | 22.06 |
| 2492.3 | 44.54 | PK | 83 | 1.2 | H | 7.21 | 51.75 | 74 | 22.25 |
| 9648.0 | 32.44 | PK | 77 | 1.0 | V | 19.28 | 51.72 | 74 | 22.28 |
| 7236.0 | 32.42 | PK | 36 | 1.2 | V | 16.62 | 49.04 | 74 | 24.96 |
| 2316.4 | 18.69 | Ave. | 26 | 1.3 | H | 5.48 | 24.17 | 54 | 29.83 |
| 2316.4 | 32.3 | PK | 26 | 1.3 | H | 5.48 | 37.78 | 74 | 36.22 |
| Middle Channel (2437 MHz) | | | | | | | | | |
| 9748.0 | 19.92 | Ave. | 12 | 1.0 | H | 19.40 | 39.32 | 54 | 14.68 |
| 7311.0 | 18.82 | Ave. | 168 | 1.2 | V | 16.49 | 35.31 | 54 | 18.69 |
| 4874.0 | 40.73 | PK | 132 | 1.3 | V | 12.46 | 53.19 | 74 | 20.81 |
| 4874.0 | 20.44 | Ave. | 132 | 1.3 | V | 12.46 | 32.9 | 54 | 21.1 |
| 9748.0 | 33.3 | PK | 12 | 1.0 | H | 19.40 | 52.7 | 74 | 21.3 |
| 2491.2 | 23.54 | Ave. | 274 | 1.3 | V | 6.81 | 30.35 | 54 | 23.65 |
| 2383.6 | 23.23 | Ave. | 113 | 1.1 | H | 6.13 | 29.36 | 54 | 24.64 |
| 7311.0 | 32.55 | PK | 168 | 1.2 | V | 16.49 | 49.04 | 74 | 24.96 |
| 2331.5 | 20.49 | Ave. | 354 | 1.4 | V | 5.48 | 25.97 | 54 | 28.03 |
| 2491.2 | 36.6 | PK | 274 | 1.3 | V | 6.81 | 43.41 | 74 | 30.59 |
| 2383.6 | 33.52 | PK | 113 | 1.1 | H | 6.13 | 39.65 | 74 | 34.35 |
| 2331.5 | 33.54 | PK | 354 | 1.4 | V | 5.48 | 39.02 | 74 | 34.98 |

| Frequency (MHz) | Receiver | Turntable Degree | Rx Antenna | Corrected Factor | Corrected Amplitude | FCC Part 15.247/205/209 |
|--------------------|----------|---------------------|------------|---------------------|------------------------|----------------------------|
|--------------------|----------|---------------------|------------|---------------------|------------------------|----------------------------|

| | Reading (dB μ V) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | (dB) | (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-------------------------|-------------------------|--------------------------|-----|---------------|----------------|-------|----------------|-------------------------|----------------|
| High Channel (2462 MHz) | | | | | | | | | |
| 2483.7 | 59.74 | PK | 176 | 1.2 | H | 7.21 | 66.95 | 74 | 7.05 |
| 2488.6 | 53.89 | PK | 68 | 1.3 | H | 7.21 | 61.1 | 74 | 12.9 |
| 2483.7 | 33.65 | Ave. | 176 | 1.2 | H | 7.21 | 40.86 | 54 | 13.14 |
| 9848.0 | 20.44 | Ave. | 88 | 1.2 | V | 19.39 | 39.83 | 54 | 14.17 |
| 2488.6 | 30.68 | Ave. | 68 | 1.3 | H | 7.21 | 37.89 | 54 | 16.11 |
| 7386.0 | 20.09 | Ave. | 235 | 1.3 | V | 15.91 | 36 | 54 | 18 |
| 4924.0 | 23.17 | Ave. | 115 | 1.1 | V | 12.50 | 35.67 | 54 | 18.33 |
| 4924.0 | 41.55 | PK | 115 | 1.1 | V | 12.50 | 54.05 | 74 | 19.95 |
| 9848.0 | 33.33 | PK | 88 | 1.2 | V | 19.39 | 52.72 | 74 | 21.28 |
| 2344.6 | 24.53 | Ave. | 138 | 1.1 | H | 5.48 | 30.01 | 54 | 23.99 |
| 7386.0 | 32.59 | PK | 235 | 1.3 | V | 15.91 | 48.5 | 74 | 25.5 |
| 2344.6 | 33.74 | PK | 138 | 1.1 | H | 5.48 | 39.22 | 74 | 34.78 |

7.6. Conducted Emission Method

Please refer to section 5 this report.


7.7. Test Requirement:

FCC Part15 C Section 15.247 (d)

7.8. Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

7.9. Test Setup



7.10. Test Result

For below 9kHz-30MHz Spurious


| Freq. (MHz) | Emission(dBuV/m) PK / AV | Limits(dBuV/m) PK / AV | Margin (dB) |
|----------------|-----------------------------|---------------------------|----------------|
| - | - | - | - |
| - | - | - | - |

Note:


2. Emissions attenuated more than 20 dB below the permissible value are not reported.

Test mode: 802.11b

Lowest channel 30MHz~25GHz





Middle channel 30MHz~25GHz



Highest channel 30MHz~25GHz




| | | | | | | |
|---|---------------|----------------|-----|---------|--------|-------|
|  | Marker 1 [T1] | | RBW | 100 kHz | RF Att | 20 dB |
| | Ref Lvl | -59.53 dBm | VBW | 300 kHz | | |
| | 4.5 dBm | 6.73537074 GHz | SWT | 6.4 s | Unit | dBm |




Test mode: 802.11g

| | |
|----------------|-------------|
| Lowest channel | 30MHz~25GHz |
|----------------|-------------|




Middle channel 30MHz~25GHz




Test mode: 802.11n(20M)


Lowest channel 30MHz~25GHz



Middle channel 30MHz~25GHz



Highest channel 30MHz~25GHz



8. §15.247(A) (2) – 6DB BANDWIDTH TESTING

8.1. Test Equipment

Please refer to Section 5 this report.

8.2. Test Procedure

1. Set EUT in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=100KHz,VBW>=RBW,Span=50MHz,Sweep=auto.
4. Mark the peak frequency and -6dB(upper and lower)frequency.
5. Repeat until all the rest channels are investigated.

8.3. Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.


8.4. Test Result:Pass.

Please refer to the following tables


| Channel | Channel Frequency (MHz) | Data Rate (Mbps) | 6dB Emission Bandwidth (MHz) | FCC Part 15.247 Limit (kHz) |
|------------------|-------------------------|------------------|------------------------------|-----------------------------|
| 802.11b mode | | | | |
| Low | 2412 | 1 | 10.100 | >500 |
| Middle | 2437 | 1 | 10.100 | >500 |
| High | 2462 | 1 | 10.100 | >500 |
| 802.11g mode | | | | |
| Low | 2412 | 6 | 16.513 | >500 |
| Middle | 2437 | 6 | 16.513 | >500 |
| High | 2462 | 6 | 16.513 | >500 |
| 802.11n-20M mode | | | | |
| Low | 2412 | 6.5 | 17.675 | >500 |
| Middle | 2437 | 6.5 | 17.675 | >500 |
| High | 2462 | 6.5 | 17.675 | >500 |

802.11b Mode:


Low Channel



Middle Channel




High Channel




802.11g Mode:

Low Channel



Middle Channel



3.5 dB Offset

▼1 [T1]
-16.47 dBm
2.42876353 GHz

▲1 [T1]
-0.45 dB
16.51302605 MHz

OPB
16.51302605 MHz

▼T1 [T1]
-16.47 dBm
2.42876353 GHz

▼T2 [T1]
-16.92 dBm
2.44527665 GHz

D1 -10.08 dBm

T1

D2 -16.08 dBm

1MAX


1MA

Center 2.437 GHz

2 MHz/


Span 20 MHz

High Channel




802.11n(20M)Mode:


Low Channel



Middle Channel



High Channel



9. §15.247(B) (3) - Maximum Peak Output Power

9.1. Test Equipment

Please refer to Section 4 this report.

9.2. Test Procedure

1. The EUT was directly connected to the power meter

9.3. Applicable Standard

According to §15.247(b) (3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

9.4. Test Result**Pass****802.11b Mode:**

| Channel | Frequency (MHz) | Data Rate (Mbps) | Conducted Power (dBm) | Limit (dBm) |
|---------|-----------------|------------------|-----------------------|-------------|
| Low | 2412 | 1 | 7.96 | 30 |
| Mid | 2437 | 1 | 8.09 | 30 |
| High | 2462 | 1 | 8.41 | 30 |

802.11g Mode:

| Channel | Frequency (MHz) | Data Rate (Mbps) | Conducted Power (dBm) | Limit (dBm) |
|---------|-----------------|------------------|-----------------------|-------------|
| Low | 2412 | 6 | 8.31 | 30 |
| Mid | 2437 | 6 | 8.08 | 30 |
| High | 2462 | 6 | 7.71 | 30 |

802.11n(20M) Mode:

| Channel | Frequency (MHz) | Data Rate (Mbps) | Conducted Power (dBm) | Limit (dBm) |
|---------|-----------------|------------------|-----------------------|-------------|
| Low | 2412 | 6.5 | 6.81 | 30 |
| Mid | 2437 | 6.5 | 7.56 | 30 |
| High | 2462 | 6.5 | 7.79 | 30 |

10. §15.247(D) – 100 KHZ Bandwidth of Frequency Band Edge

10.1.Test Equipment

Please refer to Section 4 this report.

10.2.Test Procedure

- 1, Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2, Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3, Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
Note: For Rdstricted Band
RBW=1MHz
VBW=1 MHz
- 4, Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5, Repeat above procedures until all measured frequencies were complete.

10.3.Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


10.4.Test Result

Pass.


| Channel | Delta Peak to Band Emission (dBc) | \geq Limit (dBc) | Result |
|------------------|-----------------------------------|--------------------|--------|
| 802.11b mode | | | |
| Left-band | 54.66 | 20 | Pass |
| Right-band | 58.39 | 20 | Pass |
| 802.11g mode | | | |
| Left-band | 50.31 | 20 | Pass |
| Right-band | 58.88 | 20 | Pass |
| 802.11n-20M mode | | | |
| Left-band | 52.16 | 20 | Pass |
| Right-band | 57.71 | 20 | Pass |

Please refer to following plots.


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side




802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side



802.11n(20M): Band Edge, Left Side



802.11n(20M): Band Edge, Right Side



11. §15.247(E) - Power Spectral Density

11.1. Test Equipment

Please refer to Section 4 this report.

11.2. Test Procedure

1. Connect EUT test port to spectrum analyzer
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at high, middle and low frequency and measure the conducted band edge spurious separately.


11.3. Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


11.4. Test Result

| Channel | Frequency (MHz) | Data Rate (Mbps) | Correct Power spectral density (dBm) | Limit (dBm) | Result |
|-------------------|-----------------|------------------|--------------------------------------|-------------|--------|
| 802.11b mode | | | | | |
| Low | 2412 | 1 | -17.63 | ≤8 | Pass |
| Middle | 2437 | 1 | -17.92 | ≤8 | Pass |
| High | 2462 | 1 | -17.06 | ≤8 | Pass |
| 802.11g mode | | | | | |
| Low | 2412 | 6 | -23.27 | ≤8 | Pass |
| Middle | 2437 | 6 | -24.77 | ≤8 | Pass |
| High | 2462 | 6 | -25.44 | ≤8 | Pass |
| 802.11n-HT20 mode | | | | | |
| Low | 2412 | 6.5 | -25.91 | ≤8 | Pass |
| Middle | 2437 | 6.5 | -26.77 | ≤8 | Pass |
| High | 2462 | 6.5 | -26.66 | ≤8 | Pass |


Power Spectral Density, 802.11b Low Channel




Power Spectral Density, 802.11b Middle Channel




Power Spectral Density, 802.11b High Channel




Power Spectral Density, 802.11g Low Channel




Power Spectral Density, 802.11g Middle Channel




Power Spectral Density, 802.11g High Channel




Power Spectral Density, 802.11n(20M) Low Channel



Power Spectral Density, 802.11n(20M) Middle Channel



Power Spectral Density, 802.11n(20M) High Channel



***** END OF REPORT *****