



RADIO TEST REPORT

Report No: STS1512109F04

Issued for

KBX GROUP

AVENIDA 1ERA. CALLE B Y C MANZANA 58 FRANCE
FIELD PANAMA Florida United States 32412

Product Name:	WCDMA/GSM MOBILE PHONE
Brand Name:	QUO
Model No.:	QSP-502QM-GD
Series Model:	QSP-502QM-WH,QSP-502QM-BK, QSP-502QM-BL,QSP-502QM-GY, QSP-502QM-GR,QSP-502QM-GN
FCC ID:	2AAPW-QSP-502QM
Test Standard:	FCC Part 15.247

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.
1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





TEST RESULT CERTIFICATION

Applicant's name: KBX GROUP

Address: AVENIDA 1ERA. CALLE B Y C MANZANA 58 FRANCE FIELD
PANAMA Florida United States 32412

Manufacture's Name: KBX GROUP

Address: AVENIDA 1ERA. CALLE B Y C MANZANA 58 FRANCE FIELD
PANAMA Florida United States 32412

Product description

Product name: WCDMA/GSM MOBILE PHONE

Model and/or type reference .: QSP-502QM-GD

Series Model.....: QSP-502QM-WH,QSP-502QM-BK,QSP-502QM-BL,
QSP-502QM-GY,QSP-502QM-GR,QSP-502QM-GN

Standards: FCC Part15.247

Test procedure ANSI C63.10-2013

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test:

Date (s) of performance of tests: 18 Dec. 2015 ~28 Dec. 2015

Date of Issue: 29 Dec. 2015

Test Result.....: **Pass**

Testing Engineer : _____

(Jin Ming)

Technical Manager : _____

(Vita Li)

Authorized Signatory : _____

(Bovey Yang)





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TEST	11
2.4 DESCRIPTION OF SUPPORT UNITS	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3. EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST RESULT	14
3.2 RADIATED EMISSION MEASUREMENT	16
3.2.1 RADIATED EMISSION LIMITS	16
3.2.2 TEST PROCEDURE	17
3.2.3 TEST SETUP	18
3.2.4 EUT OPERATING CONDITIONS	19
3.2.5 TEST RESULT	20
4. CONDUCTED SPURIOUS EMISSIONS	26
4.1 APPLIED PROCEDURES / LIMIT	26
4.2 TEST PROCEDURE	26
4.3 DEVIATION FROM STANDARD	26
4.4 TEST SETUP	26
4.5 EUT OPERATION CONDITIONS	26
4.6 TEST RESULTS	27
5. POWER SPECTRAL DENSITY TEST	39
5.1 APPLIED PROCEDURES / LIMIT	39
5.2 TEST PROCEDURE	39
5.3 DEVIATION FROM STANDARD	39
5.4 TEST SETUP	39
5.5 EUT OPERATION CONDITIONS	39
5.6 TEST RESULTS	40



Table of Contents	Page
6. BANDWIDTH TEST	48
6.1 APPLIED PROCEDURES / LIMIT	48
6.2 TEST PROCEDURE	48
6.3 DEVIATION FROM STANDARD	48
6.4 TEST SETUP	48
6.5 EUT OPERATION CONDITIONS	48
6.6 TEST RESULTS	49
7. PEAK OUTPUT POWER TEST	57
7.1 APPLIED PROCEDURES / LIMIT	57
7.2 TEST PROCEDURE	57
7.3 DEVIATION FROM STANDARD	57
7.4 TEST SETUP	57
7.5 EUT OPERATION CONDITIONS	57
7.6 TEST RESULTS	58
8. ANTENNA REQUIREMENT	59
8.1 STANDARD REQUIREMENT	59
8.2 EUT ANTENNA	59
APPENDIX - PHOTOS OF TEST SETUP	60

**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	29 Dec. 2015	STS1512109F04	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b) (reference KDB 558074 d05 v02. /9.1.2)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Conducted Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China

CNAS Registration No.: L7649;

FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	$\pm 2.88\text{dB}$
2	Conducted Emission (150KHz-30MHz)	$\pm 2.67\text{dB}$
3	RF power,conducted	$\pm 0.70\text{dB}$
4	Spurious emissions,conducted	$\pm 1.19\text{dB}$
5	All emissions,radiated(<1G) 30MHz-200MHz	$\pm 2.83\text{dB}$
6	All emissions,radiated(<1G) 200MHz-1000MHz	$\pm 2.94\text{dB}$
7	All emissions,radiated(>1G)	$\pm 3.03\text{dB}$
8	Temperature	$\pm 0.5^{\circ}\text{C}$
9	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	WCDMA/GSM MOBILE PHONE	
Trade Name	QUO	
Model Name	QSP-502QM-GD	
Series Model	QSP-502QM-WH,QSP-502QM-BK,QSP-502QM-BL, QSP-502QM-GY,QSP-502QM-GR,QSP-502QM-GN	
Model Difference	Only different in model name	
Product Description	The EUT is a WCDMA/GSM MOBILE PHONE	
	Operation Frequency:	802.11b/g/n 20: 2412~2462 MHz 802.11n 40: 2422~2452MHz
	Modulation Type:	CCK/OFDM/DBPSK/DAPSK
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20/40MHz):300/150/144.44/130/ 117/115.56/104/86.67/78/52/6.5Mbps
	Number Of Channel	802.11b/g/n20: 11CH 802.11n 40: 7CH
	Antenna Designation:	Please see Note 3.
	Antenna Gain (dBi)	0 dBi
	Duty cycle	>98%
Channel List	Please refer to the Note 2.	
Ratings	DC 3.7V from battery	
Adapter	Input: AC100-240V, 500mA, 50/60 Hz Output: DC 5V, 1000mA	
Battery	Rated Voltage: 3.7V Capacity :1900mAh	
Hardware version number	--	
Software versioning number	--	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

- 1 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2

Channel List for 802.11b/g/n(20MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	06	2437	09	2452		
04	2427	07	2442				
05	2432	08	2447				

3 Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	QUO	QSP-502QM-GD	PIFA Antenna	N/A	0	N/A



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Low
Mode 2	Middle
Mode 3	High
Mode 4	Charging + Keeping TX mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Charging + Keeping TX mode


For Radiated Emission	
Final Test Mode	Description
Mode 1	Low
Mode 2	Middle
Mode 3	High
Mode 4	Charging + Keeping TX mode

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported
- (3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TEST



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	WCDMA/GSM MOBILE PHONE	QUO	QSP-502QM-GD	N/A	EUT
E-2	Adapter	QUO	GKYP50100050UL	N/A	EUT
E-3	Earphone	N/A	N/A	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable shielded line (Charging)	NO	101cm	N/A
C-2	Earphone Cable shielded line	NO	120cm	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Spectrum Analyzer	Agilent	E4407B	MY50140340	2015.10.25	2016.10.24
Test Receiver	R&S	ESCI	101427	2015.10.25	2016.10.24
Bilog Antenna	TESEQ	CBL6111D	34678	2015.11.25	2016.11.24
Horn Antenna	Schwarzbeck	BBHA 9120D(1201)	9120D-1343	2015.03.06	2016.03.05
50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.06	2016.06.05
PreAmplifier	Agilent	8449B	60538	2015.10.25	2016.10.24
Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	102086	2015.11.20	2016.11.19
LISN	R&S	ENV216	101242	2015.10.25	2016.10.24
LISN	EMCO	3810/2NM	000-23625	2015.10.25	2016.10.24

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2015.10.25	2016.10.24
Spectrum Analyzer	Agilent	E4407B	MY50140340	2015.10.25	2016.10.24
Signal Analyzer	Agilent	N9020A	MY49100060	2015.11.18	2016.11.17



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver



3.1.2 TEST RESULT


EUT:	WCDMA/GSM MOBILE PHONE	Model Name.:	QSP-502QM-GD
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	L
Test Voltage:	DC 5V from Adapter AC120V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1631	37.77	10.00	47.77	65.30	-17.53	QP
0.1631	19.58	10.00	29.58	55.30	-25.72	AVG
0.1990	33.91	10.00	43.91	63.65	-19.74	QP
0.1990	14.17	10.00	24.17	53.65	-29.48	AVG
0.6148	25.11	9.96	35.07	56.00	-20.93	QP
0.6148	7.18	9.96	17.14	46.00	-28.86	AVG
1.4613	17.84	9.95	27.79	56.00	-28.21	QP
1.4613	5.23	9.95	15.18	46.00	-30.82	AVG
3.8766	18.13	10.20	28.33	56.00	-27.67	QP
3.8766	4.07	10.20	14.27	46.00	-31.73	AVG
17.5977	22.36	10.56	32.92	60.00	-27.08	QP
17.5977	7.30	10.56	17.86	50.00	-32.14	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV






EUT:	WCDMA/GSM MOBILE PHONE	Model Name.:	QSP-502QM-GD
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	N
Test Voltage:	DC 5V from Adapter AC120V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1587	36.76	10.16	46.92	65.53	-18.61	QP
0.1587	14.84	10.16	25.00	55.53	-30.53	AVG
0.1991	32.93	10.00	42.93	63.65	-20.72	QP
0.1991	14.42	10.00	24.42	53.65	-29.23	AVG
0.5882	30.49	9.94	40.43	56.00	-15.57	QP
0.5882	11.69	9.94	21.63	46.00	-24.37	AVG
1.1904	25.24	10.00	35.24	56.00	-20.76	QP
1.1904	7.25	10.00	17.25	46.00	-28.75	AVG
3.0902	23.17	10.00	33.17	56.00	-22.83	QP
3.0902	8.51	10.00	18.51	46.00	-27.49	AVG
11.8582	22.96	10.30	33.26	60.00	-26.74	QP
11.8582	8.11	10.30	18.41	50.00	-31.59	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

6 dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&205(a), then the Part 15.247&209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10 th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /10 Hz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



3.2.5 TEST RESULT

9KHz-30MHz

EUT:	WCDMA/GSM MOBILE PHONE	Model Name. :	QSP-502QM-GD
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	Link mode	Polarization :	--

Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	--
--	--	--	--	--	--

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



30MHz - 1000MHz


EUT:	WCDMA/GSM MOBILE PHONE	Model Name. :	QSP-502QM-GD
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	Mode 4	Polarization :	Horizontal

Frequency	Reading	Correct	Result	Limit	Margin	Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
30.3170	5.41	18.54	23.95	40.00	-16.05	QP
53.6931	18.77	6.69	25.46	40.00	-14.54	QP
85.2980	19.82	8.85	28.67	40.00	-11.33	QP
125.8863	13.88	11.66	25.54	43.50	-17.96	QP
152.1297	13.34	11.92	25.26	43.50	-18.24	QP
501.1790	7.23	20.38	27.61	46.00	-18.39	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

80.0 dBuV/m





30MHz - 1000MHz


EUT:	WCDMA/GSM MOBILE PHONE	Model Name. :	QSP-502QM-GD
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz
Test Mode :	Mode 4	Polarization :	Vertical

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
33.0950	11.30	17.13	28.43	40.00	-11.57	QP
54.2610	23.57	6.51	30.08	40.00	-9.92	QP
84.1100	26.04	8.60	34.64	40.00	-5.36	QP
124.1330	23.35	12.48	35.83	43.50	-7.67	QP
153.2004	24.42	11.89	36.31	43.50	-7.19	QP
375.9384	9.46	16.81	26.27	46.00	-19.73	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

80.0 dBuV/m





Above 1000MHz

EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11b/2412 MHz)							
4824.20	67.18	-3.58	63.60	74	-10.40	PK	Vertical
4824.22	48.05	-3.58	44.47	54	-9.53	AV	Vertical
7236.14	63.06	-0.8	62.26	74	-11.74	PK	Vertical
7236.12	42.37	-0.8	41.57	54	-12.43	AV	Vertical
4824.19	63.10	-3.58	59.52	74	-14.48	PK	Horizontal
4824.22	45.13	-3.58	41.55	54	-12.45	AV	Horizontal
Mid Channel (802.11b/2437 MHz)							
4874.09	66.02	-3.56	62.46	74	-11.54	PK	Vertical
4874.07	50.12	-3.56	46.56	54	-7.44	AV	Vertical
7311.22	62.10	-0.78	61.32	74	-12.68	PK	Vertical
7311.21	45.12	-0.78	44.34	54	-9.66	AV	Vertical
4874.18	62.35	-3.56	58.79	74	-15.21	PK	Horizontal
4874.15	46.10	-3.56	42.54	54	-11.46	AV	Horizontal
High Channel (802.11b/2462 MHz)							
4944.26	62.17	-3.54	58.63	74	-15.37	PK	Vertical
4944.30	46.35	-3.54	42.81	54	-11.19	AV	Vertical
7416.32	62.18	-0.75	61.43	74	-12.57	PK	Vertical
7416.30	46.40	-0.75	45.65	54	-8.35	AV	Vertical
4944.26	62.18	-3.54	58.64	74	-15.36	PK	Horizontal
4944.31	46.40	-3.54	42.86	54	-11.14	AV	Horizontal

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- Scan with 802.11b, 802.11g, 802.11n (HT-20), 802.11n (HT-40), the worst case is 802.11b.



3.2.6 TEST RESULTS (Band edge)

EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter AC120V/60Hz

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
802.11 b							
2390.0	69.25	-12.99	56.26	74	-17.74	PK	Vertical
2390.0	55.11	-12.99	42.12	54	-11.88	AV	Vertical
2390.0	70.27	-12.99	57.28	74	-16.72	PK	Horizontal
2390.0	54.22	-12.99	41.23	54	-12.77	AV	Horizontal
2483.6	71.10	-12.78	58.32	74	-15.68	PK	Vertical
2483.6	54.06	-12.78	41.28	54	-12.72	AV	Vertical
2483.6	71.15	-12.78	58.37	74	-15.63	PK	Horizontal
2483.6	54.07	-12.78	41.29	54	-12.71	AV	Horizontal
802.11 g							
2390.0	69.11	-12.99	56.12	74	-17.88	PK	Vertical
2390.0	55.25	-12.99	42.26	54	-11.74	AV	Vertical
2390.0	70.17	-12.99	57.18	74	-16.82	PK	Horizontal
2390.0	54.07	-12.99	41.08	54	-12.92	AV	Horizontal
2483.6	71.12	-12.78	58.34	74	-15.66	PK	Vertical
2483.6	54.26	-12.78	41.48	54	-12.52	AV	Vertical
2483.6	71.08	-12.78	58.30	74	-15.70	PK	Horizontal
2483.6	54.16	-12.78	41.38	54	-12.62	AV	Horizontal



802.11 n20							
2390.0	69.18	-12.99	56.19	74	-17.81	PK	Vertical
2390.0	55.12	-12.99	42.13	54	-11.87	AV	Vertical
2390.0	70.13	-12.99	57.14	74	-16.86	PK	Horizontal
2390.0	54.14	-12.99	41.15	54	-12.85	AV	Horizontal
2483.6	71.19	-12.78	58.41	74	-15.59	PK	Vertical
2483.6	54.12	-12.78	41.34	54	-12.66	AV	Vertical
2483.6	71.04	-12.78	58.26	74	-15.74	PK	Horizontal
2483.6	54.10	-12.78	41.32	54	-12.68	AV	Horizontal
802.11 n40							
2390.0	69.21	-12.99	56.22	74	-17.78	PK	Vertical
2390.0	55.48	-12.99	42.49	54	-11.51	AV	Vertical
2390.0	70.17	-12.99	57.18	74	-16.82	PK	Horizontal
2390.0	54.24	-12.99	41.25	54	-12.75	AV	Horizontal
2483.6	71.18	-12.78	58.40	74	-15.60	PK	Vertical
2483.6	54.09	-12.78	41.31	54	-12.69	AV	Vertical
2483.6	71.23	-12.78	58.45	74	-15.55	PK	Horizontal
2483.6	54.16	-12.78	41.38	54	-12.62	AV	Horizontal
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.							
Low measurement frequencies is range from 2310 to 2400 MHz, high measurement frequencies is range from 2483.5 to 2500 MHz. Only show the worst point data of the emissions in the frequency 2310-2400 MHz and 2483.5-2500 MHz.							

4. CONDUCTED SPURIOUS EMISSIONS

4.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold


For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2430 MHz Upper Band Edge: 2450 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



4.6 TEST RESULTS


EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX b Mode /CH01, CH06, CH11(11Mbps)		

CH 01






CH 06




CH 11






Band edge

CH 01




CH 11






EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX g Mode /CH01, CH06, CH11(54Mbps)		

CH 01




CH06






CH 11






Band edge

CH 01




CH11






EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11(150Mbps)		

CH 01




CH 06






CH 11






Band edge

CH 01




CH 11






EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09(300Mbps)		

CH 03






CH06




CH09






Band edge

CH03



CH 09





5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the $100\text{ kHz} \geq \text{RBW} \geq 3\text{ kHz}$.
4. Set the $\text{VBW} \geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




5.6 TEST RESULTS

EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX b Mode /CH01, CH06, CH11(11Mbps)		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-5.719	8	PASS
2437 MHz	-6.733	8	PASS
2462 MHz	-7.414	8	PASS

TX CH01






TX CH06



TX CH11






EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX g Mode /CH01, CH06, CH11(54Mbps)		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-14.901	8	PASS
2437 MHz	-13.725	8	PASS
2462 MHz	-12.641	8	PASS

TX CH01






TX CH06



TX CH11






EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11(150Mbps)		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-13.894	8	PASS
2437 MHz	-13.758	8	PASS
2462 MHz	-13.988	8	PASS

TX CH01






TX CH06



TX CH11






EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09(300Mbps)		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-17.928	8	PASS
2437 MHz	-14.543	8	PASS
2452 MHz	-16.655	8	PASS

TX CH03






TX CH06



TX CH09





6. BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

6.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW \geq 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




6.6 TEST RESULTS

EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX b Mode /CH01, CH06, CH11(11Mbps)		


Frequency	6dB Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	10.04	>=500KHz	PASS
2437 MHz	10.04	>=500KHz	PASS
2462 MHz	10.04	>=500KHz	PASS

TX CH 01






TX CH 06



TX CH 11






EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX g Mode /CH01, CH06, CH11(54Mbps)		


Frequency	6dB Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	15.30	>=500KHz	PASS
2437 MHz	15.14	>=500KHz	PASS
2462 MHz	15.13	>=500KHz	PASS

TX CH 01






TX CH 06



TX CH 11






EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11(150Mbps)		


Frequency	6dB Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	16.08	>=500KHz	PASS
2437 MHz	15.70	>=500KHz	PASS
2462 MHz	15.13	>=500KHz	PASS

TX CH 01






TX CH 06



TX CH 11






EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09(300Mbps)		


Frequency	6dB Bandwidth (MHz)	Channel Separation (KHz)	Result
2422 MHz	35.18	>=500KHz	PASS
2437 MHz	35.36	>=500KHz	PASS
2452 MHz	35.46	>=500KHz	PASS

TX CH 03






TX CH 06



TX CH 09





7. PEAK OUTPUT POWER TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.2 TEST PROCEDURE

- The EUT was directly connected to the Power Sensor&Power meter

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



7.6 TEST RESULTS

EUT :	WCDMA/GSM MOBILE PHONE	Model Name :	QSP-502QM-GD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX b/g/n(20M,40M) Mode /CH01, CH06, CH11		

TX 802.11b Mode(11Mbps)			
Test Channe	Frequency	Peak Conducted Output Power	LIMIT
	(MHz)	(dBm)	dBm
CH01	2412	17.1	30
CH06	2437	17.6	30
CH11	2462	17.4	30

TX 802.11g Mode(54 Mbps)			
Test Channe	Frequency	Peak Conducted Output Power	LIMIT
	(MHz)	(dBm)	dBm
CH01	2412	15.8	30
CH06	2437	16.3	30
CH11	2462	16.5	30

TX 802.11n20 Mode(150 Mbps)			
Test Channe	Frequency	Peak Conducted Output Power	LIMIT
	(MHz)	(dBm)	dBm
CH01	2412	15.8	30
CH06	2437	16.4	30
CH11	2462	16.5	30

TX 802.11n40 Mode(300 Mbps)			
Test Channe	Frequency	Peak Conducted Output Power	LIMIT
	(MHz)	(dBm)	dBm
CH03	2422	13.1	30
CH06	2437	14.7	30
CH09	2452	14.9	30



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



8.2 EUT ANTENNA

The EUT antenna is PIFA Antenna. It comply with the standard requirement.



APPENDIX - PHOTOS OF TEST SETUP

Radiated Measurement Photos





Conducted Measurement Photos



*****END OF THE REPORT*****